

DWG No:	KC-01-1834											
Revision:	V2.0											
Drawn:	J. Rostoker	6/13/2026										
Approved:	J. Kerman	6/13/2026										
Issued:	6/13/2026											
Status:	RELEASED											
Doc Type:	CCA Placement File											
Designator	Device	Footprint	Mid X	Mid Y	Ref X	Ref Y	Pad X	Pad Y	Pins	Layer	Rotation	SMD
C1	CL05B104KO5NNNC	C0402	26.416mm	-21.336mm	26.416mm	-21.336mm	25.996mm	-21.336mm	2 B		0	Yes
C2	0402CG101J500NT	C0402	24.892mm	-24.638mm	24.892mm	-24.638mm	24.892mm	-24.218mm	2 B		270	Yes
C3	CL21B475KAFNNNE	C0805	35.814mm	-16.764mm	35.814mm	-16.764mm	35.814mm	-15.764mm	2 B		270	Yes
C4	CL21B106KAYQNNE	C0805	31.877mm	-13.843mm	31.877mm	-13.843mm	32.877mm	-13.843mm	2 B		180	Yes
C5	CL05B104KO5NNNC	C0402	7.493mm	-15.448mm	7.493mm	-15.448mm	7.073mm	-15.448mm	2 B		0	Yes
C6	CL05B104KO5NNNC	C0402	7.747mm	-43.515mm	7.747mm	-43.515mm	7.327mm	-43.515mm	2 B		0	Yes
C7	CL05A105KA5NQNC	C0402	27.051mm	-32.258mm	27.051mm	-32.258mm	26.754mm	-31.961mm	2 B		315	Yes
C8	CL05B104KO5NNNC	C0402	26.162mm	-33.147mm	26.162mm	-33.147mm	25.865mm	-32.85mm	2 B		315	Yes
D1	SS34_C8678	SMA_L4.3-W2.6-LS5.2-RD	40.259mm	-9.305mm	40.259mm	-9.305mm	40.259mm	-11.505mm	2 B		90	Yes
D2	BAT54C_C2135	SOT-23-3_L2.9-W1.6-P1.90-LS2.8-BR	30.099mm	-32.004mm	30.099mm	-32.004mm	31.334mm	-31.054mm	3 B		0	Yes
F1	MF-MSMF150/24X-2	F1812	40.259mm	-15.875mm	40.259mm	-15.875mm	40.259mm	-14.022mm	2 B		270	Yes
H1	2.54-1*3P针	HDR-TH_3P-P2.54-V-M-1	44.45mm	-24.13mm	44.45mm	-24.13mm	44.45mm	-26.67mm	3 B		90	No
P1	2.54-2*8P筒牛	IDC-TH_16P-P2.54_C3406	24mm	-5mm	24mm	-5mm	32.89mm	-6.27mm	16 B		180	No
R1	0402WGF4701TCE	R0402	26.162mm	-27.94mm	26.162mm	-27.94mm	26.595mm	-27.94mm	2 B		180	Yes
R10	0402WGF2002TCE	R0402	19.304mm	-10.922mm	19.304mm	-10.922mm	19.304mm	-11.355mm	2 B		90	Yes
R11	0402WGF1002TCE	R0402	46.482mm	-24.13mm	46.482mm	-24.13mm	46.482mm	-24.563mm	2 B		90	Yes
R12	0402WGF3300TCE	R0402	7.493mm	-23.495mm	7.493mm	-23.495mm	7.926mm	-23.495mm	2 B		180	Yes
R2	0402WGF4701TCE	R0402	29.464mm	-27.94mm	29.464mm	-27.94mm	29.031mm	-27.94mm	2 B		0	Yes
R3	0402WGF1003TCE	R0402	34.036mm	-19.812mm	34.036mm	-19.812mm	33.603mm	-19.812mm	2 B		0	Yes
R4	FRC0402F1912TS	R0402	31.877mm	-19.812mm	31.877mm	-19.812mm	31.444mm	-19.812mm	2 B		0	Yes
R5	0402WGF1000TCE	R0402	7.493mm	-16.718mm	7.493mm	-16.718mm	7.926mm	-16.718mm	2 B		180	Yes
R6	0402WGF1002TCE	R0402	15.748mm	-12.4mm	15.748mm	-12.4mm	15.315mm	-12.4mm	2 B		0	Yes
R7	0402WGF1000TCE	R0402	7.747mm	-44.785mm	7.747mm	-44.785mm	8.18mm	-44.785mm	2 B		180	Yes
R8	0402WGF1002TCE	R0402	16.002mm	-40.467mm	16.002mm	-40.467mm	15.569mm	-40.467mm	2 B		0	Yes
R9	0402WGF1002TCE	R0402	20.447mm	-10.922mm	20.447mm	-10.922mm	20.447mm	-10.489mm	2 B		270	Yes
SW1	PB26-13M RGB	PB26-13M	18.035mm	-21mm	16mm	-21mm	21.21mm	-26.08mm	7 T		0	No
SW2	PB26-13M RGB	PB26-13M	18.035mm	-49mm	16mm	-49mm	21.21mm	-54.08mm	7 T		0	No
U1	PCA9306DCTR	SM8_L3.2-W2.9-P0.65-LS4.3-BL	27.178mm	-24.638mm	27.178mm	-24.638mm	26.203mm	-22.813mm	8 B		0	Yes
U2	MPM3610GQV-Z	QFN-20_L5.0-W3.0-TL-MPM3610GQV-Z	32.512mm	-17.018mm	32.512mm	-17.018mm	33.462mm	-18.443mm	14 B		90	Yes
U3	WS2811	SOP-8_L4.9-W3.9-P1.27-LS6.0-BL	7.493mm	-20.066mm	7.493mm	-20.066mm	10.175mm	-18.161mm	8 B		270	Yes
U4	WS2811	SOP-8_L4.9-W3.9-P1.27-LS6.0-BL	7.747mm	-48.133mm	7.747mm	-48.133mm	10.429mm	-46.228mm	8 B		270	Yes
U5	ATTINY816-MNR	UQFN-20_L3.0-W3.0-P0.40-BL-EP1.7	24mm	-34.999mm	24mm	-35mm	24.495mm	-33.374mm	21 B		315	Yes
U6	DB127S-5.08-6P-GN-S	CONN-TH_6P-P5.08_DIBO_DB127S-5.08	42mm	-45mm	42mm	-45mm	42mm	-57.7mm	6 B		270	No