

PSScriptTools Manual v3.0.0



Table of Contents

Introduction	1
PSScriptTools Overview	2
Abstract	3
Installation	4
General Tools	5
Get-MyCounter	5
Get-DirectoryInfo	6
Get-FormatView	8
Copy-PSFunction	8
Get-PSProfile	9
Get-MyAlias	10
Get-ModuleCommand	11
Get-PSScriptTools	13
Convert-EventLogRecord	13
Get-WhoIs	14
Compare-Module	15
Get-WindowsVersion	15
New-PSDriveHere	16
Get-MyVariable	16
ConvertFrom-Text	17
Get-PSWho	17
Out-VerboseTee	18
Remove-Runspace	19
Get-PSLocation	19
Get-PowerShellEngine	20
Get-PathVariable	21
File Tools	22
Get-LastModifiedFile	22
Get-FileExtensionInfo	23
Test-EmptyFolder	23
Get-FolderSizeInfo	24
Optimize-Text	25
Get-FileItem	25
New-CustomFileName	25
New-RandomFilename	26
ConvertTo-Markdown	26
Editor Integrations	29
Insert ToDo	29
Set Terminal Location	30
Graphical Tools	31
Invoke-InputBox	31

New-WPFMessageBox	31
ConvertTo-WPFGrid	33
Hashtable Tools	36
Convert-CommandToHashtable	36
Convert-HashtableString	36
Convert-HashtableToCode	36
ConvertTo-Hashtable	37
Join-Hashtable	37
Rename-Hashtable	37
Select Functions	39
Select-First	39
Select-Last	39
Select-After	39
Select-Before	40
Select-Newest	41
Select-Oldest	41
Time Functions	43
ConvertTo-UTCTime	43
ConvertFrom-UTCTime	43
Get-MyTimeInfo	43
ConvertTo-LocalTime	44
Get-TZList	44
Get-TZData	44
ConvertTo-LexicalTime	45
ConvertFrom-LexicalTime	45
Console Utilities	47
Get-PSSessionInfo	47
Out-Copy	47
Out-More	48
Set-ConsoleTitle	49
Add-Border	49
Show-Tree	50
New-RedGreenGradient	52
Format Functions	53
Format-Percent	53
Format-String	53
Format-Value	53
Scripting Tools	55
Get-TypeMember	55
Get-TypeConstructor	57
New-PSDynamicParameter	57
Get-PSUnique	59
Test-IsElevated	60

New-FunctionItem	60
Show-FunctionItem.....	61
ConvertTo-TitleCase	61
Trace-Message	61
Get-CommandSyntax.....	62
Test-Expression	63
Copy-HelpExample	65
Get-GitSize	66
Remove-MergedBranch.....	66
Test-WithCulture	67
Copy-Command	67
Get-ParameterInfo	68
New-PSFormatXML.....	68
Test-IsPSWindows.....	70
Write-Detail	70
Save-GitSetup	71
CIM Tools	72
Find-CimClass	72
Get-CimNamespace	72
Get-CimClassList	73
Get-CimClassProperty	73
Get-CimClassMethod	74
Get-CimMember	74
Get-CimClassPropertyQualifier.....	75
ANSI Tools	76
PSAnsiMap	76
Get-PSAnsiFileMap	78
Set-PSAnsiFileMap.....	79
Remove-PSAnsiFileEntry	79
Export-PSAnsiFileMap	79
Convert-HtmlToAnsi.....	79
New-ANSIBar.....	80
Write-ANSIProgress	80
Show-ANSISequence	81
Other Module Features	83
Custom Format Views	83
Custom Type Extensions	84
PSSpecialChar	86
Sample Scripts.....	88
Open-PSScriptToolsHelp	88
Deprecated Commands.....	89
Related Modules.....	90
Compatibility	91

Module Commands	92
Add-Border	94
Synopsis	94
Syntax	94
Description.....	94
Examples	94
Parameters.....	96
Inputs	98
Outputs.....	98
Notes.....	98
Related Links	98
Compare-Module	99
Synopsis	99
Syntax	99
Description.....	99
Examples	99
Parameters.....	100
Inputs	101
Outputs.....	101
Notes.....	101
Related Links	101
Compare-Script.....	102
Synopsis	102
Syntax	102
Description.....	102
Examples	102
Parameters.....	102
Inputs	103
Outputs.....	103
Notes.....	103
Related Links	103
Convert-CommandToHashtable.....	105
Synopsis	105
Syntax	105
Description.....	105
Examples	105
Parameters.....	105
Inputs	106
Outputs.....	106
Notes.....	106
Related Links	106
Convert-EventLogRecord.....	107
Synopsis	107

Syntax	107
Description.....	107
Examples	107
Parameters.....	110
Inputs	110
Outputs.....	110
Related Links	110
Convert-HashtableString.....	111
Synopsis	111
Syntax	111
Description.....	111
Examples	111
Parameters.....	111
Inputs	112
Outputs.....	112
Notes.....	112
Related Links	112
Convert-HashtableToCode	113
Synopsis	113
Syntax	113
Description.....	113
Examples	113
Parameters.....	114
Inputs	115
Outputs.....	115
Notes.....	115
Related Links	115
Convert-HtmlToAnsi.....	116
Synopsis	116
Syntax	116
Description.....	116
Examples	116
Parameters.....	116
Inputs	117
Outputs.....	117
Notes.....	117
Related Links	117
ConvertFrom-LexicalTimespan.....	118
Synopsis	118
Syntax	118
Description.....	118
Examples	118
Parameters.....	119

Inputs	119
Outputs.....	119
Notes.....	120
Related Links	120
ConvertFrom-Text.....	121
Synopsis	121
Syntax	121
Description.....	121
Examples	121
Parameters.....	123
Inputs	125
Outputs.....	125
Notes.....	125
Related Links	125
ConvertFrom-UTCTime	126
Synopsis	126
Syntax	126
Description.....	126
Examples	126
Parameters.....	126
Inputs	127
Outputs.....	127
Notes.....	127
Related Links	127
ConvertTo-Hashtable.....	128
Synopsis	128
Syntax	128
Description.....	128
Examples	128
Parameters.....	129
Inputs	130
Outputs.....	130
Notes.....	130
Related Links	131
ConvertTo-LexicalTimespan	132
Synopsis	132
Syntax	132
Description.....	132
Examples	132
Parameters.....	132
Inputs	133
Outputs.....	133
Notes.....	133

Related Links	133
ConvertTo-LocalTime	134
Synopsis	134
Syntax	134
Description.....	134
Examples	134
Parameters.....	135
Inputs	136
Outputs.....	136
Notes.....	136
Related Links	136
ConvertTo-Markdown	137
Synopsis	137
Syntax	137
Description.....	137
Examples	137
Parameters.....	139
Inputs	141
Outputs.....	141
Notes.....	141
Related Links	141
ConvertTo-TitleCase.....	142
Synopsis	142
Syntax	142
Description.....	142
Examples	142
Parameters.....	142
Inputs	143
Outputs.....	143
Notes.....	143
Related Links	143
ConvertTo-UTCTime.....	144
Synopsis	144
Syntax	144
Description.....	144
Examples	144
Parameters.....	144
Inputs	145
Outputs.....	145
Notes.....	145
Related Links	145
ConvertTo-WPFGrid	146
Synopsis	146

Syntax	146
Description.....	146
Examples	147
Parameters.....	148
Inputs	150
Outputs.....	151
Notes.....	151
Related Links	151
Copy-Command	152
Synopsis	152
Syntax	152
Description.....	152
Examples	152
Parameters.....	153
Inputs	154
Outputs.....	154
Notes.....	155
Related Links	155
Copy-HelpExample	156
Synopsis	156
Syntax	156
Description.....	156
Examples	156
Parameters.....	157
Inputs	158
Outputs.....	158
Notes.....	158
Related Links	158
Copy-HistoryCommand	159
Synopsis	159
Syntax	159
Description.....	159
Examples	159
Parameters.....	160
Inputs	161
Outputs.....	161
Notes.....	161
Related Links	161
Copy-PSFunction.....	163
Synopsis	163
Syntax	163
Description.....	163
Examples	163

Parameters.....	163
Inputs	164
Outputs.....	164
Notes.....	164
Related Links	165
Export-PSAnsiFileMap	166
Synopsis	166
Syntax	166
Description.....	166
Examples	166
Parameters.....	166
Inputs	167
Outputs.....	167
Notes.....	168
Related Links	168
Find-CimClass	169
Synopsis	169
Syntax	169
Description.....	169
Examples	169
Parameters.....	170
Inputs	171
Outputs.....	171
Notes.....	171
Related Links	171
Format-Percent.....	172
Synopsis	172
Syntax	172
Description.....	172
Examples	172
Parameters.....	173
Inputs	174
Outputs.....	174
Notes.....	174
Related Links	174
Format-String	176
Synopsis	176
Syntax	176
Description.....	176
Examples	176
Parameters.....	177
Inputs	179
Outputs.....	179

Notes.....	179
Related Links	179
Format-Value.....	180
Synopsis	180
Syntax	180
Description.....	180
Examples	180
Parameters.....	181
Inputs	183
Outputs.....	183
Notes.....	184
Related Links	184
Get-CimClassListing	185
Synopsis	185
Syntax	185
Description.....	185
Examples	185
Parameters.....	186
Inputs	187
Outputs.....	187
Notes.....	187
Related Links	187
Get-CimClassMethod	188
Synopsis	188
Syntax	188
Description.....	188
Examples	188
Parameters.....	189
Inputs	190
Outputs.....	190
Notes.....	190
Related Links	190
Get-CimClassProperty	191
Synopsis	191
Syntax	191
Description.....	191
Examples	191
Parameters.....	192
Inputs	194
Outputs.....	194
Notes.....	194
Related Links	194
Get-CimClassPropertyQualifier	195

Synopsis	195
Syntax	195
Description.....	195
Examples	195
Parameters.....	195
Inputs	197
Outputs.....	197
Notes.....	197
Related Links	197
Get-CimMember	198
Synopsis	198
Syntax	198
Description.....	198
Examples	198
Parameters.....	199
Inputs	201
Outputs.....	201
Notes.....	201
Related Links	201
Get-CimNamespace	202
Synopsis	202
Syntax	202
Description.....	202
Examples	202
Parameters.....	203
Inputs	204
Outputs.....	204
Notes.....	204
Related Links	204
Get-CommandSyntax.....	205
Synopsis	205
Syntax	205
Description.....	205
Examples	205
Parameters.....	206
Inputs	206
Outputs.....	206
Notes.....	207
Related Links	207
Get-DirectoryInfo	208
Synopsis	208
Syntax	208
Description.....	208

Examples	208
Parameters.....	209
Inputs	210
Outputs.....	210
Notes.....	210
Related Links	211
Get-FileExtensionInfo.....	212
Synopsis	212
Syntax	212
Description.....	212
Examples	212
Parameters.....	213
Inputs	214
Outputs.....	214
Notes.....	214
Related Links	214
Get-FileItem.....	215
Synopsis	215
Syntax	215
Description.....	215
Examples	215
Parameters.....	216
Inputs	218
Outputs.....	218
Notes.....	218
Related Links	218
Get-FolderSizeInfo	220
Synopsis	220
Syntax	220
Description.....	220
Examples	220
Parameters.....	221
Inputs	222
Outputs.....	222
Notes.....	223
Related Links	223
Get-FormatView	224
Synopsis	224
Syntax	224
Description.....	224
Examples	224
Parameters.....	225
Inputs	226

Outputs.....	226
Notes.....	226
Related Links	226
Get-GitSize	227
Synopsis	227
Syntax	227
Description.....	227
Examples	227
Parameters.....	228
Inputs	228
Outputs.....	228
Notes.....	228
Related Links	229
Get-LastModifiedFile	230
Synopsis	230
Syntax	230
Description.....	230
Examples	230
Parameters.....	231
Inputs	232
Outputs.....	232
Notes.....	232
Related Links	233
Get-ModuleCommand.....	234
Synopsis	234
Syntax	234
Description.....	234
Examples	234
Parameters.....	236
Inputs	237
Outputs.....	237
Notes.....	237
Related Links	237
Get-MyAlias	238
Synopsis	238
Syntax	238
Description.....	238
Examples	238
Parameters.....	239
Inputs	239
Outputs.....	240
Notes.....	240
Related Links	240

Get-MyCounter	241
Synopsis	241
Syntax	241
Description.....	241
Examples	241
Parameters.....	243
Inputs	245
Outputs.....	245
Notes.....	245
Related Links	245
Get-MyTimeInfo	246
Synopsis	246
Syntax	246
Description.....	246
Examples	246
Parameters.....	247
Inputs	249
Outputs.....	249
Notes.....	250
Related Links	250
Get-MyVariable	251
Synopsis	251
Syntax	251
Description.....	251
Examples	251
Parameters.....	253
Inputs	253
Outputs.....	253
Notes.....	254
Related Links	254
Get-ParameterInfo	255
Synopsis	255
Syntax	255
Description.....	255
Examples	255
Parameters.....	257
Inputs	258
Outputs.....	258
Notes.....	258
Related Links	258
Get-PathVariable.....	259
Synopsis	259
Syntax	259

Description.....	259
Examples	259
Parameters.....	260
Inputs	260
Outputs.....	260
Notes.....	260
Related Links	260
Get-PowerShellEngine	261
Synopsis	261
Syntax	261
Description.....	261
Examples	261
Parameters.....	262
Inputs	262
Outputs.....	262
Notes.....	262
Related Links	262
Get-PSAnsiFileMap	263
Synopsis	263
Syntax	263
Description.....	263
Examples	263
Parameters.....	263
Inputs	263
Outputs.....	264
Notes.....	264
Related Links	264
Get-PSLocation	265
Synopsis	265
Syntax	265
Description.....	265
Examples	265
Parameters.....	265
Inputs	266
Outputs.....	266
Notes.....	266
Related Links	266
Get-PSProfile	267
Synopsis	267
Syntax	267
Description.....	267
Examples	267
Parameters.....	268

Inputs	268
Outputs.....	268
Notes.....	268
Related Links	269
Get-PSScriptTools	270
Synopsis	270
Syntax	270
Description.....	270
Examples	270
Parameters.....	272
Inputs	272
Outputs.....	272
Notes.....	272
Related Links	272
Get-PSScriptToolsTypeExtension	273
Synopsis	273
Syntax	273
Description.....	273
Examples	273
Parameters.....	273
Inputs	274
Outputs.....	274
Notes.....	274
Related Links	274
Get-PSSessionInfo	275
Synopsis	275
Syntax	275
Description.....	275
Examples	275
Parameters.....	276
Inputs	276
Outputs.....	276
Notes.....	276
Related Links	276
Get-PSUnique	277
Synopsis	277
Syntax	277
Description.....	277
Examples	277
Parameters.....	277
Inputs	278
Outputs.....	278
Notes.....	278

Related Links	278
Get-PSWho	279
Synopsis	279
Syntax	279
Description.....	279
Examples	279
Parameters.....	280
Inputs	280
Outputs.....	280
Notes.....	280
Related Links	280
Get-TypeConstructor	282
Synopsis	282
Syntax	282
Description.....	282
Examples	282
Parameters.....	283
Inputs	283
Outputs.....	283
Notes.....	283
Related Links	284
Get-TypeMember	285
Synopsis	285
Syntax	285
Description.....	285
Examples	285
Parameters.....	287
Inputs	289
Outputs.....	289
Notes.....	289
Related Links	289
Get-TZData.....	290
Synopsis	290
Syntax	290
Description.....	290
Examples	290
Parameters.....	291
Inputs	292
Outputs.....	292
Notes.....	292
Related Links	292
Get-TZList.....	293
Synopsis	293

Syntax	293
Description.....	293
Examples	293
Parameters.....	294
Inputs	295
Outputs.....	295
Notes.....	295
Related Links	295
Get-WhoIs	296
Synopsis	296
Syntax	296
Description.....	296
Examples	296
Parameters.....	296
Inputs	297
Outputs.....	297
Notes.....	297
Related Links	297
Get-WindowsVersion	298
Synopsis	298
Syntax	298
Description.....	298
Examples	298
Parameters.....	299
Inputs	302
Outputs.....	302
Notes.....	302
Related Links	302
Get-WindowsVersionString.....	303
Synopsis	303
Syntax	303
Description.....	303
Examples	303
Parameters.....	303
Inputs	306
Outputs.....	306
Notes.....	306
Related Links	306
Import-PSScriptToolsTypeExtension	307
Synopsis	307
Syntax	307
Description.....	307
Examples	307

Parameters.....	307
Inputs	308
Outputs.....	308
Notes.....	309
Related Links	309
Invoke-InputBox.....	310
Synopsis	310
Syntax	310
Description.....	310
Examples	310
Parameters.....	311
Inputs	312
Outputs.....	312
Notes.....	312
Related Links	312
Join-Hashtable.....	313
Synopsis	313
Syntax	313
Description.....	313
Examples	313
Parameters.....	314
Inputs	315
Outputs.....	315
Notes.....	315
Related Links	315
New-ANSIBar.....	316
Synopsis	316
Syntax	316
Description.....	316
Examples	316
Parameters.....	317
Inputs	318
Outputs.....	318
Notes.....	318
Related Links	319
New-CustomFileName.....	320
Synopsis	320
Syntax	320
Description.....	320
Examples	321
Parameters.....	322
Inputs	323
Outputs.....	323

Notes.....	323
Related Links	323
New-FunctionItem	324
Synopsis	324
Syntax	324
Description.....	324
Examples	324
Parameters.....	324
Inputs	326
Outputs.....	326
Notes.....	326
Related Links	326
New-PSDriveHere	327
Synopsis	327
Syntax	327
Description.....	327
Examples	327
Parameters.....	328
Inputs	330
Outputs.....	330
Notes.....	330
Related Links	331
New-PSDynamicParameter.....	332
Synopsis	332
Syntax	332
Description.....	332
Examples	332
Parameters.....	332
Inputs	337
Outputs.....	338
Notes.....	338
Related Links	338
New-PSDynamicParameterForm	339
Synopsis	339
Syntax	339
Description.....	339
Examples	339
Parameters.....	339
Inputs	339
Outputs.....	339
Notes.....	340
Related Links	340
New-PSFormatXML.....	341

Synopsis	341
Syntax	341
Description.....	341
Examples	341
Parameters.....	344
Inputs	347
Outputs.....	348
Notes.....	348
Related Links	348
New-RandomFileName	349
Synopsis	349
Syntax	349
Description.....	349
Examples	349
Parameters.....	350
Inputs	351
Outputs.....	351
Notes.....	351
Related Links	351
New-RedGreenGradient	352
Synopsis	352
Syntax	352
Description.....	352
Examples	352
Parameters.....	353
Inputs	354
Outputs.....	354
Notes.....	354
Related Links	354
New-WPFMessageBox.....	355
Synopsis	355
Syntax	355
Description.....	355
Examples	355
Parameters.....	356
Inputs	358
Outputs.....	359
Notes.....	359
Related Links	359
Open-PSScriptToolsHelp	360
Synopsis	360
Syntax	360
Description.....	360

Examples	360
Parameters.....	360
Inputs	360
Outputs.....	360
Notes.....	360
Related Links	361
Optimize-Text	362
Synopsis	362
Syntax	362
Description.....	362
Examples	362
Parameters.....	364
Inputs	366
Outputs.....	366
Notes.....	366
Related Links	366
Out-Copy	367
Synopsis	367
Syntax	367
Description.....	367
Examples	367
Parameters.....	368
Inputs	369
Outputs.....	369
Notes.....	369
Related Links	369
Out-More	371
Synopsis	371
Syntax	371
Description.....	371
Examples	371
Parameters.....	372
Inputs	372
Outputs.....	373
Notes.....	373
Related Links	373
Out-VerboseTee	374
Synopsis	374
Syntax	374
Description.....	374
Examples	374
Parameters.....	375
Inputs	376

Outputs.	376
Notes.	376
Related Links	376
Remove-MergedBranch.	377
Synopsis	377
Syntax	377
Description.	377
Examples	377
Parameters.	378
Inputs	379
Outputs.	379
Notes.	379
Related Links	379
Remove-PSAnsiFileEntry	380
Synopsis	380
Syntax	380
Description.	380
Examples	380
Parameters.	380
Inputs	381
Outputs.	382
Notes.	382
Related Links	382
Remove-Runspace	383
Synopsis	383
Syntax	383
Description.	383
Examples	383
Parameters.	384
Inputs	385
Outputs.	385
Notes.	385
Related Links	385
Rename-Hashtable	386
Synopsis	386
Syntax	386
Description.	386
Examples	386
Parameters.	387
Inputs	389
Outputs.	389
Notes.	389
Related Links	389

Save-GitSetup	391
Synopsis	391
Syntax	391
Description.....	391
Examples	391
Parameters.....	391
Inputs	392
Outputs.....	392
Notes.....	392
Related Links	392
Select-After	393
Synopsis	393
Syntax	393
Description.....	393
Examples	393
Parameters.....	394
Inputs	395
Outputs.....	395
Notes.....	395
Related Links	395
Select-Before.....	396
Synopsis	396
Syntax	396
Description.....	396
Examples	396
Parameters.....	397
Inputs	398
Outputs.....	398
Notes.....	398
Related Links	398
Select-First	399
Synopsis	399
Syntax	399
Description.....	399
Examples	399
Parameters.....	399
Inputs	401
Outputs.....	401
Notes.....	401
Related Links	401
Select-Last	402
Synopsis	402
Syntax	402

Description.....	402
Examples	402
Parameters.....	403
Inputs	404
Outputs.....	404
Notes.....	404
Related Links	405
Select-Newest	406
Synopsis	406
Syntax	406
Description.....	406
Examples	406
Parameters.....	407
Inputs	408
Outputs.....	408
Notes.....	408
Related Links	408
Select-Oldest	409
Synopsis	409
Syntax	409
Description.....	409
Examples	409
Parameters.....	410
Inputs	411
Outputs.....	411
Notes.....	411
Related Links	411
Set-ConsoleTitle	412
Synopsis	412
Syntax	412
Description.....	412
Examples	412
Parameters.....	412
Inputs	413
Outputs.....	413
Notes.....	414
Related Links	414
Set-LocationToFile	415
Synopsis	415
Syntax	415
Description.....	415
Examples	415
Parameters.....	415

Inputs	415
Outputs.....	415
Notes.....	416
Related Links	416
Set-PSAnsiFileMap	417
Synopsis	417
Syntax	417
Description.....	417
Examples	417
Parameters.....	417
Inputs	419
Outputs.....	419
Notes.....	419
Related Links	419
Show-ANSISquence	421
Synopsis	421
Syntax	421
Description.....	421
Examples	421
Parameters.....	422
Inputs	424
Outputs.....	424
Notes.....	424
Related Links	424
Show-FunctionItem	426
Synopsis	426
Syntax	426
Description.....	426
Examples	426
Parameters.....	426
Inputs	427
Outputs.....	427
Notes.....	427
Related Links	427
Show-Tree	428
Synopsis	428
Syntax	428
Description.....	428
Examples	428
Parameters.....	430
Inputs	433
Outputs.....	433
Notes.....	433

Related Links	433
Test-EmptyFolder	434
Synopsis	434
Syntax	434
Description.....	434
Examples	434
Parameters.....	435
Inputs	436
Outputs.....	436
Notes.....	436
Related Links	436
Test-Expression.....	437
Synopsis	437
Syntax	437
Description.....	437
Examples	437
Parameters.....	439
Inputs	442
Outputs.....	442
Notes.....	442
Related Links	442
Test-ExpressionForm	443
Synopsis	443
Syntax	443
Description.....	443
Examples	443
Parameters.....	443
Inputs	443
Outputs.....	444
Notes.....	444
Related Links	444
Test-IsElevated	445
Synopsis	445
Syntax	445
Description.....	445
Examples	445
Parameters.....	445
Inputs	445
Outputs.....	445
Notes.....	446
Related Links	446
Test-IsPSWindows	447
Synopsis	447

Syntax	447
Description.....	447
Examples	447
Parameters.....	447
Inputs	447
Outputs.....	447
Notes.....	448
Related Links	448
Test-WithCulture.....	449
Synopsis	449
Syntax	449
Description.....	449
Examples	449
Parameters.....	450
Inputs	451
Outputs.....	451
Notes.....	451
Related Links	451
Trace-Message	452
Synopsis	452
Syntax	452
Description.....	452
Examples	452
Parameters.....	453
Inputs	454
Outputs.....	454
Notes.....	454
Related Links	455
Write-ANSIProgress	456
Synopsis	456
Syntax	456
Description.....	456
Examples	456
Parameters.....	457
Inputs	459
Outputs.....	459
Notes.....	459
Related Links	459
Write-Detail	460
Synopsis	460
Syntax	460
Description.....	460
Examples	460

Parameters.....	461
Inputs	462
Outputs.....	462
Notes.....	462
Related Links	463
Change Log for PSScriptTools	464
3.0.0 - 2025-03-26	465
Added	465
Changed.....	465
Removed	465
Fixed	465
2.50.0 - 2024-07-13	466
Added	466
Changed.....	466
Fixed	466
2.49.0 - 2024-06-06	467
Added	467
Changed.....	467
Fixed	467
v2.48.0 - 2023-07-28	468
Added	468
Changed.....	468
v2.47.0 - 2023-05-25	469
Changed.....	469
v2.46.0 - 2023-03-03	470
Changed.....	470
Fixed	470
Added	470
Deprecated	470
v2.45.0 - 2022-09-16	471
[v2.43.0] - 2022-04-04.....	472
Archive	473

Introduction

This manual is a PDF version of several module-related reference files as well as all of the command help. The goal is to provide a single source for all module documentation. Take note that many of the source files contain internal cross-references. Best efforts have been made to port those links to this document. External links should work as expected.

If you need to ask a question or report a problem, please visit the module's [Github repository](#).

PSScriptTools Overview

Abstract

This module contains a collection of functions, variables, and format files that you can use to enhance your PowerShell scripting work or get more done from a PowerShell prompt with less typing. Most of the commands are designed to work cross-platform. Please post any questions, problems, or feedback in the [Issues](#) section of this module's GitHub repository. Feedback is greatly appreciated.

The contents of this file and other documentation can be viewed using the `Open-PSScriptToolsHelp` command. You can also use `Get-PSScriptTools` to see a summary of module commands.

Please note that code samples have been formatted to *fit an **80-character** width*. Some example code breaks lines without using line continuation characters. I'm trusting that you can figure out how to run the example.

Installation

You can get the current release from this repository or install this from the [PowerShell Gallery](#):

```
Install-Module PSScriptTools
```

or in PowerShell 7:

```
Install-Module PSScriptTools [-scope CurrentUser] [-force]
```

Starting in v2.2.0, the module was restructured to better support `Desktop` and `Core` editions. However, starting with v2.13.0, the module design has reverted. All module commands will be exported. Anything that is platform-specific should be handled on a per-command basis. It is assumed you will be running this module in Windows PowerShell 5.1 or PowerShell 7.

It is recommended to install this module from the PowerShell Gallery and not GitHub.

To remove the module from your system, you can easily uninstall it with common PowerShell commands.

```
Get-Module PSScriptTools | Remove-Module  
Uninstall-Module PSScriptTools -AllVersions
```

General Tools

Get-MyCounter

Get-MyCounter is an enhanced version of the legacy Get-Counter cmdlet, which is available on Windows platforms to retrieve performance counter data. One of the challenges with using Get-Counter is how it formats results. The information may be easy to read on the screen, but it is cumbersome to use in a pipelined expression.

Get-MyCounter takes the same information and writes a custom object to the pipeline that is easier to work with. You can pipe counters from Get-Counter to Get-MyCounter.

```
PS C:\> Get-Counter -list IPV4 | Get-MyCounter
```

Computername: PROSPERO

Timestamp	Category	Counter	Value
11/4/2020 10:59:43 AM	ipv4	datagrams/sec	42.3661
11/4/2020 10:59:43 AM	ipv4	datagrams received/sec	29.5577
11/4/2020 10:59:43 AM	ipv4	datagrams received header errors	0
11/4/2020 10:59:43 AM	ipv4	datagrams received address errors	11815
11/4/2020 10:59:43 AM	ipv4	datagrams forwarded/sec	0
11/4/2020 10:59:43 AM	ipv4	datagrams received unknown protocol	0
11/4/2020 10:59:43 AM	ipv4	datagrams received discarded	10283
11/4/2020 10:59:43 AM	ipv4	datagrams received delivered/sec	14.7789
11/4/2020 10:59:43 AM	ipv4	datagrams sent/sec	12.8083
11/4/2020 10:59:43 AM	ipv4	datagrams outbound discarded	41
11/4/2020 10:59:43 AM	ipv4	datagrams outbound no route	26
11/4/2020 10:59:43 AM	ipv4	fragments received/sec	0
11/4/2020 10:59:43 AM	ipv4	fragments re-assembled/sec	0
11/4/2020 10:59:43 AM	ipv4	fragment re-assembly failures	0
11/4/2020 10:59:43 AM	ipv4	fragmented datagrams/sec	0
11/4/2020 10:59:43 AM	ipv4	fragmentation failures	0
11/4/2020 10:59:43 AM	ipv4	fragments created/sec	0

```
PS C:\>
```

```
PS C:\> Get-MyCounter -computername think1.prospero | Sort-Object -Property Computername
```

computername: PROSPERO

Timestamp	Category	Counter	Value
11/4/2020 11:17:42 AM	network interface(intel[r] ethernet connection [11] 1218 1n)	bytes total/sec	34005.154
11/4/2020 11:17:42 AM	network interface(intel[r] wi-fi 8 ax201 160mhz)	bytes total/sec	5
11/4/2020 11:17:42 AM	processor(_total)	% processor time	1.2988
11/4/2020 11:17:42 AM	memory	% committed bytes in use	40.3811
11/4/2020 11:17:42 AM	memory	cache faults/sec	0
11/4/2020 11:17:42 AM	physical disk(_total)	% disk time	0.1027
11/4/2020 11:17:42 AM	physical disk(_total)	current disk queue length	0

computername: think1

Timestamp	Category	Counter	Value
11/4/2020 11:17:44 AM	network interface(intel[r] ethernet connection [7] 1219 v)	bytes total/sec	0
11/4/2020 11:17:44 AM	network interface(rockip loopback adapter)	bytes total/sec	0
11/4/2020 11:17:44 AM	network interface(intel[r] wireless ac 9560 160mhz)	bytes total/sec	32630.3095
11/4/2020 11:17:44 AM	processor(_total)	% processor time	0.5377
11/4/2020 11:17:44 AM	memory	% committed bytes in use	13.2772
11/4/2020 11:17:44 AM	memory	cache faults/sec	0
11/4/2020 11:17:44 AM	physical disk(_total)	% disk time	0
11/4/2020 11:17:44 AM	physical disk(_total)	current disk queue length	0

One advantage of Get-MyCounter over Get-Counter is that the performance data is easier to work with.

```
Get-MyCounter '\IPv4\datagrams/sec' -MaxSamples 60 -SampleInterval 5 -computer SRV1 | Export-CSV c:\work\srv1_ipperf.csv -NoTypeInfo
```

In this example, the performance counter is sampled 60 times every 5 seconds and the data is exported to a CSV file which could easily be opened in Microsoft Excel. Here's a sample of the output object.

```
Computername : SRV1
Category      : ipv4
Counter       : datagrams/sec
Instance      :
Value         : 66.0818918347238
Timestamp     : 11/4/2022 11:31:29 AM
```

`Get-MyCounter` writes a custom object to the pipeline which has an associated formatting file with custom views.

```
PS C:\> Get-MyCounter -ComputerName ThinkP1 | Format-table -view category
```

Category: network interface(intel[r] ethernet connection [7] i219-v)

Computername	Timestamp	Counter	Value
THINKP1	11/4/2020 11:21:27 AM	bytes total/sec	0

Category: network interface(npcap loopback adapter)

Computername	Timestamp	Counter	Value
THINKP1	11/4/2020 11:21:27 AM	bytes total/sec	0

Category: network interface(intel[r] wireless-ac 9560 160mhz)

Computername	Timestamp	Counter	Value
THINKP1	11/4/2020 11:21:27 AM	bytes total/sec	26231.2466

Category: processor(_total)

Computername	Timestamp	Counter	Value
THINKP1	11/4/2020 11:21:27 AM	% processor time	1.1277

Category: memory

Computername	Timestamp	Counter	Value
THINKP1	11/4/2020 11:21:27 AM	% committed bytes in use	13.2964
THINKP1	11/4/2020 11:21:27 AM	cache faults/sec	0

Category: physicaldisk(_total)

Computername	Timestamp	Counter	Value
THINKP1	11/4/2020 11:21:27 AM	% disk time	0

Get-DirectoryInfo

This command, which has an alias of *dw*, is designed to provide quick access to top-level directory information.

The default behavior is to show the total number of files in the immediate directory. Although, the command will also capture the total file size in the immediate directory. You can use the Depth parameter to recurse through a specified number of levels. The default displays use ANSI escape sequences.

```
PS C:\> Get-DirectoryInfo D:\

Path: D:\

autolab [0]      backtemp [0]      Backup [3]      Backups [1]      bovine320 [0]
Databases [0]    Experts [0]        iso [0]          JDHIT [20]       Logitech [0]
MailRecovery [0] NewTiny340 [17]    OneDrive [1]    rip [5]          temp [17]
video [1]        VMDisks [5]        VMs [0]          Windows10Upgrade [2]
```

The command output will use a wide format by default. However, other wide views are available.

```
PS C:\> Get-DirectoryInfo D:\ -Depth 1 | Format-Wide -View sizemb

Path: D:\

autolab [0MB]      backtemp [0MB]      Backups [140.49MB]
Backup [0.01MB]    Databases [0MB]     iso [16137.65MB]
bovine320 [0MB]    Experts [0MB]        Logitech [0MB]
JDHIT [35.58MB]    NewTiny340 [1782.17MB]
MailRecovery [0MB] rip [60.99MB]
OneDrive [0MB]     temp [10.67MB]       video [83.56MB]
VMDisks [68053MB] VMs [0MB]
Windows10Upgrade [6807.64MB]

Path: D:\autolab

Configurations [0MB]
ISOs [16058.7MB]
Resources [0MB]

Path: D:\bovine320

Scripting [5.19MB]

Hotfixes [0MB]
MasterVirtualHardDisks [21292MB]
VMVirtualHardDisks [0MB]


TickleEvent [101MB]
```

You can use the object in other ways.

```
PS C:\> Get-DirectoryInfo D:\onedrive\Presentations\ | format-table -GroupBy Parent -Property Name,File*
```

Parent: D:\onedrive\Presentations

Name	FileCount	FileSize
Azure-PowerShell-DeepDive	1	25664889
Creating CIM Commands	11	2989760
Creating REST Tools	6	107122
DataDecisions	5	3288395
Intro to DSC	11	14924113
JEA	1	4052530
JEA-Fundamentals	3	6287972
PowerShell Scheduled Jobs	3	1056828
PowerShell Scripting Secrets	1	1588874
PowerShell Traps	5	6348269
PowerShell Workshop	1	8229621
PSChat	3	1309
PSChat19	3	1378512
PSChicago2020	3	3917202
PSConfAsia18	1	14888282



Get-FormatView

PowerShell's formatting system includes several custom views that display objects in different ways. Unfortunately, this information is not readily available to a typical PowerShell user. This command displays the available views for a given object type.

```
PS C:\> Get-FormatView system.serviceprocess.servicecontroller
```

Type: System.ServiceProcess.ServiceController

Format	Name
Table	service
List	System.ServiceProcess.ServiceController
Table	service
Table	Ansi

This command has an alias of `gfv`.

Copy-PSFunction

This command is designed to solve the problem when you want to run a function loaded locally on a remote computer. `Copy-PSFunction` will copy a PowerShell function that is loaded in your current PowerShell session to a remote PowerShell session. The remote session must already be created. The copied function only exists remotely for the duration of the remote PowerShell session.

```
$s = New-PSSession -ComputerName win10 -cred $art
Copy-PSFunction Get-Status -Session $s
```


Once copied, you might use `Invoke-Command` to run it.

```
Invoke-Command { Get-Status -AsString } -session $s
```

If the function relies on external or additional files, you will have to copy them to the remote session separately.

Get-PSProfile

This command is designed for Windows systems and makes it easy to identify all possible PowerShell profile scripts. Including those for hosts such as VSCode or the PowerShell ISE. The command writes a custom object to the pipeline which has defined formatting. The default view is a table.

```
PS C:\> Get-PSProfile

Name: PowerShell

Scope      Path                                     Exists
-----
AllUsersCurrentHost C:\Program Files\PowerShell\7\Microsoft.PowerShell_profile.ps1 False
AllUsersAllHosts   C:\Program Files\PowerShell\7\profile.ps1 False
CurrentUserAllHosts C:\Users\Jeff\Documents\PowerShell\profile.ps1 True
CurrentUserCurrentHost C:\Users\Jeff\Documents\PowerShell\Microsoft.PowerShell_profile.ps1 True

Name: Windows PowerShell

Scope      Path                                     Exists
-----
AllUsersCurrentHost C:\WINDOWS\System32\WindowsPowerShell\v1.0\Microsoft.PowerShell... True
AllUsersAllHosts   C:\WINDOWS\System32\WindowsPowerShell\v1.0\profile.ps1 True
CurrentUserAllHosts C:\Users\Jeff\Documents\WindowsPowerShell\profile.ps1 True
CurrentUserCurrentHost C:\Users\Jeff\Documents\WindowsPowerShell\Microsoft.PowerShell_p... True
```

There is also a list view.

```
PS C:\> Get-PSProfile | Where-Object {$_.name -eq 'powershell'} | Format-List

Name: PowerShell

Scope      : AllUsersCurrentHost
Path       : C:\Program Files\PowerShell\7\Microsoft.PowerShell_profile.ps1
Exists     : False
LastModified :

Scope      : AllUsersAllHosts
Path       : C:\Program Files\PowerShell\7\profile.ps1
Exists     : False
LastModified :

Scope      : CurrentUserAllHosts
Path       : C:\Users\Jeff\Documents\PowerShell\profile.ps1
Exists     : True
LastModified : 9/9/2024 2:35:45 PM
```

```

Scope      : CurrentUserCurrentHost
Path       : C:\Users\Jeff\Documents\PowerShell\Microsoft.PowerShell_profile.ps1
Exists     : True
LastModified : 9/9/2024 2:03:44 PM

```

Get-MyAlias

Often you might define aliases for functions and scripts you use all of the time. It may be difficult sometimes to remember them all or to find them in the default `Get-Alias` output. This command will list all currently defined aliases that are not part of the initial PowerShell state.

```

PS C:\> Get-MyAlias

```

CommandType	Name	Version	Source
Alias	awk -> awk.exe		
Alias	cart -> ConvertTo-ASCIIart		
Alias	cb -> Set-Clipboard		
Alias	cc -> Copy-Command	2.27.0	PSScriptTools
Alias	cfn -> New-CustomFileName	2.27.0	PSScriptTools
Alias	cft -> ConvertFrom-Text	2.27.0	PSScriptTools
Alias	chc -> Convert-HashtableToCode	2.27.0	PSScriptTools
Alias	che -> Copy-HelpExample	2.27.0	PSScriptTools
Alias	clr -> Convert-EventLogRecord	2.27.0	PSScriptTools
Alias	clt -> ConvertTo-LocalTime	2.27.0	PSScriptTools
Alias	cno -> Compare-Module	2.27.0	PSScriptTools
Alias	ctm -> ConvertTo-Markdown	2.27.0	PSScriptTools
Alias	cwg -> ConvertTo-WPGrid	2.27.0	PSScriptTools
Alias	daily -> dailysummary.ps1		
Alias	df -> Get-DiskFree		
Alias	dirdate -> Get-Dirdate		
Alias	fcc -> Find-CimClass	2.27.0	PSScriptTools
Alias	ff -> firefox.exe		
Alias	fnx -> Format-Nex	7.0.0.0	Microsoft.PowerShell.Utility
Alias	fmo -> Find-Module	2.2.4.1	PowerShellGet
Alias	first -> Select-First	2.27.0	PSScriptTools
Alias	fp -> Format-Percent	2.27.0	PSScriptTools
Alias	frut -> ConvertFrom-UTCtime	2.27.0	PSScriptTools
Alias	fs -> Format-String	2.27.0	PSScriptTools
Alias	fv -> Format-Value	2.27.0	PSScriptTools
Alias	gcb -> Get-Clipboard	7.0.0.0	Microsoft.PowerShell.Management
Alias	gcm2 -> Get-Command2		
Alias	gih -> Get-ComputerInfo	7.0.0.0	Microsoft.PowerShell.Management
Alias	gma -> Get-MyAlias	2.27.0	PSScriptTools

These are all aliases defined in the current session that aren't part of the initial session state. You can filter aliases to make it easier to find those that aren't defined in a module. These aliases should be ones created in your stand-alone scripts or PowerShell profile.

```

PS C:\> Get-MyAlias -NoModule

```

CommandType	Name	Version	Source
Alias	awk -> awk.exe		
Alias	cart -> ConvertTo-ASCIIart		
Alias	cb -> Set-Clipboard		
Alias	daily -> dailysummary.ps1		
Alias	df -> Get-DiskFree		
Alias	dirdate -> Get-Dirdate		
Alias	ff -> firefox.exe		
Alias	gcm2 -> Get-Command2		
Alias	gmf -> Get-MyFunctions		
Alias	grep -> grep.exe		
Alias	grok -> Get-Help		
Alias	gst -> Get-Status		

The PSScriptTools module also includes a custom formatting file for alias objects which you can use with `Get-Alias` or `Get-MyAlias`.

Get-Alias | Sort-Object Source | Format-Table -View source

```

gcb          Get-Clipboard
gtz          Get-TimeZone
gin          Get-ComputerInfo
scb          Set-Clipboard

Source: Microsoft.PowerShell.Utility 7.0.0.0

Name          Definition
----          -
fhx          Format-Hex

Source: PowerShellGet 2.2.4.1

Name          Definition
----          -
inmo          Install-Module
pumo          Publish-Module
upmo          Update-Module
fimo          Find-Module

Source: PSScriptTools 2.27.0

Name          Definition
----          -
Tee-Verbose   Out-VerboseTee
tex           Test-Expression
pswho         Get-PSWho
che           Copy-HelpExample

```

This command has an alias of `gma`.

Get-ModuleCommand

This is an alternative to `Get-Command` to make it easier to see at a glance what commands are contained within a module and what they can do. By default, `Get-ModuleCommand` looks for loaded modules. Use `-ListAvailable` to see commands in the module not currently loaded. Note that if the help file is malformed or missing, you might get oddly formatted results.

```
PS C:\> Get-ModuleCommand PSCalendar -ListAvailable
```

```
ModuleName: PSCalendar [v2.9.0]
```

```
Name          Alias Synopsis
```

```

-----
Get-Calendar          cal  Displays a visual representation of a
                        calendar.
Get-MonthName         Get the list of month names.
Get-NCalendar         ncal Display a Linux-style ncal calendar.
Get-PSCalendarConfiguration Get the current PSCalendar ANSI configuration.
Set-PSCalendarConfiguration Modify the PSCalendar ANSI configuration.
Show-Calendar         scal Display a colorized calendar month in the
                        console.
Show-GuiCalendar      gcal Display a WPF-based calendar.
Show-PSCalendarHelp   Display a help PDF file for the PSCalendar
                        module.

```

There are also alternate table views.

```

PS C:\> Get-ModuleCommand PSCalendar | Format-Table -View verb

    Verb: Get

Name           Alias      Type      Synopsis
----
Get-Calendar   cal        Function  Displays a visual
                        representation of a
                        calendar.
Get-MonthName             Function  Get the list of
                        month names.
Get-NCalendar   ncal      Function  Display a
                        Linux-style ncal
                        calendar.
Get-PSCalendarConfiguration Function  Get the current
                        PSCalendar ANSI
                        configuration.

    Verb: Set

Name           Alias      Type      Synopsis
----
Set-PSCalendarConfiguration Function  Modify the
                        PSCalendar ANSI
                        configuration.

    Verb: Show

Name           Alias      Type      Synopsis
----
Show-Calendar   scal      Function  Display a colorized
                        calendar month in
                        the console.
Show-GuiCalendar gcal      Function  Display a WPF-based
                        calendar.
Show-PSCalendarHelp   Function  Display a help PDF
                        file for the
                        PSCalendar module.

```

Get module commands using the default formatted view. There is also a default view for `Format-List`.

Get-PSScriptTools

You can use this command to get a summary list of functions in this module.

```
PS C:\> Get-PSScriptTools

Verb: Add

Name           Alias           Synopsis
----           -
Add-Border           Create a text border around a string.

Verb: Compare

Name           Alias           Synopsis
----           -
Compare-Module cmo           Compare PowerShell module versions.
...
```

Here's another way you could use this command to list functions with defined aliases in the PSScriptTools module.

```
PS C:\> Get-PSScriptTools | Where-Object alias |
Select-Object Name,alias,Synopsis

Name           Alias Synopsis
----           -
Compare-Module cmo           Compare PowerShell module versions.
Convert-EventLogRecord clr       Convert EventLogRecords to structured objects
ConvertFrom-Text cft         Convert structured text to objects.
ConvertFrom-UTCTime frut        Convert a datetime value from universal
ConvertTo-LocalTime clt         Convert a foreign time to local
...
```

Convert-EventLogRecord

When you use [Get-WinEvent](#), the results are objects you can work with in PowerShell. However, often, there is additional information that is part of the event log record, such as replacement strings, that are used to construct a message. This additional information is not readily exposed. You can use this command to convert the results of a `Get-WinEvent` command into a PowerShell custom object with additional information.

```
PS C:\> Get-WinEvent -FilterHashtable @{LogName='System';ID=7045} -MaxEvents 1 |
Convert-EventLogRecord

LogName       : System
RecordType    : Information
TimeCreated   : 1/21/2024 3:49:46 PM
ID            : 7045
ServiceName   : Netwrix Account Lockout Examiner
ImagePath     : "C:\Program Files (x86)\Netwrix\Account Lockout Examiner
               \ALEService.exe"
ServiceType   : user mode service
```

```
StartType      : auto start
AccountName    : bovine320\jeff
Message        : A service was installed in the system.

                Service Name: Netwrix Account Lockout Examiner
                Service File Name: "C:\Program Files (x86)\Netwrix\Account
                Lockout Examiner\ALEService.exe"
                Service Type: user mode service
                Service Start Type: auto start
                Service Account: bovine320\jeff
Keywords       : {Classic}
Source         : Service Control Manager
Computername   : Bovine320
```

Get-WhoIs

This command will retrieve WhoIs information from the ARIN database for a given IPv4 address.

```
PS C:\> Get-WhoIs 208.67.222.222 | Select-Object -Property *

IP                : 208.67.222.222
Name              : OPENDNS-NET-1
RegisteredOrganization : Cisco OpenDNS, LLC
City              : San Jose
StartAddress      : 208.67.216.0
EndAddress        : 208.67.223.255
NetBlocks         : 208.67.216.0/21
Updated           : 12/14/2024 8:28:33 PM

PS C:\> '1.1.1.1','8.8.8.8','208.67.222.222' | Get-WhoIs | Format-List

IP                : 1.1.1.1
Name              : APNIC-1
RegisteredOrganization : Asia Pacific Network Information Centre
City              : South Brisbane
StartAddress      : 1.0.0.0
EndAddress        : 1.255.255.255
NetBlocks         : 1.0.0.0/8
Updated           : 7/30/2010 9:23:43 AM

IP                : 8.8.8.8
Name              : GOGL
RegisteredOrganization : Google LLC
City              : Mountain View
StartAddress      : 8.8.8.0
EndAddress        : 8.8.8.255
NetBlocks         : 8.8.8.0/24
Updated           : 12/28/2023 5:24:56 PM

IP                : 208.67.222.222
Name              : OPENDNS-NET-1
RegisteredOrganization : Cisco OpenDNS, LLC
City              : San Jose
StartAddress      : 208.67.216.0
EndAddress        : 208.67.223.255
NetBlocks         : 208.67.216.0/21
Updated           : 12/14/2024 8:28:33 PM
```

This module includes a custom format file for these results.

Compare-Module

Use this command to compare module versions between what is installed against an online repository like the PSGallery

```
PS C:\> Compare-Module Platyps

Name           : platyps
OnlineVersion   : 0.14.2
InstalledVersion : 0.14.2
PublishedDate   : 7/2/2024 10:53:28 PM
UpdateNeeded    : False
```

Or you can compare and manage multiple modules.

```
Compare-Module | Where UpdateNeeded |
Out-GridView -title "Select modules to update" -outputMode multiple |
Foreach { Update-Module $_.name }
```

This example compares modules and sends the results to Out-GridView. Use Out-GridView as an object picker to decide what modules to update.

Get-WindowsVersion

This is a PowerShell version of the `winver.exe` utility. This command uses PowerShell remoting to query the registry on a remote machine to retrieve Windows version information.

```
Get-WindowsVersion -Computersname win10,srv1,srv2 -Credential company\artd
```

```
Computersname: WIN10
-----
ProductName      EditionID      ReleaseID      Build      InstalledUTC
-----
Windows 10 Enterprise Evaluation  EnterpriseEval  1909      18363      5/30/2020 2:49:55 PM

Computersname: SRV1
-----
ProductName      EditionID      ReleaseID      Build      InstalledUTC
-----
Windows Server 2016 Standard Evaluation  ServerStandardEval  1607      14393      5/30/2020 2:49:15 PM

Computersname: SRV2
-----
ProductName      EditionID      ReleaseID      Build      InstalledUTC
-----
Windows Server 2016 Standard Evaluation  ServerStandardEval  1607      14393      5/30/2020 2:50:00 PM
```

The output has a default table view but there are other properties you might want to use.

```
PS C:\> Get-WindowsVersion | Select-Object *

ProductName      : Microsoft Windows 11 Pro
ReleaseVersion   : 24H2
EditionID        : Professional
ReleaseID        : 2009
Build            : 26100.3613
Branch           : ge_release
InstalledUTC     : 6/17/2024 1:30:52 AM
Computersname    : PROSPERO
```

Beginning with version 2.45.0, `Get-WindowsVersion` will use the command-line tool `systeminfo.exe` to retrieve the operating system name. If this fails, then the registry value will be used. Windows 11 systems don't yet reflect with Windows 11 name in the registry.

Get-WindowsVersionString

This command is a variation of `Get-WindowsVersion` that returns a formatted string with version information.

```
PS C:\> Get-WindowsVersionString
PROSPERO Microsoft Windows 11 Pro Version Professional (OS Build 26100.3613)
```

New-PSDriveHere

This function will create a new PSDrive at the specified location. The default is the current location, but you can specify any `PSPath`. by default, the function will take the last word of the path and use it as the name of the new PSDrive.

```
PS C:\users\jeff\documents\Enterprise Mgmt Webinar> New-PSDriveHere -SetLocation
PS Webinar:\>
```

You can use the first word in the leaf location or specify something completely different.

```
New-PSDriveHere \\ds416\backup\ Backup
```

Get-MyVariable

This function will return all variables not defined by PowerShell or by this function itself. The default is to return all user-created variables from the global scope, but you can also specify a scope such as `script`, `local`, or a number 0 through 5.

```
PS C:\> Get-MyVariable

NName Value                                Type
----
a      bits                                ServiceController
dt      10/22/2024 10:49:38 AM              DateTime
foo     123                                  Int32
```

```
r {1, 2, 3, 4...}      Object[]
...
```

Depending on the value and how PowerShell chooses to display it, you may not see the type.

ConvertFrom-Text

This command can be used to convert text from a file or a command-line tool into objects. It uses a regular expression pattern with named captures and turns the result into a custom object. You have the option of specifying a type name in case you are using custom format files.

```
PS C:\> $arp = '(?<IPAddress>(\d{1,3}\.){3}\d{1,3})\s+(?<MAC>(\w{2}-){5}\w{2})\s+(?<Type>\w+)$'
PS C:\> arp -g -N 172.16.10.22 | Select-Object -skip 3 |
foreach {$_.Trim()} | ConvertFrom-Text $arp -TypeName arpData -NoProgress
```

IPAddress	MAC	Type
-----	---	----
172.16.10.1	b6-fb-e4-16-41-be	dynamic
172.16.10.100	00-11-32-58-7b-10	dynamic
172.16.10.115	5c-aa-fd-0c-bf-fa	dynamic
172.16.10.120	5c-1d-d9-58-81-51	dynamic
172.16.10.159	3c-e1-a1-17-6d-0a	dynamic
172.16.10.162	00-0e-58-ce-8b-b6	dynamic
172.16.10.178	00-0e-58-8c-13-ac	dynamic
172.16.10.185	d0-04-01-26-b5-61	dynamic
172.16.10.186	e8-b2-ac-95-92-98	dynamic
172.16.10.197	fc-77-74-9f-f4-2f	dynamic
172.16.10.211	14-20-5e-93-42-fb	dynamic
172.16.10.222	28-39-5e-3b-04-33	dynamic
172.16.10.226	00-0e-58-e9-49-c0	dynamic
172.16.10.227	48-88-ca-e1-a6-00	dynamic
172.16.10.239	5c-aa-fd-83-f1-a4	dynamic
172.16.255.255	ff-ff-ff-ff-ff-ff	static
224.0.0.2	01-00-5e-00-00-02	static
224.0.0.7	01-00-5e-00-00-07	static
224.0.0.22	01-00-5e-00-00-16	static
224.0.0.251	01-00-5e-00-00-fb	static
224.0.0.252	01-00-5e-00-00-fc	static
239.255.255.250	01-00-5e-7f-ff-fa	static

This example uses a previously created and imported format.ps1xml file for the custom type name.

Get-PSWho


This command will provide a summary of relevant information for the current user in a PowerShell Session. You might use this to troubleshoot an end-user problem running a script or command.

```
PS C:\> Get-PSWho

User           : COMPANY\ArtD
Elevated       : True
Computername   : WIN10
OperatingSystem : Microsoft Windows 10 Enterprise [64-bit]
OSVersion      : 10.0.19045
```

```
PSVersion      : 5.1.19041.5607
Edition       : Desktop
PSTHost       : ConsoleHost
WSMan         : 3.0
ExecutionPolicy : RemoteSigned
Culture       : English (United States)
```

You can also turn this into a text block using the `AsString` parameter. This is helpful when you want to include the output in some type of report.



The screenshot shows a Windows PowerShell window with a blue title bar that reads "Admin: PowerShell 7.0". The command prompt shows the following commands and output:

```
PS C:\>
PS C:\> add-border -textblock (get-pswho -asstring) -ANSIBorder ""e[92m" -border $PSSpecialChar.Lozenge
```

The output is a table of system information enclosed in a green border made of Lozenge characters. The table content is as follows:

User	: BOVINE320\Jeff
Elevated	: True
Computername	: BOVINE320
OperatingSystem	: Microsoft Windows 10 Pro [64-bit]
OSVersion	: 10.0.18363
PSVersion	: 7.8.1
Edition	: Core
PSHost	: ConsoleHost
WSMan	: 3.8
ExecutionPolicy	: RemoteSigned
Culture	: English (United States)

The prompt returns to "PS C:\>" after the output.

Out-VerboseTee

This command is intended to let you see your verbose output and write the verbose messages to a log file. It will only work if the verbose pipeline is enabled, usually when your command is run with `-Verbose`. This function is designed to be used within your scripts and functions. You either have to hard-code a file name or find some other way to define it in your function or control script. You could pass a value as a parameter or set it as a `PSDefaultParameterValue`.

This command has aliases `Tee-Verbose` and `tv`.

```
Begin {
    $log = New-RandomFilename -useTemp -extension log
    Write-Detail "Starting $($MyInvocation.MyCommand)" -Prefix begin |
    Tee-Verbose $log
    Write-Detail "Logging verbose output to $log" -prefix begin |
    Tee-Verbose -append
    Write-Detail "Initializing data array" -Prefix begin |
    Tee-Verbose $log -append
    $data = @()
} #begin
```


When the command is run with `-Verbose` you will see the verbose output **and** it will be saved to the specified log file.

Remove-Runspace

Throughout your PowerShell work, you may discover that some commands and scripts can leave behind runspaces such as `ConvertTo-WPFGrid`. You may even deliberately be creating additional runspaces. These runspaces will remain until you exit your PowerShell session. Or use this command to cleanly close and dispose of runspaces.

```
Get-Runspace | where ID -gt 1 | Remove-Runspace
```

Get all runspaces with an ID greater than 1, which is typically your current session, and remove the runspace.

Get-PSLocation

A simple function to get common locations. This can be useful with cross-platform scripting.

```
PS C:\> Get-PSLocation

Temp       : C:\Users\Jeff\AppData\Local\Temp\
Home       : C:\Users\Jeff\Documents
Desktop    : C:\Users\Jeff\Desktop
PowerShell : C:\Users\Jeff\Documents\PowerShell
PSHome     : C:\Program Files\PowerShell\7

PS C:\> _
```

```
PS /home/jeff> Get-PSLocation

Temp       : /tmp/
Home       : /home/jeff
Desktop    :
PowerShell : /home/jeff/.config/powershell
PSHome     : /opt/microsoft/powershell/7
```

Get-PowerShellEngine


Use this command to quickly get the path to the PowerShell executable. In Windows, you should get a result like this:

```
PS C:\> Get-PowerShellEngine
C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe
```

But PowerShell on non-Windows platforms is a bit different:

```
PS /home/jhicks> Get-PowerShellEngine
/opt/microsoft/powershell/7/pwsh
```

You can also get detailed information.



A terminal window with a black background and white text. The prompt is 'PS /home/jhicks>'. The command entered is 'Get-PowerShellEngine -Detail'. The output is a list of properties and their values: Path, FileVersion, PSVersion, ProductVersion, Edition, Host, Culture, and Platform.


```
PS /home/jhicks>
PS /home/jhicks> Get-PowerShellEngine -Detail

Path       : /opt/microsoft/powershell/6.0.0-rc/pmsh
FileVersion :
PSVersion  : 6.0.0-rc
ProductVersion :
Edition    : Core
Host       : ConsoleHost
Culture    : en-US
Platform   : Unix
```

Results will vary depending on whether you are running PowerShell on Windows or non-Windows systems.

Get-PathVariable

Over time, as you add and remove programs, your %PATH% might change. An application may add a location but not remove it when you uninstall the application. This command makes it easier to identify locations and whether they are still good.

A terminal window with a dark background and light text. The prompt is 'PS C:\>'. The command entered is 'Get-PathVariable'. The output is a table with four columns: Scope, UserName, Path, and Exists. The table lists several paths and their existence status.

```
PS C:\> Get-PathVariable

Scope  UserName Path                                Exists
-----
User   Jeff    C:\Program Files\kdiff3                True
User   Jeff    C:\Program Files (x86)\Bitwise SSH Client True
User   Jeff    C:\Program Files\OpenSSH                True
User   Jeff    C:\Program Files\Intel\WiFi\bin\        True
User   Jeff    C:\Program Files\Common Files\Intel\WirelessCommon\ True
User   Jeff    C:\Users\Jeff\AppData\Local\Programs\Microsoft VS Co... True
User   Jeff    C:\Program Files (x86)\Vale\            True
...
```

File Tools

Get-LastModifiedFile

Get files last modified within a certain interval. The default is 24 hours.

```
PS C:\> Get-LastModifiedFile -Path c:\work

Directory: C:\work

Mode                LastWriteTime         Length Name
----                -
-a---             11/30/2024   1:52 PM          2010 a.txt
-a---             11/30/2024   1:52 PM          5640 b.txt
```

But you can specify other ranges.

```
PS C:\> Get-LastModifiedFile -Path c:\scripts -filter *.xml -Interval Months -IntervalCount 6

Directory: C:\Scripts

Mode                LastWriteTime         Length Name
----                -
-a---             8/31/2024   7:12 PM          17580 DefaultDomainPolicy.xml
-a---             8/31/2024   7:12 PM          17290 PKIAutoEnroll.xml
-a---             8/31/2024   8:43 PM           9786 sample-gpo.xml
-a---             8/31/2024   7:24 PM          50062 TestUser.xml
-a---             6/22/2024   7:47 PM           4628 vaults.xml
```

You might use this command with other PowerShell commands to get usage statistics.

```
PS C:\> Get-LastModifiedFile -Path c:\scripts -Recurse -Interval Years -IntervalCount 1 |
Group-Object {$_.LastWriteTime.month} |
Select-Object @{Name="Month";Expression = "{0:MMM}" -f (Get-Date -Month $_.Name)}},
Count

Month Count
-----
Jan      152
Feb      200
Mar      228
Apr      169
May      106
Jun       92
Jul       86
Aug      112
Sep      109
Oct      136
Nov      225
Dec      216
```

Get-FileExtensionInfo

This command will search a given directory and produce a report of all files based on their file extension. This command is only available in PowerShell 7. The extension with the largest total size will be highlighted in color.

```
PS C:\> Get-FileExtensionInfo -Path c:\scripts -Recurse | Sort-object Count -descending |
>> Select-Object -first 20
```

Path: C:\scripts [PROSPERO]

Extension	Count	TotalSize	Smallest	Average	Largest
.ps1	4890	21366917	0	4369.51	502858
.md	820	3346884	0	4081.57	92654
.txt	697	24704216	0	35443.64	5329533
.json	367	1062612	24	2895.4	356232
.png	302	43042979	1270	142526.42	1565971
.psml	294	3237702	24	11012.59	227866
.ps1xml	218	876749	137	4021.78	17454
.psd1	211	1047045	50	4962.3	23530
.xml	137	88782742	166	648049.21	83457712
.zip	130	40525187	24	311732.21	18559167
.mof	100	188981	214	1889.81	51120
.csv	86	3399223	67	39525.85	1164546
.pdf	66	66870599	23922	1013190.89	13627600
.pptx	57	72096503	333902	1264850.93	3592374
.wsf	33	531104	3444	16094.06	254328
	29	1547000	0	53344.83	1519288
.vbs	28	10766405	30	384514.46	6238714
.exe	28	60332664	2938	2154738	51891200
.docx	28	994142	12944	35505.07	124806
.jpg	26	1601735	807	61605.19	201244

Test-EmptyFolder

This command will test if a given folder path is empty of all files anywhere in the path. This includes hidden files. The command will return True even if there are empty sub-folders. The default output is True or False but you can use -PassThru to get more information.

```
PS C:\> Get-ChildItem c:\work -Directory | Test-EmptyFolder -PassThru |
Where-Object {$_.IsEmpty} |
Foreach-Object { Remove-Item -LiteralPath $_.path -Recurse -force -WhatIf}

What if: Performing the operation "Remove Directory" on target "C:\work\demo3".
What if: Performing the operation "Remove Directory" on target "C:\work\installers".
What if: Performing the operation "Remove Directory" on target "C:\work\new".
What if: Performing the operation "Remove Directory" on target "C:\work\sqlback".
What if: Performing the operation "Remove Directory" on target "C:\work\todd".
What if: Performing the operation "Remove Directory" on target "C:\work\[data]".
```

Find all empty sub-folders under C:\Work and pipe them to Remove-Item. This is one way to remove empty folders. The example is piping objects to ForEach-Object so that Remove-Item can use the -LiteralPath parameter because C:\work\[data] is a non-standard path.

Get-FolderSizeInfo

Use this command to quickly get the size of a folder. You also have the option to include hidden files. The command will measure all files in all subdirectories.

```
PS C:\> Get-FolderSizeInfo c:\work
```

Computername	Path	TotalFiles	TotalSize
BOVINE320	C:\work	931	137311146

```
PS C:\> Get-FolderSizeInfo c:\work -Hidden
```

Computername	Path	TotalFiles	TotalSize
BOVINE320	C:\work	1375	137516856

The command includes a format file with an additional view to display the total size in KB, MB, GB, or TB.

```
PS C:\> Get-ChildItem D:\ -Directory | Get-FolderSizeInfo -Hidden |
Where-Object TotalSize -gt 1gb | Sort-Object TotalSize -Descending |
Format-Table -View gb
```

Computername	Path	TotalFiles	TotalSizeGB
BOVINE320	D:\Autolab	159	137.7192
BOVINE320	D:\VMDisks	18	112.1814
BOVINE320	D:\ISO	17	41.5301
BOVINE320	D:\FileHistory	104541	36.9938
BOVINE320	D:\Vagrant	13	19.5664
BOVINE320	D:\Vms	83	5.1007
BOVINE320	D:\2016	1130	4.9531
BOVINE320	D:\video	125	2.592
BOVINE320	D:\blog	21804	1.1347
BOVINE320	D:\pstranscripts	122092	1.0914

Or you can use the `name` view.

```
PS C:\> Get-ChildItem c:\work -Directory | Get-FolderSizeInfo -Hidden |
Where-Object {$_.TotalSize -ge 2mb} | Format-Table -view name
```

```
Path: C:\work
```

Name	TotalFiles	TotalKB
A	20	5843.9951
keepass	15	5839.084
PowerShellBooks	26	4240.3779
sunday	47	24540.6523

Optimize-Text

Use this command to clean and optimize content from text files. Sometimes text files have blank lines, or the content has trailing spaces. These sorts of issues can cause problems when passing the content to other commands.

This command will strip out any lines that are blank or have nothing by white space, and trim leading and trailing spaces. The optimized text is then written back to the pipeline. Optionally, you can specify a property name. This can be useful when your text file is a list of computer names and you want to take advantage of pipeline binding.

Get-FileItem

A PowerShell version of the CLI `where.exe` command. You can search with a simple or regex pattern.

```
PS C:\> pswhere winword.exe -Path c:\ -Recurse -first  
  
C:\Program Files\Microsoft Office\root\Office16\WINWORD.EXE
```

Note that you might see errors for directories where you don't have access permission. This is normal.

New-CustomFileName

This command will generate a custom file name based on a template string that you provide.

```
PS C:\> New-CustomFileName %computername_%day%monthname%yr-%time.log  
PC_28Nov19-142138.log  
  
PS C:\> New-CustomFileName %dayofweek-%####.dat  
Tuesday-3128.dat
```

You can create a template string using any of these variables. Most of these should be self-explanatory.

- %username
- %computername
- %year - 4-digit year
- %yr - 2-digit year
- %monthname - The abbreviated month name
- %month - The month number
- %dayofweek - The full name of the weekday
- %day
- %hour
- %minute
- %time

- %string - A random string
- %guid

You can also insert a random number using % followed by a # character for each digit you want.

```
22 = ###  
654321 = #####
```

New-RandomFilename

Create a new random file name. The default is a completely random name, including the extension.

```
PS C:\> New-RandomFilename  
fykxecvh.ipw
```

But you can specify an extension.

```
PS C:\> New-RandomFilename -extension dat  
emevgq3r.dat
```

Optionally you can create a random file name using the TEMP folder or your HOME folder. On Windows platforms, this will default to your Documents folder.

```
PS C:\> New-RandomFilename -extension log -UseHomeFolder  
C:\Users\Jeff\Documents\kbyw4fda.log
```

On Linux machines, it will be the home folder.

```
PS /mnt/c/scripts> New-RandomFilename -home -Extension tmp  
/home/jhicks/oces0epq.tmp
```

ConvertTo-Markdown

This command is designed to accept pipelined output and create a markdown document. The pipeline output will be formatted as a text block or a table. You can optionally define a title, content to appear before the output, and content to appear after the output. You can run a command like this:

```
Get-Service Bits,Winrm |  
ConvertTo-Markdown -title "Service Check" -PreContent "## $($env:computername)"  
-PostContent "_report $(Get-Date)_"
```

which generates this markdown:

```
# Service Check
```



```
## THINKX1

```dos

Status Name DisplayName

Running Bits Background Intelligent Transfer Ser...
Running Winrm Windows Remote Management (WS-Manag...
```

_report 09/25/2024 09:57:12_
```

You also have the option to format the output as a markdown table.

```
ConvertTo-Markdown -title "OS Summary" -PreContent "## $($env:computername)" -PostContent "_Confidential_" -AsTable
```

Which creates this markdown output.

```
# OS Summary

## THINKX1-JH

ProductName	EditionID	ReleaseID	Build	Branch	InstalledUTC	Computername
Windows 10 Pro	Professional	2009	22000.376	co_release	08/10/2024 00:17:07	THINKX1-JH

_Confidential_
```

THINKX1-JH

| ProductName | EditionID | ReleaseID | Build | Branch | InstalledUTC | Computername |
|----------------|--------------|-----------|-----------|------------|---------------------|--------------|
| Windows 10 Pro | Professional | 2009 | 22000.376 | co_release | 08/10/2021 00:17:07 | THINKX1-JH |

Confidential

Or you can create a list table with the property name in one column and the value in the second column.

```
Get-WindowsVersion | ConvertTo-Markdown -title "OS Summary" -PreContent "## $($env:computername)" -PostContent "_Confidential_" -AsList
```

```
# OS Summary

## THINKX1-JH

ProductName	Windows 10 Pro
EditionID	Professional
ReleaseID	2009
Build	22000.376
Branch	co_release
InstalledUTC	8/10/2024 12:17:07 AM
```

```
| Computername | THINKX1-JH |
```

```
_Confidential_
```

OS Summary

THINKX1-JH

| | |
|--------------|-----------------------|
| ProductName | Windows 10 Pro |
| EditionID | Professional |
| ReleaseID | 2009 |
| Build | 22000.376 |
| Branch | co_release |
| InstalledUTC | 8/10/2021 12:17:07 AM |
| Computername | THINKX1-JH |

Confidential

Because the function writes markdown to the pipeline you will need to pipe it to a command `Out-File` to create a file.

Editor Integrations


Because this module is intended to make scripting easier for you, it adds a few editor-specific features if you import this module in either the PowerShell ISE or Visual Studio Code. The VS Code features assume you are using the integrated PowerShell terminal.

Insert ToDo


One such feature is the ability to insert ToDo statements into PowerShell files. If you are using the PowerShell ISE or VS Code and import this module, it will add the capability to insert a line like this:

```
# [12/13/2024 16:52:40] TODO: Add parameters
```

In the PowerShell ISE, you will get a new menu under Add-Ons.



You can use the menu or keyboard shortcut which will launch an input box.



The comment will be inserted at the current cursor location.

In VS Code, access the command palette (Ctrl+Shift+P) and then `PowerShell: Show Additional Commands from PowerShell Modules`. Select `Insert ToDo` from the list, and you'll get the same input box. Note that this will only work for PowerShell files.

Set Terminal Location

Another feature is the ability to set your terminal location to match that of the currently active file. For example, if the current file is located in `C:\Scripts\Foo` and your terminal location is `D:\Temp\ABC`, you can quickly jump to the file location.

```
PS D:\Temp\ABC\> sd
PS C:\Scripts\Foo\>
```


The full command name is `Set-LocationToFile` but you'll find it easier to use the `sd` or `jmp` aliases. This command will also clear the host.

Graphical Tools

Invoke-InputBox


This function is a graphical replacement for `Read-Host`. It creates a simple WPF form that you can use to get user input. The value of the text box will be written to the pipeline.

```
$name = Invoke-InputBox -Prompt "Enter a user name" -Title "New User Setup"
```



You can also capture a secure string.

```
Invoke-InputBox -Prompt "Enter a password for $Name" -AsSecureString  
-BackgroundColor red
```



This example also demonstrates that you can change the form's background color. This function will **not** work in PowerShell Core.

New-WPFMessageBox


This function creates a Windows Presentation Foundation (WPF) based message box. This is intended to

replace the legacy MsgBox function from VBScript and the Windows Forms library. The command uses a set of predefined button sets, each of which will close the form and write a value to the pipeline.

- OK = 1
- Cancel = 0
- Yes = \$True
- No = \$False


You can also create an ordered hashtable of buttons and values. It is assumed you will typically use this function in a script where you can capture the output and take some action based on the value.

```
New-WPFMessageBox -Message "Are you sure you want to do this?"  
-Title Confirm -Icon Question -ButtonSet YesNo
```



You can also create your a custom button set as well as modify the background color.

```
New-WPFMessageBox -Message "Select a system option from these choices:"  
-Title "You Decide" -Background cornsilk -Icon Warning  
-CustomButtonSet ([ordered]@{"Reboot"=1;"Shutdown"=2;"Cancel"=3})
```



ConvertTo-WPFGrid

This command is an alternative to `Out-GridView`. It works much the same way. Run a PowerShell command and pipe it to this command. The output will be displayed in an auto-sized data grid. You can click on column headings to sort. You can resize columns and you can re-order columns.

```
Get-Eventlog -list -ComputerName DOM1,SRV1,SRV2 |  
Select MachineName,Log,MaximumKilobytes,OverflowAction,  
@{Name="RetentionDays";Expression={$_.MinimumRetentionDays}},  
@{Name="Entries";Expression = {$_.entries.count}} |  
ConvertTo-WPFGrid -Title "Event Log Report"
```

Event Log Report

| MachineName | Log | MaximumKilobytes | OverflowAction | RetentionDays | Entries |
|-------------|-------------------------------|------------------|-------------------|---------------|---------|
| DOM1 | Active Directory Web Services | 512 | OverwriteOlder | 7 | 38 |
| DOM1 | Application | 20480 | OverwriteAsNeeded | 0 | 16722 |
| DOM1 | DFS Replication | 15168 | OverwriteAsNeeded | 0 | 39 |
| DOM1 | Directory Service | 512 | OverwriteAsNeeded | 0 | 291 |
| DOM1 | DNS Server | 102400 | OverwriteAsNeeded | 0 | 2762 |
| DOM1 | HardwareEvents | 20480 | OverwriteAsNeeded | 0 | 0 |
| DOM1 | Internet Explorer | 512 | OverwriteOlder | 7 | 0 |
| DOM1 | Key Management Service | 20480 | OverwriteAsNeeded | 0 | 0 |
| DOM1 | Security | 131072 | OverwriteAsNeeded | 0 | 194724 |
| DOM1 | System | 20480 | OverwriteAsNeeded | 0 | 8105 |
| DOM1 | Windows PowerShell | 15360 | OverwriteAsNeeded | 0 | 459 |
| SRV1 | Application | 20480 | OverwriteAsNeeded | 0 | 17377 |
| SRV1 | HardwareEvents | 20480 | OverwriteAsNeeded | 0 | 0 |
| SRV1 | Internet Explorer | 512 | OverwriteOlder | 7 | 0 |
| SRV1 | Key Management Service | 20480 | OverwriteAsNeeded | 0 | 0 |
| SRV1 | Security | 20480 | OverwriteAsNeeded | 0 | 30287 |
| SRV1 | System | 20480 | OverwriteAsNeeded | 0 | 7463 |
| SRV1 | Windows PowerShell | 15360 | OverwriteAsNeeded | 0 | 1209 |
| SRV2 | Application | 20480 | OverwriteAsNeeded | 0 | 15885 |
| SRV2 | HardwareEvents | 20480 | OverwriteAsNeeded | 0 | 0 |
| SRV2 | Internet Explorer | 512 | OverwriteOlder | 7 | 0 |
| SRV2 | Key Management Service | 20480 | OverwriteAsNeeded | 0 | 0 |
| SRV2 | Security | 20480 | OverwriteAsNeeded | 0 | 17536 |
| SRV2 | System | 20480 | OverwriteAsNeeded | 0 | 6529 |
| SRV2 | Windows PowerShell | 15360 | OverwriteAsNeeded | 0 | 274 |

last updated 02/12/2019 20:27:44

You can also automatically refresh the data.

```
Get-Process | Sort-Object WS -Descending |
Select-Object -first 20 ID,Name,WS,VM,PM,Handles,StartTime |
ConvertTo-WPFGrid -Refresh -timeout 20 -Title "Top Processes"
```


| Top Processes | | | | | | |
|---|--------------------|------------|---------------|------------|---------|-----------------------|
| Id | Name | WS | VM | PM | Handles | StartTime |
| 3092 | Memory Compression | 1747447808 | 1814691840 | 4161536 | 0 | 1/30/2019 9:46:01 AM |
| 16728 | Code | 745938944 | 2204812578816 | 775516160 | 638 | 2/12/2019 4:35:06 PM |
| 1472 | dwm | 373415936 | 2205525884928 | 1036087296 | 1292 | 1/30/2019 9:46:01 AM |
| 11976 | slack | 361508864 | 2204708483072 | 307527680 | 491 | 2/12/2019 1:02:50 PM |
| 6984 | Code | 248057856 | 2205164032000 | 244703232 | 530 | 2/12/2019 4:35:06 PM |
| 12612 | thunderbird | 232312832 | 1015586816 | 324341760 | 1028 | 2/12/2019 9:11:11 AM |
| 2544 | brave | 202432512 | 2204164759552 | 217972736 | 423 | 2/12/2019 10:39:54 AM |
| 13968 | slack | 187772928 | 2204290772992 | 237174784 | 714 | 1/30/2019 9:47:14 AM |
| 14700 | SugarSync | 183324672 | 464482304 | 241012736 | 1208 | 1/30/2019 9:46:38 AM |
| 13972 | brave | 168230912 | 2238674284544 | 302723072 | 2777 | 2/7/2019 9:32:50 AM |
| 3016 | powershell | 164237312 | 2204586930176 | 322105344 | 1620 | 2/12/2019 12:32:00 PM |
| 3844 | Code | 153067520 | 2204334030848 | 159526912 | 451 | 2/12/2019 4:35:08 PM |
| 22104 | powershell | 140689408 | 2204716986368 | 924684288 | 874 | 2/12/2019 4:35:10 PM |
| 2088 | ekrn | 138780672 | 2203913326592 | 122093568 | 956 | 1/30/2019 9:46:01 AM |
| 17264 | slack | 122294272 | 2205174013952 | 131186688 | 2617 | 1/30/2019 9:47:04 AM |
| 7016 | sqlservr | 120057856 | 46579154944 | 637329408 | 715 | 1/30/2019 9:46:02 AM |
| 24040 | brave | 114626560 | 2204050501632 | 137789440 | 418 | 2/12/2019 9:37:56 AM |
| 9996 | explorer | 109133824 | 2204844474368 | 195948544 | 3396 | 1/30/2019 9:46:08 AM |
| 22984 | WmiPrvSE | 99557376 | 2204058812416 | 81039360 | 1095 | 2/12/2019 8:18:23 PM |
| 17964 | ONENOTE | 98279424 | 637419520 | 60428288 | 1149 | 2/12/2019 5:49:47 PM |
| Last updated 02/12/2019 20:18:47 - refresh in 6 seconds | | | | | | |

Note that in v2.4.0 the form layout was modified and may not be reflected in these screenshots.

Hashtable Tools

Convert-CommandToHashtable

This command is intended to convert a long PowerShell expression with named parameters into a splatting alternative.

```
PS C:\> Convert-CommandToHashtable -Text "get-eventlog -listlog  
-computername a,b,c,d -ErrorAction stop"  
  
$paramHash = @{  
    listlog = $True  
    computername = "a","b","c","d"  
    ErrorAction = "stop"  
}  
  
Get-EventLog @paramHash
```

The idea is that you can copy the output of the command into a script file.

Convert-HashtableString

This function is similar to `Import-PowerShellDataFile`. But where that command can only process a file, this command will take any hashtable-formatted string and convert it into an actual hashtable.

```
PS C:\> Get-Content c:\work\test.psd1 | Unprotect-CMSMessage |  
Convert-HashtableString  
  
Name                               Value  
----                               -  
CreatedBy                          BOVINE320\Jeff  
CreatedAt                          10/02/2024 21:28:47 UTC  
Computername                       Think51  
Error                                
Completed                          True  
Date                               10/02/2024 21:29:35 UTC  
Scriptblock                        restart-service spooler -force  
CreatedOn                          BOVINE320
```

The test.psd1 file is protected as a CMS Message. In this example, the contents are decoded as a string which is then in turn converted into an actual hashtable.

Convert-HashtableToCode

Use this command to convert a hashtable into its text or string equivalent.

```
PS C:\> $h = @{Name="SRV1";Asset=123454;Location="Omaha"}  
PS C:\> Convert-HashtableToCode $h  
@{  
    Name = 'SRV1'  
    Asset = 123454  
}
```

```
    Location = 'Omaha'  
}
```

Convert a hashtable object to a string equivalent that you can copy into your script.

ConvertTo-Hashtable

This command will take an object and create a hashtable based on its properties. You can have the hashtable exclude some properties as well as properties that have no value.

```
PS C:\> Get-Process -id $pid | Select-Object Name,Id,Handles,WorkingSet |  
ConvertTo-Hashtable
```

| Name | Value |
|------------|----------------|
| ----- | ----- |
| WorkingSet | 418377728 |
| Name | powershell_ise |
| Id | 3456 |
| Handles | 958 |

Join-Hashtable

This command will combine two hash tables into a single hash table. `Join-Hashtable` will test for duplicate keys. If any of the keys from the first, or primary hashtable are found in the secondary hashtable, you will be prompted for which to keep. Or you can use `-Force` which will always keep the conflicting key from the first hashtable.

```
PS C:\> $a = @{Name="Jeff";Count=3;Color="Green"}  
PS C:\> $b = @{Computer="HAL";Enabled=$True;Year=2024;Color="Red"}  
PS C:\> Join-Hashtable $a $b  
Duplicate key Color  
A Green  
B Red  
Which key do you want to KEEP \[AB\]?: A
```

| Name | Value |
|----------|-------|
| ----- | ----- |
| Year | 2024 |
| Name | Jeff |
| Enabled | True |
| Color | Green |
| Computer | HAL |
| Count | 3 |

Rename-Hashtable

This command allows you to rename a key in an existing hashtable or ordered dictionary object.

```
PS C:\> $h = Get-Service Spooler | ConvertTo-Hashtable
```

The hashtable in \$h has a MachineName property which can be renamed.

```
PS C:\> Rename-Hashtable -Name h -Key MachineName -NewKey Computername  
-PassThru
```

| Name | Value |
|---------------------|-------------------------------------|
| ----- | ----- |
| ServiceType | Win32OwnProcess, InteractiveProcess |
| ServiceName | Spooler |
| Container | |
| CanPauseAndContinue | False |
| RequiredServices | {RPCSS, http} |
| ServicesDependedOn | {RPCSS, http} |
| Computername | . |
| CanStop | True |
| StartType | Automatic |
| Site | |
| ServiceHandle | SafeServiceHandle |
| DisplayName | Print Spooler |
| CanShutdown | False |
| Status | Running |
| Name | Spooler |
| DependentServices | {Fax} |

Select Functions

The module contains several functions that simplify the use of `Select-Object` or `Select-Object` in conjunction with `Where-Object`. The commands are intended to make it easier to select objects in a pipelined expression. The commands include features so that you can sort the incoming objects on a given property first.

Select-First

Normally, you might run a command with `Select-Object` like this:

```
Get-Process | Select-Object -first 5 -Property WS -Descending
```

| Handles | NPM(K) | PM(K) | WS(K) | CPU(s) | Id | SI | ProcessName |
|---------|--------|--------|--------|--------|-------|----|-----------------|
| 696 | 89 | 615944 | 426852 | 391.97 | 7352 | 0 | sqlservr |
| 541 | 78 | 262532 | 274576 | 278.41 | 6208 | 8 | Code |
| 1015 | 70 | 227824 | 269504 | 137.39 | 16484 | 8 | powershell_ise |
| 1578 | 111 | 204852 | 254640 | 98.58 | 21332 | 8 | firefox |
| 884 | 44 | 221872 | 245712 | 249.23 | 12456 | 8 | googledrivesync |

To streamline the process a bit, you can use `Select-First`.

```
Get-Process | Select-First 5 -Property WS -Descending
```

| Handles | NPM(K) | PM(K) | WS(K) | CPU(s) | Id | SI | ProcessName |
|---------|--------|--------|--------|--------|-------|----|-----------------|
| 696 | 89 | 615944 | 426852 | 391.97 | 7352 | 0 | sqlservr |
| 541 | 78 | 262532 | 274576 | 278.41 | 6208 | 8 | Code |
| 1015 | 70 | 227824 | 269504 | 137.39 | 16484 | 8 | powershell_ise |
| 1578 | 111 | 204852 | 254640 | 98.58 | 21332 | 8 | firefox |
| 884 | 44 | 221872 | 245712 | 249.23 | 12456 | 8 | googledrivesync |

Even better, use the command alias *first*.

```
Get-Process | Sort-Object ws -Descending | first 5
```

Select-Last

You can perform a similar operation using `Select-Last` or its alias *last*.

```
Get-ChildItem -Path c:\scripts\*.ps1 | Sort-Object LastWriteTime | last 10
```

Select-After

`Select-After` is a simplified version of `Select-Object`. The premise is that you can pipe a collection of objects to this command and select objects after a given `DateTime`, based on a property, like `LastWriteTime`, which is the default. This command has an alias of *after*.

```
Get-ChildItem -Path c:\scripts\ -file | after 11/1/2024
```

```
Directory: C:\Scripts
```

| Mode | LastWriteTime | Length | Name |
|-------|--------------------|--------|----------------------------|
| -a--- | 11/2/2024 11:08 AM | 3522 | Get-ServiceWPFRunspace.ps1 |
| -a--- | 11/1/2024 11:05 AM | 5321 | Trace.ps1 |
| -a--- | 11/2/2024 11:39 AM | 2321 | WinFormDemo2.ps1 |

Or you can specify property depending on the object.

```
Get-Process | after (Get-Date).AddMinutes(-1) -Property StartTime
```

| NPM(K) | PM(M) | WS(M) | CPU(s) | Id | SI | ProcessName |
|--------|-------|-------|--------|-------|----|-------------|
| 13 | 3.14 | 13.73 | 0.05 | 19156 | 2 | notepad |

This is selecting all processes that started within the last minute.

Select-Before

Select-Before is the opposite of Select-After.

```
Get-ChildItem -Path c:\scripts -file | before 1/1/2008
```

```
Directory: C:\Scripts
```

| Mode | LastWriteTime | Length | Name |
|-------|-------------------|--------|--------------------|
| -a--- | 12/5/2007 2:19 PM | 29618 | 1000MaleNames.txt |
| -a--- | 4/8/2006 10:27 AM | 3779 | 530215.ps1 |
| -a--- | 8/7/2005 1:00 AM | 4286 | ADUser.wsc |
| -a--- | 9/18/2006 9:27 PM | 1601 | allserviceinfo.ps1 |
| ... | | | |

As with Select-After, you can specify a property to use.

```
Get-AdUser -filter * -Properties WhenCreated |  
Before 11/1/2024 -Property WhenCreated | Select-Object Name,WhenCreated
```

| Name | WhenCreated |
|----------------|-----------------------|
| Administrator | 10/26/2024 6:47:39 PM |
| Guest | 10/26/2024 6:47:39 PM |
| DefaultAccount | 10/26/2024 6:47:39 PM |
| krbtgt | 10/26/2024 6:50:47 PM |
| MaryL | 10/26/2024 6:56:24 PM |
| ArtD | 10/26/2024 6:56:24 PM |
| Aprils | 10/26/2024 6:56:25 PM |

```
MikeS      10/26/2024 6:56:25 PM
...
```

Select-Newest

Select-Newest is designed to make it easier to select X number of objects based on a DateTime property. The default property value is LastWriteTime.

```
Get-ChildItem -Path d:\temp -file | newest 10

Directory: D:\temp

Mode                LastWriteTime         Length Name
----                -
-a---         11/4/2024  5:12 PM       5149954 watcherlog.txt
-a---         11/3/2024 10:00 PM         3215 DailyIncremental_202411031000.txt
-a---         11/2/2024 10:00 PM        11152 DailyIncremental_202411021000.txt
-a---         11/2/2024  3:40 PM         852 t.ps1
-a---         11/1/2024 10:00 PM         2376 DailyIncremental_202411011000.txt
-a---        10/31/2024 10:00 PM         3150 DailyIncremental_202410311000.txt
-a---        10/30/2024 10:07 PM        17844 WeeklyFull_202410301000.txt
-a---        10/30/2024  1:00 PM       208699 datatfile-5.png
-a---        10/30/2024 12:57 PM      1264567 datatfile-4.png
-a---        10/30/2024 12:27 PM       421341 datatfile-3.png
```

Or specify a property.

```
Get-ADUser -filter * -Properties WhenCreated |
  Select-Newest 5 -Property WhenCreated |
  Select-object DistinguishedName,WhenCreated

DistinguishedName                                WhenCreated
-----
CN=Marcia Brady,OU=Employees,DC=Company,DC=Pri  11/4/2024 3:15:27 PM
CN=Gladys Kravitz,OU=Employees,DC=Company,DC=Pri 11/4/2024 3:14:45 PM
CN=S.Talone,OU=Employees,DC=Company,DC=Pri      10/26/2024 3:56:31 PM
CN=A.Fieldhouse,OU=Employees,DC=Company,DC=Pri   10/26/2024 3:56:31 PM
CN=K.Moshos,OU=Employees,DC=Company,DC=Pri      10/26/2024 3:56:31 PM
```

Select-Oldest

Select-Oldest is the opposite of Select-Newest and works the same way.

```
Get-Process | newest 5 -Property StartTime

Handles  NPM(K)  PM(K)  WS(K)  CPU(s)  Id  SI ProcessName
-----
145      8      1692   7396   0.02   9676 0 SearchFilterHost
344     13     2604  13340   0.02  33668 0 SearchProtocolHost
114      7     1340   6116   0.02  35028 0 svchost
140      8     2684   8796   0.03  32552 0 svchost
```

```
118      8      1580      7476      0.02  35668      0 svchost
```

These custom Select commands are not necessarily designed for performance and there may be better ways to achieve the same results from these examples.

Time Functions

The module has a couple of date and time-related commands.

ConvertTo-UTCTime

Convert a local `DateTime` value to universal time. The default is to convert the current time, but you can specify a datetime value.

```
PS C:\> ConvertTo-UTCTime

Wednesday, March 26, 2025 5:09:31 PM
```

Convert a datetime that is UTC-5 to universal time.

ConvertFrom-UTCTime

```
PS C:\> ConvertFrom-UTCTime "3/4/2025 6:00PM"

Tuesday, March 4, 2025 1:00:00 PM
```

Convert a universal `DateTime` to the local time.

Get-MyTimeInfo

Display a group of time settings for a collection of locations. This command is a PowerShell equivalent of a world clock. It will display a `DateTime` value against a collection of locations. You can specify an ordered hashtable of locations and time zones. You can run a command like:

```
[System.TimeZoneInfo]::GetSystemTimeZones() | Out-GridView
```

or

```
Get-TimeZone -ListAvailable
```

To discover time zone names. Note that the ID is case-sensitive. You can then use the command like this:

```
PS C:\> Get-MyTimeInfo -Locations ([ordered]@{Seattle="Pacific Standard time";
"New Zealand" = "New Zealand Standard Time"}) -HomeTimeZone
"central standard time" | Select Now,Home,Seattle,'New Zealand'

Now                Home                Seattle             New Zealand
---                -
3/26/2025 1:10:55 PM 3/26/2025 12:10:55 PM 3/26/2025 10:10:55 AM 3/27/2025 6:10:55 AM
```

This is a handy command when traveling and your laptop is using a locally derived time and you want to see the time in other locations. It is recommended that you set a `PSDefaultParameter` value for the `HomeTimeZone` parameter in your PowerShell profile.

ConvertTo-LocalTime

It can be tricky sometimes to see a time in a foreign location and try to figure out the local time. This command attempts to simplify this process. In addition to the remote time, you need the base UTC offset for the remote location.

```
PS C:\> Get-TimeZone -ListAvailable | Where-Object id -match Hawaii

Id                : Hawaiian Standard Time
HasIanaId          : False
DisplayName        : (UTC-10:00) Hawaii
StandardName       : Hawaiian Standard Time
DaylightName       : Hawaiian Daylight Time
BaseUtcOffset      : -10:00:00
SupportsDaylightSavingTime : False

PS C:\> ConvertTo-LocalTime "10:00AM" -10:00:00

Wednesday, March 26, 2025 4:00:00 PM
```

In this example, the user is first determining the UTC offset for Hawaii. Then 10:00 AM, in say Honolulu, is converted to local time, which in this example is in the Eastern Time zone.

Get-TZList

This command uses a free and publicly available REST API offered by <http://worldtimeapi.org> to get a list of time zone areas. You can get a list of all areas or by geographic location. Use `Get-TZData` to then retrieve details.

```
PS C:\> Get-TZList Australia
Australia/Adelaide
Australia/Brisbane
Australia/Broken_Hill
Australia/Currie
Australia/Darwin
Australia/Eucla
Australia/Hobart
Australia/Lindeman
Australia/Lord_Howe
Australia/Melbourne
Australia/Perth
Australia/Sydney
```

Get-TZData

This command also uses the API from WorldTimeAPI.org to retrieve details about a given time zone area.

```
PS C:\> Get-TZData Australia/Hobart
```

| Timezone | Label | Offset | DST | Time |
|------------------|-------|----------|------|----------------------|
| ----- | ----- | ----- | --- | ---- |
| Australia/Hobart | AEDT | 11:00:00 | True | 3/27/2025 4:12:04 AM |

The Time value is the current time at the remote location. The command presents a formatted object but you can also get the raw data.

```
PS C:\> Get-TZData Australia/Hobart -Raw
```

```
week_number   : 13
utc_offset    : +11:00
unixtime      : 1743009143
timezone      : Australia/Hobart
dst_until     : 2025-04-05T16:00:00+00:00
dst_from      : 2024-10-05T16:00:00+00:00
dst           : True
day_of_year   : 86
day_of_week   : 4
datetime      : 2025-03-27T04:12:23.000000+11:00
abbreviation  : AEDT
```

ConvertTo-LexicalTime

When working with `TimeSpan` objects or durations in XML files, such as those from scheduled tasks, the format is a little different than what you might expect. The specification is described at <https://www.w3.org/TR/xmlschema-2/#duration>. Use this command to convert a timespan into a lexical format you can use in an XML file where you need to specify a duration.

```
PS C:\> ConvertTo-LexicalTimespan (New-TimeSpan -Days 7 -hours 12)
P7DT12H
```

ConvertFrom-LexicalTime

Likewise, you might need to convert a lexical value back into a timespan.

```
PS C:\> ConvertFrom-LexicalTimeSpan P7DT12H
```

```
Days           : 7
Hours           : 12
Minutes         : 0
Seconds         : 0
Milliseconds    : 0
Ticks           : 6480000000000
TotalDays       : 7.5
TotalHours      : 180
TotalMinutes    : 10800
TotalSeconds    : 648000
TotalMilliseconds : 648000000
```

These functions were first described at <https://jdhitsolutions.com/blog/powershell/7101/convert-ing-lexical-timespans-with-powershell/>

Console Utilities

Get-PSSessionInfo

Get-PSSessionInfo will display a summary of your current PowerShell session. It should work on all platforms.

```
PS C:\> Get-PSSessionInfo

ProcessID : 1112
Command   : "C:\Program Files\PowerShell\7\pwsh.exe" -noprofile
Host      : ConsoleHost
Started   : 4/9/2021 9:36:13 AM
PSVersion : 7.1.3
Elevated  : True
Parent    : System.Diagnostics.Process (WindowsTerminal)
Runtime   : 01:35:43
MemoryMB  : 149

PS C:\> _
```

```
PS /home> Get-PSSessionInfo

ProcessID : 71
Command   : pwsh
Host      : ConsoleHost
Started   : 04/09/2021 09:38:55
PSVersion : 7.1.3
Elevated  : False
Parent    : System.Diagnostics.Process (bash)
Runtime   : 01:34:11
MemoryMB  : 158
```

If you are running in a PowerShell console session, and the Elevated value is True, it will be displayed in color. The Memory and Runtime values are calculated `ScriptProperties`.

Out-Copy

This command is intended for writers and those who need to document with PowerShell. You can pipe any command to this function, and you will get the regular output in your PowerShell session. Simultaneously, a copy of the output will be sent to the Windows clipboard. The copied output will include a prompt constructed from the current location unless you use the `CommandOnly` parameter.

You can run a command like:

```
Get-Process | Sort WS -Descending | Select-Object -first 5 | Out-Copy
```

This text will be copied to the clipboard.

```
PS C:\> Get-Process | Sort WS -Descending | Select -first 5
```

| Handles | NPM(K) | PM(K) | WS(K) | CPU(s) | Id | SI | ProcessName |
|---------|--------|--------|--------|--------|-------|----|-------------|
| 1849 | 253 | 810320 | 820112 | 445.38 | 17860 | 1 | firefox |
| 765 | 61 | 949028 | 758200 | 23.36 | 6052 | 0 | sqlservr |
| 446 | 115 | 441860 | 471032 | 28.59 | 18204 | 1 | Teams |
| 2307 | 192 | 313204 | 459616 | 325.23 | 15748 | 1 | firefox |
| 2050 | 163 | 451744 | 433772 | 94.63 | 19780 | 1 | thunderbird |

Out-More

This command provides a PowerShell alternative to the cmd.exe **MORE** command, which doesn't work in the PowerShell ISE. When you have screens of information, you can page it with this function.

```
Get-Service | Out-More
```

```
Running CertPropSvc Certificate Propagation
Running ClickToRunSvc Microsoft Office Click-to-Run Service
Stopped ClipSvc Client License Service (ClipSvc)
Stopped COMSysApp COM+ System Application
Running CoreMessagingRe... CoreMessaging
Running cphs Intel(R) Content Protection HECI Se...
Running cplspcon Intel(R) Content Protection HDCP Se...
Running CryptSvc Cryptographic Services
Stopped CscService Offline Files
Stopped dbupdate Dropbox Update Service (dbupdate)
Stopped dbupdatem Dropbox Update Service (dbupdatem)
Running DbxSvc DbxSvc
Running DcomLaunch DCOM Server Process Launcher
Stopped debugregsvc debugregsvc
Stopped defragsvc Optimize drives
Stopped DeveloperToolsS... Developer Tools Service
Running DeviceAssociati... Device Association Service
Stopped DeviceInstall Device Install Service
Stopped DevicesFlowUser... DevicesFlowUserSvc_44fb1
Stopped DevQueryBroker DevQuery Background Discovery Broker
Running Dhcp DHCP Client
Stopped diagnosticshub... Microsoft (R) Diagnostics Hub Stand...
Stopped diagsvc Diagnostic Execution Service
Running DiagTrack Connected User Experiences and Tele...
Stopped DmEnrollmentSvc Device Management Enrollment Service
Stopped dmwappushservice dmwappushsvc
Running Dnscache DNS Client
[M]ore [A]ll [N]ext [Q]uit
```

This also works in PowerShell 7.

Set-ConsoleTitle

Set the title bar of the current PowerShell console window.

```
if (Test-IsAdministrator) {  
    Set-ConsoleTitle "Administrator: $($PSVersionTable.PSVersion)"  
}
```

Add-Border

This command will create a character or text-based border around a line of text. You might use this to create a formatted text report or to improve the display of information on the screen.

```
PS C:\> Add-Border $env:computername  
  
*****  
* WIN11 *  
*****
```

Starting in v2.23.0 you can also use ANSI escape sequences to color the text and/or the border.

```
PS C:\> add-border -Text "Today is a good day for PowerShell" -ANSIBorder "`e[38;5;47m" -ANSIText "`e[93m"  
  
*****  
* Today is a good day for PowerShell *  
*****  
PS C:\>
```

```
$params =@{  
    TextBlock = (Get-PSWho -AsString ).trim()  
    ANSIBorder = "`e[38;5;214m"  
    Character = ([char]0x25CA)  
    ANSIText = "`e[38;5;225m"  
}  
Add-Border @params
```

This example assumes you are running PowerShell 7.

[illegible]

Show-Tree

`Show-Tree` will display the specified path as a graphical tree in the console. This is intended as a PowerShell alternative to the DOS `tree` command. This function should work for any type of PowerShell provider and can be used to explore providers used for configuration like the WSMAN provider or the registry. By default, the output will only show directory items or equivalent structures. But you can opt to include items as well as item details.

```

Administrator: C:\Program Files\PowerShell\powershell.exe
PS C:\> show tree c:\work
C:\work
---A
|   \--B
|       \--C
---dmsuffix
++-docs
++-en-us
\--images
gpo
|   {6595E040-A0D4-4508-A100-B6EAF4E0E595}
|   \--DomainSysvol
|       \--GPO
|           +-Machine
|               +-Applications
|               +-microsoft
|                   \--windows nt
|                       \--SecEdit
|               Preferences
|               +-Folders
|               \--NetworkShares
|       \--Scripts
|           +-Shutdown
|           \--Startup
|   \--User
\--{7E7F01CE-5889-4498-9083-B18F0284EDE9}
    \--DomainSysvol
        \--GPO
            +-Machine
            +-Applications

```

If you are running Windows PowerShell 5.1 and specifying a file system path, you can display the tree in a colored format by using the `-InColor` dynamic parameter.


```

PS C:\> pstree c:\work\alpha -ShowItem -InColor
C:\work\alpha
+--bravo
| +--delta
| | +--FunctionDemo.ps1
| | +--function-form.ps1
| | +--function-logstamp.ps1
| | +--FunctionNotes.ps1
| | \--Function-SwitchTest.ps1
| +--gamma
| | \--x.txt
| +--images
| | +--wpfbox-1.png
| | +--wpfbox-2.png
| | +--wpfgrid.png
| | \--wpfgrid2.png
| +--data.txt
| +--sample-1.json
| +--sample-2.json
| +--sample-3.json
| +--sample-4.json
| | \--something2.xml
+--documents-log.csv
+--dropbox-log.csv
+--GoogleDrive-log.csv
+--junk.txt
+--Scripts-log.csv
+--stuff.tmp
\--test.data
PS C:\>

```

Beginning with module version 2.21.0, this command uses ANSI Color schemes from a JSON file. You can customize the file if you wish. See the [PSAnsiMap](#) section of this README. If you are using `$PSStyle.FileInfo`, colorization will use these values.`$(ps)`

This command has an alias of `pstree`.

```

PS C:\> pstree c:\work\alpha -files -properties LastWriteTime,Length

C:\work\Alpha\
+-- LastWriteTime = 02/28/2024 11:19:32
+--bravo
| +-- LastWriteTime = 02/28/2024 11:20:30
| +--delta
| | +-- LastWriteTime = 02/28/2024 11:17:35
| | +--FunctionDemo.ps1
| | | +-- Length = 888
| | | \-- LastWriteTime = 06/01/2009 15:50:47
| | +--function-form.ps1
| | | +-- Length = 1117
| | | \-- LastWriteTime = 04/17/2024 17:18:28
| | +--function-logstamp.ps1
| | | +-- Length = 598
| | | \-- LastWriteTime = 05/23/2007 11:39:55
| | +--FunctionNotes.ps1

```

```


| | | +-- Length = 617
| | | \-- LastWriteTime = 02/24/2016 08:59:03
| | \--Function-SwitchTest.ps1
| | +-- Length = 242
| | \-- LastWriteTime = 06/09/2008 15:55:44
| +--gamma
...

```

This example uses parameter and command aliases. You can display a tree listing with files including user-specified properties. Use a value of * to show all properties.

New-RedGreenGradient

New-RedGreenGradient, which displays a bar going from red to green. This might be handy when you want to present a visual indicator.



```

Admin: PowerShell 7.0
PS C:\>
PS C:\> New-RedGreenGradient -Percent .75
PS C:\>
PS C:\> Get-Volume | Where-Object {$_.FileSystemType -eq 'NTFS' -AND $_.driveletter -match "[C-Zc-z]"} |
>> Sort-Object -property DriveLetter |
>> Select-Object -property DriveLetter, FileSystemLabel,
>> @(Name="FreeGB";Expression={Format-Value -input $_.SizeRemaining -unit GB}),
>> @(Name = "PctFree"; Expression = {$pct = Format-Percent -value $_.sizereamaining -total $_.size -decimal 2;
>> "{1} {0}" -f $(New-RedGreenGradient -percent ($pct/100) -step 6),$pct})

DriveLetter FileSystemLabel FreeGB PctFree
-----
C Windows 87 36.86
D Data 102 21.37

```

Format Functions

The module contains a set of simple commands to make it easier to format values.

Format-Percent

Treat a value as a percentage. This will write a [double] and not include the % sign.

```
PS C:\> Format-Percent -Value 123.5646MB -total 1GB -Decimal 4
12.0669
```

Format-String

Use this command to perform one of several string manipulation "tricks".

```
PS C:\> Format-String "powershell" -Reverse -Case Proper
Llehsrewop
PS C:\> Format-String PowerShell -Randomize
wSlhoeepLr
PS C:\> Format-String "!MySecretPWord" -Randomize
-Replace @{S="$";e=&{Get-Random -min 1 -max 9};o="^"} -Reverse
yr7!^7WcMtr$Pd
```

Format-Value

This command will format a given numeric value. By default, it will treat the number as an integer. Or you can specify a certain number of decimal places. The command will also allow you to format the value in KB, MB, etc.

```
PS C:\> Format-Value 1235465676 -Unit kb
1206509
PS C:\> Format-Value 123.45 -AsCurrency
$123.45
PS C:\> (Get-Process | Measure-Object ws -sum).sum |
Format-Value -Unit mb | Format-Value -AsNumber
9,437
```

Or pull it all together:

```
Get-CimInstance Win32_OperatingSystem |
Select-Object @{Name = "TotalMemGB";
Expression={Format-Value $_.TotalVisibleMemorySize -Unit mb}},
@{Name="FreeMemGB";
Expression={Format-Value $_.FreePhysicalMemory -unit mb -Decimal 2}},
@{Name="PctFree";
Expression={Format-Percent -Value $_.FreePhysicalMemory `
-Total $_.totalVisibleMemorySize -Decimal 2}}
```

| TotalMemGB | FreeMemGB | PctFree |
|------------|-----------|---------|
| ----- | ----- | ----- |
| 32 | 14.05 | 44.06 |

Scripting Tools

Get-TypeMember

This command is an alternative to using `Get-Member`. Specify a type name to see a simple view of an object's members. The output will only show native members, including static methods, but not those added by PowerShell such as `ScriptProperties`.

```
PS C:\> Get-TypeMember system.io.path -MemberType Method
```

Type: System.IO.Path

| Name | MemberType | ResultType | IsStatic |
|-----------------------------|------------|------------|----------|
| ChangeExtension | Method | String | True |
| Combine | Method | String | True |
| Equals | Method | Boolean | False |
| GetDirectoryName | Method | String | True |
| GetExtension | Method | String | True |
| GetFileName | Method | String | True |
| GetFileNameWithoutExtension | Method | String | True |
| GetFullPath | Method | String | True |
| GetHashCode | Method | Int32 | False |
| GetInvalidFileNameChars | Method | Char[] | True |
| GetInvalidPathChars | Method | Char[] | True |
| GetPathRoot | Method | String | True |
| GetRandomFileName | Method | String | True |
| GetTempFileName | Method | String | True |
| GetTempPath | Method | String | True |
| GetType | Method | Type | False |
| HasExtension | Method | Boolean | True |
| IsPathRooted | Method | Boolean | True |
| ToString | Method | String | False |

The command will highlight properties that are enumerations.

```
PS C:\> Get-TypeMember system.serviceprocess.servicecontroller -MemberType Property
```

Type: System.ServiceProcess.ServiceController

| Name | MemberType | ResultType | IsStatic | IsEnum |
|---------------------|------------|-------------------------|----------|--------|
| CanPauseAndContinue | Property | Boolean | | |
| CanShutdown | Property | Boolean | | |
| CanStop | Property | Boolean | | |
| Container | Property | IContainer | | |
| DependentServices | Property | ServiceController[] | | |
| DisplayName | Property | String | | |
| MachineName | Property | String | | |
| ServiceHandle | Property | SafeHandle | | |
| ServiceName | Property | String | | |
| ServicesDependedOn | Property | ServiceController[] | | |
| ServiceType | Property | ServiceType | | True |
| Site | Property | ISite | | |
| StartType | Property | ServiceStartMode | | True |
| Status | Property | ServiceControllerStatus | | True |

The highlighting only works in the console and VSCode.

The output includes a property set type extension.

```
PS C:\> Get-TypeMember datetime -MemberType method | Select MethodSyntax
```

| Name | ReturnType | IsStatic | Syntax |
|-----------------|-----------------|----------|--------------------------------------|
| ---- | ----- | ----- | ----- |
| Add | System.DateTime | False | \$obj.Add([TimeSpan]value) |
| AddDays | System.DateTime | False | \$obj.AddDays([Double]value) |
| AddHours | System.DateTime | False | \$obj.AddHours([Double]value) |
| AddMilliseconds | System.DateTime | False | \$obj.AddMilliseconds([Double]value) |
| AddMinutes | System.DateTime | False | \$obj.AddMinutes([Double]value) |
| ... | | | |

Or you can use the custom view.

```
PS C:\> Get-TypeMember datetime -MemberType method | Format-Table -View Syntax
```

Type: System.DateTime

| Name | ReturnType | Syntax |
|-----------------|------------|--------------------------------------|
| ---- | ----- | ----- |
| Add | DateTime | \$obj.Add([TimeSpan]value) |
| AddDays | DateTime | \$obj.AddDays([Double]value) |
| AddHours | DateTime | \$obj.AddHours([Double]value) |
| AddMilliseconds | DateTime | \$obj.AddMilliseconds([Double]value) |
| AddMinutes | DateTime | \$obj.AddMinutes([Double]value) |
| AddMonths | DateTime | \$obj.AddMonths([Int32]months) |
| AddSeconds | DateTime | \$obj.AddSeconds([Double]value) |
| AddTicks | DateTime | \$obj.AddTicks([Int64]value) |
| AddYears | DateTime | \$obj.AddYears([Int32]value) |

...

Get-TypeConstructor

You might also want to easily discover constructors for .NET classes. It isn't that difficult to view `OverLoadDefinitions` for the `New()` method.

```
PS C:\> [System.Drawing.rectangle]::new.OverloadDefinitions
System.Drawing.Rectangle new(int x, int y, int width, int height)
System.Drawing.Rectangle new(System.Drawing.Point location, System.Drawing.Size size)
```

The `Get-TypeConstructor` command will display the same information, but in an easier to read and use format.

```
PS C:\> Get-TypeConstructor System.Drawing.Rectangle

[System.Drawing.Rectangle]::new([System.Int32]$X),
                                [System.Int32]$Y),
                                [System.Int32]$Width),
                                [System.Int32]$Height))

[System.Drawing.Rectangle]::new([System.Drawing.Point]$Location), [System.Drawing.Size]$Size))
```

The default formatted view highlights the type and variable names using the color values from `Get-PSReadLineOption`. The output is designed so that you could copy and paste a constructor method into your script.

The command output is a rich object in the event you want to do something else with the result.

```
PS C:\> $c = Get-TypeConstructor System.Drawing.Rectangle | Select -first 1
PS C:\> $c.type
System.Drawing.Rectangle
PS C:\> $c.Parameters

ParameterType ParameterName
-----
System.Int32  x
System.Int32  y
System.Int32  width
System.Int32  height
```

New-PSDynamicParameter

This command will create the code for a dynamic parameter that you can insert into your PowerShell script file. You need to specify a parameter name and a condition. The condition value is code that would run inside an `If` statement. Use a value like `$True` if you want to add it later in your scripting editor.

```
PS C:\> New-PSDynamicParameter -Condition "$PSEdition -eq 'Core'" -ParameterName ANSI -Alias color -Comment "Create a parameter to use ANSI if running
PowerShell 7" -ParameterType switch

DynamicParam {
```

```
# Create a parameter to use ANSI if running PowerShell 7
If (Core -eq 'Core') {

    $paramDictionary = New-Object -Type System.Management.Automation.RuntimeDefinedParameterDictionary

    # Defining parameter attributes
    $attributeCollection = New-Object -Type System.Collections.ObjectModel.Collection[System.Attribute]
    $attributes = New-Object System.Management.Automation.ParameterAttribute
    $attributes.ParameterSetName = '__AllParameterSets'
    $attributeCollection.Add($attributes)

    # Adding a parameter alias
    $dynalias = New-Object System.Management.Automation.AliasAttribute -ArgumentList 'color'
    $attributeCollection.Add($dynalias)

    # Defining the runtime parameter
    $dynParam1 = New-Object -Type System.Management.Automation.RuntimeDefinedParameter('ANSI', [Switch], $attributeCollection)
    $paramDictionary.Add('ANSI', $dynParam1)

    return $paramDictionary
} # end if
} #end DynamicParam
```

This creates dynamic parameter code that you can use in a PowerShell function. Normally you would save this output to a file or copy it to the clipboard so that you can paste it into your scripting editor.

You can also use a WPF-based front-end command, [New-PSDynamicParameterForm](#). You can enter the values in the form. Required values are indicated by an asterisk.

New Dynamic Parameter

Parameter Name* ☐ Mandatory

Parameter Alias Parameter Set Name

Default Value Help Message

Parameter Type

Condition*

Parameter Validations

☒ ValidateNotNullorEmpty ☒ ValueFromPipelineByPropertyName

ValidateCount ValidateLength ValidateRange

ValidatePattern

ValidateScript

ValidateSet

Comment

Clicking **Create** will generate the dynamic parameter code and copy it to the Windows clipboard. You can then paste it into your scripting editor.

```
DynamicParam {
    If ($Filter -eq 'domain') {
```



```

$paramDictionary = New-Object -Type System.Management.Automation.RuntimeDefinedParameterDictionary

# Defining parameter attributes
$attributeCollection = New-Object -Type System.Collections.ObjectModel.Collection[System.Attribute]
$attributes = New-Object System.Management.Automation.ParameterAttribute
$attributes.ParameterSetName = '__AllParameterSets'
$attributes.ValueFromPipelineByPropertyName = $True

# Adding ValidatePattern parameter validation
$value = '^\\w+-\\w+$'
$v = New-Object System.Management.Automation.ValidatePatternAttribute($value)
$attributeCollection.Add($v)

# Adding ValidateNotNullOrEmpty parameter validation
$v = New-Object System.Management.Automation.ValidateNotNullOrEmptyAttribute
$attributeCollection.Add($v)
$attributeCollection.Add($attributes)


# Adding a parameter alias
$dynAlias = New-Object System.Management.Automation.AliasAttribute -ArgumentList 'cn'
$attributeCollection.Add($dynAlias)

# Defining the runtime parameter
$dynParam1 = New-Object -Type System.Management.Automation.RuntimeDefinedParameter('Computername', [String], $attributeCollection)
$paramDictionary.Add('Computername', $dynParam1)


return $paramDictionary
} # end if
} #end DynamicParam

```

If you import the PSScriptTools module in the PowerShell ISE, you will get a menu shortcut under Add-Ins.



If you import the module in VS Code using the integrated PowerShell terminal, it will add a new command. In the command palette, use "PowerShell: Show Additional Commands from PowerShell Modules".



Get-PSUnique

For the most part, objects you work with in PowerShell are guaranteed to be unique. But you might import data where there is the possibility of duplicate items. Consider this CSV sample.

```

$Obj = "Animal,Snack,Color
Horse,Quiche,Chartreuse
Cat,Doritos,Red
Cat,Pringles,Yellow

```

```
Dog,Doritos,Yellow
Dog,Doritos,Yellow
Rabbit,Pretzels,Green
Rabbit,Popcorn,Green
Marmoset,Cheeseburgers,Black
Dog,Doritos,White
Dog,Doritos,White
Dog,Doritos,White
" | ConvertFrom-Csv
```

There are duplicate objects you might want to filter out. For that task, you can use `Get-PSUnique`.

```
PS C:\> $obj | Get-PSUnique | Sort-Object animal
```

| Animal | Snack | Color |
|----------|---------------|------------|
| ----- | ----- | ----- |
| Cat | Pringles | Yellow |
| Cat | Doritos | Red |
| Dog | Doritos | White |
| Dog | Doritos | Yellow |
| Horse | Quiche | Chartreuse |
| Marmoset | Cheeseburgers | Black |
| Rabbit | Popcorn | Green |
| Rabbit | Pretzels | Green |

The duplicate items have been removed. This command works best with simple objects. If your objects have nested object properties, you will need to test if this command can properly filter for unique items. For more complex objects, you should use the `Property` parameter.

Test-IsElevated

This simple command will test if the current PowerShell session is running elevated, or as Administrator. On Windows platforms, the function uses the .NET Framework to test. On non-Windows platforms, the command tests the user's UID value.

```
PS C:\> Test-IsElevated
False
```

You can also use the `Get-PSWho` command to get more information.

New-FunctionItem

```
{Get-Date -format g | Set-Clipboard} | New-FunctionItem -name Copy-Date
```

The script block has been converted into a function.

```
PS C:\> Get-Command Copy-Date
```

| CommandType | Name | Version | Source |
|-------------|------|---------|--------|
| ----- | ---- | ----- | ----- |

| Function | Copy-Date |
|----------|-----------|
|----------|-----------|

You can use this function to create a quick function definition directly from the console. This lets you quickly prototype a function. If you are happy with it, you can "export" to a file with `Show-FunctionItem`.

Show-FunctionItem

This command will display a loaded function as it might look in a code editor. You could use this command to export a loaded function to a file.

```
Show-FunctionItem Copy-Date | Out-File c:\scripts\Copy-Date.ps1
```

ConvertTo-TitleCase

This is a simple command that uses `[System.Globalization.CultureInfo]` to convert a string to Title casing.

```
PS C:\> ConvertTo-TitleCase "disk usage report"
Disk Usage Report
```

Trace-Message

`Trace-Message` is designed to be used with your script or function on a Windows platform. Its purpose is to create a graphical trace window using Windows Presentation Foundation (WPF). Inside the function or script, you can use this command to send messages to the window. When finished, you have the option to save the output to a text file.

There are three steps to using this function. First, in your code, you need to create a boolean global variable called `TraceEnabled`. When the value is `$True`, the `Trace-Message` command will run. When set to false, the command will be ignored. Second, you need to initialize a form, specifying the title and dimensions. Finally, you can send trace messages to the window. All messages are prepended with a timestamp.

Here is a code excerpt from `$PSSamplePath\Get-Status.ps1`:

```
Function Get-Status {
    [cmdletbinding(DefaultParameterSetName = 'name')]
    [alias("gst")]
    Param(
        #parameter details...
        [Parameter(HelpMessage="Enable with graphical trace window")]
        [switch]$Trace
    )

    Begin {
        Write-Verbose "[$((Get-Date).TimeOfDay) BEGIN ] Starting $($MyInvocation.MyCommand)"
        if ($Trace) {
            $global:TraceEnabled = $True
            $TraceTitle = "{0} Trace Log" -f $($MyInvocation.MyCommand)
            Trace-Message -title $TraceTitle
        }
    }
}
```

```

    Trace "Starting $($MyInvocation.MyCommand)"
  }
} #begin
Process {
  Write-Verbose "[$(Get-Date).TimeOfDay] PROCESS] Using parameter set $($PSCmdlet.ParameterSetName)"
  Trace-Message -message "Using parameter set: $($PSCmdlet.ParameterSetName)"
  #code ...
} #close function
$data = Get-Status -trace
#code ...
}

```

The trace window starts with pre-defined metadata.

```

16:50:34.2557095 - User: PROSPERO\Jeff
16:50:34.5198190 - Elevated : True
16:50:34.7023501 - Computer: PROSPERO
16:50:35.0406358 - OS: Microsoft Windows 10 Pro
16:50:35.3115122 - Ver.: 10.0.19042
16:50:35.5770522 - Architecture: 64-bit
16:50:35.8427966 - *****
16:50:36.0942951 - Starting Get-Status
16:50:36.3406886 - Using parameter set: name
16:50:36.6105952 - Create a temporary permission
16:50:36.9161293 - Querying Win32_OperatingSystem
16:50:37.2267858 - Querying Win32_LogicalDisk
16:50:37.4099070 - Creating new object
16:50:37.7541594 -
Name                                Value
----                                -
Computersname                       PROSPERO
Uptime                              09:49:33.2247843
PctFreeMem                          63.95
PctFreeC                             50.96
PctFreeD                             78.16

16:50:38.0186744 - Removing temporary permission
16:50:38.2047403 - Ending Get-Status

```

Buttons: Quit, Save

Your output might vary from this screenshot. You have the option to Save the text. The default location is `$env:temp`.


Get-CommandSyntax

Some PowerShell commands are provider-aware and may have special syntax or parameters depending on what PSDrive you are using when you run the command. In Windows PowerShell, the help system could show you syntax based on a given path. However, this no longer appears to work. `Get-CommandSyntax` is intended as an alternative and should work in both Windows PowerShell and PowerShell 7.

Specify a cmdlet or function name, and the output will display the syntax detected when using different providers.

```
Get-CommandSyntax -Name Get-Item
```

Dynamic parameters will be highlighted with an ANSI-escape sequence.



This command has an alias of *gsyn*.

Test-Expression

The primary command can be used to test a PowerShell expression or script block for a specified number of times and calculate the average runtime, in milliseconds, over all the tests.

When you run a single test with `Measure-Command` the result might be affected by any number of factors. Likewise, running multiple tests may also be influenced by things such as caching. The goal of this module is to provide a test framework where you can run a test repeatedly with either a static or random interval between each test. The results are aggregated and analyzed. Hopefully, this will provide a more meaningful or realistic result.

The output will also show the median and trimmed values, as well as some metadata about the current PowerShell session.

```
PS C:\> $cred = Get-Credential Globomantics\administrator
PS C:\> Test-Expression {
    param($cred)
    Get-CimInstance win32_LogicalDisk -computer chi-dc01 -credential $cred
} -argumentList $cred

Tests          : 1
TestInterval   : 0.5
AverageMS      : 1990.6779
MinimumMS      : 1990.6779
MaximumMS      : 1990.6779
MedianMS       : 1990.6779
TrimmedMS      :
PSVersion      : 5.1.17763.134
OS             : Microsoft Windows 10 Pro
```

You can also run multiple tests with random time intervals.

```
PS C:\>Test-Expression {
  param([string[]]$Names)
  Get-Service $names
} -count 5 -IncludeExpression -ArgumentList @('bits','wuauerv','winrm') `
-RandomMinimum .5 -RandomMaximum 5.5

Tests          : 5
TestInterval   : Random
AverageMS      : 1.91406
MinimumMS      : 0.4657
MaximumMS      : 7.5746
MedianMS       : 0.4806
TrimmedMS      : 0.51
PSVersion      : 5.1.17763.134
OS             : Microsoft Windows 10 Pro
Expression     : param([string[]]$Names) Get-Service $names
Arguments      : {bits, wuauerv, winrm}
```

For very long-running tests, you can run them as a background job.

Graphical Testing

The module also includes a graphical command called `Test-ExpressionForm`. This is intended to serve as both an entry and results form.

The screenshot shows a Windows application window titled "Test Expression". The window is divided into several sections:

- Enter code for your scriptblock:** A text area containing the PowerShell code:

```
param([string]$Computer)
get-ciminstance win32_process -
computer $Computer
```
- Arguments:** A text box containing the value "chi-hvr2".
- Results:** A list of test results:


```
Tests          : 10
TestInterval    : 6300
AverageMS       : 80.4023
MinimumMS       : 75.895
MaximumMS       : 106.2808
MedianMS        : 77.92295
TrimmedMS       : 77.7309
PSVersion       : 5.1.14409.1005
```
- Test Count:** A numeric input field set to "10".
- Test Interval:** A section with two radio buttons: "Static" (selected) and "Random". Below the "Random" option are input fields for "Minimum" (set to "1") and "Maximum" (set to "5").
- Buttons:** Two buttons at the bottom right labeled "Run" and "Quit".

When you quit the form the last result will be written to the pipeline including all metadata, the scriptblock, and any arguments.

Copy-HelpExample

This command is designed to make it (slightly) easier to copy code snippets from help examples. Specify the name of a function or cmdlet, presumably one with documented help examples, and you will be offered a selection of code snippets to copy to the clipboard. Code snippets have been trimmed of blank lines, most prompts, and comments. Many examples include command output. You will have to manually remove what you don't want after pasting.

The default behavior is to use a console-based menu, which works cross-platform.



```
PS C:\> Copy-HelpExample Stop-Service

Code Samples

Each help example is numbered to the left. At the prompt below,
select the code samples you want to copy to the clipboard. Separate
multiple values with a comma.

Some example code includes the output.

[1] Example 1: Stop a service on the local computer
    Stop-Service -Name "sysmonlog"

[2] Example 2: Stop a service by using the display name
    Get-Service -DisplayName "telnet" | Stop-Service


[3] Example 3: Stop a service that has dependent services
    Get-Service -Name "iisadmin" | Format-List -Property Name, DependentServices
    Stop-Service -Name "iisadmin" -Force -Confirm

Please select items to copy to the clipboard by number. Separate multiple entries with a comma. Press Enter alone to cancel:
```

Enter the number of the code to copy to the clipboard. Enter multiple numbers separated by commas.

If you are running a Windows platform, there is a dynamic help parameter to use `Out-GridView`.

```
Copy-HelpExample Stop-Service -UseGridView
```

If you are running this in the PowerShell ISE this is the default behavior, even if you don't specify the parameter.

Get-GitSize

Use this command to determine how much space the hidden `.git` folder is consuming.

```
PS C:\scripts\PSScriptTools> Get-GitSize
```

| Path | Files | SizeKB |
|--------------------------|-------|-----------|
| ---- | ----- | ----- |
| C:\scripts\PSScriptTools | 751 | 6859.9834 |

This is the default formatted view. The object has other properties you can use.

```
Name       : PSScriptTools
Path       : C:\scripts\PSScriptTools
Files      : 751
Size       : 7024623
Date       : 3/5/2024 2:57:06 PM
Computername : BOVINE320
```

Remove-MergedBranch

When using `git` you may create some branches. Presumably, you merge these branches into the main or master branch. You can use this command to remove all merged branches other than `master` or `main`, and the current branch. You must be at the root of your project to run this command.

```
PS C:\MyProject> Remove-MergedBranch
```

```
Remove merged branch from MyProject?
```



```
2.1.1
[Y] Yes [N] No [S] Suspend [?] Help (default is "Y"): n

Remove merged branch from MyProject?
dev1
[Y] Yes [N] No [S] Suspend [?] Help (default is "Y"): y
Deleted branch dev1 (was 75f6ab8).

Remove merged branch from MyProject?
dev2
[Y] Yes [N] No [S] Suspend [?] Help (default is "Y"): y
Deleted branch dev2 (was 75f6ab8).

Remove merged branch from MyProject?
patch-254
[Y] Yes [N] No [S] Suspend [?] Help (default is "Y"): n

PS C:\MyProject>
```

By default, you will be prompted to remove each branch.

Test-WithCulture

When writing PowerShell commands, sometimes the culture you are running under becomes critical. For example, European countries use a different `DateTime` format than North Americans, which might present a problem with your script or command. Unless you have a separate computer running under a foreign culture, it is difficult to test. This command will allow you to test a script block or even a file under a different culture, such as DE-DE for German.

```
PS C:\> Test-WithCulture fr-fr -Scriptblock {
    Get-winEvent -log system -max 500 |
    Select-Object -Property TimeCreated,ID,OpCodeDisplayName,Message |
    Sort-Object -property TimeCreated |
    Group-Object {$_.TimeCreated.ToShortDateString()} -NoElement}


Count Name
-----
165 10/07/2024
249 11/07/2024
17 12/07/2024
16 13/07/2024
20 14/07/2024
26 15/07/2024
7 16/07/2024
```

Copy-Command

This command will copy a PowerShell command, including parameters and help to a new user-specified command. You can use this to create a "wrapper" function or to easily create a proxy function. The default behavior is to create a copy of the command complete with the original comment-based help block.

Get-ParameterInfo

Using `Get-Command`, this function will return information about parameters for any loaded cmdlet or function. Common parameters like `Verbose` and `ErrorAction` are omitted. `Get-ParameterInfo` returns a custom object with the most useful information an administrator might need to know. The custom object includes default format views for a list and table.



```
PS C:\> Get-ParameterInfo Test-WSMan | Sort Parameterset | Format-Table


ParameterSet: __AllParameterSets

Name                Aliases Mandatory Position Type
-----
CertificateThumbprint      False      Named      System.String
Credential                cred,c     False      Named      System.Management.Automation.PSCredential
ComputerName              cn         False      B          System.String
Authentication             auth,an    False      Named      Microsoft.WSMan.Management.AuthenticationMechanism

ParameterSet: ComputerName

Name                Aliases Mandatory Position Type
-----
UseSSL              False      Named      System.Management.Automation.SwitchParameter
Port                False      Named      System.Int32
ApplicationName      False      Named      System.String

PS C:\> |
```



```
PS C:\> Get-ParameterInfo -Command Get-Counter -Parameter computername

ParameterSet: __AllParameterSets

Name                : computername
Aliases             : Cn
Mandatory           : False
IsDynamic            : False
Position            : Named
Type                : System.String[]
ValueFromPipeline    : False
ValueFromPipelineByPropertyName : False
```

New-PSFormatXML

When defining custom objects with a new type name, PowerShell by default will display all properties. However, you may wish to have a specific default view, be it a table or a list. Or you may want to have different views display the object differently. Format directives are stored in `format.ps1xml` files which can be tedious to create. This command simplifies that process.

Define a custom object:

```
$tName = "myThing"
$obj = [PSCustomObject]@{
    PSTypeName    = $tName
    Name          = "Jeff"
    Date          = (Get-Date)
    Computername  = $env:computername
    OS            = (Get-CimInstance Win32_OperatingSystem).caption
}
$upParams = @{
    TypeName = $tName
    MemberType = "ScriptProperty"
    MemberName = "Runtime"
    value = {(Get-Date) - [datetime]"1/1/2024"}
    force = $True
}
Update-TypeData @upParams
```

The custom object looks like this by default:

```
PS C:\> $obj

Name          : Jeff
Date          : 2/10/2024 8:49:10 PM
Computername  : BOVINE320
OS            : Microsoft Windows 10 Pro
Runtime       : 40.20:49:43.9205882
```

Now you can create new formatting directives.

```
$tName = "myThing"
$params = @{
    Properties = "Name","Date","Computername","OS"
    FormatType = "Table"
    Path = "C:\scripts\$tName.format.ps1xml"
}
$obj | New-PSFormatXML @params

$params.Properties= "Name","OS","Runtime"
$params.Add("ViewName","runtime")
$params.Add(Append,$True)
$obj | New-PSFormatXML @params

$params.formatType = "list"
$params.remove("Properties")
$obj | New-PSFormatXML @params

Update-FormatData -AppendPath $params.path
```

And, here is what the object looks like now:

```
PS C:\> $obj

Name Date          Computername Operating System
----
Jeff 2/10/2024 8:49:10 PM BOVINE320      Microsoft Windows 10 Pro
```

```
PS C:\> $obj | Format-Table -View runtime

Name OS Runtime
---- --
Jeff  40.20:56:24.5411481

PS C:\> $obj | Format-List

Name           : Jeff
Date           : Sunday, February 10, 2024
Computername   : BOVINE320
OperatingSystem : Microsoft Windows 10 Pro
Runtime        : 40.21:12:01
```

Starting with v2.31.0, you can also use a hashtable to define custom properties from script blocks.

```
$p = @{
    FormatType = "List"
    ViewName = "run"
    Path = "c:\scripts\run.ps1xml"
    Properties = "ID", "Name", "Path", "StartTime",
    @{Name="Runtime"; Expression={ (Get-Date) - $_.StartTime }}
}
Get-Process -id $pid | New-PSFormatXML @p
```

If you run this command from Visual Studio Code and specify `-PassThru`, the resulting file will be opened in your editor.

Test-IsPSWindows

PowerShell 7 introduced the `$IsWindows` variable. However, it is not available on Windows PowerShell. Use this command to perform a simple test if the computer is either running Windows or using the `Desktop` PSEdition. The command returns `True` or `False`.

Write-Detail

This command is designed to be used within your functions and scripts to make it easier to write a detailed message that you can use as verbose output. The assumption is that you are using an advanced function with the `Begin`, `Process`, and `End` script blocks. You can create a detailed message to indicate what part of the code is being executed. The output can be configured to include a `DateTime` stamp or just the time.

```
PS C:\> Write-Detail "Getting file information" -Prefix Process -Date
3/26/2025 01:23:38 [PROCESS] Getting file information
```

In a script, you might use it like this:

```
Begin {
    Write-Detail "Starting $($MyInvocation.MyCommand)" -Prefix begin -time |
    Write-Verbose
```

```
$tabs = "`t" * $tab
Write-Detail "Using a tab of $tab" -Prefix BEGIN -time | Write-Verbose
} #begin
```

Save-GitSetup

This command is intended for Windows users to easily download the latest 64-bit version of `Git`.

```
PS C:\> Save-GitSetup -Path c:\work -PassThru

Directory: C:\work

Mode                LastWriteTime         Length Name
----                -
-a---             1/23/2024  4:31 PM       46476880 Git-2.25.0-64-bit.exe
```

You will need to manually install the file. Or you can try something like this:

```
Save-GitSetup -Path c:\work -PassThru | Invoke-Item
```

CIM Tools

The module includes a set of commands to work with CIM and are alternatives to `Get-CimClass`. The information from `Get-CimClass` is helpful, but you often need to take steps to format the results to be something meaningful. These commands aim to simplify the process.

Many of these commands have autocompletion features for the `Namespace` and `ClassName` parameters. Note that even though you can query a remote computer, the tab completion uses values from the local computer.

Find-CimClass

This function is designed to search an entire CIM repository for a class name. Sometimes, you may guess a class name but not know the full name or even the correct namespace. `Find-CimClass` will recursively search for a given class name. You can use wildcards and search remote computers.

```
PS C:\> Find-CimClass
Searching for class *Protection* in 138 namespaces
[oooooooooooooooooooo]

processing W:\CIMV2\Root\CIMV2\mdm

PS C:\> Find-CimClass *Protection*

Namespace: Root\CIMV2\mdm\dmmap

CimClassName      CimClassMethods  CimClassProperties
-----
New_Appliance_EnterpriseDataProt ... {
New_Appliance_EnterpriseDataProt ... {InstanceID, ParentID, Policy}
New_EnterpriseDataProtection       {InstanceID, ParentID, Policy}
New_EnterpriseDataProtection       {InstanceID, ParentID, Status}
New_Policy_Config81_DataProtecti ... {AllowAzurePSForEEP, AllowUserDecryption, DataRecoveryCertificate, EDPEnforce...
New_Policy_Res1181_DataProtecti ... {AllowDirectMemoryAccess, InstanceID, LegacySelectiveWipeID, ParentID}
New_Reporting_EnterpriseDataProt ... {AllowDirectMemoryAccess, InstanceID, LegacySelectiveWipeID, ParentID}
New_Reporting_EnterpriseDataProt ... {InstanceID, LogCount, Logs, ParentID...}
New_WindowsAdvancedThreatProtecti ... {InstanceID, Logs, ParentID, StartTime...}
New_WindowsAdvancedThreatProtecti ... {InstanceID, Onboarding, Unboarding, ParentID}
New_WindowsAdvancedThreatProtecti ... {4aadDeviceID, GroupIDs, InstanceID, ParentID...}
New_WindowsAdvancedThreatProtecti ... {Criticality, Group, IdMethod, InstanceID...}
New_WindowsAdvancedThreatProtecti ... {InstanceID, LastConnected, OnboardingState, OrgId...}
```

Get-CimNamespace

You can use this command to enumerate all WMI/CIM namespaces on a computer starting from ROOT. The default behavior is to recursively enumerate on the local machine, but you can query a remote computer. If you need to support alternate credentials, create a `CIMSession` and pass it to the command.

```
PS C:\> Get-CimNamespace
Root\subscription
Root\subscription\ms_41d
Root\subscription\ms_409
Root\DEFAULT
Root\DEFAULT\ms_41d
Root\DEFAULT\ms_409
Root\CIMV2
Root\CIMV2\mdm
...
```

You can limit the search to top-level namespaces.

```
PS C:\> Get-CimNamespace -TopLevelOnly -CimSession DOM1
Root\subscription
Root\DEFAULT
Root\MicrosoftDfs
Root\CIMV2
Root\msdtc
Root\Cli
Root\MicrosoftActiveDirectory
Root\SECURITY
Root\RSOP
Root\MicrosoftDNS
Root\PEH
...
```

Get-CimClassList

Sometimes `Get-CimClass` is overkill when all you want is a list of class names under a given namespace. `Get-CimClassList` is designed to quickly give you a list of class names. You can filter by name and exclude.

```
PS C:\> Get-CimClassListing *usb* -Exclude cim*

    Namespace: Root/Cimv2

ClassName
-----
Win32_USBController
Win32_USBControllerDevice
Win32_USBHub
```

Get-CimClassProperty

Use this command to quickly get a list of class properties.

```
PS C:\> Get-CimClassProperty win32_USBHub

    Class: Root/Cimv2:Win32_USBHub

Property                ValueType    Flags
-----
Availability             UInt16      ReadOnly, NullValue
Caption                 String      ReadOnly, NullValue
ClassCode               UInt8       NullValue
ConfigManagerErrorCode  UInt32      ReadOnly, NullValue
ConfigManagerUserConfig Boolean      ReadOnly, NullValue
CreationClassName       String      ReadOnly, NullValue
CurrentAlternateSettings UInt8Array   NullValue
CurrentConfigValue      UInt8       NullValue
Description             String      ReadOnly, NullValue
DeviceID                String      Key, ReadOnly, NullValue
ErrorCleared            Boolean     ReadOnly, NullValue
ErrorDescription        String      ReadOnly, NullValue
GangSwitched            Boolean     NullValue
InstallDate             DateTime    ReadOnly, NullValue
```

...

Key properties will be highlighted in green.

Or you can limit output specifying a property name.

```
PS C:\> Get-CimClassProperty Win32_OperatingSystem -Property *memory*
```

```
Class: Root/Cimv2:Win32_OperatingSystem
```

| Property | ValueType | Flags |
|------------------------|-----------|---------------------|
| FreePhysicalMemory | UInt64 | ReadOnly, NullValue |
| FreeVirtualMemory | UInt64 | ReadOnly, NullValue |
| MaxProcessMemorySize | UInt64 | ReadOnly, NullValue |
| TotalVirtualMemorySize | UInt64 | ReadOnly, NullValue |
| TotalVisibleMemorySize | UInt64 | ReadOnly, NullValue |

Get-CimClassMethod

You can likewise query for class methods.

```
PS C:\> Get-CimClassMethod Win32_ComputerSystem
```

```
Class: Root/Cimv2:Win32_ComputerSystem
```

| Name | ResultType | Parameters |
|-------------------------|------------|--|
| JoinDomainOrWorkgroup | UInt32 | {Name, Password, UserName, AccountOU...} |
| Rename | UInt32 | {Name, Password, UserName} |
| SetPowerState | UInt32 | {PowerState, Time} |
| UnjoinDomainOrWorkgroup | UInt32 | {Password, UserName, FUnjoinOptions} |

Get-CimMember

This is a wrapper function that will invoke Get-CimClassProperty or Get-CimClassMethod based on the parameter set used. The default is to show all properties for a given class.

```
PS C:\> Get-CimMember -ClassName win32_bios -Method *
```

```
WARNING: No methods found for Root\Cimv2:WIN32_BIOS
```

```
PS C:\> Get-CimMember -ClassName win32_Volume -Property q*
```

```
Class: Root/Cimv2:Win32_Volume
```

| Property | ValueType | Flags |
|------------------|-----------|---------------------|
| QuotasEnabled | Boolean | ReadOnly, NullValue |
| QuotasIncomplete | Boolean | ReadOnly, NullValue |
| QuotasRebuilding | Boolean | ReadOnly, NullValue |

Get-CimClassPropertyQualifier

This command is an alternative to Get-CimClass to make it easier to get information about property qualifiers of a WMI/CIM class.

```
PS C:\> Get-CimClassPropertyQualifier -ClassName Win32_Service -Property Name
```

```
Property: Root/Cimv2:Win32_Service [Name]
```

```
Name Value CimType Flags
```

```
----
```

```
key   True   Boolean DisableOverride, ToSubclass
```

```
read  True   Boolean EnableOverride, ToSubclass
```

ANSI Tools



ANSI tools related to the filesystem are not loaded on computers where `PSStyle` is detected.

This module includes several custom format files for common objects like services. You can run `Get-Service` and pipe it to the custom table view.

```
Get-Service | Format-Table -view ansi
```

This will display the service status color-coded.

```
Stopped WFDSConMgrSvc Wi-Fi Direct Services Connection Manager ...
Stopped WiaRpc Still Image Acquisition Events
Stopped WinDefend Windows Defender Antivirus Service
Running WinHttpAutoProxySvc WinHTTP Web Proxy Auto-Discovery Service
Paused Winmgmt Windows Management Instrumentation
Running WinRM Windows Remote Management (WS-Management)
Stopped wisvc Windows Insider Service
Running WlanSvc WLAN AutoConfig
Stopped wlidsvc Microsoft Account Sign-in Assistant
Stopped wlpasvc Local Profile Assistant Service
Stopped WManSvc Windows Management Service
Stopped wmiApSrv WMI Performance Adapter
Stopped WMPNetworkSvc Windows Media Player Network Sharing Serv...
Stopped workfolderssvc Work Folders
Stopped WpcMonSvc Parental Controls
Stopped WPDBusEnum Portable Device Enumerator Service
Running WpnService Windows Push Notifications System Service
Running WpnUserService_d9... Windows Push Notifications User Service_d...
Running wscsvc Security Center
Running WSearch Windows Search
```

ANSI formatting will only work in a PowerShell 5.1 console window or VS Code. It will not display properly in the PowerShell ISE or older versions of PowerShell.

PSAnsiMap


I have done something similar for output from `Get-ChildItem`. The module includes a JSON file that is exported as a global variable called `PSAnsiFileMap`.

```
PS C:\> $PSAnsiFileMap
```

| Description | Pattern | Ansi |
|-------------|---|------|
| PowerShell | \.ps(d m)?1\$ | ---- |
| Text | \.(txt) (md) (log)\$ | |
| DataFile | \.(json) (xml) (csv)\$ | |
| Executable | \.(exe) (bat) (cmd) (sh)\$ | |
| Graphics | \.(jpg) (png) (gif) (bmp) (jpeg)\$ | |
| Media | \.(mp3) (m4v) (wav) (au) (flac) (mp4)\$ | |
| Archive | \.(zip) (rar) (tar) (gzip)\$ | |

```
TopContainer
ChildContainer
```

The map includes ANSI settings for different file types. You won't see the ANSI value in the output. The module will add a custom table view called `ansi` which you can use to display colorized file results.



```
PS C:\> dir c:\work\alpha -Recurse | format-table -view ansi

Directory: C:\work\Alpha

Mode                LastWriteTime         Length Name
----                -
da---             3/5/2020  4:46 PM              bravo
-a---             11/8/2019  3:29 PM            12109 documents-log.csv
-a---             11/9/2019  9:00 AM           30335 dropbox-log.csv
-a---             11/9/2019  1:00 AM             671 GoogleDrive-log.csv
-a---             10/31/2019  1:42 PM              45 junk.txt
-a---             11/9/2019  9:03 AM          166435 Scripts-log.csv
-a---             11/10/2019  4:32 PM            2673 stuff.tep
-a---             11/10/2019 12:49 PM             43 test.data

Directory: C:\work\Alpha\bravo

Mode                LastWriteTime         Length Name
----                -
d----             2/28/2020 11:17 AM              delta
da---             11/6/2017  4:21 PM              gamma
d----             2/28/2020 11:16 AM             images
-a---             11/6/2017  4:47 PM            636 data.txt
-a---             11/7/2019 10:32 AM            131 sample-1.json
-a---             11/7/2019 10:32 AM            131 sample-2.json
-a---             11/7/2019 10:32 AM            131 sample-3.json
-a---             11/7/2019 10:32 AM            131 sample-4.json
-a---             10/31/2019  5:25 PM          5769412 something2.xml
-a---             3/5/2020  4:46 PM              0 zz.foo

Directory: C:\work\Alpha\bravo\delta

Mode                LastWriteTime         Length Name
----                -
-a---             6/1/2009  3:50 PM            888 FunctionDemo.ps1
-a---             4/17/2019  5:18 PM           1117 function-form.ps1
-a---             5/23/2007 11:39 AM            598 function-logstamp.ps1
```

The mapping file is user-customizable. Copy the `psansifilemap.json` file from the module's root directory to `$HOME`. When you import this module, if the file is found, it will be imported and used as `psansifilemap`, otherwise, the module's file will be used.

The file will look like this:

```
[
{
  "Description": "PowerShell",
  "Pattern": "\\.(ps(d|m)?1$)",
  "Ansi": "\u001b[38;2;252;127;12m"
},
{
  "Description": "Text",
  "Pattern": "\\.(txt)|(md)|(log)$",
  "Ansi": "\u001b[38;2;58;120;255m"
},
{
  "Description": "DataFile",
  "Pattern": "\\.(json)|(xml)|(csv)$",
  "Ansi": "\u001b[38;2;249;241;165m"
}
```

```
},
{
  "Description": "Executable",
  "Pattern": "\\.(exe)|(bat)|(cmd)|(sh)$",
  "Ansi": "\u001b[38;2;197;15;31m"
},
{
  "Description": "Graphics",
  "Pattern": "\\.(jpg)|(png)|(gif)|(bmp)|(jpeg)$",
  "Ansi": "\u001b[38;2;255;0;255m"
},
{
  "Description": "Media",
  "Pattern": "\\.(mp3)|(m4v)|(wav)|(au)|(flac)|(mp4)$",
  "Ansi": "\u001b[38;2;255;199;6m"
},
{
  "Description": "Archive",
  "Pattern": "\\.(zip)|(rar)|(tar)|(gzip)$",
  "Ansi": "\u001b[38;2;118;38;113m"
},
{
  "Description": "TopContainer",
  "Pattern": "",
  "Ansi": "\u001b[38;2;0;255;255m"
},
{
  "Description": "ChildContainer",
  "Pattern": "",
  "Ansi": "\u001b[38;2;255;255;0m"
}
]
```

You can create or modify file groups. The Pattern value should be a regular expression pattern to match the filename. Don't forget you will need to escape characters for the JSON format. The ANSI value will be an ANSI escape sequence. You can use `\u001b` for the ``e` character.

If you prefer not to edit JSON files, you can use the `PSAnsiFileMap` commands from this module.

Get-PSAnsiFileMap

This command will display the value of the `$PSAnsiFileMap` variable, but will also show the ANSI sequence using the sequence itself.

```
PS C:\> Get-PSAnsiFileMap
```

| Description | Pattern | ANSI |
|----------------|---|----------------------------------|
| PowerShell | \.((ps(d n)?1) {ps1xml}))\$ | <code>e[38;2;252;127;12m</code> |
| Text | \.((txt) (log) (htm(l)?))\$ | <code>e[38;2;58;120;255m</code> |
| Documents | \.((pdf) (doc(x)?) (md) (xls(x)?) (ppt(x)?) (xps))\$ | <code>e[38;5;121m</code> |
| Temporary | \.((tmp) (bak) (sav) (temp))\$ | <code>e[38;5;200m</code> |
| DataFile | \.((json) (xml) (csv) (db) (mof) (mdb) (dat))\$ | <code>e[38;2;249;241;165m</code> |
| Executable | \.((exe) (bat) (cmd) (sh) (py))\$ | <code>e[38;2;197;15;31m</code> |
| System | \.((sys) (dll) (bin) (conf^) (ini))\$ | <code>e[38;5;204m</code> |
| Graphics | \.((jpg) (png) (gif) (bmp) (jpeg) (ico) (svg) (tif) (raw))\$ | <code>e[38;2;255;0;255m</code> |
| Media | \.((mp[34]) (n4v) (wav) (au) (flac) (mov)))\$ | <code>e[38;2;255;199;6m</code> |
| Archive | \.((zip) (rar) (tar) (gz(ip)?dir) (7z) (win) (bzip2) (nsi(x)?) (rpm))\$ | <code>e[38;5;75m</code> |
| TopContainer | | <code>e[38;2;0;255;255m</code> |
| ChildContainer | | <code>e[38;2;255;255;0m</code> |

```
PS C:\>
```

Set-PSAnsiFileMap

Use this command to modify an existing entry. You need to specify a regular expression pattern to match the filename and/or an ANSI escape sequence. If the entry description doesn't exist, you will need to specify the regex pattern and the ANSI sequence to add the entry to \$PSAnsiFileMap.

```
Set-PSAnsiFileMap Archive -Ansi "`e[38;5;75m"
```

Remove-PSAnsiFileEntry

If you need to, you can remove an entry from \$PSAnsiFileMap.

```
Remove-PSAnsiFileEntry DevFiles
```

Export-PSAnsiFileMap

Any changes you make to \$PSAnsiFileMap will only last until you import the module again. To make the change permanent, use [Export-PSAnsiFileMap](#). This will create the `psansifilemap.json` file in your \$HOME directory. When you import the PSScriptTools module, if this file is found, it will be imported. Otherwise, the default version from the module will be used.

Convert-HtmlToAnsi

This simple function is designed to convert an HTML color code like `#ff5733` into an ANSI escape sequence.

```
PS C:\> Convert-HtmlToAnsi "#ff5733"
[38;2;255;87;51m
```


To use the resulting value you still need to construct an ANSI string with the escape character and the closing `[0m`.

```
PS C:\> "`e$(Convert-HtmlToAnsi "#ff8738")Hello, World`e[0m"
Hello, World
```

In PowerShell 7 you can use ``e`. Or `$([char]27)` which works in all PowerShell versions.

New-ANSIBar


You can use this command to create colorful bars using ANSI escape sequences based on a 256-color scheme. The default behavior is to create a gradient bar that goes from first to last values in the range and then back down again. Or you can create a single gradient that runs from the beginning of the range to the end. You can use one of the default characters or specify a custom one.



```
Admin: PowerShell 7.0
PS C:\>
PS C:\> New-ANSIBar -Range (232..255)
PS C:\>
PS C:\> New-ANSIBar -range (46..51) -Character BlackSquare -Spacing 3
PS C:\>
PS C:\> New-ANSIBar -range (214..219) -Gradient -Spacing 5 -Character DarkShade
PS C:\>
```

Write-ANSIProgress

You could also use `Write-ANSIProgress` to show a custom ANSI bar.



```
Admin: PowerShell 7.0
PS C:\>
PS C:\> Write-ANSIProgress -PercentComplete .78 -BarSymbol Circle -ProgressColor "$([char]0x1b)[92m"
78% .....
PS C:\>
PS C:\>

PS C:\> Get-CimInstance win32_operatingsystem |
>> Select-Object @(Name = "MemGB"; Expression = {$_ .TotalVisibleMemorySize/1MB -as [int]}),
>> FreePhysicalMemory,
>> @(Name = "PctFree"; Expression = { $pct = $([math]::round($_.FreePhysicalMemory/$_.TotalVisibleMemorySize, 2));
>> Write-ANSIProgress -PercentComplete $pct | Select-Object -last 1})

MemGB FreePhysicalMemory PctFree
-----
32      14687996 44% .....
```

Or you can use it in your code to display a console progress bar.




```
$sb = {
    Clear-Host
    $top = Get-ChildItem c:\scripts -Directory
```

```

$i = 0
$out=@()
$pos = $host.UI.RawUI.CursorPosition
Foreach ($item in $top) {
    $i++
    $pct = [math]::round($i/$top.count,2)
    Write-ANSIProgress -PercentComplete $pct -position $pos
    Write-Host "   Processing $($item.FullName).PadRight(80))"
    -ForegroundColor Yellow -NoNewline
    $out+= Get-ChildItem -Path $item -Recurse -file |
    Measure-Object -property length -sum |
    Select-Object @{Name="Path";Expression={$item.FullName}},Count,
    @{Name="Size";Expression={$_.Sum}}
}
Write-Host ""
$out | Sort-Object -property Size -Descending
}

```



42%
 Processing C:\scripts\MyClass

Show-ANSISequence

You can use `Show-ANSISequence` to preview how it will look in your PowerShell session. You might get a different appearance in Windows Terminal depending on the color scheme you are using.

The default behavior is to show basic sequences.

```

PS C:\>
PS C:\> Show-ANSISequence

*****
* Basic Sequences *
*****
`e[9mCrossedOut`e[0m
`e[7mReverse`e[0m
`e[6mRapidBlink`e[0m
`e[5mSlowBlink`e[0m
`e[4mUnderline`e[0m
`e[3mItalic`e[0m
`e[2mFaint`e[0m
`e[1mBold`e[0m

PS C:\> _

```

You can also view foreground and or background settings.


```

PS C:\> Show-ANSISequence -Foreground

*****
* Foreground *
*****
`e[30mHello`e[0m      `e[31mHello`e[0m      `e[32mHello`e[0m
`e[33mHello`e[0m      `e[34mHello`e[0m      `e[35mHello`e[0m
`e[36mHello`e[0m      `e[37mHello`e[0m      `e[90mHello`e[0m
`e[91mHello`e[0m      `e[92mHello`e[0m      `e[93mHello`e[0m
`e[94mHello`e[0m      `e[95mHello`e[0m      `e[96mHello`e[0m

*****
* 8-Bit Foreground *
*****
`e[38;5;1mHello`e[0m  `e[38;5;2mHello`e[0m  `e[38;5;3mHello`e[0m
`e[38;5;4mHello`e[0m  `e[38;5;5mHello`e[0m  `e[38;5;6mHello`e[0m
`e[38;5;7mHello`e[0m  `e[38;5;8mHello`e[0m  `e[38;5;9mHello`e[0m
`e[38;5;10mHello`e[0m `e[38;5;11mHello`e[0m `e[38;5;12mHello`e[0m
`e[38;5;13mHello`e[0m `e[38;5;14mHello`e[0m `e[38;5;15mHello`e[0m
`e[38;5;16mHello`e[0m `e[38;5;17mHello`e[0m `e[38;5;18mHello`e[0m
`e[38;5;19mHello`e[0m `e[38;5;20mHello`e[0m `e[38;5;21mHello`e[0m
`e[38;5;22mHello`e[0m `e[38;5;23mHello`e[0m `e[38;5;24mHello`e[0m
`e[38;5;25mHello`e[0m `e[38;5;26mHello`e[0m `e[38;5;27mHello`e[0m
`e[38;5;28mHello`e[0m `e[38;5;29mHello`e[0m `e[38;5;30mHello`e[0m
`e[38;5;31mHello`e[0m `e[38;5;32mHello`e[0m `e[38;5;33mHello`e[0m
`e[38;5;34mHello`e[0m `e[38;5;35mHello`e[0m `e[38;5;36mHello`e[0m
`e[38;5;37mHello`e[0m `e[38;5;38mHello`e[0m `e[38;5;39mHello`e[0m
`e[38;5;40mHello`e[0m `e[38;5;41mHello`e[0m `e[38;5;42mHello`e[0m

```

You can even use an RGB value.

```

PS C:\> Show-ANSISequence -rgb 200,250,240

`e[38;2;200;250;240m256 Color (R:200)(G:250)(B:240)`e[0m

PS C:\> _

```

The escape character will match what is acceptable in your version of PowerShell. These screenshots are showing PowerShell 7.

Other Module Features

These are additional items in the module that you might find useful in your PowerShell work.

Custom Format Views

The module includes several custom `format.ps1xml` files that define additional views for common objects. Some of these have already been demonstrated elsewhere in this document.

For example, there is a custom table view for Aliases.

```
PS C:\> Get-Alias | Sort-Object Source | Format-Table -view Source
```

Source:

| Name | Definition |
|-------|--------------------------------|
| ---- | ----- |
| nmo | New-Module |
| ni | New-Item |
| npssc | New-PSSessionConfigurationFile |
| nv | New-Variable |
| nsn | New-PSSession |
| ... | |

Source: Microsoft.PowerShell.Management 3.1.0.0

| Name | Definition |
|------|--------------|
| ---- | ----- |
| gtz | Get-TimeZone |
| stz | Set-TimeZone |
| ... | |

Source: Microsoft.PowerShell.Utility 3.1.0.0

| Name | Definition |
|------|--------------------|
| ---- | ----- |
| fhx | Format-Hex |
| CFS | ConvertFrom-String |

Source: PSScriptTools 3.0.0

| Name | Definition |
|------|------------------------|
| ---- | ----- |
| clr | Convert-EventLogRecord |
| gsi | Get-FolderSizeInfo |
| wver | Get-WindowsVersion |
| gpi | Get-ParameterInfo |
| che | Copy-HelpExample |
| ... | |

Some custom formats use ANSI to highlight information, assuming you are running in PowerShell Console Host.

```
PS C:\> get-alias | Format-Table -view options
```

| Name | Definition | Options | ModuleName | Version |
|---------|-------------------------|--------------------|---------------|---------|
| ? | Where-Object | ReadOnly, AllScope | | |
| % | ForEach-Object | ReadOnly, AllScope | | |
| ab | Add-Border | None | PSScriptTools | 2.36.0 |
| ac | Add-Content | ReadOnly | | |
| after | Select-After | None | PSScriptTools | 2.36.0 |
| before | Select-Before | None | PSScriptTools | 2.36.0 |
| cart | ConvertTo-ASCIITart | None | PSScriptTools | 2.36.0 |
| cat | Get-Content | None | | |
| cc | Copy-Command | None | PSScriptTools | 2.36.0 |
| cd | Set-Location | AllScope | | |
| cft | ConvertFrom-Text | None | PSScriptTools | 2.36.0 |
| chc | Convert-HashtableToCode | None | PSScriptTools | 2.36.0 |
| chdir | Set-Location | None | | |
| che | Copy-HelpExample | None | PSScriptTools | 2.36.0 |
| clc | Clear-Content | ReadOnly | | |
| clear | Clear-Host | None | | |
| clhy | Clear-History | ReadOnly | | |
| cli | Clear-Item | ReadOnly | | |
| clp | Clear-ItemProperty | ReadOnly | | |
| clr | Convert-EventLogRecord | None | PSScriptTools | 2.36.0 |
| cls | Clear-Host | None | | |
| clt | ConvertTo-LocalTime | None | PSScriptTools | 2.36.0 |
| clv | Clear-Variable | ReadOnly | | |
| cmo | Compare-Module | None | PSScriptTools | 2.36.0 |
| cnsn | Connect-PSSession | ReadOnly | | |
| compare | Compare-Object | ReadOnly | | |
| copy | Copy-Item | AllScope | | |
| cp | Copy-Item | AllScope | | |

In this format view, ReadOnly aliases are displayed in Red.

Use [Get-FormatView](#) to discover available format views. Or if you'd like to create custom views look at [New-PSFormatXML](#)

Custom Type Extensions

The module includes custom type extensions for several common object types. These are designed to make it easier to work with common objects in PowerShell. Beginning with version 2.50.1, you must manually import these extensions. You can use [Get-PSScriptToolsTypeExtension](#) to see what is available.

```
PS C:\> Get-PSScriptToolsTypeExtension -TypeName *file*
```

| | |
|---|-------------------|
| TypeName : System.IO.FileInfo | |
| Description: Alias and script properties designed to extend the file object. There is also a PropertySet called AgeInfo. | |
| MemberType | MemberName |
| AliasProperty | Size |
| AliasProperty | Created |
| AliasProperty | Modified |
| PropertySet | AgeInfo |
| ScriptProperty | SizeKB |
| ScriptProperty | SizeMB |
| ScriptProperty | ModifiedAge |
| ScriptProperty | CreatedAge |

Use [Import-PSScriptToolsTypeExtension](#) to import the extensions.

System.IO.FileInfo

The module will extend file objects with the following alias properties:

| New Alias | Property |
|-----------|----------|
| Size | Length |

| New Alias | Property |
|-----------|---------------|
| Created | CreationTime |
| Modified | LastWriteTime |

You also have new script properties

| Script Property | Description |
|-----------------|---|
| ModifiedAge | A timespan between the current date the and last write time |
| CreatedAge | A timespan between the current date the and creation time |
| SizeKB | The file size formatted in KB to 2 decimal places |
| SizeMB | The file size formatted in MB to 2 decimal places |

```
PS C:\> Get-ChildItem C:\Scripts\SharedProfileDefault.ps1 | Select-Object Name,Size,SizeKB,SizeMB,Created,CreatedAge,Modified,ModifiedAge

Name      : SharedProfileDefault.ps1
Size       : 3288
SizeKB     : 3.21
SizeMB     : 0
Created    : 8/17/2023 8:47:13 AM
CreatedAge : 586.05:33:54.5461727
Modified   : 3/21/2025 9:29:40 AM
ModifiedAge : 4.04:51:27.6225204
```

There is also a custom property set.

```
PS C:\> Get-ChildItem C:\Scripts\SharedProfileDefault.ps1 | Select-Object AgeInfo

Directory      : C:\Scripts
Name           : SharedProfileDefault.ps1
Size           : 3288
LastWriteTime  : 3/21/2025 9:29:40 AM
ModifiedAge    : 4.04:52:29.3136140
```

System.Diagnostics.Process

The module can extend process objects with a `Runtime` script property.

```
PS C:\> Get-Process | Sort-Object runtime -Descending |
Select-Object -first 5 -Property ID,Name,Runtime

Id Name           Runtime
-- ----
120 Secure System 20:44:51.6139043
204 Registry      20:44:51.3661961
  4 System        20:44:48.2820565
704 smss          20:44:48.2726401
820 csrss         20:44:44.7760844
```

The Idle process will have a null value for this property.

Microsoft.PowerShell.Commands.GenericMeasureInfo

When using `Measure-Object`, you often want to format `Sum` or `Average` values to megabytes or kilobytes. If you import the `GenericMeasureInfo` type extension, you will have new script properties for `Sum` and `Average` that will be formatted to MB or KB.

```
PS C:\> dir c:\work\ -file | Measure -Property Size -sum -Average | Select Count,Sum*,Average*

Count      : 378
SumKB      : 74162.5576
SumMB      : 72.4244
SumGB      : 0.0707
Sum        : 75942459
AverageKB  : 196.1972
AverageMB  : 0.1916
AverageGB  : 0.0002
Average    : 200905.976190476
```

This example is using the `Size` property from the custom `FileInfo` type extension.

PSSpecialChar

A number of the commands in this module can use special characters. To make it easier, when you import the module, it will create a global variable that is a hash table of common special characters. Because it is a hashtable, you can add to it.

```
PS C:\> $PSSpecialChar
```

| Name | Value |
|------------------|---|
| ----- | ----- |
| MediumShade |  |
| FullBlock |  |
| WhiteSquare |  |
| Heart |  |
| DarkShade |  |
| SixPointStar |  |
| Spade |  |
| WhiteCircle |  |
| LightShade |  |
| BlackSquare |  |
| DownTriangle |  |
| BlackSmallSquare |  |
| WhiteSmallSquare |  |
| Diamond |  |
| WhiteFace |  |
| UpTriangle |  |
| BlackFace |  |
| Lozenge |  |
| Club |  |
| BlackCircle |  |

```
PS C:\> $PSSpecialChar.blackcircle
```

```
•
```

```
PS C:\> $PSSpecialChar.blackcircle -as [int]
```

```
9679
```

```
PS C:\> [char]9679
```

```
•
```

```
PS C:\> _
```

The names are the same as used in `CharMap.exe`. Don't let the naming confuse you. It may say `BlackSquare`,

```
Get-WindowsVersionString |  
Add-Border -border $PSSpecialChar.BlackSmallSquare `   
-ANSIBorder "$([char]0x1b)[38;5;214m"  
  
Admin: PowerShell 7.0  
PS C:\>  
PS C:\> Get-WindowsVersionString | Add-Border -border $PSSpecialChar.BlackSmallSquare -ANSIBorder "$([char]0x1b)[38;5;214m"  
• BOVINE320 Windows 10 Pro Version Professional (OS Build 18363.836) •  
PS C:\>
```

This PowerShell module contains several functions you might use to enhance your functions and scripts. The **Samples** folder contains demonstration script files. You can access the folder in PowerShell using the `$PSSamplePath`.

```
dir $PSSamplePath
```

```
PS C:\> . $PSSamplePath\ProcessPercent.ps1
```

| Name | Id | Handles | WS(MB) | PctWS | |
|----------------------|-------|---------|--------|-------|--|
| ---- | -- | ----- | ----- | ----- | |
| TabNine | 35188 | 293 | 1384 | 10.73 | ██ |
| Memory Compression | 3044 | 0 | 1249 | 09.69 | ██ |
| firefox | 18936 | 1630 | 798 | 06.18 | ████████████████████ |
| LenovoVantageService | 5724 | 1273 | 784 | 06.08 | ████████████████████ |
| dwm | 1532 | 2835 | 382 | 02.96 | ████████ |
| firefox | 18368 | 3187 | 349 | 02.71 | ████████ |
| firefox | 21912 | 1573 | 338 | 02.62 | ████████ |
| pwsh | 25220 | 1183 | 311 | 02.41 | ████ |
| thunderbird | 23268 | 2032 | 247 | 01.91 | ████ |
| powershell_ise | 4896 | 946 | 244 | 01.89 | ████ |
| firefox | 28208 | 901 | 224 | 01.74 | ████ |
| Code | 34948 | 598 | 213 | 01.65 | ████ |
| powershell | 24608 | 917 | 209 | 01.62 | ████ |
| pwsh | 21864 | 1219 | 203 | 01.57 | ████ |

I've created a PDF version of this document which I thought you might find useful since it includes screenshots and sample output rendered nicer than what you can get in PowerShell help. Run `Open-PSScriptToolsHelp` to open the PDF using the default associated application.

Deprecated Commands

The following commands have been removed as of v2.50.0.

- `Set-ConsoleColor`
- `Out-ConditionalColor`

Related Modules

If you find this module useful, you might also want to look at my PowerShell tools for:

- [Keeping up to date with PowerShell 7 releases](#)
- [Module and Project Status](#)
- [Creating and managing customized type extensions](#)
- [Managing scheduled jobs](#)
- [Automating the PowerShell scripting process](#)
- [A simple command-line task and to-do manager](#)

Compatibility

Where possible, module commands have been tested with PowerShell 7, but not on every platform. If you encounter problems, have suggestions, or have other feedback, please post an [issue](#). It is assumed you will **not** be running these commands on any edition of PowerShell Core, i.e. PowerShell 6.

Module Commands

This section contains the same help content you would get from a PowerShell prompt using `Get-Help`. Note that most code examples have been formatted to fit the 80 character page width and sometimes with artificial formatting. Don't assume you can run examples *exactly* as they are shown. Some of the help examples might also use special or custom characters that might not render properly in the PDF.


Remember, you can also view the online help for each command:

```
Help ConvertTo-WPFGrid -online
```

If you can't remember what commands are in this module, you can always ask PowerShell.

```
Get-Command -module PSScriptTools
```

Or use the `Get-PSScriptTools` command.



You can also filter by verb.

Add-Border

Synopsis

Create a text border around a string.

Syntax

single (Default)

```
Add-Border [-Text] <String> [-Character <String>] [-InsertBlanks]  
[-Tab <Int32>] [-ANSIBorder <String>] [-ANSIText <String>] [<CommonParameters>]
```

block

```
Add-Border [-TextBlock] <String[]> [-Character <String>] [-InsertBlanks]  
[-Tab <Int32>] [-ANSIBorder <String>] [-ANSIText <String>] [<CommonParameters>]
```

Description

This command will create a character or text-based border around a line of text. You might use this to create a formatted text report or to improve the display of information to the screen.

Examples

Example 1

```
PS C:\> Add-Border "PowerShell Wins!"
```

```
*****  
* PowerShell Wins! *  
*****
```

Example 2

```
PS C:\> Add-Border "PowerShell Wins!" -tab 1
```

```
*****  
* PowerShell Wins! *  
*****
```

Note that this example may not format properly in all consoles.

Example 3

```
PS C:\> Add-Border "PowerShell Wins!" -character "-" -insertBlanks
```

```
-----
- PowerShell Wins! -
-----
```

Example 4

```
PS C:\> Add-Border -TextBlock (Get-Service win* | Out-String).trim()
```

```
*****
* Status      Name                      DisplayName                                *
* -----    ----                      -
* Stopped     WinDefend                 Windows Defender Antivirus Service        *
* Running     WinHttpAutoProx...       WinHTTP Web Proxy Auto-Discovery Se...    *
* Running     Winmgmt                  Windows Management Instrumentation         *
* Stopped     WinRM                    Windows Remote Management (WS-Manag...    *
*****
```

Create a border around the output of a Get-Service command.

Example 5

```
PS C:\> Add-Border -Text $t -ANSIBorder "$([char]0x1b)[38;5;47m"  
-ANSIText "$([char]0x1b)[93m" -InsertBlanks
```

```
*****
*                                     *
*  I am the walrus  *
*                                     *
*****
```

This will write a color version of the text and border. You would this type of ANSI syntax for Windows PowerShell. In PowerShell 7, you can use the same syntax or the much easier "``e[38;5;47m``".

Example 6

```
PS C:\> Add-Border -TextBlock (Get-PSWho -AsString ).trim() -ANSIBorder
`e[38;5;214m" -Character ([char]0x25CA) -ANSIText "`e[38;5;225m"
```

```

0000000000000000000000000000000000000000000000000000000000000000
0 User           : BOVINE320\Jeff                                0
0 Elevated       : True                                           0
0 Computername   : BOVINE320                                       0
0 OperatingSystem : Microsoft Windows 10 Pro [64-bit]             0
0 OSVersion      : 10.0.18363                                     0

```

[illegible]

This example requires PowerShell 7 because of the way the escape sequence is defined. The border character is a diamond. Depending on how you are viewing this help content, it may not display properly.

Parameters

-Text

A single line of text that will be wrapped in a border.

```
Type: String
Parameter Sets: single
Aliases:

Required: True
Position: 1
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-TextBlock

A multi-line block of text. You might want to trim blank lines from the beginning, end or both.

```
Type: String[]
Parameter Sets: block
Aliases: tb

Required: True
Position: 1
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Character

The character to use for the border. It must be a single character.

```
Type: String
Parameter Sets: (All)
Aliases: border

Required: False
Position: Named
```

```
Default value: *
Accept pipeline input: False
Accept wildcard characters: False
```

-InsertBlanks

Insert blank lines before and after the text. The default behavior is to create a border box close to the text. See examples.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

-Tab

Insert X number of tabs.

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: 0
Accept pipeline input: False
Accept wildcard characters: False
```

-ANSIBorder

Enter an ANSI escape sequence to color the border characters.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-ANSIText

Enter an ANSI escape sequence to color the text.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

System.String

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[New-ANSIBar](#)

Compare-Module

Synopsis

Compare PowerShell module versions.

Syntax

```
Compare-Module [[-Name] <String>] [-Gallery <String>] [<CommonParameters>]
```

Description

Use this command to compare module versions between what is installed against an online repository like the PSGallery. Results will be automatically sorted by module name.

Examples

Example 1

```
PS C:\> Compare-Module | Where-Object {$_.UpdateNeeded}

Name           : ActiveDirectoryDsc
OnlineVersion  : 6.6.2
InstalledVersion : 6.2.0,6.0.1
PublishedDate  : 3/17/2025 4:41:19 PM
UpdateNeeded   : True

Name           : ComputerManagementDsc
OnlineVersion  : 10.0.0
InstalledVersion : 9.0.0,8.5.0,8.4.0
PublishedDate  : 1/25/2025 3:17:04 PM
UpdateNeeded   : True

Name           : DynamicTitle
OnlineVersion  : 0.4.0
InstalledVersion : 0.3.0
PublishedDate  : 7/10/2023 1:15:44 PM
UpdateNeeded   : True
...
```

List all modules that could be updated.

Example 2

```
PS C:\> Compare-Module | Where UpdateNeeded |
Out-GridView -title "Select modules to update" -outputMode multiple |
Foreach-Object { Update-Module $_.name }
```

Compare modules and send results to Out-GridView. Use Out-GridView as an object picker to decide what modules to update.

Example 3

```
PS C:\> Compare-Module -name xWin* | Format-Table
```

| Name | OnlineVersion | InstalledVersion | PublishedDate | UpdateNeeded |
|----------------|---------------|------------------|----------------------|--------------|
| xWindowsUpdate | 2.8.0.0 | 2.8.0.0 | 4/3/2019 10:53:09 PM | False |

Compare all modules that start with xWin* and display results in a table format.

Example 4

```
PS C:\> Get-DSCResource xAD* | Select-Object moduleName -Unique |  
Compare-Module
```

Name : xActiveDirectory
OnlineVersion : 3.0.0.0
InstalledVersion : 3.0.0.0
PublishedDate : 6/26/2019 9:34:27 PM
UpdateNeeded : False

Name : xAdcsDeployment
OnlineVersion : 1.4.0.0
InstalledVersion : 1.4.0.0
PublishedDate : 12/20/2017 10:10:43 PM
UpdateNeeded : False

Get all DSC Resources that start with xAD and select the corresponding module name. Since the module name will be listed for every resource, get a unique list and pipe that to Compare-Module.

Parameters

-Name

The name of a module to check. Wildcards are permitted.

```
Type: String  
Parameter Sets: (All)  
Aliases: modulename  
  
Required: False  
Position: 1  
Default value: None  
Accept pipeline input: True (ByPropertyName)  
Accept wildcard characters: True
```

-Gallery

Specify the remote repository or gallery to check.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: PSGallery
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

System.String

Outputs

PSCustomObject

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Find-Module

Get-Module

Update-Module

Compare-Script

Synopsis

Compare PowerShell script versions.

Syntax

```
Compare-Script [[-Name] <String>] [-Gallery <String>] [<CommonParameters>]
```

Description

Use this command to compare script versions between what is installed against an online repository like the PSGallery. Results will be automatically sorted by the script name.

Examples

Example 1

```
PS C:\> Compare-Script | Where-object {$_.UpdateNeeded}
```

```
Name           : winfetch
OnlineVersion   : 2.5.1
InstalledVersion : 1.0
PublishedDate   : 8/26/2023 8:12:46 PM
UpdateNeeded    : True
```

List all scripts that could be updated.

Example 2

```
PS C:\> Compare-Script | Where UpdateNeeded |
Out-GridView -Title "Select scripts to update" -OutputMode multiple |
Foreach-Object { Update-Script $_.name }
```

Compare scripts and send results to Out-GridView. Use Out-GridView as an object picker to decide what scripts to update.

Parameters

-Name

The name of a script to check. Wildcards are permitted.

```
Type: String
Parameter Sets: (All)
Aliases: scriptname

Required: False
Position: 1
Default value: None
Accept pipeline input: True (ByPropertyName)
Accept wildcard characters: True
```

-Gallery

Specify the remote repository or gallery to check.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: PSGallery
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

System.String

Outputs

PSCustomObject

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Find-Script

Get-InstalledScript

Update-Script

Convert-CommandToHashtable

Synopsis

Convert a PowerShell expression into a splatting equivalent.

Syntax

```
Convert-CommandToHashtable [-Text] <String> [<CommonParameters>]
```

Description

This command is intended to convert a long PowerShell expression with named parameters into a splatting alternative. The central concept is that you are editing a script file with a lengthy PowerShell expression with multiple parameters and you would like to turn it into splatting code.

Examples

Example 1

```
PS C:\> $text ="Get-WinEvent -ListLog p* -computername SRV1 -ErrorAction stop"  
PS C:\> Convert-CommandToHashtable -Text $text | Set-Clipboard
```

The \$text variable might be a line of code from your script. The second line converts into a splatting sequence and copies it to the Windows clipboard so you can paste it back into your script. You could create a VS Code task sequence using this function.

Parameters

-Text

A PowerShell command using a single cmdlet or function, preferably with named parameters.

```
Type: String  
Parameter Sets: (All)  
Aliases:  
  
Required: True  
Position: 0  
Default value: None  
Accept pipeline input: False  
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

None

Outputs

Hashtable

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Convert-HashtableToCode](#)

Convert-EventLogRecord

Synopsis

Convert EventLogRecords to structured objects.

Syntax

```
Convert-EventLogRecord [-LogRecord] <EventLogRecord[]> [<CommonParameters>]
```

Description

When you use Get-WinEvent, the results are objects you can work with in PowerShell. However, often times there is additional information that is part of the eventlog record, such as replacement strings, that are used to construct a message. This additional information is not readily exposed. You can use this command to convert the results of a Get-WinEvent command into a PowerShell custom object with additional information. For best results, you should pipe the same event IDs to this command.

Note that not every event record exposes data that is compatible with this command. For those types of event log records, you will see a RawProperties property with most likely an array of strings. Use the Message property for more information.

Examples

Example 1

```
PS C:\> Get-WinEvent -FilterHashtable @{LogName = 'security';ID=5059} |  
Convert-EventLogRecord | Select-Object -Property TimeCreated,Subject*,  
Computername  
  
TimeCreated      : 3/26/2025 9:03:41 AM  
SubjectUserSid   : S-1-5-21-3465062479-264850141-705915528-1001  
SubjectUserName  : Jeff  
SubjectDomainName : PROSPERO  
SubjectLogonId   : 0x34cb5c  
Computername     : Prospero  
  
TimeCreated      : 3/26/2025 9:03:41 AM  
SubjectUserSid   : S-1-5-21-3465062479-264850141-705915528-1001  
SubjectUserName  : Jeff  
SubjectDomainName : PROSPERO  
SubjectLogonId   : 0x34cb5c  
Computername     : Prospero  
...
```

Example 2

```
PS C:\> Get-WinEvent -FilterHashtable @{LogName = 'security';ID=4624} `
-MaxEvents 100 -computername win10 | Convert-EventLogRecord |
Where-Object {$_.LogonType -eq 3} |
Select-Object -first 10 -property TargetUsername,IPAddress,
TimeCreated,Computername | Format-Table
```

| TargetUsername | IpAddress | TimeCreated | Computername |
|----------------|---------------------------|-----------------------|-------------------|
| ArtD | fe80::ddae:8ade:c3ff:e584 | 1/20/2025 12:05:12 PM | WIN10.Company.Pri |
| WIN10\$ | - | 1/20/2025 11:56:52 AM | WIN10.Company.Pri |
| WIN10\$ | - | 1/20/2025 11:56:52 AM | WIN10.Company.Pri |
| WIN10\$ | - | 1/20/2025 11:56:52 AM | WIN10.Company.Pri |
| WIN10\$ | - | 1/20/2025 11:56:51 AM | WIN10.Company.Pri |
| ArtD | 192.168.3.10 | 1/20/2025 11:45:31 AM | WIN10.Company.Pri |
| WIN10\$ | ::1 | 1/20/2025 11:39:52 AM | WIN10.Company.Pri |
| ArtD | 192.168.3.10 | 1/20/2025 11:35:49 AM | WIN10.Company.Pri |
| ArtD | 192.168.3.10 | 1/20/2025 11:34:36 AM | WIN10.Company.Pri |
| ArtD | 192.168.3.10 | 1/20/2025 11:32:06 AM | WIN10.Company.Pri |

This example filters on a property added by this command to only show interactive logons.

Example 3

```
PS C:\> Get-WinEvent -FilterHashtable @{LogName = 'system';
ID = 7040} -MaxEvent 10 | Convert-EventlogRecord |
Select-Object -Property TimeCreated,@{Name="Service";Expression={$_.param4}},
@{Name="OriginalState";Expression = {$_.param2}},
@{Name="NewState";Expression={$_.param3}},Computername | Format-Table
```

| TimeCreated | Service | OriginalState | NewState | Computername |
|----------------------|------------------|---------------|--------------|--------------|
| 3/26/2025 9:03:23 AM | BITS | auto start | demand start | Prospero |
| 3/26/2025 9:01:20 AM | BITS | demand start | auto start | Prospero |
| 3/26/2025 9:00:32 AM | TrustedInstaller | auto start | demand start | Prospero |
| 3/26/2025 8:54:48 AM | BITS | auto start | demand start | Prospero |
| 3/26/2025 8:51:13 AM | BITS | demand start | auto start | Prospero |
| 3/26/2025 8:50:41 AM | WslInstaller | auto start | disabled | Prospero |
| 3/26/2025 5:09:35 AM | BITS | auto start | demand start | Prospero |
| 3/26/2025 5:07:35 AM | BITS | demand start | auto start | Prospero |
| 3/26/2025 4:34:26 AM | BITS | auto start | demand start | Prospero |
| 3/26/2025 4:31:49 AM | BITS | demand start | auto start | Prospero |

Once you know the type of data, you can customize the output or build a script around it.

Example 4

```
PS C:\> Get-WinEvent -FilterHashtable @{LogName = "Application";
ID=17137} -MaxEvents 1 | Convert-EventLogRecord
```

```
LogName      : Application
RecordType   : Information
TimeCreated  : 3/26/2025 9:04:02 AM
```

```
RecordID      : 17137
RawProperties  : {TickleEventDB}
Message       : Starting up database 'TickleEventDB'.
Keywords      : {Classic}
Source        : MSSQL$SQLEXPRESS
Computername  : Prospero
```

This record doesn't have structured extra data. The replacement strings are stored as text so the command displays the data using the RawProperties property.

Example 5

```
PS C:\> $all = New-PSSession -ComputerName 'win10','srv1','srv2','dom1'
PS C:\> $local = Get-Item Function:\Convert-EventLogRecord
PS C:\> Invoke-Command -ScriptBlock {
    New-item -Path Function: -Name $using:local.name -Value $using:local.ScriptBlock
} -Session $all
PS C:\> Invoke-Command {
    Get-WinEvent -FilterHashtable @{LogName='security';id=4624} -MaxEvents 10 |
    Convert-EventLogRecord |
    Select-Object -Property Computername,Time*,TargetUser*,
    TargetDomainName,Subject*} -session $all -HideComputerName |
    Select-Object -Property * -ExcludeProperty runspaceID
```

```
Computername      : WIN10.Company.Pri
TimeCreated       : 1/20/2025 5:21:17 PM
TargetUserSid     : S-1-5-18
TargetUserName    : SYSTEM
TargetDomainName  : NT AUTHORITY
SubjectUserSid    : S-1-5-18
SubjectUserName   : WIN10$
SubjectDomainName : COMPANY
SubjectLogonId    : 0x3e7
```

```
Computername      : WIN10.Company.Pri
TimeCreated       : 1/20/2025 5:18:51 PM
TargetUserSid     : S-1-5-18
TargetUserName    : SYSTEM
TargetDomainName  : NT AUTHORITY
SubjectUserSid    : S-1-5-18
SubjectUserName   : WIN10$
SubjectDomainName : COMPANY
SubjectLogonId    : 0x3e7
```

```
Computername      : WIN10.Company.Pri
TimeCreated       : 1/20/2025 5:16:07 PM
TargetUserSid     : S-1-5-21-278538743-3177530655-100218012-1105
TargetUserName    : ArtD
TargetDomainName  : COMPANY.PRI
SubjectUserSid    : S-1-0-0
SubjectUserName   : -
SubjectDomainName : -
SubjectLogonId    : 0x0
...
```

The first command creates PSSessions to several remote computers. The local copy of this command is created in the remote PSSessions. Then event log data is retrieved in the remote sessions and converted using the

Convert-EventlogRecord function in each session.

Parameters

-LogRecord

An event log record from the Get-WinEvent command.

```
Type: EventLogRecord[]
Parameter Sets: (All)
Aliases:

Required: True
Position: 1
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.Diagnostics.Eventing.Reader.EventLogRecord

Outputs

PSCustomObject

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-WinEvent

Convert-HashtableString

Synopsis

Convert a hashtable string into a hashtable object.

Syntax

```
Convert-HashtableString [-Text] <String> [<CommonParameters>]
```

Description

This function is similar to Import-PowerShellDataFile. But where that command can only process a file, this command will take any hashtable-formatted string and convert it into an actual hashtable.

Examples

Example 1

```
PS C:\> Get-Content c:\work\test.psd1 | Unprotect-CmsMessage | Convert-HashtableString
```

| Name | Value |
|--------------|--------------------------------|
| ---- | ----- |
| CreatedBy | BOVINE320\Jeff |
| CreatedAt | 10/02/2024 21:28:47 UTC |
| Computername | Think51 |
| Error | |
| Completed | True |
| Date | 10/02/2024 21:29:35 UTC |
| Scriptblock | restart-service spooler -force |
| CreatedOn | BOVINE320 |

The test.psd1 file is protected as a CMS Message. In this example, the contents are decoded as a string which is then in turn converted into an actual hashtable.

Parameters

-Text

Enter your hashtable string.

```
Type: String
Parameter Sets: (All)
Aliases:
Required: True
```

```
Position: 0
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

System.String

Outputs

hashtable

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Import-PowerShellDatafile](#)

[Convert-HashtableToCode](#)

Convert-HashtableToCode

Synopsis

Convert a hashtable to a string representation.

Syntax

psd1 (Default)

```
Convert-HashtableToCode [-Hashtable] <Hashtable> [-Indent <Int32>]  
[<CommonParameters>]
```

inline

```
Convert-HashtableToCode [-Hashtable] <Hashtable> [-Inline] [<CommonParameters>]
```

Description

Use this command to convert a hashtable into its text or string equivalent. It is assumed that any array values contain items of the same type. This command has not been tested with large or complex hashtables, so you might need to manually edit the output to meet your tastes or requirements.

Examples

Example 1

```
PS C:\> $h = @{Name="SRV1";Asset=123454;Location="Omaha"}  
PS C:\> Convert-HashtableToCode $h  
@{  
    Name = 'SRV1'  
    Asset = 123454  
    Location = 'Omaha'  
}
```

Convert a hashtable object to a string equivalent that you can copy into your script.

Example 2

```
PS C:\> Convert-HashtableToCode $h -inline  
@{Name = 'SRV1';Asset = 123454;Location = 'Omaha'}
```

Create an inline string version of the hashtable.

Parameters

-Hashtable

A hashtable to convert. It can be standard or ordered hashtable.

```
Type: Hashtable
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-Indent

Specify the number of tabs to indent. You shouldn't need to specify this parameter. It exists for situations where there are nested hashtables.

```
Type: Int32
Parameter Sets: psd1
Aliases: tab

Required: False
Position: Named
Default value: 1
Accept pipeline input: False
Accept wildcard characters: False
```

-Inline

Write the hashtable as an inline expression.

```
Type: SwitchParameter
Parameter Sets: inline
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```


CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.Collections.Hashtable

Outputs

System.String

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Convert-HashtableString](#)

Convert-HtmlToAnsi

Synopsis

Convert an HTML color code to ANSI.

Syntax

```
Convert-HtmlToAnsi [-HtmlCode] <String> [<CommonParameters>]
```

Description

This simple function is designed to convert an HTML color code like #ff5733 into an ANSI escape sequence. To use the resulting value you still need to construct an ANSI string with the escape character and the closing [0m.

Examples

Example 1

```
PS C:\> Convert-HtmlToAnsi "#ff5733"

[38;2;255;87;51m
```

Example 2

```
PS C:\> "Running processes: `e$(cha "#ff337d")$((Get-Process).count)`e[0m"

Running processes: 306
```

The number of processes will be displayed in color. This example is using the cha alias for Convert-HtmlToAnsi.

Parameters

-HtmlCode

Specify an HTML color code like #13A10E. You need to include the # character.

```
Type: String
Parameter Sets: (All)
Aliases: code

Required: True
Position: 0
Default value: None
```

```
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.String

Outputs

System.String

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

ConvertFrom-LexicalTimespan

Synopsis

Convert a lexical timespan into a PowerShell timespan.

Syntax

```
ConvertFrom-LexicalTimespan [-String] <String> [-AsString] [<CommonParameters>]
```

Description

When working with some XML data, such as that from scheduled tasks, time spans or durations are stored in a lexical format like P0DT0H0M47S. You can use this command to convert that value into a timespan object.

Examples

Example 1

```
PS C:\> ConvertFrom-LexicalTimespan P0DT0H0M47S
```

```
Days           : 0
Hours          : 0
Minutes        : 0
Seconds        : 47
Milliseconds    : 0
Ticks          : 470000000
TotalDays      : 0.000543981481481481
TotalHours     : 0.0130555555555556
TotalMinutes   : 0.783333333333333
TotalSeconds   : 47
TotalMilliseconds : 47000
```

Example 2

```
PS C:\> Get-ScheduledTask -TaskName DailyWatcher |
Select-Object TaskName,
@{Name="ExecutionLimit";Expression = `
{ ConvertFrom-LexicalTimespan $_.settings.ExecutionTimeLimit }}

TaskName      ExecutionLimit
-----
DailyWatcher  3.00:00:00
```

Parameters

-AsString

Format the timespan as a string

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-String

Enter a lexical time string like P23DT3H43M. This is case-sensitive.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.String

Outputs

String

Timespan

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[ConvertTo-LexicalTimespan](#)

ConvertFrom-Text

Synopsis

Convert structured text to objects.

Syntax

File (Default)

```
ConvertFrom-Text [-Pattern] <Regex> [-Path] <String> [-TypeName <String>]  
[-NoProgress] [<CommonParameters>]
```

InputObject

```
ConvertFrom-Text [-Pattern] <Regex> [-InputObject] <String>  
[-TypeName <String>] [-NoProgress] [<CommonParameters>]
```

Description

This command will take structured text such as from a log file and convert it to objects that you can use in the PowerShell pipeline. You can specify the path to a text file, or pipe content directly into this command. The piped content could even be output from command-line tools. You have to specify a regular expression pattern that uses named captures. The names will become property names in the custom objects.

The command will write a generic custom object to the pipeline. However, you can specify a custom type name. You might want to do this if you have your own format ps1xml file and want to handle formatting through that file.

Examples

Example 1

```
PS C:\> $b = "(?<Date>\d{2}-\d{2}-\d{4}\s\d{2}:\d{2}).*(?<Error>\d+),\s+(?<Step>.*):\s+(?<Action>\w+),\s+(?<Path>(\w+\\)*\w+\\.\\w+)"  
PS C:\> ConvertFrom-Text -pattern $b -Path C:\windows\DtcInstall.log  
  
Date : 10-18-2025 10:49  
Error : 0  
Step : CMsdtcUpgradePlugin::PostApply  
Action : Enter  
Path : com\complus\dtc\dtc\msdtcstp\msdtcplugin.cpp  
  
Date : 10-18-2025 10:49  
Error : 0  
Step : CMsdtcUpgradePlugin::PostApply  
Action : Exit  
Path : com\complus\dtc\dtc\msdtcstp\msdtcplugin.cpp  
...
```

The first command creates a variable to hold the regular expression pattern that defines named captures for content in the DtcInstall.log. The second line runs the command using the pattern and the log file.

Example 2

```
PS C:\> $wu = "(?<Date>\d{4}-\d{2}-\d{2})\s+(?<Time>(\d{2}:)+\d{3})\s+(?<PID>\d+)\s+(?<TID>\w+)\s+(?<Component>\w+)\s+(?<Message>.*)"
PS C:\> $out == ConvertFrom-Text -pattern $wu -Path C:\Windows\WindowsUpdate.log -NoProgress
PS C:\> $out | Group-Object Component | Sort-Object Count
```

| Count | Name | Group |
|-------|---------|---|
| 20 | DtaStor | {@{Date=2025-01-27; Time=07:19:19:584; PID=1... |
| 72 | Setup | {@{Date=2025-01-27; Time=07:19:05:868; PID=1... |
| 148 | SLS | {@{Date=2025-01-27; Time=07:19:05:086; PID=1... |
| 150 | PT | {@{Date=2025-01-27; Time=07:19:08:946; PID=1... |
| 209 | WuTask | {@{Date=2025-01-26; Time=20:05:28:483; PID=1... |
| 256 | EP | {@{Date=2025-01-26; Time=21:21:23:341; PID=1... |
| 263 | Handler | {@{Date=2025-01-27; Time=07:19:42:878; PID=3... |
| 837 | Report | {@{Date=2025-01-26; Time=21:21:23:157; PID=1... |
| 900 | IdleTmr | {@{Date=2025-01-26; Time=21:21:23:338; PID=1... |
| 903 | Service | {@{Date=2025-01-26; Time=20:05:29:104; PID=1... |
| 924 | Misc | {@{Date=2025-01-26; Time=21:21:23:033; PID=1... |
| 1062 | DnldMgr | {@{Date=2025-01-26; Time=21:21:23:159; PID=1... |
| 2544 | AU | {@{Date=2025-01-26; Time=19:55:27:449; PID=1... |
| 2839 | Agent | {@{Date=2025-01-26; Time=21:21:23:045; PID=1... |

```
PS C:\> $out |
Where-Object {[datetime]$_.date -ge [datetime]"2/10/2025" -AND $_.component -eq "AU"} |
Format-Table Date,Time,Message -wrap
```

| Date | Time | Message |
|------------|--------------|--|
| 2025-02-10 | 05:36:44:183 | ##### AU: Initializing Automatic Updates ##### |
| 2025-02-10 | 05:36:44:184 | Additional Service {117CAB2D-82B1-4B5A-A08C-4D62DBEE7782} with Approval type {Scheduled} added to AU services list |
| 2025-02-10 | 05:36:44:184 | AIR Mode is disabled |
| 2025-02-10 | 05:36:44:185 | # Approval type: Scheduled (User preference) |
| 2025-02-10 | 05:36:44:185 | # Auto-install minor updates: Yes (User preference) |
| 2025-02-10 | 05:36:44:185 | # ServiceTypeDefault: Service 117CAB2D-82B1-4B5A-A08C-4D62DBEE7782 Approval type: (Scheduled) |
| 2025-02-10 | 05:36:44:185 | # Will interact with non-admins (Non-admins are elevated (User preference)) |
| 2025-02-10 | 05:36:44:204 | WARNING: Failed to get Wu Exemption info from NLN, assuming not exempt, error = 0x80070490 |
| 2025-02-10 | 05:36:44:213 | AU finished delayed initialization |
| 2025-02-10 | 05:38:01:000 | ##### |
| ... | | |

In this example, the WindowsUpdate log is converted from text to objects using the regular expression pattern. Given the size of the log file this process can take some time to complete so the progress bar is turned off to improve performance.

Example 3

```
PS C:\> Get-Content c:\windows\windowsupdate.log -totalcount 50 |
ConvertFrom-Text $wu
```

This example gets the first 50 lines from the Windows update log and converts that to objects using the pattern from the previous example.

Example 4

```
PS C:\> $c = "(?<Protocol>\w{3})\s+(?<LocalIP>(\d{1,3}\.){3}\d{1,3}):(?<LocalPort>\d+)\s+(?<ForeignIP>.*):(?<ForeignPort>\d+)\s+(?<State>\w+)"
PS C:\> netstat | select -skip 4 | ConvertFrom-Text $c |
Format-Table -AutoSize
```

| Protocol | LocalIP | LocalPort | ForeignIP | ForeignPort | State |
|----------|--------------|-----------|----------------|-------------|-------------|
| TCP | 127.0.0.1 | 19872 | Novo8 | 50835 | ESTABLISHED |
| TCP | 127.0.0.1 | 50440 | Novo8 | 50441 | ESTABLISHED |
| TCP | 127.0.0.1 | 50441 | Novo8 | 50440 | ESTABLISHED |
| TCP | 127.0.0.1 | 50445 | Novo8 | 50446 | ESTABLISHED |
| TCP | 127.0.0.1 | 50446 | Novo8 | 50445 | ESTABLISHED |
| TCP | 127.0.0.1 | 50835 | Novo8 | 19872 | ESTABLISHED |
| TCP | 192.168.6.98 | 50753 | 74.125.129.125 | 5222 | ESTABLISHED |

The first command creates a variable to be used with output from the Netstat command which is used in the second command.

Example 5

```
PS C:\> $arp = "(?<IPAddress>(\d{1,3}\.){3}\d{1,3})\s+(?<MAC>(\w{2}-){5}\w{2})\s+(?<Type>\w+)"
PS C:\> arp -g -N 172.16.10.22 | Select-Object -skip 3 |
ForEach-Object {$_.Trim()} |
ConvertFrom-Text $arp -NoProgress -typename arpData
```

| IPAddress | MAC | Type |
|---------------|-------------------|---------|
| 172.16.10.1 | 00-13-d3-66-50-4b | dynamic |
| 172.16.10.100 | 00-0d-a2-01-07-5d | dynamic |
| 172.16.10.101 | 2c-76-8a-3d-11-30 | dynamic |
| 172.16.10.121 | 00-0e-58-ce-8b-b6 | dynamic |
| 172.16.10.122 | 1c-ab-a7-99-9a-e4 | dynamic |
| 172.16.10.124 | 00-1e-2a-d9-cd-b6 | dynamic |
| 172.16.10.126 | 00-0e-58-8c-13-ac | dynamic |
| 172.16.10.128 | 70-11-24-51-84-60 | dynamic |
| ... | | |

The first command creates a regular expression for the ARP command. The second prompt shows the ARP command being used to select the content, trimming each line, and then converting the output to text using the regular expression named pattern. This example also defines a custom type name for the output.

Parameters

-InputObject

Any text that you want to pipe into this command. It can be a certain number of lines from a large text or log file. Or the output of a command line tool. Be sure to filter out blank lines.

```
Type: String
Parameter Sets: InputObject
Aliases:

Required: True
Position: 1
```

```
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-NoProgress

By default this command will display a progress bar to inform the user on the status. For large data sets this can impact performance. Use this parameter to suppress the progress messages.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

-Path

The filename and path to the text or log file.

```
Type: String
Parameter Sets: File
Aliases: file

Required: True
Position: 1
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Pattern

A regular expression pattern that uses named captures. This parameter has an aliases of regex and rx.

```
Type: Regex
Parameter Sets: (All)
Aliases: regex, rx

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-TypeName

Enter an optional typename for the object output. If you don't use one, the command will write a generic

custom object to the pipeline.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.String

Outputs

PSCustomObject

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-Content

About_Regular_Expressions

ConvertFrom-UTCTime

Synopsis

Convert a datetime value from universal.

Syntax

```
ConvertFrom-UTCTime [-DateTime] <DateTime> [<CommonParameters>]
```

Description

Use this command to convert a universal datetime object into local time.

This command was introduced in v2.3.0.

Examples

Example 1

```
PS C:\> ConvertFrom-UTCTime "18:00"  
  
Monday, March 4, 2020 1:00:00 PM
```

Covert the time 18:00 for the current day from universal time to local time. This result reflects Eastern Time which on this date is UTC-5.

Parameters

-DateTime

Enter a Universal Datetime value

```
Type: DateTime  
Parameter Sets: (All)  
Aliases:  
  
Required: True  
Position: 0  
Default value: None  
Accept pipeline input: True (ByValue)  
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

System.DateTime

Outputs

System.DateTime

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[ConvertTo-UTCTime](#)

[Get-Date](#)

ConvertTo-Hashtable

Synopsis

Convert an object into a hashtable.

Syntax

```
ConvertTo-Hashtable [-InputObject] <Object> [-NoEmpty] [-Exclude <String[]>]
[-Alphabetical] [<CommonParameters>]
```

Description

This command will take an object and create a hashtable based on its properties. You can have the hashtable exclude some properties as well as properties that have no value.

Examples

Example 1

```
PS C:\> Get-Process -id $pid |
Select-Object name,id,handles,WorkingSet |
ConvertTo-Hashtable

Name                Value
----                -
WorkingSet          418377728
Name                powershell_ise
Id                  3456
Handles             958
```

Example 2

```
PS C:\> $hash = Get-Service spooler |
ConvertTo-Hashtable -Exclude CanStop,CanPauseAndContinue -NoEmpty
PS C:\> $hash

Name                Value
----                -
ServiceType         Win32OwnProcess, InteractiveProcess
ServiceName         spooler
ServiceHandle       SafeServiceHandle
DependentServices   {Fax}
ServicesDependedOn  {RPCSS, http}
Name                spooler
Status              Running
MachineName         .
RequiredServices    {RPCSS, http}
```

```
DisplayName          Print Spooler
```

This created a hashtable from the Spooler service object, skipping empty properties and excluding CanStop and CanPauseAndContinue.

Example 3

```
PS C:\> Get-Service bits |  
Select-Object Name,DisplayName,Status,  
@{Name="Computername";Expression={$_.MachineName}} |  
ConvertTo-Hashtable -Alphabetical  
  
Name          Value  
----          -  
Computername  .  
DisplayName    Background Intelligent Transfer Service  
Name          bits  
Status        Running
```

Convert an object to a hashtable and order the properties alphabetically.

Parameters

-InputObject

A PowerShell object to convert to a hashtable.

```
Type: Object  
Parameter Sets: (All)  
Aliases:  
  
Required: True  
Position: 1  
Default value: None  
Accept pipeline input: True (ByValue)  
Accept wildcard characters: False
```

-NoEmpty

Do not include object properties that have no value.

```
Type: SwitchParameter  
Parameter Sets: (All)  
Aliases:  
  
Required: False  
Position: Named  
Default value: False  
Accept pipeline input: False  
Accept wildcard characters: False
```

-Exclude

An array of property names to exclude from the hashtable.

```
Type: String[]
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Alphabetical

Create a hashtable with property names arranged alphabetically.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

System.Object

Outputs

System.Collections.Specialized.OrderedDictionary

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

This was originally described at: <http://jdhitsolutions.com/blog/2013/01/convert-powershell-object-to->

hashtable-revised

Related Links

About_Hash_Tables

Get-Member

ConvertTo-LexicalTimespan

Synopsis

Convert a timespan to lexical time.

Syntax

```
ConvertTo-LexicalTimespan [-Timespan] <TimeSpan> [<CommonParameters>]
```

Description

Convert a timespan into a lexical version that you can insert into an XML document.

Examples

Example 1

```
PS C:\> ConvertTo-LexicalTimespan (New-Timespan -Days 7)

P7D
```

You can insert this value into an XML document where you need to represent a time-span.

Parameters

-Timespan

Enter a timespan object

```
Type: TimeSpan
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and

-WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.TimeSpan

Outputs

String

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[ConvertFrom-LexicalTimespan](#)

ConvertTo-LocalTime

Synopsis

Convert a foreign time to local.

Syntax

```
ConvertTo-LocalTime [-Datetime] <DateTime> [-UTCOffset] <TimeSpan>  
[-DaylightSavingTime] [<CommonParameters>]
```

Description

It can be tricky sometimes to see a time in a foreign location and try to figure out what that time is locally. This command attempts to simplify this process. In addition to the remote time, you need the base UTC offset for the remote location. You can use `Get-Timezone` or `Get-TZData` to help. See examples.

The parameter for `DaylightSavingTime` is to indicate that the remote location is observing DST. You can use this with the location's standard UTC offset, or you can specify an offset that takes DST into account.

Examples

Example 1

```
PS C:\> ConvertTo-LocalTime "3/15/2025 7:00AM" 8:00:00  
  
Friday, March 14, 2025 7:00:00 PM
```

Convert a time that is in Singapore to local (Eastern) time.

Example 2

```
PS C:\> Get-TimeZone -ListAvailable | where-object id -match hawaii  
  
Id                : Hawaiian Standard Time  
DisplayName        : (UTC-10:00) Hawaii  
StandardName       : Hawaiian Standard Time  
DaylightName       : Hawaiian Daylight Time  
BaseUtcOffset      : -10:00:00  
SupportsDaylightSavingTime : False  
  
PS C:\> ConvertTo-LocalTime "10:00AM" -10:00:00  
  
Friday, March 14, 2025 4:00:00 PM
```

In this example, the user is first determining the UTC offset for Hawaii. Then 10:00AM in Honolulu, is converted to local time which in this example is in the Eastern Time zone.

Parameters

-Datetime

Enter a non-local date time

```
Type: DateTime
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-UTCOffset

Enter the location's' UTC Offset. You can use Get-Timezone to discover it.

```
Type: TimeSpan
Parameter Sets: (All)
Aliases: offset

Required: True
Position: 1
Default value: None
Accept pipeline input: True (ByPropertyName)
Accept wildcard characters: False
```

-DaylightSavingTime

Indicate that the foreign location is using Daylight Saving Time

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: dst

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

None

Outputs

DateTime

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-TimeZone

Get-Date

[Get-MyTimeInfo](#)

[Get-TZList](#)

[ConvertFrom-UTCTime](#)

[ConvertTo-UTCTime](#)

ConvertTo-Markdown

Synopsis

Convert pipeline output to a markdown document.

Syntax

text (Default)

```
ConvertTo-Markdown [[-InputObject] <Object>] [-Title <String>]  
[-PreContent <String[]>] [-PostContent <String[]>] [-Width <Int32>] [<CommonParameters>]
```

table

```
ConvertTo-Markdown [[-InputObject] <Object>] [-Title <String>] [-PreContent <String[]>] [-PostContent <String[]>] [-AsTable] [<CommonParameters>]
```

list

```
ConvertTo-Markdown [[-InputObject] <Object>] [-Title <String>] [-PreContent <String[]>] [-PostContent <String[]>] [-AsList] [<CommonParameters>]
```

Description

This command is designed to accept pipelined output and create a generic markdown document. The pipeline output will be formatted as a text block or you can specify a table. The AsList parameter technically still creates a table, but it is two columns with the property name and value.

You can optionally define a title, content to appear before the output, and content to appear after the output. Best efforts have been made to produce markdown output that meets basic standards.

The command does not create a text file. You need to pipe results from this command to a cmdlet like Out-File or Set-Content. See examples.

Examples

Example 1

```
PS C:\> Get-Service Bits,Winrm |  
ConvertTo-Markdown -title "Service Check" -PreContent "## $($env:computername)"`  
-PostContent "_report $(Get-Date)_" | Out-File c:\work\svc.md
```

Create markdown output from a Get-Service command and save the output to a file.

Example 2

```
PS C:\> $computers = "srv1","srv2","srv4"
PS C:\> $Title = "System Report"
PS C:\> $Footer = "_report run by $($env:USERDOMAIN)\$($env:USERNAME)_"
PS C:\> $sb = {
$os = Get-CimInstance -ClassName Win32_OperatingSystem -property caption,
LastBootUpTime
[PSCustomObject]@{
PSVersion = $PSVersionTable.PSVersion
OS = $os.caption
Uptime = (Get-Date) - $os.LastBootUpTime
SizeFreeGB = (Get-Volume -DriveLetter C).SizeRemaining /1GB
}
}
PS C:\> $out == ConvertTo-Markdown -title $Title
PS C:\> foreach ($computer in $computers) {
$out+= Invoke-command -ScriptBlock $sb -Computer $computer -HideComputerName |
Select-Object -Property * -ExcludeProperty RunspaceID |
ConvertTo-Markdown -PreContent "## $($computer.ToUpper())"
}
PS C:\> $out += ConvertTo-Markdown -PostContent $Footer
PS C:\> $out | Set-Content c:\work\report.md
```

Here is an example that creates a series of markdown fragments for each computer and in the end creates a markdown document. The commands are shown at a PowerShell prompt, but you are likely to put them in a PowerShell script file.

Example 3

```
PS C:\> Get-WindowsVersion | ConvertTo-Markdown -title "OS Summary" -PreContent "## $($env:computername)" -AsList
# OS Summary
## THINKX1-JH

Property	Value
ProductName	Microsoft Windows 11 Pro
ReleaseVersion	23H2
EditionID	Professional
ReleaseID	2009
Build	22631.2191
Branch	ni_release
InstalledUTC	5/17/2022 6:54:52 PM
Computername	THINKX1-JH
```

Create a "list" table with output from the Get-WindowsVersion command.

Example 4

```
PS C:\> Get-Service | Sort-Object -property DisplayName |
Foreach-Object -begin {
    "# Service Status`n"
} -process {
    -----
```



```
$name = $_.DisplayName
$_ | Select-Object -property Name,StartType,Status,
@{Name="RequiredServices";Expression = {$_.RequiredServices.name -join ','}} |
ConvertTo-Markdown -asList -PreContent "## $Name"
} -end {
    "### $($env:computername) $(Get-Date)"
} | Out-File c:\work\services.md
```

The example will create a markdown file with a title of Service Status. Each service will be converted to a markdown list with the DisplayName as pre-content.

Parameters

-InputObject

Typically the results of a PowerShell command or expression.

```
Type: Object
Parameter Sets: (All)
Aliases:

Required: False
Position: 1
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-Title

Specify a top-level title. You do not need to include any markdown. It will automatically be formatted with a H1 tag.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-PreContent

Enter whatever content you want to appear before converted input. You can use whatever markdown you wish.

```
Type: String[]
Parameter Sets: (All)
Aliases:

Required: False
```

```
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-PostContent

Enter whatever content you want to appear after converted input. You can use whatever markdown you wish.

```
Type: String[]
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Width

Specify the document width. Depending on what you intend to do with the markdown from this command you may want to adjust this value.

```
Type: Int32
Parameter Sets: text
Aliases:

Required: False
Position: Named
Default value: 80
Accept pipeline input: False
Accept wildcard characters: False
```

-AsTable

Format the incoming data as a markdown table. This works best with similar content such as the result of running a PowerShell command.

```
Type: SwitchParameter
Parameter Sets: table
Aliases: table

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-AsList

Display results as a 2 column markdown table. The first column will be the property name with the value formatted as a string in the second column.

```
Type: SwitchParameter
Parameter Sets: list
Aliases: list

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.Object

Outputs

System.String

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/blog/essential-powershell-resources/>

Related Links

ConvertTo-HTML

Out-File

ConvertTo-TitleCase

Synopsis

Convert a string to title case.

Syntax

```
ConvertTo-TitleCase [-Text] <String> [<CommonParameters>]
```

Description

This command is a simple function to convert a string to title or proper case.

Examples

Example 1

```
PS C:\> ConvertTo-TitleCase "working summary"

Working Summary
```

Example 2

```
PS C:\> "art deco","jack frost","al fresco" | ConvertTo-TitleCase

Art Deco
Jack Frost
Al Fresco
```

Parameters

-Text

Text to convert to title case.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByValue)
```

```
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.String

Outputs

System.String

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

ConvertTo-UTCTime

Synopsis

Convert a local datetime to universal time.

Syntax

```
ConvertTo-UTCTime [[-DateTime] <DateTime>] [-AsString] [<CommonParameters>]
```

Description

Convert a local datetime to universal time. The default is now but you can specify a datetime value. You also have an option to format the result as a sortable string.

This command was introduced in v2.3.0.

Examples

Example 1

```
PS C:\> Get-Date

Wednesday, March 26, 2025 11:01:57 AM

PS C:\> ConvertTo-UTCTime

Wednesday, March 26, 2025 3:02:13 PM
```

Example 2

```
PS C:\> ConvertTo-UTCTime -asString
2025-03-26 15:02:29Z
```

Parameters

-DateTime

Enter a Datetime value

```
Type: DateTime
Parameter Sets: (All)
Aliases:
```

```
Required: False
Position: 0
Default value: now
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-AsString

Convert the date-time value to a sortable string. This is the same thing as running a command like "{0:u}" -f (Get-Date).ToUniversalTime()

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.DateTime

Outputs

System.DateTime

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

ConvertFrom-UTCTime

Get-Date

ConvertTo-WPFGrid

Synopsis

Send command output to an interactive WPF-based grid.

Syntax

input (Default)

```
ConvertTo-WPFGrid [[-Title] <String>] [[-Timeout] <Int32>] [-Refresh]
[-GridLines <String>] [-InitializationScript <ScriptBlock>]
[-UseLocalVariable <String[]>] [-UseProfile] [<CommonParameters>]
```

Input

```
ConvertTo-WPFGrid [-InputObject] <PSObject> [[-Title] <String>]
[[ -Timeout] <Int32>] [-Refresh] [-GridLines <String>]
[-InitializationScript <ScriptBlock>] [-UseLocalVariable <String[]>]
[-UseProfile] [<CommonParameters>]
```

scriptblock

```
ConvertTo-WPFGrid [-Scriptblock <ScriptBlock>] [[-Title] <String>]
[[ -Timeout] <Int32>] [-Refresh] [-GridLines <String>]
[-InitializationScript <ScriptBlock>] [-UseLocalVariable <String[]>]
[-UseProfile] [<CommonParameters>]
```

Description

This command is an alternative to Out-GridView. It works much the same way. Run a PowerShell command and pipe it to this command. The output will be displayed in an auto-sized data grid. You can click on column headings to sort. You can resize columns and you can re-order columns. You will want to be selective about which properties you pipe through to this command. See examples.

You can specify a timeout value which will automatically close the form. If you specify a timeout and the Refresh parameter, then the contents of the datagrid will automatically refreshed using the timeout value as an integer. This will only work when you pipe a PowerShell expression to ConvertTo-WPFGrid as one command. This will fail if you break the command in the PowerShell ISE or use a nested prompt. Beginning with v2.4.0 the form now has a Refresh button which will automatically refresh the datagrid. You should set a refresh interval that is greater than the time it takes to complete the command.

Because the grid is running in a new background runspace, it does not automatically inherit anything from your current session. However, you can use the -UserProfile parameter which will load your user profile scripts into the runspace. You can specify a list of locally defined variables to be used in the form. Use the variable

name without the \$. Finally, you can also use the `-InitializationScript` parameter and specify a scriptblock of PowerShell code to initialize the runspace. This is helpful when you need to dot source external scripts or import modules not in your module path.

This command runs the WPF grid in a new runspace so your PowerShell prompt will not be blocked. However, after closing the form you may be left with the runspace. You can use `Remove-Runspace` to clean up or wait until you restart PowerShell.

This command requires a Windows platform.

Examples

Example 1

```
PS C:\> Get-Process | Sort-Object WS -Descending |  
Select-object -first 20 ID,Name,WS,VM,PM,Handles,StartTime |  
ConvertTo-WPFGrid -Refresh -timeout 20 -Title "Top Processes"
```

Get the top 20 processes based on the value of the `WorkingSet` property and display selected properties in the WPF Grid. The contents will automatically refresh every 20 seconds. You will need to manually close the form.

Example 2

```
PS C:\> $vmhost = "CHI-HVR2"  
PS C:\> Get-VM -computername $VMHost | Select Name,State,Uptime,  
@{Name="AssignedMB";Expression={$_.MemoryAssigned/1mb -as [int]}},  
@{Name="DemandMB";Expression={$_.MemoryDemand/1mb -as [int]}} |  
ConvertTo-WPFGrid -title "VM Report $VMHost" -timeout 30 -refresh  
-UseLocalVariable VMHost
```

Get Hyper-V virtual machine information and refresh every 30 seconds. Because the command is using a locally defined variable it is also being used in the form. Note that this would be written as one long pipelined expression. It is formatted here for the sake of the help documentation.

Example 3

```
PS C:\> Get-VMData -host CHI-HVR2 |  
ConvertTo-WPFGrid -title "VM Data" -refresh -timeout 60 -UseProfile
```

This example uses a hypothetical command that might be defined in a PowerShell profile script. `ConvertTo-WPFGrid` will load the profile scripts so that the data can be updated every 60 seconds.

Example 4

```
PS C:\> (Get-ProcessData -Computername $computers).where({$_.WorkingSet -ge 100mb}) |  
ConvertTo-WPFGrid -Title "Process Report" -UseLocalVariable computers -InitializationScript { . C:\scripts\Get-ProcessData.ps1 } -Refresh -Timeout 30
```

This command runs a function that is defined in a script file. In order for the form to refresh, it must also dot source the script which is happening with the InitializationScript parameter. The example is also loading the local \$computers variable so that it too is available upon refresh.

Parameters

-InputObject

Typically the results of a PowerShell command or expression. You should select the specific properties you wish to display.

```
Type: PSObject
Parameter Sets: Input
Aliases:

Required: False
Position: 1
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-Title

Specify a title for your form.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 2
Default value: ConvertTo-WPFGrid
Accept pipeline input: False
Accept wildcard characters: False
```

-Timeout

By default, the grid will remain displayed until you manually close it. But you can specify a timeout interval in seconds. The minimum accepted value is 5 seconds. If you use this parameter with -Refresh, then the datagrid will be refreshed with results of the PowerShell expression you piped to ConvertTo-WPFGrid.

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: False
Position: 3
Default value: 0
Accept pipeline input: False
Accept wildcard characters: False
```

-Refresh

If you specify this parameter and a Timeout value, this command will refresh the datagrid with the PowerShell expression piped into ConvertTo-WPFGrid. You should use a value that is longer than the time it takes to complete the command that generates your data.

This parameter will only work if you are using ConvertTo-WPFGrid at the end of a pipelined expression. See examples.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-UseProfile

Load your PowerShell profiles into the background runspace.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: profile

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Scriptblock

Enter a scriptblock that will generate data to be populated in the form

```
Type: ScriptBlock
Parameter Sets: scriptblock
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-UseLocalVariable

Load locally defined variables into the background runspace

```
Type: String[]
Parameter Sets: (All)
Aliases: var

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-InitializationScript

Run this scriptblock to initialize the background runspace. You might need to dot source a script file or load a non-standard module.

```
Type: ScriptBlock
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-GridLines

Control how grid lines are displayed in the form. You may not want to have any or perhaps only vertical or horizontal lines.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

System.Object

Outputs

None

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Out-GridView

ConvertTo-HTML

[ConvertTo-Markdown](#)

Copy-Command

Synopsis

Copy a PowerShell command.

Syntax

```
Copy-Command [-Command] <String> [[-NewName] <String>] [-IncludeDynamic]  
[-AsProxy] [-UseForwardHelp] [<CommonParameters>]
```

Description

This command will copy a PowerShell command, including parameters and help to a new user-specified command. You can use this to create a "wrapper" function or to easily create a proxy function. The default behavior is to create a copy of the command complete with the original comment-based help block.

For best results, run this in the PowerShell ISE or Visual Studio code, the copied command will be opened in a new tab or file.

Examples

Example 1

```
PS C:\> Copy-Command Get-Process Get-MyProcess
```

Create a copy of Get-Process called Get-MyProcess.

Example 2

```
PS C:\> Copy-Command Get-Eventlog -AsProxy -UseForwardHelp
```

Create a proxy function for Get-Eventlog and use forwarded help links.

Example 3

```
PS C:\> Copy-Command Get-ADComputer Get-MyADComputer -IncludeDynamic
```

Create a wrapper function for Get-ADComputer called Get-MyADComputer. Due to the way the Active Directory cmdlets are written, most parameters appear to be dynamic so you need to include dynamic parameters otherwise there will be no parameters in the final function.

Parameters

-Command

The name of a PowerShell command, preferably a cmdlet but that is not a requirement. You can specify an alias and it will be resolved.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 1
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-NewName

Specify a name for your copy of the command. If no new name is specified, the original name will be used.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 2
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-IncludeDynamic

The command will only copy explicitly defined parameters unless you specify to include any dynamic parameters as well. If you copy a command and it seems to be missing parameters, re-copy and include dynamic parameters.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

-AsProxy

Create a traditional proxy function.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

-UseForwardHelp

By default the copy process will create a comment-based help block with the original command's help which you can then edit to meet your requirements. Or you can opt to retain the forwarded help links to the original command.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

None

Outputs

System.String

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-Command

Copy-HelpExample

Synopsis

Copy code snippet from help examples.

Syntax

```
Copy-HelpExample [-Name] <String> [-Path <String>] [-UseGridView]
[<CommonParameters>]
```

Description

This command is intended to make it easier to copy code snippets from help examples to the clipboard. You can select one or more examples which have been trimmed of comments, blank lines and most prompts. Some code examples contain the output or have several lines of code. You will need to manually delete what you don't want. If this command is run on a Windows system you have a dynamic parameter to use Out-GridView to display your choices. When prompted enter a comma-separated list of the examples you wish to copy. Otherwise, the command will display a console-based menu. Note that if you are using the PowerShell ISE you will be forced to use Out-GridView.

Examples

Example 1

```
PS C:\> Copy-HelpExample -Name Stop-Process

Code Samples

Each help example is numbered to the left. At the prompt below, select the code samples you want to copy to the clipboard. Separate multiple values with a comma.

Some example code includes the output.

[1] Example 1: Stop all instances of a process

    Stop-Process -Name "notepad"

[2] Example 2: Stop a specific instance of a process

    Stop-Process -Id 3952 -Confirm -PassThru
Confirm
Are you sure you want to perform this action?
Performing operation "Stop-Process" on Target "notepad (3952)".
[Y] Yes  [A] Yes to All  [N] No  [L] No to All  [S] Suspend  [?] Help
(default is "Y"):y
Handles      NPM(K)      PM(K)      WS(K) VM(M)      CPU(s)      Id ProcessName
-----
41           2         996       3212    31         3952 notepad

[3] Example 3: Stop a process and detect that it has stopped

    calc
    $p = Get-Process -Name "calc"
    Stop-Process -InputObject $p
    Get-Process | Where-Object {$_.HasExited}

[4] Example 4: Stop a process not owned by the current user
```

```
Get-Process -Name "lsass" | Stop-Process

Stop-Process : Cannot stop process 'lsass (596)' because of the following error
: Access is denied
At line:1 char:34
+ Get-Process -Name "lsass" | Stop-Process <<<<

[ADMIN]: Get-Process -Name "lsass" | Stop-Process

Warning!
Are you sure you want to perform this action?
Performing operation 'Stop-Process' on Target 'lsass(596)'
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"):
[ADMIN]: Get-Process -Name "lsass" | Stop-Process -Force
[ADMIN]:

Please select items to copy to the clipboard by number. Separate multiple entries with a comma. Press Enter alone to cancel:
```

The console menu will be displayed using ANSI. Enter a comma separated list of numbers for the items to copy to the clipboard.

Parameters

-Name

Enter the name of the PowerShell command.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Path

Gets help that explains how the cmdlet works in the specified provider path. Enter a PowerShell provider path.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-UseGridView

Select help examples using Out-GridView. This parameter is only available on Windows systems. The parameter has an alias of 'ogv'.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: ogv

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

None

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-Help

Copy-HistoryCommand

Synopsis

Copy a history command line to the clipboard.

Syntax

```
Copy-HistoryCommand [[-ID] <Int32[]>] [-PassThru] [-WhatIf] [-Confirm] [<CommonParameters>]
```

Description

You can use this command to copy the command line from a given PowerShell history item to the clipboard. The default item will be the last history item. Once copied, you can paste into your following prompt to edit and/or re-run.

Linux platforms require the xclip utility to be in the path.

Lee Holmes has a similar function called Copy-History in the PowerShell Cookbook that lets you copy a range of history commands to the clipboard.

Examples

Example 1

```
PS C:\> Copy-HistoryCommand
```

Copy the last command to the clipboard.

Example 2

```
PS C:\> Copy-HistoryCommand 25 -PassThru  
Get-Process -computername $computer | Sort-Object ws -Descending |  
Select-Object -first 3
```

Copy the command from history item 25 to the clipboard and also pass it to the pipeline.

Example 3

```
PS C:\> Copy-HistoryCommand (100..110)
```

Copy history items 100 through 110 to the clipboard.

Example 4

```
PS C:\> $c = [scriptblock]::Create($(Copy-HistoryCommand 25 -PassThru))
PS C:\> &$c
```

| Handles | NPM(K) | PM(K) | WS(K) | VM(M) | CPU(s) | Id | SI | ProcessName |
|---------|--------|--------|--------|-------|--------|------|----|---------------|
| 10414 | 12744 | 488164 | 461596 | ...76 | | 3128 | 0 | dns |
| 581 | 67 | 171868 | 141620 | ...82 | | 3104 | 0 | MsMpEng |
| 678 | 48 | 118132 | 89572 | 840 | | 7180 | 0 | ServerManager |

This copies the command from history item 25 and turns it into a scriptblock.

Parameters

-Confirm

Prompts you for confirmation before running the cmdlet.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: cf

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-ID

The history ID number. The default is the last command.

```
Type: Int32[]
Parameter Sets: (All)
Aliases:

Required: False
Position: 0
Default value: $(Get-History).Count
Accept pipeline input: False
Accept wildcard characters: False
```

-PassThru

Use this parameter if you also want to see the command as well as copy it to the clipboard.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:
```

```
Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

-WhatIf

Shows what would happen if the cmdlet runs. The cmdlet is not run.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: wi

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

Int

Outputs

None

System.String

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-History

Set-Clipboard

Out-Copy

Copy-PSFunction

Synopsis

Copy a local PowerShell function to a remote session.

Syntax

```
Copy-PSFunction [-Name] <String[]> -Session <PSSession> [-Force]  
[<CommonParameters>]
```

Description

This command is designed to solve the problem when you want to run a function loaded locally on a remote computer. Copy-PSFunction will copy a PowerShell function that is loaded in your current PowerShell session to a remote PowerShell session. The remote session must already be created. The copied function only exists remotely for the duration of the remote PowerShell session.

If the function relies on external or additional files, you will have to copy them to the remote session separately.

Examples

Example 1

```
PS C:\> "Get-LastBoot","Get-DiskFree" | Copy-PSFunction -session $S
```

Copy the local functions Get-LastBoot and Get-DiskFree to a previously created PSSession saved as \$S. You could then run the function remotely using Invoke-Command.

Parameters

-Force

Overwrite an existing function with the same name. The default behavior is to skip existing functions.

```
Type: SwitchParameter  
Parameter Sets: (All)  
Aliases:  
  
Required: False  
Position: Named  
Default value: None  
Accept pipeline input: False  
Accept wildcard characters: False
```

-Name

Enter the name of a local function.

```
Type: String[]
Parameter Sets: (All)
Aliases:

Required: True
Position: 1
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-Session

Specify an existing PSSession.

```
Type: PSSession
Parameter Sets: (All)
Aliases:

Required: True
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.String[]

Outputs

Deserialized.System.Management.Automation.FunctionInfo

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Copy-Item

Export-PSAnsiFileMap

Synopsis

Export a PSAnsiFileMap to a file.

Syntax

```
Export-PSAnsiFileMap [-PassThru] [-WhatIf] [-Confirm] [<CommonParameters>]
```

Description

The PSScriptTools module includes a JSON file that is automatically imported as the global PSAnsiFileMap variable. This variable is used for the custom ANSI formatted table view, among other module commands. If you wish to customize the file map, you can use the Set-PSAnsiFileMap command. These changes are not permanent and will be overwritten the next time you import the PSScriptTools module. To use your customized settings, you need to export your modified \$PSAnsiFileMap object with this command.

The command will export the settings to a JSON file called psansifilemap.json in the root of \$HOME. The next time you import the PSScriptTools module, it will use this file if found. To revert to the default file map either rename or delete the file in \$HOME.

Examples

Example 1

```
PS C:\>Export-PSAnsiFileMap -PassThru
```

```
Directory: C:\Users\Jeff
```

| Mode | LastWriteTime | Length | Name |
|-------|--------------------|--------|--------------------|
| ---- | ----- | ----- | ---- |
| -a--- | 12/28/2024 1:02 PM | 1631 | psansifilemap.json |

Parameters

-Confirm

Prompts you for confirmation before running the cmdlet.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: cf

Required: False
Position: Named
```

```
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-PassThru

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-WhatIf

Shows what would happen if the cmdlet runs. The cmdlet is not run.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: wi

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

None

System.IO.FileInfo

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Get-PSAnsiFileMap](#)

[Set-PSAnsiFileMap](#)

Find-CimClass

Synopsis

Search CIM for a class.

Syntax

```
Find-CimClass [-ClassName] <String> [-Exclude <String>] [-CimSession <CimSession>] [<CommonParameters>]
```

Description

This function is designed to search an entire CIM repository for a class name. Sometimes, you can guess a CIM/WMI class name but not know the full name or even the correct namespace. Find-CimClass will recursively search for a given class name in all namespaces. You can use wildcards and search remote computers.

This command requires a Windows platform.

Examples

Example 1

```
PS C:\> Find-CimClass -ClassName *protection*

NameSpace: Root/CIMV2/mdm/dmmap

CimClassName          CimClassMethods      CimClassProperties
-----
MDM_AppLocker_EnterpriseDataProt... {}                    {InstanceID, Parent...
MDM_AppLocker_EnterpriseDataProt... {}                    {InstanceID, Parent...
MDM_EnterpriseDataProtection        {}                    {InstanceID, Parent...
MDM_EnterpriseDataProtection_Set... {}                    {AllowAzureRMSForED...
MDM_Policy_Config01_DataProtecti... {}                    {AllowDirectMemoryA...
MDM_Policy_Result01_DataProtecti... {}                    {AllowDirectMemoryA...
MDM_Reporting_EnterpriseDataProt... {}                    {InstanceID, LogCou...
MDM_Reporting_EnterpriseDataProt... {}                    {InstanceID, Logs, ...
MDM_WindowsAdvancedThreatProtection {}                    {InstanceID, Offboa...
MDM_WindowsAdvancedThreatProtect... {}                    {GroupIds, Instance...
MDM_WindowsAdvancedThreatProtect... {}                    {Criticality, Grou ...
MDM_WindowsAdvancedThreatProtect... {}                    {InstanceID, LastCo...

NameSpace: Root/Microsoft/SecurityClient

CimClassName          CimClassMethods      CimClassProperties
-----
ProtectionTechnologyStatus {}                    {PackedXml, SchemaV...
...
```

Example 2

```
PS C:\> Find-CimClass -ClassName *volume* -Exclude "win32_Perf"
```

Search for any class with 'volume' in the name but exclude anything that starts with 'win32_Perf'.

Parameters

-ClassName

Enter the name of a CIM/WMI class. Wildcards are permitted.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: True
```

-Exclude

Enter a pattern for class names to EXCLUDE from the results. You can use wildcards or regular expressions.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: True
```

-CimSession

Specify a computer name or an existing CimSession object.

```
Type: CimSession
Parameter Sets: (All)
Aliases: CN

Required: False
Position: Named
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```


CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

Microsoft.Management.Infrastructure.CimClass

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-CimClass

[Get-CimMember](#)

Format-Percent

Synopsis

Format a value as a percentage.

Syntax

None (Default)

```
Format-Percent [-Value] <Object> [-Total] <Object> [-Decimal <Int32>]  
[<CommonParameters>]
```

String

```
Format-Percent [-Value] <Object> [-Total] <Object> [-Decimal <Int32>]  
[-AsString] [<CommonParameters>]
```

Description

This command calculates a percentage of a value from a total, with the formula: $(\text{value}/\text{total}) \times 100$. The default is to return a value to 2 decimal places but you can configure that with -Decimal. There is also an option to format the percentage as a string which will include the % symbol.

Examples

Example 1

```
PS C:\> Format-Percent -value 1234.567 -total 5000 -decimal 4  
  
24.6913
```

Calculate a percentage from 1234.567 out of 5000 (i.e. 1234.567/5000) to 4 decimal points.

Example 2

```
PS C:\> Get-CimInstance Win32_OperatingSystem -computer chi-dc04 |  
Select-Object PSComputername,TotalVisibleMemorySize,  
@{Name="PctFreeMem";Expression={  
Format-Percent $_.FreePhysicalMemory $_.TotalVisibleMemorySize}}  
  
PSComputerName      TotalVisibleMemorySize      PctFreeMem  
-----  
-----  
-----
```

```
chi-dc04 1738292 23.92
```

Example 3

```
PS C:\> Get-CimInstance Win32_OperatingSystem -computer chi-dc04 |  
Select-Object PSComputername,TotalVisibleMemorySize,  
@{Name="PctFreeMem";Expression={  
Format-Percent $_.FreePhysicalMemory $_.TotalVisibleMemorySize -asString}}
```

| PSComputerName | TotalVisibleMemorySize | PctFreeMem |
|----------------|------------------------|------------|
| ----- | ----- | ----- |
| chi-dc04 | 1738292 | 23.92% |

Parameters

-Value

The numerator value.

```
Type: Object  
Parameter Sets: (All)  
Aliases: X, Numerator  
  
Required: True  
Position: 1  
Default value: None  
Accept pipeline input: False  
Accept wildcard characters: False
```

-Total

The denominator value.

```
Type: Object  
Parameter Sets: (All)  
Aliases: Y, Denominator  
  
Required: True  
Position: 2  
Default value: None  
Accept pipeline input: False  
Accept wildcard characters: False
```

-Decimal

The number of decimal places to return between 0 and 15.

```
Type: Int32
```

```
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: 2
Accept pipeline input: False
Accept wildcard characters: False
```

-AsString

Write the result as a string.

```
Type: SwitchParameter
Parameter Sets: String
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

System.Object

Outputs

System.Double

System.String

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Format-Value](#)

Format-String

Format-String

Synopsis

Options for formatting strings.

Syntax

```
Format-String [-Text] <String> [-Reverse] [-Case <String>]  
[-Replace <Hashtable>] [-Randomize] [<CommonParameters>]
```

Description

Use this command to apply different types of formatting to strings. You can apply multiple transformations.

They are applied in this order:

1) Reverse 2) Randomization 3) Replace 4) Case

Examples

Example 1

```
PS C:\> "P@ssw0rd" | Format-String -Reverse  
dr0wss@P
```

Example 2

```
PS C:\> "P@ssw0rd" | Format-String -Reverse -Randomize  
rs0Pd@ws
```

Example 3

```
PS C:\> $env:computername | Format-String -Case Lower  
win81-ent-01
```

Example 4

```
PS C:\> Format-String "p*wer2she!!" -Case Alternate
```

```
P*WeR2ShE!!
```

Example 5

```
PS C:\> Format-String "alphabet" -Randomize -Replace @{a="@";e=3} `
-Case Alternate

3bPl@tH@
```

Example 6

```
PS C:\> "pOWERSHELL" | Format-String -Case Toggle

Powershell
```

Parameters

-Text

Any string you want to format.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 1
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-Reverse

Reverse the text string.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

-Case

Valid values are Upper, Lower, Proper, Alternate, and Toggle.

Proper case will capitalize the first letter of the string.

Alternate case will alternate between upper and lower case, starting with upper case, e.g. PoWeRsHeLl

Toggle case will make upper case lower and vice versa, e.g. Powershell -> pOWERSHELL

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Replace

Specify a hashtable of replacement values. The hashtable key is the string you want to replace and the value is the replacement (see examples). Replacement keys are CASE SENSITIVE.

```
Type: Hashtable
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Randomize

Re-arrange the text in a random order.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```


CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

System.String

Outputs

System.String

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Format-Value](#)

[Format-Percent](#)

Format-Value

Synopsis

Format a numeric value.

Syntax

Default (Default)

```
Format-Value [-InputObject] <Object> [[-Unit] <String>] [-Decimal <Int32>]  
[<CommonParameters>]
```

Number

```
Format-Value [-InputObject] <Object> [-Decimal <Int32>] [-AsNumber]  
[<CommonParameters>]
```

Auto

```
Format-Value [-InputObject] <Object> [-Decimal <Int32>] [-Autodetect]  
[<CommonParameters>]
```

Currency

```
Format-Value [-InputObject] <Object> [-AsCurrency] [<CommonParameters>]
```

Description

This command will format a given numeric value. By default, it will treat the number as an integer. Or you can specify a certain number of decimal places. The command will also allow you to format the value in KB, MB, etc.

You can let the command auto-detect the value and divide with an appropriate value.

Examples

Example 1

```
PS C:\> Get-CimInstance -class win32_logicaldisk -filter "DriveType=3" |  
Select-Object DeviceID,  
@{Name="SizeGB";Expression={$_.Size | Format-Value -unit GB}},
```

```
@{Name="FreeGB";Expression={$_.FreeSpace | Format-Value -unit GB -decimal 2}}
```

| DeviceID | SizeGB | FreeGB |
|----------|--------|--------|
| ----- | ----- | ----- |
| C: | 200 | 124.97 |
| D: | 437 | 29.01 |
| E: | 25 | 9.67 |

Example 2

```
PS C:\> (Get-Process chrome | measure ws -sum ).sum |  
Format-Value -Autodetect -verbose -Decimal 4
```

```
VERBOSE: Starting: Format-Value  
VERBOSE: Status: Using parameter set Auto  
VERBOSE: Status: Formatting 965332992  
VERBOSE: Status: Using Autodetect  
VERBOSE: ..as MB  
VERBOSE: Status: Reformatting 920.61328125  
VERBOSE: ..to 4 decimal places  
920.6133  
VERBOSE: Ending: Format-Value
```

Example 3

```
PS C:\> 3456.5689 | Format-Value -AsCurrency  
  
$3,456.57
```

Format a value as currency.

Example 4

```
PS C:\> 1234567.8973 | Format-Value -AsNumber -Decimal 2  
  
1,234,567.90
```

Format the value as a number to 2 decimal points.

Parameters

-InputObject

```
Type: Object  
Parameter Sets: (All)  
Aliases:  
  
Required: True  
Position: 2
```

```
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-Unit

The unit of measurement for your value. Valid choices are "KB", "MB", "GB", "TB", and "PB".

If you don't specify a unit, the value will remain as is, although you can still specify the number of decimal places.

```
Type: String
Parameter Sets: Default
Aliases:

Required: False
Position: 1
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Decimal

The number of decimal places to return between 0 and 15.

```
Type: Int32
Parameter Sets: Default, Number, Auto
Aliases:

Required: False
Position: Named
Default value: 0
Accept pipeline input: False
Accept wildcard characters: False
```

-Autodetect

Attempt to autodetect and format the value.

```
Type: SwitchParameter
Parameter Sets: Auto
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

-AsCurrency

Format the numeric value as currency using detected cultural settings. The output will be a string.

```
Type: SwitchParameter
Parameter Sets: Currency
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

-AsNumber

Format the numeric value as a number using detected cultural settings for a separator like a comma. If the incoming value contains decimal points, by default they will be removed unless you use -Decimal.

The output will be a string.

```
Type: SwitchParameter
Parameter Sets: Number
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

System.Object

Outputs

System.Object

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Format-String](#)

[Format-Percent](#)

Get-CimClassListing

Synopsis

A faster way to list CIM classes in a given namespace.

Syntax

```
Get-CimClassListing [[-Namespace] <String>] [[-Exclude] <String>] [[-CimSession] <CimSession>]  
[<CommonParameters>]
```

Description

This command is a faster alternative to Get-CimClass. It will only list the class name and not the entire class object. You may find this useful when all you need is the class name. The command will filter out system properties that start with __.

Examples

Example 1

```
PS C:\> Get-CimClassListing -Namespace Root\RSOP
```

```
Namespace: Root/RSOP
```

```
ClassName
```

```
-----
```

```
CIM_ClassCreation  
CIM_ClassDeletion  
CIM_ClassIndication  
CIM_ClassModification  
CIM_Error  
CIM_Indication  
CIM_InstCreation  
CIM_InstDeletion  
CIM_InstIndication  
CIM_InstModification  
MSFT_ExtendedStatus  
MSFT_WmiError  
RsopLoggingModeProvider  
RsopPlanningModeProvider
```

CimSystemProperties are excluded.

Example 2

```
PS C:\> Get-CimClassListing -Namespace Root\RSOP -Exclude cim*
```

```
Namespace: Root/RSOP

ClassName
-----
MSFT_ExtendedStatus
MSFT_WmiError
RsopLoggingModeProvider
RsopPlanningModeProvider
```

You can exclude classnames using wildcards.

Parameters

-CimSession

Specify a computer name or an existing CimSession object.

```
Type: CimSession
Parameter Sets: (All)
Aliases: CN

Required: False
Position: 2
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-Exclude

Enter a pattern for class names to EXCLUDE from the results. You can use wildcards.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 1
Default value: None
Accept pipeline input: False
Accept wildcard characters: True
```

-Namespace

Specify the class namespace beginning with ROOT.

```
Type: String
Parameter Sets: (All)
Aliases: NS
```



```
Required: False
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

Microsoft.Management.Infrastructure.CimSession

Outputs

cimClassListing

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Get-CimClass](#)

[Get-CimClassMember](#)

[Find-CimClass](#)

Get-CimClassMethod

Synopsis

Get the methods of a CIM class.

Syntax

```
Get-CimClassMethod [-ClassName] <String> [-Method <String>] [-Namespace <String>] [-CimSession <CimSession>] [<CommonParameters>]
```

Description

This command is an alternative to Get-CimClass to make it easier to get information about methods of a WMI/CIM class. The default behavior is to query classes on the local host, but you can query a remote computer using the CimSession parameter. You can specify a computer name, or an existing CIMSession if you need alternate credentials.

Examples

Example 1

```
PS C:\> Get-CimClassMethod Win32_ComputerSystem

Class: Root/Cimv2:Win32_ComputerSystem

Name                      ResultType Parameters
----                      -
JoinDomainOrWorkgroup     UInt32      {Name, Password, UserName, AccountOU...}
Rename                    UInt32      {Name, Password, UserName}
SetPowerState             UInt32      {PowerState, Time}
UnjoinDomainOrWorkgroup   UInt32      {Password, UserName, FUnjoinOptions}
```

The default is to show all methods.

Example 2

```
PS C:\> Get-CimClassMethod Win32_ComputerSystem -Name Rename | Select-Object -ExpandProperty Parameters

Name      CimType Qualifiers ReferenceClassName
----      -
Name      String {ID, In}
Password  String {ID, In}
UserName  String {ID, In}
```

You can get a single method by name.

Parameters

-CimSession

Specify a computer name or an existing CimSession object.

```
Type: CimSession
Parameter Sets: (All)
Aliases: CN

Required: False
Position: Named
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-ClassName

Specify a CIM Class.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-Method

Specify a method name. Wildcards are permitted.

```
Type: String
Parameter Sets: (All)
Aliases: Name

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: True
```

-Namespace

Specify the class namespace beginning with ROOT

```
Type: String
Parameter Sets: (All)
```

```
Aliases: NS
Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.String

Outputs

CimClassMethod

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Get-CimMember](#)

[Get-CimClass](#)

Get-CimClassProperty

Synopsis

Get the properties of a CIM class.

Syntax

property (Default)

```
Get-CimClassProperty [-ClassName] <String> [-Namespace <String>] [-Property <String>]  
[-CimSession <CimSession>] [<CommonParameters>]
```

key

```
Get-CimClassProperty [-ClassName] <String> [-Namespace <String>] [-KeyOnly] [-CimSession <CimSession>] [<CommonParameters>]
```

Description

This command is an alternative to Get-CimClass to make it easier to get information about properties of a WMI/CIM class. The default behavior is to query classes on the local host, but you can query a remote computer using the CimSession parameter. You can specify a computer name, or an existing CIMSession if you need alternate credentials.

Examples

Example 1

```
PS C:\> Get-CimClassProperty Win32_ace  
  
Class: Root/Cimv2:Win32_ACE  
  
Property           ValueType  Flags  
-----  
AccessMask          UInt32     NullValue  
AceFlags            UInt32     NullValue  
AceType             UInt32     NullValue  
GuidInheritedObjectType String     NullValue  
GuidObjectType      String     NullValue  
TIME_CREATED        UInt64     NullValue  
Trustee             Instance   NullValue
```

The default is to get all properties. Key properties, if defined, will be highlighted in the output.

Example 2

```
PS C:\> Get-CimClassProperty Win32_OperatingSystem -Property *memory*

Class: Root/Cimv2:Win32_OperatingSystem

Property          ValueType  Flags
-----
FreePhysicalMemory UInt64     ReadOnly, NullValue
FreeVirtualMemory  UInt64     ReadOnly, NullValue
MaxProcessMemorySize UInt64     ReadOnly, NullValue
TotalVirtualMemorySize UInt64     ReadOnly, NullValue
TotalVisibleMemorySize UInt64     ReadOnly, NullValue
```

You can use wildcards to filter properties.

Example 3

```
PS C:\> Get-CimClassProperty win32_process -KeyOnly

Class: Root/Cimv2:Win32_Process

Property ValueType  Flags
-----
Handle   String      Key, ReadOnly, NullValue
```

You can limit the results to key properties only.

Parameters

-CimSession

Specify a computer name or an existing CimSession object.

```
Type: CimSession
Parameter Sets: (All)
Aliases: CN

Required: False
Position: Named
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-ClassName

Specify a CIM Class.

```
Type: String
Parameter Sets: (All)
```

```
Aliases:  
  
Required: True  
Position: 0  
Default value: None  
Accept pipeline input: True (ByValue)  
Accept wildcard characters: False
```

-KeyOnly

Only show Key properties.

```
Type: SwitchParameter  
Parameter Sets: key  
Aliases:  
  
Required: False  
Position: Named  
Default value: None  
Accept pipeline input: False  
Accept wildcard characters: False
```

-Namespace

Specify the class namespace beginning with ROOT.

```
Type: String  
Parameter Sets: (All)  
Aliases: NS  
  
Required: False  
Position: Named  
Default value: None  
Accept pipeline input: False  
Accept wildcard characters: False
```

-Property

Specify a property name. Wildcards are permitted.

```
Type: String  
Parameter Sets: property  
Aliases:  
  
Required: False  
Position: Named  
Default value: None  
Accept pipeline input: False  
Accept wildcard characters: True
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.String

Outputs

CimClassProperty

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Get-CimMember](#)

[Get-CimClass](#)

Get-CimClassPropertyQualifier

Synopsis

Get the property qualifiers of a CIM class.

Syntax

```
Get-CimClassPropertyQualifier [-ClassName] <String> [-Property <String>] [-Namespace <String>]  
[-CimSession <CimSession>] [<CommonParameters>]
```

Description

This command is an alternative to Get-CimClass to make it easier to get information about property qualifiers of a WMI/CIM class. The default behavior is to query classes on the local host, but you can query a remote computer using the CimSession parameter. You can specify a computer name, or an existing CIMSession if you need alternate credentials.

Examples

Example 1

```
PS C:\> Get-CimClassPropertyQualifier -ClassName Win32_Service -Property Name  
  
Property: Root/Cimv2:Win32_Service [Name]  
  
Name Value CimType Flags  
----  
key   True  Boolean DisableOverride, ToSubclass  
read  True  Boolean EnableOverride, ToSubclass
```

The default behavior is to show all qualifiers for all properties, but you are most likely to filter to subset of properties. The Property parameter supports wildcards.

Parameters

-CimSession

Specify a computer name or an existing CimSession object.

```
Type: CimSession  
Parameter Sets: (All)  
Aliases: CN  
  
Required: False  
Position: Named
```

```
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-ClassName

Specify a CIM Class.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-Namespace

Specify the class namespace beginning with Root\

```
Type: String
Parameter Sets: (All)
Aliases: NS

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Property

Specify a property name. Wildcards are permitted.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: True
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and

-WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.String

Outputs

cimClassPropertyQualifier

Notes

Related Links

[Get-CimClassProperty](#)

[Get-CimClass](#)

Get-CimMember

Synopsis

Get information about CIM class members.

Syntax

property (Default)

```
Get-CimMember [[-ClassName] <String>] [-Property <String>] [-Namespace <String>] [-CimSession <CimSession>] [<CommonParameters>]
```

method

```
Get-CimMember [[-ClassName] <String>] -Method <String> [-Namespace <String>] [-CimSession <CimSession>] [<CommonParameters>]
```

Description

This is a wrapper function that will invoke Get-CimClassProperty or Get-CimClassMethod based on the parameter set used. The default is to show all properties for a given class.

Examples

Example 1

```
PS C:\> Get-CimMember -ClassName win32_volume

Class: Root/Cimv2:Win32_Volume

Property      ValueType      Flags
-----
Access        UInt16         ReadOnly, NullValue
Automount      Boolean        ReadOnly, NullValue
Availability    UInt16         ReadOnly, NullValue
BlockSize      UInt64         ReadOnly, NullValue
BootVolume     Boolean        ReadOnly, NullValue
Capacity       UInt64         ReadOnly, NullValue
Caption        String         ReadOnly, NullValue
Compressed     Boolean        ReadOnly, NullValue
...
```

The default is to show all properties for a given class.

Example 2

```
PS C:\> Get-CimMember -ClassName win32_Volume -Property q*

Class: Root/Cimv2:Win32_Volume

Property      ValueType  Flags
-----
QuotasEnabled  Boolean    ReadOnly, NullValue
QuotasIncomplete Boolean    ReadOnly, NullValue
QuotasRebuilding Boolean    ReadOnly, NullValue
```

You can filter the output by property name using wildcards.

Example 3

```
PS C:\> Get-CimMember -ClassName win32_bios -Method *
WARNING: No methods found for Root\Cimv2:WIN32_BIOS
```

Parameters

-CimSession

Specify a computer name or an existing CimSession object.

```
Type: CimSession
Parameter Sets: (All)
Aliases: CN

Required: False
Position: Named
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-ClassName

The name of a CIM class.

```
Type: String
Parameter Sets: (All)
Aliases: CimClassName

Required: False
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Method

Specify a method name. Wildcards are permitted.

```
Type: String
Parameter Sets: method
Aliases: Name

Required: True
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Namespace

Specify the class namespace beginning with ROOT.

```
Type: String
Parameter Sets: (All)
Aliases: NS

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Property

Specify a property name. Wildcards are permitted.

```
Type: String
Parameter Sets: property
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: True
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.String

Outputs

CimClassProperty

CimClassMethod

Notes

Related Links

[Get-CimClassProperty](#)

[Get-CimClassMethod](#)

Get-CimNamespace

Synopsis

Enumerate WMI/CIM namespaces.

Syntax

```
Get-CimNamespace [[-Namespace] <String>] [-TopLevelOnly] [-CimSession <CimSession>] [<CommonParameters>]
```

Description

You can use this command to enumerate all WMI/CIM namespaces on a computer starting from ROOT. The default behavior is to recursively enumerate on the local machine, but you can query a remote computer. If you need to support alternate credentials, create a CIMSession and pass it to the command.

Examples

Example 1

```
PS C:\> Get-CimNamespace

Root\subscription
Root\subscription\ms_41d
Root\subscription\ms_409
Root\DEFAULT
Root\DEFAULT\ms_41d
Root\DEFAULT\ms_409
Root\CIMV2
Root\CIMV2\mdm
Root\CIMV2\mdm\dmmap
...
```

Output is written to the pipeline as it is discovered.

Example 2

```
PS C:\> Get-CimNamespace -Namespace root\cimv2 -TopLevelOnly
root\cimv2\mdm
root\cimv2\Security
root\cimv2\vs
root\cimv2\ms_41d
root\cimv2\power
root\cimv2\ms_409
root\cimv2\TerminalServices
root\cimv2\NV
```


Only get top-level namespaces under the specified namespace.

Parameters

-CimSession

Specify a CimSession object.

```
Type: CimSession
Parameter Sets: (All)
Aliases: CN

Required: False
Position: Named
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-Namespace

Specify the root namespace to query. The default is Root.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-TopLevelOnly

Only list the top-level namespaces under the specified namespace.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and

-WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.String

Outputs

System.String

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Get-CimMember](#)

[Get-CimClassMethod](#)

[Get-CimClassProperty](#)

Get-CommandSyntax

Synopsis

Get provider-specific command syntax.

Syntax

```
Get-CommandSyntax [-Name] <String> [-ProviderName <String>] [<CommonParameters>]
```

Description

Some PowerShell commands are provider aware and may have special syntax or parameters depending on what PSDrive you are using when you run the command. In Windows PowerShell, the help system could show you syntax based on a given path. However, this no longer appears to work. This command is intended as an alternative. Specify a cmdlet or function name, and the output will display the syntax detected when using different providers. Dynamic parameters will be highlighted with an ANSI-escape sequence.

Examples

Example 1

```
PS C:\> Get-CommandSyntax -Name Get-Item

Registry

Get-Item [-Path] <string[]> [-Filter <string>] [-Include <string[]>]
[-Exclude <string[]>] [-Force] [-Credential <PSCredential>]
[<CommonParameters>]

Get-Item -LiteralPath <string[]> [-Filter <string>] [-Include <string[]>]
[-Exclude <string[]>] [-Force] [-Credential <PSCredential>]
[<CommonParameters>]

Alias

Get-Item [-Path] <string[]> [-Filter <string>] [-Include <string[]>]
[-Exclude <string[]>] [-Force] [-Credential <PSCredential>]
[<CommonParameters>]

Get-Item -LiteralPath <string[]> [-Filter <string>] [-Include <string[]>]
[-Exclude <string[]>] [-Force] [-Credential <PSCredential>]
[<CommonParameters>]
...
```

The output will show each PowerShell Provider and the corresponding command syntax. Dynamic parameters will be highlighted by color.

Parameters

-Name

Enter the name of a PowerShell cmdlet or function. Ideally, it has been loaded into the current PowerShell session.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-ProviderName

Enter a specific provider name. The default is all currently loaded providers.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

System.String

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-Help

Get-Command

[Get-ParameterInfo](#)

Get-DirectoryInfo

Synopsis

Get directory information.

Syntax

```
Get-DirectoryInfo [[-Path] <String>] [-Depth <Int32>] [<CommonParameters>]
```

Description

This command is designed to provide quick access to top-level directory information. The default behavior is to show the total number of files in the immediate directory. Although the command will also capture the total file size in the immediate directory. You can use the Depth parameter to recurse through a specified number of levels.

The command output will use a wide format by default. However, other wide views are available. See Examples.

Examples

Example 1

```
PS C:\> Get-DirectoryInfo

Path: C:\

gemfonts [15]                PerfLogs [0]
Pluralsight [17]            Presentations [1]
Program Files [0]           Program Files (x86) [0]
Ruby27-x64 [3]              Scripts [3652]
Thunderbird [0]             Training [3]
Users [0]                   Windows [38]
Windows.old [0]             Windows10Upgrade [23]
work [13]
```

The default output will use ANSI escape sequences.

Example 2

```
PS C:\> Get-DirectoryInfo -Path D:\ | Format-Wide -View sizemb

Path: D:\

autolab [0MB]                backtemp [0MB]
Backup [0.01MB]              Backups [140.49MB]
bovine320 [0MB]              Databases [0MB]
Exports [0MB]                iso [16137.65MB]
```

```

JDHIT [35.58MB]
OneDrive [0MB]
temp [10.67MB]
VMDisks [68053MB]
Logitech [0MB]
rip [60.99MB]
video [83.56MB]
VMs [0MB]

```

Using one of the alternate Format-Wide views. Other views are Size and SizeKb.

Example 3

```

PS C:\> Get-DirectoryInfo D:\Autolab\ -Depth 2 |
Format-Table -GroupBy parent -Property Name,File* -wrap

```

```

Parent: D:\Autolab

Name                FileCount  FileSize
----                -
Configurations      0           0
Hotfixes            0           0
ISOs                6 16838768742
MasterVirtualHardDisks 3 22326280192
Resources           0           0
VMVirtualHardDisks  0           0


Parent: D:\Autolab\Configurations

Name                FileCount  FileSize
----                -
Implement-Windows-Server-DHCP-2016      7    65126
Jason-DSC-Env                          7    66933
microsoft-powershell-implementing-jea   7    65462
MultiRole                             7    65820
MultiRole-Server-2016                   7    62063
PowerShellLab                           7    83541
SingleServer                           4    15784
SingleServer2012R2                      4    15937
SingleServer2012R2-GUI                   4    16005
SingleServer-GUI-2016                    4    16397
SingleServer-GUI-2019                    4    15845
Windows10                               4    20695


Parent: D:\Autolab\Configurations\PowerShellLab

Name    FileCount  FileSize
----    -
PostSetup      5    15275

```

Here's an example using the DirectoryStat object with different formatting.

Parameters

-Depth

The Depth parameter determines the number of subdirectories to recursively query.

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Path

Specify the top-level path.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

DirectoryStat

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-ChildItem

Get-FileExtensionInfo

Synopsis

Get a report of files based on their extension.

Syntax

```
Get-FileExtensionInfo [[-Path] <String>] [-Recurse] [-Hidden] [-IncludeFiles] [<CommonParameters>]
```

Description

This command will search a given directory and produce a report of all files based on their file extension. This command is only available in PowerShell 7.

Examples

Example 1

```
PS C:\> Get-FileExtensionInfo c:\work

Path: C:\work [THINKP1]

Extension Count TotalSize Smallest Average Largest
-----
.bat          1          0          0          0          0
.bmp          1         122         122         122         122
.bmp          2        14113        4509        7056.5        9604
.csv          7       188085         107    26869.29    129351
.db           3       18432        6144         6144         6144
.gif          1         7110        7110         7110         7110
.htm          1         2586        2586         2586         2586
.html         8       580178        1060    72522.25    238054
.jdh          1          92          92          92          92
.jpg          1         9604        9604         9604         9604
.jpg          2        23827        9604     11913.5     14223
.json         8       366166          546    45770.75    310252
.log          1         6323        6323         6323         6323
.md           2         4031          389      2015.5         3642
.pdf          1        80704       80704       80704       80704
.png          4        47598        1071     11899.5     22700
.ps1          5         2713          64        542.6        1530
.ps1xml       2         5765        2794      2882.5        2971
.psd1         1         7696        7696         7696         7696
.reg          1         8802        8802         8802         8802
.txt         27       332297          7     12307.3     72047
.xml         10      67920544        1584   6792054.4   58504746
.zip          1     13493443   13493443   13493443   13493443
```

The extension with the largest total size will be highlighted in color.

Parameters

-Hidden

Include files in hidden folders

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-IncludeFiles

Add the corresponding collection of files. You can access these items by the Files property.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Path

Specify the root directory path to search

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Recurse

Recurse through all folders.

```
Type: SwitchParameter
Parameter Sets: (All)
```

```
Aliases:
Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

FileExtensionInfo

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Get-FolderSizeInfo](#)

Get-FileItem

Synopsis

A PowerShell version of the Where CLI command.

Syntax

Default (Default)

```
Get-FileItem [-Pattern] <String[]> [-Regex] [-Full] [-Quiet] [-First]  
[<CommonParameters>]
```

Path

```
Get-FileItem [-Pattern] <String[]> [-Regex] [-Path <String[]>] [-Recurse]  
[-Full] [-Quiet] [-First] [<CommonParameters>]
```

Description

This is an enhanced, PowerShell version of the WHERE command from the traditional CLI which will find files in %PATH% that match a particular pattern.

Examples

Example 1

```
PS C:\> Get-FileItem notepad.exe  
C:\Windows\notepad.exe  
C:\Windows\System32\notepad.exe  
C:\Windows\System32\notepad.exe  
C:\Windows\notepad.exe  
C:\Users\Jeff\AppData\Local\Microsoft\WindowsApps\notepad.exe
```

Find notepad.exe in %PATH% and return the complete file name. This is the default behavior.

Example 2

```
PS C:\> PSWhere foo.exe -Quiet  
False
```

Search for foo.exe and return \$True if found. This command is using the PSWhere alias.

Example 3

```
PS C:\> Get-FileItem "^d+\S+\.txt" -Regex -Path c:\scripts -full
```

Directory: C:\Scripts

| Mode | LastWriteTime | Length | Name |
|-------|--------------------|--------|---------------------|
| -a--- | 10/28/2021 9:36 AM | 30145 | 1000FemaleNames.txt |
| -a--- | 12/5/2007 2:19 PM | 29618 | 1000MaleNames.txt |
| -a--- | 6/2/2010 11:02 AM | 31206 | 1000names.txt |
| -a--- | 6/3/2010 8:52 AM | 3154 | 100names.txt |
| -a--- | 5/28/2014 1:38 PM | 1601 | 100NewUsers.txt |
| -a--- | 2/17/2015 4:47 PM | 2300 | 2015.txt |
| -a--- | 2/7/2011 1:37 PM | 78542 | 2500names.txt |

Find all TXT files in C:\Scripts that start with a number and display full file information.

Parameters

-Pattern

The name of the file to find. Separate multiple entries with a comma. Wildcards are allowed. You can also specify a regular expression pattern by including the -REGEX parameter.

```
Type: String[]
Parameter Sets: (All)
Aliases:

Required: True
Position: 1
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Regex

Indicates that the pattern is a regular expression.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

-Path

The folders to search other than %PATH%.

```
Type: String[]
Parameter Sets: Path
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Recurse

Used with -Path to indicate a recursive search.

```
Type: SwitchParameter
Parameter Sets: Path
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

-Full

Write the full file object to the pipeline. The default is just the full name.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

-Quiet

Returns True if a match is made. This parameter will override -Full.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
```

```
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

-First

Stop searching after the pattern is found. Don't search any more paths.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

String

Outputs

String

Boolean

System.IO.FileInfo

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-ChildItem

Where.exe

Get-FolderSizeInfo

Synopsis

Get folder size information.

Syntax

```
Get-FolderSizeInfo [-Path] <String[]> [-Hidden] [-EnableLongFileName] [<CommonParameters>]
```

Description

This command is an alternative to discovering the size of a folder, or at least an easier method. Use the -Hidden parameter to include hidden files in the output. The measurement will include all files in all sub-folders.

Note that this command has been optimized for performance, but if you have a lot of files to count that will take time, especially when using Windows PowerShell. When querying system folders like C:\Windows on a Windows PowerShell platform, you might get better results including hidden files. Due to the nature of the .NET Framework changes, you might see different results for the same folder when run in PowerShell 7 compared to Windows PowerShell 5.1.

This command will ignore reparse points, such as symbolic links and junctions.

If using on a profile folder, you will most likely get access denied warnings in Windows PowerShell and you can assume those locations will not be counted.

Examples

Example 1

```
PS C:\> Get-FolderSizeInfo -Path d:\temp
```

| Computername | Path | TotalFiles | TotalSize |
|--------------|---------|------------|-----------|
| ----- | ---- | ----- | ----- |
| BOVINE320 | D:\temp | 48 | 121824451 |

Example 2

```
PS C:\> Get-FolderSizeInfo -Path d:\temp -hidden
```

| Computername | Path | TotalFiles | TotalSize |
|--------------|---------|------------|-----------|
| ----- | ---- | ----- | ----- |
| BOVINE320 | D:\temp | 146 | 125655552 |

Include hidden files.

Example 3

```
PS C:\> Get-ChildItem d:\ -Directory | Get-FolderSizeInfo |
Where-Object TotalSize -gt 1MB | Sort-Object TotalSize -Descending |
Format-Table -View mb
```

| Computername | Path | TotalFiles | TotalSizeMB |
|--------------|-----------------------|------------|-------------|
| BOVINE320 | D:\VMDisks | 18 | 114873.7246 |
| BOVINE320 | D:\ISO | 17 | 42526.8204 |
| BOVINE320 | D:\SQLServer2017Media | 1 | 710.8545 |
| BOVINE320 | D:\officeViewers | 4 | 158.9155 |
| BOVINE320 | D:\Temp | 48 | 116.1809 |
| BOVINE320 | D:\Sysinternals | 153 | 59.6169 |
| BOVINE320 | D:\blog | 41 | 21.9948 |
| BOVINE320 | D:\BackTemp | 2 | 21.6734 |
| BOVINE320 | D:\rip | 3 | 11.1546 |
| BOVINE320 | D:\logs | 134 | 3.9517 |
| BOVINE320 | D:\2016 | 5 | 1.5608 |

Get the top-level directories from D and pipe them to Get-FolderSizeInfo. Items with a total size of greater than 1MB are sorted on the total size and then formatted as a table using a built-in view called MB which formats the total size in MB. There are also views named KB,GB and TB to display formatted results accordingly.

Example 4

```
PS C:\> Get-ChildItem c:\work -Directory | Get-FolderSizeInfo -Hidden |
Where-Object {$_.TotalSize -ge 2mb} | Format-Table -view name
```

Path: C:\work

| Name | TotalFiles | TotalKB |
|-----------------|------------|------------|
| A | 20 | 5843.9951 |
| keepass | 15 | 5839.084 |
| PowerShellBooks | 26 | 4240.3779 |
| sunday | 47 | 24540.6523 |

Get all sub-folders under C:\work greater than 2MB in size and display using the Name table view.

Parameters

-Hidden

Include hidden directories.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:
Required: False
```

```
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Path

Enter a file system path like C:\Scripts.

```
Type: String[]
Parameter Sets: (All)
Aliases: PSPath

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByPropertyName, ByValue)
Accept wildcard characters: False
```

-EnableLongFileName

Enable support for long file and folder names. Read <https://learn.microsoft.com/windows/win32/fileio/maximum-file-path-limitation?tabs=registry> to learn more.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: lfn, EnableLN

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.String[]

Outputs

FolderSizeInfo

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Test-EmptyFolder](#)

[Get-ChildItem](#)

[Measure-Object](#)

Get-FormatView

Synopsis

Get defined format views.

Syntax

```
Get-FormatView [[-TypeName] <String>] [[-PowerShellVersion] <Version>] [<CommonParameters>]
```

Description

PowerShell's formatting system includes custom views that display objects in different ways. Unfortunately, this information is not readily available to a typical PowerShell user. Get-FormatView displays the available views for a given object type. You might get additional views when importing modules such as the PSScriptTools module. The result is there might be different views depending on if you use Format-Table, or Format-List. If you only see a single defined view, that is the default for that type of control.

Examples

Example 1

```
PS C:\> Get-FormatView system.diagnostics.process
```

```
    Type: System.Diagnostics.Process
```

```
Format    Name
-----
Table     process
Table     Priority
Table     StartTime
Wide      process
Table     WS
```

The default view should be the first one listed for each format type. With this information, you can now run a command like `Get-Process | Format-Table -view Priority`. The WS view is added when you import the PSScriptTools module.

Example 2

```
PS C:\> (Get-Service bits).GetType() | Get-FormatView
```

```
    Type: System.ServiceProcess.ServiceController
```

```
Format    Name
```

```

-----
Table      service
List       System.ServiceProcess.ServiceController
Table      service
Table      Ansi

```

You can pipe a type name to the command.

Example 3

```

PS C:\> Get-FormatView | Where-Object Format -eq Table |
Group-Object typename | Where-Object count -gt 1 | Select-Object Name,
@{Name="Names";Expression = {$_.group.name}}

Name                                     Names
----                                     -
FolderSizeInfo                         {default, MB, GB, KB...}
gitsize                                {mb, default}
ModuleCommand                          {default, verb}
System.Diagnostics.Process              {process, Priority, StartTime..
System.IO.DirectoryInfo                 {children, ansi}
System.IO.FileInfo                     {children, ansi}
System.Management.Automation.AliasInfo  {CommandInfo, AliasInfo, opti..
System.Management.Automation.ApplicationInfo {CommandInfo, ApplicationInfo}
System.Management.Automation.ExternalScriptInfo {CommandInfo, ExternalScriptI..
System.Management.Automation.FilterInfo  {CommandInfo, FilterInfo}
System.Management.Automation.FunctionInfo {CommandInfo, FunctionInfo}
System.Management.Automation.ScriptInfo  {CommandInfo, ScriptInfo}
System.ServiceProcess.ServiceController {service, service, Ansi}

```

This example expression is getting all Table format views for types that have more than 1 defined. If a type only has a single view, that is the default which you are seeing already. The output you see here shows additional table views for different object types.

Parameters

-TypeName

Specify a typename such as System.Diagnostics.Process.

```

Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 0
Default value: *
Accept pipeline input: True (ByValue)
Accept wildcard characters: True

```

-PowerShellVersion

Specify the version of PowerShell this cmdlet gets for the formatting data. Enter a two-digit number separated by a period.

```
Type: Version
Parameter Sets: (All)
Aliases:

Required: False
Position: 1
Default value: your current PowerShell version
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

PSFormatView

Notes

This command relies on data provided by Get-FormatData. Some object types might be stored in PowerShell in unexpected ways. This command should have an alias of gfv.

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-FormatData

Get-Member

[New-PSFormatXML](#)

Get-GitSize

Synopsis

Get the size of .git folder.

Syntax

```
Get-GitSize [[-Path] <String>] [<CommonParameters>]
```

Description

When using git, it creates a hidden folder for change tracking. Because the file is hidden it is easy to overlook how large it might become. The command uses a formatting file to display a default view. There is an additional table view called MB that you can use.

Examples

Example 1

```
PS C:\Scripts\PiedPiper> Get-GitSize
```

| Path | Files | SizeKB |
|----------------------|-------|-----------|
| ---- | ----- | ----- |
| C:\scripts\PiedPiper | 751 | 6859.9834 |

Get the size of the .git folder from the current path.

Example 2

```
PS C:\> Get-ChildItem c:\scripts -Directory | Get-GitSize |  
Sort-Object -property Size -descending |  
Select-Object -first 5 -property Computername,Name,Files,Size
```

| Computername | Name | Files | Size |
|--------------|----------------|-------|-----------|
| ----- | ---- | ----- | ---- |
| WIN10DSK2 | PSAutoLab | 526 | 193760657 |
| WIN10DSK2 | DevOps-Courses | 29 | 53298180 |
| WIN10DSK2 | PSScriptTools | 751 | 7024623 |
| WIN10DSK2 | PSGUI | 32 | 6705894 |
| WIN10DSK2 | DscWorkshop | 24 | 5590511 |

Get the directories under C:\Scripts that have a .git folder and sort on the Size property in descending order. Then select the first 5 directories and use the specified properties.

Example 3

```
PS S:\PSReleaseTools> Get-GitSize | Format-Table -view mb

Path                               Files      SizeMB
----                               -
C:\scripts\PSReleaseTools         440        3.0588
```

Get the git folder size and format using the MB table view.

Parameters

-Path

The path to the parent folder, not the .git folder.

```
Type: String
Parameter Sets: (All)
Aliases: pspath

Required: False
Position: 1
Default value: current location
Accept pipeline input: True (ByPropertyName, ByValue)
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.String

Outputs

gitSize

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

This is a variation of code posted at <https://gist.github.com/jdhitsolutions/cbdc7118f24ba551a0bb325664415649>

Related Links

[Get-ChildItem](#)

[Measure-Object](#)

[Remove-MergedBranch](#)

Get-LastModifiedFile

Synopsis

Get files based on last modified data.

Syntax

```
Get-LastModifiedFile [[-Filter] <String>] [[-Path] <String>]  
[-Interval <String>] [-IntervalCount <Int32>] [-Recurse] [<CommonParameters>]
```

Description

This command is designed to make it easier to identify last modified files. You can specify by an interval such as 3 months or 24 hours.

Examples

Example 1

```
PS C:\> Get-LastModifiedFile -Path c:\work  
  
Directory: C:\work  
  
Mode                LastWriteTime         Length Name  
----                -  
-a---          11/30/2024   1:52 PM           2010 a.txt  
-a---          11/30/2024   1:52 PM           5640 b.txt
```

The default behavior is to find all files modified in the last 24 hours.

Example 2

```
PS C:\> Get-LastModifiedFile -Path c:\scripts -Filter *.ps1 -Interval Months -IntervalCount 6  
  
Directory: C:\Scripts  
  
Mode                LastWriteTime         Length Name  
----                -  
-a---          11/19/2024   2:36 PM           1434 calendar-prompt.ps1  
-a---          10/11/2024  11:26 AM           1376 ChangeOSCaption.ps1  
-a---           8/27/2024   8:06 AM           2754 Check-ModuleUpdate.ps1  
-a---           9/17/2024   9:23 AM           1822 CleanJobs.ps1  
-a---           7/14/2024  10:36 AM            436 Clear-Win11Recommended.ps1  
-a---          10/18/2024   5:24 PM           5893 ComingSoon.ps1  
-a---          10/25/2024   5:23 PM           4966 Configure-PSVirtualMachine.ps1  
...
```

Get all .ps1 files in C:\Scripts that have been modified in the last 6 months.

Parameters

-Filter

Specify a file filter like *.ps1.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Interval

Specify the search interval based on the last write time.

```
Type: String
Parameter Sets: (All)
Aliases:
Accepted values: Hours, Minutes, Days, Months, Years

Required: False
Position: Named
Default value: Hours
Accept pipeline input: False
Accept wildcard characters: False
```

-IntervalCount

Specify the number of intervals.

```
Type: Int32
Parameter Sets: (All)
Aliases: ic

Required: False
Position: Named
Default value: 24
Accept pipeline input: False
Accept wildcard characters: False
```

-Path

Specify the folder to search.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 1
Default value: current location
Accept pipeline input: False
Accept wildcard characters: False
```

-Recurse

Recurse from the specified path.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

System.IO.FileInfo

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

This command was first described at <https://jdhitsolutions.com/blog/powershell/8622/finding-modified-files-with-powershell/>

Related Links

[Get-ChildItem](#)

[Get-DirectoryInfo](#)

[Get-FolderSizeInfo](#)

Get-ModuleCommand

Synopsis

Get a summary of module commands.

Syntax

name (Default)

```
Get-ModuleCommand [-Name] <String> [-ListAvailable] [<CommonParameters>]
```

fqdn

```
Get-ModuleCommand -FullyQualifiedName <ModuleSpecification> [-ListAvailable] [<CommonParameters>]
```

Description

This is an alternative to Get-Command to make it easier to see at a glance what commands are contained within a module and what they can do. By default, Get-ModuleCommand looks for loaded modules. Use -ListAvailable to see commands in the module but not currently loaded. Note that if the help file is malformed or missing, you might get oddly formatted results. If the help file does not define a synopsis, you will see the command's syntax.

Examples

Example 1

```
PS C:\> Get-ModuleCommand PSCalendar
```

```
ModuleName: PSCalendar [v2.9.0]
```

| Name | Alias | Synopsis |
|------------------|-------|--|
| Get-Calendar | cal | Displays a visual representation of a calendar. |
| Show-Calendar | scal | Display a colorized calendar month in the console. |
| Show-GuiCalendar | gcal | Display a WPF-based calendar |

Get module commands using the default formatted view. You can install this module from the PowerShell Gallery.

Example 2

```
PS C:\> Get-ModuleCommand SmbShare -ListAvailable | Format-List

ModuleName : SmbShare
Name       : Block-SmbShareAccess
Alias      : blsmba
Synopsis   : Adds a deny ACE for a trustee to the security descriptor of the SMB share.

ModuleName : SmbShare
Name       : Close-SmbOpenFile
Alias      : cssmbo
Synopsis   : Closes a file that is open by one of the clients of the SMB server.

ModuleName : SmbShare
Name       : Close-SmbSession
Alias      : cssmbse
Synopsis   : Ends forcibly the SMB session.
...
```

Using the default list view.

Example 3

```
PS C:\> Get-ModuleCommand PSScriptTools | Format-Table -view verb

Verb: Add

Name      Alias      Type      Synopsis
----      -
Add-Border      Function  Create a text border around a string.

Verb: Compare

Name      Alias      Type      Synopsis
----      -
Compare-Module cmo        Function  Compare PowerShell module versions.
...
```

Display commands using a custom table view called 'Verb'.

Example 4

```
PS C:\> Get-ModuleCommand PSScriptTools | Format-Table -view version

ModuleName: PSScriptTools [v3.0.0]

Name      Alias      Compatible      PSVersion
----      -
Add-Border      ab          {Desktop, Core} 5.1
Compare-Module  cmo         {Desktop, Core} 5.1
```

```
Compare-Script          csc          {Desktop, Core}    5.1
Convert-CommandToHashtable {Desktop, Core}    5.1
...
```

Using the custom table view 'version'.

Parameters

-FullyQualifiedName

Specifies names of modules in the form of ModuleSpecification objects. The FullyQualifiedName parameter accepts a module name that is specified in the following formats:

```
@{ModuleName = "modulename"; ModuleVersion = "version_number"}
```

```
@{ModuleName = "modulename"; ModuleVersion = "version_number"; Guid = "GUID"}
```

ModuleName and ModuleVersion are required, but Guid is optional.

You cannot specify the FullyQualifiedName parameter in the same command as a Name parameter.

```
Type: ModuleSpecification
Parameter Sets: fqdn
Aliases:

Required: True
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-ListAvailable

Indicates that this cmdlet gets all installed modules. Get-Module finds modules in paths listed in the PSModulePath environment variable. Without this parameter, Get-ModuleCommand gets only the modules that are both listed in the PSModulePath environment variable, and that are loaded in the current session.

ListAvailable does not return information about modules that are not found in the PSModulePath environment variable, even if those modules are loaded in the current session.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Name

The name of an installed module.

```
Type: String
Parameter Sets: name
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByPropertyName)
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

ModuleCommand

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-Command

Get-Module

Get-MyAlias

Synopsis

Get non-default aliases defined in the current session.

Syntax

```
Get-MyAlias [-NoModule] [<CommonParameters>]
```

Description

Often you might define aliases for functions and scripts you use often. It may difficult sometimes to remember them all or to find them in the default Get-Alias output. This command will list all currently defined aliases that are not part of the initial PowerShell state.

The PSScriptTools module also includes a custom formatting file for alias objects which you can use with Get-Alias or Get-MyAlias. See examples.

Examples

Example 1

```
PS C:\> Get-MyAlias
```

| CommandType | Name | Version | Source |
|-------------|--------------------------------|---------|-----------------|
| ----- | ---- | ----- | ----- |
| Alias | abt -> Get-AboutInfo | | |
| Alias | bv -> Brave | | |
| Alias | cal -> Get-Calendar | 1.11.0 | PSCalendar |
| Alias | cc -> Copy-Command | 3.0.0 | PSScriptTools |
| Alias | cfn -> New-CustomFileName | 3.0.0 | PSScriptTools |
| Alias | CFS -> ConvertFrom-String | 3.1.0.0 | Microsoft.Po... |
| Alias | cft -> ConvertFrom-Text | 3.0.0 | PSScriptTools |
| Alias | chc -> Convert-HashTableToCode | 3.0.0 | PSScriptTools |
| Alias | che -> Copy-HelpExample | 3.0.0 | PSScriptTools |
| Alias | cl -> Create-List | | |
| Alias | clr -> Convert-EventLogRecord | 3.0.0 | PSScriptTools |
| Alias | clt -> ConvertTo-LocalTime | 3.0.0 | PSScriptTools |
| Alias | cmo -> Compare-Module | 3.0.0 | PSScriptTools |
| ... | | | |

Get all aliases that aren't par of the initial session state. This will include aliases defined in any modules you have loaded.

Example 2

```
PS C:\> Get-MyAlias -NoModule
```

| CommandType | Name | Version | Source |
|-------------|----------------------|---------|--------|
| ----- | ---- | ----- | ----- |
| Alias | abt -> Get-AboutInfo | | |
| Alias | bv -> Brave | | |
| Alias | cl -> Create-List | | |

Get defined aliases that don't belong to a module. These should be aliases you have defined in stand-alone scripts or your profile.

Example 3

```
PS C:\> Get-MyAlias -NoModule | Format-Table -View options
```

| Name | Definition | Options | ModuleName | Version |
|------|---------------|----------|------------|---------|
| ---- | ----- | ----- | ----- | ----- |
| abt | Get-AboutInfo | None | | |
| bv | Brave | None | | |
| cl | Create-List | None | | |
| np | notepad | ReadOnly | | |

Get your aliases and pipe to format table using a custom view defined by the PSScriptTools module.

Parameters

-NoModule

Only show aliases that DO NOT belong to a module.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

System.Management.Automation.AliasInfo

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-Alias

Get-MyCounter

Synopsis

Get performance counter data.

Syntax

```
Get-MyCounter [[-Counter] <String[]>] [-SampleInterval <Int32>]  
[-MaxSamples <Int64>] [-Continuous] [-ComputerName <String[]>]  
[<CommonParameters>]
```

Description

Get-MyCounter is an enhanced version of Get-Counter which is available on Windows platforms to retrieve performance counter data. One of the challenges with Get-Counter is how it formats results. Get-MyCounter takes the same information and writes a custom object to the pipeline that is easier to work with. You can pipe counters from Get-Counter to this command.

The custom object has an associated formatting file with custom views. See examples.

Examples

Example 1

```
PS C:\> Get-Counter -list "system" | Get-MyCounter
```

Computername: SERVER18

| Timestamp | Category | Counter | Value |
|-----------------------|----------|-----------------------------|-------------|
| ----- | ----- | ----- | ----- |
| 11/4/2024 10:48:47 AM | system | file read operations/sec | 203.3096 |
| 11/4/2024 10:48:47 AM | system | file write operations/sec | 252.6566 |
| 11/4/2024 10:48:47 AM | system | file control operations/sec | 197.3879 |
| 11/4/2024 10:48:47 AM | system | file read bytes/sec | 206336.5281 |
| 11/4/2024 10:48:47 AM | system | file write bytes/sec | 56409.5271 |
| 11/4/2024 10:48:47 AM | system | file control bytes/sec | 10452.6787 |
| 11/4/2024 10:48:47 AM | system | context switches/sec | 6068.6924 |
| 11/4/2024 10:48:47 AM | system | system calls/sec | 17854.7266 |
| 11/4/2024 10:48:47 AM | system | file data operations/sec | 455.9662 |
| 11/4/2024 10:48:47 AM | system | system up time | 73056.4005 |
| 11/4/2024 10:48:47 AM | system | processor queue length | 0 |
| 11/4/2024 10:48:47 AM | system | processes | 301 |
| 11/4/2024 10:48:47 AM | system | threads | 4502 |
| 11/4/2024 10:48:47 AM | system | alignment fixups/sec | 0 |
| 11/4/2024 10:48:47 AM | system | exception dispatches/sec | 6.9086 |
| 11/4/2024 10:48:47 AM | system | floating emulations/sec | 0 |
| 11/4/2024 10:48:47 AM | system | % registry quota in use | 4.0327 |

Get all of the System counters with Get-Counter and pipe them to Get-MyCounter.

Example 2

```
PS C:\> Get-MyCounter -computername server18 | Format-table -view category
```

Category: network interface(intel[r] ethernet connection [11] i219-lm)

| Computername | Timestamp | Counter | Value |
|--------------|-----------------------|-----------------|-----------|
| SERVER18 | 11/4/2024 11:20:09 AM | bytes total/sec | 2662.0477 |

Category: network interface(intel[r] wi-fi 6 ax201 160mhz)

| Computername | Timestamp | Counter | Value |
|--------------|-----------------------|-----------------|-------|
| SERVER18 | 11/4/2024 11:20:09 AM | bytes total/sec | 0 |

Category: processor(_total)

| Computername | Timestamp | Counter | Value |
|--------------|-----------------------|------------------|--------|
| SERVER18 | 11/4/2024 11:20:09 AM | % processor time | 1.4158 |

Category: memory

| Computername | Timestamp | Counter | Value |
|--------------|-----------------------|--------------------------|---------|
| SERVER18 | 11/4/2024 11:20:09 AM | % committed bytes in use | 40.5214 |
| SERVER18 | 11/4/2024 11:20:09 AM | cache faults/sec | 0 |

Category: physicaldisk(_total)

| Computername | Timestamp | Counter | Value |
|--------------|-----------------------|---------------------------|--------|
| SERVER18 | 11/4/2024 11:20:09 AM | % disk time | 0.0217 |
| SERVER18 | 11/4/2024 11:20:09 AM | current disk queue length | 0 |

Get the default counter set and pipe to Get-MyCounter to get values for the local host.

Example 3

```
PS C:\> $c = (Get-Counter -list logicaldisk).PathsWithInstances |
Where-Object {$_. -match "\\(c:)\\"}
PS C:\> Get-MyCounter -Counter $c -ComputerName SERVER18,SERVER2 |
Format-Table -view category
```

Category: logicaldisk(c:)

| Computername | Timestamp | Counter | Value |
|--------------|-----------------------|------------------|---------|
| SERVER18 | 11/4/2024 10:50:03 AM | % free space | 48.3822 |
| SERVER2 | 11/4/2024 10:50:04 AM | % free space | 54.5916 |
| SERVER18 | 11/4/2024 10:50:03 AM | % disk time | 1.4669 |
| SERVER2 | 11/4/2024 10:50:04 AM | % disk time | 5.3787 |
| SERVER18 | 11/4/2024 10:50:03 AM | % disk read time | 0.8467 |


```

SERVER2      11/4/2024 10:50:04 AM % disk read time          0
SERVER18     11/4/2024 10:50:03 AM % disk write time         0.6203
SERVER2      11/4/2024 10:50:04 AM % disk write time         5.3787
SERVER18     11/4/2024 10:50:03 AM % idle time               98.5846
SERVER2      11/4/2024 10:50:04 AM % idle time               93.3567

```

```

PS C:\> Get-MyCounter -Counter $c -ComputerName SERVER18,SERVER2 |
Sort-Object Computername

```

```

    Computername: SERVER18

```

| Timestamp | Category | Counter | Value |
|-----------------------|-----------------|-------------------|---------|
| 11/4/2024 10:50:35 AM | logicaldisk(c:) | % free space | 48.3822 |
| 11/4/2024 10:50:35 AM | logicaldisk(c:) | % disk time | 0.0263 |
| 11/4/2024 10:50:35 AM | logicaldisk(c:) | % disk read time | 0 |
| 11/4/2024 10:50:35 AM | logicaldisk(c:) | % disk write time | 0.0263 |
| 11/4/2024 10:50:35 AM | logicaldisk(c:) | % idle time | 99.9435 |

```

    Computername: SERVER2

```

| Timestamp | Category | Counter | Value |
|-----------------------|-----------------|-------------------|---------|
| 11/4/2024 10:50:37 AM | logicaldisk(c:) | % free space | 54.5916 |
| 11/4/2024 10:50:37 AM | logicaldisk(c:) | % disk time | 0 |
| 11/4/2024 10:50:37 AM | logicaldisk(c:) | % disk read time | 0 |
| 11/4/2024 10:50:37 AM | logicaldisk(c:) | % disk write time | 0 |
| 11/4/2024 10:50:37 AM | logicaldisk(c:) | % idle time | 99.0114 |

The first command gets a collection of logical disk counters for drive C. The second command gets performance counter data for two remote computers and formats the results using a custom view. The last command repeats the process but sorts the result by the computer name.

Example 4

```

PS C:\> $p == Get-MyCounter -Counter "\IPv4\Datagrams/sec" -ComputerName SERVER2
-SampleInterval 5 -MaxSamples 30

```

This command will get the specified counter value every 5 seconds for a total of 30 samples.

Parameters

-ComputerName

The name of a remote computer. Querying a remote computer does not use PowerShell remoting and requires administrator-level permissions. Typically, the RemoteRegistry service must also be running.

```

Type: String[]
Parameter Sets: (All)
Aliases: Cn

Required: False
Position: Named
Default value: localhost

```

```
Accept pipeline input: False
Accept wildcard characters: False
```

-Continuous

Gets samples continuously until you press CTRL+C. By default, Get-MyCounter gets only one counter sample. You can use the SampleInterval parameter to set the interval for continuous sampling.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-Counter

Gets data from the specified performance counters. Enter one or more counter paths. Wildcards are permitted only in the Instance value. You can also pipe counter path strings to Get-MyCounter.

Each counter path has the following format:

```
\\ComputerName\CounterSet(Instance)\CounterName
```

For example:

```
\\Server01\Processor(2)\% User Time
```

The ComputerName element is optional. If you omit it, Get-MyCounter uses the value of the ComputerName parameter.

```
Type: String[]
Parameter Sets: (All)
Aliases:

Required: False
Position: 0
Default value: None
Accept pipeline input: True (ByPropertyName, ByValue)
Accept wildcard characters: False
```

-MaxSamples

Specifies the number of samples to get from each counter. The default is 1 sample. To get samples continuously (no maximum sample size), use the Continuous parameter.

```
Type: Int64
Parameter Sets: (All)
```

```
Aliases:  
  
Required: False  
Position: Named  
Default value: None  
Accept pipeline input: False  
Accept wildcard characters: False
```

-SampleInterval

Specifies the time between samples in seconds. The minimum value and the default value are 1 second

```
Type: Int32  
Parameter Sets: (All)  
Aliases:  
  
Required: False  
Position: Named  
Default value: None  
Accept pipeline input: False  
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.String[]

Outputs

myCounter

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-Counter

Get-MyTimeInfo

Synopsis

Display time settings for a collection of locations.

Syntax

```
Get-MyTimeInfo [[-Locations] <OrderedDictionary>] [-HomeTimeZone <String>]  
[-DateTime <DateTime>] [-AsTable] [-AsList] [<CommonParameters>]
```

Description

This command is designed to present a console-based version of a world clock. You provide a hashtable of locations and their respective time zones and the command will write a custom object to the pipeline. Be aware that TimeZone names may vary depending on the .NET Framework version. You may need to enumerate using a command like [System.TimeZoneInfo]::GetSystemTimeZones().ID or the Get-TZList command.

A Note on Formatting:

Normally, a PowerShell command should write an object to the pipeline and then you could use Format-Table or Format-List as you wanted. Those commands will continue to work. However, given the way this command writes to the pipeline, that is with dynamically generated properties, it is difficult to create the usual format ps1xml file. To provide some nicer formatting this command has optional parameters to help your format the output. Note that even though it may look like a table, the output object will be a string.

This command was added in v2.3.0.

Examples

Example 1

```
PS C:\> Get-MyTimeInfo  
  
Now           : 3/26/2025 11:27:14 AM  
Home          : 3/26/2025 11:27:14 AM  
UTC           : 3/26/2025 3:27:14 PM  
Singapore     : 3/26/2025 11:27:14 PM  
Seattle       : 3/26/2025 8:27:14 AM  
Stockholm     : 3/26/2025 4:27:14 PM  
IsDaylightSavings : True
```

The default output is a custom object with each timezone as a property.

Example 2

```
PS C:\> Get-MyTimeInfo -AsList

Now: 03/26/2025 11:28:29
UTC: 03/26/2025 15:28:29

Home           : 3/26/2025 11:28:29 AM
Singapore      : 3/26/2025 11:28:29 PM
Seattle        : 3/26/2025 8:28:29 AM
Stockholm      : 3/26/2025 4:28:29 PM
IsDaylightSavings : True
```

Get current time info formatted as a list. You can also try the AsTable parameter.

Example 3

```
PS C:\> $loc = [ordered]@{"Hong Kong"="China Standard Time";Honolulu="Hawaiian Standard Time";Mumbai = "India Standard Time"}
PS C:\> Get-MyTimeInfo -Locations $loc -ft

Now: 03/26/2025 11:29:33
UTC: 03/26/2025 15:29:33

Home           Hong Kong           Honolulu           Mumbai           DaylightSavings
-----
3/26/2025 11:29:33 AM 3/26/2025 11:29:33 PM 3/26/2025 5:29:33 AM 3/26/2025 8:59:33 PM True
```

Using a custom location hashtable, get time zone information formatted as a table. This example is using the -ft alias for the AsTable parameter. Even though this is formatted as a table the actual output is a string.

Example 5

```
PS C:\> Get-MyTimeInfo -Locations ([ordered]@{"Seattle"="Pacific Standard time";"New Zealand" = "New Zealand Standard Time"}) -HomeTimeZone "central standard time" | Select Now,Home,Seattle,'New Zealand'

Now           Home           Seattle           New Zealand
---
3/26/2025 11:30:36 AM 3/26/2025 10:30:36 AM 3/26/2025 8:30:36 AM 3/27/2025 4:30:36 AM
```

This is a handy command when traveling and your laptop is using a locally derived time and you want to see the time in other locations. It is recommended that you set a PSDefaultParameter value for the HomeTimeZone parameter in your PowerShell profile.

Parameters

-Locations

Use an ordered hashtable of location names and timezones. You can find timezones with the Get-TimeZone cmdlet or through the .NET Framework with an expression like

```
[System.TimeZoneinfo]::GetSystemTimeZones()
```

The hashtable key should be the location or city name and the value should be the time zone ID. Be careful as it appears time zone IDs are case-sensitive.

The default value is:

```
[ordered]@{
    Singapore = "Singapore Standard Time";
    Seattle    = "Pacific Standard Time";
    Stockholm  = "Central Europe Standard Time";
}
```

You might want to define a default value in `$PSDefaultParameterValues` with your own defaults.

It is recommended you limit this hashtable to no more than 5 locations, especially if you want to format the results as a table.

```
Type: OrderedDictionary
Parameter Sets: (All)
Aliases:

Required: False
Position: 1
Default value: see note
Accept pipeline input: False
Accept wildcard characters: False
```

-HomeTimeZone

Specify the timezone ID of your home location. You might want to set this as a `PSDefaultParameterValue`

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: Eastern Standard Time
Accept pipeline input: False
Accept wildcard characters: False
```

-DateTime

Specify the datetime value to use. The default is now.

```
Type: DateTime
Parameter Sets: (All)
Aliases:
```

```
Required: False
Position: Named
Default value: $(Get-Date)
Accept pipeline input: False
Accept wildcard characters: False
```

-AsTable

Display the results as a formatted table. This parameter has an alias of ft.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: ft

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

-AsList

Display the results as a formatted list. This parameter has an alias of fl.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: fl

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

Datetime

Outputs

myTimeInfo

System.String

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-TimeZone

Get-MyVariable

Synopsis

Get all user-defined variables.

Syntax

```
Get-MyVariable [[-Scope] <String>] [-NoTypeInfoInformation] [<CommonParameters>]
```

Description

This function will return all variables not defined by PowerShell or by this function itself. The default is to return all user-created variables from the global scope but you can also specify a scope such as script, local, or a number 0 through 5. The command will also display the value type for each variable. If you want to suppress this output use the -NoTypeInfoInformation switch.

Examples

Example 1

```
PS C:\> Get-MyVariable

Name Value                                     Type
----
a     bits                                     ServiceController
dt    10/22/2020 10:49:38 AM DateTime
foo   123                                       Int32
r     {1, 2, 3, 4...}                           Object[]
...
```

Depending on the value and how PowerShell chooses to display it, you may not see the type.

Example 2

```
PS C:\> Get-MyVariable | Select-Object name,type

Name Type
----
a     ServiceController
dt    DateTime
foo   Int32
r     Object[]
```

Example 3

```
PS C:\> Get-MyVariable | Export-Clixml myvar.xml
PS C:\> import-clixml .\myvar.xml |
ForEach-Object {set-variable -Name $_.name -Value $_.value}
```

You can then import this XML file in another session to restore these variables.

Example 4

```
PS C:\> function foo {
    c:\scripts\Get-MyVariable2.ps1;
    $a=4;$b=2;$c=$a*$b;
    Get-MyVariable -NoTypeInfoInformation -scope 1 -verbose;
    $c
}

PS C:\> foo
VERBOSE: Getting system defined variables
VERBOSE: Found 49
VERBOSE: Getting current variables in 1 scope
VERBOSE: Found 27
VERBOSE: Filtering variables

Name                                Value
----                                -
a                                    4
b                                    2
c                                    8
VERBOSE: Finished getting my variables
8
```

This sample function dot sources the script with this function. Within the function, Get-MyVariable is called specifying scope 1, or the parent scope. Scope 0 would be the scope of the Get-MyVariable function. Here's the result.

Example 5

```
PS C:\> Get-MyVariable | where {$_.type -eq "Scriptblock"} |
Select-Object name,value

Name                                Value
----                                -
bigp                                ps | where {$_.ws -gt 100mb}
dirt                                Param(\[string\]$Path=$env:temp) Get-C...
disk                                Param (\[string\]$computername=$env:co...
run                                 gsv | where {$_.status -eq "running"}
up                                  Param(\[string\]$computername=$env:com...
```

Get all my variables that are script blocks.

Parameters

-Scope

The scope to query. The default is the Global scope but you can also specify Local, Script, Private or a number between 0 and 3 where 0 is the current scope, 1 is the parent scope, 2 is the grandparent scope, and so on.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 1
Default value: Global
Accept pipeline input: False
Accept wildcard characters: False
```

-NoTypeInfoInformation

If specified, suppress the type information for each variable value.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

None

Outputs

System.Management.Automation.PSVariable

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

An earlier version of this function is described at <http://jdhitsolutions.com/blog/2012/05/get-my-variable-revisited>

Related Links

Get-Variable

About_Variables

About_Scope

Get-ParameterInfo

Synopsis

Retrieve command parameter information.

Syntax

```
Get-ParameterInfo [-Command] <String> [-Parameter <String>]  
[<CommonParameters>]
```

Description

Using Get-Command, this function will return information about parameters for any loaded cmdlet or function. The common parameters like Verbose and ErrorAction are omitted. Get-ParameterInfo returns a custom object with the most useful information an administrator might need to know. See examples.

Examples

Example 1

```
PS C:\> Get-ParameterInfo Export-Clixml  
  
ParameterSet: __AllParameterSets  
  
Name           Aliases           Mandatory Position Type  
----           -  
Depth           False            Named    System.Int32  
Encoding         False            Named    System.Text.Encoding  
Force            False            Named    System.Management.Auto...  
InputObject      True             Named    System.Management.Auto...  
NoClobber        NoOverwrite       False    Named    System.Management.Auto...  
  
ParameterSet: ByLiteralPath  
  
Name           Aliases           Mandatory Position Type  
----           -  
LiteralPath     PSPath,LP         True     Named    System.String  
  
ParameterSet: ByPath  
  
Name           Aliases           Mandatory Position Type  
----           -  
Path            True              0        System.String
```

Return parameter information for Export-Clixml using the default table view.

Example 2

```
PS C:\> Get-ParameterInfo mkdir | Select-Object Name,Type,Position,ParameterSet
```

| Name | Type | Position | ParameterSet |
|------------|--|----------|-------------------|
| Credential | System.Management.Automation.PSCredential | Named | __AllParameter... |
| Force | System.Management.Automation.SwitchParameter | Named | __AllParameter... |
| Value | System.Object | Named | __AllParameter... |
| Path | System.String[] | 0 | nameSet |
| Name | System.String | Named | nameSet |
| Path | System.String[] | 0 | pathSet |

Get selected parameter information for the mkdir command.

Example 3

```
PS C:\> Get-ParameterInfo Test-WSMan | Format-List
```

ParameterSet: __AllParameterSets

```
Name           : ComputerName
Aliases        : cn
Mandatory      : False
IsDynamic      : False
Position       : 0
Type           : System.String
ValueFromPipeline : True
ValueFromPipelineByPropertyName : False

Name           : Authentication
Aliases        : auth,am
Mandatory      : False
IsDynamic      : False
Position       : Named
Type           : Microsoft.WSMan.Management.AuthenticationMechanism
ValueFromPipeline : False
ValueFromPipelineByPropertyName : False

Name           : CertificateThumbprint
Aliases        :
Mandatory      : False
IsDynamic      : False
Position       : Named
Type           : System.String
ValueFromPipeline : False
ValueFromPipelineByPropertyName : False

Name           : Credential
Aliases        : cred,c
Mandatory      : False
IsDynamic      : False
Position       : Named
Type           : System.Management.Automation.PSCredential
ValueFromPipeline : False
ValueFromPipelineByPropertyName : True
```

```

ParameterSet: ComputerName

Name           : ApplicationName
Aliases        :
Mandatory      : False
IsDynamic      : False
Position       : Named
Type           : System.String
ValueFromPipeline      : False
ValueFromPipelineByPropertyName : False

Name           : Port
Aliases        :
Mandatory      : False
IsDynamic      : False
Position       : Named
Type           : System.Int32
ValueFromPipeline      : False
ValueFromPipelineByPropertyName : False

Name           : UseSSL
Aliases        :
Mandatory      : False
IsDynamic      : False
Position       : Named
Type           : System.Management.Automation.SwitchParameter
ValueFromPipeline      : False
ValueFromPipelineByPropertyName : False

```

Get all parameters from Test-WSMan and display details as a list.

Example 4

```

PS C:\> Get-ParameterInfo -Command Get-Counter -Parameter computername

ParameterSet: __AllParameterSets

Name           : computername
Aliases        : Cn
Mandatory      : False
IsDynamic      : False
Position       : Named
Type           : System.String[]
ValueFromPipeline      : False
ValueFromPipelineByPropertyName : False

```

Get details on the Computername parameter of the Get-Counter cmdlet.

Parameters

-Command

The name of a cmdlet or function. The parameter has an alias of Name.

```
Type: String
Parameter Sets: (All)
Aliases: name

Required: True
Position: 1
Default value: None
Accept pipeline input: True (ByPropertyName, ByValue)
Accept wildcard characters: False
```

-Parameter

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.String

Outputs

PSPParameterInfo

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-Command

[Get-CommandSyntax](#)

Get-PathVariable

Synopsis

Get information from locations in %PATH%.

Syntax

```
Get-PathVariable [[-Scope] <String>] [<CommonParameters>]
```

Description

Use this command to test the locations specified in the %PATH% environment variable. On Windows platforms, you can distinguish between settings set per machine and those set per user. On non-Windows platforms, the scope will be Process.

Examples

Example 1

```
PS C:\> Get-PathVariable
```

| Scope | UserName | Path | Exists |
|---------|----------|---|--------|
| User | Jeff | C:\Program Files\kdiff3 | True |
| User | Jeff | C:\Program Files (x86)\Bitvise SSH Client | True |
| User | Jeff | C:\Program Files\OpenSSH | True |
| ... | | | |
| Machine | Jeff | C:\WINDOWS | True |
| Machine | Jeff | C:\WINDOWS\system32 | True |
| Machine | Jeff | C:\WINDOWS\System32\Wbem | True |
| ... | | | |

Example 2

```
PS /home/jeff> Get-PathVariable | Where-Object {-Not $_.exists}
```

| | |
|--------------|-------------|
| Scope | : Process |
| Computername | : Bovine320 |
| UserName | : jeff |
| Path | : /snap/bin |
| Exists | : False |

This example is on a Linux platform, finding locations that don't exist or can be verified. You could run the same command on Windows.

Parameters

-Scope

On Windows platforms you can distinguish between Machine and User specific settings.

```
Type: String
Parameter Sets: (All)
Aliases:
Accepted values: All, User, Machine

Required: False
Position: 0
Default value: All
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

EnvPath

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-PowerShellEngine

Synopsis

Get the path to the current PowerShell engine.

Syntax

```
Get-PowerShellEngine [-Detail]
```

Description

Use this command to find the path to the PowerShell executable, or engine that is running your current session. The default is to provide the path only. But you can also get detailed information

Examples

Example 1

```
PS C:\> Get-PowerShellEngine
C:\WINDOWS\System32\WindowsPowerShell\v1.0\powershell.exe
```

Example 2

```
PS C:\> Get-PowerShellEngine -detail

Path           : C:\WINDOWS\System32\WindowsPowerShell\v1.0\powershell.exe
FileVersion    : 10.0.15063.0 (WinBuild.160101.0800)
PSVersion      : 5.1.15063.502
ProductVersion : 10.0.15063.0
Edition        : Desktop
Host           : Visual Studio Code Host
Culture        : en-US
Platform       :
```

This result is from running in the Visual Studio Code integrated PowerShell terminal.

Example 3

```
PS C:\> Get-PowerShellEngine -detail

Path           : C:\Program Files\PowerShell\7\pwsh.exe
FileVersion    : 7.5.0.500
PSVersion      : 7.5.0
ProductVersion : 7.5.0 SHA: 99dab561892364d82d4965068f7f8b175e768b1b+99dab561892364d82d4965068f7f8b175e768b1b
```

```
Edition      : Core
Host         : ConsoleHost
Culture      : en-US
Platform     : Win32NT
```

This result is from running in a PowerShell 7 session on Windows 11.

Parameters

-Detail

Include additional information. Not all properties may have values depending on operating system and PowerShell version.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

Inputs

Outputs

System.String

PSCustomObject

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

\$PSVersionTable

\$Host

Get-Process

Get-PSAnsiFileMap

Synopsis

Display the PSAnsiFileMap.

Syntax

```
Get-PSAnsiFileMap [<CommonParameters>]
```

Description

Use this command to display the PSAnsiFileMap global variable. The Ansi pattern will be shown using the pattern.

Examples

Example 1

```
PS C:\> Get-PSAnsiFileMap

Description Pattern                ANSI
-----
PowerShell \.((ps(d|m)?1)|(ps1xml))$ `e[38;2;252;127;12m`e[38;2;252;127;12m
Text      \.((txt)|(log)|(htm(1)?))$ `e[38;2;58;120;255m`e[38;2;58;120;255m
...
```

The output will display the ANSI sequence using the sequence itself. The escape character will be based on the version of PowerShell you are using. This example shows output from PowerShell 7.

Parameters

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

PSAnsiFileEntry

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Set-PSAnsiFileMap](#)

Get-PSLocation

Synopsis

Get common location values.

Syntax

```
Get-PSLocation [<CommonParameters>]
```

Description

This command will write an object to the pipeline that displays the values of common file locations. You might find this helpful when scripting cross-platform.

Examples

Example 1

```
PS C:\> Get-PSLocation

Temp      : C:\Users\Jeff\AppData\Local\Temp\
Home      : C:\Users\Jeff\Documents
Desktop   : C:\Users\Jeff\Desktop
PowerShell : C:\Users\Jeff\Documents\WindowsPowerShell
PSHome    : C:\Windows\System32\WindowsPowerShell\v1.0
```

Results on a Windows system.

Example 2

```
PS C:\> Get-PSLocation

Temp      : /tmp/
Home      : /home/jeff
Desktop   :
PowerShell : /home/jeff/.config/powershell
PSHome    : /opt/microsoft/powershell/7
```

Results on a Linux system running PowerShell.

Parameters

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

PSLocation

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-Location

Set-Location

Get-PSProfile

Synopsis

Get PowerShell profile locations.

Syntax

```
Get-PSProfile [<CommonParameters>]
```

Description

This command is designed for Windows-based systems to show all possible PowerShell profile scripts. Including those for VS Code and the PowerShell ISE.

Examples

Example 1

```
PS C:\> Get-PSProfile

Name: PowerShell

Scope      Path                                                                 Exists
-----
AllUsersCurrentHost C:\Program Files\PowerShell\7\Microsoft.PowerShell_profile.ps1 False
AllUsersAllHosts    C:\Program Files\PowerShell\7\profile.ps1                        False
CurrentUserAllHosts C:\Users\Jeff\Documents\PowerShell\profile.ps1                  True
CurrentUserCurrentHost C:\Users\Jeff\Documents\PowerShell\Microsoft.PowerShell_profile.ps1 True

Name: Windows PowerShell

Scope      Path                                                                 Exists
-----
AllUsersCurrentHost C:\WINDOWS\System32\WindowsPowerShell\v1.0\Microsoft.PowerShell_profile.ps1 True
AllUsersAllHosts    C:\WINDOWS\System32\WindowsPowerShell\v1.0\profile.ps1          True
CurrentUserAllHosts C:\Users\Jeff\Documents\WindowsPowerShell\profile.ps1          True
CurrentUserCurrentHost C:\Users\Jeff\Documents\WindowsPowerShell\Microsoft.PowerShell_profile.ps1 True

Name: VSCode PowerShell

Scope      Path                                                                 Exists
-----
CurrentUserCurrentHost C:\Users\Jeff\Documents\PowerShell\Microsoft.VSCode_profile.ps1 True
AllUsersCurrentHost    C:\Program Files\PowerShell\7\Microsoft.VSCode_profile.ps1      False
...
```

The command has a default formatted table view.

Example 2

```
PS C:\> Get-PSProfile | Where-Object Exists | Format-List

Name: PowerShell

Scope      : CurrentUserAllHosts
Path       : C:\Users\Jeff\Documents\PowerShell\profile.ps1
Exists     : True
LastModified : 9/9/2020 2:35:45 PM

Scope      : CurrentUserCurrentHost
Path       : C:\Users\Jeff\Documents\PowerShell\Microsoft.PowerShell_profile.ps1
Exists     : True
LastModified : 9/9/2020 2:03:44 PM

Name: Windows PowerShell

Scope      : AllUsersCurrentHost
Path       : C:\WINDOWS\System32\WindowsPowerShell\v1.0\Microsoft.PowerShell_profile.ps1
Exists     : True
LastModified : 10/9/2020 4:08:35 PM
...
```

The command has a default list view.

Parameters

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

PSProfilePath

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-PSScriptTools

Synopsis

Get a summary of PSScriptTools commands.

Syntax

```
Get-PSScriptTools [-Verb <String>] [<CommonParameters>]
```

Description

You can use this command to get a summary display of functions included in the PSScriptTools module. Use the -Verb parameter to filter the output.

Examples

Example 1

```
PS C:\> Get-PSScriptTools
```

```

_ _ _ _ _
| _ \ _ / _ | _ _ ( _ ) _ _ | _ _ | _ _ | _ _
| _ \ _ \ _ \ _ | ' _ | ' _ \ _ | / _ \ _ \ ( _ <
| _ | _ / _ \ _ | _ | . _ \ _ | _ \ _ \ _ / _ /
| _ |
v3.0.0
```

Verb: Add

| Name | Alias | Synopsis |
|------------|-------|---------------------------------------|
| ---- | ----- | ----- |
| Add-Border | | Create a text border around a string. |

Verb: Compare

| Name | Alias | Synopsis |
|----------------|-------|-------------------------------------|
| ---- | ----- | ----- |
| Compare-Module | cmo | Compare PowerShell module versions. |

Verb: Convert

| Name | Alias | Synopsis |
|----------------------------|-------|--------------------------------------|
| ---- | ----- | ----- |
| Convert-CommandToHashtable | | Convert a PowerShell expression i... |
| Convert-EventLogRecord | clr | Convert EventLogRecords to struct... |
| Convert-HashtableString | | Convert a hashtable string into a... |
| Convert-HashtableToCode | | Convert a hashtable to a string r... |

...

The header is written to the host and not the pipeline.

Example 2

```
PS C:\> Get-PSScriptTools | Where alias
```

1. 在“开始”选项卡“文字”组中，单击“拼写和语法”按钮，如图 1-1-10 所示。

v3.0.0

Verb: Compare

| Name | Alias | Synopsis |
|----------------|-------|-------------------------------------|
| ----- | ----- | ----- |
| Compare-Module | cmo | Compare PowerShell module versions. |
| Compare-Script | csc | Compare PowerShell script versions. |

Verb: Convert

```

Name                Alias      Synopsis
----                -
Convert-EventLogRecord  clr       Convert EventLogRecords to structured...
Convert-HashtableToCode chc       Convert a hashtable to a string repre...
...
```

List commands with defined aliases in the PSScriptTools module.

Example 3

```
PS C:\> Get-PSScriptTools -Verb Select
```

[illegible]

v3.0.0

Verb:Select

| Name | Alias | Synopsis |
|---------------|--------|--------------------------------|
| ---- | ---- | ----- |
| Select-After | after | Select objects after a give... |
| Select-Before | before | Select objects before a giv... |
| Select-First | First | Select the first X number o... |
| Select-Last | Last | Select the last X number of... |
| Select-Newest | newest | Select the newest X number ... |
| Select-Oldest | oldest | Select the oldest X number .. |

Get all module commands that use the Select verb.

Parameters

-Verb

Filter commands based on a standard PowerShell verb.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

PSScriptTool

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-Command

Get-Module

[Open-PSScriptToolsHelp](#)

Get-PSScriptToolsTypeExtension

Synopsis

Get available custom type extensions

Syntax

```
Get-PSScriptToolsTypeExtension [[-TypeName] <String>] [<CommonParameters>]
```

Description

The PSScriptTools module includes several custom type extensions that you can import. These will add functionality to output of commands like Get-Process and Measure-Object. Use this command to get information about available extensions.

Examples

Example 1

```
PS C:\> Get-PSScriptToolsTypeExtension -TypeName *file*

TypeName      : System.IO.FileInfo
Description: Alias and script properties designed to extend the file object. There is also a PropertySet called AgeInfo.

MemberType  MemberName
-----
AliasProperty Created
AliasProperty Modified
AliasProperty Size
PropertySet AgeInfo
ScriptProperty SizeKB
ScriptProperty ModifiedAge
ScriptProperty CreatedAge
ScriptProperty SizeMB
```

The default behavior is to list all available extensions. You can filter the list by providing a wildcard pattern for the TypeName parameter.

Parameters

-TypeName

The name of the custom type extension set

```
Type: String
Parameter Sets: (All)
Aliases:
```

```
Required: False
Position: 0
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: True
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

System.String

Outputs

PSScriptToolsTypeExtension

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Import-PSScriptToolsTypeExtension](#)

Get-PSSessionInfo

Synopsis

Get details about the current PowerShell session.

Syntax

```
Get-PSSessionInfo [<CommonParameters>]
```

Description

This command will provide a snapshot of the current PowerShell session. The Runtime and Memory properties are defined by script so if you save the result to a variable, you will get current values every time you look at the variable.

Examples

Example 1

```
PS C:\> Get-PSSessionInfo

ProcessID      : 1112
Command        : "C:\Program Files\PowerShell\7\pwsh.exe" -noprofile
Host           : ConsoleHost
Started        : 4/9/2024 9:36:13 AM
PSVersion      : 7.1.3
Elevated        : True
Parent         : System.Diagnostics.Process (WindowsTerminal)
Runtime        : 00:31:26.2716486
MemoryMB       : 129
```

The Memory value is in MB. If running in a PowerShell console session, the Elevated value will be displayed in color.

Example 2

```
PS /home> Get-PSSessionInfo

ProcessID      : 71
Command        : pwsh
Host           : ConsoleHost
Started        : 04/09/2024 09:38:55
PSVersion      : 7.1.3
Elevated        : False
Parent         : System.Diagnostics.Process (bash)
Runtime        : 00:30:07.1669248
```

```
MemoryMB      : 133
```

The result from a Linux host.

Parameters

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

PSSessionInfo

Notes

This command has an alias of gsin.

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-Host

Get-Process

Get-PSUnique

Synopsis

Filter for unique objects.

Syntax

```
Get-PSUnique [-InputObject] <Object> [-Property <String[]>] [<CommonParameters>]
```

Description

You can use this command to filter for truly unique objects. That is, every property on every object is considered unique. Most things in PowerShell are already guaranteed to be unique, but you might import data from a CSV file with duplicate entries. Get-PSUnique can help filter.

This command works best with simple objects. Objects with nested objects as properties may not be properly detected. For complex objects, you might need to specify the property or properties to use for comparison.

Examples

Example 1

```
PS C:\> $clean = Import-CSV c:\data\newinfo.csv | Get-PSUnique
```

Import unique objects from a CSV file and save the results to a variable.

Parameters

-InputObject

Simple, objects. The flatter the better this command will work.

```
Type: Object
Parameter Sets: (All)
Aliases:

Required: True
Position: 1
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

-Property

Specify a property to use for the comparison.

```
Type: String[]
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

Object

Outputs

Object

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Compare-Object

Get-PSWho

Synopsis

Get PowerShell user summary information.

Syntax

```
Get-PSWho [-AsString] [<CommonParameters>]
```

Description

This command will provide a summary of relevant information for the current user in a PowerShell session. You might use this to troubleshoot an end-user problem running a script or command.

The default behavior is to write an object to the pipeline, but you can use the `-AsString` parameter to force the command to write a string. This makes it easier to use in your scripts with `Write-Verbose`.

Examples

Example 1

```
PS C:\> Get-PSWho

User           : PROSPERO\Jeff
Elevated        : True
Computersname   : PROSPERO
OperatingSystem : Microsoft Windows 11 Pro [64-bit]
OSVersion       : 10.0.26100
PSVersion       : 7.5.0
Edition         : Core
PSHost          : ConsoleHost
WSMan           : 3.0
ExecutionPolicy : RemoteSigned
Culture         : English (United States)
```

Example 2

```
PS /home/jhicks> Get-PSWho

User           : jeff
Elevated        : False
Computersname   : Desk01
OperatingSystem : Linux 5.4.72-microsoft-standard-WSL2 #1 SMP Wed Oct 28 23:40:43 UTC 2020
OSVersion       : Ubuntu 20.04.2 LTS
PSVersion       : 7.1.3
Edition         : Core
PSHost          : ConsoleHost
```

```
WSMan      : 3.0
ExecutionPolicy : Unrestricted
Culture     : Invariant Language (Invariant Country)
```

Parameters

-AsString

Write the summary object as a string. This can be useful when you want to save the information in a log file.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

Inputs

None

Outputs

PSWho

System.String

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Test-IsElevated](#)

[Get-CimInstance](#)

Get-ExecutionPolicy

\$PSVersionTable

Get-Host

Get-TypeConstructor

Synopsis

Get constructor details for a .NET type.

Syntax

```
Get-TypeConstructor [-TypeName] <Type> [<CommonParameters>]
```

Description

Often you need to create a new instance of a .NET type and you need to know what constructors are available. This function will return the constructors for a .NET type. The default output is formatted to display the kind of syntax you would use in your PowerShell code.

Examples

Example 1

```
PS C:\> Get-TypeConstructor System.Drawing.SolidBrush

[System.Drawing.SolidBrush]::new([System.Drawing.Color]$Color))
```

The default formatting will use color to highlight the parameter name you would need.

Example 2

```
PS C:\> Get-TypeConstructor diagnostics.process

[System.Diagnostics.Process]::new()
```

This type doesn't need any parameters to create a new instance.

Example 3

```
PS C:\> Get-TypeConstructor system.drawing.rectangle

[System.Drawing.Rectangle]::new([System.Int32]$X),
                                [System.Int32]$Y),
                                [System.Int32]$Width),
                                [System.Int32]$Height))

[System.Drawing.Rectangle]::new([System.Drawing.Point]$Location),[System.Drawing.Size]$Size))
```


Constructors with more than three parameters will be displayed in a list to make it easier to read.

Example 4

```
PS C:\> ctor int32
WARNING: No constructors found for Int32
```

The function has an alias of `ctor` for convenience. Note there is no period.

Parameters

-TypeName

Specify a .NET type name like `DateTime`

```
Type: Type
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

CommonParameters

This cmdlet supports the common parameters: `-Debug`, `-ErrorAction`, `-ErrorVariable`, `-InformationAction`, `-InformationVariable`, `-OutVariable`, `-OutBuffer`, `-PipelineVariable`, `-Verbose`, `-WarningAction`, and `-WarningVariable`. For more information, see [about_CommonParameters](#).

Inputs

None

Outputs

psTypeConstructor

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

[Get-TypeMember](#)

Get-TypeMember

Synopsis

Get type member information.

Syntax

member (Default)

```
Get-TypeMember [-TypeName] <Type> [-MemberType <String>] [<CommonParameters>]
```

static

```
Get-TypeMember [-TypeName] <Type> [-StaticOnly] [<CommonParameters>]
```

name

```
Get-TypeMember [-TypeName] <Type> -MemberName <String> [<CommonParameters>]
```

Description

This is an alternative to using Get-Member. Specify a type name to see a simple view of an object's members. The output will only show native members, including static methods, but not those added by PowerShell such as ScriptProperties. The command in this module includes custom format and type extensions. See help examples.

Examples

Example 1

```
PS C:\> Get-TypeMember DateTime
```

```
    Type: System.DateTime
```

| Name | MemberType | ResultType | IsStatic | IsEnum |
|-----------------|------------|------------|----------|--------|
| ----- | ----- | ----- | ----- | ----- |
| MaxValue | Field | datetime | True | |
| MinValue | Field | datetime | True | |
| Add | Method | DateTime | | |
| AddDays | Method | DateTime | | |
| AddHours | Method | DateTime | | |
| AddMilliseconds | Method | DateTime | | |
| AddMinutes | Method | DateTime | | |

```

AddMonths      Method      DateTime
AddSeconds     Method      DateTime
...
Date           Property    DateTime
Day            Property    Int32
DayOfWeek      Property    DayOfWeek      True
DayOfYear      Property    Int32
Hour           Property    Int32
Kind           Property    DateTimeKind      True
Millisecond     Property    Int32
Minute         Property    Int32
...

```

Static items will be shown in green. Enum properties will be shown in orange.

Example 2

```

PS C:\> Get-TypeMember DateTime -StaticOnly

Type: System.DateTime

Name      MemberType ResultType IsStatic IsEnum
----      -
MaxValue  Field      datetime    True
MinValue  Field      datetime    True
Compare   Method     Int32       True
DaysInMonth Method     Int32       True
Equals    Method     Boolean     True
FromBinary Method     DateTime    True
FromFileTime Method     DateTime    True
...

```

Example 3

```

PS C:\> Get-TypeMember system.io.fileinfo -MemberType Property

Type: System.IO.FileInfo

Name      MemberType ResultType IsStatic IsEnum
----      -
Attributes Property    FileAttributes      True
CreationTime Property    DateTime
CreationTimeUtc Property    DateTime
Directory  Property    DirectoryInfo
DirectoryName Property    String
Exists     Property    Boolean
Extension  Property    String
FullName   Property    String
...

```

Get only properties for System.IO.FileInfo.

Example 4

```
PS C:\> Get-TypeMember datetime -MemberName add* | Format-Table -view syntax
```

```
    Type: System.DateTime
```

| Name | ReturnType | Syntax |
|-----------------|------------|--------------------------------------|
| Add | DateTime | \$obj.Add([TimeSpan]value) |
| AddDays | DateTime | \$obj.AddDays([Double]value) |
| AddHours | DateTime | \$obj.AddHours([Double]value) |
| AddMicroseconds | DateTime | \$obj.AddMicroseconds([Double]value) |
| AddMilliseconds | DateTime | \$obj.AddMilliseconds([Double]value) |
| AddMinutes | DateTime | \$obj.AddMinutes([Double]value) |
| AddMonths | DateTime | \$obj.AddMonths([Int32]months) |
| AddSeconds | DateTime | \$obj.AddSeconds([Double]value) |
| AddTicks | DateTime | \$obj.AddTicks([Int64]value) |
| AddYears | DateTime | \$obj.AddYears([Int32]value) |

Use the custom table view to see method syntax.

Example 5

```
PS C:\> Get-TypeMember system.io.path -static | Where-Object MemberType -eq 'method' | Select-Object MethodSyntax
```

| Name | ReturnType | IsStatic | Syntax |
|-----------------------------|---------------|----------|--------------------------------|
| ChangeExtension | System.String | True | \$obj.ChangeExtension([Str... |
| Combine | System.String | True | { \$obj.Combine([String[]]p... |
| GetDirectoryName | System.String | True | \$obj.GetDirectoryName([St... |
| GetExtension | System.String | True | \$obj.GetExtension([String... |
| GetFileName | System.String | True | \$obj.GetFileName([String]... |
| GetFileNameWithoutExtension | System.String | True | \$obj.GetFileNameWithoutEx... |
| GetFullPath | System.String | True | \$obj.GetFullPath([String]... |
| ... | | | |

MethodSyntax is a custom property set for Get-TypeMember output.

Parameters

-TypeName

Specify a .NET type name like DateTime

```
Type: Type
Parameter Sets: (All)
Aliases:

Required: True
Position: 1
Default value: None
Accept pipeline input: False
```

```
Accept wildcard characters: False
```

-StaticOnly

Get only static members.

```
Type: SwitchParameter
Parameter Sets: static
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

-MemberType

Filter for a specific member type. Valid values are Property, Method, Event, and Field.

```
Type: String
Parameter Sets: member
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

-MemberName

Specify a member name.

```
Type: String
Parameter Sets: name
Aliases: Name

Required: True
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: True
```

CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about_CommonParameters](#).

Inputs

Outputs

psTypeMember

Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

Related Links

Get-Member

[Get-TypeConstructor](#)

Get-TZData

Synopsis

Get time zone details.

Syntax

```
Get-TZData [-TimeZoneArea] <String> [-Raw] [<CommonParameters>]
```

Description

This command uses a free and publicly available REST API offered by <http://worldtimeapi.org> to get information about a time zone. You can use Get-TZList to find an area and this command to display the details. The time zone area name is case-sensitive. The default is to write a custom object to the pipeline, but you also have an option of seeing the raw data that is returned from the API. On PowerShell Core, the raw data will be slightly different.

Note that if the site is busy you may get an error. If that happens, wait a minute and try again.

Examples

Example 1

```
PS C:\> Get-TZData Australia/Hobart
```

| Timezone | Label | Offset | DST | Time |
|------------------|-------|----------|------|------------------------|
| ----- | ----- | ----- | --- | ---- |
| Australia/Hobart | AEDT | 11:00:00 | True | 3/27/2025 2:44:24 AM`` |

```
Get time zone information for Hobart.
```

Example 2

```
```powershell
PS C:\> Get-TZData Asia/Tokyo -Raw
```

```
week_number : 13
utc_offset : +09:00
unixtime : 1743003902
timezone : Asia/Tokyo
dst_until :
dst_from :
dst : False
day_of_year : 86
day_of_week : 4
datetime : 2025-03-27T00:45:02.000000+09:00
abbreviation : JST
```



Get time zone information for Tokyo as a raw format.

## Example 3

```
PS C:\> Get-TZList Antarctica | Get-TZData | Sort-Object Offset
```

Timezone	Label	Offset	DST	Time
-----	-----	-----	---	----
Antarctica/Palmer	-03	-03:00:00	False	...26/2025 12:45:23 PM
Antarctica/Rothera	-03	-03:00:00	False	...26/2025 12:45:23 PM
Antarctica/Troll	+00	00:00:00	False	3/26/2025 3:45:23 PM
Antarctica/Mawson	+05	05:00:00	False	3/26/2025 8:45:23 PM
Antarctica/Vostok	+05	05:00:00	False	3/26/2025 8:45:23 PM
Antarctica/Davis	+07	07:00:00	False	...26/2025 10:45:23 PM
Antarctica/Casey	+08	08:00:00	False	...26/2025 11:45:23 PM
Antarctica/Macquarie	AEDT	11:00:00	True	3/27/2025 2:45:23 AM

Get all time zone areas in Antarctica and pipe them to Get-TZData to retrieve the details.

## Example 4

```
PS C:\> Get-TZData Europe/Rome | ConvertTo-LocalTime -Datetime "3/15/2020 4:00PM"
```

```
Saturday, March 15, 2025 11:00:00 AM
```

Convert the datetime in Rome to local time, which in this example is Eastern time.

## Parameters

### -Raw

Return raw, unformatted data. Due to the way PowerShell Core automatically wants to format date time strings, raw output had to be slightly adjusted.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -TimeZoneArea

Enter a timezone location like Pacific/Auckland. It is case sensitive. Use Get-TZList to retrieve a list of areas.

```
Type: String
```

```
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about\_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

## Inputs

### System.String

## Outputs

### PSCustomObject

### TimeZoneData

## Notes

Learn more about PowerShell:<https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Get-TZList](#)

# Get-TZList

## Synopsis

Get a list of time zone areas.

## Syntax

### zone (Default)

```
Get-TZList [-TimeZoneArea] <String> [<CommonParameters>]
```

### all

```
Get-TZList [-All] [<CommonParameters>]
```

## Description

This command uses a free and publicly available REST API offered by <http://worldtimeapi.org> to get a list of time zone areas. You can get a list of all areas or by geographic location. Use Get-TZData to then retrieve details. You must have Internet access for this command to work. Note that if the site is busy you may get an error. If that happens, wait a minute and try again.

## Examples

### Example 1

```
PS C:\> Get-TZList -all

Africa/Abidjan
Africa/Accra
Africa/Algiers
Africa/Bissau
Africa/Cairo
...
```

Get a list of all time zone areas.

### Example 2

```
PS C:\> Get-TZList Atlantic

Atlantic/Azores
Atlantic/Bermuda
```

```
Atlantic/Canary
Atlantic/Cape_Verde
Atlantic/Faroe
Atlantic/Madeira
Atlantic/Reykjavik
Atlantic/South_Georgia
Atlantic/Stanley
```

Get all time zone areas in the Atlantic region.

## Parameters

### -All

Get a list of all timezone areas

```
Type: SwitchParameter
Parameter Sets: all
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -TimeZoneArea

Specify a time zone region.

```
Type: String
Parameter Sets: zone
Aliases:
Accepted values: Africa, America, Antarctica, Asia, Atlantic, Australia, Europe, Indian, Pacific

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about\_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

## Inputs

### System.String

## Outputs

### string

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Get-TZData](#)

# Get-WhoIs

## Synopsis

Lookup WhoIS data for a given IPv4 address.

## Syntax

```
Get-WhoIs [-IPAddress] <String> [<CommonParameters>]
```

## Description

This command queries the ARIN database to lookup WhoIs information for a given IPv4 address.

## Examples

### Example 1

```
PS C:\> Get-WhoIs 208.67.222.222 | Select-Object -Property *

IP : 208.67.222.222
Name : OPENDNS-NET-1
RegisteredOrganization : Cisco OpenDNS, LLC
City : San Jose
StartAddress : 208.67.216.0
EndAddress : 208.67.223.255
NetBlocks : 208.67.216.0/21
Updated : 12/14/2021 8:28:33 PM
```

### Example 2

```
PS C:\> '1.1.1.1','8.8.8.8','208.67.222.222' | Get-WhoIs | Select Name,IP,RegisteredOrganization

Name IP RegisteredOrganization
---- -
APNIC-1 1.1.1.1 Asia Pacific Network Information Centre
GOGL 8.8.8.8 Google LLC
OPENDNS-NET-1 208.67.222.222 Cisco OpenDNS, LLC
```

## Parameters

### -IPAddress

Enter a valid IPV4 address to lookup with WhoIs. It is assumed all of the octets are less than 254.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByPropertyName, ByValue)
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### System.String

## Outputs

### WhoIsResult

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

Invoke-RestMethod

# Get-WindowsVersion

## Synopsis

Get Windows version information.

## Syntax

```
Get-WindowsVersion [[-Computername] <String[]>] [-Credential <PSCredential>]
[-UseSSL] [-ThrottleLimit <Int32>] [-Authentication <String>] [<CommonParameters>]
```

## Description

This is a PowerShell version of the winver.exe utility. This command uses PowerShell remoting to query the registry on a remote machine to retrieve Windows version information. The parameters are the same as in Invoke-Command.

If you are querying the local computer, all other parameters will be ignored.

This command is an alternative to using Get-CimInstance and querying the Win32\_OperatingSystem.

## Examples

### Example 1

```
PS C:\> Get-WindowsVersion
 Computername: PROSPERO

ProductName EditionID Release Build InstalledUTC

Microsoft Windows 11 Pro Professional 24H2 26100 6/17/2024 1:30:52 AM
```

Query the local host.

### Example 2

```
PS C:\> Get-WindowsVersion -Computername srv1,srv2,win10 -Credential $art

 Computername: WIN10

ProductName EditionID Release Build InstalledUTC

Microsoft Windows 10 EnterpriseEval 22H2 19045 2/10/2025 2:48:00 PM
Enterprise

 Computername: SRV1
```



```

ProductName EditionID Release Build InstalledUTC

Microsoft Windows Server 2019 ServerStandardEval 17763 2/10/2025 2:48:01 PM
Standard

 Computername: SRV2

ProductName EditionID Release Build InstalledUTC

Microsoft Windows Server 2019 ServerStandardEval 17763 2/10/2025 2:48:06 PM
Standard

```

Get Windows version information from remote computers using an alternate credential.

## Example 3

```

PS C:\> Get-WindowsVersion -Computername Dom1 | Select-Object *

ProductName : Microsoft Windows Server 2019 Standard
ReleaseVersion :
EditionID : ServerStandard
ReleaseID : 1809
Build : 17763.253
Branch : rs5_release
InstalledUTC : 2/10/2025 2:39:17 PM
Computername : DOM1

```

## Parameters

### -Computername

Specifies the computers on which the command runs. The default is the local computer.

When you use the ComputerName parameter, Windows PowerShell creates a temporary connection that is used only to run the specified command and is then closed. If you need a persistent connection, use the Session parameter.

Type the NETBIOS name, IP address, or fully qualified domain name of one or more computers in a comma-separated list. To specify the local computer, type the computer name, localhost, or a dot (.).

To use an IP address in the value of ComputerName , the command must include the Credential parameter. Also, the computer must be configured for HTTPS transport or the IP address of the remote computer must be included in the WinRM TrustedHosts list on the local computer. For instructions for adding a computer name to the TrustedHosts list, see "How to Add a Computer to the Trusted Host List" in about\_Remote\_Troubleshooting.

On Windows Vista and later versions of the Windows operating system, to include the local computer in the value of ComputerName, you must open Windows PowerShell by using the Run as administrator option.

```

Type: String[]
Parameter Sets: (All)
Aliases:

```

```
Required: False
Position: 1
Default value: $env:COMPUTERNAME
Accept pipeline input: True (ByPropertyName, ByValue)
Accept wildcard characters: False
```

## -Credential

Specifies a user account that has permission to perform this action. The default is the current user.

Type a user name, such as User01 or Domain01\User01. Or, enter a PSCredential object, such as one generated by the Get-Credential cmdlet. If you type a user name, this cmdlet prompts you for a password.

```
Type: PSCredential
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -UseSSL

Indicates that this cmdlet uses the Secure Sockets Layer (SSL) protocol to establish a connection to the remote computer. By default, SSL is not used.

WS-Management encrypts all Windows PowerShell content transmitted over the network. The UseSSL parameter is an additional protection that sends the data across an HTTPS, instead of HTTP.

If you use this parameter, but SSL is not available on the port that is used for the command, the command fails.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## -ThrottleLimit

Specifies the maximum number of concurrent connections that can be established to run this command. If you omit this parameter or enter a value of 0, the default value, 32, is used.

The throttle limit applies only to the current command, not to the session or to the computer.

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: 0
Accept pipeline input: False
Accept wildcard characters: False
```

## -Authentication

Specifies the mechanism that is used to authenticate the user's credentials. The acceptable values for this parameter are:

- Default
- Basic
- Credssp
- Digest
- Kerberos
- Negotiate
- NegotiateWithImplicitCredential

The default value is Default.

CredSSP authentication is available only in Windows Vista, Windows Server 2008, and later versions of the Windows operating system.

For information about the values of this parameter, see the description of the AuthenticationMechanismEnumeration (<http://go.microsoft.com/fwlink/?LinkID=144382>) in the Microsoft Developer Network (MSDN) library.



Credential Security Support Provider (CredSSP) authentication, in which the user's credentials are passed to a remote computer to be authenticated, is designed for commands that require authentication on more than one resource, such as accessing a remote network share. This mechanism increases the security risk of the remote operation. If the remote computer is compromised, the credentials that are passed to it can be used to control the network session.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: Default
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about\_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

## Inputs

### System.String

## Outputs

### WindowsVersion

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Get-WindowsVersionString](#)

WinVer.exe

SystemInfo.exe

Invoke-Command

# Get-WindowsVersionString

## Synopsis

Get Windows version information.

## Syntax

```
Get-WindowsVersionString [[-Computername] <String[]>]
[-Credential <PSCredential>] [-UseSSL] [-ThrottleLimit <Int32>]
[-Authentication <String>] [<CommonParameters>]
```

## Description

This is a PowerShell version of the winver.exe utility. This command uses PowerShell remoting to query the registry on a remote machine to retrieve Windows version information. The parameters are the same as in Invoke-Command. The command writes a string of version information.

If you are querying the local computer, all other parameters will be ignored.

## Examples

### Example 1

```
PS C:\> Get-WindowsVersionString -Computername win10 -credential company\artd
WIN10 Microsoft Windows 10 Enterprise Version Enterprise (OS Build 19045.5608)
```

Get a string version of Windows version information from a remote computer and use an alternate credential.

### Example 2

```
PS C:\> Get-WindowsVersionString
PROSPERO Microsoft Windows 11 Pro Version Professional (OS Build 26100.3613)
```

Get version information for the local host.

## Parameters

### -Computername

Specifies the computers on which the command runs. The default is the local computer.

When you use the ComputerName parameter, Windows PowerShell creates a temporary connection that is used only to run the specified command and is then closed. If you need a persistent connection, use the

Session parameter.

Type the NETBIOS name, IP address, or fully qualified domain name of one or more computers in a comma-separated list. To specify the local computer, type the computer name, localhost, or a dot (.).

To use an IP address in the value of `ComputerName`, the command must include the `Credential` parameter. Also, the computer must be configured for HTTPS transport or the IP address of the remote computer must be included in the WinRM TrustedHosts list on the local computer. For instructions for adding a computer name to the TrustedHosts list, see "How to Add a Computer to the Trusted Host List" in `about_Remote_Troubleshooting`.

On Windows Vista and later versions of the Windows operating system, to include the local computer in the value of `ComputerName`, you must open Windows PowerShell by using the Run as administrator option.

```
Type: String[]
Parameter Sets: (All)
Aliases:

Required: False
Position: 1
Default value: $env:COMPUTERNAME
Accept pipeline input: True (ByPropertyName, ByValue)
Accept wildcard characters: False
```

## -Credential

Specifies a user account that has permission to perform this action. The default is the current user.

Type a user name, such as `User01` or `Domain01\User01`. Or, enter a `PSCredential` object, such as one generated by the `Get-Credential` cmdlet. If you type a user name, this cmdlet prompts you for a password.

```
Type: PSCredential
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -UseSSL

Indicates that this cmdlet uses the Secure Sockets Layer (SSL) protocol to establish a connection to the remote computer. By default, SSL is not used.

WS-Management encrypts all Windows PowerShell content transmitted over the network. The `UseSSL` parameter is an additional protection that sends the data across an HTTPS, instead of HTTP.

If you use this parameter, but SSL is not available on the port that is used for the command, the command fails.

```
Type: SwitchParameter
Parameter Sets: (All)
```

```
Aliases:
Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## -ThrottleLimit

Specifies the maximum number of concurrent connections that can be established to run this command. If you omit this parameter or enter a value of 0, the default value, 32, is used.

The throttle limit applies only to the current command, not to the session or to the computer.

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: 0
Accept pipeline input: False
Accept wildcard characters: False
```

## -Authentication

Specifies the mechanism that is used to authenticate the user's credentials. The acceptable values for this parameter are:

- Default
- Basic
- Credssp
- Digest
- Kerberos
- Negotiate
- NegotiateWithImplicitCredential

The default value is Default.

CredSSP authentication is available only in Windows Vista, Windows Server 2008, and later versions of the Windows operating system.

For information about the values of this parameter, see the description of the AuthenticationMechanismEnumeration (<http://go.microsoft.com/fwlink/?LinkID=144382>) in the Microsoft Developer Network (MSDN) library.



Credential Security Support Provider (CredSSP) authentication, in which the user's credentials are passed to a remote computer to be authenticated, is designed for commands that

require authentication on more than one resource, such as accessing a remote network share. This mechanism increases the security risk of the remote operation. If the remote computer is compromised, the credentials that are passed to it can be used to control the network session.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: Default
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about\_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

## Inputs

### System.String

## Outputs

### System.String

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Get-WindowsVersion](#)

Winver.exe



# Import-PSScriptToolsTypeExtension

## Synopsis

Import a custom type extension file

## Syntax

```
Import-PSScriptToolsTypeExtension [[-TypeName] <String>] [-WhatIf] [-Confirm] [<CommonParameters>]
```

## Description

Use this command to import a PSScriptTools type extension file. This will add functionality to output of commands like Get-Process and Measure-Object. You can pipe output from Get-PSScriptToolsTypeExtension to this command.

## Examples

### Example 1

```
PS C:\> Import-PSScriptToolsTypeExtension
```

Import all available custom type extensions.

### Example 2

```
PS C:\> Import-PSScriptToolsTypeExtension -typename *file*
```

Import all custom type extensions that have "file" in the name.

## Parameters

### -Confirm

Prompts you for confirmation before running the cmdlet.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: cf

Required: False
Position: Named
Default value: None
```

```
Accept pipeline input: False
Accept wildcard characters: False
```

## -TypeName

The TypeName of the custom type extension set

```
Type: String
Parameter Sets: (All)
Aliases: Type

Required: False
Position: 0
Default value: None
Accept pipeline input: True (ByPropertyName, ByValue)
Accept wildcard characters: True
```

## -WhatIf

Shows what would happen if the cmdlet runs. The cmdlet is not run.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: wi

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### System.String

## Outputs

### None

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Get-PSScriptToolsTypeExtension](#)

# Invoke-InputBox

## Synopsis

Launch a graphical input box.

## Syntax

### plain (Default)

```
Invoke-InputBox [-Title <String>] [-Prompt <String>]
[-BackgroundColor <String>] [<CommonParameters>]
```

### secure

```
Invoke-InputBox [-Title <String>] [-Prompt <String>] [-AsSecureString]
[-BackgroundColor <String>] [<CommonParameters>]
```

## Description

Use this command as a graphical replacement for Read-Host. The command will write either a string or a secure string to the pipeline. You can customize the prompt, title and background color.

This command requires a Windows platform.

## Examples

### Example 1

```
PS C:\> $name == Invoke-InputBox -prompt "Enter a user name" -title "New User"
```

Display an graphical inputBox with a given prompt and title. The entered value will be saved to \$name.

### Example 2

```
PS C:\> $pass == Invoke-InputBox -prompt "Enter a new password" -title "New User" -asSecureString -background red
```

Get a secure string value from the user. This example also changes the form background to red.

## Parameters

### -AsSecureString

Use to mask the entry and return a secure string.

```
Type: SwitchParameter
Parameter Sets: secure
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -BackgroundColor

Set the form background color. You can use a value like 'red' or a '#c0c0c0'.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: White
Accept pipeline input: False
Accept wildcard characters: False
```

### -Prompt

Enter a prompt. No more than 50 characters.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: "Please enter a value"
Accept pipeline input: False
Accept wildcard characters: False
```

### -Title

Enter the title for the input box. No more than 25 characters.

```
Type: String
Parameter Sets: (All)
```

```
Aliases:
Required: False
Position: Named
Default value: "User Input"
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### None

## Outputs

### System.String

### System.Security.SecureString

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

Read-Host

[New-WPFMessageBox](#)

# Join-Hashtable

## Synopsis

Combine two hashtables into one.

## Syntax

```
Join-Hashtable [[-First] <Hashtable>] [[-Second] <Hashtable>] [-Force]
[<CommonParameters>]
```

## Description

This command will combine two hashtables into a single hashtable. Normally this is as easy as `$hash1+$hash2`. But if there are duplicate keys, this will fail. Join-Hashtable will test for duplicate keys. If any of the keys from the first, or primary hashtable are found in the secondary hashtable, you will be prompted for which to keep. Or you can use `-Force` which will always keep the conflicting key from the first hashtable.

The original hashtables will not be modified.

## Examples

### Example 1

```
PS C:\> $a=@{Name="Jeff";Count=3;Color="Green"}
PS C:\> $b=@{Computer="HAL";Enabled=$True;Year=2020;Color="Red"}
PS C:\> Join-Hashtable $a $b
Duplicate key Color
A Green
B Red
Which key do you want to KEEP \[AB\]?: A

Name Value
---- -
Year 2020
Name Jeff
Enabled True
Color Green
Computer HAL
Count 3
```

### Example 2

```
PS C:\>$c == Join-Hashtable $a $b -force
PS C:\> $c
```

```
Name Value
---- -
```

```
Year 2020
Name Jeff
Enabled True
Color Green
Computer HAL
Count 3
```

## Parameters

### -First

The primary hashtable. If there are any duplicate keys and you use -Force, values from this hashtable will be kept.

```
Type: Hashtable
Parameter Sets: (All)
Aliases:

Required: False
Position: 1
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Second

The secondary hashtable.

```
Type: Hashtable
Parameter Sets: (All)
Aliases:

Required: False
Position: 2
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Force

Do not prompt for conflicts. Always keep the key from the first hashtable.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
```



```
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about\_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

## Inputs

### hashtable

## Outputs

### hashtable

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

About\_Hash\_Tables

# New-ANSIBar

## Synopsis

Display an ANSI colored bar.

## Syntax

### standard (Default)

```
New-ANSIBar -Range <Int32[]> [-Spacing <Int32>] [-Character <String>]
[-Gradient] [<CommonParameters>]
```

### custom

```
New-ANSIBar -Range <Int32[]> [-Spacing <Int32>] [-Custom <Char>] [-Gradient]
[<CommonParameters>]
```

## Description

You can use this command to create colorful bars using ANSI escape sequences based on a 256 color scheme. The default behavior is to create a gradient bar that goes from first to last values in the range and then back down again. Or you can create a single gradient that runs from the beginning of the range to the end. You can use one of the default characters or specify a custom one.

You can learn more about ANSI escape codes at [https://en.wikipedia.org/wiki/ANSI\\_escape\\_code](https://en.wikipedia.org/wiki/ANSI_escape_code).

## Examples

### Example 1

```
PS C:\> New-ANSIBar -range (232..255)
```

This will create a grayscale gradient bar that goes from dark to light to dark.

### Example 2

```
PS C:\> New-ANSIBar -range (46..51) -Character BlackSquare -Spacing 3
```

## Example 3

```
PS C:\> New-ANSIBar -range (214..219) -Gradient -Spacing 5 -Character DarkShade
```

## Parameters

### -Character

Specify a character to use for the bar.

```
Type: String
Parameter Sets: standard
Aliases:
Accepted values: FullBlock, LightShade, MediumShade, DarkShade, BlackSquare, WhiteSquare

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Custom

Specify a custom character.

```
Type: Char
Parameter Sets: custom
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Gradient

Display as a single gradient from the first value to the last.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Range

Enter a range of 256 color values, e.g. (232..255)

```
Type: Int32[]
Parameter Sets: (All)
Aliases:

Required: True
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Spacing

How many characters do you want in the bar of each value? This will increase the overall length of the bar.

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### None

## Outputs

### System.String

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[New-RedGreenGradient](#)

[Write-ANSIProgress](#)

[Show-ANSISquence](#)

# New-CustomFileName

## Synopsis

Create a custom file name based on a template.

## Syntax

```
New-CustomFileName [-Template] <String> [-Case <String>] [<CommonParameters>]
```

## Description

This command will generate a custom file name based on a template string that you provide. You can create a template string using any of these variables. Most of these should be self-explanatory

- %username
- %computername
- %year - 4 digit year
- %yr - 2 digit year
- %monthname - The abbreviated month name
- %month - The month number
- %dayofweek - The full name of the week day
- %day
- %hour - the hour of the day in 12-hour format to 2 digits
- %hour24 - the hour of the day in 24-hour format to 2 digits
- %minute
- %seconds
- %time - A compact string of HourMinuteSecond
- %string - A random string
- %guid

You can also insert a random number using %**# with a # character for each digit. If you want a 2 digit random number use %**. If you want 6 digits, use %.

The command will attempt to preserve case for any non-pattern string, but you should separate it from other placeholder patterns with one of these characters: - ( ) [ ] or a . Using an underscore will not work.

Another option, is to turn the entire custom name into upper or lower case.

## Examples

### Example 1

```
PS C:\> New-CustomFileName %computername_%day%monthname%yr-%time.log
COWPC_28Nov20-142138.log
```

### Example 2

```
PS C:\> New-CustomFileName %dayofweek-%####.dat
Tuesday-3128.dat
```

Create a custom file name using the day of the week and a 4 digit random number.

### Example 3

```
PS C:\> New-CustomFileName %username-%string.tmp -Case Upper
JEFF-Z0XUXMFS.TMP
```

Create an upper case custom file name. The %string placeholder will be replaced with a random 8 character string.

### Example 4

```
PS C:\> Join-Path c:\work (New-CustomFilename "%Year%Monthname-LOG-%computername[%username].txt" -case lower)
c:\work\2020nov-log-bovine320[jeff].txt
```

Create a lower case filename using Join-Path. This command does not create the file, it only generates a name for you to use.

### Example 5

```
PS C:\> 1..10 | foreach-object {
 $file = New-Item (Join-Path c:\work\data (New-CustomFileName %string-%####.dat))
 $stream =$file.open("OpenOrCreate")
 $stream.Seek((Get-Random -minimum 250 -Maximum 2KB), "Begin") | Out-Null
 $stream.WriteByte(0)
 $stream.Close()
 $file
}
```

Directory: C:\work\data

Mode	LastWriteTime	Length	Name
----	-----	-----	----
-a----	3/15/2020 4:46 PM	976	rcphz2nj-6431.dat

```
-a---- 3/15/2020 4:46 PM 1797 viz32er5-0526.dat
-a---- 3/15/2020 4:46 PM 1775 k2mukuv4-8267.dat
-a---- 3/15/2020 4:46 PM 666 0encqdl1t-8753.dat
-a---- 3/15/2020 4:46 PM 513 dbswpujf-6314.dat
-a---- 3/15/2020 4:46 PM 371 qlkdufp0-0481.dat
-a---- 3/15/2020 4:46 PM 2010 5cxq3tb5-5624.dat
-a---- 3/15/2020 4:46 PM 2043 mcvoh4n5-8041.dat
-a---- 3/15/2020 4:46 PM 1048 4iwibnmf-1584.dat
-a---- 3/15/2020 4:46 PM 378 fgsj0rtd-2894.dat
```

Create 10 dummy files with random names and sizes.

## Parameters

### -Case

Some values like username or computername might be in a different case than what you want. You can use the default value, or return a value that is all upper or lower case.

```
Type: String
Parameter Sets: (All)
Aliases:
Accepted values: Lower, Upper, Default

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Template

A string that defines the naming pattern based on a set of placeholders. You can create a template string using any of these variables, including the % symbol.

- %username
- %computername
- %year - 4 digit year
- %yr - 2 digit year
- %monthname - The abbreviated month name
- %month - The month number
- %dayofweek - The full name of the week day
- %day
- %hour - the hour of the day in 12-hour format to 2 digits
- %hour24 - the hour of the day in 24-hour format to 2 digits
- %minute
- %seconds



- %time - A compact string of HourMinuteSecond
- %string - A random string
- %guid
- %**#** - a random number matching the number of # characters

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### None

## Outputs

### System.String

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[New-RandomFileName](#)

# New-FunctionItem

## Synopsis

Create a function item from the console.

## Syntax

```
New-FunctionItem [-Name] <String> [-Scriptblock] <ScriptBlock> [[-Description] <String>] [-PassThru] [-WhatIf] [-Confirm] [<CommonParameters>]
```

## Description

You can use this function to create a quick function definition directly from the console. This command does not write anything to the pipeline unless you use -PassThru.

## Examples

### Example 1

```
PS C:\> New-FunctionItem -name ToTitle -scriptblock {param([string]$Text)
(Get-Culture).TextInfo.ToTitleCase($text.ToLower())} -PassThru
```

CommandType	Name	Version	Source
Function	ToTitle		

### Example 2

```
PS C:\> {Get-Date -format g | Set-Clipboard} | New-FunctionItem -name Copy-Date
```

## Parameters

### -Name

What is the name of your function?

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 1
Default value: None
Accept pipeline input: False
```

```
Accept wildcard characters: False
```

## -Scriptblock

What is your function's scriptblock?

```
Type: ScriptBlock
Parameter Sets: (All)
Aliases:

Required: True
Position: 2
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

## -Description

You can specify an optional description. This only lasts for as long as your function is loaded.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 3
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -PassThru

Show the newly created function.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## -WhatIf

Shows what would happen if the cmdlet runs. The cmdlet is not run.

```
Type: SwitchParameter
Parameter Sets: (All)
```

```
Aliases: wi

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Confirm

Prompts you for confirmation before running the cmdlet.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: cf

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

## Scriptblock

## Outputs

## None

## System.Management.Automation.FunctionInfo

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Show-FunctionItem](#)

# New-PSDriveHere

## Synopsis

Create a new PSDrive at the current location.

## Syntax

### Folder (Default)

```
New-PSDriveHere [[-Path] <String>] [-First] [-SetLocation] [-PassThru]
[-WhatIf] [-Confirm] [<CommonParameters>]
```

### Name

```
New-PSDriveHere [[-Path] <String>] [[-Name] <String>] [-SetLocation]
[-PassThru] [-WhatIf] [-Confirm] [<CommonParameters>]
```

## Description

This function will create a new PSDrive at the specified location. The default is the current location, but you can specify any PSPATH. The function will take the last word of the path and use it as the name of the new PSDrive. If you prefer to use the first word of the location, use -First. If you prefer to specify a completely different name, then use the -Name parameter.

This command will not write anything to the pipeline unless you use -PassThru.

## Examples

### Example 1

```
PS C:\users\jeff\documents\Enterprise Mgmt Webinar\> New-PSDriveHere
```

This will create a new PSDrive called Webinar rooted to the current location.

### Example 2

```
PS C:\users\jeff\documents\Enterprise Mgmt Webinar\> New-PSDriveHere -first
```

This will create a new PSDrive called Enterprise rooted to the current location.

## Example 3

```
PS C:\> New-PSDriveHere HKLM:\software\microsoft -PassThru |
Select-Object -Expandproperty Name

microsoft
```

## Example 4

```
PS C:\> New-PSDriveHere -Path "\\NAS\files\powershell" -Name PSFiles
```

Create a new PSDrive called PSFiles rooted to the specified path.

## Example 5

```
PS C:\Users\Jeff\Documents\DeepDive\> New-PSDriveHere . DeepDive -setlocation
PS DeepDive:\>
```

Create a new PSDrive and change location to it.

## Parameters

### -Path

The path for the new PSDrive. The default is the current location.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 1
Default value: .
Accept pipeline input: False
Accept wildcard characters: False
```

### -Name

The name for the new PSDrive. The default is the last word in the specified location, unless you use -First.

```
Type: String
Parameter Sets: Name
Aliases:

Required: False
Position: 2
Default value: None
```

```
Accept pipeline input: False
Accept wildcard characters: False
```

## -First

Use the first word of the current location for the new PSDrive.

```
Type: SwitchParameter
Parameter Sets: Folder
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## -SetLocation

Set location to this new drive. This parameter has an alias of CD.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: cd

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## -WhatIf

Shows what would happen if the cmdlet runs. The cmdlet is not run.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: wi

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Confirm

Prompts you for confirmation before running the cmdlet.

```
Type: SwitchParameter
```

```
Parameter Sets: (All)
Aliases: cf

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -PassThru

Pass the new PSDrive object to the pipeline.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### None

## Outputs

### None

## System.Management.Automation.PSDrive

## Notes

Originally published at <http://jdhitsolutions.com/blog/2010/08/New-PSDriveHere/>

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>



## Related Links

[Get-PSDrive](#)

[New-PSDrive](#)

# New-PSDynamicParameter

## Synopsis

Create a PowerShell function dynamic parameter.

## Syntax

```
New-PSDynamicParameter [-ParameterName] <String[]> [-Condition <String> [-Mandatory]
[-DefaultValue <Object[]>] [-Alias <String[]>] [-ParameterType <Type>] [-HelpMessage <String>][[-ValueFromPipelineByPropertyName] [-ParameterSetName <String>][
-Comment <String>] [-ValidateNotNullOrEmpty] [-ValidateLength <Int32[]>] [-ValidateSet <Object[]>]
[-ValidateRange <Int32[]>] [-ValidateCount <Int32[]>] [-ValidatePattern <String>] [-ValidateScript <ScriptBlock>] [<CommonParameters>]
```

## Description

This command will create the code for a dynamic parameter that you can insert into your PowerShell script file. You need to specify a parameter name and a condition. The condition value is code that would run inside an If statement. Use a value like \$True if you want to add it later in your scripting editor.

## Examples

### Example 1

```
PS C:\> New-PSDynamicParameter -Condition "$PSEdition -eq 'Core'" -ParameterName ANSI -Alias color -Comment "Create a parameter to use ANSI if running
PowerShell 7" -ParameterType switch
```

```
DynamicParam {
Create a parameter to use ANSI if running PowerShell 7
If (Core -eq 'Core') {

 $paramDictionary = New-Object -Type System.Management.Automation.RuntimeDefinedParameterDictionary

 # Defining parameter attributes
 $attributeCollection = New-Object -Type System.Collections.ObjectModel.Collection[System.Attribute]
 $attributes = New-Object System.Management.Automation.ParameterAttribute
 $attributes.ParameterSetName = '__AllParameterSets'
 $attributeCollection.Add($attributes)

 # Adding a parameter alias
 $dynalias = New-Object System.Management.Automation.AliasAttribute -ArgumentList 'color'
 $attributeCollection.Add($dynalias)

 # Defining the runtime parameter
 $dynParam1 = New-Object -Type System.Management.Automation.RuntimeDefinedParameter('ANSI', [Switch], $attributeCollection)
 $paramDictionary.Add('ANSI', $dynParam1)

 return $paramDictionary
} # end if
} #end DynamicParam
```

This creates dynamic parameter code that you can use in a PowerShell function. Normally you would save this output to a file or copy to the clipboard so that you can paste it into scripting editor.

## Parameters

## -ParameterName

Enter the name of your dynamic parameter. This is a required value.

```
Type: String[]
Parameter Sets: (All)
Aliases: Name

Required: True
Position: 1
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Condition

Enter an expression that evaluates to True or False. This is code that will go inside an IF statement. If using variables, wrap this in single quotes. You can also enter a placeholder like '\$True' and edit it later. This is a required value.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Mandatory

Is this dynamic parameter mandatory?

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## -DefaultValue

Enter an optional default value.

```
Type: Object[]
Parameter Sets: (All)
```

```
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Alias

Enter an optional parameter alias. Specify multiple aliases separated by commas.

```
Type: String[]
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -ParameterType

Enter the parameter value type such as String or Int32. Use a value like string[] to indicate an array.

```
Type: Type
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: String
Accept pipeline input: False
Accept wildcard characters: False
```

## -HelpMessage

Enter an optional help message.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -ValueFromPipelineByPropertyName

Does this dynamic parameter take pipeline input by property name?

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## -ParameterSetName

Enter an optional parameter set name.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Comment

Enter an optional comment for your dynamic parameter. It will be inserted into your code as a comment.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -ValidateNotNullOrEmpty

Validate that the parameter is not NULL or empty.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
```

```
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## -ValidateLength

Enter a minimum and maximum string length for this parameter value as an array of comma-separated set values.

```
Type: Int32[]
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -ValidateSet

Enter a set of parameter validations values

```
Type: Object[]
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -ValidateRange

Enter a set of parameter range validations values as a comma-separated list from minimum to maximum

```
Type: Int32[]
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -ValidateCount

Enter a set of parameter count validations values as a comma-separated list from minimum to maximum

```
Type: Int32[]
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -ValidatePattern

Enter a parameter validation regular expression pattern

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -ValidateScript

Enter a parameter validation scriptblock. If using the form, enter the scriptblock text.

```
Type: ScriptBlock
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

## Outputs

### System.String[]

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[New-PSDynamicParameterForm](#)

[about\\_Functions\\_Advanced\\_Parameters](#)



# New-PSDynamicParameterForm

## Synopsis

Launch a WPF front-end to New-PSDynamicParameter.

## Syntax

```
New-PSDynamicParameterForm [<CommonParameters>]
```

## Description

This function will launch a WPF form that you can use to enter values for the New-PSDynamicParameter function. The resulting PowerShell code is copied to the clipboard so that you can paste it into your scripting editor. Mandatory settings are indicated with an asterisk. There should be tool tip help for every setting.

If you import the PSScriptTools module in the PowerShell ISE, you will get a menu shortcut under Add-Ins. If you import the module in VS Code using the integrated PowerShell terminal, it will a a new command.

## Examples

### Example 1

```
PS C:\> New-PSDynamicParameterForm
```

## Parameters

### CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

None

## Outputs

None

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[New-PSDynamicParameter](#)

[about\\_Functions\\_Advanced\\_Parameters](#)

# New-PSFormatXML

## Synopsis

Create or modify a format.ps1xml file.

## Syntax

```
New-PSFormatXML [-InputObject] <Object> [[-Properties] <Object[]>]
[-TypeName <String>] [[-FormatType] <String>] [[-ViewName] <String>]
[-Path] <String> [-GroupBy <String>] [-Wrap] [-Append]
[-PassThru] [-WhatIf] [-Confirm] [<CommonParameters>]
```

## Description

When defining custom objects with a new typename, PowerShell by default will display all properties. However, you may wish to have a specific default view, such as a table or list. Or you may want to have different views that display the object differently. Format directives are stored in format.ps1xml files which can be tedious to create. This command simplifies that process.

Note that the table and wide views are set to Autosize. However, the table definition will include best guesses for column widths. If you prefer a more granular approach you can delete the Autosize tag and experiment with varying widths. Don't forget to run Update-FormatData to load your new file. You may need to start a new PowerShell session to fully test changes.

Pipe an instance of your custom object to this function and it will generate a format.ps1xml file based on either all the properties or a subset that you provide. You can repeat the process to add additional views. When finished, edit the format.ps1xml file and fine-tune it. The file will have notes on how to substitute script blocks. Although, beginning with v2.31.0, you can specify a hashtable as a custom property name just as you can with Select-Object.

Even though this command was written to make it easier when writing modules that might use custom objects, you can use this command to define additional views for standard objects such as files and processes. See Examples.

If you run this command inside the Visual Studio Code PowerShell Integrated Console and use -PassThru, the new file will automatically be opened in your editor.

## Examples

### Example 1

```
PS C:\> $tname = "myThing"
PS C:\> $obj = [PSCustomObject]@{
 PSTypeName = $tname
 Name = "Jeff"
 Date = (Get-Date)
 Computername = $env:computername
}
```

```

 OS = (Get-Ciminstance Win32_OperatingSystem).caption
}
PS C:\> $upParams = @{
 TypeName = $tname
 MemberType = "ScriptProperty"
 MemberName = "Runtime"
 Value = {(Get-Date) - [datetime]"1/1/2020"}
 Force = $True
}
PS C:\> Update-TypeData @upParams
PS C:\> $obj

Name : Jeff
Date : 2/10/2020 8:49:10 AM
Computersname : BOVINE320
OS : Microsoft Windows 10 Pro
Runtime : 40.20:49:43.9205882

```

This example begins by creating a custom object. You might normally do this in a script or module.

## Example 2

```

PS C:\> $fmt = "C:\scripts\$tname.format.ps1xml"
PS C:\> $obj | New-PSFormatXML -Prop Name,Date,Computersname,OS -Path $fmt
PS C:\> $obj | New-PSFormatXML -Prop Name,OS,Runtime -view runtime -Path $fmt -append
PS C:\> $obj | New-PSFormatXML -FormatType List -Path $fmt -append

```

The object is then piped to New-PSFormatXML to generate a new format.ps1xml file. Subsequent commands add more formatted views. When the file is completed it can be modified. Note that these examples are using shortened parameter names.

## Example 3

```

PS C:\> Update-FormatData -appendpath "C:\work\$tname.format.ps1xml"
PS C:\> $obj

Name Date Computersname Operating System
---- --
Jeff 2/10/2020 8:49:10 AM BOVINE320 Microsoft Windows 10 Pro

PS C:\> $obj | Format-Table -View runtime

Name OS Runtime
---- --
Jeff 40.20:56:24.5411481

PS C:\> $obj | Format-List

Name : Jeff
Date : Sunday, February 10, 2020
Computersname : BOVINE320
OperatingSystem : Microsoft Windows 10 Pro
Runtime : 40.21:12:01

```

After the format.ps1xml file is applied, the object can be formatted as designed.

## Example 4

```
PS C:\> $obj | New-PSFormatXML -view computer -Group Computername
-Path "c:\work\$tname.format.ps1xml" -append
PS C:\> Update-FormatData -appendpath "C:\work\$tname.format.ps1xml"
PS C:\> $obj | Format-Table -View computer

 Computername: BOVINE320

Name Date OS Runtime
---- ---- -
Jeff 2/10/2020 8:49:10 AM Microsoft Windows 10 Pro 40.20:56:24.5411481
```

This adds another view called Computer that groups objects on the Computername property.

## Example 5

```
PS C:\> $params = @{
Properties = "DisplayName"
FormatType = "Wide"
Path = "C:\work\svc.format.ps1xml"
GroupBy = "Status"
ViewName = "Status"
}
PS C:\> Get-Service bits | New-PSFormatXML @params
PS C:\> Update-FormatData $params.path
```

This will create a custom format file for service objects. This will create a wide display using the DisplayName property. Once loaded into PowerShell, you can run a command like this:

Get-Service	Sort-Object Status	Format-Wide -view Status
-------------	--------------------	--------------------------

## Example 6

```
PS C:\> '' | Select-Object -Property Name,Size,Date,Count,Age |
New-PSFormatXML -Typename myThing -Path c:\scripts\mything.format.ps1xml
```

This is an example of creating a formatting file from an empty object. Normally, you would first define your object and verify it has all the properties you need, and then you would create the formatting file. But you may want to create the formatting file in parallel using an older technique like this.

## Example 7

```
PS C:\> $p = @{
FormatType = "List"
ViewName = "run"
```

```
Path = "c:\scripts\run.ps1xml"
Properties = "ID","Name","Path","StartTime",
@{Name="Runtime";Expression={(Get-Date) - $_.starttime}}
}
PS C:\> Get-Process -id $pid | New-PSFormatXML @p
```

Beginning with v2.31.0 of the PSScriptTools module, you can specify a property defined as a scriptblock, just as you do with Select-Object. The XML file will be automatically created using the script block.

## Parameters

### -Append

Append the new view to an existing format.ps1xml file. You need to make sure that view names are unique. With the exception of default. You can have multiple default views as long as they are different types, such as table and list.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Confirm

Prompts you for confirmation before running the cmdlet.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: cf

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -FormatType

Specify whether to create a table, list, or wide view.

```
Type: String
Parameter Sets: (All)
Aliases:
Accepted values: Table, List, Wide

Required: False
```

```
Position: 2
Default value: Table
Accept pipeline input: False
Accept wildcard characters: False
```

## -InputObject

Specify an object to analyze and generate or update a ps1xml file. All you need is one instance of the object. Ideally, the object will have values for all properties.

```
Type: Object
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

## -PassThru

Write the ps1xml file object to the pipeline. If you run this command inside the VS Code PowerShell integrated console, or the PowerShell ISE and use this parameter, the file will be opened in the editor.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Path

Enter full filename and path for the format.ps1xml file.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 4
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Properties

Enter a set of properties to include. If you don't specify anything then all properties will be used. When creating a Wide view you should only specify a single property. If you specify an invalid property name, the ps1xml file will NOT be created. Ideally, you will specify an instance of the object that contains a value for all the properties you want to use.

```
Type: Object[]
Parameter Sets: (All)
Aliases:

Required: False
Position: 1
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -ViewName

Enter the name of your view.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 3
Default value: default
Accept pipeline input: False
Accept wildcard characters: False
```

## -WhatIf

Shows what would happen if the cmdlet runs. The cmdlet is not run.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: wi

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Typename

Specify the object typename. If you don't, then the command will use the detected object type from the InputObject.



```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -GroupBy

Specify a property name to group objects on. You can edit the file if you need to change how it is displayed and/or calculated.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Wrap

Wrap long lines. This only applies to Tables.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

## System.Object

## Outputs

None

**System.IO.FileInfo**

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

Update-FormatData

[Get-FormatView](#)

# New-RandomFileName

## Synopsis

Create a random file name.

## Syntax

### none (Default)

```
New-RandomFileName [-Extension <String>] [<CommonParameters>]
```

### temp

```
New-RandomFileName [-Extension <String>] [-UseTempFolder] [<CommonParameters>]
```

### home

```
New-RandomFileName [-Extension <String>] [-UseHomeFolder] [<CommonParameters>]
```

## Description

Create a new random file name. The default is a completely random name including the extension. But you can also create a filename that includes either the TEMP folder or the user's home folder. In the case of a Windows system, the home folder will be the documents folder.

This command does not create the file, it only generates a name for you to use.

## Examples

### Example 1

```
PS C:\> New-RandomFileName
fykxecvh.ipw
```

### Example 2

```
PS C:\> New-RandomFileName -extension dat
emevgq3r.dat
```

Specify a file extension.

## Example 3

```
PS C:\> New-RandomFileName -extension log -UseHomeFolder
C:\Users\Jeff\Documents\kbyw4fda.log
```

Create a random file name using the user's home folder. In Windows, this will be the Documents folder.

## Example 4

```
PS /mnt/c/scripts> new-randomfilename -home -Extension tmp
/home/jhicks/oces0epq.tmp
```

Create a random file name using the user's home folder on a Linux installation.

## Parameters

### -Extension

Use a specific extension. Do not include the period.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -UseHomeFolder

Include the user's HOME folder.

```
Type: SwitchParameter
Parameter Sets: home
Aliases: home

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -UseTempFolder

Include the TEMP folder.

```
Type: SwitchParameter
Parameter Sets: temp
Aliases: temp

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about\_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

## Inputs

None

## Outputs

System.String

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[New-CustomFileName](#)

## Synopsis

## Syntax

## Description

## Examples

## Example 1

This will display a red to green gradient bar.

## Example 2

The bar graph will be colored from red towards green. This example is using the Format-Percent and Format-Value commands from the PSScriptTools module.

## Parameters

### -Character

Specify a character to use for the gradient bar

```
Type: Char
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: [char]0x2588
Accept pipeline input: False
Accept wildcard characters: False
```

### -Percent

Specify a percentage as a decimal value like .35

```
Type: Double
Parameter Sets: (All)
Aliases:

Required: False
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Step

Specify a relative bar length between 2 and 10. The smaller the number the longer the bar.

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: 5
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

None

## Outputs

**System.String**

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[New-ANSIBar](#)

[Write-ANSIProgress](#)



# New-WPFMessageBox

## Synopsis

Display a customizable WPF-based message box.

## Syntax

### standard (Default)

```
New-WPFMessageBox [-Message] <String> [-Title <String>] [-Icon <String>]
[-ButtonSet <String>] [-Background <String>] [-Quiet] [<CommonParameters>]
```

### custom

```
New-WPFMessageBox [-Message] <String> [-Title <String>] [-Icon <String>]
[-CustomButtonSet <OrderedDictionary>] [-Background <String>] [-Quiet]
[<CommonParameters>]
```

## Description

This function creates a Windows Presentation Foundation (WPF) based message box. This is intended to replace the legacy MsgBox function from VBScript and the Windows Forms library. The command uses a set of predefined button sets, each of which will close the form and write a value to the pipeline.

```
OK = 1

Cancel = 0

Yes = $True

No = $False
```

You can also create an ordered hashtable of your own buttons and values. See examples. If you prefer to simply display the form, you can use the -Quiet parameter to suppress any output. PowerShell will block until a button is clicked or the form dismissed.

This command requires a Windows platform.

## Examples

### Example 1

```
PS C:\> New-WPFMessageBox -Message "Are you sure you want to do this?" -Title Confirm -Icon Question -ButtonSet YesNo
```

```
False
```

Display a Yes/No message box. The value of the clicked button will be written to the pipeline. It is assumed you would use this in a script and have logic to determine what to do based on the value.

## Example 2

```
PS C:\> New-WPFMessageBox -Message "Press OK when ready to continue."
-Title "User Deletion" -Quiet -Background crimson -Icon Shield
```

Display a message box with a crimson background and using the Shield icon. No value will be written to the pipeline and PowerShell will wait until OK is clicked or the form dismissed.

## Example 3

```
PS C:\> New-WPFMessageBox -Message "Select a system option from these choices:" -Title "You Decide" -Background cornsilk -Icon Warning -CustomButtonSet
([ordered]@{"Reboot"=1;"Shutdown"=2;"Cancel"=3})
```

Create a custom message box with a user-defined set of buttons.

## Parameters

### -Background

You can specify any console color or any value from <https://docs.microsoft.com/en-us/dotnet/api/system.windows.media.brushes?view=netframework-4.7.2>. You can use the name or the code. Keep in mind there are no provisions to change the font color.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: White
Accept pipeline input: False
Accept wildcard characters: False
```

### -ButtonSet

Select a pre-defined set of buttons. Each button will close the form and write a value to the pipeline. This can serve as the "return value" of the form.

OK = 1

Cancel = 0

Yes = \$True

No = \$False

```
Type: String
Parameter Sets: standard
Aliases:
Accepted values: OK, OKCancel, YesNo

Required: False
Position: Named
Default value: OK
Accept pipeline input: False
Accept wildcard characters: False
```

## -CustomButtonSet

You can specify your own button set defined in an ordered hashtable. Buttons will be displayed in order from left to right. You can display up to 3 buttons. The key should be the text to display and the value should be the value you expect to write to the pipeline. It is recommended that you keep the button text short. The first letter of each key will automatically be formatted as an accelerator so you should make sure each key starts with a different letter. The first key will also be set as the default.

```
Type: OrderedDictionary
Parameter Sets: custom
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Icon

Select one of the standard system icons.

```
Type: String
Parameter Sets: (All)
Aliases:
Accepted values: Information, Warning, Error, Question, Shield

Required: False
Position: Named
Default value: Information
Accept pipeline input: False
Accept wildcard characters: False
```

## -Message

Enter the text message to display.

```
Type: String
```

```
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Quiet

Suppress any pipeline output.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Title

Enter the text to be displayed in the title bar. You should keep this brief.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about\_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

## Inputs

### None

## Outputs

**System.Int32**

**System.Boolean**

**System.String**

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Invoke-InputBox](#)

# Open-PSScriptToolsHelp

## Synopsis

Open the PSScriptTools PDF manual.

## Syntax

```
Open-PSScriptToolsHelp [<CommonParameters>]
```

## Description

This command will launch a PDF manual for all commands in the PSScriptTools module. It is assumed you have a default application associated with PDF files.

## Examples

### Example 1

```
PS C:\> Open-PSScriptToolsHelp
```

## Parameters

### CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

None

## Outputs

None

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Get-Help](#)

[Get-PSScriptTools](#)

# Optimize-Text

## Synopsis

Clean and optimize text input.

## Syntax

### default (Default)

```
Optimize-Text [[-Text] <String[]>] [-Filter <Regex>] [-Ignore <String>]
[-ToUpper] [<CommonParameters>]
```

### object

```
Optimize-Text [[-Text] <String[]>] [-Filter <Regex>][-Ignore <String>]
[-ToUpper] [-PropertyName <String>] [<CommonParameters>]
```

## Description

Use this command to clean and optimize content from text files. Sometimes text files have blank lines or the content has trailing spaces. These sorts of issues can cause problems when passing the content to other commands.

This command will strip out any lines that are blank or have nothing by white space, and trim leading and trailing spaces. The optimized text is then written back to the pipeline. Optionally, you can specify a property name. This can be useful when your text file is a list of computer names and you want to take advantage of pipeline binding. See examples.

If your text file has commented lines, use the ignore parameter. As long as the character is the first non-whitespace character in the line, the line will be treated as a comment and ignored.

Finally, you can use the -Filter parameter to specify a regular expression pattern to further filter what text is written to the pipeline. The filter is applied after leading and trailing spaces have been removed and before any text is converted to upper case.

## Examples

### Example 1

```
PS C:\> Get-Content c:\scripts\computers.txt

win10-ent-01
srv1
 srv2
```



```
dc01
app02

PS C:\> Get-Content c:\scripts\computers.txt | Optimize-Text
win10-ent-01
srv1
quark
dc01
app02
```

The first example shows a malformed text file. In the second command, it has been optimized or normalized.

## Example 2

```
PS C:\> Get-Content c:\scripts\computers.txt | Optimize-Text -property computername

computername

win10-ent-01
srv1
quark
dc01
app02
```

Using the same text file, the command creates a custom object using the Computername property.

## Example 3

```
PS C:\> Get-Content computers.txt | Optimize-Text -prop computername |
Where-Object {Test-Connection $_.computername -count 1 -ea SilentlyContinue} |
Get-Service bits | Select-Object Name,Status,MachineName

Name Status MachineName
---- -
bits Running win10-ent-01
bits Running dc01
bits Running app02
```

Optimize the computer names in computers.txt and add a Computername property. Test each computer, ignoring those that fail, and get the Bits service on the ones that can be pinged.

## Example 4

```
PS C:\> Get-Content .\ChicagoServers.txt | Optimize-Text -Ignore "#" -Property ComputerName

ComputerName

chi-fp01
chi-fp02
```

```
chi-core01
chi-test
chi-dc01
chi-dc02
chi-dc04
chi-db01
```

Optimize the text file ignoring any lines that start with the # character.

## Example 5

```
PS C:\> Get-Content .\ChicagoServers.txt |
Optimize-Text -filter "dc\d{2}" -ToUpper -PropertyName Computername |
Test-Connection -count 1
```

Source	Destination	IPv4Address	IPv6Address	Bytes	Time(ms)
win10-ENT-01	CHI-DC01	172.16.30.200		32	0
win10-ENT-01	CHI-DC02	172.16.30.201		32	0
win10-ENT-01	CHI-DC04	172.16.30.203		32	0

Get names from a text file that match the pattern, turn into an object with a property name, and pipe to Test-Connection.

## Parameters

### -Text

The text to be optimized. Typically read in from a file.

```
Type: String[]
Parameter Sets: default
Aliases:

Required: False
Position: 1
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

```
Type: String[]
Parameter Sets: object
Aliases:

Required: False
Position: 1
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

## -Filter

Use a regular expression pattern to filter. The filtering is applied after leading and trailing spaces have been trimmed and before text can be converted to upper case.

```
Type: Regex
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -PropertyName

Assign each line of text a property name. This has the effect of turning your text file into an array of objects with a single property.

```
Type: String
Parameter Sets: object
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Ignore

Specify a character that will be interpreted as a comment character. It must be the first-word character in a line. These lines will be ignored. This parameter has an alias of 'comment'.

```
Type: String
Parameter Sets: (All)
Aliases: comment

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -ToUpper

Write text output as upper case.

```
Type: SwitchParameter
```

```
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about\_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

## Inputs

### System.String

## Outputs

### System.String

### System.Management.Automation.PSObject

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

This function was originally described at <http://jdhitsolutions.com/blog/2014/09/using-optimized-text-files-in-powershell>

## Related Links

Get-Content

# Out-Copy

## Synopsis

Send command output to the pipeline and clipboard.

## Syntax

```
Out-Copy [-InputObject] <Object> [-Width <Int32>] [-CommandOnly] [-Ansi] [<CommonParameters>]
```

## Description

This command is intended for writers and those who need to document with PowerShell. You can pipe any command to this function and you will get the regular output in your PowerShell session. Simultaneously, a copy of the output will be sent to the Windows clipboard. The copied output will include a prompt constructed from the current location unless you use the CommandOnly parameter.



You can only capture what is written to the Success pipeline. This command will not copy any other streams such as Verbose, Warning, or Error.

## Examples

### Example 1

```
PS C:\> Get-Process | Sort WS -Descending | Select-First 5 | Out-Copy
```

This will execute your expression and write the output to the pipeline. The output plus the command except for the pipe to Out-Copy will be copied to the clipboard. This example is using the Select-First function from the PSScriptTools module.

### Example 2

```
PS C:\> Get-ChildItem *.ps1 | Out-File c:\work\ps.txt | Out-Copy
```

Even if your command doesn't write anything to the pipeline, Out-Copy will still capture a prompt and PowerShell expression.

### Example 3

```
PS C:\> Get-CimInstance -class win32_logicaldisk -filter "DriveType = 3" |
Out-Copy -CommandOnly
```

This will run the Get-CimInstance command and write results to the pipeline. But the only text that will be copied to the clipboard is:

```
Get-CimInstance -class win32_logicaldisk -filter "DriveType = 3"
```

## Example 4

```
PS C:\> Get-Process | Sort WS -Descending | Select-Object -first 5 | Out-Copy -ansi
```

Copy the command and output including any ANSI formatting which you might get in PowerShell 7.

## Parameters

### -InputObject

This is the piped in command.

```
Type: Object
Parameter Sets: (All)
Aliases:

Required: True
Position: 1
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

### -Width

Specifies the number of characters in each line of output. Any additional characters are truncated, not wrapped.

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: 80
Accept pipeline input: False
Accept wildcard characters: False
```

### -CommandOnly

Only copy the executed command, without references to Out-Copy, to the Windows clipboard.

```
Type: SwitchParameter
Parameter Sets: (All)
```

```
Aliases:
Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## -Ansi

Include any Ansi formatting. The default behavior is to capture plain text.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### System.Object

## Outputs

### System.Object

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

Out-String

Set-Clipboard

Tee-Object

Copy-HistoryCommand



# Out-More

## Synopsis

Send "pages" of objects to the pipeline.

## Syntax

```
Out-More [-InputObject] <Object[]> [[-Count] <Int32>] [-ClearScreen]
```

## Description

This function is designed to display groups or "pages" of objects to the PowerShell pipeline. It is modeled after the legacy More.com command-line utility. By default, the command will write objects out to the pipeline in groups of 50. You will be prompted after each grouping.

Pressing M or Enter will get the next group. Pressing A will stop paging and display all of the remaining objects. Pressing N will display the next object. Press Q to stop writing anything else to the pipeline.

Note that you may encounter an error message when quitting prematurely, especially on non-Windows platforms. You can ignore these errors.

## Examples

### Example 1

```
PS C:\> Get-Process | Out-More -count 10
```

Handles	NPM(K)	PM(K)	WS(K)	VM(M)	CPU(s)	Id	SI	ProcessName
103	9	1448	4220	67	0.02	1632	0	BtwRSupportService
80	9	3008	8588	...27	21.00	5192	1	conhost
40	5	752	2780	...82	0.00	5248	0	conhost
53	7	972	3808	...07	0.02	6876	1	conhost
482	17	1932	3692	56	0.91	708	0	csrss
520	30	2488	134628	180	31.67	784	1	csrss
408	18	6496	12436	...35	0.56	1684	0	dasHost
180	14	3348	6748	66	0.50	4688	0	devmonsrv

```

\[M\]ore \[A\]ll \[N\]ext \[Q\]uit

```

Display processes in groups of 10.

### Example 2

```
PS C:\> dir c:\work -file -Recurse | Out-More -ClearScreen | tee -Variable work
```

List all files in C:\Work and page them to Out-More using the default count, but after clearing the screen first. The results are then piped to Tee-Object which saves them to a variable.

## Parameters

### -InputObject

```
Type: Object[]
Parameter Sets: (All)
Aliases:

Required: True
Position: 1
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

### -Count

The number of objects to group as a page.

```
Type: Int32
Parameter Sets: (All)
Aliases: i

Required: False
Position: 2
Default value: 50
Accept pipeline input: False
Accept wildcard characters: False
```

### -ClearScreen

Clear the screen before writing data to the pipeline.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: cls

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## Inputs

### System.Object

## Outputs

### System.Object

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

This command was first demonstrated at <http://jdhitsolutions.com/blog/powershell/4707/a-better-powershell-more/>

## Related Links

more

# Out-VerboseTee

## Synopsis

Write to the Verbose stream and a file.

## Syntax

```
Out-VerboseTee -Value <Object> [-Path] <String> [-Encoding <Encoding>]
[-Append] [<CommonParameters>]
```

## Description

This command is intended to let you see your verbose output and write the verbose messages to a log file. It will only work if the verbose pipeline is enabled, usually when your command is run with `-Verbose`. This function is designed to be used within your scripts and functions. You either have to hard code a file name or find some other way to define it in your function or control script. You could pass a value as a parameter or set it as a `PSDefaultParameterValue`.

This command has an alias of `Tee-Verbose`.

You might use it like this in a script.

Begin {

```
$log = New-RandomFilename -useTemp -extension log

Write-Detail "Starting $($MyInvocation.MyCommand)" -Prefix begin | Tee-Verbose $log

Write-Detail "Logging verbose output to $log" -prefix begin | Tee-Verbose -append

Write-Detail "Initializing data array" -Prefix begin | Tee-Verbose $log -append

$data = @()
```

} #begin

When the command is run with `-Verbose` you will see the verbose output and it will be saved to the specified log file.

## Examples

### Example 1

```
PS C:\> $VerbosePreference= "continue"
PS C:\> $log = New-CustomFileName ".\VerboseLog_%time.txt"
PS C:\> Write-Detail "This is a verbose log test" | Out-VerboseTee -Path $log
```

```
PS C:\> Get-Content $log
11/29/2024 08:21:31:0704 [PROCESS] This is a verbose log test
PS C:\> $verbosePreference = "SilentlyContinue"
```

Normally you would use this command inside a function or script, but you can run it from the console if you want to understand how it works.

## Parameters

### -Append

Append to the specified text file.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Encoding

Specify a file encoding.

```
Type: Encoding
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Path

The path for the output file.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Value

The message to be displayed as a verbose message and saved to the file.

```
Type: Object
Parameter Sets: (All)
Aliases:

Required: True
Position: Named
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about\_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

## Inputs

### System.Object

## Outputs

### System.Object

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

Write-Verbose

Write-Detail

Tee-Object

# Remove-MergedBranch

## Synopsis

Removed merged git branches.

## Syntax

```
Remove-MergedBranch [-MainBranch <String>] [-Force] [-WhatIf] [-Confirm] [<CommonParameters>]
```

## Description

When using git you may create multiple branches. Presumably, you merge these branches into the main or master branch. The development or patching branch remains. You can use git to remove branches. Or use this command to remove all merged branches other than master and the current branch. You must be in the root of your project to run this command.

## Examples

### Example 1

```
PS C:\MyProject> Remove-MergedBranch

Remove merged branch from MyProject?
2.1.1
[Y] Yes [N] No [S] Suspend [?] Help (default is "Y"): n

Remove merged branch from MyProject?
dev1
[Y] Yes [N] No [S] Suspend [?] Help (default is "Y"): y
Deleted branch dev1 (was 75f6ab8).

Remove merged branch from MyProject?
dev2
[Y] Yes [N] No [S] Suspend [?] Help (default is "Y"): y
Deleted branch dev2 (was 75f6ab8).

Remove merged branch from MyProject?
patch-254
[Y] Yes [N] No [S] Suspend [?] Help (default is "Y"): n
PS C:\MyProject>
```

By default you will be prompted to remove each branch.

### Example 2

```
PS C:\MyProject> Remove-MergedBranch main -force
Deleted branch 2.1.1 (was 75f6ab8).
```

```
Deleted branch patch-254 (was 75f6ab8).
```

Remove all branches with no prompting. This example assumes the master branch is called main.

## Parameters

### -Confirm

Prompts you for confirmation before running the cmdlet.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: cf

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Force

Remove all merged branches except current and master with no prompting.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -WhatIf

Shows what would happen if the cmdlet runs. The cmdlet is not run.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: wi

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```



## -MainBranch

Specify the name of your master branch.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: master
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### None

## Outputs

### String

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

git.exe

[Get-GitSize](#)

# Remove-PSAnsiFileEntry

## Synopsis

Remove a PSAnsiFileMap entry.

## Syntax

```
Remove-PSAnsiFileEntry [-Description] <String> [-PassThru] [-WhatIf] [-Confirm] [<CommonParameters>]
```

## Description

Use this command to remove an entry from the global \$PSAnsiFileMap variable. The change will not be persistent unless you export the map to a file.

## Examples

### Example 1

```
PS C:\> Remove-PSAnsiFileEntry Samples
```

Remove a PSAnsiFileMap entry with a description of 'Samples'. The change will not be persistent unless you export the map to a file.

## Parameters

### -Confirm

Prompts you for confirmation before running the cmdlet.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: cf

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Description

Specify the description of the entry to remove.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -PassThru

Display the updated PSAnsiFileMap.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -WhatIf

Shows what would happen if the cmdlet runs. The cmdlet is not run.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: wi

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### None

## Outputs

### PSAnsiFileEntry

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Set-PSAnsiFileMapEntry](#)

[Get-PSAnsiFileMapEntry](#)

# Remove-Runspace

## Synopsis

Remove a runspace from your session.

## Syntax

### id (Default)

```
Remove-Runspace [-ID] <Int32> [-WhatIf] [-Confirm] [<CommonParameters>]
```

### runspace

```
Remove-Runspace [-Runspace] <Runspace> [-WhatIf] [-Confirm] [<CommonParameters>]
```

## Description

When working with PowerShell, you may discover that some commands and scripts can leave behind runspaces. You may even deliberately be creating additional runspaces. These runspaces will remain until you exit your PowerShell session. Or use this command to cleanly close and dispose of runspaces. You cannot remove any runspace with an availability of Busy or that is already closing.

This command does not write anything to the pipeline.

## Examples

### Example 1

```
PS C:\> Remove-Runspace -id 18 -WhatIf
What if: Performing the operation "Remove-Runspace" on target "18 - Runspace18".
```

Show what would have happened to remove runspace with an ID of 18.

### Example 2

```
PS C:\> Get-Runspace | where ID -gt 1 | Remove-Runspace
```

Get all runspaces with an ID greater than 1, which is typically your session, and remove the runspace.

## Parameters

### -Confirm

Prompts you for confirmation before running the cmdlet.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: cf

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -ID

The runspace ID number.

```
Type: Int32
Parameter Sets: id
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Runspace

A runspace presumably piped into this command using Get-Runspace.

```
Type: Runspace
Parameter Sets: runspace
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

### -WhatIf

Shows what would happen if the cmdlet runs. The cmdlet is not run.

```
Type: SwitchParameter
Parameter Sets: (All)
```

```
Aliases: wi
Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about\_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

## Inputs

## System.Management.Automation.Runspaces.Runspace

## Outputs

None

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

Get-Runspace

# Rename-Hashtable

## Synopsis

Rename a hashtable key.

## Syntax

### Pipeline (Default)

```
Rename-Hashtable [-InputObject] <Object> [-Key] <String> [-NewKey] <String>
[-PassThru] [-Scope <String>] [-WhatIf] [-Confirm] [<CommonParameters>]
```

### Name

```
Rename-Hashtable [-Name] <String> [-Key] <String> [-NewKey] <String>
[-PassThru] [-Scope <String>] [-WhatIf] [-Confirm] [<CommonParameters>]
```

## Description

This command will rename a key in an existing hashtable or ordered dictionary. You can either pipe a hashtable object to this command or you can specify a variable name for a pre-defined hashtable. If you use this option, specify the variable name without the \$.

This command will create a temporary copy of the hashtable, create the new key, and copy the value from the old key, before removing the old key. The temporary hashtable is then set as the new value for your original variable.

This command does not write anything to the pipeline when you use a variable name unless you use -PassThru. If you pipe a hashtable to this command, the new hashtable will automatically be written to the pipeline.

You might find this command useful when building a hashtable that you intend to use with splatting where you need to align key names with parameter names.

## Examples

### Example 1

```
PS C:\> Rename-Hashtable -name MyHash -key Name -newKey Computername
```

### Example 2

```
PS C:\> $newHash = Get-Service spooler |
```



```
ConvertTo-HashTable |
Rename-Hashtable -Key Machinename -NewKey Computername
```

This command uses the ConvertTo-Hashtable command from the PSScriptTools module to turn an object into a hashtable. The Machinename key is then renamed to Computername.

## Parameters

### -Name

The variable name of your hash table. DO NOT include the \$.

```
Type: String
Parameter Sets: Name
Aliases:

Required: True
Position: 1
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -InputObject

A piped in hashtable object

```
Type: Object
Parameter Sets: Pipeline
Aliases:

Required: True
Position: 1
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

### -Key

The name of the existing hashtable key you want to rename.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 2
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -NewKey

The new name of the hashtable key.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 3
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -PassThru

Write the revised hashtable back to the pipeline. If you pipe a variable to this command, PassThru will happen automatically.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## -Scope

The scope where your variable is defined. The default is the global scope.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: Global
Accept pipeline input: False
Accept wildcard characters: False
```

## -WhatIf

Shows what would happen if the cmdlet runs. The cmdlet is not run.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: wi
```

```
Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Confirm

Prompts you for confirmation before running the cmdlet.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: cf

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### hashtable

## Outputs

### None

### Hashtable

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

This code was first described at <http://jdhitsolutions.com/blog/2013/01/Rename-Hashtable-key-revised>

## Related Links

About\_hash\_tables

[ConvertTo-Hashtable](#)

Join-Hashtable

# Save-GitSetup

## Synopsis

Download the latest 64bit version of Git for Windows.

## Syntax

```
Save-GitSetup [[-Path] <String>] [-PassThru] [<CommonParameters>]
```

## Description

Non-Windows platforms have package management that make it easy to install newer versions of git. This command is for Windows platforms. You can run this command to download the latest 64bit version of Git for Windows. You will need to manually install it.

## Examples

### Example 1

```
C:\> Save-GitSetup -Path c:\work -PassThru

Directory: C:\work

Mode LastWriteTime Length Name
---- -
-a--- 3/26/2025 10:50 AM 70287136 Git-2.49.0-64-bit.exe
```

## Parameters

### -PassThru

Show the downloaded file.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Path

Specify the location to store the downloaded file.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 0
Default value: $env:TEMP
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

None

## Outputs

None

## System.IO.FileInfo

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

git.exe

# Select-After

## Synopsis

Select objects after a given datetime.

## Syntax

```
Select-After -InputObject <PSObject> [-After] <DateTime> [-Property <String>]
[<CommonParameters>]
```

## Description

Select-After is a simplified version of Select-Object. The premise is that you can pipe a collection of objects to this command and select objects after a given datetime, based on a property, like LastWriteTime, which is the default.

## Examples

### Example 1

```
PS C:\> Get-ChildItem c:\work -file | Select-After "11/1/2024"
```

Directory: C:\work

Mode	LastWriteTime	Length	Name
----	-----	-----	----
-a---	11/4/2024 11:36 AM	5008	ipperf.csv

Select all objects that have been modified after 11/1/2024. This example is using the default -Property value of LastWriteTime.

### Example 2

```
PS C:\> Get-Process | After (Get-Date).AddMinutes(-10) -Property StartTime
```

NPM(K)	PM(M)	WS(M)	CPU(s)	Id	SI	ProcessName
8	1.49	7.17	0.00	33248	0	SearchFilterHost
12	2.46	12.99	0.02	15328	0	SearchProtocolHost
8	2.60	8.58	0.03	9756	0	svchost
76	20.27	39.93	2.14	22976	0	svchost
8	1.53	7.29	0.00	29752	0	svchost

Get all processes where the StartTime property value is within the last 10 minutes. This example is using the

"after" alias.

## Parameters

### -After

Enter the cutoff date.

```
Type: DateTime
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -InputObject

A piped in object.

```
Type: PSObject
Parameter Sets: (All)
Aliases:

Required: True
Position: Named
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

### -Property

Enter the property name to use for the datetime sort. It needs to be a datetime object.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: LastWriteTime
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and



-WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

**System.Management.Automation.PSObject**

## Outputs

**System.Object**

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Select-Before](#)

[Select-Object](#)

# Select-Before

## Synopsis

Select objects before a given datetime.

## Syntax

```
Select-Before -InputObject <PSObject> [-Before] <DateTime> [-Property <String>]
[<CommonParameters>]
```

## Description

Select-Before is a simplified version of Select-Object. The premise is that you can pipe a collection of objects to this command and select objects before a given datetime, based on a property, like LastWriteTime, which is the default.

## Examples

### Example 1

```
PS C:\> Get-ChildItem c:\work -file | Select-Before "11/1/2024"

Directory: C:\work

Mode LastWriteTime Length Name
---- -
-a--- 10/10/2024 2:09 PM 8862 Book1.xlsx
-a--- 10/30/2024 10:48 AM 0 dummy.dat
-a--- 10/13/2024 9:35 AM 447743 key1013.pdf
-a--- 10/6/2024 4:03 PM 2986 labsummary.format.ps1xml
-a--- 10/11/2024 12:33 PM 1678 prun.format.ps1xml
-a--- 10/10/2024 6:49 PM 1511 w.format.ps1xml
```

Select all objects that have been modified before 11/1/2024. This example is using the default -Property value of LastWriteTime.

### Example 2

```
PS C:\> Get-Process | before (Get-Date).AddMinutes(-10) -Property StartTime

NPM(K) PM(M) WS(M) CPU(s) Id SI ProcessName

33 30.21 46.19 0.81 9952 2 ApplicationFrameHost
75 102.42 126.08 4.89 16048 2 Box
23 25.27 33.83 0.33 5320 0 Box.Desktop.UpdateService
30 46.92 60.98 0.91 17384 2 BoxUI
```

```
31 39.82 4.34 0.56 26992 2 Calculator
...
```

Get all processes where the StartTime property value is before the last 10 minutes. This example is using the "before" alias.

## Parameters

### -Before

Enter the cutoff date.

```
Type: DateTime
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -InputObject

A piped in object.

```
Type: PSObject
Parameter Sets: (All)
Aliases:

Required: True
Position: Named
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

### -Property

Enter the property name to use for the datetime sort. It needs to be a datetime object.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: LastWritetime
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### System.Management.Automation.PSObject

## Outputs

### System.Object

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Select-After](#)

Select-Object

# Select-First

## Synopsis

Select the first X number of objects.

## Syntax

```
Select-First -InputObject <PSObject> [-First] <Int32> [[-Property] <String>]
[-Skip <Int32>] [-Descending] [<CommonParameters>]
```

## Description

This command is intended to take pipelined input and select the first specified number of objects which are then written to the pipeline. You also have the option to sort on a specified property.

When using this command, there is a trade-off of convenience for performance. For a very large number of processed objects, use `Select-Object`.

## Examples

### Example 1

```
PS C:\> Get-Process | Select-First 3 -property WS -descending
```

Handles	NPM(K)	PM(K)	WS(K)	VM(M)	CPU(s)	Id	SI	ProcessName
-----	-----	-----	-----	-----	-----	--	--	-----
1118	66	419952	392396	...12	107.33	7312	1	powershell
343	43	237928	235508	1237	3,905.22	6424	1	slack
1051	88	231216	234728	1175	61.88	8324	1	powershell_ise

### Example 2

```
PS C:\> 1..10 | Select-First 3 -Skip 2
```

```
3
4
5
```

Select the first 3 objects after skipping 2.

## Parameters

## -InputObject

Pipelined input to be selected.

```
Type: PSObject
Parameter Sets: (All)
Aliases:

Required: True
Position: Named
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

## -First

How many items do you want to select?

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: True
Position: 1
Default value: 0
Accept pipeline input: False
Accept wildcard characters: False
```

## -Property

Sort first on this property then select the specified number of items.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 2
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Skip

Skip or omit the first X number of items.

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: False
```

```
Position: Named
Default value: 0
Accept pipeline input: False
Accept wildcard characters: False
```

## -Descending

Sort the property in descending order.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### Object[]

## Outputs

### Object[]

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

Select-Object

Select-Last

# Select-Last

## Synopsis

Select the last X number of objects.

## Syntax

```
Select-Last -InputObject <PSObject> [-Last] <Int32> [[-Property] <String>]
[-Skip <Int32>] [-Descending] [<CommonParameters>]
```

## Description

This is a modified version of Select-Object designed to select the last X number of objects. The command takes pipelined input and selects the last specified number of objects which are then written to the pipeline. You have an option to first sort on the specified property.

When using this command, there is a trade-off of convenience for performance. For a very large number of processed objects, use Select-Object.

## Examples

### Example 1

```
PS C:\> dir c:\scripts*.ps1 | last 5 -property lastwritetime

Directory: C:\scripts

Mode LastWriteTime Length Name
---- -
-a---- 1/11/2024 7:18 PM 1818 demo-v5Classes.ps1
-a---- 1/11/2024 7:20 PM 1255 demo-v5DSCClassResource.ps1
-a---- 1/14/2024 12:58 PM 1967 Demo-ParamTest.ps1
-a---- 1/15/2024 9:23 AM 971 Get-WorkflowVariable.ps1
-a---- 1/15/2024 12:08 PM 1555 Cost.ps1
```

Get the last 5 ps1 files sorted on the LastWritetime property. This example is using the alias 'last' for Select-Last.

### Example 2

```
PS C:\> 1..10 | Select-Last 3 -skip 1

7
8
```



9

Select the last 3 items, skipping the last 1.

## Parameters

### -InputObject

Pipelined input to be selected.

```
Type: PSObject
Parameter Sets: (All)
Aliases:

Required: True
Position: Named
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

### -Last

How many items do you want to select?

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: True
Position: 1
Default value: 0
Accept pipeline input: False
Accept wildcard characters: False
```

### -Property

Sort first on this property then select the specified number of items.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 2
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Skip

Skip or omit the last X number of items.

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: 0
Accept pipeline input: False
Accept wildcard characters: False
```

## -Descending

Sort on the specified property in descending order.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### Object[]

## Outputs

### Object[]

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Select-Object](#)

[Select-First](#)

# Select-Newest

## Synopsis

Select the newest X number of objects after a given datetime.

## Syntax

```
Select-Newest -InputObject <PSObject> [-Newest] <Int32> [-Property <String>]
[<CommonParameters>]
```

## Description

Select-Newest is a variation on Select-Object. It is designed to make it easier to select X number of objects based on a datetime property. The default property value is LastWriteTime.

## Examples

### Example 1

```
PS C:\> Get-ChildItem c:\work -file | Select-Newest 1

Directory: C:\work

Mode LastWriteTime Length Name
---- -
-a--- 11/4/2024 11:36 AM 5008 ipperf.csv
```

Get the newest file in the Work folder. This example is using the default -Property parameter value of LastWriteTime.

### Example 2

```
PS C:\> Get-Process | newest 10 -Property starttime

NPM(K) PM(M) WS(M) CPU(s) Id SI ProcessName

15 5.34 12.85 0.09 25208 0 WmiPrvSE
7 1.31 5.95 0.02 10552 0 svchost
35 128.28 136.05 8.62 3376 0 esrv_svc
98 47.31 40.01 0.48 24496 2 firefox
99 48.46 46.07 0.53 22064 2 firefox
13 3.41 16.19 0.77 33136 2 notepad
14 6.78 10.96 0.06 31784 0 svchost
69 110.45 150.37 4.28 8848 2 pwsh
5 2.52 4.52 0.02 34024 2 cmd
```

```
10 2.06 9.00 0.12 25384 2 OpenConsole
```

Get the 10 most recent processes based on the StartTime property. This example is using the "newest" alias.

## Parameters

### -InputObject

A piped in object.

```
Type: PSObject
Parameter Sets: (All)
Aliases:

Required: True
Position: Named
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

### -Newest

Enter the number of newest items to select.

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Property

Enter the property name to select on. It must be a datetime object.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: LastWriteTime
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### System.Management.Automation.PSObject

## Outputs

### System.Object

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Select-Oldest](#)

[Select-Object](#)

# Select-Oldest

## Synopsis

Select the oldest X number of objects before a given datetime.

## Syntax

```
Select-Oldest -InputObject <PSObject> [-Oldest] <Int32> [-Property <String>]
[<CommonParameters>]
```

## Description

Select-Oldest is a variation on Select-Object. It is designed to make it easier to select X number of objects based on a datetime property. The default property value is LastWriteTime.

## Examples

### Example 1

```
PS C:\> Get-ChildItem c:\work -file | Select-oldest 1
```

Directory: C:\work

Mode	LastWriteTime	Length	Name
----	-----	-----	----
-a---	10/6/2024 4:03 PM	2986	labsummary.format.ps1xml

Get the oldest file in the Work folder. This example is using the default -Property parameter value of LastWriteTime.

### Example 2

```
PS C:\> Get-Process | where-object name -NotMatch "idle|System" |
oldest 10 -Property starttime
```

NPM(K)	PM(M)	WS(M)	CPU(s)	Id	SI	ProcessName
-----	-----	-----	-----	--	--	-----
16	8.43	99.83	2.27	204	0	Registry
3	1.03	1.12	0.44	712	0	smss
30	2.23	5.67	4.23	816	0	csrss
11	1.52	6.65	0.02	1592	0	wininit
11	6.55	11.63	25.33	1676	0	services
7	1.10	3.27	0.09	1696	0	LsaIso
28	9.81	24.70	29.61	1704	0	lsass
4	0.81	3.31	0.00	1824	0	svchost
26	13.48	30.38	22.62	1852	0	svchost

```
6 1.91 4.15 0.11 1876 0 fontdrvhost
```

Get the oldest 10 processes that don't include Idle or System. This example is using the "oldest" alias.

## Parameters

### -InputObject

A piped in object.

```
Type: PSObject
Parameter Sets: (All)
Aliases:

Required: True
Position: Named
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

### -Oldest

Enter the number of Oldest items to select.

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Property

Enter the property name to select on. It must be a datetime object.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```



## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### System.Management.Automation.PSObject

## Outputs

### System.Object

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Select-Newest](#)

[Select-Object](#)

# Set-ConsoleTitle

## Synopsis

Set the console title text.

## Syntax

```
Set-ConsoleTitle [-Title] <String> [-WhatIf] [-Confirm] [<CommonParameters>]
```

## Description

Use this command to modify the text displayed in the title bar of your PowerShell console window. This command is intended for use in a traditional PowerShell console. It will not work in consoles that are part of the PowerShell ISE or Visual Studio Code. It should work in a PowerShell session running in Windows Terminal.

## Examples

### Example 1

```
PS C:\> Set-ConsoleTitle $env:computername
```

Set the console title to the computer name.

### Example 2

```
PS C:\> if (Test-IsAdministrator) {
 Set-ConsoleTitle "Admin: PS $($PSVersionTable.PSVersion)"
}
```

Modify the console title if running as Administrator

## Parameters

### -Confirm

Prompts you for confirmation before running the cmdlet.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: cf

Required: False
```

```
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Title

Enter the title for the console window.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -WhatIf

Shows what would happen if the cmdlet runs. The cmdlet is not run.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: wi

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable.

For more information, see about\_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

## Inputs

**None**

## Outputs

**None**

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Set-ConsoleColor](#)

# Set-LocationToFile

## Synopsis

Change your script editor terminal location. Only valid in VSCode or the ISE.

## Syntax

```
Set-LocationToFile [<CommonParameters>]
```

## Description

This command will only be available if you import the PSScriptTools module into an integrated PowerShell terminal in Visual Studio Code or the PowerShell ISE. It is designed to set the location of the terminal to the same directory as the active file. Run the command or its aliases in the integrated terminal. Use the aliases `sd` or `jmp`.

## Examples

### Example 1

```
PS D:\> sd
PS C:\Scripts\Foo\>
```

Use the `sd` alias in the integrated terminal window to change location to the directory of the active file in Visual Studio Code or the PowerShell ISE. This will also clear the host.

## Parameters

### CommonParameters

This cmdlet supports the common parameters: `-Debug`, `-ErrorAction`, `-ErrorVariable`, `-InformationAction`, `-InformationVariable`, `-OutVariable`, `-OutBuffer`, `-PipelineVariable`, `-Verbose`, `-WarningAction`, and `-WarningVariable`. For more information, see [about\\_CommonParameters](#).

## Inputs

None

## Outputs

None

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

Set-Location

# Set-PSAnsiFileMap

## Synopsis

Modify or add a PSAnsiFileEntry.

## Syntax

```
Set-PSAnsiFileMap [-Description] <String> [-Pattern <String>] [-Ansi <String>]
[-PassThru] [-WhatIf] [-Confirm] [<CommonParameters>]
```

## Description

Use this command to modify an existing entry in the global \$PSAnsiFileMap variable or add a new entry. If modifying, you must specify a regular expression pattern or an ANSI escape sequence. If you are adding a new entry, you need to supply both values.

## Examples

### Example 1

```
PS C:\> Set-PSAnsiFileMap Temporary -Ansi "`e[38;5;190m"
```

Update the ANSI pattern for temporary files. This change will not persist unless you export the map.

### Example 2

```
PS C:\> Set-PSAnsiFileMap -Description "Config" -Pattern "\.(yaml)$" -Ansi "`e[38;5;25m"ge
```

Add a new PSAnsiFileMap entry. This change will not persist unless you export the map.

## Parameters

### -Ansi

Specify an ANSI escape sequence. You only need to define the opening sequence.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
```

```
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Confirm

Prompts you for confirmation before running the cmdlet.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: cf

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Description

Specify the file map entry. If it is a new entry it will be added.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -PassThru

Display the updated map.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Pattern

Specify a regular expression pattern for the file name.



```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -WhatIf

Shows what would happen if the cmdlet runs. The cmdlet is not run.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: wi

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### None

## Outputs

### PSAnsiFileEntry

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Get-PSAnsiFileMap](#)

[Remove-PSAnsiFileEntry](#)

Export-PSAnsiFileMap

# Show-ANSISequence

## Synopsis

Display ANSI escape sequences.

## Syntax

### basic (Default)

```
Show-ANSISequence [-Basic] [-AsString] [<CommonParameters>]
```

### foreback

```
Show-ANSISequence [-Foreground] [-Background] [-Type <String>] [-AsString]
[<CommonParameters>]
```

### RGB

```
Show-ANSISequence [-RGB <Int32[]>] [-AsString] [<CommonParameters>]
```

## Description

This script is designed to make it easy to see ANSI escape sequences and how they will display in your PowerShell session. Use the -AsString parameter to write simple strings to the pipeline which makes it easier to copy items to the clipboard.

The escape character will depend on whether you are running Windows PowerShell or PowerShell 7.x. For best results, you need to run this command in a PowerShell session and host that supports ANSI escape sequences.

## Examples

### Example 1

```
PS C:\> Show-ANSISequence
```

```

* Basic Sequences *

`e[9mCrossedOut`e[0m
`e[7mReverse`e[0m
`e[6mRapidBlink`e[0m
`e[5mSlowBlink`e[0m
`e[4mUnderline`e[0m
```

```
`e[3mItalic`e[0m
`e[2mFaint`e[0m
`e[1mBold`e[0m
```

The output will be formatted using the corresponding ANSI escape sequence as seen in PowerShell 7.x.

## Example 2

```
PS C:\> Show-ANSISequence -Foreground -Type simple

* Foreground *

`e[30mHello`e[0m `e[31mHello`e[0m `e[32mHello`e[0m
`e[34mHello`e[0m `e[35mHello`e[0m `e[36mHello`e[0m
`e[90mHello`e[0m `e[91mHello`e[0m `e[92mHello`e[0m
`e[94mHello`e[0m `e[95mHello`e[0m `e[96mHello`e[0m
```

## Example 3

```
PS C:\> Show-ANSISequence -RGB 225,100,50

`e[38;2;225;100;50m256 Color (R:225)(G:100)(B:50)`e[0m
```

Show an RGB ANSI sequence. The output will be formatted using the sequence.

## Example 4

```
PS C:\> Show-ANSISequence -RGB 225,100,50 -AsString | Set-Clipboard
```

Repeat the previous example but write the output as a plain string and copy it to the clipboard.

## Parameters

### -Basic

Display basic ANSI settings. This is the default output.

```
Type: SwitchParameter
Parameter Sets: basic
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
```

```
Accept wildcard characters: False
```

## -Foreground

Display foreground ANSI format settings. If you use -Type without specifying -Foreground or -Background, -Foreground will be used by default.

```
Type: SwitchParameter
Parameter Sets: foreback
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## -Background

Display background ANSI format settings.

```
Type: SwitchParameter
Parameter Sets: foreback
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## -Type

You can display simple ANSI, 8-bit, or all sequences. Valid values are All, Simple and 8bit.

```
Type: String
Parameter Sets: foreback
Aliases:

Required: False
Position: Named
Default value: All
Accept pipeline input: False
Accept wildcard characters: False
```

## -RGB

Display an RGB ANSI sequence. You must pass an array of values for Red, Blue, and Green. Each value must be between 0 and 255.

```
Type: Int32[]
Parameter Sets: RGB
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -AsString

Show the value as an unformatted string.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### None

## Outputs

### System.String

## Notes

Learn more about ANSI sequences at [https://en.wikipedia.org/wiki/ANSI\\_escape\\_code](https://en.wikipedia.org/wiki/ANSI_escape_code)

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Write-ANSIPROGRESS](#)

New-ANSIBar

# Show-FunctionItem

## Synopsis

Show a function in written form.

## Syntax

```
Show-FunctionItem [-Name] <String> [<CommonParameters>]
```

## Description

This command will display a loaded function as it might look in a code editor. You could use this command to export a loaded function to a file.

## Examples

### Example 1

```
PS C:\> Show-FunctionItem prompt

Function Prompt {

"PS $($ExecutionContext.SessionState.Path.CurrentLocation)$('\'>' * ($nestedPromptLevel + 1)) ";
.Link
https://go.microsoft.com/fwlink/?LinkID=225750
.ExternalHelp System.Management.Automation.dll-help.xml

} #close prompt
```

### Example 2

```
PS C:\> Show-FunctionItem Copy-Zip | Out-File c:\Scripts\copy-zip.ps1
```

Here's how you can save or export a function you might have created on-the-fly to a file.

## Parameters

### -Name

What is the name of your function?

```
Type: String
Parameter Sets: (All)
```



```
Aliases:

Required: True
Position: 1
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

## Outputs

## String

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[New-FunctionItem](#)

# Show-Tree

## Synopsis

Shows the specified path as a tree.

## Syntax

### Path (Default)

```
Show-Tree [[-Path] <String[]>] [[-Depth] <Int32>] [-IndentSize <Int32>]
[-ShowItem] [-ShowProperty <String[]>] [-InColor] [<CommonParameters>]
```

### LiteralPath

```
Show-Tree [[-LiteralPath] <String[]>] [[-Depth] <Int32>] [-IndentSize <Int32>]
[-ShowItem] [-ShowProperty <String[]>] [-InColor] [<CommonParameters>]
```

## Description

Shows the specified path as a graphical tree in the console. Show-Tree is intended as a PowerShell alternative to the tree DOS command. This function should work for any type of PowerShell provider and can be used to explore providers used for configuration like the WSMAN provider or the registry. Currently, this will *not work* with any PSDrives created with the Certificate provider. It should work cross-platform.

By default, the output will only show directory or equivalent structures. But you can opt to include items well as item details by using the ShowProperty parameter. Specify a comma-separated list of properties or use \* to view them all.

If the Path is a FileSystem path there is a dynamic parameter, -InColor, that will write ANSI-colored output to the pipeline. This parameter has an alias of ansi.



This is an update to an older function in my library. I seem to recall I found the original code somewhere online, perhaps from someone like Lee Holmes. Sadly, I neglected to record the source.

## Examples

### Example 1

```
PS C:\> Show-Tree C:\Work -Depth 2

C:\work
+--A
| \--B
```

```

+---dnssuffix
| +---docs
| +---en-us
| \---images
+---gpo
| +---{65D9E940-AAD4-4508-A199-86EAE4E9E535}
| \---{7E7F01CE-6889-44B0-9D03-818F8284EDE0}
+---installers
+---remoteop
| \---archive
+---test files
\---tryme
 +---.vscode
 +---docs
 +---en-us
 \---test

```

Shows the directory tree structure, recursing down two levels.

## Example 2

```

PS C:\> Show-Tree HKLM:\SOFTWARE\Microsoft\.NETFramework -Depth 2 -ShowProp *

HKLM:\SOFTWARE\Microsoft\.NETFramework
+--- Enable64Bit = 1
+--- InstallRoot = C:\Windows\Microsoft.NET\Framework64\
+--- UseRyuJIT = 1
+---Advertised
| +---Policy
| \---v2.0.50727
+---AssemblyFolders
| +---ADOMD.Client 14.0
| | \--- (default) = C:\Program Files\Microsoft.NET\ADOMD.NET\140\
| +---Microsoft .NET Framework 3.5 Reference Assemblies
| | \--- (default) = C:\Program Files\Reference Assemblies\Microsoft\Framew...
| +---SQL Server Assemblies 140
| | \--- (default) = C:\Program Files\Microsoft SQL Server\140\SDK\Assemblies\
| +---v3.0
| | +--- <IncludeDotNet2Assemblies> = 1
| | \--- All Assemblies In = C:\Program Files\Reference Assemblies\Microsof...
| \---v3.5
| +--- <IncludeDotNet2Assemblies> = 1
| \--- All Assemblies In = C:\Program Files\Reference Assemblies\Microsof...
...

```

Shows the hierarchy of registry keys and values (-ShowProperty), recursing down two levels.

## Example 3

```

PS C:\> Show-Tree WSMAN: -ShowItem

WSMAN:\
\---localhost
 +---MaxEnvelopeSizekb
 +---MaxTimeoutms
 +---MaxBatchItems

```

```

+--MaxProviderRequests
+--Client
| +--NetworkDelays
| +--URLPrefix
| +--AllowUnencrypted
| +--Auth
| +--Basic
| +--Digest
| +--Kerberos
| +--Negotiate
...

```

Shows all the containers and items in the WSMAN: drive.

## Example 4

```

PS C:\> pstree c:\work\alpha -files -properties LastWriteTime,Length -ansi

C:\work\Alpha\
+-- LastWriteTime = 02/28/2020 11:19:32
+--bravo
| +-- LastWriteTime = 02/28/2020 11:20:30
| +--delta
| +-- LastWriteTime = 02/28/2020 11:17:35
| +--FunctionDemo.ps1
| +-- Length = 888
| \-- LastWriteTime = 06/01/2009 15:50:47
| +--function-form.ps1
| +-- Length = 1117
| \-- LastWriteTime = 04/17/2019 17:18:28
| +--function-logstamp.ps1
| +-- Length = 598
| \-- LastWriteTime = 05/23/2007 11:39:55
| +--FunctionNotes.ps1
| +-- Length = 617
| \-- LastWriteTime = 02/24/2016 08:59:03
| \--Function-SwitchTest.ps1
| +-- Length = 242
| \-- LastWriteTime = 06/09/2008 15:55:44
+--gamma
...

```

Show a tree listing with files including a few user-specified properties in color. This example is using parameter and command aliases.

## Parameters

### -Path

The path to the root of the tree that will be shown.

```

Type: String[]
Parameter Sets: Path
Aliases: FullName

```

```
Required: False
Position: 1
Default value: current location
Accept pipeline input: True (ByPropertyName, ByValue)
Accept wildcard characters: False
```

## -LiteralPath

Use a literal path value.

```
Type: String[]
Parameter Sets: LiteralPath
Aliases:

Required: False
Position: 1
Default value: None
Accept pipeline input: True (ByPropertyName)
Accept wildcard characters: False
```

## -Depth

Specifies how many levels of the specified path are recursed and shown.

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: False
Position: 2
Default value: 2147483647
Accept pipeline input: False
Accept wildcard characters: False
```

## -IndentSize

The size of the indent per level. The default is 3. The minimum value is 1. You shouldn't have to modify this parameter.

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: 3
Accept pipeline input: False
Accept wildcard characters: False
```

## -ShowItem

Shows the items in each container or folder.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: files

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## -ShowProperty

Shows the properties on containers and items. Use \* to display all properties otherwise specify a comma separated list.

```
Type: String[]
Parameter Sets: (All)
Aliases: properties

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## -InColor

Show tree and item colored. Values are from the \$PSAnsiMap variable, unless you have \$PSStyle and have configured FileInfo settings.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: ansi

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

**System.String**

## Outputs

**System.String**

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

tree.com

Get-ChildItem

# Test-EmptyFolder

## Synopsis

Test if a folder is empty of files.

## Syntax

```
Test-EmptyFolder [-Path] <String[]> [-PassThru] [<CommonParameters>]
```

## Description

This command will test if a given folder path is empty of all files anywhere in the path. This includes hidden files. The command will return True even if there are empty sub-folders. The default output is True or False but you can use -PassThru to get more information. See examples.

## Examples

### Example 1

```
PS C:\> Test-EmptyFolder c:\work
False
```

Test a single folder from a parameter.

### Example 2

```
PS C:\> Get-ChildItem c:\work -Directory | Test-EmptyFolder -PassThru
```

Path	Name	IsEmpty	Computername
----	----	-----	-----
C:\work\A	A	False	DESK10
C:\work\alpha	alpha	False	DESK10
C:\work\B	B	True	DESK10
C:\work\data	data	False	DESK10
C:\work\demo3	demo3	True	DESK10
C:\work\demos	demos	False	DESK10
...			

Test child folders under C:\work.

### Example 3

```
PS C:\> Get-ChildItem c:\work -Directory | Test-EmptyFolder -PassThru |
```



```
Where-object {$_.IsEmpty} |
Foreach-Object { Remove-Item -LiteralPath $_.path -Recurse -force -WhatIf}

What if: Performing the operation "Remove Directory" on target "C:\work\demo3".
What if: Performing the operation "Remove Directory" on target "C:\work\installers".
What if: Performing the operation "Remove Directory" on target "C:\work\new".
What if: Performing the operation "Remove Directory" on target "C:\work\sqlback".
What if: Performing the operation "Remove Directory" on target "C:\work\todd".
What if: Performing the operation "Remove Directory" on target "C:\work\[data]".
```

Find all empty sub-folders under C:\Work and pipe them to Remove-Item. This is one way to remove empty folders. The example is piping objects to ForEach-Object so that Remove-Item can use the -LiteralPath parameter, because C:\work[data] is a non-standard path.

## Parameters

### -PassThru

Write a test object to the pipeline.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Path

Enter a file system path like C:\Scripts.

```
Type: String[]
Parameter Sets: (All)
Aliases: PSPath

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByPropertyName, ByValue)
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

**System.String[]**

## Outputs

**Boolean**

**EmptyFolder**

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Get-FolderSizeInfo](#)

# Test-Expression

## Synopsis

Test a PowerShell expression over a period of time.

## Syntax

### Interval (Default)

```
Test-Expression [-Expression] <ScriptBlock> [-ArgumentList <Object[]>]
[-Count <Int32>] [-Interval <Double>] [-IncludeExpression] [-AsJob]
[<CommonParameters>]
```

### Random

```
Test-Expression [-Expression] <ScriptBlock> [-ArgumentList <Object[]>]
[-Count <Int32>] -RandomMinimum <Double> -RandomMaximum <Double>
[-IncludeExpression] [-AsJob] [<CommonParameters>]
```

## Description

This command will test a PowerShell expression or scriptblock for a specified number of times and calculate the average runtime, in milliseconds, over all the tests. The output will also show the median and trimmed values.

The median is calculated by sorting the values in ascending order and selecting the value in the center of the array. If the array has an even number of elements then the median is the average of the two values in the center. The trimmed value will toss out the lowest and highest values and average the remaining values. This may be the most accurate indication as it will eliminate any small values which might come from caching and any large values which may come a temporary shortage of resources. You will only get a value if you run more than 1 test.

## Examples

### Example 1

```
PS C:\> $cred = Get-Credential globomantics\administrator
PS C:\> $c = "chi-dc01","chi-dc04"
PS C:\> Test-Expression {
 param ([string[]]$computer,$cred)
 Get-CimInstance win32_logicaldisk -computername $computer -credential $cred
} -argumentList $c,$cred

Tests : 1
TestInterval : 0.5
```

```
AverageMS : 1990.6779
MinimumMS : 1990.6779
MaximumMS : 1990.6779
MedianMS : 1990.6779
TrimmedMS :
PSVersion : 5.1.19041.1
OS : Microsoft Windows 10 Pro
```

Test a command once passing an argument to the scriptblock. There is no TrimmedMS value because there was only one test.

## Example 2

```
PS C:\> $sb = {1..1000 | Foreach-Object {$_*2}}
PS C:\> Test-Expression $sb -count 10 -interval 2

Tests : 10
TestInterval : 2
AverageMS : 72.78199
MinimumMS : 29.4449
MaximumMS : 110.6553
MedianMS : 90.3509
TrimmedMS : 73.4649625
PSVersion : 5.1.19041.1
OS : Microsoft Windows 10 Pro

PS C:\> $sb2 = { foreach ($i in (1..1000)) {$_*2}}
PS C:\> Test-Expression $sb2 -Count 10 -interval 2

Tests : 10
TestInterval : 2
AverageMS : 6.40283
MinimumMS : 0.7466
MaximumMS : 22.968
MedianMS : 2.781
TrimmedMS : 5.0392125
PSVersion : 5.1.19041.1
OS : Microsoft Windows 10 Pro
```

These examples are testing two different approaches that yield the same results over a span of 10 test runs, pausing for 2 seconds between each test. The values for Average, Minimum, and Maximum are in milliseconds.

## Example 3

```
PS C:\> Test-Expression {
 Param([string]$computer)
 Get-Service bits,wuauserv,winrm -computername $computer
} -count 5 -IncludeExpression -argumentList chi-hvr2

Tests : 5
TestInterval : 500
AverageMS : 15.53376
MinimumMS : 11.6745
MaximumMS : 24.9331
```

```

MedianMS : 13.8928
TrimmedMS : 13.6870666666667
PSVersion : 5.1.19041.1
OS : Microsoft Windows 10 Pro
Expression : Param([string]$computer) get-service bits,wuauserv,winrm -com...
Arguments : {chi-hvr2}

```

Include the tested expression in the output.

## Example 4

```

PS C:\> $j == Test-Expression { get-eventlog -list } -count 10 -Interval 5 -AsJob
PS C:\> $j | Receive-Job -keep

Tests : 10
TestInterval : 5
AverageMS : 2.80256
MinimumMS : 0.7967
MaximumMS : 14.911
MedianMS : 1.4469
TrimmedMS : 1.5397375
PSVersion : 5.1.19041.1
OS : Microsoft Windows 10 Pro
RunspaceId : f30eb879-fe8f-4ad0-8d70-d4c8b6b4eccc

```

Run the test as a background job. When the job is complete, get the results.

## Example 5

```

PS C:\> {1..1000} | Test-Expression -count 10 -RandomMinimum 1 -RandomMaximum 10

Tests : 10
TestInterval : Random
AverageMS : 0.63899
MinimumMS : 0.2253
MaximumMS : 3.9062
MedianMS : 0.24475
TrimmedMS : 0.2823
PSVersion : 5.1.19041.1
OS : Microsoft Windows 10 Pro

```

Pipe a scriptblock to be tested.

## Parameters

### -ArgumentList

An array of parameters to pass to the test scriptblock. Arguments are positional. If passing an array for a value enter with @().

```
Type: Object[]
```

```
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -AsJob

Run the tests as a background job.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: False
Accept pipeline input: False
Accept wildcard characters: False
```

## -Count

The number of times to test the scriptblock.

```
Type: Int32
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: 1
Accept pipeline input: True (ByPropertyName)
Accept wildcard characters: False
```

## -Expression

The scriptblock you want to test.

```
Type: ScriptBlock
Parameter Sets: (All)
Aliases: sb

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

## -IncludeExpression

Include the test scriptblock in the output.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases: ie

Required: False
Position: Named
Default value: False
Accept pipeline input: True (ByPropertyName)
Accept wildcard characters: False
```

## -Interval

How much time to sleep in seconds between each test. The maximum value is 60. You may want to use a sleep interval to mitigate possible caching effects.

```
Type: Double
Parameter Sets: Interval
Aliases: sleep

Required: False
Position: Named
Default value: 0.5
Accept pipeline input: True (ByPropertyName)
Accept wildcard characters: False
```

## -RandomMaximum

You can also specify a random interval by providing random minimum and maximum values in seconds.

```
Type: Double
Parameter Sets: Random
Aliases: max

Required: True
Position: Named
Default value: 0
Accept pipeline input: False
Accept wildcard characters: False
```

## -RandomMinimum

You can also specify a random interval by providing random minimum and maximum values in seconds.

```
Type: Double
Parameter Sets: Random
Aliases: min
```

```
Required: True
Position: Named
Default value: 0
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about\_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

## Inputs

### scriptblock

## Outputs

## TestResult

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

This command was first described at <https://github.com/jdhitsolutions/Test-Expression/blob/master/docs/Test-Expression.md>

## Related Links

Measure-Command

[Test-ExpressionForm](#)



# Test-ExpressionForm

## Synopsis

Display a graphical test form for Test-Expression.

## Syntax

```
Test-ExpressionForm [<CommonParameters>]
```

## Description

This command will display a WPF-based form that you can use to enter in testing information. Testing intervals are in seconds. All of the values are then passed to the Test-Expression command. Results will be displayed in the form. The results only show you how long the tests took, regardless of whether or not there were errors.

When you close the form, the last result object will be passed to the pipeline, including all metadata, the scriptblock, and arguments.

This command requires a Windows platform that supports WPF.

## Examples

### Example 1

```
PS C:\> Test-ExpressionForm
```

Launch the form.

## Parameters

### CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about\_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

## Inputs

### None

## Outputs

## System.Object

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

This command was first explained at <https://github.com/jdhitsolutions/Test-Expression/blob/master/docs/Test-ExpressionForm.md>

## Related Links

[Test-Expression](#)

[Measure-Command](#)

# Test-IsElevated

## Synopsis

Test if the current user is running elevated.

## Syntax

```
Test-IsElevated [<CommonParameters>]
```

## Description

This command will test if the current session is running elevated, or as Administrator. On Windows platforms, the command uses the .NET Framework to determine if the user is running as Administrator. On non-Windows systems, the command is checking the user's UID value.

## Examples

### Example 1

```
PS C:\> Test-IsElevated
True
```

## Parameters

### CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### None

## Outputs

### Boolean

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[Get-PSWho](#)

# Test-IsPSWindows

## Synopsis

Test if running PowerShell on a Windows platform.

## Syntax

```
Test-IsPSWindows [<CommonParameters>]
```

## Description

PowerShell Core introduced the `$IsWindows` variable. However, it is not available on Windows PowerShell. Use this command to perform a simple test if the computer is either running Windows or using the Desktop PSEdition.

## Examples

### Example 1

```
PS C:\> Test-IsPSWindows
True
```

## Parameters

### CommonParameters

This cmdlet supports the common parameters: `-Debug`, `-ErrorAction`, `-ErrorVariable`, `-InformationAction`, `-InformationVariable`, `-OutVariable`, `-OutBuffer`, `-PipelineVariable`, `-Verbose`, `-WarningAction`, and `-WarningVariable`. For more information, see [about\\_CommonParameters](#).

## Inputs

### None

## Outputs

### System.Boolean

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

# Test-WithCulture

## Synopsis

Test your PowerShell code using a different culture.

## Syntax

### scriptblock (Default)

```
Test-WithCulture [-Culture] <CultureInfo> [-Scriptblock] <ScriptBlock>
[-ArgumentList <Object[]>] [<CommonParameters>]
```

### file

```
Test-WithCulture [-Culture] <CultureInfo> -FilePath <ScriptBlock>
[-ArgumentList <Object[]>] [<CommonParameters>]
```

## Description

When writing PowerShell commands, sometimes the culture you are running under becomes critical. For example, European countries use a different datetime format than North Americans which might present a problem with your script or command. Unless you have a separate computer running under the foreign culture, it is difficult to test. This command will allow you to test a scriptblock or even a file under a different culture, such as DE-DE for German.

Note that this command is not an absolute test. There may be commands that fail to produce the alternate culture results you expect.

## Examples

### Example 1

```
PS C:\> Test-WithCulture de-de -Scriptblock {(Get-Date).addDays(90)}
Montag, 14. Oktober 2020 08:59:01
```

### Example2

```
PS C:\> Test-WithCulture fr-fr -Scriptblock {
 Get-winEvent -log system -max 500 |
 Select-Object -Property TimeCreated,ID,OpCodeDisplayName,Message |
 Sort-Object -property TimeCreated |
 Group-Object {$_.TimeCreated.ToShortDateString()} -NoElement
```

```
}

Count Name

165 10/07/2020
249 11/07/2020
17 12/07/2020
16 13/07/2020
20 14/07/2020
26 15/07/2020
7 16/07/2020
```

## Parameters

### -ArgumentList

Specify an array of positional arguments to pass to the scriptblock for file.

```
Type: Object[]
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Culture

Enter a new culture like de-de

```
Type: CultureInfo
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -FilePath

Enter the path to a PowerShell script file to execute using the specified culture.

```
Type: ScriptBlock
Parameter Sets: file
Aliases:

Required: True
```



```
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Scriptblock

Enter a scriptblock to execute using the specified culture. Be aware that long or complex pipelined expressions might not give you the culture-specific results you expect.

```
Type: ScriptBlock
Parameter Sets: scriptblock
Aliases:

Required: True
Position: 1
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### None

## Outputs

## System.Object

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

Get-Culture

Get-UICulture

# Trace-Message

## Synopsis

Create a graphical trace window.

## Syntax

### message (Default)

```
Trace-Message [[-Message] <String>] [<CommonParameters>]
```

### init

```
Trace-Message [-Title <String>] [-BackgroundColor <String>] [-Width <Int32>]
[-Height <Int32>] [<CommonParameters>]
```

## Description

Trace-Message is designed to be used with script or function. Its purpose is to create a graphical trace window using Windows Presentation Foundation. Inside the function or script, you can use this command to send messages to the window. When finished, you have an option to save the output to a text file.

There are 3 steps to using this function. First, in your code, you need to create a boolean global variable called `TraceEnabled`. When the value is `$True`, the `Trace-Message` command will run. When set to false, the command will be ignored. Second, you need to initialize a form, specifying the title and dimensions. The form will automatically include some pre-defined metadata. Finally, you can send trace messages to the window. All messages are prepended with a timestamp.

This command is not optimized for performance and is intended for development purposes. When your code is finished, you can set `$TraceEnabled` to `$False`. If you need to troubleshoot, you can set it to `$True`.

## Examples

### Example 1

```
PS C:\> Trace-Message -title "Troubleshooting Log" -width 600
```

This command will initialize a trace window with the given title and width. It is assumed you have set `$TraceEnabled` to `$True`. This is a command you would normally run in your code and not from the console.

## Example 2

```
PS C:\> Trace-Message -message "Starting MyCommand"
```

This example is a continuation of the previous example. The message text will be appended to the graphical form, prepended with a timestamp.

## Parameters

### -BackgroundColor

Specify a background color for the trace window. You can use console colors like "Cyan" or HTML color codes.

```
Type: String
Parameter Sets: init
Aliases:

Required: False
Position: Named
Default value: "#FFFFFF8DC",
Accept pipeline input: False
Accept wildcard characters: False
```

### -Height

Specify the Width of the trace window.

```
Type: Int32
Parameter Sets: init
Aliases:

Required: False
Position: Named
Default value: 500
Accept pipeline input: False
Accept wildcard characters: False
```

### -Message

Specify a message to write to the trace window.

```
Type: String
Parameter Sets: message
Aliases:

Required: $True
Position: 0
Default value: None
Accept pipeline input: True (ByValue)
```

```
Accept wildcard characters: False
```

## -Title

Specify a title for the trace window.

```
Type: String
Parameter Sets: init
Aliases:

Required: False
Position: Named
Default value: "Trace Messages"
Accept pipeline input: False
Accept wildcard characters: False
```

## -Width

Specify the Width of the trace window.

```
Type: Int32
Parameter Sets: init
Aliases:

Required: False
Position: Named
Default value: 800
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### System.String

## Outputs

### None

## Notes

Look at \$PSSamplePath\Get-Status.ps1 for a demonstration of this command in a function. The buttons have

key accelerators of Q and S.

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

Write-Verbose

## Synopsis

## Syntax

## Description



## Examples

## Example 1

78%

## Example 2

Create a single progress bar for 78% using the Circle symbol and a custom color.

## Example 3

```
PS C:\> Get-CimInstance -ClassName Win32_OperatingSystem |
Select-Object -property @{Name="Computername";Expression={$_.CSName}},
@{Name="TotalMemGB";Expression={Format-Value $_.TotalVisibleMemorySize -unit MB}},
@{Name="FreeMemGB";Expression={Format-Value $_.FreePhysicalMemory -unit MB}},
@{Name="PctFree"; Expression={
$pct = Format-Percent $_.FreePhysicalMemory $_.TotalVisibleMemorySize
Write-ANSIProgress -PercentComplete ($pct/100) | Select-Last 1
}}
```

```
Computername TotalMemGB FreeMemGB PctFree

BOVINE320 32 12 37.87% ██████████
```

Note that this example uses abbreviations in the Select-Object hashtables.

## Example 4

```
PS C:\> $sb = {
 Clear-Host
 $top = Get-ChildItem c:\scripts -Directory
 $i = 0
 $out=@()
 $pos = $host.UI.RawUI.CursorPosition
 Foreach ($item in $top) {
 $i++
 $pct = [math]::round($i/$top.count,2)
 Write-ANSIProgress -PercentComplete $pct -position $pos
 Write-Host " Processing $($item.FullName.PadRight(80))" -NoNewline
 $out+= Get-ChildItem -Path $item -Recurse -file |
 Measure-Object -property length -sum |
 Select-Object @{Name="Path";Expression={$item.FullName}},Count,
 @{Name="Size";Expression={$_.Sum}}
 }
 Write-Host ""
 $out | Sort-Object -property Size -Descending
}
PS C:\> Invoke-Command -scriptblock $sb
```

You are most likely to use this command in a function or script. This example demonstrates using a script block.

## Parameters

### -BarSymbol

Specify what shape to use for the progress bar.

```
Type: String
Parameter Sets: (All)
Aliases:
Accepted values: Box, Block, Circle
```

```
Required: False
Position: Named
Default value: Box
Accept pipeline input: False
Accept wildcard characters: False
```

## -PercentComplete

Enter a percentage in a decimal value like .25 up to 1.

```
Type: Double
Parameter Sets: (All)
Aliases:

Required: True
Position: 0
Default value: None
Accept pipeline input: True (ByValue)
Accept wildcard characters: False
```

## -Position

Specify the cursor position or where you want to place the progress bar.

```
Type: Coordinates
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: Current position
Accept pipeline input: False
Accept wildcard characters: False
```

## -ProgressColor

Specify an ANSI escape sequence for the progress bar color. You could also use a PSStyle setting.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```



## -ToHost

Write to the host, not the PowerShell pipeline. You may want to do this if using this command in a script or function so the output is not commingled with your command output.

```
Type: SwitchParameter
Parameter Sets: (All)
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see [about\\_CommonParameters](#).

## Inputs

### System.Double

## Outputs

### System.String

## Notes

This command will not work in the PowerShell ISE. The verbose output should only be used when troubleshooting a display problem.

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

## Related Links

[New-ANSIBar](#)

[New-RedGreenGradient](#)

[Show-ANSISquence](#)

# Write-Detail

## Synopsis

Write a detailed message string.

## Syntax

### Default (Default)

```
Write-Detail [[-Message] <String>] [-Prefix <String>] [<CommonParameters>]
```

### Time

```
Write-Detail [[-Message] <String>] [-Prefix <String>] [-Time]
[<CommonParameters>]
```

### Date

```
Write-Detail [[-Message] <String>] [-Prefix <String>] [-Date]
[<CommonParameters>]
```

## Description

This command is designed to be used within your functions and scripts to make it easier to write a detailed message that you can use as verbose output. The assumption is that you are using an advanced function with Begin, Process, and End scriptblocks. You can create a detailed message to indicate what part of the code is being executed. The output can include a full-time stamp, or a time string which includes a millisecond value.

In a script you might use it like this in a Begin block:

```
$pfx = "BEGIN"

Write-Detail "Starting $($MyInvocation.MyCommand)" -Prefix $pfx | Write-Verbose

Write-Detail "PS $($PSVersionTable.PSVersion)" -Prefix $pfx | Write-Verbose
```

If you don't specify a prefix, it will default to PROCESS.

## Examples

## Example 1

```
PS C:\> Write-Detail "Getting file information" -Prefix Process
[PROCESS] Getting file information
```

Normally you would use this command in a function, but here is an example from the console so that you can see what to expect.

## Example 2

```
PS C:\> Write-Detail -message "Initializing variables" -Prefix Begin -time
01:25:29:8700 [BEGIN] Initializing variables
```

## Parameters

### -Message

The message to display after the time stamp and prefix.

```
Type: String
Parameter Sets: (All)
Aliases:

Required: False
Position: 0
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

### -Prefix

Indicate whether you are in the BEGIN, PROCESS, or END script block. Although you can specify any text. It will be displayed in upper case.

```
Type: String
Parameter Sets: (All)
Aliases:
Accepted values:

Required: False
Position: Named
Default value: PROCESS
Accept pipeline input: False
Accept wildcard characters: False
```

## -Date

Display a date value like 9/15/2024 11:36:41.

```
Type: SwitchParameter
Parameter Sets: Date
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## -Time

Display a time value with milliseconds like 11:37:01:4029.

```
Type: SwitchParameter
Parameter Sets: Time
Aliases:

Required: False
Position: Named
Default value: None
Accept pipeline input: False
Accept wildcard characters: False
```

## CommonParameters

This cmdlet supports the common parameters: -Debug, -ErrorAction, -ErrorVariable, -InformationAction, -InformationVariable, -OutVariable, -OutBuffer, -PipelineVariable, -Verbose, -WarningAction, and -WarningVariable. For more information, see about\_CommonParameters (<http://go.microsoft.com/fwlink/?LinkID=113216>).

## Inputs

### None

## Outputs

### System.String

## Notes

Learn more about PowerShell: <https://jdhitsolutions.com/yourls/newsletter>

**Related Links**

Write-Verbose

# Change Log for PSScriptTools

This file contains the most recent change history for the PSScriptTools module.

## 3.0.0 - 2025-03-26

### Added

- Added command `Get-FileExtensionInfo`.
- Added command `Get-TypeConstructor` with an alias of `ctor` and a custom formatting file.
- Added commands `Get-PSScriptToolsTypeExtension` and ``Import-PSScriptToolTypeExtension`
- Added custom type extension file for `MeasureInfo` objects.

### Changed

- Updated formatting for `Get-PSProfile` to display profiles not found in red.
- Updating formatting for `Get-ModuleCommand` to display aliases using the command color and italicized.
- Modified `Convert-EventLogRecord` ([Issue #153](#))
- Merged [PR#153](#) Thanks [@jaols](#)
- Changed required module from the soon to be deprecated `ThreadJob` to `Microsoft.PowerShell.ThreadJob`.
- Major help updates and corrections.
- Updated `README.md`.

### Removed

- Removed sample script `today.ps1` because `ConvertTo-ASCIIArt` is no longer part of this module.

### Fixed

- Fixed download link in `Save-GitSetup`.
- Corrected wrong type name for the `FilePath` parameter in `Test-WithCulture`.
- Corrected a bug in `Get-PSWhoIs` that was failing when no organization information was present. [Issue #151](#)
- Corrected code typo on `Trace-Message`.

## 2.50.0 - 2024-07-13

### Added

- Added an argument completer for the `Name` parameter of `Show-FunctionItem`.
- Added a new `Property` parameter to `Get-PSUnique` to allow the user to specify a property or properties to use for comparison. The command will also display a warning if a comparison can't be made. [Issue #150](#)

### Changed

- Ongoing and general code cleanup.
- Removed previously deprecated commands `Set-ConsoleColor` and `Out-ConditionalColor`.
- Changed `Get-PSScriptTools` to use saved data from a JSON file instead of building the data from `Get-Command`, `Get-Alias`, and `Get-Help``. This also fixes display problems with the `Synopsis` property in Linux.
- Changed `Write-ANSIProgress` by adding a parameter to write to the host and not the pipeline.
- Updated `README`.

### Fixed

- Removed obsolete comment-based help for `New-PSDynamicParameter`.



## 2.49.0 - 2024-06-06

### Added

- Modified `ConvertTo-Markdown` to use `Property` and `Value` headings when converting to a list.
- Added `CimMember` functions `Get-CimNamespace`, `Get-CimClassMethod`, `Get-CimClassProperty`, `Get-CimClassPropertyQualifier`, `Get-CimClassName` and `Get-CimMember`. ([Issue #137](#))
- Added custom formatting for `Get-CimClassName`.
- Added the module `ThreadJob` as a module dependency to the manifest.

### Changed

- Modified module manifest to remove version logic on function export. Now exporting everything. If there is an OS limitation, try to handle it on a per-command basis. **This may be a breaking change.**
- Changed PDF manual theme from `github` to `github.dark`.
- Updated `Get-ParameterInfo` to recognize `ProgressAction` as a common parameter. This parameter was add in PowerShell 7.
- Updated the default table view for output from `Get-ModuleCommand` to include the module version number.
- Modified `Show-Tree` to better handle multi-string and binary values in the registry.
- Modified `Show-Tree` to use `PSStyle.FileInfo` for color information if detected. ([Issue #147](#))
- Updated `README.md`
- Revised `Get-FolderSizeInfo` to be more consistent between PowerShell versions. The command will skip counting all reparse points. **This may be a breaking change.** ([Issue #145](#))
- Re-wrote `Find-CimClass` to use `CimSession`.
- Revised `Get-ParameterInfo` to sort the output by default using `ParameterSet`, `Position`, and `Name`
- Help updates.

### Fixed

- Revised `Get-WindowsVersion` to handle non-English cultures. ([Issue #142](#))
- Fixed bug in `Convert-EventLogRecord` that failed on duplicate property name ID. ([Issue #143](#))

## v2.48.0 - 2023-07-28

### Added

- Added parameter `ProviderName` to `Get-CommandSyntax` to let the user specify a provider.  
[Issue #139](#)

### Changed

- Modified `Get-ParameterInfo` to sort output by parameter set. [Issue #138](#)
- Modified the format file for `psparameterinfo` objects to use a table as the default.
- Added `EnumOnly` parameter to `Get-TypeMember` [Issue #135](#)
- Help updates

## v2.47.0 - 2023-05-25

### Changed

- Added missing online help links.
- Updated module description in the manifest.
- Added `EnableLN` parameter alias to `Get-FolderSizeInfo`.
- Help updates.
- Update `Get-TypeMember` to identify properties that are enumerations.
- Updated format file for `Get-TypeMember` to highlight enum properties.
- Updated `README.md`.

## v2.46.0 - 2023-03-03

### Changed

- General code cleanup and formatting.
- Modified module to only load ANSI file format features if PSStyle is not detected.
- Modified `psparameterinfo.format.ps1xml` to highlight True values with an ANSI highlight color.
- Modified `Get-FolderSizeInfo` to use `System.Collections.Generic.List[]` in place of `ArrayList`.
- Modified back-end processing for the help PDF file to reduce its size.
- Restored header to `Get-PSScriptTools`.
- Help updates.
- Revised Changelog layout.
- Updated `README.md`.

### Fixed

- Fixed a bug in `Get-GitSize` that was failing to get hidden items in the `.git` folders. Also modified the command to use `Get-FolderSizeInfo` which is faster than using `Get-ChildItem`.
- Modified `Get-PSScriptTools` to properly return version information.

### Added

- Added function `Get-TypeMember` with format file `pstypemember.format.ps1xml` and type extension `pstypemember.types.ps1xml`. The function has an alias of `gtm`.
- Added the parameter `MainBranch` to `Remove-MergedGitBranch` to allow the user to specify the name of their main or master branch. The default is `master`.

### Deprecated

- Marked `Out-ConditionalColor` and `Set-ConsoleColor` as deprecated. They will be removed in a future release.

## v2.45.0 - 2022-09-16

- Fixed help typo for `Get-PSUnique` [PR 133](#). Thank you @fiala-sns.
- Updated `Get-WindowsVersion` to include `DisplayVersion`, e.g. 22H2.
- Modified format file `windowsversion.format.ps1xml` to replace `ReleaseID` with the `DisplayVersion` value.
- Revised `Get-WindowsVersion` to use `systeminfo` to retrieve the operating system name and if that fails, fall back to using the registry entry. The registry entry for Windows 11 typically still shows Windows 10.
- Help updates.
- Updated `README.md`.

## [v2.43.0] - 2022-04-04

- Fixed VSCode snippets to run in a PowerShell 7 integrated console. [Issue #124](#)
- Updated `Show-AnsiSequence` to fix a display bug that was dropping values. [Issue #125](#)
- Removed `ConvertTo-ASCIIArt` as the online resource no longer appears to exist. [Issue #127](#)
- Updated missing online help links.
- Updated `Get-FoldersizeInfo` to better handle null values. [Issue #129](#)
- Added new sample script `today.ps1`.
- Help updates.
- Updated `README.md`.

## Archive

If you need to see older change history, look at the [Archive ChangeLog](#) online.