

Combining physics-informed machine learning with transportation science methods to tackle large-scale urban mobility problems

Carolina Osorio
Google Research, HEC Montreal

Martin Mladenov, Chao Zhang, Chih-wei Hsu, Sanjay Ganapathy Subramaniam,
Quan Nguyen, Suyash Vishnoi, Akhil Shetty, Iveel Tsogsuren
Yechen Li, Neha Arora, Andrew Tomkins, Craig Boutilier

Google Research

Big Data, AI and Transportation
Planning Applications
May 30, 2025, UW, Seattle WA


Physics-informed Traffic Optimization




- Digital twins of mobility systems
- Physics-informed algorithms:
 - Sample efficiency
 - Dimensionality reduction
 - Variance reduction
- Future research opportunities

Simulation-based optimization for traffic operations and planning

Building high quality traffic simulations to evaluate traffic management policies and use simulation-based optimization to suggest interventions to optimize transportation networks for sustainability, safety and reduction of congestion.





Simulation of car traffic near an intersection in Salt Lake City






Urban mobility simulation + optimization
finds best configurations for
infrastructure and policy

Simulation Platform



OD demand calibration



$$\begin{aligned} \min_x \quad & f(x) = \frac{1}{|I|} \sum_{i \in I} w_i (v_i^{\text{GT}} - E[v_i(x, u_1; u_2)])^2 \\ \text{s.t.} \quad & 0 \leq x \leq x_U \end{aligned}$$

- Goal: find a travel demand input that, once simulated, yields simulated traffic statistics that match ground truth field data.
- Traffic statistics: segment counts, segment speeds.
- Regularization
- Inverse problem
- Challenges: dimensionality, stochasticity, compute-time, non-differentiability

A decorative blue line graphic in the top right corner, consisting of several connected segments with circular endpoints, forming a jagged, upward-pointing shape.

(1) Achieving sample efficiency through metamodeling

Sample efficiency: metamodeling

$$\begin{aligned} \min_x \quad & f(x) = \frac{1}{|\mathcal{I}|} \sum_{i \in \mathcal{I}} w_i (v_i^{\text{GT}} - E[v_i(x, u_1; u_2)])^2 \\ \text{s.t.} \quad & 0 \leq x \leq x_U \end{aligned}$$

\leftrightarrow

$$\begin{aligned} \min_x \quad & m_k(x; \beta_k) = \beta_{k,0} f_A(x) + \phi(x; \beta_k) \\ \text{s.t.} \quad & f_A(x) = \frac{1}{|\mathcal{I}|} \sum_{i \in \mathcal{I}} w_i (v_i^{\text{GT}} - v_i^{\text{a}})^2 \\ & \phi(x; \beta_k) = \beta_{k,1} + \sum_{z \in \mathcal{Z}} \beta_{k,z+1} x_z \end{aligned}$$

- Combining macroscopic + microscopic models
- Macro: differentiable and compute-efficient
- Micro: high-resolution

$$v_i^{\text{a}} = v_i^{\min} + (v_i^{\max} - v_i^{\min}) \left(1 - \left(\frac{q_i}{q_i^{\max}} \right)^{\alpha_i^1} \right)^{\alpha_i^2} \quad \forall i \in \mathcal{I}$$

$$q = Ax$$

$$0 \leq x \leq x_U$$

Calibration on:

Path travel times:

Segment speeds:

Probe segment counts:


Zhang et al. (2024) IEEE ITSC

Vishnoi et al. (2023) ACM SIGSPATIAL

Alanqary et al. (2025) TRISTAN

Sample efficiency: metamodeling

- Salt Lake City
- Segment speeds calibration
- 62-dimensional instance
- 100 sequential simulations





Vishnoi, S., Tsogsuren, I., Arora, N., Osorio, C. (2023) ACM SIGSPATIAL

(2) Achieving scalability through dimensionality reduction

OD demand calibration

$$\begin{aligned} \min_x \quad & f(x) = \frac{1}{|I|} \sum_{i \in I} w_i (v_i^{\text{GT}} - E[v_i(x, u_1; u_2)])^2 \\ \text{s.t.} \quad & 0 \leq x \leq x_U \end{aligned}$$

- Traditional modeling approach:
 - Discretize space into disjoint zones, traffic analysis zones (TAZes)
 - Consider the set of plausible pairs of zones. High dimensional set !
- OD calibration problem is underdetermined
 - Level of underdetermination typically increases with road network size
- **Should we be solving the problem in this high-dimensional space ?**
- Find lower dimensional spaces to:
 - Enhance computational efficiency of existing calibration algorithms
 - Reduce underdetermination



Scalability: dimensionality reduction

- Can we develop sample-efficient transportation-relevant dimensionality reduction techniques ?
- A: **assignment matrix**, network loading map
- Use a low-rank approximation of the assignment matrix A
- Singular value decomposition of A
- Select a submatrix of V of column-dimension k that captures the most information in A
- This low-rank approximation of A minimizes the L2 norm and the Frobenius norm of the difference from A
- Maps from the high d-dimensional OD space to the low k-dimensional space, designed to
 - **Preserve traffic-specific information from the assignment matrix A**
 - **Is sample-efficient: approach does not require any simulation data**
- We theoretically prove that this method reduces the underdetermination of the problem



$$A \theta = s$$

$$A = U \Sigma V^{\top}$$


$$\hat{V} \in R^{d \times k}$$

Scalability: dimensionality reduction

- 62-dimensional instance
- 79 count sensors
- Optimizer: metamodel, Osorio (2019)
- Dimensionality reduction (DR)
 - PCA principal component analysis, Pearson (1901)
 - SIR: sliced inverse regression, Li et al. (1991)
 - Active subspace, Constantine et al. (2014)
 - Physics-informed active subspace, Nguyen and Osorio (2023)
 - Assignment: Physics-informed metamodel DR, Nguyen and Osorio (2023)



Carolina Osorio





Salt Lake City


Google Research

Scalability: dimensionality reduction

- 2449-dimensional instance
- 76 sensors
- Count data from Utah DOT



- Lack of sample efficiency
 - SIR: sliced inverse regression: requires initial sample of size at least d (OD dimension)
 - Active subspace: requires derivatives (simulation-based or surrogate-based)

A decorative blue line graphic in the top right corner, consisting of several connected segments with circular endpoints, forming a jagged, upward-pointing shape.


(3) Achieving scalability through variance reduction

Scalability challenges: gradient estimation

- Adversarial formulation
 - Mladenov et al. (2022) ACM SIGSPATIAL
- Gradients can be estimated by a scoring function estimator:

$$\begin{aligned}\nabla_{\omega} \mathbb{E}_{\theta \sim \pi_{\omega}, o \sim s(\theta)} [\text{loss}(o)] &= \mathbb{E}_{\theta \sim \pi_{\omega}, o \sim s(\theta)} \left[\text{loss}(o) \frac{\nabla_{\theta} \pi_{\omega}(\theta)}{\pi_{\omega}(\theta)} \right] \\ &\approx \frac{1}{n} \sum_i \text{loss}(o_i) \frac{\nabla \pi_{\omega}(\theta_i)}{\pi_{\omega}(\theta_i)} = \frac{1}{n} \sum_i \text{loss}(o_i) \nabla \log \pi_{\omega}(\theta_i)\end{aligned}$$

- The variance of the estimator may grow exponentially with the number of ODs (dimensionality)
- Mitigation:
 - variance reduction technique
 - metamodel-based control variates



Field data	$o \in O$
Parameter space:	$\theta \in \Theta$
Simulator:	$s_{\theta} \in \Delta(O)$

Variance reduction techniques

- In Monte Carlo simulation the error goes as: σ / \sqrt{n}
- Reduce variance by:
 - Increasing n
 - Decreasing σ
- Control variates
 - Goal: estimate $E[X] = \nu$
 - Consider a r.v. Y with known mean μ
 - Choose Y such that:
 - $E[X - (Y - \mu)] = \nu$
 - $\text{Var}(X - (Y - \mu)) < \text{Var}(X)$
 - Simulate: $X - \lambda(Y - \mu)$
 - With an optimal choice of λ : $\text{Var}(X - \lambda(Y - \mu)) = \text{Var}(X) (1 - \rho^2)$
 ρ : correlation of X and Y
 - Amount of variance reduction depends on how well the two correlate.
- Define metamodel-based control variates

Metamodel-based variance reduction

$$\nabla_{\omega} \mathbb{E}_{\theta \sim \pi_{\omega}, o \sim s(\theta)} [\text{loss}(o)] \approx \frac{1}{n} \sum_i \text{loss}(o_i) \nabla \log \pi_{\omega}(\theta_i)$$



$$\nabla_{\omega} \mathbb{E}_{\theta \sim \pi_{\omega}, o \sim s(\theta)} [\text{loss}(o)] = \frac{1}{n} \sum_i (\text{loss}(o_i) - \lambda \text{loss}(s_i)) \nabla \log \pi_{\omega}(\theta_i) + \lambda \mu$$


1. Sample ODs θ_i from π_{ω}
2. Simulate θ_i to obtain counts o_i
3. Compute metamodel counts s_i : $A \theta = s$
4. New gradient estimator based on metamodel error

$$\nabla_{\omega} \mathbb{E}_{\theta \sim \pi_{\omega}, o \sim s(\theta)} [\text{loss}(o)] = \frac{1}{n} \sum_i (\text{loss}(o_i) - \lambda \text{loss}(s_i)) \nabla \log \pi_{\omega}(\theta_i) + \lambda \mu$$


- μ : mean of the metamodel gradient estimator (can be computed on a much larger sample)
- λ : scaling parameter

Metamodel-based variance reduction

62-dimensional Salt Lake City case study



- 2x faster convergence
- Variance reduction on the order of 10x is often observed.



Gradient covariance matrix: vanilla vs. control variate

Opportunities

- Travel demand calibration: Traffic physics + metamodeling enables scalability through:
 - Enhanced sample efficiency
 - Dimensionality reduction
 - Variance reduction
- Treating the transportation system and data as a gray-box rather than a black-box
- Big-data + deep learning models are not plug-and-play
 - Lack sample efficiency, lack scalability
 - There is great potential to enhance them for transportation applications through the use of simple transportation science ideas
- Most transportation stakeholders live in a data sparse, and/or often compute sparse, environment: Importance of designing data-efficient and sample-efficient methods relevant for transportation
- Data-efficiency
 - How can we make the most out of our existing field data?
 - Use of higher-order statistics from, spatially or temporally, sparse field data
 - How can we use it to:
 - Quantify uncertainty, and derive more resilient and robust mobility solutions ?
 - Quantification of model parameter uncertainty: Greisemer et al. (2024) NeurIPS
 - Reduce the level undetermination or ill-posedness of fundamental transportation problems?

Thank You