

## 0.DG配置要点

prod1归档模式

prod1归档路径/home/oracle/flash

强制日志：alter database force logging

redo log日志组追加：alter database add standby logfile ('/u01/app/oracle/oradata/PROD1/redo04.log') size 50m;

关闭闪回：alter database flashback off;

删除外部表:通过select owner,table\_name from dba\_external\_tables;来查看

查看数据库data文件路径是否都是:/u01/app/oracle/oradata/PROD1

控制文件 都存在:/u01/app/oracle/oradata/PROD1

local\_listener置空

diag日志路径为:/u01/app/oracle

initPROD1.ora里面注意下面参数设置

**DB\_NAME=chicago**

**CONTROL\_FILES='/arch1/chicago/control1.ctl', '/arch2/chicago/control2.ctl'**

**LOG\_ARCHIVE\_MAX\_PROCESSES=30**

启动要以spfile为启动

Listener静态监听

TNSNAMES注意括号匹配

**init文件中确认db\_recovery参数**

SBDB1的initSBDB1.ora注意替换时候不要忘记保留DB\_NAME='PROD1'

提前创建好路径目录

启动以spfile为启动

start nomout方式启动

**PROD1/SBDB1启动都以SPFILE方式启动**

## 1.关于prodsrv设置

```
[oracle@edbjr2p2 admin]$ tnsping prodsrv
```

TNS Ping Utility for Linux: Version 11.2.0.3.0 - Production on 14-NOV-2016 10:54:06

Copyright (c) 1997, 2011, Oracle. All rights reserved.

Used parameter files:

```
/u01/app/oracle/product/11.2.0/db_1/network/admin/sqlnet.ora
```

Used TNSNAMES adapter to resolve the alias

```
Attempting to contact (DESCRIPTION= (FAILOVER=on) (LOAD_BALANCE=off) (ADDRESS=(PROTOCOL=tcp)(HOST=edbjr2p1.example.com)(PORT=1521)) (ADDRESS=(PROTOCOL=tcp)(HOST=edbjr2p2.example.com)(PORT=1521)) (CONNECT_DATA=(SERVICE_NAME=PRODSRV.us.oracle.com)))
```

OK (0 msec)

```
[oracle@edbjr2p2 admin]$
```

错误:

```
PRODSRV=
```

```
(DESCRIPTION=
```

```
(ADDRESS_LIST=
```

```
(FAILOVER=on)
```

```
(LOAD_BALANCE=off)
```

```
(ADDRESS=(PROTOCOL=tcp)(HOST=edbjr2p1.example.com)(PORT=1521))
```

```
(ADDRESS=(PROTOCOL=tcp)(HOST=edbjr2p2.example.com)(PORT=1521))  
(CONNECT_DATA=(SERVICE_NAME=PRODSRV.us.oracle.com)))  
)
```

正确:

PRODSRV=

```
(DESCRIPTION=  
  (FAILOVER=on)  
  (LOAD_BALANCE=off)  
  (ADDRESS=(PROTOCOL=tcp)(HOST=edbjr2p1.example.com)(PORT=1521))  
  (ADDRESS=(PROTOCOL=tcp)(HOST=edbjr2p2.example.com)(PORT=1521))  
  (CONNECT_DATA=(SERVICE_NAME=PRODSRV.us.oracle.com))  
)
```

错误提示:

ERROR:

ORA-12504: TNS:listener was not given the SERVICE\_NAME in CONNECT\_DATA

总结:注意不要有list的包含语句和括号的匹配

## 2.偶数机目录

```
[oracle@edbjr2p2 dbs]$ cd  
[oracle@edbjr2p2 ~]$ mkdir -p /u01/app/oracle/oradata/SBDB1/  
[oracle@edbjr2p2 ~]$ mkdir -p /u01/app/oracle/admin/SBDB1/adump  
[oracle@edbjr2p2 ~]$ mkdir flash
```

```
[oracle@edbjr2p2 ~]$ df -h
```

Filesystem	Size	Used	Avail	Use%	Mounted on
------------	------	------	-------	------	------------

/dev/sda1	433G	31G	380G	8%	/
-----------	------	-----	------	----	---

tmpfs	4.0G	1.4G	2.7G	34%	/dev/shm
-------	------	------	------	-----	----------

如果/dev/shm可用空间小于参数文件中的Memory\_target值，可以执行:mount -o remount,size=4G /dev/shm，使得内存变大

```
[oracle@edbjr2p2 ~]$ export ORACLE_SID=SBDB1
```

```
[oracle@edbjr2p2 ~]$ sqlplus "/as sysdba"
```

```
SQL*Plus: Release 11.2.0.3.0 Production on Mon May 9 15:59:03 2016
```

```
Copyright (c) 1982, 2011, Oracle. All rights reserved.
```

失败时候:

检查tnsname是否配置

listener是否起来静态监听

清理上次失败文件 包括控制文件/adump审计归档目录下文件

3.broker时候如果有disable起不来，可以确认下sbdb1的参数是否被修改了

4.sbdbsrv的service的备库服务，不要启动service

5.prodsrv的确认，通过两边连接和查看listener状态是否有PRODSRV.us.oracle.com

6.dgmgri时候configuration， remove configuration方法

