

# Plane Crash Analysis: There exist such a thing as a safest seat?

Inferential Statistics 2025/2026

Barbato Alberto, Naldoni Martina

2026-01-12

## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Perspective</b>	<b>1</b>
<b>3</b>	<b>Analysis</b>	<b>23</b>
<b>4</b>	<b>Results</b>	<b>23</b>
<b>5</b>	<b>Conclusions</b>	<b>23</b>

## 1 Introduction

The Aviation industry is one of the safest in the world. The systems that it has in place to learn lessons from accidents and make sure they never happen again is well-established and highly regarded. This has made travelling by plane the safest way to travel. <https://flyfright.com/plane-crash-statistics/#:~:text=Based%20on%20statistics%20from%202015,unharmed%2C%20injured%2C%20or%20killed>

But perhaps due to these high safety standards, when an aircraft accident happens it makes headlines all over the world. Anxious passengers fear it's going to happen to them as well and they can't help but ask themselves if there is something they could do to have a safer flight.

One of the most frequent question that gets asked is : is there a part of the plane that is "safer" than other parts? Can the seating location make a difference in an accident? There are many articles where experts in the field give their opinions, and most answer that "yes, there are areas that give a higher chance of survival in case of an aircraft accident". But there are also studies that suggest that there is no safest seats on an airplane.

So, who is right? We are going to try to answer this question using statistics.

## 2 Perspective

We are studying if the seating in an airplane has an effect on the survivability of an aircraft accident. To study this, we need to look at all aircraft accidents, then rule out the accidents where every passenger survived, and every accident in which every passenger died. This is an extremely narrow data set of accidents. Of these accidents, we gathered the seatings arrangements and survivor seating maps for 47 crashes.

If 47 crashes look like a lot, we should consider the greater perspective of air travel safety in general.

<https://flyfright.com/plane-crash-statistics/#tve-jump-18c020d9166> reported these figures studying the US General aviation data between 2015 and 2020 :

- $\frac{1}{260256}$  : chance of boarding any flight and it being an accident flight
- $\frac{1}{6,864,250}$  : chance of being on a plane involved in an accident that results in at least 1 fatality (possible case study of this study)
- $\frac{1}{816,545,929}$  chance of you specifically, dying in a plane crash

```
data <- read.csv("Aerei_Final.csv")
```

```
str(data)
```

```
## 'data.frame': 47 obs. of 21 variables:
## $ NumVolo : int 6 28 92 120 123 129 140 148 191 204 ...
## $ X1.terzo.lievi: int 17 36 0 0 0 4 0 0 0 3 ...
## $ X1.terzo.gravi: int 2 0 11 0 0 0 0 0 0 0 ...
## $ X1.terzo.morti: int 15 0 22 0 136 14 18 16 55 33 ...
## $ X2.terzo.lievi: int 1 30 4 5 0 5 7 1 0 25 ...
## $ X2.terzo.gravi: int 15 0 30 0 0 0 0 0 8 0 ...
## $ X2.terzo.morti: int 64 16 13 8 214 60 139 34 51 1 ...
## $ X3.terzo.lievi: int 26 10 0 5 36 24 0 8 10 29 ...
## $ X3.terzo.gravi: int 17 0 27 0 0 0 0 0 7 0 ...
## $ X3.terzo.morti: int 0 36 11 21 109 43 91 30 16 0 ...
## $ X1.meta.lievi : int 17 56 32 3 0 7 7 1 0 7 ...
## $ X1.meta.gravi : int 3 0 0 0 0 0 0 0 1 0 ...
## $ X1.meta.morti : int 41 8 34 6 226 23 95 36 79 35 ...
## $ X2.meta.lievi : int 26 20 39 7 4 26 0 7 10 46 ...
## $ X2.meta.gravi : int 31 0 0 0 0 0 0 0 14 0 ...
## $ X2.meta.morti : int 34 44 13 23 225 90 145 46 48 0 ...
## $ fonte : chr "W" "W" "W" "W" ...
## $ PhaseOfFlight : chr "Takeoff" "Takeoff" "Landing" "Landing" ...
## $ Time : chr "Night" "Day" "Night" "Day" ...
## $ Place : chr "Airport " "Outside" "Outside" "Airport " ...
## $ HasFire : chr "Fire" "Fire" "Fire" "Fire" ...
```

```
summary(data)
```

```
##      NumVolo      X1.terzo.lievi      X1.terzo.gravi      X1.terzo.morti
## Min.   : 6      Min.   : 0.00      Min.   : 0.000      Min.   : 0.00
## 1st Qu.: 227      1st Qu.: 0.00      1st Qu.: 0.000      1st Qu.: 1.50
## Median : 812      Median : 4.00      Median : 0.000      Median : 11.00
## Mean   :1591      Mean   : 12.87      Mean   : 2.553      Mean   : 16.15
## 3rd Qu.:1603      3rd Qu.: 17.00      3rd Qu.: 4.000      3rd Qu.: 19.00
## Max.   :9642      Max.   :141.00      Max.   :16.000      Max.   :136.00
## X2.terzo.lievi      X2.terzo.gravi      X2.terzo.morti      X3.terzo.lievi
## Min.   : 0.00      Min.   : 0.000      Min.   : 0.00      Min.   : 0.0
## 1st Qu.: 1.00      1st Qu.: 0.000      1st Qu.: 2.00      1st Qu.: 3.0
## Median : 7.00      Median : 2.000      Median : 12.00      Median : 10.0
## Mean   : 22.11      Mean   : 4.638      Mean   : 28.62      Mean   : 20.4
```

```
## 3rd Qu.: 26.50 3rd Qu.: 8.000 3rd Qu.: 31.00 3rd Qu.: 27.0
## Max. :174.00 Max. :30.000 Max. :214.00 Max. :142.0
## X3.terzo.gravi X3.terzo.morti X1.meta.lievi X1.meta.gravi
## Min. : 0.000 Min. : 0.00 Min. : 0.00 Min. : 0.00
## 1st Qu.: 0.000 1st Qu.: 1.50 1st Qu.: 1.50 1st Qu.: 0.00
## Median : 0.000 Median : 8.00 Median : 11.00 Median : 0.00
## Mean : 3.872 Mean : 19.83 Mean : 29.23 Mean : 4.34
## 3rd Qu.: 4.500 3rd Qu.: 24.50 3rd Qu.: 40.50 3rd Qu.: 7.00
## Max. :27.000 Max. :113.00 Max. :221.00 Max. :34.00
## X1.meta.morti X2.meta.lievi X2.meta.gravi X2.meta.morti
## Min. : 0.00 Min. : 0.00 Min. : 0.000 Min. : 0.00
## 1st Qu.: 5.00 1st Qu.: 6.50 1st Qu.: 0.000 1st Qu.: 3.50
## Median : 20.00 Median : 14.00 Median : 0.000 Median : 15.00
## Mean : 28.57 Mean : 28.98 Mean : 5.234 Mean : 36.53
## 3rd Qu.: 35.00 3rd Qu.: 37.50 3rd Qu.: 7.500 3rd Qu.: 45.00
## Max. :226.00 Max. :184.00 Max. :31.000 Max. :225.00
## fonte PhaseOfFlight Time Place
## Length:47 Length:47 Length:47 Length:47
## Class :character Class :character Class :character Class :character
## Mode :character Mode :character Mode :character Mode :character
##
##
##
## HasFire
## Length:47
## Class :character
## Mode :character
##
##
##
```

```
#> data <- read.csv("Aerei_Final.csv")
#>
#> str(data)
#'data.frame': 47 obs. of 21 variables:
# $ NumVolo : int 6 28 92 120 123 129 140 148 191 204 ...
# $ X1.terzo.lievi : int 17 36 0 0 0 4 0 0 0 3 ...
# $ X1.terzo.gravi : int 2 0 11 0 0 0 0 0 0 0 ...
# $ X1.terzo.morti : int 15 0 22 0 136 14 18 16 55 33 ...
# $ X2.terzo.lievi : int 1 30 4 5 0 5 7 1 0 25 ...
# $ X2.terzo.gravi : int 15 0 30 0 0 0 0 0 0 8 0 ...
# $ X2.terzo.morti : int 64 16 13 8 214 60 139 34 51 1 ...
# $ X3.terzo.lievi : int 26 10 0 5 36 24 0 8 10 29 ...
# $ X3.terzo.gravi : int 17 0 27 0 0 0 0 0 0 7 0 ...
# $ X2.terzo.morti.1: int 0 36 11 21 109 43 91 30 16 0 ...
# $ X1.meta.lievi : int 17 56 32 3 0 7 7 1 0 7 ...
# $ X1.meta.gravi : int 3 0 0 0 0 0 0 0 1 0 ...
# $ X1.meta.morti : int 41 8 34 6 226 23 95 36 79 35 ...
# $ X2.meta.lievi : int 26 20 39 7 4 26 0 7 10 46 ...
# $ X2.meta.gravi : int 31 0 0 0 0 0 0 0 14 0 ...
# $ X2.meta.morti : int 34 44 13 23 225 90 145 46 48 0 ...
# $ fonte : chr "W" "W" "W" "W" ...
# $ PhaseOfFlight : chr "Takeoff" "Takeoff" "Landing" "Landing" ...
# $ Time : chr "Night" "Day" "Night" "Day" ...
```

```

# $ Place      : chr  "Airport " "Outside" "Outside" "Airport " ...
# $ HasFire    : chr  "Fire" "Fire" "Fire" "Fire" ...
#> summary(data)
#   NumVolo      X1.terzo.lievi  X1.terzo.gravi  X1.terzo.morti
# Min.   : 6      Min.   : 0.00  Min.   : 0.000  Min.   : 0.00
# 1st Qu.: 227    1st Qu.: 0.00  1st Qu.: 0.000  1st Qu.: 1.50
# Median : 812    Median : 4.00  Median : 0.000  Median : 11.00
# Mean   :1591    Mean   :12.87  Mean   : 2.553  Mean   :16.15
# 3rd Qu.:1603    3rd Qu.:17.00  3rd Qu.: 4.000  3rd Qu.:19.00
# Max.   :9642    Max.   :141.00  Max.   :16.000  Max.   :136.00
# X2.terzo.lievi  X2.terzo.gravi  X2.terzo.morti  X3.terzo.lievi
# Min.   : 0.00  Min.   : 0.000  Min.   : 0.00  Min.   : 0.0
# 1st Qu.: 1.00  1st Qu.: 0.000  1st Qu.: 2.00  1st Qu.: 3.0
# Median : 7.00  Median : 2.000  Median :12.00  Median :10.0
# Mean   :22.11  Mean   : 4.638  Mean   :28.62  Mean   :20.4
# 3rd Qu.:26.50  3rd Qu.: 8.000  3rd Qu.:31.00  3rd Qu.:27.0
# Max.   :174.00  Max.   :30.000  Max.   :214.00  Max.   :142.0
# X3.terzo.gravi  X2.terzo.morti.1  X1.meta.lievi  X1.meta.gravi
# Min.   : 0.000  Min.   : 0.00  Min.   : 0.00  Min.   : 0.00
# 1st Qu.: 0.000  1st Qu.: 1.50  1st Qu.: 1.50  1st Qu.: 0.00
# Median : 0.000  Median : 8.00  Median :11.00  Median : 0.00
# Mean   : 3.872  Mean   :19.83  Mean   :29.23  Mean   : 4.34
# 3rd Qu.: 4.500  3rd Qu.:24.50  3rd Qu.:40.50  3rd Qu.: 7.00
# Max.   :27.000  Max.   :113.00  Max.   :221.00  Max.   :34.00
# X1.meta.morti  X2.meta.lievi  X2.meta.gravi  X2.meta.morti
# Min.   : 0.00  Min.   : 0.00  Min.   : 0.000  Min.   : 0.00
# 1st Qu.: 5.00  1st Qu.: 6.50  1st Qu.: 0.000  1st Qu.: 3.50
# Median :20.00  Median :14.00  Median : 0.000  Median :15.00
# Mean   :28.57  Mean   :28.98  Mean   : 5.234  Mean   :36.53
# 3rd Qu.:35.00  3rd Qu.:37.50  3rd Qu.: 7.500  3rd Qu.:45.00
# Max.   :226.00  Max.   :184.00  Max.   :31.000  Max.   :225.00
#   fonte      PhaseOfFlight      Time      Place
# Length:47     Length:47      Length:47     Length:47
# Class :character  Class :character  Class :character  Class :character
# Mode  :character  Mode  :character  Mode  :character  Mode  :character

```

Some random text...

```

# add a colum of # of seat for each airplain section

data$X1.third.total <- data$X1.terzo.lievi + data$X1.terzo.gravi + data$X1.terzo.morti
data$X2.third.total <- data$X2.terzo.lievi + data$X2.terzo.gravi + data$X2.terzo.morti
data$X3.third.total <- data$X3.terzo.lievi + data$X3.terzo.gravi + data$X3.terzo.morti
data$X1.half.total <- data$X1.meta.lievi + data$X1.meta.gravi + data$X1.meta.morti
data$X2.half.total <- data$X2.meta.lievi + data$X2.meta.gravi + data$X2.meta.morti

# now make a colum of mortality rate for each section

data$X1.third.mortality.rate <- data$X1.terzo.morti / data$X1.third.total
data$X2.third.mortality.rate <- data$X2.terzo.morti / data$X2.third.total
data$X3.third.mortality.rate <- data$X3.terzo.morti / data$X3.third.total
data$X1.half.mortality.rate <- data$X1.meta.morti / data$X1.half.total
data$X2.half.mortality.rate <- data$X2.meta.morti / data$X2.half.total

```

```
head(data)
```

```
##      NumVolo X1.terzo.lievi X1.terzo.gravi X1.terzo.morti X2.terzo.lievi
## 1         6          17          2          15          1
## 2        28          36          0          0          30
## 3        92          0         11         22          4
## 4       120          0          0          0          5
## 5       123          0          0         136          0
## 6       129          4          0          14          5
##      X2.terzo.gravi X2.terzo.morti X3.terzo.lievi X3.terzo.gravi X3.terzo.morti
## 1          15          64          26          17          0
## 2           0          16          10          0          36
## 3          30          13           0          27          11
## 4           0           8           5           0          21
## 5           0         214          36           0         109
## 6           0          60          24           0          43
##      X1.meta.lievi X1.meta.gravi X1.meta.morti X2.meta.lievi X2.meta.gravi
## 1          17           3          41          26          31
## 2          56           0           8          20           0
## 3          32           0          34          39           0
## 4           3           0           6           7           0
## 5           0           0         226           4           0
## 6           7           0          23          26           0
##      X2.meta.morti fonte PhaseOfFlight Time Place HasFire X1.third.total
## 1          34      W      Takeoff Night Airport Fire          34
## 2          44      W      Takeoff Day Outside Fire          36
## 3          13      W      Landing Night Outside Fire          33
## 4          23      W      Landing Day Airport Fire           0
## 5         225      W      Takeoff Night Outside Fire         136
## 6          90      W      Landing Day Outside Fire          18
##      X2.third.total X3.third.total X1.half.total X2.half.total
## 1          80          43          61          91
## 2          46          46          64          64
## 3          47          38          66          52
## 4          13          26           9          30
## 5         214         145         226         229
## 6          65          67          30         116
##      X1.third.mortality.rate X2.third.mortality.rate X3.third.mortality.rate
## 1          0.4411765          0.8000000          0.0000000
## 2          0.0000000          0.3478261          0.7826087
## 3          0.6666667          0.2765957          0.2894737
## 4           NaN          0.6153846          0.8076923
## 5          1.0000000          1.0000000          0.7517241
## 6          0.7777778          0.9230769          0.6417910
##      X1.half.mortality.rate X2.half.mortality.rate
## 1          0.6721311          0.3736264
## 2          0.1250000          0.6875000
## 3          0.5151515          0.2500000
## 4          0.6666667          0.7666667
## 5          1.0000000          0.9825328
## 6          0.7666667          0.7758621
```

```
## Plot mortality rates as scatter plots for each section
## they must be separated on the x axis by group

boxplot(data$X1.third.mortality.rate,
        data$X2.third.mortality.rate,
        data$X3.third.mortality.rate,
        data$X1.half.mortality.rate,
        data$X2.half.mortality.rate,
        names = c("Front Third", "Middle Third", "Rear Third", "Front Half", "Rear Half"),
        main = "Mortality Rates by Section",
        ylab = "Mortality Rate",
        xlab = "Sections",
        col = c("red", "red", "red", "green", "green"))
```



```
# Perform ANOVA to test if there are significant differences in mortality rates between sections (only
mortality_data <- data.frame(
```

```

Section = rep(c("Front Third", "Middle Third", "Rear Third"), each = nrow(data)),
MortalityRate = c(data$X1.third.mortality.rate, data$X2.third.mortality.rate, data$X3.third.mortality
)
mortality_data$Section <- as.factor(mortality_data$Section)

anova_result <- aov(MortalityRate ~ Section, data = mortality_data)
summary(anova_result)

```

```

##              Df Sum Sq Mean Sq F value Pr(>F)
## Section      2  0.364  0.1818   1.251  0.289
## Residuals   137 19.906  0.1453
## 1 observation deleted due to missingness

```

```
library(multcomp)
```

```
## Loading required package: mvtnorm
```

```
## Loading required package: survival
```

```
## Loading required package: TH.data
```

```
## Loading required package: MASS
```

```
##
```

```
## Attaching package: 'TH.data'
```

```
## The following object is masked from 'package:MASS':
```

```
##
```

```
##      geyser
```

```

test_result <- glht(anova_result, linfct = mcp(Section = "Tukey"))
summary(test_result)

```

```
##
```

```
## Simultaneous Tests for General Linear Hypotheses
```

```
##
```

```
## Multiple Comparisons of Means: Tukey Contrasts
```

```
##
```

```
##
```

```
## Fit: aov(formula = MortalityRate ~ Section, data = mortality_data)
```

```
##
```

```
## Linear Hypotheses:
```

```

##              Estimate Std. Error t value Pr(>|t|)
## Middle Third - Front Third == 0 -0.04032    0.07906  -0.510    0.867
## Rear Third - Front Third == 0  -0.12252    0.07906  -1.550    0.271
## Rear Third - Middle Third == 0 -0.08220    0.07863  -1.045    0.550
## (Adjusted p values reported -- single-step method)

```

```
#half sections
mortality_data_half <- data.frame(
  Section = rep(c("Front Half", "Rear Half"), each = nrow(data)),
  MortalityRate = c(data$X1.half.mortality.rate, data$X2.half.mortality.rate)
)
anova_result_half <- aov(MortalityRate ~ Section, data = mortality_data_half)
summary(anova_result_half)
```

```
##           Df Sum Sq Mean Sq F value Pr(>F)
## Section      1  0.056  0.05591    0.409  0.524
## Residuals   92 12.581  0.13675
```

```
#try using non-parametric test if ANOVA assumptions are not met
kruskal_result <- kruskal.test(MortalityRate ~ Section, data = mortality_data)
kruskal_result_half <- kruskal.test(MortalityRate ~ Section, data = mortality_data_half)
kruskal_result
```

```
##
##  Kruskal-Wallis rank sum test
##
## data:  MortalityRate by Section
## Kruskal-Wallis chi-squared = 2.9755, df = 2, p-value = 0.2259
```

```
kruskal_result_half
```

```
##
##  Kruskal-Wallis rank sum test
##
## data:  MortalityRate by Section
## Kruskal-Wallis chi-squared = 0.65567, df = 1, p-value = 0.4181
```

```
#oneway test
```

```
oneway_result <- oneway.test(MortalityRate ~ Section, data = mortality_data, var.equal = FALSE)
oneway_result_half <- oneway.test(MortalityRate ~ Section, data = mortality_data_half, var.equal = FALSE)
oneway_result
```

```
##
##  One-way analysis of means (not assuming equal variances)
##
## data:  MortalityRate and Section
## F = 1.2857, num df = 2.000, denom df = 91.026, p-value = 0.2814
```

```
oneway_result_half
```

```
##
##  One-way analysis of means (not assuming equal variances)
##
## data:  MortalityRate and Section
## F = 0.40883, num df = 1.000, denom df = 91.667, p-value = 0.5242
```



```
# now we do the same thing but considering the "gravi" as casualties too
```

```
data$X1.casualties_rate_new <- (data$X1.terzo.morti + data$X1.terzo.gravi) / data$X1.third.total
data$X2.casualties_rate_new <- (data$X2.terzo.morti + data$X2.terzo.gravi) / data$X2.third.total
data$X3.casualties_rate_new <- (data$X3.terzo.morti + data$X3.terzo.gravi) / data$X3.third.total
data$X1.half.casualties_rate_new <- (data$X1.meta.morti + data$X1.meta.gravi) / data$X1.half.total
data$X2.half.casualties_rate_new <- (data$X2.meta.morti + data$X2.meta.gravi) / data$X2.half.total
```


```
head(data)
```

```
##   NumVolo X1.terzo.lievi X1.terzo.gravi X1.terzo.morti X2.terzo.lievi
## 1      6          17          2          15          1
## 2     28          36          0          0          30
## 3     92          0          11          22          4
## 4    120          0          0          0          5
## 5    123          0          0          136         0
## 6    129          4          0          14          5
##   X2.terzo.gravi X2.terzo.morti X3.terzo.lievi X3.terzo.gravi X3.terzo.morti
## 1             15             64             26             17             0
## 2              0             16             10              0             36
## 3             30             13              0             27             11
## 4              0              8              5              0             21
## 5              0            214             36              0            109
## 6              0             60             24              0             43
##   X1.meta.lievi X1.meta.gravi X1.meta.morti X2.meta.lievi X2.meta.gravi
## 1             17              3            41            26            31
## 2             56              0              8            20              0
## 3             32              0            34            39              0
## 4              3              0              6              7              0
## 5              0              0           226              4              0
## 6              7              0            23            26              0
##   X2.meta.morti fonte PhaseOfFlight Time Place HasFire X1.third.total
## 1             34      W      Takeoff Night Airport      Fire            34
## 2             44      W      Takeoff  Day  Outside      Fire            36
## 3             13      W      Landing Night  Outside      Fire            33
## 4             23      W      Landing  Day  Airport      Fire             0
## 5            225      W      Takeoff Night  Outside      Fire           136
## 6             90      W      Landing  Day  Outside      Fire            18
##   X2.third.total X3.third.total X1.half.total X2.half.total
## 1             80             43             61             91
## 2             46             46             64             64
## 3             47             38             66             52
## 4             13             26              9             30
## 5            214            145            226            229
## 6             65             67             30            116
##   X1.third.mortality.rate X2.third.mortality.rate X3.third.mortality.rate
## 1             0.4411765             0.8000000             0.0000000
## 2             0.0000000             0.3478261             0.7826087
## 3             0.6666667             0.2765957             0.2894737
## 4              NaN             0.6153846             0.8076923
## 5             1.0000000             1.0000000             0.7517241
## 6             0.7777778             0.9230769             0.6417910
##   X1.half.mortality.rate X2.half.mortality.rate X1.casualties_rate_new
```

```
## 1      0.6721311      0.3736264      0.5000000
## 2      0.1250000      0.6875000      0.0000000
## 3      0.5151515      0.2500000      1.0000000
## 4      0.6666667      0.7666667      NaN
## 5      1.0000000      0.9825328      1.0000000
## 6      0.7666667      0.7758621      0.7777778
## X2.casualties_rate_new X3.casualties_rate_new X1.half.casualties_rate_new
## 1      0.9875000      0.3953488      0.7213115
## 2      0.3478261      0.7826087      0.1250000
## 3      0.9148936      1.0000000      0.5151515
## 4      0.6153846      0.8076923      0.6666667
## 5      1.0000000      0.7517241      1.0000000
## 6      0.9230769      0.6417910      0.7666667
## X2.half.casualties_rate_new
## 1      0.7142857
## 2      0.6875000
## 3      0.2500000
## 4      0.7666667
## 5      0.9825328
## 6      0.7758621
```

```
# Plot new casualties rates as scatter plots for each section
boxplot(data$X1.casualties_rate_new,
  data$X2.casualties_rate_new,
  data$X3.casualties_rate_new,
  data$X1.half.casualties_rate_new,
  data$X2.half.casualties_rate_new,
  names = c("Front Third", "Middle Third", "Rear Third", "Front Half", "Rear Half"),
  main = "Casualties Rates by Section (Including Serious Injuries)",
  ylab = "Casualties Rate",
  xlab = "Sections",
  col = c("blue", "blue", "blue", "orange", "orange"))
```

## Casualties Rates by Section (Including Serious Injuries)



```
# Perform ANOVA to test if there are significant differences in casualties rates between sections (only
casualties_data <- data.frame(
  Section = rep(c("Front Third", "Middle Third", "Rear Third"), each = nrow(data)),
  CasualtiesRate = c(data$X1.casualties_rate_new, data$X2.casualties_rate_new, data$X3.casualties_rate_new)
)
anova_casualties_result <- aov(CasualtiesRate ~ Section, data = casualties_data)
summary(anova_casualties_result)
```

```
##              Df Sum Sq Mean Sq F value Pr(>F)
## Section      2   0.33  0.1648   1.228  0.296
## Residuals  137  18.38  0.1342
## 1 observation deleted due to missingness
```

```
#half sections
casualties_data_half <- data.frame(
  Section = rep(c("Front Half", "Rear Half"), each = nrow(data)),
```

```

CasualtiesRate = c(data$X1.half.casualties_rate_new, data$X2.half.casualties_rate_new)
)
anova_casualties_result_half <- aov(CasualtiesRate ~ Section, data = casualties_data_half)
summary(anova_casualties_result_half)

```

```

##           Df Sum Sq Mean Sq F value Pr(>F)
## Section      1  0.039  0.03904    0.318  0.574
## Residuals   92 11.283  0.12264

```

```

#try using non-parametric test if ANOVA assumptions are not met
kruskal_casualties_result <- kruskal.test(CasualtiesRate ~ Section, data = casualties_data)
kruskal_casualties_result_half <- kruskal.test(CasualtiesRate ~ Section, data = casualties_data_half)
kruskal_casualties_result

```

```

##
## Kruskal-Wallis rank sum test
##
## data: CasualtiesRate by Section
## Kruskal-Wallis chi-squared = 2.6064, df = 2, p-value = 0.2717

```

```
kruskal_casualties_result_half
```

```

##
## Kruskal-Wallis rank sum test
##
## data: CasualtiesRate by Section
## Kruskal-Wallis chi-squared = 0.4796, df = 1, p-value = 0.4886

```

```

#oneway test
oneway_casualties_result <- oneway.test(CasualtiesRate ~ Section, data = casualties_data, var.equal = FALSE)
oneway_casualties_result_half <- oneway.test(CasualtiesRate ~ Section, data = casualties_data_half, var.equal = FALSE)
oneway_casualties_result

```

```

##
## One-way analysis of means (not assuming equal variances)
##
## data: CasualtiesRate and Section
## F = 1.2205, num df = 2.000, denom df = 91.313, p-value = 0.2999

```

```
oneway_casualties_result_half
```

```

##
## One-way analysis of means (not assuming equal variances)
##
## data: CasualtiesRate and Section
## F = 0.31829, num df = 1.000, denom df = 91.975, p-value = 0.574

```

```

# t.test only the firsts third against the rears third
t_test_result <- t.test(data$X1.third.mortality.rate, data$X3.third.mortality.rate, var.equal = FALSE)
t_test_result

```

```
##
## Welch Two Sample t-test
##
## data: data$X1.third.mortality.rate and data$X3.third.mortality.rate
## t = 1.5556, df = 89.487, p-value = 0.1233
## alternative hypothesis: true difference in means is not equal to 0
## 95 percent confidence interval:
## -0.03396324 0.27900140
## sample estimates:
## mean of x mean of y
## 0.5434137 0.4208946

#use non-parametric test if t-test assumptions are not met
wilcox_test_result <- wilcox.test(data$X1.third.mortality.rate, data$X3.third.mortality.rate)

## Warning in wilcox.test.default(data$X1.third.mortality.rate,
## data$X3.third.mortality.rate): cannot compute exact p-value with ties

wilcox_test_result

##
## Wilcoxon rank sum test with continuity correction
##
## data: data$X1.third.mortality.rate and data$X3.third.mortality.rate
## W = 1291, p-value = 0.1052
## alternative hypothesis: true location shift is not equal to 0

# now we want to test if there is a difference in mortality rate based on the other variables
# PhaseOfFlight, Time, Place, HasFire
# using the total mortality rate, only deaths, do this for ewwey third

out <- lm(data$X1.third.mortality.rate ~ data$PhaseOfFlight + data$Time + data$Place + data$HasFire)
summary(out)

##
## Call:
## lm(formula = data$X1.third.mortality.rate ~ data$PhaseOfFlight +
## data$Time + data$Place + data$HasFire)
##
## Residuals:
## Min 1Q Median 3Q Max
## -0.62619 -0.27399 0.07094 0.26658 0.66495
##
## Coefficients:
## Estimate Std. Error t value Pr(>|t|)
## (Intercept) 0.55633 0.12745 4.365 9.43e-05 ***
## data$PhaseOfFlightLanding 0.31337 0.34121 0.918 0.3642
## data$PhaseOfFlightTakeoff -0.17701 0.12568 -1.408 0.1671
## data$TimeDay -0.10427 0.26774 -0.389 0.6991
## data$TimeNight 0.01703 0.14142 0.120 0.9048
## data$PlaceAirport 0.06205 0.17287 0.359 0.7216
## data$PlaceOutside 0.24686 0.14262 1.731 0.0916 .
```

```
## data$HasFireNo-Fire      -0.29114      0.13331  -2.184    0.0352 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.3851 on 38 degrees of freedom
## (1 observation deleted due to missingness)
## Multiple R-squared:  0.2155, Adjusted R-squared:  0.07096
## F-statistic: 1.491 on 7 and 38 DF,  p-value: 0.1999

out_2 <- lm(data$X2.third.mortality.rate ~ data$PhaseOfFlight + data$Time + data$Place + data$HasFire)
summary(out_2)
```

```
##
## Call:
## lm(formula = data$X2.third.mortality.rate ~ data$PhaseOfFlight +
##     data$Time + data$Place + data$HasFire)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.63420 -0.37099  0.01981  0.31813  0.59990
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      0.38769    0.12962   2.991  0.0048 **
## data$PhaseOfFlightLanding  0.08039    0.34876   0.230  0.8189
## data$PhaseOfFlightTakeoff  0.01241    0.12735   0.097  0.9229
## data$TimeDay      -0.03338    0.27323  -0.122  0.9034
## data$TimeNight     0.06944    0.14302   0.486  0.6300
## data$PlaceAirport   0.20788    0.17042   1.220  0.2298
## data$PlaceOutside   0.23411    0.14574   1.606  0.1163
## data$HasFireNo-Fire -0.20291    0.13559  -1.497  0.1426
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.3937 on 39 degrees of freedom
## Multiple R-squared:  0.1128, Adjusted R-squared: -0.04639
## F-statistic: 0.7086 on 7 and 39 DF,  p-value: 0.6648
```


```
out_3 <- lm(data$X3.third.mortality.rate ~ data$PhaseOfFlight + data$Time + data$Place + data$HasFire)
summary(out_3)
```

```
##
## Call:
## lm(formula = data$X3.third.mortality.rate ~ data$PhaseOfFlight +
##     data$Time + data$Place + data$HasFire)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.56827 -0.23612 -0.04599  0.25262  0.58917
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      0.413075    0.120342   3.433  0.00143 **
```

```
## data$PhaseOfFlightLanding -0.057355  0.323798 -0.177  0.86032
## data$PhaseOfFlightTakeoff -0.002242  0.118232 -0.019  0.98497
## data$TimeDay -0.288042  0.253673 -1.135  0.26310
## data$TimeNight -0.071894  0.132786 -0.541  0.59129
## data$PlaceAirport  0.137487  0.158220  0.869  0.39019
## data$PlaceOutside  0.155196  0.135307  1.147  0.25837
## data$HasFireNo-Fire -0.186705  0.125886 -1.483  0.14608
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.3655 on 39 degrees of freedom
## Multiple R-squared:  0.118, Adjusted R-squared: -0.04035
## F-statistic: 0.7452 on 7 and 39 DF, p-value: 0.6355
```

```
#plot the mortality rates based on HasFire
boxplot(data$X1.third.mortality.rate ~ data$HasFire,
        main = "Front Third Mortality Rate by Fire Presence",
        xlab = "Has Fire",
        ylab = "Mortality Rate",
        col = c("yellow", "red"))
```


### Front Third Mortality Rate by Fire Presence



```
boxplot(data$X2.third.mortality.rate ~ data$HasFire,  
        main = "Middle Third Mortality Rate by Fire Presence",  
        xlab = "Has Fire",  
        ylab = "Mortality Rate",  
        col = c("yellow", "red"))
```




### Middle Third Mortality Rate by Fire Presence




```
boxplot(data$X3.third.mortality.rate ~ data$HasFire,  
        main = "Rear Third Mortality Rate by Fire Presence",  
        xlab = "Has Fire",  
        ylab = "Mortality Rate",  
        col = c("yellow", "red"))
```

## Rear Third Mortality Rate by Fire Presence



```
#and full plane mortality rate
data$Total.mortality.rate <- (data$X1.terzo.morti + data$X2.terzo.morti + data$X3.terzo.morti) / (data$X1.terzo.morti + data$X2.terzo.morti + data$X3.terzo.morti + 1)

boxplot(data$Total.mortality.rate ~ data$HasFire,
        main = "Total Mortality Rate by Fire Presence",
        xlab = "Has Fire",
        ylab = "Mortality Rate",
        col = c("yellow", "red"))
```



```
# now for the halves
out_half_1 <- lm(data$X1.half.mortality.rate ~ data$PhaseOfFlight + data$Time + data$Place + data$HasFire)
summary(out_half_1)
```

```
##
## Call:
## lm(formula = data$X1.half.mortality.rate ~ data$PhaseOfFlight +
##     data$Time + data$Place + data$HasFire)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.6724 -0.3041  0.0530  0.2636  0.5802
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    0.47111    0.12149   3.878 0.000394 ***
```


```
## data$PhaseOfFlightLanding -0.08327    0.32688 -0.255 0.800265
## data$PhaseOfFlightTakeoff -0.06912    0.11936 -0.579 0.565829
## data$TimeDay -0.26135    0.25609 -1.021 0.313758
## data$TimeNight 0.05772    0.13405 0.431 0.669130
## data$PlaceAirport 0.14255    0.15973 0.892 0.377613
## data$PlaceOutside 0.27041    0.13659 1.980 0.054827 .
## data$HasFireNo-Fire -0.25262    0.12708 -1.988 0.053881 .
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.369 on 39 degrees of freedom
## Multiple R-squared:  0.2038, Adjusted R-squared:  0.06089
## F-statistic: 1.426 on 7 and 39 DF,  p-value: 0.2228
```

```
out_half_2 <- lm(data$X2.half.mortality.rate ~ data$PhaseOfFlight + data$Time + data$Place + data$HasFire)
summary(out_half_2)
```

```
##
## Call:
## lm(formula = data$X2.half.mortality.rate ~ data$PhaseOfFlight +
##     data$Time + data$Place + data$HasFire)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.60915 -0.23925  0.02419  0.28219  0.58485
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      0.41515    0.12107   3.429  0.00144 **
## data$PhaseOfFlightLanding 0.13238    0.32575   0.406  0.68669
## data$PhaseOfFlightTakeoff 0.01443    0.11894   0.121  0.90409
## data$TimeDay -0.17559    0.25520  -0.688  0.49549
## data$TimeNight -0.03249    0.13359  -0.243  0.80910
## data$PlaceAirport 0.17936    0.15917   1.127  0.26669
## data$PlaceOutside 0.19400    0.13612   1.425  0.16205
## data$HasFireNo-Fire -0.21447    0.12664  -1.693  0.09834 .
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.3677 on 39 degrees of freedom
## Multiple R-squared:  0.1079, Adjusted R-squared: -0.05217
## F-statistic: 0.6742 on 7 and 39 DF,  p-value: 0.6926
```


```
#boxplots for halves
boxplot(data$X1.half.mortality.rate ~ data$HasFire,
        main = "Front Half Mortality Rate by Fire Presence",
        xlab = "Has Fire",
        ylab = "Mortality Rate",
        col = c("lightgreen", "darkgreen"))
```

## Front Half Mortality Rate by Fire Presence



```
boxplot(data$X2.half.mortality.rate ~ data$HasFire,  
        main = "Rear Half Mortality Rate by Fire Presence",  
        xlab = "Has Fire",  
        ylab = "Mortality Rate",  
        col = c("lightgreen", "darkgreen"))
```


## Rear Half Mortality Rate by Fire Presence



# Data Description

This is an example of r-chuch. You can instrt the R code, Knit-it and your report is compiled in pdf.

```
x <- rnorm(1000)
hist(x)
```



**3 Analysis**

**4 Results**

**5 Conclusions**