

Batman BM201-LPD mmWave EVM Kit

mmWAVE SENSOR EVALUATION SOLUTION

mmWAVE SENSOR EVALUATION SOLUTION

Joybien Batman BM201-LPD mmWave EVM Kit is a Texas Instruments (TI) IWR6843 ASIC based millimeter-wave (mmWave) Kit with Frequency-Modulated Continuous Wave (FMCW) radar technology capable of operation in the 60GHz to 64GHz band with up to 4 GHz continuous chirp, using 3 Transmission Antennas and 4 Receiving Antennas, for sensing target object's range, velocity, and angle parameters.

Batman BM201-LPD mmWave EVM Kit is with a small and compact mmWave Module (with low-power, self-monitored, ultra-accurate, and lighting condition independent versatilities), along with a Pi-Hat Board for simple and direct connectivity to a Raspberry Pi or NVIDIA Jetson Nano computer, suitable for various applications including: Education, Engineering, Science, Industrial, Medical, and Business & Consumer.

Applications

- Education's Practical Radar Introduction
- Engineering & Science's Motion Detection, Displacement, etc.
- Industrial sensor for Displacement & Safe Guard, Factory Automation, Robotics, etc.
- Building Automation sensor for Occupancy Detection, Proximity & Position sensing, People Counting, Security and Surveillance
- Business' Traffic Monitoring, and Proximity Advertisement

Long-Range People Detection (LPD)

The Kit's mmWave Module is built-in with Long-Range People Counting Firmware; for a contactless and wearableless real-time detection of people movement from 1 meter to 50 meter range for various applications that require people sensing or counting without privacy invasion.

Features

- Operating Frequency: 60GHz ~ 64GHz coverage
with 4GHz continuous bandwidth
- Antenna: 3 Tx and 4 Rx Antennas on Module, with:
TX Power: 10 dBm
RX Noise Figure: 14 dB
- Processors: ARM R4F based MCU and C674x DSP
for advanced signal processing
- On-Chip Memory: 1.75MB
- Internal Memories With ECC
- Integrated Peripherals
- Input Power: 3.3Vdc, 2.1A


Batman BM201-LPD mmWave EVM Kit

mmWAVE SENSOR EVALUATION SOLUTION

mmWAVE SENSOR EVALUATION SOLUTION

Packing List: mmWave Module, Raspberry Pi-Hat Board, Python SDK

- Make sure you are using the correct power supply of 5 V, >2.0 A with a Micro USB connection



Batman BM201-LPD Kit includes



Long-Range People Detection	<p>mmWave + Raspberry Pi-Hat Board / Jetson Nano carrier board + Python SDK</p>
-----------------------------	---

Batman Kit + NVIDIA Jetson Nano / Batman Kit + Raspberry Pi

Please make sure that the JUMPER SETTING is for Raw Data Mode

Batman BM201-LPD EVM Kit + Jetson Nano

Batman BM201-LPD EVM Kit + Raspberry Pi




Batman BM201-LPD mmWave EVM Kit

mmWAVE SENSOR EVALUATION SOLUTION


mmWAVE SENSOR EVALUATION SOLUTION

Selection : Key Data Mode or Raw Data Mode Application

(A) Raw Data Mode




(B) Key Data Mode



Batman BM201-LPD mmWave EVM Kit

mmWAVE SENSOR EVALUATION SOLUTION

mmWAVE SENSOR EVALUATION SOLUTION



Specifications

mmWave Sensor Evaluation Module


mmWave ASIC	TI IWR6843 Single Chip mmWave Sensor
FMCW Transceiver	<ul style="list-style-type: none"> ● Integrated PLL, Transmitter, Receiver, Baseband, and A2D ● 60GHz to 64GHz Coverage With 4GHz Continuous Bandwidth ● Four Receive Channels ● Three Transmit Channels ● Ultra-Accurate Chirp Engine Based on Fractional-N PLL ● TX Power: 10 dBm ● RX Noise Figure: 14 dB ● Phase Noise at 1 MHz: -92 dBc/Hz ● Antenna Type : ISK Antenna
Built-in Calibration and Self-Test (Monitoring)	<ul style="list-style-type: none"> ● ARM® Cortex® -R4F-Based Radio Control System ● Built-in Firmware (ROM) ● Self-calibrating System Across Frequency and Temperature
DSP	<ul style="list-style-type: none"> ● C674x DSP for Advanced Signal Processing
On-Chip Memory	<ul style="list-style-type: none"> ● 1.75MB
MCU	<ul style="list-style-type: none"> ● ARM R4F Microcontroller for Object Detection, and Interface Control ● Joybien mmWave Protocol (Per configuration)
I/O	<ul style="list-style-type: none"> ● Up to 6 ADC Channels (low sample rate monitoring) ● Up to 2 SPI Ports ● Up to 2 UARTs ● I2C – GPIOs
Power Management	<ul style="list-style-type: none"> ● Built-in LDO Network for Enhanced PSRR ● I/Os Support Dual Voltage 3.3 V/1.8 V
Clock Source	40MHz
Antenna Orientation	4 receive(RX) 3 transmit (TX) antenna with 108° azimuth field of view (FoV) and 44° elevation FoV
Input Power	3.3VDC, 2.1A source
Operating Temperature & Humidity	0°C ~ 40°C 10% ~ 85% Non-Condensing
Dimensions & Weight	67mm x 46mm x 2mm ; 15 grams net

Batman BM201-LPD mmWave EVM Kit

mmWAVE SENSOR EVALUATION SOLUTION

mmWAVE SENSOR EVALUATION SOLUTION

Raspberry Pi-Hat Board /
Jetson Nano carrier board



Connector	<ul style="list-style-type: none"> ● Matching mmWave Module Female Connector ● Matching Raspberry Pi GPIO Female Connector ● Micro USB Power Connector ● Jumpers for Bluetooth Tx/Rx or Raspberry Pi Tx/Rx Selection ● Jumper for mmWave Raw Data or Key Data Selection
Bluetooth (optional)	<ul style="list-style-type: none"> ● Joybien JBT24M Bluetooth Low Energy Module
Micro USB Input Power	<ul style="list-style-type: none"> ● 5VDC, 2Amp. (Note: Power Adapter and Micro USB Cable NOT included)
Operating Temperature Operating Humidity	<ul style="list-style-type: none"> ● 0° to 40° degree Celsius ● 10 ~ 85% Non-Condensing
Dimensions & Weight	<ul style="list-style-type: none"> ● 65.3mm x 56.3mm ● 30 grams with JBT24M Bluetooth

Python SDK



Python SDK	<ul style="list-style-type: none"> ● Available on GitHub Note: Please refer to README.md file first for proper configuration <div>  <div> GitHub https://github.com/bigheadG/mmWave </div>  </div>
------------	--

Batman BM201-LPD mmWave EVM Kit

mmWAVE SENSOR EVALUATION SOLUTION


mmWAVE SENSOR EVALUATION SOLUTION

mmWave Pin Assignment

J3

J3 Pin Assignment

Pin#	Name	Name	Pin#
01	D3V3	D3V3	02
03	D3V3	PI SDA	04
05	GND	PI SCL	06
07	RS232 RX	SYNC IN JBRX1	08
09	RS232 TX	GND	10
11	nRST	GPIO 0	12
13	GND	GPIO 1	14
15	DP0	CS1	16
17	DP1	3V3_LS	18
19	GND	MOSI 1	20
21	BSS LOGGER	MISO 1	22
23	MSS LOGGER JBTX1	SPICLK 1	24
25	PMIC CLKOUT SOP2	GND	26
27	SYNC OUT SOP1	nERRIN	28
29	GND	nERROUT	30
31	WARMRST	GPIO 2	32



Batman BM201-LPD mmWave EVM Kit

mmWAVE SENSOR EVALUATION SOLUTION

mmWAVE SENSOR EVALUATION SOLUTION

J3 Pin Assignment


Pin No	Name	Pin Type	Function Description
01	D3V3	I	POWER DC 3V3 Input
02	D3V3	I	POWER DC 3V3 Input
03	D3V3	I	POWER DC 3V3 Input
04	SDA	IO	I2C Pin
05	GND	GROUND	Digital ground
06	SCL	IO	I2C Pin
07	RS232 RX0	I	UART A Receive
08	SYNC IN JBRX1	I	Low frequency Synchronization signal input, UART B Receive
09	RS232 TX0	O	UART A Transmit
10	GND	GROUND	Digital ground
11	nRST	I	Power on reset for chip. Active low
12	GOIO 0	I	Select KeyData or RawData
13	GND	GROUND	Digital ground
14	GPIO 1	I	Reserved
15	DP0	IO	GPIO Pin
16	CS1	IO	SPI Channel A - chip Select
17	DP1	IO	GPIO Pin
18	3V3	O	For meaurement only
19	GND	GROUND	Digital ground
20	MOSI 1	IO	SPI Channel A - Master Out Slave In
21	BSS LOGGER	IO	BSS LOGGER
22	MISO 1	IO	SPI Channel A - Master In Slave Out
23	MSS LOGGER JBTX1	O	UART B Transmit
24	SPICLK 1	IO	SPI Channel A - Clock
25	SOP2	I	SOP2
26	GND	GROUND	Digital ground
27	SOP1	I	SOP1
28	nERRIN	I	Failsafe input to the device. Nerror output from any other device can be concentrated in the error signaling monitor module inside the device and appropriate action can be taken by Firmware.
29	GND	GROUND	Mistake Proofing Pin
30	nERROUT	O	Open drain fail safe output signal. Connected to PMIC/Processor/MCU to indicate that some severe criticatlity fault has happened. Recovery would be through reset.
31	WARMRST	IO	Open drain fail safe warm reset signal. Can be driven from PMIC for diagnostic or can be used as status signal that the device is going through reset.
32	GPIO2	O	LED Indicator

Batman BM201-LPD mmWave EVM Kit

mmWAVE SENSOR EVALUATION SOLUTION

mmWAVE SENSOR EVALUATION SOLUTION

mmWave Raspberry Pi Hat Pin Assignment




Batman BM201-LPD mmWave EVM Kit

mmWAVE SENSOR EVALUATION SOLUTION

mmWAVE SENSOR EVALUATION SOLUTION

Product Dimensions



Copyright ©2019 , Joybien Technologies Co., Ltd.

Joybien reserves the right to make changes without further notice to and products herein. Joybien makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Joybien assume any liability arising out of the application or use of any product or circuit. Joybien's products are not to be used in life support devices or systems, if a failure of an Joybien's product can reasonably be expected to cause the failure of that life support device or system, or to affect the safety or effectiveness of that device or system.

For the latest version of this document, visit our website:

www.joybien.com



Note:

NVIDIA logo, and Jetson Nano are trademarks and/or registered trademarks of NVIDIA Corporation.

Raspberry Pi logo and Raspberry Pi 4 are trademarks and/or registered trademarks of Raspberry Pi Foundation.

"Python" is a registered trademark of the PSF.

This EVM Kit does not include Raspberry Pi computer, nor NVIDIA Jetson Nano computer.

mmWave Specification

 <p>(VSD) Vital Signs Detection</p>	<p>30cm ~ 90cm (about 1~3 feet)</p> <p>Built-in with Vital Signs Detection (VSD) Firmware; for a contactless and wearableless 30cm ~ 90cm (about 1~3 feet) distance detection of Vital Signs (Heartbeat Rate & Respiration Rate) of a person, a pet, or an animal.</p>
 <p>(HAM) High Accuracy Measurement</p>	<p>30cm ~ 3meters (about 1~10 feet)</p> <p>Built-in with High Accuracy Measurement (HAM) Firmware; for measuring object distance from the mmWave Sensor Module with the range of 30cm ~ 3meters (about 1~10 feet) with millimeter resolution.</p>
 <p>(PMB) People Movement Behavior</p>	<p>4 x 4 meter or 16 meter square area (or about 172 square feet)</p> <p>Built-in with People Movement Behavior (PMB) Trigger Firmware; for detecting People movement in a 4 x 4 meter or 16 meter square area (or about 172 square feet), and with software that could set virtual geo-fence(s) to trigger alert or action when People are moving into the geo-fence(s).</p>
 <p>(SRR) Short Range Radar</p>	<p>For Human:1 meters ~ 20meters (about 3 ~ 66 feet)</p> <p>For Vechile:1 meters ~ 50meters (about 3 ~ 164 feet)</p> <p>and with viewing angle of 120 degrees</p> <p>Built-in with Short Range Radar Firmware; for detecting objects' distance with the range of 1meters ~ 20meters (about 3 ~ 66 feet) and with viewing angle of 120 degrees, along with Doppler Data to distinguish for whether the objects are moving-towards or moving-away from the mmWave sensor.</p>
 <p>(LPD) Long-Range People Detection</p>	<p>For Human:1 meters ~ 50meters (about 3 ~ 164 feet)</p> <p>The Kit's mmWave Module is built-in with Long-Range People Counting Firmware; for a contactless and wearableless real-time detection of people movement from 1 meter to 50 meter range for various applications that require people sensing or counting without privacy invasion.</p>
 <p>(FDS) Fall Detection Sensing</p>	<p>For Human: 3-dimensional movement from -3 meter ~ +3 meter on one direction, and -3 meter ~ + 3meter on the perpendicular/orthogonal direction, and +3 meter from ceiling to ground</p> <p>Built-in with Fall Detection Sensing Firmware; when positioned in the center of a room's ceiling, the mmWave Module is capable of detecting People's 3-dimensional movement from -3 meter ~ +3 meter on one direction, and -3 meter ~ + 3meter on the perpendicular/orthogonal direction, and +3 meter from ceiling to ground, all with the respect to the mmWave Sensor positioned in the center of the ceiling; and thus, the Sensor is capable to detect and track people movement along with standing, sitting, lying down positions.</p>