

# Batman BM301-FDS mmWave EVM Kit

## mmWAVE SENSOR EVALUATION SOLUTION

### mmWAVE SENSOR EVALUATION SOLUTION

Joybien Batman BM301-FDS mmWave EVM Kit is a Texas Instruments (TI) IWR6843 ASIC based millimeter-wave (mmWave) Kit with Frequency-Modulated Continuous Wave (FMCW) radar technology capable of operation in the 60GHz to 64GHz band with up to 4 GHz continuous chirp, using 3 Transmission Antennas and 4 Receiving Antennas, for sensing target object's range, velocity, and angle parameters.

Batman BM301-FDS mmWave EVM Kit is with a small and compact mmWave Module (with low-power, self-monitored, ultra-accurate, and lighting condition independent versatilities), along with a Pi-Hat Board for simple and direct connectivity to a Raspberry Pi or NVIDIA Jetson Nano computer, suitable for various applications including: Education, Engineering, Science, Industrial, Medical, and Business & Consumer.

### Applications

- Education's Practical Radar Introduction
- Engineering & Science's People Motion Detection
- Building Automation sensor for Occupancy Detection, Proximity & Position sensing, People Counting, Security and Surveillance

### Fall Detection Sensing (FDS)

The Kit's mmWave Module is built-in with Fall Detection Sensing Firmware; when positioned in the center of a room's ceiling, the mmWave Module is capable of detecting People's 3-dimensional movement from -3 meter ~ +3 meter on one direction, and -3 meter ~ + 3meter on the perpendicular/orthogonal direction, and +3 meter from ceiling to ground, all with the respect to the mmWave Sensor positioned in the center of the ceiling; and thus, the Sensor is capable to detect and track people movement along with standing, sitting, lying down positions.

### Features

- Operating Frequency: 60GHz ~ 64GHz coverage  
with 4GHz continuous bandwidth
- Antenna: 3 Tx and 4 Rx Antennas on Module, with:  
TX Power: 10 dBm  
RX Noise Figure: 14 dB
- Processors: ARM R4F based MCU and C674x DSP  
for advanced signal processing
- On-Chip Memory: 1.75MB
- Internal Memories With ECC
- Integrated Peripherals
- Input Power:3.3Vdc, 2.1A


# Batman BM301-FDS mmWave EVM Kit

mmWAVE SENSOR EVALUATION SOLUTION

## mmWAVE SENSOR EVALUATION SOLUTION

### Packing List: mmWave Module, Raspberry Pi-Hat Board, Python SDK

- Make sure you are using the correct power supply of 5 V, >2.0 A with a Micro USB connection




### Batman BM301-FDS Kit includes

Fall Detection Sensing



+



Raspberry Pi-Hat Board /  
Jetson Nano carrier board

+





Python SDK

### Batman Kit + NVIDIA Jetson Nano / Batman Kit + Raspberry Pi

Please make sure that the JUMPER SETTING is for Raw Data Mode

Batman BM301-FDS EVM Kit + Jetson Nano

Batman BM301-FDS EVM Kit + Raspberry Pi




# Batman BM301-FDS mmWave EVM Kit

mmWAVE SENSOR EVALUATION SOLUTION


## mmWAVE SENSOR EVALUATION SOLUTION

### Selection : Key Data Mode or Raw Data Mode Application

#### (A) Raw Data Mode



#### (B) Key Data Mode




# Batman BM301-FDS mmWave EVM Kit

mmWAVE SENSOR EVALUATION SOLUTION

## mmWAVE SENSOR EVALUATION SOLUTION

Raspberry Pi-Hat Board /  
Jetson Nano carrier board



Connector	<ul style="list-style-type: none"> <li>● Matching mmWave Module Female Connector</li> <li>● Matching Raspberry Pi GPIO Female Connector</li> <li>● Micro USB Power Connector</li> <li>● Jumpers for Bluetooth Tx/Rx or Raspberry Pi Tx/Rx Selection</li> <li>● Jumper for mmWave Raw Data or Key Data Selection</li> </ul>
Bluetooth (optional)	<ul style="list-style-type: none"> <li>● Joybien JBT24M Bluetooth Low Energy Module</li> </ul>
Micro USB Input Power	<ul style="list-style-type: none"> <li>● 5VDC, 2Amp.</li> </ul> <p>(Note: Power Adapter and Micro USB Cable NOT included)</p>
Operating Temperature Operating Humidity	<ul style="list-style-type: none"> <li>● 0° to 40° degree Celsius</li> <li>● 10 ~ 85% Non-Condensing</li> </ul>
Dimensions & Weight	<ul style="list-style-type: none"> <li>● 65.3mm x 56.3mm</li> <li>● 30 grams with JBT24M Bluetooth</li> </ul>

Python SDK



Python SDK	<ul style="list-style-type: none"> <li>● Available on GitHub</li> </ul> <p>Note: Please refer to README.md file first for proper configuration</p> <div>  <div> <p><b>GitHub</b></p> <p><a href="https://github.com/bigheadG/mmWave">https://github.com/bigheadG/mmWave</a></p> </div>  </div>
------------	--



# Batman BM301-FDS mmWave EVM Kit


mmWAVE SENSOR EVALUATION SOLUTION

mmWAVE SENSOR EVALUATION SOLUTION

## mmWave Pin Assignment

### J3 J3 Pin Assignment

Pin#	Name	Name	Pin#
01	D3V3	D3V3	02
03	D3V3	PI SDA	04
05	GND	PI SCL	06
07	RS232 RX	SYNC IN JBRX1	08
09	RS232 TX	GND	10
11	nRST	GPIO 0	12
13	GND	GPIO 1	14
15	DP0	CS1	16
17	DP1	3V3_LS	18
19	GND	MOSI 1	20
21	BSS LOGGER	MISO 1	22
23	MSS LOGGER JBTX1	SPICLK 1	24
25	PMIC CLKOUT SOP2	GND	26
27	SYNC OUT SOP1	nERRIN	28
29	GND	nERROUT	30
31	WARMRST	GPIO 2	32



# Batman BM301-FDS mmWave EVM Kit

## mmWAVE SENSOR EVALUATION SOLUTION

### mmWAVE SENSOR EVALUATION SOLUTION

#### J3 Pin Assignment


Pin No	Name	Pin Type	Function Description
01	D3V3	I	POWER DC 3V3 Input
02	D3V3	I	POWER DC 3V3 Input
03	D3V3	I	POWER DC 3V3 Input
04	SDA	IO	I2C Pin
05	GND	GROUND	Digital ground
06	SCL	IO	I2C Pin
07	RS232 RX0	I	UART A Receive
08	SYNC IN JBRX1	I	Low frequency Synchronization signal input, UART B Receive
09	RS232 TX0	O	UART A Transmit
10	GND	GROUND	Digital ground
11	nRST	I	Power on reset for chip. Active low
12	GOIO 0	I	Select KeyData or RawData
13	GND	GROUND	Digital ground
14	GPIO 1	I	Reserved
15	DP0	IO	GPIO Pin
16	CS1	IO	SPI Channel A - chip Select
17	DP1	IO	GPIO Pin
18	3V3	O	For meaurement only
19	GND	GROUND	Digital ground
20	MOSI 1	IO	SPI Channel A - Master Out Slave In
21	BSS LOGGER	IO	BSS LOGGER
22	MISO 1	IO	SPI Channel A - Master In Slave Out
23	MSS LOGGER JBTX1	O	UART B Transmit
24	SPICLK 1	IO	SPI Channel A - Clock
25	SOP2	I	SOP2
26	GND	GROUND	Digital ground
27	SOP1	I	SOP1
28	nERRIN	I	Failsafe input to the device. Nerror output from any other device can be concentrated in the error signaling monitor module inside the device and appropriate action can be taken by Firmware.
29	GND	GROUND	Mistake Proofing Pin
30	nERROUT	O	Open drain fail safe output signal. Connected to PMIC/Processor/MCU to indicate that some severe critacatlty fault has happened. Recovery would be through reset.
31	WARMRST	IO	Open drain fail safe warm reset signal. Can be driven from PMIC for diagnostic or can be used as status signal that the device is going through reset.
32	GPIO2	O	LED Indicator

# Batman BM301-FDS mmWave EVM Kit

mmWAVE SENSOR EVALUATION SOLUTION

mmWAVE SENSOR EVALUATION SOLUTION

## mmWave Raspberry Pi Hat Pin Assignment




# Batman BM301-FDS mmWave EVM Kit

mmWAVE SENSOR EVALUATION SOLUTION

## mmWAVE SENSOR EVALUATION SOLUTION

### Product Dimensions



Copyright ©2019 , Joybien Technologies Co., Ltd.

Joybien reserves the right to make changes without further notice to and products herein. Joybien makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Joybien assume any liability arising out of the application or use of any product or circuit. Joybien's products are not to be used in life support devices or systems, if a failure of an Joybien's product can reasonably be expected to cause the failure of that life support device or system, or to affect the safety or effectiveness of that device or system.

For the latest version of this document, visit our website:

[www.joybien.com](http://www.joybien.com)



**Note:**

NVIDIA logo, and Jetson Nano are trademarks and/or registered trademarks of NVIDIA Corporation.

Raspberry Pi logo and Raspberry Pi 4 are trademarks and/or registered trademarks of Raspberry Pi Foundation.

"Python" is a registered trademark of the PSF.

This EVM Kit does not include Raspberry Pi computer, nor NVIDIA Jetson Nano computer.