



GTC4Lusso USA - Glossary - Latest Update: 2021-01-26

Protected by copyright. Copying for private or commercial purposes, in part or in whole, is not permitted unless authorised by Ferrari S.p.A. Ferrari S.p.A. does not guarantee or accept any liability with respect to the correctness of information in this document.

Copyright by Ferrari S.p.A. - P.IVA 00159560366

01.04 Glossary

N₂

Nitrogen

CO

Carbon Monoxide

CO₂

Carbon Dioxide

NO_x

Nitrogen Oxide

HC

Hydrocarbons

Standard

Indicates reference value

Service limit

Indicates the limit value beyond which a part or coupling must be serviced to bring it back within the prescribed tolerance range

Right hand and/or left hand

The terms right hand and/or left hand indicate the right hand and/or left-hand side of the vehicle with respect to the front of the vehicle

ABS

Anti Blockier System

ABS prevents wheel lock-up under braking to maintain directional control over the vehicle.

A.C.

Air conditioning

ASR

Antriebs Schlupf Regelung

Wheelspin control under acceleration.

AVH

Automatic Vehicle Holding

Supplementary function of the electric parking brake (EPB): releases the brake shoes and brake pads at different times. The result is optimised brake release behaviour, assisting the driver.

CAN

Controller Area Network

Communication line between ECUs.

CST

Control Stability Traction

Stability and traction control

DCt

Dual Clutch Transmission

Dual clutch transmission. Each of the two clutches is associated to a different part of the gearbox, with one part engaging even gears and the other engaging odd gears.

E-DIFF

Electronic Differential

Electronically controlled differential integrated with the EF1-Trac traction control system.

EBD

Electronic Brake Force Distribution

Electronic brake force distribution system.

ECU

Electronic Control Unit

Electronic control unit

EF1-TRAC

Traction control integrated with Hy-Kers system.

Excess torque produced by the engine is used by the Hy-Kers system to charge the high voltage battery.

The system is self-adaptive and calculates the maximum grip available by constantly monitoring the relative speeds of the wheels.

EPB

Electric Parking Brake

Electric parking brake, with an electric motor actuating the rear brake shoes controlled by an electronic control unit.

ESC

Electronic Stability Control

The ESC function is implemented by the two systems: VDC and EF1-Trac

F1-Trac

Traction control system based on race technology.

The system is self-adaptive and calculates the maximum grip available by constantly monitoring the relative speeds of the wheels. F1-Trac correlates real data against a vehicle dynamics model stored in the control system and optimises the behaviour of the vehicle by controlling engine torque delivery.

FPB

Ferrari Brake Prefill

A system that eliminates the gap between the brake pads and discs by applying slight pressure to the brake system as soon as the accelerator pedal is released when imminent braking is expected. The result is improved brake response.

HV

High Voltage

High voltage electrical system.

HVB

High Voltage Battery

480 Volt high voltage battery situated under the passenger compartment, which accumulates the energy necessary to power the Hy-Kers hybrid system.

HPU

Hybrid Power Unit

Power unit of the Hy-Kers hybrid system, consisting of a DC-DC inverter and converter.

LC

Launch Control
Performance start strategy.

LV

Low Voltage
Low voltage electrical system.

PTU

Power Transfer Unit
Transmission power unit.

RHT

Retractable Hard Top
Retractable hard top.

TPMS

Tyre Pressure Monitoring System
System monitoring the pressure and temperature of the vehicle's tyres. An ECU receives data transmitted by special sensors installed on the interior of the wheel rims near the valves. Tyre pressure and temperature information and the relative messages are displayed on the instrument panel.

VDC

Vehicle Dynamic Control
Vehicle dynamics control using the brake system and engine torque.

4WD

4 Wheel Drive
4 wheel drive system.