



Fluids and lubricants table

Model	Last revision
GTC4LUSSO	December 2017

Parts to be refilled	Required fluid specifications for correct vehicle operation:	Ferrari recommended product:	Quantity
Engine lub. system	Synthetic engine oil SAE ¹⁾ 10W-60 API ²⁾ SN/CF ACEA ³⁾ A3/B4	PENNZOIL PLATINUM Racing SAE 10W-60	13.74 qts ⁶⁾ 1.59 qts ⁷⁾ 1.06 to 2.11 l / 621.4 mi ⁸⁾
Hydraulic syst. DCT gearbox gears	Synthetic transmission fluid SAE ¹⁾ 75W-90 API ²⁾ GL-4 / GL-5 / MT-1	SHELL Spirax S5 ATE 75W-90	3.70 qts
Hydraulic syst. DCT gearbox clutches	Transmission fluid 7DCL750 ⁹⁾	SHELL DCT-F3	8.19 qts
Hydraulic syst. Brakes	DOT4 ⁴⁾ synthetic brake fluid	PETRONAS Tutela Brake Fluid Extreme HT	1.16 qts
Engine cooling syst.	Protective antifreeze coolant pre-diluted to 50% concentration with demineralised water	PAKELO Coolant G30® Red Long Life to be diluted to 50% concentration with demineralised water	17.86 qts
Hydraulic syst. Steering	Synthetic hydraulic fluid	PENTOSIN CHF 11S	1.69 qts
Hydraulic syst. PTU gears	Synthetic transmission fluid SAE ¹⁾ 75W-90	SHELL TF 1055	3.06 qts
Hydraulic syst. PTU actuators	Synthetic transmission fluid	SHELL DCT-F3	0.63 qts
Hydraulic syst. Suspension lift	Synthetic transmission fluid	SHELL Spirax S4 ATF HDX	1.16 qts
Fuel system	Unleaded petrol/gasoline (at least 95 R.O.N. ⁵⁾)	Unleaded petrol/gasoline (at least 98 R.O.N. ⁵⁾)	99.16 qts
Reserve			(13.74 qts)
A/C system	Refrigerant gas R 1234yf		1.32 ± 0.06 lbs
	Compressor oil PS-D1		10.98 cu.in.
Windscreen/Headlamp washer sys.	Mixture of demineralised water and glass cleaner		5.28 qts



This vehicle is compatible with unleaded petrol/gasoline with an ethanol content of up to 10% (E10).
Using fuels with an ethanol content between 10% to 25% ethanol may cause engine malfunction.
Using fuels with an ethanol content above 25% may cause permanent damage to the components of the engine fuel system.

1) SAE - Viscosity grade

Example: SAE 5W – 40

5W = indicates the viscosity grade at low temperatures (winter)

40 = indicates the viscosity grade at high temperatures

2) API - American Petroleum Institute

Example: SN/CF

SN = the first letter indicates that an engine oil is suitable for petrol engines, the second letter indicates the oil quality as defined by API tables.

CF = the first letter indicates that an engine oil is suitable for diesel engines, the second letter indicates the oil quality as defined by API tables.

3) ACEA - European Automobile Manufacturers Association:

Example: A3/B4

A3 = indicates a high performance engine oil suitable for petrol engines.

B4 = indicates a high performance engine oil suitable for diesel engines.

4) DOT - Brake fluid classification

indicates the chemical/physical characteristics of the brake fluid.

5) R.O.N. - Octane rating

indicates the knock resistance of a fuel.

6) Quantity at empty level.

7) Quantity between MIN and MAX.

8) Consumption.

9) Meets specification.