



GTC4Lusso USA - Technical specifications - Latest Update: 2021-01-26

Protected by copyright. Copying for private or commercial purposes, in part or in whole, is not permitted unless authorised by Ferrari S.p.A. Ferrari S.p.A. does not guarantee or accept any liability with respect to the correctness of information in this document.

Copyright by Ferrari S.p.A. - P.IVA 00159560366

D1.01 Technical specifications

Wheels

Front

Wheel rim size

Light alloy 8.5 " J x 20 "

Spare wheel 4.5 " J x 20 "

Tyre size

245/35 ZR20 Pirelli P Zero (F01)

245/35 ZR20 Michelin XL Pilot Sport 4S K1 TL

Winter 235/35 R20 Michelin Pilot Alpin PA4

Winter 235/35 R20 Pirelli Winter 270 Sottozero Series II

Spare wheel 145/60 R20

Rear

Wheel rim size

Light alloy 10.5 " J x 20 "

Spare wheel 4.5 " J x 20 "

Tyre size

295/35 ZR20 Pirelli P Zero (F01)

295/35 ZR20 Michelin XL Pilot Sport 4S K1 TL

Winter 285/35 R20 Michelin Pilot Alpin PA4

Winter 285/35 R20 Pirelli Winter 270 Sottozero Series II

Spare wheel 145/60 R20



Do not fit snow chains without activating “Snow chain mode” beforehand from the SETTINGS menu of the left hand TFT display, as described as follows.

Inflation pressure (cold)

	Front	Rear
Michelin XL Pilot Sport 4S K1 TL	34.81 psi	33.36 psi
Michelin Pilot Alpin PA4	34.81 psi	33.36 psi
Pirelli P Zero (F01)	30.46 psi	29 psi
Pirelli Winter 270 Sottozero Series II	30.46 psi	29 psi
Collapsible spare wheel	60.92 psi	60.92 psi



If prolonged driving at speeds in excess of 280 km/h is envisaged, inflate the Pirelli PZERO tyres to a pressure of 2.6 bar (front) and 2.5 bar (rear).

The maximum permitted speed with winter tyres is 240 km/h.

Brake system

CCM discs

Front: 398 mm x 38 mm

Rear: 360 mm x 32 mm

Callipers

Front: 6 pistons

Rear: 4 pistons

Electronic control systems

ABS (Anti Blockier System): system preventing wheel lock-up under braking.

EBD (Electronic Brake Force Distribution): a system optimising brake force distribution between the wheels.

VDC (Vehicle Dynamic Control): a system which uses the brakes to control vehicle dynamics.

FBP (Ferrari Brake Prefill): a system which eliminates the air gap between the calliper and disc by applying slight pressure to the brake system as soon as the accelerator is released.

4WS (4 Wheel Steering): a system improving grip extreme driving situations by steering the rear wheels as well as the front wheels.

Suspension

Arms

Front: double wishbones

Rear: Multilink

Shock absorbers

Adjustable damping control (MagneRide)

Electronic control systems

SCM (Magnetorheological Control System): a system (MagneRide) using magnetorheological fluid to vary the damping rate of the suspension.

4WS system (virtual short wheelbase)

The 4WS or Virtual Short Wheelbase system actively controls the rear axle, allowing the rear wheels to steer around a vertical axis.

The system automatically adjusts the steering angle of the rear wheels to attain the optimum steering effect in relation to steering angle, steering rate and vehicle speed.

The system offers the following benefits in terms of vehicle dynamics:

- faster response to steering wheel input;
- less understeer;
- reduced steering wheel activity when entering and following curves;
- consistent vehicle behaviour in bends.

If 4WS functionality is not available, the message "Steering rear axle not available" is shown on the left hand TFT display.

In the event of a severe 4WS system fault, the message "Steering rear axle failure" is shown on the left hand TFT display.

"Snow chain" mode



Do not fit snow chains without activating "Snow chain mode" beforehand from the SETTINGS menu of the left hand TFT display, as described as follows.



In “Snow chain mode”, rear axle steering is disabled.

To activate the mode, access the SETTINGS menu of the left hand TFT display, select the 2nd level menu “**Car setup**”, and enable the option “**Snow chain mode**”.