

Error Architecture

From Matchi Wiki

Contents

- 1 Error Code Reference
 - 1.1 General Error Codes
 - 1.2 Operating System Error Codes
 - 1.3 MySQL Error Codes
 - 1.4 Notify Error Codes
 - 1.5 Login Error Codes
 - 1.6 Organization Error Codes
 - 1.7 Geospatial Error Codes
 - 1.8 Innovation Error Codes
 - 1.9 Challenge Error Codes
 - 1.10 Event Error Codes
 - 1.11 Config Error Codes
 - 1.12 Content Error Codes
 - 1.13 System Error Codes
- 2 How to refresh this documentation

Error Code Reference

- Notes:
 - Errors groups by subsystem.
 - Each subsystem has a range of errors that start on a 1000.
 - Error codes are all negative, to make it easy to test for an error condition from a returning function in most cases.
 - Error codes shown here for MySQL and Linux Operating system are the same error codes used by the vendors.

General Error Codes

General			
Code	Alias	Error	Explanation
0	SUCCESS	Success	Operation successfully completed
-10000	UNKNOWN	Unknown Error	%s
-10001	FATAL	Fatal	%s
-10002	ERROR	Error	%s
-10003	WARN	Warn	%s
-10004	INFO	Information	%s
-10005	DEBUG	Debug	%s
-10006	TRACE	Trace	%s

Operating System Error Codes

Operating System			
Code	Alias	Error	Explanation
-1	EPERM	Operation not permitted	
-2	ENOENT	No such file or directory	
-3	ESRCH	No such process	
-4	EINTR	Interrupted system call	
-5	EIO	I/O error	
-6	ENXIO	No such device or address	
-7	E2BIG	Argument list too long	
-8	ENOEXEC	Exec format error	
-9	EBADF	Bad file number	
-10	ECHILD	No child processes	
-11	EAGAIN	Try again	
-12	ENOMEM	Out of memory	
-13	EACCES	Permission denied	
-14	EFAULT	Bad address	
-15	ENOTBLK	Block device required	
-16	EBUSY	Device or resource busy	
-17	EEXIST	File exists	
-18	EXDEV	Cross-device link	
-19	ENODEV	No such device	
-20	ENOTDIR	Not a directory	
-21	EISDIR	Is a directory	
-22	EINVAL	Invalid argument	
-23	ENFILE	File table overflow	
-24	EMFILE	Too many open files	
-25	ENOTTY	Not a typewriter	
-26	ETXTBSY	Text file busy	
-27	EFBIG	File too large	
-28	ENOSPC	No space left on device	
-29	ESPIPE	Illegal seek	
-30	EROFS	Read-only file system	
-31	EMLINK	Too many links	
-32	EPIPE	Broken pipe	
-33	EDOM	Math argument out of domain of func	
-34	ERANGE	Math result not representable	
-35	EDEADLK	Resource deadlock would occur	
-36	ENAMETOOLONG	File name too long	
-37	ENOLCK	No record locks available	
-38	ENOSYS	Function not implemented	
-39	ENOTEMPTY	Directory not empty	
-40	ELOOP	Too many symbolic links encountered	
-42	ENMSG	No message of desired type	
-43	EIDRM	Identifier removed	
-44	ECHRNG	Channel number out of range	
-45	EL2NSYNC	Level 2 not synchronized	
-46	EL3HLT	Level 3 halted	
-47	EL3RST	Level 3 reset	
-48	ELNRNG	Link number out of range	
-49	EUNATCH	Protocol driver not attached	
-50	ENOCSS	No CSI structure available	
-51	EL2HLT	Level 2 halted	
-52	EBADE	Invalid exchange	
-53	EBADR	Invalid request descriptor	
-54	EXFULL	Exchange full	
-55	ENOANO	No anode	
-56	EBADRQC	Invalid request code	
-57	EBADSLT	Invalid slot	
-59	EBFONT	Bad font file format	
-60	ENOSTR	Device not a stream	
-61	ENODATA	No data available	
-62	ETIME	Timer expired	

-63	ENOSR	Out of streams resources	
-64	ENONET	Machine is not on the network	
-65	ENOPKG	Package not installed	
-66	EREMOTE	Object is remote	
-67	ENOLINK	Link has been severed	
-68	EADV	Advertise error	
-69	ESRMNT	Srmount error	
-70	ECOMM	Communication error on send	
-71	EPROTO	Protocol error	
-72	EMULTIHOP	Multihop attempted	
-73	EDOTDOT	RFS specific error	
-74	EBADMSG	Not a data message	
-75	EOVERFLOW	Value too large for defined data type	
-76	ENOTUNIQ	Name not unique on network	
-77	EBADFD	File descriptor in bad state	
-78	EREMCHG	Remote address changed	
-79	ELIBACC	Can not access a needed shared library	
-80	ELIBBAD	Accessing a corrupted shared library	
-81	ELIBSCN	.lib section in a.out corrupted	
-82	ELIBMAX	Attempting to link in too many shared libraries	
-83	ELIBEXEC	Cannot exec a shared library directly	
-84	EILSEQ	Illegal byte sequence	
-85	ERESTART	Interrupted system call should be restarted	
-86	ESTRPIPE	Streams pipe error	
-87	EUSERS	Too many users	
-88	ENOTSOCK	Socket operation on non-socket	
-89	EDESTADDRREQ	Destination address required	
-90	EMSGSIZE	Message too long	
-91	EPROTOTYPE	Protocol wrong type for socket	
-92	ENOPROTOOPT	Protocol not available	
-93	EPROTONOSUPPORT	Protocol not supported	
-94	ESOCKTNOSUPPORT	Socket type not supported	
-95	EOPNOTSUPP	Operation not supported on transport endpoint	
-96	EPFNOSUPPORT	Protocol family not supported	
-97	EAFNOSUPPORT	Address family not supported by protocol	
-98	EADDRINUSE	Address already in use	
-99	EADDRNOTAVAIL	Cannot assign requested address	
-100	ENETDOWN	Network is down	
-101	ENETUNREACH	Network is unreachable	
-102	ENETRESET	Network dropped connection because of reset	
-103	ECONNABORTED	Software caused connection abort	
-104	ECONNRESET	Connection reset by peer	
-105	ENOBUFS	No buffer space available	
-106	EISCONN	Transport endpoint is already connected	
-107	ENOTCONN	Transport endpoint is not connected	
-108	ESHUTDOWN	Cannot send after transport endpoint shutdown	
-109	ETOOMANYREFS	Too many references: cannot splice	
-110	ETIMEDOUT	Connection timed out	
-111	ECONNREFUSED	Connection refused	
-112	EHOSTDOWN	Host is down	
-113	EHOSTUNREACH	No route to host	
-114	EALREADY	Operation already in progress	
-115	EINPROGRESS	Operation now in progress	
-116	ESTALE	Stale NFS file handle	
-117	EUCLEAN	Structure needs cleaning	
-118	ENOTNAM	Not a XENIX named type file	
-119	ENAVAIL	No XENIX semaphores available	
-120	EISNAM	Is a named type file	
-121	EREMOTEIO	Remote I/O error	
-122	EDQUOT	Quota exceeded	
-123	ENOMEDIUM	No medium found	
-124	EMEDIUMTYPE	Wrong medium type	
-125	ECANCELED	Operation Canceled	

-126	ENOKEY	Required key not available	
-127	EKEYEXPIRED	Key has expired	
-128	EKEYREVOKED	Key has been revoked	
-129	EKEYREJECTED	Key was rejected by service	
-130	EOWNERDEAD	Owner died	
-131	ENOTRECOVERABLE	State not recoverable	

MySQL Error Codes

MySQL

Code	Alias	Error	Explanation
-1002	ER_NO	NO	Used in the construction of other messages.
-1003	ER_YES	YES	Used in the construction of other messages. Extended EXPLAIN form Note messages. ER_YES is used in the Code column for these messages. SHOW WARNINGS output.
-1004	ER_CANT_CREATE_FILE	Can't create file '%s' (errno: %d). Occurs for failure to copy an .frm file to a new location, during	Possible causes: Permissions problem for source .frm file; destination exists but is not writeable.
-1005	ER_CANT_CREATE_TABLE	Can't create table '%s' (errno: %d)	
-1006	ER_CANT_CREATE_DB	Can't create database '%s' (errno: %d)	
-1007	ER_DB_CREATE_EXISTS	Can't create database '%s'; database exists. An attempt to create a database failed because the data	Drop the database first if you really want to replace an existing database. NOT EXISTS clause to the CREATE DATABASE statement if to replace database without having the statement produce an error.
-1008	ER_DB_DROP_EXISTS	Can't drop database '%s'; database doesn't exist	
-1009	ER_DB_DROP_DELETE	Error dropping database (can't delete '%s', (errno: %d)	
-1010	ER_DB_DROP_RMDIR	Error dropping database (can't rmdir '%s', (errno: %d)	
-1011	ER_CANT_DELETE_FILE	Error on delete of '%s' (errno: %d)	
-1012	ER_CANT_FIND_SYSTEM_	Can't read record in system table	Returned by InnoDB for attempts to access InnoDB INFORMATION tables when InnoDB is unavailable.
-1013	ER_CANT_GET_STAT	Can't get status of '%s' (errno: %d)	
-1014	ER_CANT_GET_WD	Can't get working directory (errno: %d)	
-1015	ER_CANT_LOCK	Can't lock file (errno: %d)	
-1016	ER_CANT_OPEN_FILE	Can't open file: '%s' (errno: %d)	
-1017	ER_FILE_NOT_FOUND	Can't find file: '%s' (errno: %d)	
-1018	ER_CANT_READ_DIR	Can't read dir of '%s' (errno: %d)	
-1019	ER_CANT_SET_WD	Can't change dir to '%s' (errno: %d)	
-1020	ER_CHECKREAD	Record has changed since last read in table '%s'	
-1021	ER_DISK_FULL	Disk full (%s); waiting for someone to free some space...	
-1022	ER_DUP_KEY	Can't write; duplicate key in table '%s'	
-1023	ER_ERROR_ON_CLOSE	Error on close of '%s' (errno: %d)	
-1024	ER_ERROR_ON_READ	Error reading file '%s' (errno: %d)	
-1025	ER_ERROR_ON_RENAME	Error on rename of '%s' to '%s' (errno: %d)	
-1026	ER_ERROR_ON_WRITE	Error writing file '%s' (errno: %d)	
-1027	ER_FILE_USED	'%s' is locked against change	
-1028	ER_FILSORT_ABORT	Sort aborted	
-1029	ER_FORM_NOT_FOUND	View '%s' doesn't exist for '%s'	
-1030	ER_GET_ERRNO	Got error %d from storage engine	Check the %d value to see what the OS error means. For example, 28 you have run out of disk space.
-1031	ER_ILLEGAL_HA	Table storage engine for '%s' doesn't have this option	
-1032	ER_KEY_NOT_FOUND	Can't find record in '%s'	
-1033	ER_NOT_FORM_FILE	Incorrect information in file: '%s'	
-1034	ER_NOT_KEYFILE	Incorrect key file for table '%s'; try to repair it	
-1035	ER_OLD_KEYFILE	Old key file for table '%s'; repair it!	
-1036	ER_OPEN_AS_READONLY	Table '%s' is read only	
-1037	ER_OUTOFMEMORY	Out of memory; restart server and try again (needed %d bytes)	
-1038	ER_OUT_OF_SORTMEMORY	Out of sort memory, consider increasing server sort buffer size	
-1039	ER_UNEXPECTED_EOF	Unexpected EOF found when reading file '%s' (errno: %d)	
-1040	ER_CON_COUNT_ERROR	Too many connections	
-1041	ER_OUT_OF_RESOURCES	Out of memory; check if mysqld or some other process uses all available memory; if not, you may have	
-1042	ER_BAD_HOST_ERROR	Can't get hostname for your address	
-1043	ER_HANDSHAKE_ERROR	Bad handshake	
-1044	ER_DBACCESS_DENIED_E	Access denied for user '%s'@'%s' to database '%s'	
-1045	ER_ACCESS_DENIED_ERR	Access denied for user '%s'@'%s' (using password: %s)	
-1046	ER_NO_DB_ERROR	No database selected	
-1047	ER_UNKNOWN_COM_ERROR	Unknown command	
-1048	ER_BAD_NULL_ERROR	Column '%s' cannot be null	
-1049	ER_BAD_DB_ERROR	Unknown database '%s'	
-1050	ER_TABLE_EXISTS_ERRO	Table '%s' already exists	

-1051	ER_BAD_TABLE_ERROR	Unknown table '%s'	
-1052	ER_NON_UNIQ_ERROR	Column '%s' in %s is ambiguous	%s = column name. %s = location of column (for example, "field list")
-1053	ER_SERVER_SHUTDOWN	Server shutdown in progress	
-1054	ER_BAD_FIELD_ERROR	Unknown column '%s' in '%s'	
-1055	ER_WRONG_FIELD_WITH	'%s' isn't in GROUP BY	
-1056	ER_WRONG_GROUP_FIELD	Can't group on '%s'	
-1057	ER_WRONG_SUM_SELECT	Statement has sum functions and columns in same statement	
-1058	ER_WRONG_VALUE_COUNT	Column count doesn't match value count	
-1059	ER_TOO_LONG_IDENT	Identifier name '%s' is too long	
-1060	ER_DUP_FIELDNAME	Duplicate column name '%s'	
-1061	ER_DUP_KEYNAME	Duplicate key name '%s'	
-1062	ER_DUP_ENTRY	Duplicate entry '%s' for key %d	The message returned with this error uses the format string for ER_DUP_ENTRY_WITH_KEY_NAME.
-1063	ER_WRONG_FIELD_SPEC	Incorrect column specifier for column '%s'	
-1064	ER_PARSE_ERROR	%s near '%s' at line %d	
-1065	ER_EMPTY_QUERY	Query was empty	
-1066	ER_NONUNIQ_TABLE	Not unique table/alias: '%s'	
-1067	ER_INVALID_DEFAULT	Invalid default value for '%s'	
-1068	ER_MULTIPLE_PRI_KEY	Multiple primary key defined	
-1069	ER_TOO_MANY_KEYS	Too many keys specified; max %d keys allowed	
-1070	ER_TOO_MANY_KEY_PART	Too many key parts specified; max %d parts allowed	
-1071	ER_TOO_LONG_KEY	Specified key was too long; max key length is %d bytes	
-1072	ER_KEY_COLUMN_DOES_N	Key column '%s' doesn't exist in table	
-1073	ER_BLOB_USED_AS_KEY	BLOB column '%s' can't be used in key specification with the used table type	
-1074	ER_TOO_BIG_FIELDLENG	Column length too big for column '%s' (max = %lu); use BLOB or TEXT instead	
-1075	ER_WRONG_AUTO_KEY	Incorrect table definition; there can be only one auto column and it must be defined as a key	
-1076	ER_READY	%s: ready for connections. Version: '%s' socket: '%s' port: %d	
-1077	ER_NORMAL_SHUTDOWN	%s: Normal shutdown	
-1078	ER_GOT_SIGNAL	%s: Got signal %d. Aborting!	
-1079	ER_SHUTDOWN_COMPLETE	%s: Shutdown complete	
-1080	ER_FORCING_CLOSE	%s: Forcing close of thread %ld user: '%s'	
-1081	ER_IPSOCK_ERROR	Can't create IP socket	
-1082	ER_NO_SUCH_INDEX	Table '%s' has no index like the one used in CREATE INDEX; recreate the table	
-1083	ER_WRONG_FIELD_TERMI	Field separator argument is not what is expected; check the manual	
-1084	ER_BLOBS_AND_NO_TERM	You can't use fixed rowlength with BLOBs; please use 'fields terminated by'	
-1085	ER_TEXTFILE_NOT_READ	The file '%s' must be in the database directory or be readable by all	
-1086	ER_FILE_EXISTS_ERROR	File '%s' already exists	
-1087	ER_LOAD_INFO	Records: %ld Deleted: %ld Skipped: %ld Warnings: %ld	
-1088	ER_ALTER_INFO	Records: %ld Duplicates: %ld	
-1089	ER_WRONG_SUB_KEY	Incorrect prefix key; the used key part isn't a string, the used length is longer than the key part,	
-1090	ER_CANT_REMOVE_ALL_F	You can't delete all columns with ALTER TABLE; use DROP TABLE instead	
-1091	ER_CANT_DROP_FIELD_O	Can't DROP '%s'; check that column/key exists	
-1092	ER_INSERT_INFO	Records: %ld Duplicates: %ld Warnings: %ld	
-1093	ER_UPDATE_TABLE_USED	You can't specify target table '%s' for update in FROM clause	
-1094	ER_NO_SUCH_THREAD	Unknown thread id: %lu	
-1095	ER_KILL_DENIED_ERROR	You are not owner of thread %lu	
-1096	ER_NO_TABLES_USED	No tables used	
-1097	ER_TOO_BIG_SET	Too many strings for column %s and SET	
-1098	ER_NO_UNIQUE_LOGFILE	Can't generate a unique log-filename %s.(1-999	
-1099	ER_TABLE_NOT_LOCKED_	Table '%s' was locked with a READ lock and can't be updated	
-1100	ER_TABLE_NOT_LOCKED	Table '%s' was not locked with LOCK TABLES	
-1101	ER_BLOB_CANT_HAVE_DE	BLOB/TEXT column '%s' can't have a default value	

-1102	ER_WRONG_DB_NAME	Incorrect database name '%s'	
-1103	ER_WRONG_TABLE_NAME	Incorrect table name '%s'	
-1104	ER_TOO_BIG_SELECT	The SELECT would examine more than MAX_JOIN_SIZE rows; check your WHERE and use SET SQL_BIG_SELECTS=	
-1105	ER_UNKNOWN_ERROR	Unknown error	
-1106	ER_UNKNOWN_PROCEDURE	Unknown procedure '%s'	
-1107	ER_WRONG_PARAMCOUNT_	Incorrect parameter count to procedure '%s'	
-1108	ER_WRONG_PARAMETERS_	Incorrect parameters to procedure '%s'	
-1109	ER_UNKNOWN_TABLE	Unknown table '%s' in %s	
-1110	ER_FIELD_SPECIFIED_T	Column '%s' specified twice	
-1111	ER_INVALID_GROUP_FUN	Invalid use of group function	
-1112	ER_UNSUPPORTED_EXTEN	Table '%s' uses an extension that doesn't exist in this MySQL version	
-1113	ER_TABLE_MUST_HAVE_C	A table must have at least 1 column	
-1114	ER_RECORD_FILE_FULL	The table '%s' is full	
-1115	ER_UNKNOWN_CHARACTER	Unknown character set: '%s'	
-1116	ER_TOO_MANY_TABLES	Too many tables; MySQL can only use %d tables in a join	
-1117	ER_TOO_MANY_FIELDS	Too many columns	
-1118	ER_TOO_BIG_ROWSIZE	Row size too large. The maximum row size for the used table type, not counting BLOBs, is %ld. You ha	
-1119	ER_STACK_OVERRUN	Thread stack overrun: Used: %ld of a %ld stack. Use 'mysqld --thread_stack=#' to specify a bigger st	
-1120	ER_WRONG_OUTER_JOIN	Cross dependency found in OUTER JOIN; examine your ON conditions	
-1121	ER_NULL_COLUMN_IN_IN	Table handler doesn't support NULL in given index. Please change column '%s' to be NOT NULL or use a	
-1122	ER_CANT_FIND_UDF	Can't load function '%s'	
-1123	ER_CANT_INITIALIZE_U	Can't initialize function '%s'; %s	
-1124	ER_UDF_NO_PATHS	No paths allowed for shared library	
-1125	ER_UDF_EXISTS	Function '%s' already exists	
-1126	ER_CANT_OPEN_LIBRARY	Can't open shared library '%s' (errno: %d %s	
-1127	ER_CANT_FIND_DL_ENTR	Can't find symbol '%s' in library	
-1128	ER_FUNCTION_NOT_DEFI	Function '%s' is not defined	
-1129	ER_HOST_IS_BLOCKED	Host '%s' is blocked because of many connection errors; unblock with 'mysqladmin flush-hosts'	
-1130	ER_HOST_NOT_PRIVILEG	Host '%s' is not allowed to connect to this MySQL server	
-1131	ER_PASSWORD_ANONYMOU	You are using MySQL as an anonymous user and anonymous users are not allowed to change passwords	
-1132	ER_PASSWORD_NOT_ALLO	You must have privileges to update tables in the mysql database to be able to change passwords for o	
-1133	ER_PASSWORD_NO_MATCH	Can't find any matching row in the user table	
-1134	ER_UPDATE_INFO	Rows matched: %ld Changed: %ld Warnings: %ld	
-1135	ER_CANT_CREATE_THREA	Can't create a new thread (errno %d); if you are not out of available memory, you can consult the ma	
-1136	ER_WRONG_VALUE_COUNT	Column count doesn't match value count at row %ld	
-1137	ER_CANT_REOPEN_TABLE	Can't reopen table: '%s'	
-1138	ER_INVALID_USE_OF_NU	Invalid use of NULL value	
-1139	ER_REGEXP_ERROR	Got error '%s' from regexp	
-1140	ER_MIX_OF_GROUP_FUNC	Mixing of GROUP columns (MIN(),MAX(),COUNT(),...) with no GROUP columns is illegal if there is no GR	
-1141	ER_NONEXISTING_GRANT	There is no such grant defined for user '%s' on host '%s'	
-1142	ER_TABLEACCESS_DENIE	%s command denied to user '%s'@'%s' for table '%s'	
-1143	ER_COLUMNACCESS_DENI	%s command denied to user '%s'@'%s' for column '%s' in table '%s'	
-1144	ER_ILLEGAL_GRANT_FOR	Illegal GRANT/REVOKE command; please consult the manual to see which privileges can be used	
-1145	ER_GRANT_WRONG_HOST_	The host or user argument to GRANT is too long	
-1146	ER_NO_SUCH_TABLE	Table '%s.%s' doesn't exist	
-1147	ER_NONEXISTING_TABLE	There is no such grant defined for user '%s' on host '%s' on table '%s'	
-1148	ER_NOT_ALLOWED_COMMA	The used command is not allowed with this MySQL version	

-1149	ER_SYNTAX_ERROR	You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version	
-1150	ER_DELAYED_CANT_CHAN	Delayed insert thread couldn't get requested lock for table %s	
-1151	ER_TOO_MANY_DELAYED_	Too many delayed threads in use	
-1152	ER_ABORTING_CONNECTI	Aborted connection %ld to db: '%s' user: '%s' (%s	
-1153	ER_NET_PACKET_TOO_LA	Got a packet bigger than 'max_allowed_packet' bytes	
-1154	ER_NET_READ_ERROR_FR	Got a read error from the connection pipe	
-1155	ER_NET_FCNTL_ERROR	Got an error from fcntl(
-1156	ER_NET_PACKETS_OUT_O	Got packets out of order	
-1157	ER_NET_UNCOMPRESS_ER	Couldn't uncompress communication packet	
-1158	ER_NET_READ_ERROR	Got an error reading communication packets	
-1159	ER_NET_READ_INTERRUPT	Got timeout reading communication packets	
-1160	ER_NET_ERROR_ON_WRIT	Got an error writing communication packets	
-1161	ER_NET_WRITE_INTERRUPT	Got timeout writing communication packets	
-1162	ER_TOO_LONG_STRING	Result string is longer than 'max_allowed_packet' bytes	
-1163	ER_TABLE_CANT_HANDLE	The used table type doesn't support BLOB/TEXT columns	
-1164	ER_TABLE_CANT_HANDLE	The used table type doesn't support AUTO_INCREMENT columns	
-1165	ER_DELAYED_INSERT_TA	INSERT DELAYED can't be used with table '%s' because it is locked with LOCK TABLES	
-1166	ER_WRONG_COLUMN_NAME	Incorrect column name '%s'	
-1167	ER_WRONG_KEY_COLUMN	The used storage engine can't index column '%s'	
-1168	ER_WRONG_MRG_TABLE	Unable to open underlying table which is differently defined or of non-MyISAM type or doesn't exist	
-1169	ER_DUP_UNIQUE	Can't write, because of unique constraint, to table '%s'	
-1170	ER_BLOB_KEY_WITHOUT_	BLOB/TEXT column '%s' used in key specification without a key length	
-1171	ER_PRIMARY_CANT_HAVE	All parts of a PRIMARY KEY must be NOT NULL; if you need NULL in a key, use UNIQUE instead	
-1172	ER_TOO_MANY_ROWS	Result consisted of more than one row	
-1173	ER_REQUIRES_PRIMARY_	This table type requires a primary key	
-1174	ER_NO_RAID_COMPILED	This version of MySQL is not compiled with RAID support	
-1175	ER_UPDATE_WITHOUT_KE	You are using safe update mode and you tried to update a table without a WHERE that uses a KEY column	
-1176	ER_KEY_DOES_NOT_EXIT	Key '%s' doesn't exist in table '%s'	
-1177	ER_CHECK_NO_SUCH_TAB	Can't open table	
-1178	ER_CHECK_NOT_IMPLEMENTED	The storage engine for the table doesn't support %s	
-1179	ER_CANT_DO_THIS_DURI	You are not allowed to execute this command in a transaction	
-1180	ER_ERROR_DURING_COMM	Got error %d during COMMIT	
-1181	ER_ERROR_DURING_ROLL	Got error %d during ROLLBACK	
-1182	ER_ERROR_DURING_FLUSH	Got error %d during FLUSH_LOGS	
-1183	ER_ERROR_DURING_CHECK	Got error %d during CHECKPOINT	
-1184	ER_NEW_ABORTING_CONN	Aborted connection %ld to db: '%s' user: '%s' host: '%s' (%s	
-1185	ER_DUMP_NOT_IMPLEMENTED	The storage engine for the table does not support binary table dump	
-1186	ER_FLUSH_MASTER_BINL	Binlog closed, cannot RESET MASTER	
-1187	ER_INDEX_REBUILD	Failed rebuilding the index of dumped table '%s'	
-1188	ER_MASTER	Error from master: '%s'	
-1189	ER_MASTER_NET_READ	Net error reading from master	
-1190	ER_MASTER_NET_WRITE	Net error writing to master	
-1191	ER_FT_MATCHING_KEY_N	Can't find FULLTEXT index matching the column list	
-1192	ER_LOCK_OR_ACTIVE_TR	Can't execute the given command because you have active locked tables or an active transaction	
-1193	ER_UNKNOWN_SYSTEM_VA	Unknown system variable '%s'	
-1194	ER_CRASHED_ON_USAGE	Table '%s' is marked as crashed and should be repaired	
-1195	ER_CRASHED_ON_REPAIR	Table '%s' is marked as crashed and last (automatic?) repair failed	

-1196	ER_WARNING_NOT_COMPL	Some non-transactional changed tables couldn't be rolled back	
-1197	ER_TRANS_CACHE_FULL	Multi-statement transaction required more than 'max_binlog_cache_size' bytes of storage; increase th	
-1198	ER_SLAVE_MUST_STOP	This operation cannot be performed with a running slave; run STOP SLAVE first	
-1199	ER_SLAVE_NOT_RUNNING	This operation requires a running slave; configure slave and do START SLAVE	
-1200	ER_BAD_SLAVE	The server is not configured as slave; fix in config file or with CHANGE MASTER TO	
-1201	ER_MASTER_INFO	Could not initialize master info structure; more error messages can be found in the MySQL error log	
-1202	ER_SLAVE_THREAD	Could not create slave thread; check system resources	
-1203	ER_TOO_MANY_USER_CON	User %s already has more than 'max_user_connections' active connections	
-1204	ER_SET_CONSTANTS_ONL	You may only use constant expressions with SET	
-1205	ER_LOCK_WAIT_TIMEOUT	Lock wait timeout exceeded; try restarting transaction	
-1206	ER_LOCK_TABLE_FULL	The total number of locks exceeds the lock table size	
-1207	ER_READ_ONLY_TRANSAC	Update locks cannot be acquired during a READ UNCOMMITTED transaction	
-1208	ER_DROP_DB_WITH_READ	DROP DATABASE not allowed while thread is holding global read lock	
-1209	ER_CREATE_DB_WITH_RE	CREATE DATABASE not allowed while thread is holding global read lock	
-1210	ER_WRONG_ARGUMENTS	Incorrect arguments to %s	
-1211	ER_NO_PERMISSION_TO_	'%s'@'%s' is not allowed to create new users	
-1212	ER_UNION_TABLES_IN_D	Incorrect table definition; all MERGE tables must be in the same database	
-1213	ER_LOCK_DEADLOCK	Deadlock found when trying to get lock; try restarting transaction	
-1214	ER_TABLE_CANT_HANDLE	The used table type doesn't support FULLTEXT indexes	
-1215	ER_CANNOT_ADD_FOREIG	Cannot add foreign key constraint	
-1216	ER_NO_REFERENCED_ROW	Cannot add or update a child row: a foreign key constraint fails	
-1217	ER_ROW_IS_REFERENCED	Cannot delete or update a parent row: a foreign key constraint fails	
-1218	ER_CONNECT_TO_MASTER	Error connecting to master: %s	
-1219	ER_QUERY_ON_MASTER	Error running query on master: %s	
-1220	ER_ERROR_WHEN_EXECUT	Error when executing command %s: %s	
-1221	ER_WRONG_USAGE	Incorrect usage of %s and %s	
-1222	ER_WRONG_NUMBER_OF_C	The used SELECT statements have a different number of columns	
-1223	ER_CANT_UPDATE_WITH_	Can't execute the query because you have a conflicting read lock	
-1224	ER_MIXING_NOT_ALLOWE	Mixing of transactional and non-transactional tables is disabled	
-1225	ER_DUP_ARGUMENT	Option '%s' used twice in statement	
-1226	ER_USER_LIMIT_REACHE	User '%s' has exceeded the '%s' resource (current value: %ld)	
-1227	ER_SPECIFIC_ACCESS_D	Access denied; you need (at least one of) the %s privilege(s) for this operation	
-1228	ER_LOCAL_VARIABLE	Variable '%s' is a SESSION variable and can't be used with SET GLOBAL	
-1229	ER_GLOBAL_VARIABLE	Variable '%s' is a GLOBAL variable and should be set with SET GLOBAL	
-1230	ER_NO_DEFAULT	Variable '%s' doesn't have a default value	
-1231	ER_WRONG_VALUE_FOR_V	Variable '%s' can't be set to the value of '%s'	
-1232	ER_WRONG_TYPE_FOR_VA	Incorrect argument type to variable '%s'	
-1233	ER_VAR_CANT_BE_READ	Variable '%s' can only be set, not read	
-1234	ER_CANT_USE_OPTION_H	Incorrect usage/placement of '%s'	
-1235	ER_NOT_SUPPORTED_YET	This version of MySQL doesn't yet support '%s'	
-1236	ER_MASTER_FATAL_ERRO	Got fatal error %d from master when reading data from binary log: '%s'	
-1237	ER_SLAVE_IGNORED_TAB	Slave SQL thread ignored the query because of replicate-*.table rules	
-1238	ER_INCORRECT_GLOBAL_	Variable '%s' is a %s variable	
-1239	ER_WRONG_FK_DEF	Incorrect foreign key definition for '%s': %s	

-1240	ER_KEY_REF_DO_NOT_MA	Key reference and table reference don't match	
-1241	ER_OPERAND_COLUMNS	Operand should contain %d column(s)	
-1242	ER_SUBQUERY_NO_1_ROW	Subquery returns more than 1 row	
-1243	ER_UNKNOWN_STMT_HAND	Unknown prepared statement handler (%.*s) given to %s	
-1244	ER_CORRUPT_HELP_DB	Help database is corrupt or does not exist	
-1245	ER_CYCLIC_REFERENCE	Cyclic reference on subqueries	
-1246	ER_AUTO_CONVERT	Converting column '%s' from %s to %s	
-1247	ER_ILLEGAL_REFERENCE	Reference '%s' not supported (%s	
-1248	ER_DERIVED_MUST_HAVE	Every derived table must have its own alias	
-1249	ER_SELECT_REDUCED	Select %u was reduced during optimization	
-1250	ER_TABLENAME_NOT_ALL	Table '%s' from one of the SELECTs cannot be used in %s	
-1251	ER_NOT_SUPPORTED_AUT	Client does not support authentication protocol requested by server; consider upgrading MySQL client	
-1252	ER_SPATIAL_CANT_HAVE	All parts of a SPATIAL index must be NOT NULL	
-1253	ER_COLLATION_CHARSET	COLLATION '%s' is not valid for CHARACTER SET '%s'	
-1254	ER_SLAVE_WAS_RUNNING	Slave is already running	
-1255	ER_SLAVE_WAS_NOT_RUN	Slave already has been stopped	
-1256	ER_TOO_BIG_FOR_UNCOM	Uncompressed data size too large; the maximum size is %d (probably, length of uncompressed data was	
-1257	ER_ZLIB_Z_MEM_ERROR	ZLIB: Not enough memory	
-1258	ER_ZLIB_Z_BUF_ERROR	ZLIB: Not enough room in the output buffer (probably, length of uncompressed data was corrupted	
-1259	ER_ZLIB_Z_DATA_ERROR	ZLIB: Input data corrupted	
-1260	ER_CUT_VALUE_GROUP_C	Row %u was cut by GROUP_CONCAT(
-1261	ER_WARN_TOO_FEW_RECO	Row %ld doesn't contain data for all columns	
-1262	ER_WARN_TOO_MANY_REC	Row %ld was truncated; it contained more data than there were input columns	
-1263	ER_WARN_NULL_TO_NOTN	Column set to default value; NULL supplied to NOT NULL column '%s' at row %ld	
-1264	ER_WARN_DATA_OUT_OF_	Out of range value for column '%s' at row %ld	
-1265	WARN_DATA_TRUNCATED	Data truncated for column '%s' at row %ld	
-1266	ER_WARN_USING_OTHER_	Using storage engine %s for table '%s'	
-1267	ER_CANT_AGGREGATE_2C	Illegal mix of collations (%s,%s) and (%s,%s) for operation '%s'	
-1268	ER_DROP_USER	Cannot drop one or more of the requested users	
-1269	ER_REVOKE_GRANTS	Can't revoke all privileges for one or more of the requested users	
-1270	ER_CANT_AGGREGATE_3C	Illegal mix of collations (%s,%s), (%s,%s), (%s,%s) for operation '%s'	
-1271	ER_CANT_AGGREGATE_NC	Illegal mix of collations for operation '%s'	
-1272	ER_VARIABLE_IS_NOT_S	Variable '%s' is not a variable component (can't be used as XXXX.variable_name	
-1273	ER_UNKNOWN_COLLATION	Unknown collation: '%s'	
-1274	ER_SLAVE_IGNORED_SSL	SSL parameters in CHANGE MASTER are ignored because this MySQL slave was compiled without SSL support	
-1275	ER_SERVER_IS_IN_SECU	Server is running in --secure-auth mode, but '%s'@'%s' has a password in the old format; please chan	
-1276	ER_WARN_FIELD_RESOLV	Field or reference '%s%s%s%s%s' of SELECT #%d was resolved in SELECT #%d	
-1277	ER_BAD_SLAVE_UNTIL_C	Incorrect parameter or combination of parameters for START SLAVE UNTIL	
-1278	ER_MISSING_SKIP_SLAV	It is recommended to use --skip-slave-start when doing step-by-step replication with START SLAVE UNT	
-1279	ER_UNTIL_COND_IGNORE	SQL thread is not to be started so UNTIL options are ignored	
-1280	ER_WRONG_NAME_FOR_IN	Incorrect index name '%s'	
-1281	ER_WRONG_NAME_FOR_CA	Incorrect catalog name '%s'	
-1282	ER_WARN_QC_RESIZE	Query cache failed to set size %lu; new query cache size is %lu	
-1283	ER_BAD_FT_COLUMN	Column '%s' cannot be part of FULLTEXT index	
-1284	ER_UNKNOWN_KEY_CACHE	Unknown key cache '%s'	

-1285	ER_WARN_HOSTNAME_WON	MySQL is started in --skip-name-resolve mode; you must restart it without this switch for this grant	
-1286	ER_UNKNOWN_STORAGE_E	Unknown storage engine '%s'	
-1287	ER_WARN_DEPRECATED_S	'%s' is deprecated and will be removed in a future release. Please use %s instead	
-1288	ER_NON_UPDATABLE_TAB	The target table %s of the %s is not updatable	
-1289	ER_FEATURE_DISABLED	The '%s' feature is disabled; you need MySQL built with '%s' to have it working	
-1290	ER_OPTION_PREVENTS_S	The MySQL server is running with the %s option so it cannot execute this statement	
-1291	ER_DUPLICATED_VALUE_	Column '%s' has duplicated value '%s' in %s	
-1292	ER_TRUNCATED_WRONG_V	Truncated incorrect %s value: '%s'	
-1293	ER_TOO_MUCH_AUTO_TIM	Incorrect table definition; there can be only one TIMESTAMP column with CURRENT_TIMESTAMP in DEFAULT	
-1294	ER_INVALID_ON_UPDATE	Invalid ON UPDATE clause for '%s' column	
-1295	ER_UNSUPPORTED_PS	This command is not supported in the prepared statement protocol yet	
-1296	ER_GET_ERRMSG	Got error %d '%s' from %s	
-1297	ER_GET_TEMPORARY_ERR	Got temporary error %d '%s' from %s	
-1298	ER_UNKNOWN_TIME_ZONE	Unknown or incorrect time zone: '%s'	
-1299	ER_WARN_INVALID_TIME	Invalid TIMESTAMP value in column '%s' at row %ld	
-1300	ER_INVALID_CHARACTER	Invalid %s character string: '%s'	
-1301	ER_WARN_ALLOWED_PACK	Result of %s() was larger than max_allowed_packet (%ld) - truncated	
-1302	ER_CONFLICTING_DECLA	Conflicting declarations: '%s%s' and '%s%s'	
-1303	ER_SP_NO_RECURSIVE_C	Can't create a %s from within another stored routine	
-1304	ER_SP_ALREADY_EXISTS	%s %s already exists	
-1305	ER_SP_DOES_NOT_EXIST	%s %s does not exist	
-1306	ER_SP_DROP_FAILED	Failed to DROP %s %s	
-1307	ER_SP_STORE_FAILED	Failed to CREATE %s %s	
-1308	ER_SP_LILABEL_MISMAT	%s with no matching label: %s	
-1309	ER_SP_LABEL_REDEFINE	Redefining label %s	
-1310	ER_SP_LABEL_MISMATCH	End-label %s without match	
-1311	ER_SP_UNINIT_VAR	Referring to uninitialized variable %s	
-1312	ER_SP_BADSELECT	PROCEDURE %s can't return a result set in the given context	
-1313	ER_SP_BADRETURN	RETURN is only allowed in a FUNCTION	
-1314	ER_SP_BADSTATEMENT	%s is not allowed in stored procedures	
-1315	ER_UPDATE_LOG_DEPREC	The update log is deprecated and replaced by the binary log; SET SQL_LOG_UPDATE has been ignored. Th	
-1316	ER_UPDATE_LOG_DEPREC	The update log is deprecated and replaced by the binary log; SET SQL_LOG_UPDATE has been translated	
-1317	ER_QUERY_INTERRUPTED	Query execution was interrupted	
-1318	ER_SP_WRONG_NO_OF_AR	Incorrect number of arguments for %s %s; expected %u, got %u	
-1319	ER_SP_COND_MISMATCH	Undefined CONDITION: %s	
-1320	ER_SP_NORETURN	No RETURN found in FUNCTION %s	
-1321	ER_SP_NORETURNEND	FUNCTION %s ended without RETURN	
-1322	ER_SP_BAD_CURSOR_QUE	Cursor statement must be a SELECT	
-1323	ER_SP_BAD_CURSOR_SEL	Cursor SELECT must not have INTO	
-1324	ER_SP_CURSOR_MISMATC	Undefined CURSOR: %s	
-1325	ER_SP_CURSOR_ALREADY	Cursor is already open	
-1326	ER_SP_CURSOR_NOT_OPE	Cursor is not open	
-1327	ER_SP_UNDECLARED_VAR	Undeclared variable: %s	
-1328	ER_SP_WRONG_NO_OF_FE	Incorrect number of FETCH variables	
-1329	ER_SP_FETCH_NO_DATA	No data - zero rows fetched, selected, or processed	
-1330	ER_SP_DUP_PARAM	Duplicate parameter: %s	
-1331	ER_SP_DUP_VAR	Duplicate variable: %s	
-1332	ER_SP_DUP_COND	Duplicate condition: %s	
-1333	ER_SP_DUP_CURS	Duplicate cursor: %s	
-1334	ER_SP_CANT_ALTER	Failed to ALTER %s %s	
-1335	ER_SP_SUBSELECT_NYI	Subquery value not supported	
-1336	ER_STMT_NOT_ALLOWED_	%s is not allowed in stored function or trigger	

-1337	ER_SP_VARCOND_AFTER_	Variable or condition declaration after cursor or handler declaration	
-1338	ER_SP_CURSOR_AFTER_H	Cursor declaration after handler declaration	
-1339	ER_SP_CASE_NOT_FOUND	Case not found for CASE statement	
-1340	ER_FPARSER_TOO_BIG_F	Configuration file '%s' is too big	
-1341	ER_FPARSER_BAD_HEADE	Malformed file type header in file '%s'	
-1342	ER_FPARSER_EOF_IN_CO	Unexpected end of file while parsing comment '%s'	
-1343	ER_FPARSER_ERROR_IN_	Error while parsing parameter '%s' (line: '%s'	
-1344	ER_FPARSER_EOF_IN_UN	Unexpected end of file while skipping unknown parameter '%s'	
-1345	ER_VIEW_NO_EXPLAIN	EXPLAIN/SHOW can not be issued; lacking privileges for underlying table	
-1346	ER_FRM_UNKNOWN_TYPE	File '%s' has unknown type '%s' in its header	
-1347	ER_WRONG_OBJECT	'%s.%s' is not %s	
-1348	ER_NONUPDATEABLE_COL	Column '%s' is not updatable	
-1349	ER_VIEW_SELECT_DERIV	View's SELECT contains a subquery in the FROM clause	
-1350	ER_VIEW_SELECT_CLAUS	View's SELECT contains a '%s' clause	
-1351	ER_VIEW_SELECT_VARIA	View's SELECT contains a variable or parameter	
-1352	ER_VIEW_SELECT_TMPTA	View's SELECT refers to a temporary table '%s'	
-1353	ER_VIEW_WRONG_LIST	View's SELECT and view's field list have different column counts	
-1354	ER_WARN_VIEW_MERGE	View merge algorithm can't be used here for now (assumed undefined algorithm)	
-1355	ER_WARN_VIEW_WITHOUT	View being updated does not have complete key of underlying table in it	
-1356	ER_VIEW_INVALID	View '%s.%s' references invalid table(s) or column(s) or function(s) or definer/invoke of view lack	
-1357	ER_SP_NO_DROP_SP	Can't drop or alter a %s from within another stored routine	
-1358	ER_SP_GOTO_IN_HNDLR	GOTO is not allowed in a stored procedure handler	
-1359	ER_TRG_ALREADY_EXIST	Trigger already exists	
-1360	ER_TRG_DOES_NOT_EXIS	Trigger does not exist	
-1361	ER_TRG_ON_VIEW_OR_TE	Trigger's '%s' is view or temporary table	
-1362	ER_TRG_CANT_CHANGE_R	Updating of %s row is not allowed in %strigger	
-1363	ER_TRG_NO_SUCH_ROW_I	There is no %s row in %s trigger	
-1364	ER_NO_DEFAULT_FOR_FI	Field '%s' doesn't have a default value	
-1365	ER_DIVISION_BY_ZERO	Division by 0	
-1366	ER_TRUNCATED_WRONG_V	Incorrect %s value: '%s' for column '%s' at row %ld	
-1367	ER_ILLEGAL_VALUE_FOR	Illegal %s '%s' value found during parsing	
-1368	ER_VIEW_NONUPD_CHECK	CHECK OPTION on non-updatable view '%s.%s'	
-1369	ER_VIEW_CHECK_FAILED	CHECK OPTION failed '%s.%s'	
-1370	ER_PROCAACCESS_DENIED	%s command denied to user '%s'@'%s' for routine '%s'	
-1371	ER_RELAY_LOG_FAIL	Failed purging old relay logs: %s	
-1372	ER_PASSWD_LENGTH	Password hash should be a %d-digit hexadecimal number	
-1373	ER_UNKNOWN_TARGET_BI	Target log not found in binlog index	
-1374	ER_IO_ERR_LOG_INDEX_	I/O error reading log index file	
-1375	ER_BINLOG_PURGE_PROH	Server configuration does not permit binlog purge	
-1376	ER_FSEEK_FAIL	Failed on fseek(
-1377	ER_BINLOG_PURGE_FATA	Fatal error during log purge	
-1378	ER_LOG_IN_USE	A purgeable log is in use, will not purge	
-1379	ER_LOG_PURGE_UNKNOWN	Unknown error during log purge	
-1380	ER_RELAY_LOG_INIT	Failed initializing relay log position: %s	
-1381	ER_NO_BINARY_LOGGING	You are not using binary logging	
-1382	ER_RESERVED_SYNTAX	The '%s' syntax is reserved for purposes internal to the MySQL server	
-1383	ER_WSAS_FAILED	WSAStartup Failed	
-1384	ER_DIFF_GROUPS_PROC	Can't handle procedures with different groups yet	
-1385	ER_NO_GROUP_FOR_PROC	Select must have a group with this procedure	
-1386	ER_ORDER_WITH_PROC	Can't use ORDER clause with this procedure	
-1387	ER_LOGGING_PROHIBIT_	Binary logging and replication forbid changing the global server %s	
-1388	ER_NO_FILE_MAPPING	Can't map file: %s, errno: %d	
-1389	ER_WRONG_MAGIC	Wrong magic in %s	

-1390	ER_PS_MANY_PARAM	Prepared statement contains too many placeholders	
-1391	ER_KEY_PART_0	Key part '%s' length cannot be 0	
-1392	ER_VIEW_CHECKSUM	View text checksum failed	
-1393	ER_VIEW_MULTIUPDATE	Can not modify more than one base table through a join view '%s.%s'	
-1394	ER_VIEW_NO_INSERT_FI	Can not insert into join view '%s.%s' without fields list	
-1395	ER_VIEW_DELETE_MERGE	Can not delete from join view '%s.%s'	
-1396	ER_CANNOT_USER	Operation %s failed for %s	
-1397	ER_XAER_NOTA	XAER_NOTA: Unknown XID	
-1398	ER_XAER_INVALID	XAER_INVALID: Invalid arguments (or unsupported command)	
-1399	ER_XAER_RMFAIL	XAER_RMFAIL: The command cannot be executed when global transaction is in the %s state	
-1400	ER_XAER_OUTSIDE	XAER_OUTSIDE: Some work is done outside global transaction	
-1401	ER_XAER_RMERR	XAER_RMERR: Fatal error occurred in the transaction branch - check your data for consistency	
-1402	ER_XA_RBROLLBACK	XA_RBROLLBACK: Transaction branch was rolled back	
-1403	ER_NONEXISTING_PROC	There is no such grant defined for user '%s' on host '%s' on routine '%s'	
-1404	ER_PROC_AUTO_GRANT_F	Failed to grant EXECUTE and ALTER ROUTINE privileges	
-1405	ER_PROC_AUTO_REVOKE	Failed to revoke all privileges to dropped routine	
-1406	ER_DATA_TOO_LONG	Data too long for column '%s' at row %ld	
-1407	ER_SP_BAD_SQLSTATE	Bad SQLSTATE: '%s'	
-1408	ER_STARTUP	%s: ready for connections. Version: '%s' socket: '%s' port: %d %s	
-1409	ER_LOAD_FROM_FIXED_S	Can't load value from file with fixed size rows to variable	
-1410	ER_CANT_CREATE_USER	You are not allowed to create a user with GRANT	
-1411	ER_WRONG_VALUE_FOR_T	Incorrect %s value: '%s' for function %s	
-1412	ER_TABLE_DEF_CHANGED	Table definition has changed, please retry transaction	
-1413	ER_SP_DUP_HANDLER	Duplicate handler declared in the same block	
-1414	ER_SP_NOT_VAR_ARG	OUT or INOUT argument %d for routine %s is not a variable or NEW pseudo-variable in BEFORE trigger	
-1415	ER_SP_NO_RESET	Not allowed to return a result set from a %s	
-1416	ER_CANT_CREATE_GEOME	Cannot get geometry object from data you send to the GEOMETRY field	
-1417	ER_FAILED_ROUTINE_BR	A routine failed and has neither NO SQL nor READS SQL DATA in its declaration and binary logging is	
-1418	ER_BINLOG_UNSAFE_ROU	This function has none of DETERMINISTIC, NO SQL, or READS SQL DATA in its declaration and binary log	
-1419	ER_BINLOG_CREATE_ROU	You do not have the SUPER privilege and binary logging is enabled (you *might* want to use the less	
-1420	ER_EXEC_STMT_WITH_OP	You can't execute a prepared statement which has an open cursor associated with it. Reset the statem	
-1421	ER_STMT_HAS_NO_OPEN	The statement (%lu) has no open cursor.	
-1422	ER_COMMIT_NOT_ALLOWE	Explicit or implicit commit is not allowed in stored function or trigger.	
-1423	ER_NO_DEFAULT_FOR_VI	Field of view '%s.%s' underlying table doesn't have a default value	
-1424	ER_SP_NO_RECURSION	Recursive stored functions and triggers are not allowed.	
-1425	ER_TOO_BIG_SCALE	Too big scale %d specified for column '%s'. Maximum is %lu.	
-1426	ER_TOO_BIG_PRECISION	Too big precision %d specified for column '%s'. Maximum is %lu.	
-1427	ER_M_BIGGER_THAN_D	For float(M,D), double(M,D) or decimal(M,D), M must be >= D (column '%s'),	
-1428	ER_WRONG_LOCK_OF_SYS	You can't combine write-locking of system tables with other tables or lock types	
-1429	ER_CONNECT_TO_FOREIG	Unable to connect to foreign data source: %s	
-1430	ER_QUERY_ON_FOREIGN	There was a problem processing the query on the foreign data source. Data source error: %s	
-1431	ER_FOREIGN_DATA_SOUR	The foreign data source you are trying to reference does not exist. Data source error: %s	

-1432	ER_FOREIGN_DATA_STRI	Can't create federated table. The data source connection string '%s' is not in the correct format	
-1433	ER_FOREIGN_DATA_STRI	The data source connection string '%s' is not in the correct format	
-1434	ER_CANT_CREATE_FEDER	Can't create federated table. Foreign data src error: %s	
-1435	ER_TRG_IN_WRONG_SCHE	Trigger in wrong schema	
-1436	ER_STACK_OVERRUN_NEE	Thread stack overrun: %ld bytes used of a %ld byte stack, and %ld bytes needed. Use 'mysqld --thread	
-1437	ER_TOO_LONG_BODY	Routine body for '%s' is too long	
-1438	ER_WARN_CANT_DROP_DE	Cannot drop default keycache	
-1439	ER_TOO_BIG_DISPLAYWI	Display width out of range for column '%s' (max = %lu	
-1440	ER_XAER_DUPID	XAER_DUPID: The XID already exists	
-1441	ER_DATETIME_FUNCTION	Datetime function: %s field overflow	
-1442	ER_CANT_UPDATE_USED_	Can't update table '%s' in stored function/trigger because it is already used by statement which inv	
-1443	ER_VIEW_PREVENT_UPDA	The definition of table '%s' prevents operation %s on table '%s'.	
-1444	ER_PS_NO_RECURSION	The prepared statement contains a stored routine call that refers to that same statement. It's not a	
-1445	ER_SP_CANT_SET_AUTOC	Not allowed to set autocommit from a stored function or trigger	
-1446	ER_MALFORMED_DEFINER	Definer is not fully qualified	
-1447	ER_VIEW_FRM_NO_USER	View '%s'.'%s' has no definer information (old table format). Current user is used as definer. Pleas	
-1448	ER_VIEW_OTHER_USER	You need the SUPER privilege for creation view with '%s'@'%s' definer	
-1449	ER_NO_SUCH_USER	The user specified as a definer ('%s'@'%s') does not exist	
-1450	ER_FORBID_SCHEMA_CHA	Changing schema from '%s' to '%s' is not allowed.	
-1451	ER_ROW_IS_REFERENCED	Cannot delete or update a parent row: a foreign key constraint fails (%s	
-1452	ER_NO_REFERENCED_ROW	Cannot add or update a child row: a foreign key constraint fails (%s	
-1453	ER_SP_BAD_VAR_SHADOW	Variable '%s' must be quoted with `...`, or renamed	
-1454	ER_TRG_NO_DEFINER	No definer attribute for trigger '%s'.'%s'. The trigger will be activated under the authorization of	
-1455	ER_OLD_FILE_FORMAT	'%s' has an old format, you should re-create the '%s' object(s	
-1456	ER_SP_RECURSION_LIMI	Recursive limit %d (as set by the max_sp_recursion_depth variable) was exceeded for routine %s	
-1457	ER_SP_PROC_TABLE_COR	Failed to load routine %s. The table mysql.proc is missing, corrupt, or contains bad data (internal	
-1458	ER_SP_WRONG_NAME	Incorrect routine name '%s'	
-1459	ER_TABLE_NEEDS_UPGRA	Table upgrade required. Please do "REPAIR TABLE '%s'" or dump/reload to fix it!	
-1460	ER_SP_NO_AGGREGATE	AGGREGATE is not supported for stored functions	
-1461	ER_MAX_PREPARED_STMT	Can't create more than max_prepared_stmt_count statements (current value: %lu	
-1462	ER_VIEW_RECURSIVE	'%s'.'%s' contains view recursion	
-1463	ER_NON_GROUPING_FIEL	Non-grouping field '%s' is used in %s clause	
-1464	ER_TABLE_CANT_HANDLE	The used table type doesn't support SPATIAL indexes	
-1465	ER_NO_TRIGGERS_ON_SY	Triggers can not be created on system tables	
-1466	ER_REMOVED_SPACES	Leading spaces are removed from name '%s'	
-1467	ER_AUTOINC_READ_FAIL	Failed to read auto-increment value from storage engine	
-1468	ER_USERNAME	user name	
-1469	ER_HOSTNAME	host name	
-1470	ER_WRONG_STRING LENG	String '%s' is too long for %s (should be no longer than %d	
-1471	ER_NON_INSERTABLE_TA	The target table %s of the %s is not insertable-into	
-1472	ER_ADMIN_WRONG_MRG_T	Table '%s' is differently defined or of non-MyISAM type or doesn't exist	
-1473	ER_TOO_HIGH_LEVEL_OF	Too high level of nesting for select	
-1474	ER_NAME_BECOMES_EMPT	Name '%s' has become '	
-1475	ER_AMBIGUOUS_FIELD_T	First character of the FIELDS TERMINATED string is ambiguous; please use non-optional and non-	

		empty	
-1476	ER_FOREIGN_SERVER_EX	The foreign server, %s, you are trying to create already exists.	
-1477	ER_FOREIGN_SERVER_DO	The foreign server name you are trying to reference does not exist. Data source error: %s	
-1478	ER_ILLEGAL_HA_CREATE	Table storage engine '%s' does not support the create option '%s'	
-1479	ER_PARTITION_REQUIRE	Syntax error: %s PARTITIONING requires definition of VALUES %s for each partition	
-1480	ER_PARTITION_WRONG_V	Only %s PARTITIONING can use VALUES %s in partition definition	
-1481	ER_PARTITION_MAXVALU	MAXVALUE can only be used in last partition definition	
-1482	ER_PARTITION_SUBPART	Subpartitions can only be hash partitions and by key	
-1483	ER_PARTITION_SUBPART	Must define subpartitions on all partitions if on one partition	
-1484	ER_PARTITION_WRONG_N	Wrong number of partitions defined, mismatch with previous setting	
-1485	ER_PARTITION_WRONG_N	Wrong number of subpartitions defined, mismatch with previous setting	
-1486	ER_CONST_EXPR_IN_PAR	Constant/Random expression in (sub)partitioning function is not allowed	In 5.5.1: ER_CONST_EXPR_IN_PARTITION_FUNC_ERROR was ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR. ER_CONST_EXPR_IN_PARTITION_FUNC_ERROR was removed
-1487	ER_NO_CONST_EXPR_IN_	Expression in RANGE/LIST VALUES must be constant	
-1488	ER_FIELD_NOT_FOUND_P	Field in list of fields for partition function not found in table	
-1489	ER_LIST_OF_FIELDS_ON	List of fields is only allowed in KEY partitions	
-1490	ER_INCONSISTENT_PART	The partition info in the frm file is not consistent with what can be written into the frm file	
-1491	ER_PARTITION_FUNC_NO	The %s function returns the wrong type	
-1492	ER_PARTITIONS_MUST_B	For %s partitions each partition must be defined	
-1493	ER_RANGE_NOT_INCREAS	VALUES LESS THAN value must be strictly increasing for each partition	
-1494	ER_INCONSISTENT_TYPE	VALUES value must be of same type as partition function	
-1495	ER_MULTIPLE_DEF_CONS	Multiple definition of same constant in list partitioning	
-1496	ER_PARTITION_ENTRY_E	Partitioning can not be used stand-alone in query	
-1497	ER_MIX_HANDLER_ERROR	The mix of handlers in the partitions is not allowed in this version of MySQL	
-1498	ER_PARTITION_NOT_DEF	For the partitioned engine it is necessary to define all %s	
-1499	ER_TOO_MANY_PARTITIO	Too many partitions (including subpartitions) were defined	
-1500	ER_SUBPARTITION_ERRO	It is only possible to mix RANGE/LIST partitioning with HASH/KEY partitioning for subpartitioning	
-1501	ER_CANT_CREATE_HANDL	Failed to create specific handler file	
-1502	ER_BLOB_FIELD_IN_PAR	A BLOB field is not allowed in partition function	
-1503	ER_UNIQUE_KEY_NEED_A	A %s must include all columns in the table's partitioning function	
-1504	ER_NO_PARTS_ERROR	Number of %s = 0 is not an allowed value	
-1505	ER_PARTITION_MGMT_ON	Partition management on a not partitioned table is not possible	
-1506	ER_FOREIGN_KEY_ON_PA	Foreign key clause is not yet supported in conjunction with partitioning	
-1507	ER_DROP_PARTITION_NO	Error in list of partitions to %s	
-1508	ER_DROP_LAST_PARTITI	Cannot remove all partitions, use DROP TABLE instead	
-1509	ER_COALESCE_ONLY_ON_	COALESCE PARTITION can only be used on HASH/KEY partitions	
-1510	ER_REORG_HASH_ONLY_O	REORGANIZE PARTITION can only be used to reorganize partitions not to change their numbers	
-1511	ER_REORG_NO_PARAM_ER	REORGANIZE PARTITION without parameters can only be used on auto-partitioned tables using HASH PARTI	
-1512	ER_ONLY_ON_RANGE_LIS	%s PARTITION can only be used on RANGE/LIST partitions	
-1513	ER_ADD_PARTITION_SUB	Trying to Add partition(s) with wrong number of subpartitions	
-1514	ER_ADD_PARTITION_NO_	At least one partition must be added	

-1515	ER_COALESCE_PARTITIO	At least one partition must be coalesced	
-1516	ER_REORG_PARTITION_N	More partitions to reorganize than there are partitions	
-1517	ER_SAME_NAME_PARTITI	Duplicate partition name %s	
-1518	ER_NO_BINLOG_ERROR	It is not allowed to shut off binlog on this command	
-1519	ER_CONSECUTIVE_REORG	When reorganizing a set of partitions they must be in consecutive order	
-1520	ER_REORG_OUTSIDE_RAN	Reorganize of range partitions cannot change total ranges except for last partition where it can ext	
-1521	ER_PARTITION_FUNCATIO	Partition function not supported in this version for this handler	
-1522	ER_PART_STATE_ERROR	Partition state cannot be defined from CREATE/ALTER TABLE	
-1523	ER_LIMITED_PART_RANG	The %s handler only supports 32 bit integers in VALUES	
-1524	ER_PLUGIN_IS_NOT_LOA	Plugin '%s' is not loaded	
-1525	ER_WRONG_VALUE	Incorrect %s value: '%s'	
-1526	ER_NO_PARTITION_FOR_	Table has no partition for value %s	
-1527	ER_FILEGROUP_OPTION_	It is not allowed to specify %s more than once	
-1528	ER_CREATE_FILEGROUP_	Failed to create %s	
-1529	ER_DROP_FILEGROUP_FA	Failed to drop %s	
-1530	ER_TABLESPACE_AUTO_E	The handler doesn't support autoextend of tablespaces	
-1531	ER_WRONG_SIZE_NUMBER	A size parameter was incorrectly specified, either number or on the form 10M	
-1532	ER_SIZE_OVERFLOW_ERR	The size number was correct but we don't allow the digit part to be more than 2 billion	
-1533	ER_ALTER_FILEGROUP_F	Failed to alter: %s	
-1534	ER_BINLOG_ROW_LOGGIN	Writing one row to the row-based binary log failed	
-1535	ER_BINLOG_ROW_WRONG_	Table definition on master and slave does not match: %s	
-1536	ER_BINLOG_ROW_RBR_TO	Slave running with --log-slave-updates must use row-based binary logging to be able to replicate row	
-1537	ER_EVENT_ALREADY_EXI	Event '%s' already exists	
-1538	ER_EVENT_STORE_FAILE	Failed to store event %s. Error code %d from storage engine.	
-1539	ER_EVENT_DOES_NOT_EX	Unknown event '%s'	
-1540	ER_EVENT_CANT_ALTER	Failed to alter event '%s'	
-1541	ER_EVENT_DROP_FAILED	Failed to drop %s	
-1542	ER_EVENT_INTERVAL_NO	INTERVAL is either not positive or too big	
-1543	ER_EVENT_ENDS_BEFORE	ENDS is either invalid or before STARTS	
-1544	ER_EVENT_EXEC_TIME_I	Event execution time is in the past. Event has been disabled	
-1545	ER_EVENT_OPEN_TABLE_	Failed to open mysql.event	
-1546	ER_EVENT_NEITHER_M_E	No datetime expression provided	
-1547	ER_COL_COUNT_DOESNT_	Column count of mysql.%s is wrong. Expected %d, found %d. The table is probably corrupted	
-1548	ER_CANNOT_LOAD_FROM_	Cannot load from mysql.%s. The table is probably corrupted	
-1549	ER_EVENT_CANNOT_DELE	Failed to delete the event from mysql.event	
-1550	ER_EVENT_COMPILE_ERR	Error during compilation of event's body	
-1551	ER_EVENT_SAME_NAME	Same old and new event name	
-1552	ER_EVENT_DATA_TOO_LO	Data for column '%s' too long	
-1553	ER_DROP_INDEX_FK	Cannot drop index '%s': needed in a foreign key constraint	
-1554	ER_WARN_DEPRECATED_S	The syntax '%s' is deprecated and will be removed in MySQL %s. Please use %s instead	
-1555	ER_CANT_WRITE_LOCK_L	You can't write-lock a log table. Only read access is possible	
-1556	ER_CANT_LOCK_LOG_TAB	You can't use locks with log tables.	
-1557	ER_FOREIGN_DUPLICATE	Upholding foreign key constraints for table '%s', entry '%s', key %d would lead to a duplicate entry	
-1558	ER_COL_COUNT_DOESNT_	Column count of mysql.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Ple	
-1559	ER_TEMP_TABLE_PREVEN	Cannot switch out of the row-based binary log format when the session has open temporary tables	
-1560	ER_STORED_FUNCTION_P	Cannot change the binary logging format inside a stored function or trigger	
-1561	ER_NDB_CANT_SWITCH_B	The NDB cluster engine does not support changing	

		the binlog format on the fly yet	
-1562	ER_PARTITION_NO_TEMP	Cannot create temporary table with partitions	
-1563	ER_PARTITION_CONST_D	Partition constant is out of partition function domain	
-1564	ER_PARTITION_FUNCIO	This partition function is not allowed	
-1565	ER_DDL_LOG_ERROR	Error in DDL log	
-1566	ER_NULL_IN_VALUES_LE	Not allowed to use NULL value in VALUES LESS THAN	
-1567	ER_WRONG_PARTITION_N	Incorrect partition name	
-1568	ER_CANT_CHANGE_TX_IS	Transaction isolation level can't be changed while a transaction is in progress	
-1569	ER_DUP_ENTRY_AUTOINC	ALTER TABLE causes auto_increment resequecing, resulting in duplicate entry '%s' for key '%s'	
-1570	ER_EVENT_MODIFY_QUEUE	Internal scheduler error %d	
-1571	ER_EVENT_SET_VAR_ERR	Error during starting/stopping of the scheduler. Error code %u	
-1572	ER_PARTITION_MERGE_E	Engine cannot be used in partitioned tables	
-1573	ER_CANT_ACTIVATE_LOG	Cannot activate '%s' log	
-1574	ER_RBR_NOT_AVAILABLE	The server was not built with row-based replication	
-1575	ER_BASE64_DECODE_ERR	Decoding of base64 string failed	
-1576	ER_EVENT_RECURSION_F	Recursion of EVENT DDL statements is forbidden when body is present	
-1577	ER_EVENTS_DB_ERROR	Cannot proceed because system tables used by Event Scheduler were found damaged at server start	To address this issue, try running mysql_upgrade.
-1578	ER_ONLY_INTEGERS_ALL	Only integers allowed as number here	
-1579	ER_UNSUPPORTED_LOG_EN	This storage engine cannot be used for log tables"	
-1580	ER_BAD_LOG_STATEMENT	You cannot '%s' a log table if logging is enabled	
-1581	ER_CANT_RENAME_LOG_T	Cannot rename '%s'. When logging enabled, rename to/from log table must rename two tables: the log t	
-1582	ER_WRONG_PARAMCOUNT_	Incorrect parameter count in the call to native function '%s'	
-1583	ER_WRONG_PARAMETERS_	Incorrect parameters in the call to native function '%s'	
-1584	ER_WRONG_PARAMETERS_	Incorrect parameters in the call to stored function '%s'	
-1585	ER_NATIVE_FCT_NAME_C	This function '%s' has the same name as a native function	
-1586	ER_DUP_ENTRY_WITH_KEY	Duplicate entry '%s' for key '%s'	The format string for this error is also used with ER_DUP_ENTRY.
-1587	ER_BINLOG_PURGE_EMFI	Too many files opened, please execute the command again	
-1588	ER_EVENT_CANNOT_CREATE	Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was dropped imm	
-1589	ER_EVENT_CANNOT_ALTE	Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was dropped imm	
-1590	ER_SLAVE_INCIDENT	The incident %s occurred on the master. %s	
-1591	ER_NO_PARTITION_FOR_	Table has no partition for some existing values	
-1592	ER_BINLOG_UNSAFE_STATEMENT	Unsafe statement written to the binary log using statement format since BINLOG_FORMAT = STATEMENT. %	
-1593	ER_SLAVE_FATAL_ERROR	Fatal error: %s	
-1594	ER_SLAVE_RELAY_LOG_READ_FAILURE	Relay log read failure: %s	
-1595	ER_SLAVE_RELAY_LOG_WRITE_FAILURE	Relay log write failure: %s	
-1596	ER_SLAVE_CREATE_EVENT_FAILURE	Failed to create %s	
-1597	ER_SLAVE_MASTER_COMMAND_FAILED	Master command %s failed: %s	
-1598	ER_BINLOG_LOGGING_IMPOSSIBLE	Binary logging not possible. %s	
-1599	ER_VIEW_NO_CREATION_CONTEXT	View '%s`.`%s`' has no creation context	
-1600	ER_VIEW_INVALID_CREATION_CONTEXT	Creation context of view %s.%s is invalid	
-1601	ER_SR_INVALID_CREATION_CONTEXT	Creation context of stored routine %s.%s is invalid	
-1602	ER_TRG_CORRUPTED_FILE	Corrupted TRG file for table '%s`.`%s`'	
-1603	ER_TRG_NO_CREATION_CONTEXT	Triggers for table '%s`.`%s`' have no creation context	
-1604	ER_TRG_INVALID_CREATION_CONTEXT	Trigger creation context of table '%s`.`%s`' is invalid	
-1605	ER_EVENT_INVALID_CREATION_CONTEXT	Creation context of event '%s`.`%s`' is invalid	
-1606	ER_TRG_CANT_OPEN_TABLE	Cannot open table for trigger '%s`.`%s`'	
-1607	ER_CANT_CREATE_SROUTINE	Cannot create stored routine '%s`. Check warnings	
-1608	ER_NEVER_USED	Ambiguous slave modes combination. %s	In 5.5.3: ER_SLAVE_AMBIGUOUS_EXEC_MODE was renamed to ER_NEVER_USED. ER_NEVER_USED was added in 5.5.3.

-1609	ER_NO_FORMAT_DESCRIP	The BINLOG statement of type '%s' was not preceded by a format description BINLOG statement.	
-1610	ER_SLAVE_CORRUPT_EVE	Corrupted replication event was detected	
-1611	ER_LOAD_DATA_INVALID	Invalid column reference (%s) in LOAD DATA	
-1612	ER_LOG_PURGE_NO_FILE	Being purged log %s was not found	
-1613	ER_XA_RBTIMEOUT	XA_RBTIMEOUT: Transaction branch was rolled back: took too long	
-1614	ER_XA_RBDEADLOCK	XA_RBDEADLOCK: Transaction branch was rolled back: deadlock was detected	
-1615	ER_NEED_REPREPARE	Prepared statement needs to be re-prepared	
-1616	ER_DELAYED_NOT_SUPPO	DELAYED option not supported for table '%s'	
-1617	WARN_NO_MASTER_INFO	The master info structure does not exist	
-1618	WARN_OPTION_IGNORED	<%s> option ignored	
-1619	WARN_PLUGIN_DELETE_B	Built-in plugins cannot be deleted	
-1620	WARN_PLUGIN_BUSY	Plugin is busy and will be uninstalled on shutdown	
-1621	ER_VARIABLE_IS_READO	%s variable '%s' is read-only. Use SET %s to assign the value	
-1622	ER_WARN_ENGINE_TRANS	Storage engine %s does not support rollback for this statement. Transaction rolled back and must be	
-1623	ER_SLAVE_HEARTBEAT_F	Unexpected master's heartbeat data: %s	
-1624	ER_SLAVE_HEARTBEAT_V	The requested value for the heartbeat period is either negative or exceeds the maximum allowed (%s s	
-1625	ER_NDB_REPLICATION_S	Bad schema for mysql.ndb_replication table. %s	
-1626	ER_CONFLICT_FN_PARSE	Error in parsing conflict function. %s	
-1627	ER_EXCEPTIONS_WRITE_	Write to exceptions table failed. %s"	
-1628	ER_TOO_LONG_TABLE_CO	Comment for table '%s' is too long (max = %lu	
-1629	ER_TOO_LONG_FIELD_CO	Comment for field '%s' is too long (max = %lu	
-1630	ER_FUNC_INEXISTENT_N	FUNCTION %s does not exist. Check the 'Function Name Parsing and Resolution' section in the Referenc	
-1631	ER_DATABASE_NAME	Database	
-1632	ER_TABLE_NAME	Table	
-1633	ER_PARTITION_NAME	Partition	
-1634	ER_SUBPARTITION_NAME	Subpartition	
-1635	ER_TEMPORARY_NAME	Temporary	
-1636	ER_RENAMED_NAME	Renamed	
-1637	ER_TOO_MANY_CONCURRE	Too many active concurrent transactions	
-1638	WARN_NON_ASCII_SEPAR	Non-ASCII separator arguments are not fully supported	
-1639	ER_DEBUG_SYNC_TIMEOU	debug sync point wait timed out	
-1640	ER_DEBUG_SYNC_HIT_LI	debug sync point hit limit reached	
-1641	ER_DUP_SIGNAL_SET	Duplicate condition information item '%s'	
-1642	ER_SIGNAL_WARN	Unhandled user-defined warning condition	
-1643	ER_SIGNAL_NOT_FOUND	Unhandled user-defined not found condition	
-1644	ER_SIGNAL_EXCEPTION	Unhandled user-defined exception condition	
-1645	ER_RESIGNAL_WITHOUT_	RESIGNAL when handler not active	
-1646	ER_SIGNAL_BAD_CONDIT	SIGNAL/RESIGNAL can only use a CONDITION defined with SQLSTATE	
-1647	WARN_COND_ITEM_TRUNC	Data truncated for condition item '%s'	
-1648	ER_COND_ITEM_TOO_LON	Data too long for condition item '%s'	
-1649	ER_UNKNOWN_LOCALE	Unknown locale: '%s'	
-1650	ER_SLAVE_IGNORE_SERV	The requested server id %d clashes with the slave startup option --replicate-same-server-id	
-1651	ER_QUERY_CACHE_DISAB	Query cache is disabled; restart the server with query_cache_type=1 to enable it	
-1652	ER_SAME_NAME_PARTITI	Duplicate partition field name '%s'	
-1653	ER_PARTITION_COLUMN_	Inconsistency in usage of column lists for partitioning	
-1654	ER_WRONG_TYPE_COLUMN	Partition column values of incorrect type	
-1655	ER_TOO_MANY_PARTITIO	Too many fields in '%s'	
-1656	ER_MAXVALUE_IN_VALUE	Cannot use MAXVALUE as value in VALUES IN	
-1657	ER_TOO_MANY_VALUES_E	Cannot have more than one value for this type of %s partitioning	
-1658	ER_ROW_SINGLE_PARTIT	Row expressions in VALUES IN only allowed for multi-field column partitioning	
-1659	ER_FIELD_TYPE_NOT_AL	Field '%s' is of a not allowed type for this type of	

		partitioning	
-1660	ER_PARTITION_FIELDS_	The total length of the partitioning fields is too large	
-1661	ER_BINLOG_ROW_ENGINE	Cannot execute statement: impossible to write to binary log since both row-incapable engines and sta	ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE was added in
-1662	ER_BINLOG_ROW_MODE_A	Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = ROW and at least o	ER_BINLOG_ROW_MODE_AND_STMT_ENGINE was added in 5
-1663	ER_BINLOG_UNSAFE_AND	Cannot execute statement: impossible to write to binary log since statement is unsafe, storage engin	ER_BINLOG_UNSAFE_AND_STMT_ENGINE was added in 5.5.3.
-1664	ER_BINLOG_ROW_INJECT	Cannot execute statement: impossible to write to binary log since statement is in row format and at	ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE was adde
-1665	ER_BINLOG_STMT_MODE_	Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = STATEMENT and at l	ER_BINLOG_STMT_MODE_AND_ROW_ENGINE was added in 5
-1666	ER_BINLOG_ROW_INJECT	Cannot execute statement: impossible to write to binary log since statement is in row format and BIN	ER_BINLOG_ROW_INJECTION_AND_STMT_MODE was added
-1667	ER_BINLOG_MULTIPLE_E	Cannot execute statement: impossible to write to binary log since more than one engine is involved a	ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_EN added in 5.5.3.
-1668	ER_BINLOG_UNSAFE_LIM	The statement is unsafe because it uses a LIMIT clause. This is unsafe because the set of rows inclu	ER_BINLOG_UNSAFE_LIMIT was added in 5.5.3.
-1669	ER_BINLOG_UNSAFE_INS	The statement is unsafe because it uses INSERT DELAYED. This is unsafe because the times when rows a	ER_BINLOG_UNSAFE_INSERT_DELAYED was added in 5.5.3.
-1670	ER_BINLOG_UNSAFE_SYS	The statement is unsafe because it uses the general log, slow query log, or performance_schema table	ER_BINLOG_UNSAFE_SYSTEM_TABLE was added in 5.5.3.
-1671	ER_BINLOG_UNSAFE_AUT	Statement is unsafe because it invokes a trigger or a stored function that inserts into an AUTO_INCR	ER_BINLOG_UNSAFE_AUTOINC_COLUMNS was added in 5.5.3
-1672	ER_BINLOG_UNSAFE_UDF	Statement is unsafe because it uses a UDF which may not return the same value on the slave.	ER_BINLOG_UNSAFE_UDF was added in 5.5.3.
-1673	ER_BINLOG_UNSAFE_SYS	Statement is unsafe because it uses a system variable that may have a different value on the slave.	ER_BINLOG_UNSAFE_SYSTEM_VARIABLE was added in 5.5.3.
-1674	ER_BINLOG_UNSAFE_SYS	Statement is unsafe because it uses a system function that may return a different value on the slave	ER_BINLOG_UNSAFE_SYSTEM_FUNCTION was added in 5.5.3.
-1675	ER_BINLOG_UNSAFE_NON	Statement is unsafe because it accesses a non-transactional table after accessing a transactional ta	ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS was added
-1676	ER_MESSAGE_AND_STATE	%s Statement: %s	ER_MESSAGE_AND_STATEMENT was added in 5.5.3.
-1677	ER_SLAVE_CONVERSION_	Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'	ER_SLAVE_CONVERSION_FAILED was added in 5.5.3.
-1678	ER_SLAVE_CANT_CREATE	Can't create conversion table for table '%s.%s'	ER_SLAVE_CANT_CREATE_CONVERSION was added in 5.5.3.
-1679	ER_INSIDE_TRANSACTION	Cannot modify @@session.binlog_format inside a transaction	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_F added in 5.5.3.
-1680	ER_PATH_LENGTH	The path specified for %s is too long.	ER_PATH_LENGTH was added in 5.5.3.
-1681	ER_WARN_DEPRECATED_S	'%s' is deprecated and will be removed in a future release.	ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT was
-1682	ER_WRONG_NATIVE_TABL	Native table '%s.%s' has the wrong structure	ER_WRONG_NATIVE_TABLE_STRUCTURE was added in 5.5.3.
-1683	ER_WRONG_PERFSCHEMA_	Invalid performance_schema usage.	ER_WRONG_PERFSCHEMA_USAGE was added in 5.5.3.
-1684	ER_WARN_I_S_SKIPPED_	Table '%s.%s' was skipped since its definition is being modified by concurrent DDL statement	ER_WARN_I_S_SKIPPED_TABLE was added in 5.5.3.
-1685	ER_INSIDE_TRANSACTION	Cannot modify @@session.binlog_direct_non_transactional_updates inside a transaction	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_D added in 5.5.3.
-1686	ER_STORED_FUNCTION_P	Cannot change the binlog direct flag inside a stored function or trigger	ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_DIR in 5.5.3.
-1687	ER_SPATIAL_MUST_HAVE	A SPATIAL index may only contain a geometrical type column	ER_SPATIAL_MUST_HAVE_GEOM_COL was added in 5.5.2.
-1688	ER_TOO_LONG_INDEX_CO	Comment for index '%s' is too long (max = %lu	ER_TOO_LONG_INDEX_COMMENT was added in 5.5.3.
-1689	ER_LOCK_ABORTED	Wait on a lock was aborted due to a pending exclusive lock	ER_LOCK_ABORTED was added in 5.5.4.
-1690	ER_DATA_OUT_OF_RANGE	%s value is out of range in '%s'	ER_DATA_OUT_OF_RANGE was added in 5.5.5.
-1691	ER_WRONG_SPVAR_TYPE_	A variable of a non-integer based type in LIMIT clause	ER_WRONG_SPVAR_TYPE_IN_LIMIT was added in 5.5.5.
-1692	ER_BINLOG_UNSAFE_MUL	Mixing self-logging and non-self-logging engines in a statement is unsafe.	ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELF_LOC was added in 5.5.5.
-1693	ER_BINLOG_UNSAFE_MIX	Statement accesses nontransactional table as well as transactional or temporary table, and writes to	ER_BINLOG_UNSAFE_MIXED_STATEMENT was added in 5.5.5.
-1694	ER_INSIDE_TRANSACTION	Cannot modify @@session.sql_log_bin inside a transaction	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LOG in 5.5.5.
-1695	ER_STORED_FUNCTION_P	Cannot change the sql_log_bin inside a stored function or trigger	ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BIN 5.5.5.
-1696	ER_FAILED_READ_FROM_	Failed to read from the .par file	ER_FAILED_READ_FROM_PAR_FILE was added in 5.5.5.
-1697	ER_VALUES_IS_NOT_INT	VALUES value for partition '%s' must have type INT	ER_VALUES_IS_NOT_INT_TYPE_ERROR was added in 5.5.7.

-1698	ER_ACCESS_DENIED_NO_	Access denied for user '%s'@'%s'	ER_ACCESS_DENIED_NO_PASSWORD_ERROR was added in 5.
-1699	ER_SET_PASSWORD_AUTH	SET PASSWORD has no significance for users authenticating via plugins	ER_SET_PASSWORD_AUTH_PLUGIN was added in 5.5.7.
-1700	ER_GRANT_PLUGIN_USER	GRANT with IDENTIFIED WITH is illegal because the user %-. *s already exists	ER_GRANT_PLUGIN_USER_EXISTS was added in 5.5.7.
-1701	ER_TRUNCATE_ILLEGAL_	Cannot truncate a table referenced in a foreign key constraint (%s	ER_TRUNCATE_ILLEGAL_FK was added in 5.5.7.
-1702	ER_PLUGIN_IS_PERMANE	Plugin '%s' is force_plus permanent and can not be unloaded	ER_PLUGIN_IS_PERMANENT was added in 5.5.7.
-1703	ER_SLAVE_HEARTBEAT_V	The requested value for the heartbeat period is less than 1 millisecond. The value is reset to 0, me	ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN was ε
-1704	ER_SLAVE_HEARTBEAT_V	The requested value for the heartbeat period exceeds the value of 'slave_net_timeout' seconds. A sen	ER_SLAVE_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX was
-1705	ER_STMT_CACHE_FULL	Multi-row statements required more than 'max_binlog_stmt_cache_size' bytes of storage; increase this	ER_STMT_CACHE_FULL was added in 5.5.9.
-1706	ER_MULTI_UPDATE_KEY_	Primary key/partition key update is not allowed since the table is updated both as '%s' and '%s'.	ER_MULTI_UPDATE_KEY_CONFLICT was added in 5.5.11.
-1707	ER_TABLE_NEEDS_REBUI	Table rebuild required. Please do "ALTER TABLE '%s' FORCE" or dump/reload to fix it!	ER_TABLE_NEEDS_REBUILD was added in 5.5.11.
-1708	WARN_OPTION_BELOW_LI	The value of '%s' should be no less than the value of '%s'	WARN_OPTION_BELOW_LIMIT was added in 5.5.12.
-1709	ER_INDEX_COLUMN_TOO_	Index column size too large. The maximum column size is %lu bytes.	ER_INDEX_COLUMN_TOO_LONG was added in 5.5.14.
-1710	ER_ERROR_IN_TRIGGER_	Trigger '%s' has an error in its body: '%s'	ER_ERROR_IN_TRIGGER_BODY was added in 5.5.15.
-1711	ER_ERROR_IN_UNKNOWN_	Unknown trigger has an error in its body: '%s'	ER_ERROR_IN_UNKNOWN_TRIGGER_BODY was added in 5.5.
-1712	ER_INDEX_CORRUPT	Index %s is corrupted	ER_INDEX_CORRUPT was added in 5.5.17.
-1713	ER_UNDO_RECORD_TOO_B	Undo log record is too big.	ER_UNDO_RECORD_TOO_BIG was added in 5.5.17.
-1714	ER_BINLOG_UNSAFE_INS	INSERT IGNORE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determ	ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT was added in
-1715	ER_BINLOG_UNSAFE_INS	INSERT... SELECT... ON DUPLICATE KEY UPDATE is unsafe because the order in which rows are retrieved	ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE was added in
-1716	ER_BINLOG_UNSAFE_REP	REPLACE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines w	ER_BINLOG_UNSAFE_REPLACE_SELECT was added in 5.5.18.
-1717	ER_BINLOG_UNSAFE_CRE	CREATE... IGNORE SELECT is unsafe because the order in which rows are retrieved by the SELECT determ	ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT was added ir
-1718	ER_BINLOG_UNSAFE_CRE	CREATE... REPLACE SELECT is unsafe because the order in which rows are retrieved by the SELECT deter	ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT was added
-1719	ER_BINLOG_UNSAFE_UPD	UPDATE IGNORE is unsafe because the order in which rows are updated determines which (if any) rows a	ER_BINLOG_UNSAFE_UPDATE_IGNORE was added in 5.5.18.
-1720	ER_PLUGIN_NO_UNINSTA	Plugin '%s' is marked as not dynamically uninstallable. You have to stop the server to uninstall it.	ER_PLUGIN_NO_UNINSTALL was added in 5.5.16.
-1721	ER_PLUGIN_NO_INSTALL	Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.	ER_PLUGIN_NO_INSTALL was added in 5.5.16.
-1722	ER_BINLOG_UNSAFE_WRI	Statements writing to a table with an auto-increment column after selecting from another table are u	ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT was added in
-1723	ER_BINLOG_UNSAFE_CRE	CREATE TABLE... SELECT... on a table with an auto-increment column is unsafe because the order in wh	ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC was added
-1724	ER_BINLOG_UNSAFE_INS	INSERT... ON DUPLICATE KEY UPDATE on a table with more than one UNIQUE KEY is unsafe	ER_BINLOG_UNSAFE_INSERT_TWO_KEYS was added in 5.5.24
-1725	ER_TABLE_IN_FK_CHECK	Table is being used in foreign key check.	ER_TABLE_IN_FK_CHECK was added in 5.5.24.
-1726	ER_UNSUPPORTED_ENGIN	Storage engine '%s' does not support system tables. [%s.%s]	ER_UNSUPPORTED_ENGINE was added in 5.5.24.
-1727	ER_BINLOG_UNSAFE_AUT	INSERT into autoincrement field which is not the first part in the composed primary key is unsafe.	
-2000	CR_UNKNOWN_ERROR	Unknown MySQL error	
-2001	CR_SOCKET_CREATE_ERR	Can't create UNIX socket, '%d'	
-2002	CR_CONNECTION_ERROR	Can't connect to local MySQL server through socket '%s', '%d'	
-2003	CR_CONN_HOST_ERROR	Can't connect to MySQL server on '%s', '%d'	
-2004	CR_IPSOCK_ERROR	Can't create TCP/IP socket, '%d'	
-2005	CR_UNKNOWN_HOST	Unknown MySQL server host '%s', '%d'	
-2006	CR_SERVER_GONE_ERROR	MySQL server has gone away	
-2007	CR_VERSION_ERROR	Protocol mismatch; server version = %d, client	

		version = %d	
-2008	CR_OUT_OF_MEMORY	MySQL client ran out of memory	
-2009	CR_WRONG_HOST_INFO	Wrong host info	
-2010	CR_LOCALHOST_CONNECT	Localhost via UNIX socket	
-2011	CR_TCP_CONNECTION	%s via TCP/IP	
-2012	CR_SERVER_HANDSHAKE	Error in server handshake	
-2013	CR_SERVER_LOST	Lost connection to MySQL server during query	
-2014	CR_COMMANDS_OUT_OF_SYNC	Commands out of sync; you can't run this command now	
-2015	CR_NAMEDPIPE_CONNECT	Named pipe: %s	
-2016	CR_NAMEDPIPEWAIT_ERR	Can't wait for named pipe to host: %s pipe: %s,%lu'	
-2017	CR_NAMEDPIPEOPEN_ERR	Can't open named pipe to host: %s pipe: %s,%lu'	
-2018	CR_NAMEDPIPESETSTATE	Can't set state of named pipe to host: %s pipe: %s,%lu'	
-2019	CR_CANT_READ_CHARSET	Can't initialize character set %s,'path: %s'	
-2020	CR_NET_PACKET_TOO_LARGE	Got packet bigger than 'max_allowed_packet' bytes	
-2021	CR_EMBEDDED_CONNECT	Embedded server	
-2022	CR_PROBE_SLAVE_STATUS	Error on SHOW SLAVE STATUS:	
-2023	CR_PROBE_SLAVE_HOSTS	Error on SHOW SLAVE HOSTS:	
-2024	CR_PROBE_SLAVE_CONNECTION	Error connecting to slave:	
-2025	CR_PROBE_MASTER_CONNECTION	Error connecting to master:	
-2026	CR_SSL_CONNECTION_ERROR	SSL connection error: %s	
-2027	CR_MALFORMED_PACKET	Malformed packet	
-2028	CR_WRONG_LICENSE	This client library is licensed only for use with MySQL servers having '%s' license	
-2029	CR_NULL_POINTER	Invalid use of null pointer	
-2030	CR_NO_PREPARE_STMT	Statement not prepared	
-2031	CR_PARAMS_NOT_BOUND	No data supplied for parameters in prepared statement	
-2032	CR_DATA_TRUNCATED	Data truncated	
-2033	CR_NO_PARAMETERS_EXISTS	No parameters exist in the statement	
-2034	CR_INVALID_PARAMETER	Invalid parameter number	
-2035	CR_INVALID_BUFFER_USAGE	Can't send long data for non-string/non-binary data types,'parameter: %d'	
-2036	CR_UNSUPPORTED_PARAM	Using unsupported buffer type: %d,'parameter: %d'	
-2037	CR_SHARED_MEMORY_CONNECT	Shared memory: %s	
-2038	CR_SHARED_MEMORY_CONNECT	Can't open shared memory; client could not create request event,%lu'	
-2039	CR_SHARED_MEMORY_CONNECT	Can't open shared memory; no answer event received from server,%lu'	
-2040	CR_SHARED_MEMORY_CONNECT	Can't open shared memory; server could not allocate file mapping,%lu'	
-2041	CR_SHARED_MEMORY_CONNECT	Can't open shared memory; server could not get pointer to file mapping,%lu'	
-2042	CR_SHARED_MEMORY_FILE	Can't open shared memory; client could not allocate file mapping,%lu'	
-2043	CR_SHARED_MEMORY_MAP	Can't open shared memory; client could not get pointer to file mapping,%lu'	
-2044	CR_SHARED_MEMORY_EVENT	Can't open shared memory; client could not create %s event,%lu'	
-2045	CR_SHARED_MEMORY_CONNECT	Can't open shared memory; no answer from server,%lu'	
-2046	CR_SHARED_MEMORY_CONNECT	Can't open shared memory; cannot send request event to server,%lu'	
-2047	CR_CONN_UNKNOW_PROTOCOL	Wrong or unknown protocol	
-2048	CR_INVALID_CONN_HANDLE	Invalid connection handle	
-2049	CR_SECURE_AUTH	Connection using old,'pre-4.1.1' authentication protocol refused, client option 'secure_auth' enable	
-2050	CR_FETCH_CANCELED	Row retrieval was canceled by mysql_stmt_close() call	
-2051	CR_NO_DATA	Attempt to read column without prior row fetch	
-2052	CR_NO_STMT_METADATA	Prepared statement contains no metadata	
-2053	CR_NO_RESULT_SET	Attempt to read a row while there is no result set associated with the statement	
-2054	CR_NOT_IMPLEMENTED	This feature is not implemented yet	
-2055	CR_SERVER_LOST_EXTEN	Lost connection to MySQL server at '%s', system error: %d	
-2056	CR_STMT_CLOSED	Statement closed indirectly because of a	

		preceeding %s() call	
-2057	CR_NEW_STMT_METADATA	The number of columns in the result set differs from the number of bound buffers. You must reset the	
-2058	CR_ALREADY_CONNECTED	This handle is already connected. Use a separate handle for each connection.	
-2059	CR_AUTH_PLUGIN_CANNON	Authentication plugin '%s' cannot be loaded: %s	

Notify Error Codes

Notify			
Code	Alias	Error	Explanation
-3000	NOTIFY_IGNORED	Notification for this event is ignored	Notification for this event is ignored. This is most likely because the eventtype is not defined in the table # inno_system_picklist_event_types, because an event was published that sis not need any notification processing.
-3001	NOTIFY_DISABLED	Notification type is disabled	The Notification type exists but it is disabled.
-3002	NOTIFY_INCOMPLETE	Notification config is incomplete	The subject line, the message content or the notificant details are missing.
-3003	NOTIFY_NON_EXIST	Notification type indicated does not exist	The Notification type does not exist in the notification configuration.
-3004	NOTIFY_NO_MESSAGE	Notification config does not contain a message	
-3005	NOTIFY_NO_SUBJECT	Notification config does not contain a subject	
-3006	NOTIFY_NO_TEMPLATE	Notification config does not contain a template	
-3007	NOTIFY_NO_DICTIONARY	Notification's substitution tag dictionary does not exist	
-3008	NOTIFY_NO_GROUPMEMBE	No members in notificant groups found even though this event exclusively signals members in a group.	
-3009	NOTIFY_UNSUPPORTED_M	This notification medium is not currently supported.	
-3010	NOTIFY_ENTITY	Entity does not exists	The indicated Entity Id in the event does not exist in the substitution-tag data, as determined by the substitution-tag data dictionary.
-3011	NOTIFY_EVENT_NOT_NOTIFY	Event type is not for notification	Event type is not for notification

Login Error Codes

Login			
Code	Alias	Error	Explanation
-3100	LOGIN_GENERAL	General problem with Registration, Login, Password Recovery, Subscriptions	General problem with Registration, Login, Password Recovery, Subscriptions. Call an Exorcist.
-3101	LOGIN_INPROCESS_FAIL	Registration process failed	Something went wrong while the user tried to register. See other error messages in log for further information.
-3102	LOGIN_DOMAIN_BAN	Registration Banned Domain	User tried to register with email from a banned domain. If the user seems plausible, contact the user and ask for a corporate email address. See list of blacklisted domains in table mtchi_inno_login_blacklisted_domains.
-3103	LOGIN_PLAN_NONEXIST	Subscription Plan does not exist	A user/organization tried to subscribe to a subscription plan that does not exist or has been deactivated.
-3104	LOGIN_PLAN_EXISTS	A different subscription plan for this organization already exists	On creation of a new subscription for a user in an organization, it was discovered that a different subscription plan for this organization already exists.
-3105	LOGIN_SUBSCRIPTION_ID_INVALID	Subscription Id does not belong to an existing Organization	Subscription that is being extended or upgraded does not actually exist at all.
-3106	LOGIN_USER_DETAILS	Insufficient details provided.	Insufficient details provided. If this is to create a user then at a minimum a full name and email is required.
-3107	LOGIN_USER_NONEXIST	User does not exist	This indicated user does not exist. The user may previously have been removed.
-3108	LOGIN_USER_EXISTS	User already exists	On creating a new user, this user has been found to already exist. Check if the user is not suspended before proceeding. It is also likely that the user has changed companies and somehow managed to keep the same email address - which is why we prefer corporate email address in preference to GMAIL and YAHOO and other personal email addresses.
-3109	LOGIN_SUBSCRIPTION_NONEXIST	No subscription exists for this user or organization	No subscription exists for this user or organization
-3110	LOGIN_SUBSCRIPTION_EXIST	Subscription already exists	A Subscription already exists for the user and the organization.
-3111	LOGIN_SUBSCRIPTION_PLAN_INVALID	Subscription plan invalid	A subscription plan with these attributes is invalid. Are all the required attributes present?
-3112	LOGIN_SUBSCRIPTION_PLAN_EXPIRED	Existing Subscription plan expired	Existing Subscription plan expired
-3113	LOGIN_SUBSCRIPTION_FAIL	Failed to create a subscription	Failed to create a subscription
-3114	LOGIN_SUBSCRIPTION_DATES	Subscription begin date must be before end date	Subscription begin date must be before end date
-3115	LOGIN_SUBSCRIPTION_DETAILS	Insufficient details to create subscription	Insufficient details to create subscription
-3116	LOGIN_SUBSCRIPTION_INSERT	Failed to insert into the the subscription table	Failed to insert into the the subscription table
-3117	LOGIN_GROUPID_INVALID	User-Group Id associated with this subscription plan is invalid.	User-Group Id associated with this subscription plan is invalid.
-3118	LOGIN_SUBSCRIPTION_SUPERCEDED	Subscription has since been superseded by another subscription	Subscription has since been superseded by another subscription
-3119	LOGIN_SUSPENDED	User is already suspended	User is already suspended
-3120	LOGIN_NOT_SUSPENDED	User is not suspended	User is not suspended
-3121	LOGIN_CANCELLED	User is cancelled	User is cancelled
-3122	LOGIN_NOT_CANCELLED	User is not cancelled	User is not cancelled
-3123	LOGIN_TRASHED	User is already trashed	User is already trashed
-3124	LOGIN_NOT_TRASHED	User is not trashed	User is not trashed
-3125	LOGIN_SUBSCRIPTION_ACTIVE	Subscription plans is still active	The subscription plans is still active.
-3126	LOGIN_SUBSCRIPTION_PLAN_NOSELECT	This subscription plan is not	This subscription plan is not selectable, either because the use-case can not select it, or because it is disabled.

		selectable	
-3127	LOGIN_NOT_REJECTED	User is not rejected	User is not rejected
-3128	LOGIN_CONFIRMED	User already confirmed email	User already confirmed email
-3129	LOGIN_NOT_CONFIRMED	User has not confirmed their email yet.	User has not confirmed email yet
-3130	LOGIN_ACTIVATIONKEY	Activation Key does not exist	Activation Key does not exist
-3131	LOGIN_ALREADY_APPROVED	User has already been approved	User has already been approved
-3132	LOGIN_USER_REJETCED	User is already rejected	User is already rejected
-3133	LOGIN_SUBSCRIPTION_RESTARTED	Subscription has alsready been restarted	Subscription has alsready been restarted
-3134	LOGIN_GROUP	User group does not exist	User group does not exist

Organization Error Codes

Organization			
Code	Alias	Error	Explanation
-3200	ORG_GENERAL	General error with Organization	General error with Organization
-3201	ORG_ID_NONEXIST	Organization for given ID not found	Organization for given ID not found
-3202	ORG_NAME_NONEXIST	Organization for given name not found	Organization for given name not found
-3203	ORG_USER_ID_NONEXIST	Organization for given User ID not found	Organization for given User ID not found
-3204	ORG_EXISTS	An organization of this name already exists	An organization of this name and other matching details already exists
-3205	ORG_MULTIPLE_SIMILAR_NAMES	Organization search for name has more than one match	Organization search for name has more than one match
-3206	ORG_DETAILS	Insufficient details to find organization	Insufficient details to find organization
-3207	ORG_USER_NONCONTAIN	User Id does not belong in this organization	User Id does not belong in this organization
-3208	ORG_NO_USERS	This organization contains no valid members	This organization contains no valid members. This will prevent amongst other the creation of a subscription for the organization, since a primary member in the organization need to be accountable for the subscription.
-3209	ORG_NO_SUBSCRIPTION	Organization does not have a subscription	Organization does not have a subscription
-3210	ORG_TYPE	Organization Type does not exist	Organization Type does not exist
-3211	ORG_LOGO_FILE	Invalid Organization Logo file	An invalid Organization Logo file was provided. It may only be a .png file and should be in lower case.
-3212	ORG_COLOURS	Organizations Corporate Colours are not defined	Organizations Corporate Colours are not defined

Geospatial Error Codes

Geospatial			
Code	Alias	Error	Explanation
-3300	GEO_GENERAL	General Geospatial Error	General Geospatial Error
-3301	GEO_REGION_NONEXIST	Could not determine geographical region	Could not determine geographical region
-3302	GEO_COUNTRY_NONEXIST	Could not determine country	Could not determine country

Innovation Error Codes

Innovation			
Code	Alias	Error	Explanation
-3400	INNO_GENERAL	General Error in the Innovation namespace	General Error in the Innovation namespace
-3401	INNO_ENTRY_INCOMPLETE	Innovation Entry incomplete	Innovation Entry incomplete. Some critical data fields are missing.
-3402	INNO_USER_NOORG	User is not associated with this innovation	User is not associated with this innovation
-3403	INNO_NONEXIST	Innovation does not exist	Innovation does not exist
-3404	INNO_STATE	Innovation state is invalid	The requested state for this innovation is invalid, probably because the state does not exist.

Challenge Error Codes

Challenge			
Code	Alias	Error	Explanation
-3500	CHALLENGE_GENERAL	General Challenge Error	General Challenge Error
-3501	CHALLENGE_ENTRY_INCOMPLETE	Entry incomplete	Entry incomplete
-3502	CHALLENGE_ENTRY_MULTICAT	No multiple categories allowed	An innovation can not be entered into multiple entry categories.
-3503	CHALLENGE_ENTRY_GROUP	User does not belong to the correct group	The user or assigned actor does not belong to one of the user groups that are allowed to enter a challenge.
-3504	CHALLENGE_CATEGORY_UNKNOWN	Challenge Category is unknown	An invalid Challenge Category Id was specified
-3505	CHALLENGE_EVENT_UNKNOWN	Challenge Event is unknown	Challenge Event is unknown
-3506	CHALLENGE_JUDGES_TOOFEW	Insufficient judges available	Insufficient judges available
-3507	CHALLENGE_INCOMPLETE	Challenge Event Incomplete	The configuration for the challenge Event Incomplete.
-3508	CHALLENGE_PHASE	Challenge phases ambiguity	Either the phase does not belong to the indicated challenge, a null was provided for the phase, the indicate phase Id simply does not exist, or the phase does exist but does have the required attributes to be used in the current context.
-3509	CHALLENGE_ENTRIES_NONE	No entries for this challenge event	No entries for this challenge event
-3510	CHALLENGE_QUORATE	Not quorate for scoring	Minimum quorum settings for this challenge have not been met.
-3512	CHALLENGE_ENTRY_ASSIGNED	Judge has entry assigned already	Judge has entry assigned already
-3513	CHALLENGE_ENOUGH_SCORESHEETS	Judge has enough entries assigned	Judge has enough entries assigned
-3514	CHALLENGE_NONSCORE_CATEGORY	Judge does not score this category	Judge does not score this category
-3515	CHALLENGE_CLOSED	Challenge is closed.	Challenge is closed. There are certain things that you can't do with a closed challenge, such as attempting to add a phase to it.
-3516	CHALLENGE_ARTICLE	Challenge Article does not exist	And Article Id referred to in the Challenge configuration does not exist.
-3517	CHALLENGE_ORGANIZATION	Organization for challenge does not exist	Organization for challenge does not exist
-3518	CHALLENGE_CATAGORY	Category Error	Insufficient or conflicting details for this category, or the category does not exist.
-3519	CHALLENGE_ACTOR_NOTEXIST	Actor User Id Error	The user specified to perform for this phase of a challege does not exist, or is disabled.
-3520	CHALLENGE_ACTOR_ASSIENGED	Actor already assigned	The user has already been assigned to this role in this phase
-3521	CHALLENGE_ACTOR_NOTEXIST	Actor does not exist	The challenge actor either does not exist or could not be created
-3522	CHALLENGE_ACTORROLE_NOTEXIST	Actor-Role does not exist	The role for this challenge actor either does not exist or could not be created
-3523	CHALLENGE_ENTRY_NOTEXIST	Challenge Entry does not exist	The selected challenge entry does not exist
-3524	CHALLENGE_ENTRY_DISQUALIFIED	This entry has been disqualified	This entry has been disqualified for whatever reasons.
-3525	CHALLENGE_ENTRY_EDIT	Insufficient user access to edit a challenge entry	You attempted to edit a challenge entry but you do not have suffucient user access for this.
-3526	CHALLENGE_EVENT_CLOSED	This Challenge Event is now closed	This Challenge Event is now closed
-3527	CHALLENGE_ENTRY_UNKNOWN	This Challenge Entry is unkown	This Challenge Entry could not be found.
-3528	CHALLENGE_TIMEZONE	Invalid UNIX Timezone	Invalid Timezone provided. See the UNIX timezones that we use in table mtchi_inno_geo_timezones, which are more than adequate to cover the world.
-3529	CHALLENGE_ENTRY_URL	Friendly URL to challenge entry is missing	Friendly URL to the challenge entry is missing

Event Error Codes

Event			
Code	Alias	Error	Explanation
-3600	EVENT_GENERAL	General Error in the Event Namespace	General Error in the Event Namespace
-3601	EVENT_INCOMPLETE	Entry incomplete	Entry incomplete
-3602	EVENT_TYPE	Unknown Event Type	Unknown Event Type
-3603	EVENT_INSERT	Failed to insert into event table	Failed to insert into event table
-3604	EVNET_DISABLED	Event type is disabled	Event type is disabled
-3605	EVENT_NOTIFYABLE	Event type is not notifiable	Event type is not notifiable

Config Error Codes

Config			
Code	Alias	Error	Explanation
-3700	CONFIG_GENERAL	General error with configuration	General error with configuration
-3701	CONFIG_PARAMETER	Parameter does not exist	Parameter does not exist
-3702	CONFIG_VALUE	Impossible value for parameter	Impossible value for parameter
-3703	CONFIG_GROUP	This is a grouping of parameters	This is a grouping of parameters
-3704	CONFIG_READONLY	This is a read-only parameter	This is a read-only parameter and can not be set

Content Error Codes

Content			
Code	Alias	Error	Explanation
-3800	CONTENT_GENERAL	General issue with site content handling	General issue with site content handling
-3801	CONTENT_ARTICLE	Invalid Article Provided	The supplied Article Id does not exist, or no article matching the given criteria could be found.
-3802	CONTENT_CATEGORY	Invalid Category Provided	The supplied article-category Id does not exist, or no article-category matching the given criteria could be found.
-3803	CONTENT_TITLE	Invalid Title	Invalid Title provided. Either it was null or too long.
-3804	CONTENT_INSERT	Could not add new content	Could not add new content
-3805	CONTENT_UPDATE	Could not update content	Could not update content
-3806	CONTENT_ACL	Access View Level does not exist	Access View Level does not exist

System Error Codes

System			
Code	Alias	Error	Explanation
-4000	SYSTEM_ERROR	General System Error	There was an as-yet unspecified System Error. See preceding and following error messages for more details.
-4001	SYSTEM_JOOMLA_CONTENT	Error in Joomla Content	The is an error in the Joomla Content: The HTML either does not parse or absolute paths have been used where they should not have been.
-4002	SYSTEM_PAGE_ACCESS	You do not have access to this page.	You need to be logged in and be assigned to a specific user group for access to this page.

How to refresh this documentation

As the Matchi system evolves, more error codes will get generated. To update the error code documentation, run the script below and paste the results in the Wiki editor.

```
set session group_concat_max_len = 1000000;
set @lastsubsystem:= '';
select concat(group_concat(wikitext separator ''),
              char(10),'|}',char(10) )
from ( select concat(if(@lastsubsystem=subsystem,
'',
concat(if(@lastsubsystem<>subsystem and @lastsubsystem<>'',
concat('}|}',char(10)),
''),
'==',subsystem,' Error Codes ==',char(10),
'|{ style="text-align:left;" class="wikitable"',char(10),
'|-',char(10),
'| colspan="4" style="font-weight: bold; font-size: 18px; text-align:left; background-color:orange;" | ',subsystem,char(10),
'|-',char(10),
'| Code',char(10),
'| Alias',char(10),
'| Error',char(10),
'| Explanation',char(10))
),
'|-',char(10),
'| ',id,'|'|',alias,'|'|',item_en_gb,'|'|',ifnull(help_en_gb,''),char(10)
) as wikitext,
(select @lastsubsystem:=subsystem)
from mtchi_inno_system_picklist_error_codes
order by display_order_id asc ) a;
```

Retrieved from "http://wiki.matchi.info/index.php?title=Error_Architecture&oldid=1752"

Category: Pages with syntax highlighting errors

- This page was last modified on 31 January 2017, at 22:47.
- Content is available under Creative Commons Attribution unless otherwise noted.