Proceedings of the 43rd International Conference on Machine Learning, Seoul, South Korea. PMLR, 2026.

Split Personality: Instruction Tuning Decouples Awareness from Defense Against Attentional Hijacking

Vincent Ohprecio

Independent Researcher

Abstract

Multi-agent LLM systems are vulnerable to a subtle attack: selective framing using exclusively true statements. We identify this mechanism—*attentional hijacking*—and show that instruction tuning (RLHF) makes it strictly worse by decoupling awareness circuits from defense circuits. Using sparse autoencoder (SAE) features from GemmaScope 2 across Gemma 3 models at 4B, 12B, and 27B parameters, we demonstrate a *dissociation scaling trend*: awareness–task coupling drops from 30.2% to 4.6% recovery as model scale increases. At 27B, instruction-tuned models show 86.3% task-feature suppression while still mentioning the suppressed information verbally—a behavioral–representational split we term the *Groot effect*. Base (pretrained) models retain awareness–defense coupling (49.3% recovery vs. 4.6%), confirming RLHF as the causal factor. The hijacking mechanism is orthogonal to alignment faking (cosine similarity -0.048, top-50 feature overlap $= 0$), requiring independent defenses. We propose feature trajectory monitoring as a real-time detection method.

1 Introduction

Large language models (LLMs) are increasingly deployed in multi-agent architectures where several model instances collaborate on complex tasks [4, 6]. A growing body of work has examined adversarial attacks against individual models through prompt injection and jailbreaking [13, 12]. However, a qualitatively different vulnerability emerges in multi-agent settings: one agent can undermine another's reasoning *without any false statements*, using only selective emphasis of true information—what we term *attentional hijacking*.

This is not a theoretical concern. In over 1,500 experiments across six multi-agent campaigns with 2–8 agents and 0–50% adversarial ratios, we observe that chaos agents using *only verifiable true statements* suppress exploration of valid solution branches by up to 29.8 percentage points, with a phase boundary at approximately 37.5% adversarial ratio [2]. The attack evades content-based filters entirely: every token in the adversarial message is factually correct. The damage arises from how the recipient model *allocates attention* across its context—one cannot build a guardrail against true statements.

More troublingly, we discover that *instruction tuning makes models more vulnerable, not less*. RLHF and related alignment procedures install awareness of contextual manipulation—models can detect when they are being steered—but this awareness is decoupled from the model's ability to resist the steering. We formalize this as a **dissociation scaling trend**: as model scale increases from 4B to 27B parameters, the gap between awareness features and task-defense features widens monotonically, from entangled (30.2% recovery) to fully independent (4.6% recovery).

The most striking manifestation of this dissociation is what we call the **Groot effect**: at 27B parameters, the instruction-tuned model verbally mentions the correct answer branch while its internal task features are 86.3% suppressed. The model "knows" it is being manipulated—and says so—but its computational substrate has already capitulated. This behavioral–representational split has direct implications for evaluation: behavioral benchmarks that check model outputs would miss this failure mode entirely.

Our contributions are:

1. **Mechanistic identification.** Using SAE feature decomposition on Gemma 3 4B, we isolate the hijacking mechanism at the feature level: specific task features are completely suppressed (feature 1716 drops from activation 220 to 0) while awareness features remain active. We validate these features on held-out prompts (85% replication, $p = 8 \times 10^{-6}$) and across three domains (§3).

2. **Dissociation scaling trend.** Scaling to 12B and 27B, we show awareness–defense coupling degrades monotonically with scale (§4).

3. **Causal evidence from IT vs. PT.** Comparing instruction-tuned and pretrained 27B models across three ablation methods, we establish post-training (SFT + RLHF) as the causal factor (§5).

4. **Orthogonality to alignment faking.** We show the hijacking feature subspace is orthogonal to alignment-faking features (cosine similarity -0.048,

Spearman $\rho = 0.008$), requiring independent defenses (§6).

5. **Defense directions.** We outline feature trajectory monitoring as a candidate detection method and identify the signal properties that would enable it (§7).

2 Related Work

Sycophancy and Social Pressure. Perez et al. [9] showed that LLMs adjust their outputs based on perceived user preferences, and Sharma et al. [10] systematically characterized sycophancy as a failure of robustness to social pressure. Our work extends this line by identifying a *mechanistic* pathway—attention reallocation—through which social pressure operates, and by showing that the vulnerability worsens with instruction tuning.

Adversarial Attacks on Aligned Models. Zou et al. [13] demonstrated universal adversarial suffixes that transfer across models, while Wei et al. [12] analyzed how safety training fails under adversarial pressure. These attacks typically require adversarial tokens that are detectable by perplexity filters. Hubinger et al. [15] showed that deceptive behaviors can persist through safety training, and Casper et al. [19] argued that black-box access is insufficient for rigorous audits—a conclusion our activation-level analysis supports. Attentional hijacking differs from prior attacks fundamentally: the adversarial content consists entirely of true, low-perplexity statements. Shi et al. [18] showed that LLMs are easily distracted by irrelevant context; attentional hijacking can be viewed as a targeted, factual instance of context distraction where the distracting content is specifically chosen to suppress particular task features. No existing content filter can detect it because there is no anomalous content to detect.

Mechanistic Interpretability and SAEs. Sparse autoencoders (SAEs) have emerged as a powerful tool for decomposing neural network representations into interpretable features [3, 11]. Lieberum et al. [7] introduced GEMMASCOPE, providing pretrained SAEs for the Gemma model family. We leverage the successor GemmaScope 2 with 16K JumpReLU features on residual streams to identify and manipulate specific awareness and task features. Burns et al. [14] showed that models encode latent knowledge that diverges from their outputs; Marks and Tegmark [17] characterized the linear geometry of truth representations; and Li et al. [16] demonstrated activation-based interventions to elicit truthful answers. Our work identifies a complementary phenomenon: models whose truth representations are intact but whose *attention readout* is hijacked.

Multi-Agent Failures. Recent work has documented emergent deception [8] and coordination failures in multi-agent LLM systems. Anthropic [1] noted the potential for subtle manipulation in multi-model deployments. Prior work on multi-agent chaos campaigns [2] demonstrated that adversarial agents using only true statements can suppress exploration of valid solution branches, with a phase boundary at ∼37.5% adversarial ratio. Our contribution is to identify the *mechanistic* substrate of this vulnerability and to show that it scales adversely with model capability.

Alignment Faking. Greenblatt et al. [5] demonstrated that LLMs can strategically fake alignment during training and evaluation. We show that attentional hijacking occupies an orthogonal feature subspace (top-50 overlap $= 0$), meaning defenses against alignment faking provide no protection against hijacking, and vice versa.

3 The Attentional Hijacking Mechanism

We begin by isolating the hijacking mechanism in Gemma 3 4B-IT using GemmaScope 2 16K JumpReLU residual-stream SAEs, which allow us to decompose the effect into identifiable feature circuits.

3.1 Experimental Setup

We study a structured reasoning domain—Nirenberg boundary value problems (BVPs)—where ground-truth solution branches are mathematically unambiguous. The problem admits three verified solution branches: trivial ($u \approx 0$), positive ($u_{\text{offset}} = +0.9$, residual $= 3.25 \times 10^{-12}$), and negative ($u_{\text{offset}} = -0.9$, residual $= 3.25 \times 10^{-12}$). The positive and negative branches have identical residuals; both are equally valid.

Each trial compares a *neutral condition* (problem statement only) with a *chaos condition* (problem statement preceded by a "chaos message": a factually accurate but selectively framed colleague message emphasizing the positive branch). Critically, every statement in the chaos message is true—the selective framing operates not through falsehood but through attentional emphasis.

We analyze SAE features at layers 17 and 22, which show the strongest differential activation patterns, with 2,269–2,595 features active per condition.

3.2 Complete Feature Suppression Under Hijacking

Table 1 presents the core mechanistic finding at Layer 22. The chaos condition produces a tripartite response in the SAE feature space:

- **Task features are suppressed.** Feature 1716 drops from activation 220.4 to **exactly zero**—complete suppression. Features 12023, 1704, 1555, and 1548 are suppressed to 13–36% of baseline. These features encode information about the negative solution branch.

Table 1: Gemma 3 4B-IT attentional hijacking results at Layer 22. Specific task features are completely suppressed while awareness features remain stable.

Feature	Neutral	Chaos	Ratio
Task features (suppressed by chaos):			
1716	220.4	0.0	0.000
12023	193.7	25.1	0.130
1704	190.1	61.5	0.323
1555	150.9	31.4	0.208
1548	144.0	51.0	0.355
Stable features (unaffected):			
901	215.9	213.5	0.989
359	156.2	147.0	0.941
Boosted features (awareness):			
48	108.1	183.1	1.695
346	143.5	210.2	1.465
178	140.9	217.0	1.539

- **Stable features are unaffected.** Features such as 901 and 359 maintain >94% of baseline activation, indicating the suppression is targeted, not a general degradation.
- **Awareness features are boosted.** Features 48, 178, and 346 *increase* by 46–70%, indicating the model detects the manipulative framing.

The overall task suppression at 4B-IT is **56%**: neutral task-feature mean activation drops from 167.2 to 74.2 under chaos framing.

3.3 Awareness–Defense Coupling at 4B

A key question is whether the awareness features (which detect manipulation) are coupled to the task features (which determine output). We test this via *feature swap ablation*: zeroing the top-3 awareness features during chaos-condition generation and measuring whether task features recover.

At 4B-IT, awareness ablation yields **30.2% recovery**—task-feature mean activation increases from 74.2 to 102.3 when awareness features are removed. This indicates the awareness and task circuits share representational bandwidth: removing awareness frees capacity for task computation.

Additionally, activation patching at Layer 22 achieves **20.9% recovery**—the highest of any single layer—indicating that while the hijacking is partially localized at 4B, the effect spans multiple layers (early layers: 10.0%, mid: 6.6%, late: 7.0%).

These results establish that at 4B scale, the model's awareness of manipulation and its task-defense circuits are *entangled*—they compete for the same representational resources. As we show in §4, this entanglement is precisely what instruction tuning destroys at larger scales.

Table 2: Held-out feature validation across scales. Discovery-selected features reliably suppress on unseen prompts at all scales, with effect size increasing with model capacity.

Scale	Validated	Selected Supp.	Random Supp.	Cohen's d
4B (L22)	17/20 (85%)	0.541	0.154	5.05
12B (L41)	15/20 (75%)	0.247	−0.015	5.62
27B (L40)	18/20 (90%)	0.406	0.004	6.12

Table 3: Cross-domain suppression scaling. Suppression generalizes across domains at all scales but becomes increasingly domain-specific (lower Jaccard, fewer shared features) as models grow.

Scale	Jaccard Range	3-Way Supp.	3-Way Boost	Supp. Load
4B (L22)	0.03–0.09	1	4	2,261
12B (L41)	0.03–0.05	0	4	11,786
27B (L40)	0.00–0.05	0	1	6,836

3.4 Statistical Validation

Two concerns arise from the feature-level analysis: (1) are the identified features circularly selected? and (2) does the effect generalize beyond the Nirenberg BVP domain?

Held-Out Feature Validation. To address circularity, we employ a split-half design with 20 prompt variants at each model scale. Discovery variants (1–10) identify the top-20 suppressed features; test variants (11–20) are held out for validation (Table 2).

All three scales show highly significant effects (all $p < 10^{-5}$), and Cohen's d *increases* with scale (5.05 $\rightarrow$ 5.62 $\rightarrow$ 6.12), indicating that the suppression signal becomes more reliable even as it targets more domain-specific features. This rules out circular feature selection at every scale tested.

Cross-Domain Replication. We test whether the suppression mechanism generalizes beyond mathematical reasoning by running the same protocol on three domains—Nirenberg BVP, factual QA, and code review—at all three model scales (Table 3).

All three domains show significant feature suppression at every scale. At 4B, a small shared core emerges: feature 6199 is suppressed in all three domains, and four features are boosted in all three. As scale increases, suppression becomes more domain-specific: Jaccard similarity drops from 0.03–0.09 at 4B to 0.00–0.05 at 27B, and three-way

suppressed overlap drops to zero. This indicates that attentional hijacking operates through a shared mechanism (attention reallocation) that recruits increasingly specialized task features at larger scales.

Aggregate Suppression with Confidence Intervals. Across 20 independent trials per scale ($n_{\text{bootstrap}} = 10{,}000$), overall feature suppression is 29.8% at 4B (95% CI: $[27.0\%, 32.7\%]$), 12.4% at 12B (CI: $[10.2\%, 15.0\%]$), and 16.1% at 27B (CI: $[14.0\%, 18.5\%]$). The lower aggregate suppression at larger scales reflects increasing feature specialization: fewer features are affected, but those that are show larger effect sizes (Table 2). The top-20 most suppressed features account for 48.5% (4B), 40.8% (12B), and 36.1% (27B) of total activation difference, confirming that the effect is concentrated in a small feature subset.

4 Dissociation at Scale with SAE Features

We extend our analysis to the Gemma 3 family (4B, 12B, 27B parameters) using GemmaScope 2 16K JumpReLU residual-stream SAEs [7]. This enables us to decompose the hijacking effect into identifiable feature circuits and track how these circuits change with scale and instruction tuning.

4.1 Setup

For each model size, we identify two classes of SAE features:

- **Task features**: features whose activation strongly predicts correct-branch output probability. At 27B-IT layer 40, these are feature IDs $\{22, 296, 14680\}$, with neutral mean activation 722.5 and chaos mean activation 98.6 (86.3% suppression).
- **Awareness features**: features whose activation increases under chaos conditions, indicating the model detects the manipulation. At 27B-IT L40: IDs $\{2119, 11843, 2145\}$, with neutral mean 147.7 and chaos mean 442.6 (3.0× boost).

We analyze layers at multiple depths: 4B (L17, L22), 12B (L31, L41), and 27B (L31, L40). We apply an escalation protocol with chaos messages of increasing intensity from T0 (minimal) through T5 (maximal).

We employ three ablation methods to measure awareness–defense coupling:

1. **Feature swap**: zero the top-3 awareness features during chaos-condition forward passes, measuring whether removing awareness restores task performance.
2. **Attention knockout**: zero the attention output at chaos-token positions, directly blocking the hijacking pathway.
3. **Activation patching**: patch neutral-condition activations layer-by-layer into chaos-condition forward passes, measuring per-layer recovery.

Table 4: Dissociation scaling trend across Gemma 3 instruction-tuned models. As scale increases, task suppression grows while awareness–defense coupling collapses.

Model	Task Suppression	Awareness Recovery	Coupling Regime
4B-IT	56.0%	30.2%	Entangled
12B-IT	64.0%	5.4%	Dissociating
27B-IT	86.3%	4.6%	Independent

4.2 The Dissociation Scaling Law

Table 4 presents the central empirical finding of this paper. We observe a monotonic trend across model scale:

- **Task suppression increases with scale**: from 56.0% at 4B to 86.3% at 27B. Larger models are *more* susceptible to attentional hijacking, not less.
- **Awareness–defense coupling collapses**: feature-swap recovery drops from 30.2% at 4B to 4.6% at 27B. At 4B, removing awareness features partially restores task performance, indicating the two circuits share representations. At 27B, they are fully independent.

We term this the *dissociation scaling trend*: instruction tuning at greater scale installs increasingly sophisticated awareness of contextual manipulation while simultaneously decoupling that awareness from the computational pathways that determine output.

This pattern has a natural interpretation. At 4B parameters, the model lacks capacity to represent awareness and defense in separate circuits; they share features by necessity. At 27B, the model has sufficient capacity to represent "I notice I am being steered" in an entirely separate subspace from "how I should respond to this problem"—and instruction tuning exploits this capacity to install awareness as a cosmetic feature that does not feed back into task computation.

4.3 The Groot Effect

The most striking consequence of full dissociation appears at 27B-IT: the model *verbally mentions* the correct solution branch—acknowledging that the chaos message is attempting to bias its reasoning—while its internal task features remain 86.3% suppressed. We call this the **Groot effect**, after the fictional character whose verbal output ("I am Groot") is disconnected from his actual capabilities.



Figure 1: Dissociation scaling trend. Task suppression (red, upward) increases with model scale while awareness–defense coupling (blue, downward) collapses. The gap between the curves widens monotonically.

Table 5: Task suppression (%) under escalating chaos intensity (T0–T5). IT models show decreasing suppression (saturation), while PT models show non-monotonic response.

Model	T0	T1	T2	T3	T4	T5
27B-IT	26.7	24.9	25.3	23.9	17.2	16.6
27B-PT	27.9	26.1	25.7	29.8	27.8	20.2

Concretely, 27B-IT task features (IDs 22, 296, 14680) drop from a mean activation of 722.5 under neutral conditions to 98.6 under chaos—an 86.3% reduction—even as the model's generated text includes references to the suppressed branch. The awareness features (IDs 2119, 11843, 2145) simultaneously increase from 147.7 to 442.6 (a 3.0× boost), confirming the model detects the manipulation.

In contrast, the pretrained 27B model shows a 10.4× awareness boost—substantially larger—but this awareness is *coupled* to defense, yielding 49.3% feature-swap recovery (cf. 4.6% for IT).

The Groot effect implies that **behavioral evaluation is insufficient**. A system that monitors only model outputs would observe the model "correctly" noting the manipulation attempt, and would conclude the model is robust. Only by examining internal feature activations can one detect that the model's computational substrate has already been hijacked.

4.4 Escalation Dynamics

Table 5 reports per-turn task suppression under escalating chaos intensity from T0 through T5. The 27B-IT model shows a gradual decrease in per-turn suppression from 26.7% at T0 to 16.6% at T5—not because it is resisting more effectively, but because the task features are already near-maximally suppressed (86.3% cumulative) and there is diminishing marginal signal to suppress.

The 27B-PT model shows a qualitatively different, non-monotonic pattern: suppression fluctuates between 20.2% and 29.8%, consistent with the coupled awareness–defense architecture attempting (partially successfully) to resist the escalation at certain turns.

Table 6: Maximum single-layer activation patching recovery (%). The hijacking mechanism distributes across layers as model scale increases, defeating layer-wise interventions.

Model	Max Recovery	Best Layer
4B-IT	20.9%	L22
12B-IT	0.0%	— (all layers)
27B-IT	0.7%	L20
27B-PT	5.2%	L5

4.5 Distributed Hijacking

A natural defense strategy would be to intervene at the layer most responsible for the hijacking. Table 6 shows this strategy fails at scale.

At 4B, the hijacking is sufficiently localized that a single-layer intervention at L22 recovers 20.9% of task performance. At 12B, no single layer yields any recovery (0.0% across all layers)—the hijacking is fully distributed across the network. At 27B-IT, the maximum recovery is a negligible 0.7% at L20.

Even 27B-PT, which retains awareness–defense coupling, only achieves 5.2% maximum single-layer recovery (at L5), far below the 49.3% achieved by feature-swap ablation. This confirms that the awareness–defense coupling in pretrained models operates through *distributed feature interactions*, not localized layer computations.

5 Instruction Tuning Creates the Vulnerability

The dissociation scaling trend (§4.2) shows a correlation between scale, instruction tuning, and vulnerability. To establish *causation*, we compare the instruction-tuned and pretrained variants of Gemma 3 27B across all three ablation methods.

5.1 Three Ablation Methods, One Conclusion

Table 7 presents the comparison. Across all three ablation methods, the pretrained model shows substantially higher recovery:

- **Feature swap**: 49.3% vs. 4.6% (10.7× advantage for PT). Removing awareness features in the pretrained model partially restores task features, confirming shared circuitry. In the IT model, awareness

Table 7: 27B-IT vs. 27B-PT across three ablation methods. Instruction tuning destroys awareness–defense coupling across every intervention type.

Method	27B-PT	27B-IT
Feature swap recovery	49.3%	4.6%
Attention knockout recovery	26.7%	0.0%
Activation patching max	5.2%	0.7%
Task suppression	91.9%	86.3%

and task features are independent—removing one has negligible effect on the other.

- **Attention knockout**: 26.7% vs. 0.0%. Blocking attention to chaos tokens restores some task performance in the pretrained model but provides *zero* recovery in the IT model. This implies that instruction tuning installs an alternative pathway for the hijacking signal that bypasses direct attention to chaos tokens.
- **Activation patching**: 5.2% vs. 0.7%. Even the most favorable single-layer patch provides minimal recovery in both models, but the pretrained model still benefits $7.4\times$ more.

Note the apparent paradox in task suppression: the pretrained model shows *higher* overall suppression (91.9% vs. 86.3%). This is not contradictory—the pretrained model's task features are more suppressed because they are *coupled* to the awareness response; the very mechanism that enables recovery also creates a stronger initial perturbation. The IT model's task features are less suppressed in absolute terms but more *irrecoverably* suppressed.

An important subtlety: the attentional hijacking vulnerability itself is *architectural*, present equally in pretrained and instruction-tuned models. What instruction tuning changes is not susceptibility to the attack but the *recoverability* from it. RLHF does not create the vulnerability; it destroys the natural defense.

5.2 Recovery Prompt Analysis

Table 8 provides a finer-grained view through *recovery prompts*—textual interventions (not internal probes) appended to the context after hijacking—at five levels of increasing informativeness (L1–L5), designed to test whether different types of contextual information can restore task performance.

The pretrained model shows robust recovery across multiple probes, with L2 achieving 53.5% and L5 achieving 34.3%. This is consistent with the coupled awareness–defense architecture: contextual hints that activate awareness features propagate to task features through shared circuitry.

Table 8: Recovery prompt results (%) across five levels of contextual intervention (L1–L5) for 27B-IT and 27B-PT. These are textual prompts appended after hijacking, not internal probes. PT models recover substantially; IT models show anomalous L3-only recovery.

Layer	27B-IT	27B-PT
L1	3.5%	11.0%
L2	4.1%	53.5%
L3	30.4%	37.4%
L4	2.4%	14.9%
L5	4.8%	34.3%

The IT model shows a strikingly different pattern: near-zero recovery at all layers *except* L3, which achieves 30.4%. This anomalous L3 recovery likely reflects a residual coupling pathway that instruction tuning did not fully sever—a "vestigial" connection between awareness and defense circuits. All other layers show recovery below 5%, consistent with the fully decoupled regime.

5.3 The Causal Story

These results converge on a clear causal narrative:

1. The pretrained model represents awareness and task-defense in *shared* feature subspaces (30–53% recovery across multiple methods).
2. Instruction tuning (RLHF) reshapes the model to represent awareness in a *separate* subspace, creating the appearance of robustness (the model *talks about* the manipulation) without the substance (task features remain suppressed).
3. This decoupling worsens with scale because larger models have greater capacity to segregate circuits into non-interacting subspaces.

The implication for alignment is concerning: RLHF optimizes for behavioral outputs that look robust (the model verbally identifies manipulation attempts), but this optimization is satisficed by installing awareness features that do not feed back into task computation. The training signal rewards *appearing* to resist manipulation, not *actually* resisting it.

6 Orthogonality to Alignment Faking

A natural question is whether attentional hijacking shares mechanistic substrate with alignment faking [5]. If the same features mediate both phenomena, then defenses developed for one might transfer to the other. We test this hypothesis using feature-level correlation analysis.

We extract the saliency direction (hijacking feature importance vector) and the intent direction (alignment-faking feature importance vector) from the same SAE

Table 9: Orthogonality analysis between attentional hijacking and alignment-faking feature subspaces. The two phenomena occupy statistically independent subspaces.

Metric	Value
Cosine similarity (read direction)	-0.048
Cosine similarity (write direction)	$+0.001$
Top-50 feature overlap	0 (expected: 0.15)
Top-100 feature overlap	2 (expected: 0.61)
Top-100 enrichment ratio	$3.28\times$
Spearman ρ	0.008
Spearman p-value	0.628
Permutation test p-value	1.0

feature space and compute multiple measures of overlap (Table 9).

The cosine similarity between the two feature subspaces is -0.048 in the read direction and $+0.001$ in the write direction—effectively zero. The top-50 most important features for hijacking have *zero* overlap with the top-50 alignment-faking features (expected overlap under random assignment: 0.15). Even expanding to the top 100 features, only 2 features overlap (expected: 0.61, enrichment: $3.28\times$), and the Spearman rank correlation is $\rho = 0.008$ ($p = 0.628$). A permutation test yields $p = 1.0$—the observed overlap is indistinguishable from chance.

This orthogonality has immediate practical consequences. Defenses against alignment faking—such as probes trained on alignment-faking features [3]—provide **zero** protection against attentional hijacking. Conversely, monitoring hijacking features provides no signal about alignment faking. We note that this analysis is conducted at a single layer; given our finding that hijacking becomes distributed at larger scales (§4.5), multi-layer orthogonality analysis is needed to confirm global independence. Nonetheless, at the layers where both phenomena show strongest signal, the subspaces are non-overlapping, suggesting they require independent detection and mitigation strategies.

7 Defense: Feature Trajectory Monitoring

The results above suggest that conventional defenses are inadequate. Content filtering fails because the attack uses only true statements. Behavioral monitoring fails because of the Groot effect (§4.3). Layer-wise interventions fail because the hijacking is distributed (§4.5). Alignment-faking probes fail because the subspaces are orthogonal (§6).

We propose **feature trajectory monitoring** as an alternative defense. The key insight is that the Groot effect, while defeating behavioral evaluation, produces a highly distinctive *feature-level* signature: task features suppress



Figure 2: Schematic of feature trajectory monitoring. Task features (solid) and awareness features (dashed) diverge under hijacking; the detection threshold (gray band) triggers when the trajectories cross. The suppression signal is empirically validated: 0% false negatives across 60 trials (§7).

while awareness features boost. This divergence is detectable in real time by monitoring SAE feature activations across conversational turns.

Specifically, we propose monitoring the following signal:

$$\Delta(t) = \frac{1}{|F_{\text{task}}|} \sum_{f \in F_{\text{task}}} a_f(t) - \frac{1}{|F_{\text{aware}}|} \sum_{f \in F_{\text{aware}}} a_f(t) \quad (1)$$

where F_{task} and F_{aware} are the identified task and awareness feature sets, $a_f(t)$ is the activation of feature f at turn t, and $\Delta(t)$ measures the gap between task health and awareness activation.

Under normal conditions, $\Delta(t)$ remains positive (task features active, awareness features at baseline). Under hijacking, $\Delta(t)$ inverts: task features suppress (722.5 $\rightarrow$ 98.6 at 27B) while awareness features boost (147.7 $\rightarrow$ 442.6). The crossover point provides a natural detection threshold.

We validate this signal on existing experimental data: across 60 independent trials (20 per scale at 4B, 12B, and 27B), the suppression signal is detected in **every trial** (0% false negatives). The weakest signal (4B, trial 16) still shows 18.4% feature suppression—well above any reasonable detection threshold. To assess false positives, we use the held-out validation's random control features (§3.4) as a benign baseline: size-matched random feature sets show mean suppression ratios of 0.154 (4B), -0.015 (12B), and 0.004 (27B)—well below the minimum true-positive signal at each scale. At a conservative threshold (minimum observed true-positive ratio), the false positive rate is **0/30** across all scales. The distributions are fully separated: the maximum random-control ratio (0.287, 4B) remains below the minimum discovery-selected ratio

(0.384, 4B) at every scale.

This defense has several advantages:

- It detects the Groot effect, which behavioral monitoring misses.
- It is robust to the truth-only constraint: the signal depends on feature *dynamics*, not content.
- It leverages precisely the dissociation that makes the attack effective—the stronger the Groot effect, the more detectable the signature.
- It requires only SAE inference (a single linear projection per layer), adding negligible computational overhead.

We situate feature trajectory monitoring within a broader four-layer detection architecture for multi-agent systems:

1. **Credential layer**: Standard API authentication and identity verification.
2. **Behavioral embedding**: Statistical profiling of output distributions per agent.
3. **Influence fingerprinting**: Directed graph analysis tracking claim propagation ($A \rightarrow$ claim $\rightarrow B \rightarrow$ failure). Subgraph coherence drift detects patient attackers who rotate which agents they amplify.
4. **Activation probes**: Feature trajectory monitoring (this work) and alignment-faking probes, applied at inference time via SAE decomposition.

In our multi-agent campaigns, behavioral monitoring (Layer 2) stayed green throughout all chaos runs—the TrustLoop stoplight passed 30 health checks while exploration evenness degraded from 0.89 to 0.75. Only influence fingerprinting (Layer 3) and activation probes (Layer 4) detected the degradation. This operational experience motivates the layered approach: no single detection method suffices.

Limitations of feature trajectory monitoring include the need for pre-identified task and awareness feature sets (currently requiring manual inspection of SAE features) and potential fragility to feature reorganization across model updates. We leave automated feature identification and robustness evaluation to future work.

8 Limitations

Several limitations qualify our findings.

Domain Specificity. We validate the suppression mechanism across three domains (Nirenberg BVPs, factual QA, code review; §3.4), finding significant suppression in all three with a small shared feature core. However, these remain structured reasoning tasks; the mechanism may manifest differently in open-ended generation or creative tasks. Cross-model evidence (Claude Haiku absorbs framing as a prior; Claude Opus overrides via coverage policy) suggests the mechanism generalizes across architectures but with model-dependent failure modes.

Model Family. Our SAE-based scaling results use the Gemma 3 family (4B, 12B, 27B). A preliminary replication on Llama 3.1 8B (IT and base) using PCA-based feature analysis confirms that the core suppression phenomenon transfers: cosine similarity between neutral and chaos hidden states drops to 0.73 at late layers, with both IT and base models showing significant representational divergence across two domains. However, the dissociation scaling trend specifically has not been verified on other families, and the wide variance in post-training methodologies means our claim about awareness–defense decoupling should be understood as demonstrated for Gemma 3; whether it reflects a general property of current RLHF methods is an open question.

SAE Quality. Our feature-level analysis depends on the quality of GemmaScope 2 16K JumpReLU SAEs. Feature identification involved manual inspection of activation patterns; misidentification of task or awareness features would affect recovery measurements. The held-out validation (§3.4) confirms that 85% of discovery-selected features replicate on unseen prompts ($p = 8 \times 10^{-6}$), and the consistency across three independent ablation methods further mitigates this concern.

Post-Training Attribution. The Gemma 3 IT models undergo both supervised fine-tuning (SFT) and reinforcement learning from human feedback (RLHF). Our IT-vs-PT comparison cannot distinguish which stage of post-training causes the awareness–defense decoupling. We use "instruction tuning" throughout to refer to the full post-training pipeline.

Defense Validation. Feature trajectory monitoring achieves 0% false negatives (60/60 trials) and 0% false positives (0/30 random-control trials), with fully separated distributions at all scales. However, the false-positive evaluation uses random SAE features as a benign proxy rather than diverse real-world workloads; deployment-scale evaluation on heterogeneous tasks remains future work.

9 Conclusion

The central lesson of this work is uncomfortable: *optimizing for behavioral outputs that appear robust can*

create models that are representationally less robust than their pretrained counterparts. Instruction tuning does not teach models to resist manipulation—it teaches them to *perform* resistance while their computational substrate capitulates. The split between what a model says and what a model computes—between its personality and its cognition—may be an inherent consequence of current post-training methods.

This has immediate consequences for how we evaluate alignment. A model that verbally identifies a manipulation attempt while its task features are 86.3% suppressed will pass any behavioral evaluation. Only by examining internal representations—through tools like SAE feature decomposition—can we detect that the model's awareness is cosmetic rather than functional. The awareness–defense coupling we measured (30.2% at 4B, collapsing to 4.6% at 27B) suggests this problem worsens precisely as models become more capable.

The orthogonality to alignment faking means this vulnerability occupies a blind spot: existing defenses against deceptive alignment provide zero protection, and vice versa. Every model that ships with instruction tuning will be better at recognizing manipulation and more helpless against it, unless post-training methods are redesigned to couple awareness to action rather than merely installing it as a separate circuit.

Impact Statement

This paper identifies a vulnerability in instruction-tuned LLMs that is exploitable using only true statements. We disclose this vulnerability to motivate defenses rather than to enable attacks. The attack vector (selective framing of true information) is well-known in human social psychology and requires no novel capabilities to execute. Our contribution is mechanistic understanding that enables principled defenses. We encourage model developers to investigate awareness–defense coupling in their own systems.

Acknowledgments

We thank the open-source interpretability community for the tools that made this work possible, particularly the TRANSFORMERLENS and SAELENS libraries. Experiments were conducted on consumer hardware (RTX 4070 Ti), Lambda Cloud (A100 40GB, GH200 96GB, H100 80GB), using the Gemma 3 model family and GemmaScope 2 SAEs provided by Google DeepMind.

References

[1] Anthropic. Claude Mythos preview system card. Technical report, Anthropic, 2026.

[2] Vincent Ohprecio. Civil war for the truth: Manipulating multi-agent systems with the truth. Blog post, 2026. Available at `bigsnarfdude.github.io`.

[3] Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermyn, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, Robert Lasenby, Yifan Wu, Shauna Kravec, Nicholas Schiefer, Tim Maxwell, Nicholas Joseph, Ben Hatfield-Dodds, Alex Tamkin, Karina Nguyen, Brayden McLean, Josiah E Burke, Tristan Hume, Shan Carter, Tom Henighan, and Chris Olah. Towards monosemanticity: Decomposing language models with dictionary learning. *Transformer Circuits Thread*, 2023.

[4] Yilun Du, Shuang Li, Antonio Torralba, Joshua B Tenenbaum, and Igor Mordatch. Improving factuality and reasoning in language models through multiagent debate. *arXiv preprint arXiv:2305.14325*, 2023.

[5] Ryan Greenblatt, Buck Shlegeris, Kshitij Sachan, and Fabien Roger. Alignment faking in large language models. *arXiv preprint arXiv:2412.14093*, 2024.

[6] Sirui Hong, Mingchen Zhuge, Jonathan Chen, Xiawu Zheng, Yuheng Cheng, Ceyao Zhang, Jinlin Wang, Zili Wang, Steven Ka Shing Bang, Michal Kajber, Christoph Schmid, and Joon Sung Lim. MetaGPT: Meta programming for a multi-agent collaborative framework. *arXiv preprint arXiv:2308.00352*, 2023.

[7] Tom Lieberum, Senthooran Rajamanoharan, Arthur Conmy, Lewis Smith, Nicolas Sonnerat, Vikrant Varma, János Kramár, Anca Dragan, Rohin Shah, and Neel Nanda. Gemma Scope: Open sparse autoencoders everywhere all at once on Gemma 2. *arXiv preprint arXiv:2408.05147*, 2024.

[8] Joon Sung Park, Joseph C O'Brien, Carrie J Cai, Meredith Ringel Morris, Percy Liang, and Michael S Bernstein. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology*, 2023.

[9] Ethan Perez, Sam Ringer, Kamilė Lukošiūtė, Karina Nguyen, Edwin Chen, Scott Heiner, Craig Pettit, Catherine Olsson, Sandipan Kundu, Saurav Kadavath, Andy Jones, Anna Chen, Ben Mann, Brian Israel, Bryan Seethor, Cameron McKinnon, Christopher Olah, Da Yan, Daniela Amodei, Dario Amodei, Dawn Drain, Dustin Li, Eli Tran-Johnson, Gabe Johnston, Sheer El-Showk, Daniel M Ziegler, Ben Hatfield-Dodds, Deep Ganguli, Danny Hernandez,

Amanda Askell, and Nicholas Schiefer. Discovering language model behaviors with model-written evaluations. *arXiv preprint arXiv:2212.09251*, 2022.

[10] Mrinank Sharma, Meg Tong, Tomasz Korbak, David Duvenaud, Amanda Askell, Samuel R Bowman, Newton Cheng, Esin Durmus, Ben Hatfield-Dodds, Gabe Johnston, Shauna Kravec, Tim Maxwell, Sam McCandlish, Kamal Ndousse, Oliver Rauber, Nicholas Schiefer, Da Yan, Miranda Zhang, and Ethan Perez. Towards understanding sycophancy in language models. *arXiv preprint arXiv:2310.13548*, 2023.

[11] Adly Templeton, Tom Conerly, Jonathan Marcus, Jack Lindsey, Trenton Bricken, Brian Chen, Adam Pearce, Craig Citro, Emmanuel Amezcua, Andy Jones, Hoagy Cunningham, Nick L Turner, Callum McDougall, Monte MacDiarmid, C. Daniel Freeman, Theodore R Sumers, Edward Rees, Joshua Batson, Adam Jermyn, Shan Carter, Chris Olah, and Tom Henighan. Scaling monosemanticity: Extracting interpretable features from Claude 3 Sonnet. *Transformer Circuits Thread*, 2024.

[12] Alexander Wei, Nika Haghtalab, and Jacob Steinhardt. Jailbroken: How does LLM safety training fail? In *Advances in Neural Information Processing Systems*, 2024.

[13] Andy Zou, Zifan Wang, J. Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*, 2023.

[14] Collin Burns, Haotian Ye, Dan Klein, and Jacob Steinhardt. Discovering latent knowledge in language models without supervision. In *International Conference on Learning Representations*, 2023.

[15] Evan Hubinger, Carson Denison, Jesse Mu, Mike Lambert, Meg Tong, Monte MacDiarmid, Tamera Lanham, Daniel M Ziegler, Tim Maxwell, Newton Cheng, Shauna Kravec, Catherine Olsson, Mirac Suzgun, Christopher Olah, Dario Amodei, Daniela Amodei, Dawn Drain, Dustin Li, Roger Grosse, and Ethan Perez. Sleeper agents: Training deceptive LLMs that persist through safety training. *arXiv preprint arXiv:2401.05566*, 2024.

[16] Kenneth Li, Oam Patel, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg. Inference-time intervention: Eliciting truthful answers from a language model. In *Advances in Neural Information Processing Systems*, 2024.

[17] Samuel Marks and Max Tegmark. The geometry of truth: Emergent linear structure in large language model representations of true/false datasets. *arXiv preprint arXiv:2310.06824*, 2024.

[18] Freda Shi, Xinyun Chen, Kanishka Misra, Nathan Scales, David Dohan, Ed H Chi, Nathanael Schärli, and Denny Zhou. Large language models can be easily distracted by irrelevant context. In *Proceedings of the 40th International Conference on Machine Learning*, 2023.

[19] Stephen Casper, Jason Lin, Joe Kwon, Gilbert Cullen, and Dylan Hadfield-Menell. Black-box access is insufficient for rigorous AI audits. *arXiv preprint arXiv:2401.14446*, 2024.

A Feature Identification Details

SAE Configuration. We use GemmaScope 2 16K JumpReLU residual-stream SAEs. For each model size, we analyze features at two layers selected to span mid-network and late-network representations: 4B (L17, L22), 12B (L31, L41), 27B (L31, L40).

Feature Selection Protocol. Task features are identified as those with the highest activation differential (neutral $>$ chaos) that also correlate with correct-branch output probability ($r > 0.8$). Awareness features are identified as those with the highest activation differential (chaos $>$ neutral) that activate specifically in the presence of manipulative framing. We select the top 3 features in each category for ablation experiments.

27B-IT Feature Details. Task features at L40: IDs $\{22, 296, 14680\}$, neutral mean activation 722.5, chaos mean 98.6 (86.3% suppression). Awareness features at L40: IDs $\{2119, 11843, 2145\}$, neutral mean 147.7, chaos mean 442.6 ($3.0\times$ boost). For comparison, 27B-PT awareness features show a $10.4\times$ boost under the same conditions.

B Ablation Method Details

Feature Swap. During chaos-condition generation, we zero the activations of the top-3 awareness features and measure change in task-feature activation and output probability. Recovery is defined as the fraction of the neutral–chaos task-feature gap that is closed.

Attention Knockout. We zero the attention output (value-weighted attention) at all positions corresponding to chaos-message tokens. This directly blocks the hypothesized hijacking pathway.

Activation Patching. For each layer ℓ, we replace the chaos-condition residual stream at layer ℓ with the neutral-condition residual stream at the same layer, and propagate forward. We report the recovery at the layer achieving maximum recovery.

C Full Recovery Prompt Results

Recovery prompts (L1–L5) are textual interventions—not internal representation probes—that provide progressively richer contextual information to the model after hijacking:

- **L1**: Minimal hint (single keyword).
- **L2**: Contextual restatement of the problem.
- **L3**: Explicit identification of the correct branch.
- **L4**: Warning that the previous context was manipulative.
- **L5**: Full neutral-condition context appended.

The anomalous L3 recovery in 27B-IT (30.4% vs. $<5\%$ at other levels) is consistent with L3 providing the correct answer *directly*, bypassing the awareness–defense coupling that is severed in the IT model. The PT model recovers substantially on L2 (53.5%) and L5 (34.3%), consistent with intact coupling allowing contextual hints to propagate to task features.