



S.P.M College, Udantpuri

Bachelor Of Computer Application (BCA)

Part -1

– Hira Kumar

4. Increment/Decrement Operators (2)

- C allows two very useful operators not generally found in other computer languages.
- These are the Increment (++) and Decrement (--) operators. The operation ++ adds 1 to its operand, and -- subtracts 1.
- It is also called unary operator.
- Example:- Assume a=10; then-
 - ✓ a++ (post increment) = (10+1) = 11
 - ✓ ++a (pre increment) = (11+1) = 12
 - ✓ a-- (post decrement) = (12-1) = 11
 - ✓ --a (pre decrement) = (11-1) = 10

Solve

1. int a =7 , b =5, c= 10;
bool result = (a+b*c > 50);
2. int x = 5;
int y = ++x + x++ + --x;
3. int a =8, b=3;
bool r = ((a/b) * b ==a);
4. int a=3;
int b= a++ + ++a + a--;
5. int a = 6, b = 9, c =2;
bool result = (a*b/c <= b+c);
6. int d =10;
int e= d-- - --d + ++d + d++;
7. int a=2, b=3;
bool r = (a++ *b-- > --a + ++b);
8. int a =4, b=5;
bool r = (a++ + ++b > 10);
9. int a=3;
int b= a++ + ++a + a--;

```

    bool r= (b == 11);
10.    int x=5, y=6;
        bool new=(x++ *2 < --y +7);

```

Answer

1→ 1, 2→18, 3→0, 4→ 13, 5→0, 6→20, 7→1, 8→0, 9→0,
10→Error,(error solve answer→ 1)

```

#include<stdio.h>
#include<conio.h>
int main()
{
    int a=10;
    printf("value of a = %d\n",a);
    a++;
    printf("value of a = %d\n",a);
    a--a--;
    printf("value of a = %d",a);

    getch();
    return 0;
}

```

C:\Users\hira\Desktop\hello.exe

```

value of a = 10
value of a = 11
value of a = 9

```

Solve

- int a = 10, b=5, c=20;
cout << (a>b && c>a);
- int x =4;
cout << (x++ > 4 || ++x ==6);
- int a =0, b=5;
cout << !(a+b);
- int x=1, y=2;
cout << (++x && y++);
- int a=10, b=3;
cout << (a %b ==1);
- int x=0, y=5;
cout << (x++ || y++);
- int a=5, b=10, c=15;
- int main()
{
 int a = 21;
 int c ;
 c = a++;
 cout << c;
 return 0;
}

```
cout << (a+b>c && b++ <c);  
8. int x=5;  
cout << (--x && x--);
```

Answer

1→1, 2→1, 3→0, 4→1, 5→1, 6→ 1, 7→ 0, 8 → 1, 9 → 21

=====HIRA KUMAR=====