INSTRUMENT AIR
NOTE 2
CIL3 LOADED CARBON SCREEN
2000-F30-PID-PR-10017
65-4243-CON-PE10-280
TO KV30647 (NOTE 2)
TO KV30646 (NOTE 2)
LEACH SLURRY
2000-F30-PID-PR-10008
CARBON TRANSFER SLURRY
FROM 30-PP66
30-909-SC-PE10-160
2000-F30-PID-PR-10008
CARBON TRANSFER SLURRY
FROM 30-PP-65D
30-937-SC-PE10-160
2000-F30-PID-PR-10008
SLURRY
FROM 30-FD-61
30-609-FS-PE-400
2000-F30-PID-PR-10019
SLURRY
FROM 30-FD-68
30-950-FS-PE10-400
2000-F30-PID-PR-10019
SLURRY
FROM 30-TK-62G
4
(MECH)
2000-F30-PID-PR-10008
SIGNAL
2000-F30-PID-PR-10008
CYANIDE NOTE 8
30-910-SC-PE10-200
2000-F30-PID-PR-10008
30-4041-SC-PE10-200
CIL3 LOADED CARBON SCREEN
2000-F30-PID-PR-10017
SLURRY CARBON
SIGNAL
TO 30AV30620
2000-F30-PID-PR-10008
30-929-CN-SS-25
30-930-CN-SS-25
CYANIDE DOSING SKID
NOTE 6
FT 30622
FCV 30622
FIC 30622
TP 21
TP 04
TP 03
TP 32
TP 20
TP 31
25V311
NOTE 7
LAH 30623
LSH 30623
SP 22
TIP 2063
TIP 2095
TP 06
F30-PP-476
F30-PP-65A-1
AAH 30620B
AAL 30620A
AAL 30620B
AAH 30620A
AI 30620B
AIC 30620A
AI 30621
pH
AIT 30625
AIT 30620B
AIT 30620A
AIT 30621
IT 30625
AE 30620B
AE 30620A
AE 30621
CN
F30-SC-62A
F30-VL-61H
30-VL-61A
2000-F30-PID-PR-10008
30-VL-61A
2000-F30-PID-PR-10008
KV 30646
25V301
250V868.200
250V868.187
NOTE 5
30-170-CS-RL-100
100V868
150x100
100V401
30-AG-62A
30-TK-62A
250V868.198
30-167-CS-RL-100
SP 154
30-166-CS-RL-250
250x200
200x150
IT 30344
II 30344
30-168-CS-RL-200
30-927-CN-SS-25
CYANIDE
DRAIN TO 30-TK-62B
2000-F30-PID-PR-10008
30-928-CN-SS-25
CYANIDE
TO 30-TK-62G
2000-F30-PID-PR-10019
PROCESS WATER
NOTE 2
30-164-PW-XS2-25
25V301
OXYGEN
2000-F30-PID-PR-10012
30-162-OXY-SS-025
COMET SCOPE
FIC 30645
TI 30648
FI 30645
ZI 30645
PI 30649
TIT 30648
FIT 30645
FY 30645
ZT 30645
PIT 30649
TE 30648
30-165-OXY-SS-015
15V331.181
15V331
SP 157
PI 30805
PI 30801
PI 30803
15V731
15V868
REMOVABLE SPOOL (FLOWMETER)
250x200
30-169-CS-RL-100
SP 156
SP 155
MMS SCOPE
30-173-CS-RL-100
100V868

NOTES:
1. REFER TO STANDARD DRAWINGS FME-00-SP-402 FOR FLUSHING POINT, WASH DOWN CONNECTION AND PRESSURE GAUGE CONNECTION DETAILS.
2. CLIENT TO NOMINATE PROCESS WATER AND INSTRUMENT AIR TIE-IN POINTS ON SITE.
3. V868 IS FOR PROVISIONAL VALVE SPEC WEIR DELTA SERIES TYPE IS KNIFEGATE, Owner TO CONFIRM.
4. OXYGEN INJECTION SYSTEM RELOCATED TO TANK G.
5. BLANK FLANGES TO BE INSTALLED ON TANK NOZZLES
6. REFER TO DRAWINGS 30-P-1187 AND 30-P-1188 FOR DETAILS.
7. EXISTING CYANIDE LINES TO TANKS A & B DEMOLISHED. DOSING LINE REDIRECTED TO TANK G. OTHER EXISTING PIPELINES TO BE REPLACED.
8. REFER TO P&ID 2000-F71-PID-PR-10001 FOR EXISTING CYANIDE DOSING MANIFOLD

LEGEND
EXISTING
NEW
DEMOLISH

LEGEND
STAGE 1 - NEW
STAGE 1 - REMOVE
STAGE 1 - DECOMMISSIONED (OTHERS)
STAGE 2 - NEW
STAGE 2 - REMOVE
STAGE 2 - DECOMMISSIONED (OTHERS)

HS
I
SV
S
IA
ZAH
ZAL
ZSH
ZSL
KV
TYPICAL KV INSTRUMENT ARRANGEMENT WITH REMOTE SOLENOID

LEACH TANK AGITATOR
30-AG-62A
LEACH TANK
30-TK-62A
CIL3 TANK A CARBON RECOVERY PUMP
F30-PP-65A-1
CIL3 TANK A INTERTANK SCREEN
F30-SC-62A
CIL3 TANK A INTERTANK SCREEN DISCHARGE LAUNDER PIECE
F30-VL-61H
CIL3 TANK A LOADED CARBON RECOVERY PUMP
F30-PP-476

APPROVED FOR CONSTRUCTION