EQUIPMENT NAME:	**SAG Mill**
EQUIPMENT NUMBER:	**F13-MS-401**

Duty		scats recycle with crushing		1	0
Closed / Open Circuit		Open		1	0
Number of Units Required		1		1	0
Location		Outdoors		1	0
Cooling Water Temperature	°C	25	Lubrication System: 30 VSD: 38 Main motor: 36	3	0
Ore Properties - Design					
Ore Type		Gold ore, underground and open pit		1	0
Ore SG (typical)		2.9		1	0
Bulk density	t/m^3	1.9		1	0
Bond Ball Mill Work Index	kWh/t	11.5 – 15		1	0
Axb		38 – 48		1	0
SAG Mill Specific Energy - 50th Percentile	kWh/t	8.34		1	0
SAG Mill Specific Energy – 80th Percentile	kWh/t	8.9		1	0
Feed Properties					
SABC Mode					
Fresh Feed Rate - Nominal	t/h solids	2,016		1	0
Solids Concentration (typical)	% w/w	75		1	0
Slurry pH		5 – 8		1	0
Feed Size F100	mm	400		1	0
Feed Size F_{99}	mm	295		1	0
Feed Size F_{80}	mm	110 – 133		1	0
Circulating Load – Pebbles (Range)	t/h solids	400 – 610		1	0
Volumetric Capacity of Grates & Pulp Lifters	m^3/h	≥2,100		1	0
Selection					
Type		SAG Mill, Grate Discharge		1	0
Number of Drives		2		1	0
Manufacturer			FLSmidth	2	0
Model			Fuller-Traylor	2	0
Aspect Ratio – L:D		0.76 : 1		1	0
Diameter – Inside Shell	m (ft)	10.97 (36)		1	0
Mill Length – Flange to Flange	m	8.991		1	1
Mill Length – EGL Inside Liner	m (ft)	8.38 (27.5)		1	0
Mill Volume	m^3		824	2	0
Mill Speed – Range	% Nc	60 – 83 (Constant Power from 78 – 83) Owner needs to be able to run at 3 when liners are worn		1	0
Mill Speed – Range	rpm		7.76 – 10.74	2	0
Mill Speed – Nominal	% Nc	76 (from Consultant		1	0
Motor Power Required	kW	20,000 (from Consultant		1	0
Mill Charge – Nominal Pinion Power					
Grinding Media Size	mm	125		3	0
Ball Charge – Nominal	%v/v	10.5 (from Consultant		3	0
Total Charge – Nominal	%v/v	27 (from Consultant		3	0
Speed – Nominal	% Nc	76 (from Consultant		1	0
Nominal Pinion Power – Required	kW	16,634 (from Consultant (New liners)	Noted	3	0
Mill Charge – Maximum Pinion Power					

	Unit	Duty	Supplier / Comment	Notes	Rev
Ball Charge – Max Power	%v/v		15	2	0
Total Load – Max Power	%v/v	27	27	3	0
Speed – Max Power – New Liners	% Nc		78	2	0
Speed – Max Power – Worn Liners	% Nc		80	2	0
Maximum Pinion Power	kW		20000	2	0
Mill Charge – Structural					
Ball Charge	%v/v	18	18	3	0
Total Charge	%v/v	35	35	3	0
Mill Shell					
Location of Manufacture			Censa - Spain	2	0
Material Shell / Flanges			ASTM A36 / A36 Z25	2	0
Number of Sections			4 x 180	2	0
Thickness Shell / Flanges	mm		85 & 100 / 117 & 132 Final thicknesses TBC via detailed project FEA	2	1
Number of Manholes		Not Required	None	3	0
Welding Details / Specification			Per AWS D1.1 or Equal	2	0
Mill Heads and Trunnions					
Location of Manufacture			Ferry Capitain - France	2	0
Material Heads / Trunnions			FerryNod	2	0
Number of Sections			4x90 Each	2	0
Material Trunnions			FerryNod	2	0
Thickness Heads / Trunnions	mm		130 – 200 / 300 Final thicknesses TBC via detailed project FEA	2	1
Heads Cone Angle	deg	15	15	3	0
Welding Details / Specification			N/A	2	0
Trommel					0
Fresh Feed (at Nom / Max Pebble Recycle)	t/h solids	2416 / 2626	Noted	1	0
Trommel Oversize Rate - Max	t/h solids	1000	Noted	1	0
Oversize - Solids Concentration - Typical	% w/w	~85 (SAG trommel o/s will discharge onto a flat vibrating screen for further classification, therefore trommel duty is only for dewatering)	Noted	3	0
Manufacture			Emalto or Equal	2	0
Materials – Frame / Spiral			Mild Steel / Rubber	2	0
Dimensions – Internal Diameter x Length	m	3.85m ID x 3.70m length (screen panel dimensions)	3.85 x 3.70	3	0
Internal Retaining Spiral Height x Pitch	mm		TBA	2	0
Panel Aperture – Slot Dimensions	mm	12 x 40	12 x 40	3	0
Open Area	%	25	25	3	0
Screening Material		Rubber / Polyurethane	Rubber / Polyurethane	3	0
Deflector Plate		Yes – presentation of feed onto the trommel to incorporate an appropriately designed deflector plate		1	0
Feed Chute					
Design Throughput (Nom. FFx120% + max pebble)	t/h solids	3,029		1, 4	0
Type		Rock Box Chute with Spout		1	0
Material			Mild Steel	2	0
Spout Pipe Size	mm		Oval - ~2200mm	2	0
Spout Materials	mm	Ni-hard lined carbon steel	Mild steel w/ AR Liners	3	0
Support		Trolley mounted on rail wheels with integrated external jacking points for a 3rd party feed chute transporter to lift from		1	0

	Unit	Duty	Supplier / Comment	Notes	Rev
Rail Size / Specification	mm		ASCE #85	2	0
Drive – Type / Travel Capability		N/A – feed chute transporter to be used		1	0
Feed Power Requirement	kW	N/A – feed chute transporter to be used		1	0
Feed End Bearing Opening ID	mm	≥2600	≥2600	2	0
Bottom of Rail Wheels to Mill Centre Line		2160 (To match existing Fim SAG)		1	0
Feed Chute Weight - Fully Sanded	kg		≤60,000 fully loaded	2	0
Liners					
Manufacturer			FLSmidth or Equal	2	0
Backing – Material / Thickness	mm	Rubber / 6	Rubber / 6	3	0
Shell Plates – Material / Thickness	mm	Steel / STA	Chrome-Moly – 90	3	0
Lifters – Material / Thickness	mm	Steel / STA	Chrome- Moly – 225/150	3	0
Grate – Port Dimensions / Open Area	mm / %	Curved grates and lifters. Fully ported slots with a minimum dimension of 75mm. Total open area between 11 & 12%. 28 segments. Supplier to provide 4 additional blank segments as commissioning spares.	Curved grates and lifters. Fully ported slots with a minimum dimension of 75mm. Total open area between 11 & 12%. 28 segments. Supplier to provide 4 additional blank segments as commissioning spares.	3	1
Grate – Material / Thickness	mm	Steel / STA	Chrome-Moly / 75	3	0
Pulp Lifters - Type		Curved, to handle up to 2,100m^3/h (SSSAG mode)	Curved	3	0
Pulp Lifter – Material / Thickness	mm	Steel / STA	Composite / 70	3	0
Trunnion – Material / Thickness	mm	Steel / STA	Discharge – Fabricated steel & Rubber	3	0
Mass of Heaviest Liner	kg	Design to be optimised with the least number of steel pieces possible up to 8,000kg each. Liners to be designed for RME grapple tool.		1	0
Mill Support					
Trunnion Bearings Type		Hydrostatic	Hydrostatic	2	0
Trunnion Bearing Design / Interface Material		Shoe, slipper / lead babbitt, polymer	Multi-Pad - Bronze	2	0
Trunnion Bearings Diameter	mm		4060 x 900	2	0
Trunnion Bearings Width	mm		4060 x 900	2	0
Trunnion Bearings Manufacturer			Meyco or Equal	2	0
Trunnion Bearings Life	h	Equivalent to L10 of >60,000	Theoretically Infinite	3	0
Sole / Sub-Sole Plates		Included	Included	3	0
Base Plates		Included	Included	3	0
Hold Down Bolts and Embedments		Included	Included	3	0
Main Drive					
Drive Type		Low speed synchronous motors each direct driving a pinion on a ring gear		1	0
Ring					
Gear Type			Single Helical	2	0
Outside Tip Diameter	mm		13887	2	0
Operating Centre Distance	mm		7365	2	0
Gear Rim Thickness	mm		200	2	0
Number of Segments			Four (4)	2	0
Material / Hardness			Forged Steel 320 BHN Min	2	0
Pitch Diameter / Width	mm/mm		13749.58 / 1020	2	0
Helix angle at standard pitch	deg		6.9	2	0
Normal Pressure Angle	deg		25	2	0
Number of Teeth / Module			350 / 39	2	0
Whole Depth of Teeth	mm		88.17	2	0
Assembled Backlash			TBA	2	0
Design Standard			AGMA 6014-B15	2	0
Pinion					
Type			Single Helical	2	0
Material / Hardness			Steel Alloy 58-62 RC	2	0

	Unit	Duty	Supplier / Comment	Notes	Rev
Pitch Diameter / Width	mm/mm		903.54 / 1030	2	0
Number of Teeth / Module			23 / 39	2	0
Shaft Material / Diameter	mm		TBA	2	0
Shaft Speed	rpm		150	2	0
Bearings Type			Spherical Roller	2	0
Bearing Span	mm		2060	2	0
Bearings Size	mm		232/500 or Equal	2	1
Bearings Manufacturer			SKF or FAG	2	0
Bearings L10 life	h	>100,000	> 100,000	3	0
Design Standard			AGMA 6014-B15	2	0
Reversible		Yes	Yes	3	0
Outside (tip) Diameter	mm		1000.26	2	0
Normal Pressure Angle	°		25	2	0
Helix Angle at Standard Pitch Diameter	°		6.9	2	0
Whole Depth of Teeth	mm		94.85	2	0
Accuracy / Quality Number		Q12	Q12	3	0
Assemble Backlash			TBA	2	0
Operating Centre Distance	mm		TBA	2	0
Couplings Low Speed					
Type and Lubrication Method		Resettable / STA	Resettable	3 / 2	0
Manufacturer / Model			Brunel or CMD	2	0
Service Factor			>2.0	2	0
Main Motor					
Drive Arrangement		Direct – Discharge End	Direct – Discharge End	3	0
Drive Quantity		2	2	3	0
Motor Manufacturer / Model			Ingeteam / Indar OF110370010101	2	0
Motor Type		Low Speed Synchronous	Low Speed Synchronous c/w Salient pole rotor & AC brushless excitation	3	0
Motor Voltage / Phases / Frequency / Poles	VAC / ϕ / Hz / No.	STA / 3 / 50 / STA	3150 / 3 / 20 / 16	3	0
Motor Rated Output	kW	2 x 10,000	2 x 10,000	3	0
Derating for Altitude (Yes / No)			N/A	2	0
Motor Load Factor	% Rating or kW		TBA	2	0
Duty Type (IEC, AS60034.1)			S1 (1.0)	2	0
Motor Power Factor	100 %		1.00	2	0
	75 %		1.00	2	0
	50 %		1.00	2	0
Motor Efficiency	100 %		97.23%	2	0
	75 %		97.66%	2	0
	50 %		97.89%	2	0
Enclosure Protection	IP		IP56	2	0
Frame			MBIO2816 / IM-7301	2	0
Motor Starting		VSD (for Synchronous motor including Rotor excitation)	VSD (for Synchronous motor including Rotor excitation)	3	0
Power Supply (to HV side of transformer)		33 kV high voltage feeder circuit breaker(s) by Others	33 kV high voltage feeder circuit breaker(s) by Others	3	0
Motor Terminal Box Fault Duty	kA/1s	25 kA/3s		1	0
Maximum VSD output / Motor Terminal Box cable size able to be terminated	No. / mm^2		Yes, refer to “NT0000IKR05_[EN]L_Guidelines for Electrical Installation	2	0
Cooling Method			IC 86W	2	0
Cooling Fans – No. / Power	kW		TBA	2	0
Cooling Water Flowrate / Pressure	m^3/hr @ kPa		60 @ 600	2	0
Cooling Water Temperature	°C		36	2	0
Motor Bearing Type			TBA	2	0
Motor Bearing Life	hrs	L10 of >60,000	L10 of >60,000	3	0
Bearing Lubrication Method		Oil	Oil	3	0
Enclosure			TBA	2	0
Insulation Class (Stator / Rotor)			F / F (Stator / Rotor)	2	0
Temperature Rise (Stator / Rotor)			B / B (Stator / Rotor)	2	0

	Unit	Duty	Supplier / Comment	Notes	Rev
Number and Position of RTDs			TBA	2	0
Number of Winding RTDs	per Phase		TBA	2	0
Rotation	Uni or Bi		Unidirectional	2	0
Anti-Condensation Heaters (Yes / No)		Yes	TBA	3	0
Anti-Condensation Heater Voltage	VAC	230		1	0
Service Factor			1.0	2	0
Starting Torque Required (Rated)	kNm		TBA	2	0
Full Load Torque (Rated)	kNm		472kN/m	2	0
Full Load Current (Rated)	Amp		1875.3 A	2	0
Required Creep Speed	rpm		TBA	2	0
Breakdown Torque (% FLT)	%		N/A	2	0
Temporary Overload Torque Short Time	kNm		150% during 30sec every 10 min start	2	0
Temporary Overload Torque 2 Minute Time	kNm		TBA	2	0
Variable Speed Drive					
Manufacturer			Ingeteam	2	0
Model Type			48 Pulse DFE Rectifier + Inverter (MV1D8-33-751-WAD-432 – 2 x 10,000kW)	2	0
Maximum Altitude	m		1000 (above sea level)	2	0
Maximum Operating Ambient Temperature	Deg C		55	2	0
Cooling Method			Water Cooled Prim. / Sec. Water Heat Exchanger	2	0
Cooling Water Flowrate / Pressure	m^3/hr @ kPa		63 @ 600	2	0
Cooling Water Temperature	°C		0-38	2	0
Maximum Cooling Water ΔT	°C		6	2	0
Heat Loss – air / water	kW		5.5 / 377	2	0
Dimensions (H x W x D)	mm		10810 x 2360 x 1460 (TBA)	2	0
Finish (Doors)		Manufacturer Standard	Manufacturer Standard	3	0
Finish (Base, Roof, and Shutters)		Manufacturer Standard	Manufacturer Standard	3	0
Maximum Short Circuit Fault Level (33 kV)	MVA	950	950	3	0
Minimum Short Circuit Fault Level (33 kV)	MVA	165	165	3	0
Input Voltage Rating / Frequency	V / Hz		8 x 1850VAC (±10%) / 50Hz (±5%)	2	0
Input Off Load Isolator		Yes, key interlocked with high voltage feeder earth switch(es)	N/A	1	0
Output Voltage	V		3150 VAC	2	0
Output Off Load Isolator and Earth Switch		Yes, key interlocked with inching drive. Fortress SL	Yes	3	0
Pulses Configuration / Modulation Principal		Quasi 48-pulse per SAG Mill (Quasi 96-pulse in conjunction with Ball Mill)		1	0
Efficiency	%		98.1%	2	0
Rated Output Current	A		2 x 1875 A	2	0
Rated Overload Capacity - % Motor FLA / Time (seconds)	% / s		150% / 30sec	2	0
Total Harmonic Distortion Current	%		TBA	2	0
Harmonic current spectrum	%		TBA	2	0
IAC rating (IEC 62477-2)		IAC 2B FLR	AFLR 10kA-0.3seg	3	0
Maximum Motor Cable Distance	m		300m	2	0
Maximum VSD incoming cable size able to be terminated	No. / mm^2		Refer to “NT0000IKR05_[EN]L_Guidelines for Electrical Installation”	2	0
Control Voltage	V	24 V DC	TBA	3	0
Control Interface		Hardwired safety interlocks, Voltage free contacts. Ethernet process control interface (Modbus TCP/IP)	Yes	3	0
Operating System			TBA	2	0
Control Mode			TBA	2	0

	Unit	Duty	Supplier / Comment	Notes	Rev
Shift Transformer			TBA	2	0
Local Speed Setpoint			TBA	2	0
Local Speed Reference			TBA	2	0
Remote Speed Setpoint			TBA	2	0
Converter Transformers					
Quantity		2		1	0
Location		Outdoors		1	0
Type		3-phase oil-filled (FR3 or equivalent less combustible to AS2067)		1	0
Oil brand and volume	L		Cargill FR3 / 9315L	2	0
Primary/secondary rated voltages	kV	33/4x1.85	33/4x1.85	3	0
Tap changer		Off-circuit	±2 x 2.5%	3	0
Primary/secondary terminations		Air terminations inside cable boxes		1	0
Rated Capacity	MVA		11.5	2	0
Cooling		KNAN	KNAN	3	0
Vector Group			D(+3.75°), y11(+7.5°), d0(+7.5°), d0(-7.5°), y11(-7.5°)	2	0
Impedance, Z	%		8.4%	2	0
Pre-magnetisation Unit	Yes/No	Yes		1	0
Conservator	Yes/No		Yes	2	0
Total mass	kg		30,000	2	0
Overall dimensions, LxWxH	mm		4350 x 2750 x 4700	2	0
Excitation Transformer					
Quantity		1		1	0
Location		Indoor		1	0
Type		3-phase dry type		3	0
Primary/secondary rated voltages	V	415/350	400/350	2	0
Tap changer		Off-circuit	±2 x 2.5%	3	0
Primary/secondary terminations		Air terminations inside transformer enclosure		1	0
Rated Capacity	kVA		300	2	0
Cooling		AN	AN	3	0
Vector Group			Dd0yn11	2	0
Impedance, Z	%		3.0%	2	0
IP rating of transformer enclosure			IP23	2	0
Total mass	kg		1150	2	1
Overall dimensions, LxWxH	mm		1000 x 1000 x 1325	2	1
Inching Drive					
Primary Type		Inching of mill will be carried out using both of the main HV drives	Inching of mill will be carried out using both of the main HV drives	3	0
Secondary Type		Portable hydraulic (will be stored away from the mill and only used when maintenance needs to be carried out on either of the mill motors)	Portable hydraulic (will be stored away from the mill and only used when maintenance needs to be carried out on either of the mill motors)	3	0
Manufacturer			ErSun	2	0
Reduction Ratio			40.66	2	0
Service Factor		≥1.5 minimum	>1.5	3	0
Design Standard			TBA	2	0
Interlocking System – Fortress Key Lockable		Required		1	0
Lubrication Details			ISO 6336:96	2	0
Brake Details / Quantity		Disc type, Fail Safe - to be mounted on the drive shaft between the HV motor and the pinion / One brake per HV motor	Disc type, Fail Safe - to be mounted on the drive shaft between the HV motor and the pinion / One brake per HV motor	3	0
Brake Model / Manufacturer			Hydraulic	2	0
Brake Holding Torque (per brake)	kN.m		MDA21	2	0
Motor Rated Output	kW		46.2 + >1.5 SF	2	0
Motor Rated Speed	rpm		315	2	0
Motor Peak Torque	kN.m		TBA	2	0
Motor Starting			DOL	2	0
Lubrication Systems					

	Unit	Duty	Supplier / Comment	Notes	Rev
Trunnion Bearings Lubrication					
Lubrication Unit Manufacturer			Rexroth or Howard Marten	2	0
Number of High Pressure Pumps		Duty / Standby required	3/1	2	0
High Pressure Pumps Capacity / Pressure	l/min @ kPa		1014 total @ 10340	2	0
Motor Rated Output	kW		90	2	0
Motor Starting			DOL or VFD	2	0
Number of Low Pressure Pumps			1/1	2	0
Low Pressure Pumps Capacity / Pressure	l/min @ kPa	Duty / Standby required	1166 @ 690	2	0
Motor Rated Output	kW		45	2	0
Motor Starting			DOL	2	0
Oil Reservoir	L		10500	2	0
Oil Type Grade			ISO VF 360	2	0
Filter System Description		Duty / Standby filters required	1 / 1	2	1
Cooling Method Description		Water Cooled	Water Cooled (Reservoir Heaters)	3	1
Cooling System Power Requirements – No. Motors / Motor Rated Output	kW		TBA	2	1
Motor Starting			N/A	2	1
Cooling Water Flowrate / Pressure	m^3/hr @ kPa		68 @ 1000	2	0
Cooling Water Temperature	°C		30	2	0
Pinion Bearing Lubrication					
Lubrication Unit Manufacturer			Rexroth	2	1
Number of Pumps		Duty / Standby required	1 / 1	2	0
Capacity / Pressure	l/min @ kPa		60 @ 1034	2	0
Motor Rated Output	kW		1.5 Each	2	0
Motor Starting			DOL	2	0
Oil Reservoir	L		N/A- Split from MB Lube	2	0
Oil Type Grade			N/A- Split from MB Lube	2	0
Cooling Method Description			N/A- Split from MB Lube	2	0
Cooling System Power Requirements – No. Motors / Motor Rated Output	kW		N/A- Split from MB Lube	2	0
Motor Starting			N/A- Split from MB Lube	2	0
Pinion / Ring Gear Mesh Lubrication					
Type / Manufacturer			Howard Marten or Alemlube	2	0
Number of Pumps			One (1)	2	0
Capacity / Pressure	l/min @ kPa		Pneumatic	2	0
Grease Reservoir	L		400lb drum	2	0
Grease Type Grade			Mobiltac 375NC or Equal	2	0
Spray Nozzle Quantity / Interval / Duration	# / min / s		200	2	0
Spray Nozzle Air Consumption	l/min @ kPa		TBA	2	0
System Heating Requirements			Drum Heater Included / Heat tracing	2	0
Bearing Purge / Seals					
Mill Seal Lubrication Requirements		Gear guard, trunnion bearing seals, pinion bearing seals etc.	Main Bearings	2	0
Lubrication Unit Manufacturer			Howard Marten or Rexroth	2	0
Number of Pumps			One (1)	2	0
Capacity / Pressure	l/min @ kPa		Pneumatic	2	0
Grease Reservoir	L		400# drum 2	2	0
Grease Type Grade			Calcium grease	2	0
System Heating Requirements		If Applicable (List kW per heating element)	Drum Heater Included / Heat tracing excluded	2	0
Main Motor Bearing Lubrication					
System Description		Hydrostatic Lift	Hydrostatic Lift	2	0
Power Requirements	kW	TBA	TBA	2	0
Air Requirements	l/min @ kPa	N/A	N/A	2	0

	Unit	Duty	Supplier / Comment	Notes	Rev
Surface Protection					
External Paint Specification		Owner Spec CS2	Owner Spec CS2	3	0
External Dry Film Thickness	µm		Owner Spec CS2	2	0
Electrical / Control					
LV Motor Manufacturer / Model		TECO Maxe3 Mining (Preferred) WEG W22 High Efficiency E3 / ABB M3BP IE3 (Acceptable alternative pro approval from Owner	TECO Maxe3 Mining (Preferred) WEG W22 High Efficiency E3 / ABB M3BP IE3 (Acceptable alternative pro approval from Owner	3	1
LV Motor Voltage / Phases / Frequency	VAC/ϕ/Hz	415 / 3 / 50	Noted	3	0
Dedicated Mill PLC		No, control via site DCS		1	0
Local Control Panel Description		N/A		1	0
Electrical Load List – Separate List Provided		Required with tender	Noted	2	0
Instrument and Control Voltage	V	24 V DC		1	0
Instrument Analogue Signals		4-20 mA HART		1	0
Process Control System Interface		Hardwired for safety interlocks Ethernet based (Modbus TCP/IP) or hardwired for process control Field instrumentation wired to local junction boxes (where practical). Signals hardwired to DCS	Noted	3	0
Preliminary I/O Count	DI DO AI AO		TBA	2	0
Instruments List – Separate List Provided		Required with tender	TBA	2	0
Ancillary Equipment					
Mill Load Measurement Description		Required, hydraulic pressure measurement	Included	2	0
Erection and Maintenance Jacking System		Cradles and jacking system, required. Suitable for installation and fully loaded mill	Maintenance Cradles & Hydraulics	3	0
Additional Information – Mill Dimensions and Weights					
Shell – Number of Pieces x Mass Each	t		4 x 70.25	2	0
Heads – Number of Pieces x Mass Each	t		8 x 30.01	2	0
Trunnions – Number of Pieces x Mass Each	t		2 x 43.96	2	0
Gear – Number of Pieces x Mass Each	t		4 x 28.5	2	0
Heaviest Component for Shipping	t		Mill Liners (702.8t total)	2	0
Heaviest Component for Maintenance	t		Mill Liners (19.52t each)	2	0
Largest Shipping Piece (L x W x H)	mm		Mill Liners (12,190 x 2,440 x 2440)	2	0
Total Shipping Mass	t		1871.0	2	0
Maximum Lift for Erection	t		Shell Section (70.25 each)	2	0

Notes
1. Fixed
2. Vendor to Advise
3. Preferred, Vendor to advise and provide reasoning for difference
4. Design throughput for sizing feed chute only.
5. Do not enter data in grey cells.

6. Battery Limits for LoadIQ as per below diagram.

