FIM III VALVE STATION
2000-F23-PID-PR-40005
FINAL TAILS

23-8174-FT-PE10-630
LINE 1 NORTH

NOTE 3

NOTE 5
NOTE 1
SP
MS-401

NOTE 5
NOTE 1
SP
MS-401

FIM III - CELL 1
SUB-CELL WEST

FIM III - CELL 1
SUB-CELL EAST

FIM III VALVE STATION
2000-F23-PID-PR-40005
FINAL TAILS

23-8178-FT-PE10-630
LINE 1 SOUTH

NOTE 3

NOTE 5
NOTE 1
SP
MS-401

NOTE 5
NOTE 1
SP
MS-401

23-8261-FT-PE10-630
NOTE 4

NOTE 5
NOTE 2
SP
MS-401

630x500

SP
MS-406

500VPLE1L1
(40703)

DISCHARGE INTO
FIM III TSF

630x500

500VPLE1L1
(40702)

630x500

SP
MS-401
NOTE 1
NOTE 5

SP
MS-401
NOTE 1
NOTE 5

DECANT DAM 4 SETTLING PONDS
2000-F75-PID-PR-40004
FINAL TAILS

23-8549-FT-PE12.5-225
NOTE 3

LEGEND:

- EXISTING
- NEW
- FUTURE
- DECOMMISSIONED

NOTES:

1. SPIGOTS PLACED AT 40m CENTRES ON TSF EMBANKMENT.
2. SPIGOTS PLACED AT 15m CENTRES ON THE CAUSEWAYS.
3. PIPING ON TSF EMBANKMENT TO BE FLANGED EVERY 40m.
4. PIPING ON CAUSEWAY TO BE FLANGED EVERY 15m.
5. REFER TO DRAWING 2000-T03-DRG-GE-40003 FOR SPIGOT DETAILS. A TOTAL OF 170 SPIGOTS REQUIRED WITH UNIQUE VALVE NUMBERS 43001 TO 43170.

APPROVED FOR CONSTRUCTION