NOTES:

1. SPIGOTS PLACED AT 40m CENTRES ON TSF EMBANKMENT.
2. SPIGOTS PLACED AT 15m CENTRES ON THE CAUSEWAYS.
3. PIPING ON TSF EMBANKMENT TO BE FLANGED EVERY 40m.
4. PIPING ON CAUSEWAY TO BE FLANGED EVERY 15m.
5. REFER TO DRAWING 2000-T02-DRG-GE-40002 FOR SPIGOT DETAILS.A TOTAL OF 166 SPIGOTS REQUIRED WITH UNIQUE VALVE NUMBERS 44204 TO 44369.

LEGEND:

- EXISTING
- NEW
- FUTURE
- DECOMMISSIONED

FIM II EXTENSION CELL G

NOTE 5 NOTE 1 SP MS-402

NOTE 5 NOTE 1 SP MS-402

NOTE 5 NOTE 2 SP MS-402

30-8476-FT-PE81-560 NOTE 4

560x400

400VPLE1L1 (44409)

560x400

400VPLE1L1 (44408)

NOTE 5 NOTE 2 SP MS-402

30-8475-FT-PE81-560 NOTE 4

560x400

400VPLE1L1 (44407)

560x400

400VPLE1L1 (44406)

560x400

NOTE 5 NOTE 1 SP MS-402

NOTE 5 NOTE 1 SP MS-402

NOTE 3

NOTE 3

SP MS-402 NOTE 1 NOTE 5

2

SP MS-407

SP MS-407

FIM II VALVE STATION No 3 2000-F75-PID-PR-40026 FINAL TAILS

30-7005-FT-PE25-630 LINE C

PE25 RL2 600x400

400VPLE1L1 (44401)

30-8474-FT-RL2-400

400VPLE1L1 (44405)

RL2 PE81

400VPLE1L1 (44402)

RL2 PE81 550x400

30-7005-FT-PE81-560

FIM II VALVE STATION No 3 2000-F75-PID-PR-40026 FINAL TAILS

30-7006-FT-PE25-630 LINE A

PE25 RL2 600x400

400VPLE1L1 (44403)

RL2 PE81

400VPLE1L1 (44404)

RL2 PE81 550x400

30-7006-FT-PE81-560

NOTE 3

APPROVED FOR CONSTRUCTION