APPROVED FOR CONSTRUCTION

NOTES:

1. REMOVABLE SPOOL TO ALLOW FOR FUTURE INSTALLATION OF HYDROGEN PEROXIDE INLINE MIXER, BY OTHERS.
2. THIS PIPE REDUNDANT AFTER STAGE 1 COMPLETION.
3. THIS PIPE REDUNDANT AFTER STAGE 2 COMPLETION.
4. THIS SPOOL TO BE REMOVED FOR UPGRADE WORKS.
5. DRAIN TO LAST CHANCE POND.
6. DRAIN TO DRIVE-IN SUMP.
7. TIE-IN POINTS AT BATTERY LIMITS TO PROCESS PLANT TO BE FITTED WITH BLIND FLANGE BY ENABLING WORKS CONTRACTOR.
8. DELETED. 4
9. ~~DURING ENABLING WORKS LINE WILL BE LABELLED 75-8062-TL-RL2-400.~~ ONCE UPGRADE WORKS HAVE BEEN COMPLETED LINE WILL BE LABELLED 23-0545-FT-RL2-400.
10. DN350 TABLE 'E' FLANGE RELOCATED FROM EXISTING BREATHER POINT TO NEW LOCATION.
11. SPOOL TO BE REMOVED FOR FUTURE WORKS.
12. DURING ENABLING WORKS LINE WILL BE LABELLED 75-8066-PW-PE16-450. ONCE FUTURE WORKS HAVE BEEN COMPLETED LINE WILL BE LABELLED 175-8512-BW-PE16-450.
13. REDUCER TO BE REMOVED DURING UPGRADE WORKS.
14. DIFFERENTIAL FLOW CALCULATION FOR LEAK DETECTION.

ACTUATED VALVES WILL BE REPLACED WITH PNEUMATIC VALVES.

16. DECOMMISSIONED DURING Owner GROWTH PROJECT.
17. FLOWMETERS BY EPC 4

LEGEND:

⬛	EXISTING
🟥	ENABLING WORKS (WORKS COMPLETED)
🟦	UPGRADE WORKS
🟩	FUTURE WORKS
– – –	DECOMMISSIONED