NOTES:

1. PIPING ON TSF EMBANKMENT TO BE FLANGED AT 40m CENTRES.
2. DESIGN AND IMPLEMENTATION OF FIM II VALVE STATION No.1 IS BY OTHERS. (2)

LEGEND:

- EXISTING
- NEW
- FUTURE
- DECOMMISSIONED

FINAL TAILS PUMP 4
2000-F75-PID-PR-40021
FINAL TAILS
30-8551-FT-PE20-560
LINE C BYPASS

FIM II BOOSTER PUMP No.1
2000-F75-PID-PR-40022
FINAL TAILS
TIP 16
30-6016-FT-PE25-630
LINE C

DECANT DAM 3 PUMPS
2000-F75-PID-PR-40022
FLUSHING WATER
175-6096-PW-PE16-355

FINAL TAILS PUMP 3
2000-F75-PID-PR-40021
FINAL TAILS
30-8552-FT-PE20-560
LINE A BYPASS

FIM II BOOSTER PUMP No.2
2000-F75-PID-PR-40022
FINAL TAILS
TIP 18
30-6018-FT-PE25-630
LINE A

FIM II VALVE STATION No.1
(BY OTHERS) NOTE 2 (2)

TIP 52
30-7002-FT-PE20-560
LINE C
VALVE STATION No.2
2000-F75-PID-PR-40025
FINAL TAILS

TIP 20
30-6016-FT-PE25W-630
LINE C
FIM II HUB
2000-F75-PID-PR-40024
FINAL TAILS

TIP 38
175-6096-PW-PE16-355
FIM II HUB
2000-F75-PID-PR-40024
FLUSHING WATER

TIP 51
30-7001-FT-PE20-560
LINE A
VALVE STATION No.2
2000-F75-PID-PR-40025
FINAL TAILS

TIP 22
30-6018-FT-PE25W-630
LINE A
FIM II HUB
2000-F75-PID-PR-40024
FINAL TAILS

75-7050-PW-PE16-450
VALVE STATION No.2
2000-F75-PID-PR-40025
FLUSHING WATER

APPROVED FOR CONSTRUCTION