Document Number :	2000-F00-DSH-PP-VKGD1L1
EPC **Project Number :**	

VKGD1L1	**Knife Gate Valve - Bidirectional, Ductile Iron, Natural Rubber replaceable sleeve, narrow body, lugged to AS2129 Table D for slurry service applications.**

Item	EPC Data	Supplier Data	Notes
Type	Kinfe Gate Valve, Bidirectional, Lug Type, Narrow Body, Push-Through Gate		1
Service	Slurry		1
Size Range (mm)	DN50 to DN600		1
End Connections	Lugged body to suit AS 2129 Table D, Metric body lugs tapping		1
Actuation	≤DN250 – Hand wheel ≥DN300 – Gearbox with hand wheel		1
Lockable	Yes	Mechanical lockout, open/closed with standard pin	3
Supplier Name		Emerson	2
Manufacturer		Clarkson	2
Model		KGD	2
Valve Standard		MSS SP-81	2
Dimensional Standard		MSS SP-81	2
Body Material	Ductile Iron with replaceable elastomer sleeve	Ductile Iron with replaceable elastomer sleeve	3
Gate Material	316 Stainless Steel	316 Stainless Steel	3
Stem Material	316 Stainless Steel	316 Stainless Steel	3
Sleeve Material	Natural Rubber with reinforcing ring	Natural Rubber with reinforcing ring	3
Packing Material	Packingless top seal	Packingless top seal	3
Deflection Cone Material	Not required	N/A	3
Design Pressure	700 kPa(g)	DN50 to 400: 150 psi MAWP (1,034 kPa(g)) DN450 to 600: 90 psi MAWP (620 kPa(g))	3
Design Temperature	0 to 80°C	0 to 80°C	3
Surface Protection	Manufacturers Standard	Manufacturers Standard TES-B-48	2
Shroud / Gate Guard	Yes - Actuated Only	Included	3

NOTES	
1	Data supplied by EPC . The Supplier shall comply with this data.
2	Data shall be provided by Supplier.
3	Data proposed by EPC . The Supplier shall confirm data or state alternative.