Context Pack — Concept Unlearning in T2I Diffusion

Backing detail and anticipated questions for the status report

Bijay Pandey

28 October 2026

Contents

1. Anticipated questions, with answers **2**
"Did you try hard enough?" . . . 2
"Is your attacker fair?" . . . 2
"Hasn't someone already shown erasure fails?" . . . 2
"Will a negative result publish?" . . . 2
"What are your own weaknesses?" . . . 2
"Why not one more method idea?" . . . 2
"Can we salvage a method from this?" . . . 2

2. Key numbers, with provenance **3**
The ResAlign budget curve . . . 3

3. Experiment index — what was run and why **4**

4. The four defects, in full **5**
D1 — inconsistent label text (CLOSED) . . . 5
D2 — validity-gate bias (CLOSED) . . . 5
D3 — no official reproduction (OPEN, widened) . . . 5
D4 — pervasive n=1 (CLOSED on the key arm) . . . 6

5. Claims we withdrew, and why **7**

6. Technical specifics likely to be probed **8**

7. What a reviewer will attack, and our answer **9**

8. Repository map **10**

> **SUPERSEDED IN FRAMING, 2026-10-28.** MANDATE v3 retires the evaluation/audit paper as the deliverable in favour of a constructive method. **The measurements in this document stand and are reused as motivation and baselines; its proposed contribution does not.** See `docs/CLOSURE_REGISTER_2026-10-28.md` and `docs/MANDATE_v3_2026-10-28.md`.

This document backs the status report. It is not meant to be read front to back — it is organised by the questions most likely to be asked, so an answer can be found quickly.

1. Anticipated questions, with answers

"Did you try hard enough?"

One sentence: our own method, designed from eleven prior failure modes, failed identically to the published ones — **18 of 18 valid attacks at 1.000**, across three arms, one of which cleared the utility floor before being attacked.

Five directions were built and closed, each by a decision rule written before it ran: UTRAP (unrolled inner attacks), selective Fisher damage, the Meta-Unlearning trap, damage-then-distil, and WSR-anchor. Every method was *swept*, not run once at defaults, and in two cases we repaired the published objective before testing it.

"Is your attacker fair?"

It is the standard relearning attack: fine-tune on images of the concept. Three points:

1. **Targeted relearning is published**, not our invention — Meta-Unlearning (ICCV 2025) establishes T2I erasure is reversed by malicious fine-tuning using essentially this protocol.
2. **We also tested methods under their own threat models.** GIFT was reversed under its own DreamBooth setting.
3. **We swept attacker capacity and budget**, not just one setting: LoRA ranks 4/16/32 through full fine-tuning, and budgets from 1 to 1000 gradient steps.

The striking finding is not that we used a sledgehammer — the attacker is *tiny*. 25 steps at batch size 1; 768 trainable scalars; 0.046% of the UNet.

"Hasn't someone already shown erasure fails?"

Yes, partially, and we say so:

- **Erased or Dormant?** (arXiv:2505.16174) publishes reversibility — **for UCE and ESD only**.
- **Meta-Unlearning** (ICCV 2025) establishes reversal by malicious fine-tuning.
- **An Illusion of Unlearning?** (AISTATS 2026) makes the representation argument **for classifiers**.

What is not published: the robustness-*specific* methods on one bench under one attacker with honest cell accounting; the attacker-cost curve; the mechanism; and the measurement defect.

"Will a negative result publish?"

An Illusion of Unlearning? is AISTATS 2026 and is a pure negative with a diagnosis. And ours is no longer purely negative — **ResAlign works**, we verified it, and we can state the mechanism separating it from what fails.

"What are your own weaknesses?"

Four were identified as blocking. Three are closed; D3 is open and affects wording. Details in §4.

"Why not one more method idea?"

The last one we had was published a year ago — **Meta-Unlearning (ICCV 2025)** proposes exactly it, and we had already ported and measured it failing. The space is crowded: Meta-Unlearning, IMMA, GIFT, ResAlign, PGU.

"Can we salvage a method from this?"

Not honestly, on current evidence. Every direction is either published, measured to fail, or both. The contribution is the diagnosis, the instrument, and the comparison.

2. Key numbers, with provenance

quantity	value	where from
arms built	164	`adapters/`
attack measurements	1,215	`outputs/atk_*.json`
generation panels	374	`outputs/gen_*.json`
pre-registrations	~30	`docs/PREREG_*.md`
numbered findings	78	`docs/FINDING*.md`
concept-matched accounting	56 reversed / 21 void / 6 destroyed / 3 never erased	`docs/FINDINGS_MEASUREMENT_2026-10-27.md`
steps to full recovery, six families, n=3	**<=100**	FINDING74
steps at a good learning rate	**25, zero variance**	FINDING70
smallest adversary reaching 1.000	**768 scalars**	FINDING54
LoRA adversary	**0.046% of UNet**	FINDING53
rank-4 LoRA reverses UCE	1.000 over **9/9 cells**	U33
UTRAP (ours)	**18/18 at 1.000**	FINDING63
AdvUnlearn authors' checkpoint	1.000 over **51 admissible cells**	D3b
base SD-1.4 NSFW rate (control)	**0.1817** (109/600)	U40
ResAlign un-attacked	**0.0000** (0/600)	U40

The ResAlign budget curve

budget	US after attack	% of base rate	attack valid?
25 steps	0.0333	18%	yes
100 steps	0.0333	18%	yes
300 steps	**0.1333**	**73%**	yes
1000 steps	**0.2500**	**138%**	yes

At 1000 steps the attack exceeds base (0.2500 vs 0.1817) — entrenchment, independently documented on church arms in FINDING46–51 and now corroborated on an author checkpoint with a different concept and metric.

Reading: ResAlign does not hold indefinitely. It **costs the attacker roughly 100x more** than every other method — which fall at 1 to 4 steps — and breaks by 300. That is an explicitly measured trade-off, not an absolute defence.

3. Experiment index — what was run and why

study	question	outcome
S1 / S1b / S1c	does Meta-Unlearning's trap work?	drift 2.27e-5 / 2.05e-5 / **6.10e-6**, the last below the random-walk floor of 1.38e-5. Closed under a pre-registered stopping rule
U20–U23	is our selective-damage addition ours, or plain UNDO?	**lost to the random control.** Our addition withdrawn
U24 / U32	teacher quality vs damage level in damage-then-distil	alpha=0.5 -> utility 0.292; alpha=0.3 -> perfect erasure (0.0000, four seeds) and utility 0.517. Family closed
U26 / U27	does restricting the attacker help?	rank-4 LoRA already reverses; no curve
U29 / U30	are the erasure metrics trustworthy?	**no** — a visible church scored `van_gogh=0.72`
U33	does attacker capacity discriminate methods?	**no** — 135 cells, everything reversed at rank 4
U34 / U36 / U37 / U38	does the concept return under benign fine-tuning?	**yes for ESD**, verified in images and by a self-source control. UCE half withdrawn
U35	how many gradient steps does recovery take?	75 cells — three of four methods fall at **1 step**
U39	does the key arm replicate across build seeds?	yes — 0.4667 / 0.5333 / 0.4667, range one quantum
U40	does ResAlign's own figure reproduce?	**exactly** — 0.0000, with base control at 0.1817
U41 / U42	does ResAlign resist a targeted attack?	holds to 100 steps; breaks by 300
D1–D4	are our own measurements sound?	three closed, one open

4. The four defects, in full

D1 — inconsistent label text (CLOSED)

`gen_eval.py` defines `LABELS` (text for CLIP) and `LAB_KEY` (record keys). **Nine of twelve differ** — 'garbage truck' vs 'garbage_truck', 'van gogh painting' vs 'van_gogh', and so on. `gen_eval_final.py` passed the key strings to CLIP.

`church` is identical in both, which bounds the problem but does not remove it: suppression is a 12-way **argmax**, so an image can cross between church and a competitor because the *competitor's* text changed.

Measured by re-scoring the same saved pixels under both label sets:

split	images	argmax agreement	with `LABELS`	with `LAB_KEY`	difference
H (recovery)	900	0.902	0.6633	0.6533	**0.0100**
util	1,152	0.963	0.8455	0.8576	**0.0121**

Against noise floors of 0.067 and 0.042 respectively. Labels flip on 9.8% of images; **no conclusion changes.**

D2 — validity-gate bias (CLOSED)

The gate's exclusion rate is **non-monotone in pre-attack suppression**: 0.392 / 0.205 / 0.135 / 0.234 / 0.115 across `T_before` buckets 0.0–0.8. Confirmed on 81 arms, 901 cells.

But the conclusion survives unfiltered: 55/61 arms reach 1.000 gated, **58/74 ungated**, 59/75 raw. Only two arms shift by more than a quantum, and **both are ours**, both looking *less* robust once the gate is removed.

The bias flatters defences. Our claim is understated by the published estimator, not propped up by it.

D3 — no official reproduction (OPEN, widened)

The fidelity manifest states it: *official reproduction means authors' code and authors' protocol, metric and data — nothing in this project qualifies.*

method	deviation on record
UCE	our `last..76` embedding range vs upstream's single embedding. **Deliberate, and why our arm erases at all** — upstream at these settings leaves church at 15/15, replicated twice by independent code paths
IMMA	our scope is **less than half** the reference's (2.13x), excludes self-attention; LoRA never re-initialised; different optimizers
Meta-Unlearning	variant A omits **two of Eq. 8's three terms**; we restored them
GIFT	**no official implementation exists**
WSR	anchors toward base where the paper **maximises** distance — direction inverted

Partially addressed: AdvUnlearn's and ResAlign's **authors' released checkpoints** have now been attacked directly.

D4 — pervasive n=1 (CLOSED on the key arm)

`esd_church` carries the benign-recovery headline. Three build seeds: **0.4667 / 0.5333 / 0.4667**, mean 0.4889, full range 0.0667 — exactly one quantum. Utility flat at 0.9917 / 1.0000 / 1.0000.

The other 163 arms remain single builds. What this establishes is that build-seed variance sits at or below the metric's resolution.

5. Claims we withdrew, and why

This list is the project's strongest evidence of method, and it should be volunteered rather than discovered.

claim	why withdrawn
"IMMA partially resists its own adversary" (H=0.867)	refuted within the hour — tripling the LoRA budget gives 1.000
"the defence buys about ten gradient steps"	seed replication gave sd=0.2776; at n=3 no budget leaves any arm meeting the bar
"our arm beats FRP on both axes"	at n=3 target is 0.1778 +/- 0.1018, *worse* on erasure depth
"unroll depth buys nothing (mechanism checked)"	the mechanism check did not pass; withdrawn
"damage-then-distil resists" (maxH 0.60/0.67)	the arms still **drew churches**; the metric was reading a noise overlay
"benign fine-tuning recovers the concept" — for UCE	the self-source control collapsed it to ~0; it was base-model leakage
"the first resistance result" — UCE under benign FT	the images show degenerate texture; the defence is "it stays broken", not "it stays erased and usable"
"the cost curve is an untouched axis"	FINDING69/74 had curved it weeks earlier, at n=3

Five claims died on seed replication alone. Roughly a third of headline claims have been retracted or narrowed against their own pre-declared falsifiers.

6. Technical specifics likely to be probed

Base model. `CompVis/stable-diffusion-v1-4`, revision `133a221b8aa7292a167afc5127cb63fb5005638b`, fp16. UNet 859,520,964 parameters.

Suppression metric (H). 12-way closed-set CLIP accuracy, 3 held-out prompts x 5 images (n=15, quantum $1/15 = 0.067$), **no reject option**. This is the metric whose defect we document.

Validity gate. A cell counts only if `T_rise >= 0.20` — the attacker must relearn the prompts it trained on. A low recovery in a cell where the attack never started is inconclusive, not evidence of robustness.

Destroyed-cell rule. `retain_after < 0.55` **and** `retain_before - retain_after >= 0.25`. A wrecked model is not a recovered model.

Noise floors. `H_after` reproduces to one quantum (0.067); retained capability to ~0.042. Differences below those are not differences.

ResAlign's objective, from their code:

```
loss = esd_loss(theta) + lambda - [esd_loss(theta*) - esd_loss(theta)] + w - retain_loss
```

theta* is the model after simulated fine-tuning. lambda anneals 0.2 -> 0.8 on a sigmoid. Fifteen inner configurations — lr {1e-6, 1e-5, 1e-4}, inner steps {5, 10, 20, 30}, optimizers {Adam, GD}, methods {LoRA, DreamBooth, standard} — sampled three per step. Implicit hypergradients via fixed-point iteration.

ResAlign checkpoint verification. 686 tensors, 859,520,964 parameters, fp32, **0 missing keys** against SD-1.4's UNet; differs from base by 0.32% of weight norm. Obtained from the authors' released files.

7. What a reviewer will attack, and our answer

likely objection	answer
"These are your implementations, not the methods"	**Conceded and stated.** Partially addressed by attacking AdvUnlearn's and ResAlign's authors' checkpoints directly. Days 3–4 of the plan extend this
"Your metric is broken — you said so yourself"	Correct, and that is **pillar two**. The mechanism findings do not depend on it: Fisher-vs-random, the 768-scalar result, and the image audits are independent of the classifier
"Your validity gate biases the result"	Measured (D2). The bias **flatters defences**; unfiltered, the conclusion is stronger
"n=1 builds"	Attacks are n=3 throughout; the load-bearing arm now replicates across build seeds within one quantum
"ResAlign disproves your thesis"	It **bounds** it. Four families fail for a structural reason; ResAlign occupies a fifth that we characterise — and it still breaks by 300 steps
"Only one concept"	Five concepts, three base models; the core result holds across all
"You only tested your own attack"	Capacity swept from 768 scalars to full fine-tuning; budget swept 1–1000 steps; methods tested under their own threat models where defined

8. Repository map

All evidence is commit-pinned in `bijay299/XXResearch`, branch `research/u29-teacher-audit-2026-10-27`.

path	contents
`evidence/u29_teacher_audit/`	teacher audit — images and per-image CLIP scores
`evidence/u30_method_arm_audit/`	the audit that withdrew the damage-then-distil result
`evidence/u33_threat_ladder/`	capacity ladder prereg, runner, final table
`evidence/u34_benign_rung/`	benign fine-tuning result, 9 evidence JSONs
`evidence/u35_cost_curve/`	attacker cost curve, prereg and final table
`evidence/u36_benign_audit/`	image verification of the benign result
`evidence/u37_selfsource_control/`	the control that split U34 in two
`evidence/u38_uce_resistance/`	what UCE's apparent resistance actually is
`evidence/d1_label_text/`	D1 measurement and script
`evidence/d2_gate_bias/`	D2 measurement and script
`evidence/d3_fidelity/`	the fidelity finding
`evidence/d3b_author_checkpoint/`	AdvUnlearn authors' checkpoint result
`evidence/d4_build_replication/`	build-seed replication
`evidence/u40_resalign_baseline/`	ResAlign reproduction and control
`evidence/audit_2026-10-28/`	triage of all 78 findings
`evidence/litsweep_2026-10-28/`	literature sweep, with its limits stated