PAY724 CORE API SPECIFICATION

INTEGRATION SPECIFICATION

VER. 0.3.11 EN (18.06.2021)

© 2015 UNIPAY DANIŞMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

Purpose

The purpose of the document is to describe Pay724 API that makes it possible to collect payments for a large set of diverse service providers.

Table of contents

Purpose....2
1. INTRODUCTION....3
2. AVAILABLE SERVICE PROVIDERS LIST....4
3.1. Check()....4
3.2. Pay()....7
3.3. GetStatus()....9
3.4. GetTransactionReport()....12
3.5. GetDeposit()....14
3.6. DealerPackagesEx()....16
4. RESPONSE CODES....18
5. SALESPOINTTYPES....20
6. PAYSOURCETYPE....20

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

1. Introduction

Pay724 Core represents a solution that provides for integration of diverse service providers and payments collecting companies (dealers) all around the world within a unified software platform with one single API.

Though different service providers use different software solutions with incompatible interfaces and protocols, contradictory rules and response codes, Pay724 Core solution tries to hide most of the integration details and expose one single web-service with clear defined and described methods that can be invoked using HTTP POST requests.

In order to receive a payment from a customer to a service provider using Pay724 Core solution, a dealer needs to initialize a payment, invoking Check() method, first and then register the payment calling Pay() method.

Every dealer has a deposit opened within Pay724 system. Dealers are allowed to register payments within their deposit balance only. Before an operation starts the dealers deposit is decreased by the operation's amount When the deposit balance reaches some predefined threshold the dealer gets an e-mail notification urging to top-up the deposit. When the system finds that the operation amount is greater than the current deposit balance, Pay() method returns 008(Deposit is not enough) response code. If deposit becomes too low, 008(Deposit is not enough) is being returned by Check() method. GetDeposit() method can be used to find out the current deposit balance

Dealer is allowed to register payments using the currency of its deposit.

Every dealer has a restriction on minimum and maximum transaction amount.

Every service provider accepts payments only in one predefined currency. If the request comes with a different currency the amount is converted using Pay724 Core exchange rates. A service provider can have constraints on amount values that can be received or a predefined list of packages with fixed amounts.

Security considerations:

1. Network connection is made using ipsec vpn
2. Web-service interaction is done via https protocols
3. Every request is authorized by user credentials (username and password)

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

2. Available service providers list.

Available service providers list is in the addendum.

3. API specification

3.1. Check()

Check() method serves to verify if there is a possibility to receive a payment for the specified service provider with the specified parameters (account number, service code/package etc.) and initialize payment operation. Account number is verified only if the service provider offers such possibility. Otherwise the input parameters are validated only.
Pay() method can be invoked only after receiving successful Check() method response.

Browser: https://hostname/PaymentsService.asmx?op=Check
POST: https://hostname/PaymentsService.asmx/Check

	Parameter name	Type	Description
1.	CompanyCode	unsignedShort	Service provider code within Pay724 Core system
2.	ServiceCode	unsignedShort	Service code (0 – for undefined)
3.	Account	string	User account, bill or invoice number that identifies payment destination within service provider system
4.	Special1	string	Additional parameter 1. Depends on service provider (should be left empty by default)
5.	Special2	string	Additional parameter 2. Depends on service provider (should be left empty by default)
6.	ExternalDate	string	Request/payment date and time value in ISO8601 format (“yyyy-MM-ddTHH:mm:ss”)
7.	ExternalId	long	unique transaction or request id on the caller's side.
8.	SalesPointType	int	salespoint type where the payment is being received (one of the predefined values). By default use parameter “3”.
9.	UserName	string	Pay724 username
10.	UserPassword	string	Pay724 user password

Possible response values:

1. a) If Check(CompanyCode = 585, ServiceCode = 0, etc.) request is successfully processed the following xml is returned:

```
<PPResponse Type="Check" Key="99f5aeb8-cc24-eb11-942f-005056b219f6" Result="000"
OperationId="22718832822" Status="Successful">
        <ResultMessage>Operation was successfully completed.</ResultMessage>
        <ProviderInfo Code="585" Name="NTC" Country="524" Currency="524"
          CurrencyRate="118.000000" DealerCurrency="840">
                <ServicesList>
                <Service Id="0" Name="NTC AIRTIME" Description="NTC AIRTIME"
                />
                </ServicesList>
                <PackagesList/>
```

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

```
                    <AmountMask Min="10.00" Max="20000.00" Step="1.00" />
          </ProviderInfo>
</PPResponse>
```

where

Key – request key in Pay724 Core system,

Result – request response code (1 of the predefined values),

OperationId – operation id in Pay724 system, is meant to be passed to Pay() method call,

Status – operation status,

ResultMessage – Response description,

ProviderInfo – service provider description: `Code="585" – company ID, Name – Company name, Country – country Code, Currency – service top up currency, DealerCurrency- dealer wallet currency, CurrencyRate – rate in dealer wallet`

ServicesList – provider service description (optional), invoked in request

`PackagesList` - provider packages list (optional), corresponds to provider service, invoked in request

AmountMask – `amount limits (for Service ID = 0 only)`

`b) If Check(CompanyCode = 78, ServiceCode = 3, etc.) request is successfully processed the following xml is returned:`

```
<PPResponse Type="Check" Key="8be0a518-d124-eb11-942f-005056b219f6" Result="000"
OperationId="22719020614" Status="Successful">
      <ResultMessage>Operation was successfully completed.</ResultMessage>
      <ProviderInfo Code="78" Name="NCell" Country="524" Currency="524"
CurrencyRate="118.000000" DealerCurrency="840">
      <ServicesList>
            <Service Id="3" Name="Data Package" Description="Data Package" />
      </ServicesList>
      <PackagesList>
      <Package ServiceId="3" Name="Per_Day_300MB" Value="9899"
Description="98.99" />
      <Package ServiceId="3" Name="Per_Day_500MB" Value="49883"
Description="498.83" />
      </PackagesList>
</ProviderInfo>
</PPResponse>
```

2. If Check() validated the account number but failed service provider's check the following xml with additional AltProvidersList tag is returned

```
 <PPResponse Type="Check"  Key="c82a82bf-bd43-e311-93f8-000c29753c30"
                                  OperationId="5410400270190"
Result="009">
<ResultMessage> Account not found </ResultMessage>
<AltProvidersList>
     <Provider Id="79" Name="Moldcell" Country="498" Currency="498" />
     <Provider Id="70" Name="Unite" Country="498" Currency="498" />
     <Provider Id="71" Name="Orange" Country="498" Currency="498" />
     </AltProvidersList>
</PPResponse>
```

where

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

AltProvidersList – alternative service providers list that are advised by the system in case the customer confused the service provider (optional)

3. If Check() fails

```
<PPResponse Type="Check"  Key="c82a82bf-bd43-e311-93f8-000c29753c30"
                                    OperationId="5410400270190"
Result="001">
<ResultMessage> Technical error occured </ResultMessage>
</PPResponse>
```

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

3.2. Pay()

Pay() method is used to register a payment. Its behavior differs depending on the service provider connectivity mode (on-line, off-line, mixed etc.).

Browser: https://hostname/PaymentsService.asmx?op=Pay

POST: https://hostname/PaymentsService.asmx/Pay

	Parameter name	Type	Description
1.	CompanyCode	unsignedShort	Service provider code within Pay724 Core system
2.	ServiceCode	unsignedShort	Service code (0 – for undefined)
3.	Account	string	User account, bill or invoice number that identifies payment destination within service provider system
4.	CurrencyCode	Int	Currency number code according to ISO 4217 standard list[1]
5.	Amount	long	Payment amount in smallest units of the currency used[2]
6.	Special1	string	Additional parameter 1. Depends on service provider (should be left emhttps://oneplus.net/ro/onepty by default)
7.	Special2	string	Additional parameter 2. Depends on service provider (should be left empty by default)
8.	ExternalDate	string	Request/payment date and time value in ISO8601 format (“yyyy-MM-ddTHH:mm:ss”)
9.	ExternalId	long	unique transaction or request id on the caller's side.
10.	OperationId	long	Unique number of ongoing operation. OperationId value returned by Check() method response xml
11.	PaySourceType		Payment method used (one of the predefined valued). By default use parameter “1”.
12.	SalesPointType	int	salespoint type where the payment is being received (one of the predefined values). By default use parameter “3”.
13.	UserName	string	Pay724 username
14.	UserPassword	string	Pay724 user password

Possible response value

1. If the payment was successfully registered on-line

1 You can use the following list as a quick reference:
498 – MDL
524 – NPR
643 – RUB
840 – USD
949 – TRY
978 – EURO
980 – UAH

2 for example, you need to input 1000 for 10.00 USD or 2000 for 20.00 MDL

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

```
<PPResponse Type="Pay" Key="c46f3315-8d4d-e611-940e-001e6878ac03"
Result="000" OperationId="90935105843889" Status="Successful">
   <ResultMessage>Operation was successfully completed.</ResultMessage>
   <RegDate>2013-11-11T08:12:04.234</RegDate>
   <PaymentInfo Currency=”498” Amount=”12000”/>
   <ClearingInfo Currency=”840” Amount=”1000”/>
</PPResponse>
```

where

Key – request key in Pay724 Core system,

OperationId – operation id in Pay724 system, is meant to be passed to Pay() method call,

Result – request response code (1 of the predefined values),

RegDate – Pay724 system registration date,

Status – operation status value, one from the following list

- New = 0, / Check initialized /
- Initialized = 1, / Successful Check /
- Started = 2, / Dealer wallet decreased /
- Successful = 3, / Successful Pay /
- InQueue = 4, / Payment in queue /
- Unknown = 5, / Payment status is Unknown. Use GetStatus() method to identify transaction status /
- Closed = 6, / Payment failed /
- Cancelled = 7, / Payment canceled /
- Confirmed = 8, / Payment confirmed /
- AutoClose = 9, / Problem payment. Reconciliation needed /
- Retransmit = 10, / Resend payment /
- Repeated = 11, / Repeat payment /
- AutoRepeated = 12, / Repeat payment automatic /
- AutoUnknown = 13, / Unknown for Repeat payment /

ResultMessage – Response description,

PaymentInfo – contains amount transferred to service provider (in service provider's currency),

ClearingInfo – contains amount deducted from dealer's deposit (in dealer's currency)

The payment can be considered to be successful. No further actions needed.

Note. If Status is InQueue = 4, Unknown = 5, AutoUnknown = 13, You need to use GetStatus() method to identify transaction status.

2. If the payment was successfully added into the processing queue (off-line mode) or the payment operation is unknown and it needs to be settled manually

```
<PPResponse Type="Pay" Key="7320cff8-2346-e311-93f8-000c29753c30"
                        OperationId="5674107857121" Result="111"
Status=”InQueue”>
   <ResultMessage>Operation was successfully completed.</ResultMessage>
   <RegDate>2013-11-11T08:12:04.234</RegDate>
   <PaymentInfo Currency=”498” Amount=”12000”/>
   <ClearingInfo Currency=”840” Amount=”1000”/>
</PPResponse>
```

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

The final status of the payment can be found using GetStatus() method with corresponding OperationId value.

3. If the status of the payment operation is unknown, it needs to be reprocessed

```
<PPResponse Type="Pay" Key="7320cff8-2346-e311-93f8-000c29753c30"
                          OperationId="5674107857121" Result="011"
Status=”Unknown”>
   <ResultMessage>Pay() could not be executed. Unknown
   error.</ResultMessage>
   <RegDate>2016-10-06T12:28:18.677</RegDate>
   <PaymentInfo Currency="980" Amount="10300" />
   <ClearingInfo Currency="980" Amount="10300" />
   </PPResponse>
```

This is the case when there was some connectivity problem and the system does not have any information about final payment state. The dealer can make another Pay() method call using the same parameters.

4. If the payment could not pass due to some invalid parameters

```
<PPResponse Type="Pay" Key="7320cff8-2346-e311-93f8-000c29753c30"
                          OperationId="5674107857121" Result="016"
Status=”AutoClose”>
   <ResultMessage>Payment amount is too low.</ResultMessage>
   <RegDate>2013-11-11T08:12:04.234</RegDate>
   <PaymentInfo Currency=”498” Amount=”12000”/>
   <ClearingInfo Currency=”840” Amount=”1000”/>
</PPResponse>
```

The operation is postponed, the operation amount was not deducted from the dealer's deposit. The dealer needs to make another Pay() method using the same Operation Id and Account values providing valid values for the others. Otherwise the operation will be considered as failed and will be automatically closed when executing clearing.

5. If the payment operation failed completely

```
<PPResponse Type="Pay" Key="7320cff8-2346-e311-93f8-000c29753c30"
      OperationId="5674107857121" Result="009" Status=”Close”>
   <ResultMessage>Subscriber does not exist.</ResultMessage>
   <RegDate>2013-11-11T08:12:04.234</RegDate>
</PPResponse>
```

The operation failed. The dealer needs to correct the operation parameters and start from the new Check

6. Note: Response code DOUBLE_PAYMENT = 010 You have to consider as SUCCESS = 000

```
<PPResponse Type="Pay" Key="895c0304-3f33-e411-9408-005056b219f6"
Result="010" OperationId="31747704760977"
Status="Successful"><ResultMessage /><RegDate>2014-09-
03T10:50:10.147</RegDate><PaymentInfo Currency="498" Amount="123"
/><ClearingInfo Currency="498" Amount="123" /></PPResponse>
```

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

3.3. GetStatus()

GetStatus() method lets find out the current status of a transaction specified and get its detailed information.

Browser: https://hostname/PaymentsService.asmx?op=GetStatus

POST: https://hostname/PaymentsService.asmx/GetStatus

	Parameter name	Type	Description
1.	OperationId	long	Unique number of ongoing operation. OperationId value returned by Check() method response xml
2.	CompanyCode	unsignedShort	Service provider code within Pay724 Core system
3.	Account	String	User account, bill or invoice number that identifies payment destination within service provider system
4.	UserName	string	Pay724 username
5.	UserPassword	string	Pay724 user password

Possible response value

1. The operation was successful

```
<PPResponse Type="GetStatus" Key="7320cff8-2346-e311-93f8-000c29753c30"
Result=”000”>
   <ResultMessage>Operation was successfully completed.</ResultMessage>
   <OperationInfo>
      <OperationId>5674107857121</OperationId>
      <ExternalId>1010101</ExternalId>
      <Result>000</Result>
      <Status Code=”3”>Successful</Status>
      <Account>+37378016831</Account>
      <PaymentAmount Currency="498">1100</PaymentAmount>
      <RequestAmount Currency="498">1100</RequestAmount>
      <ClearingAmount Currency="498">1100</ClearingAmount>
      <RegDate>2013-11-11T08:12:04.234</RegDate>
      <ExternalId>100</ExternalId>
   </OperationInfo>
   <ProviderInfo Code="79" Name="Moldcell" Country="498" Currency="498"/>
</PPResponse>
```

2. The operation was not found

```
<PPResponse Type="GetStatus" Key="7320cff8-2346-e311-93f8-000c29753c30"
Result="064">
   <ResultMessage>Record not found</ResultMessage>
</PPResponse>
```

3. The operation failed

```
<PPResponse Type="GetStatus" Key="7320cff8-2346-e311-93f8-000c29753c30"
Result=”000”>
   <ResultMessage>GetStatus successfully completed</ResultMessage>
```

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

```
   <OperationInfo>
      <OperationId>5674107857121</OperationId>
      <ExternalId>1010101</ExternalId>
      <Result>000</Result>
      <Status Code=”6”>Closed</Status>
      <RegDate>2013-11-11T08:12:04.234</RegDate>
      <ExternalDate> 2013-11-11T08:11:04.873</ExternalDate>
      <Account>+37378016831</Account>
      <PaymentAmount Currency="498">1100</PaymentAmount>
      <RequestAmount Currency="498">1100</RequestAmount>
      <ClearingAmount Currency="498">1100</ClearingAmount>
      </OperationInfo>
   <ProviderInfo Code="79" Name="Moldcell" Country="498" Currency="498"/>
   <ProviderMessage>The system could not proceed with the
   operation.</ProviderMessage>
</PPResponse>
```

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

3.4. GetTransactionReport()

GetTransactionReport() method helps in payments reconciliation/cross-checking for a given period of time. Returns the list of successful operation from DateStart till DateEnd.

Browser: https://hostname/PaymentsService.asmx?op=GetTransactionReport

POST: https://hostname/PaymentsService.asmx/GetTransactionReport

	Parameter name	Type	Description
1.	DateStart	string	Report starting date and time value in ISO8601 format (“yyyy-MM-ddTHH:mm:ss”)
2.	DateEnd	string	Report end date and time value in ISO8601 format (“yyyy-MM-ddTHH:mm:ss”)
3.	UserName	string	Pay724 username
4.	UserPassword	string	Pay724 user password

Possible response values:
1. The operation was successful

```
<PPResponse Type="TransactionReport" Key="a57b9281-ea51-e311-93fa-000c29753c30"
Result="000">
    <ResultMessage>Operation was successfully completed.</ResultMessage>
    <TransactionReport>
        <Transaction Id="6966397077027" Key="d07e9894-e451-e311-93fa-
000c29753c30">
            <CompanyCode>79</CompanyCode>
            <ServiceCode>0</ServiceCode>
            <Account>+37378016831</Account>
            <RegDate>2013-11-20T15:06:39.513</RegDate>
            <RequestAmount Currency="498">1100</RequestAmount>
            <Amount Currency="498">1100</Amount>
            <ClearingAmount Currency="498">1100</ClearingAmount>
        </Transaction>
        <Transaction Id="6966400350563" Key="e07e9894-e451-e311-93fa-
000c29753c30">
            <CompanyCode>79</CompanyCode>
            <ServiceCode>0</ServiceCode>
            <Account>+37378016831</Account>
            <RegDate>2013-11-20T15:06:42.063</RegDate>
            <RequestAmount Currency="498">1100</RequestAmount>
            <Amount Currency="498">1100</Amount>
            <ClearingAmount Currency="498">1100</ClearingAmount>
        </Transaction>
        <Transaction Id="6966403000585" Key="f17e9894-e451-e311-93fa-
000c29753c30">
            <CompanyCode>79</CompanyCode>
            <ServiceCode>0</ServiceCode>
            <Account>+37378016831</Account>
            <RegDate>2013-11-20T15:06:44.547</RegDate>
            <RequestAmount Currency="498">1100</RequestAmount>
            <Amount Currency="498">1100</Amount>
            <ClearingAmount Currency="498">1100</ClearingAmount>
```

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

```
        </Transaction>
    </TransactionReport>
  </PPResponse>
```

2. No records found for the provided period

```
<PPResponse Type="TransactionReport" Key="d3fed830-ec51-e311-93fa-000c29753c30"
Result="000">
    <ResultMessage>Operation was successfully completed.</ResultMessage>
    <TransactionReport />
</PPResponse>
```

3. Authentication failed

```
<PPResponse Type="TransactionReport" Key="f3295cf1-ea51-e311-93fa-000c29753c30"
Result="003">
    <ResultMessage>Authentication failed - invalid username or password
    provided.</ResultMessage>
</PPResponse>
```

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

3.5. GetDeposit()

GetDeposit() method can be used to find our dealer's current deposit balance.

Browser: https://hostname/PaymentsService.asmx?op=GetDeposit

POST: https://hostname/PaymentsService.asmx/GetDeposit

	Parameter name	Type	Description
1.	DealerId	int	DealerId value
2.	UserName	string	Pay724 username
3.	UserPassword	string	Pay724 user password

Possible response value

1. GetDeposit() method successfully returns the current deposit balance value

```
<PPResponse Type="GetDeposit" Key="7320cff8-2346-e311-93f8-000c29753c30"
Result="000">
   <ResultMessage>Operation was successfully completed.</ResultMessage>
   <RegDate>2013-11-11T08:12:04.234</RegDate>
   <Dealer id=”1010”>
      <status code=”1”>Active</status>
      <name>Very important company</name>
      </Dealer>
   <DepositInfo Currency=”840”>101000</DepositInfo>
   </PPResponse>
```

2. GetDeposit() method fails

```
<PPResponse Type="GetDeposit" Key="0f103482-c451-e311-93fa-000c29753c30"
Result="003">
   <ResultMessage>Authentication failed - invalid username or password
   provided.</ResultMessage>
 </PPResponse>
```

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

3.6. DealerPackagesEx()

DealerPackagesEx() method can be used to find information about active countries and companies for Your dealer.

Browser: https://hostname/ManagerService.asmx?op=DealerPackagesEx

POST: https://hostname/PaymentsService/ManagerService.asmx/DealerPackagesEx

	Parameter name	Type	Description
1.	userName	string	Pay724 username
2.	userPassword	string	Pay724 password
3.	country	int	0 – for ALL
4.	companyId	int	0 – for ALL
5.	account	string	EMPTY – not used !!!

Possible response value

1. DealerPackagesEx(country = 0, companyId = 0) method successfully returns all available active countries for the dealer:

```
<PPResponse Type="DealerPackages" Key="4ce7e119-d324-eb11-942f-005056b219f6" Result="000">
                        <ResultMessage>Operation was successfully completed.</ResultMessage>
                        <CountryList>
                         <Country Id="4" Name="Afghanistan" CodePhone="93" PhoneLength="9" />
                         <Country Id="24" Name="Angola" CodePhone="244" PhoneLength="9" />
                         <Country Id="32" Name="Argentina" CodePhone="54" PhoneLength="11" />
                         <Country Id="283" Name="Armenia" CodePhone="374" PhoneLength="8" />
….
                <Country Id="524" Name="Nepal" CodePhone="977" PhoneLength="10" />
….
                <Country Id="716" Name="Zimbabwe" CodePhone="263" PhoneLength="9" />
                        </CountryList>
                </PPResponse>
```

2. DealerPackagesEx(country = 524, companyId = 0) method successfully returns the available active companies of the country (524) selected:

```
<PPResponse Type="DealerPackages" Key="cb66786d-d324-eb11-942f-005056b219f6" Result="000">
                <ResultMessage>Operation was successfully completed.</ResultMessage>
                <CountryList>
                <Country Id="524" Name="Nepal" CodePhone="977" PhoneLength="10">
                <Companies>
                <Company Id="78" Name="NCell" AccountMask="^[+]{1}977[8-9]{1}[0-9]{9}$"
AmountMax="500000" AmountMin="1000" AmountStep="1" CurrencyCode="524"
TestAccounts="+9778800000238,+9778800000239,+9779809399558">
                <Packages>
                <Package CompanyId="78" SubService="3" Name="Per_Day_300MB" DealerAmount="83"
DealerCurrencyId="840" ProviderAmount="9899" ProviderCurrencyId="524" />
                <Package CompanyId="78" SubService="3" Name="Per_Day_500MB" DealerAmount="422"
DealerCurrencyId="840" ProviderAmount="49883" ProviderCurrencyId="524" />
                <Package CompanyId="78" SubService="4" Name="S173284" DealerAmount="52"
DealerCurrencyId="840" ProviderAmount="6250" ProviderCurrencyId="524" />
                </Packages>
```

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

```
                </Company>
                <Company Id="585" Name="NTC" AccountMask="^[+]{1}9779(84|85|86|75|74)[0-9]{7}$"
AmountMax="2000000" AmountMin="1000" AmountStep="100" CurrencyCode="524"
TestAccounts="+9779849650000,+9779851076917,+9779741076917,+9779751076917">
                <Packages>
                <Package CompanyId="585" SubService="0" Name="10 NRP" DealerAmount="8"
DealerCurrencyId="840" ProviderAmount="1000" ProviderCurrencyId="524" />
                ...
                <Company Id="761" Name="Khanepani Water" AccountMask="" AmountMax="10000000"
AmountMin="1" AmountStep="1" CurrencyCode="524" TestAccounts="1212" />
                </Companies>
                </Country>
                </CountryList>
</PPResponse>
```

3. DealerPackagesEx(country = 524, companyId = 78) method successfully returns details for the country (524) and the company (78) selected:

```
<PPResponse Type="DealerPackages" Key="faa678f5-d324-eb11-942f-005056b219f6" Result="000">
<ResultMessage>Operation was successfully completed.</ResultMessage>
                <CountryList>
                <Country Id="524" Name="Nepal" CodePhone="977" PhoneLength="10">
                <Companies>
                <Company Id="78" Name="NCell" AccountMask="^[+]{1}977[8-9]{1}[0-9]{9}$"
AmountMax="500000" AmountMin="1000" AmountStep="1" CurrencyCode="524"
TestAccounts="+9778800000238,+9778800000239,+9779809399558">
                <Services>
                        <Service Id="0" Name="Prepaid" Description="Prepaid" />
                        <Service Id="1" Name="PostPaid" Description="PostPaid" />
                        <Service Id="3" Name="Data Package" Description="Data Package" />
                        <Service Id="4" Name="Voice Package" Description="Voice Package" />
                </Services>
                <Packages>
                       <Package CompanyId="78" SubService="3" Name="Per_Day_300MB" DealerAmount="83"
DealerCurrencyId="840" ProviderAmount="9899" ProviderCurrencyId="524" />
                      <Package CompanyId="78" SubService="3" Name="Per_Day_500MB" DealerAmount="422"
DealerCurrencyId="840" ProviderAmount="49883" ProviderCurrencyId="524" />
                       <Package CompanyId="78" SubService="4" Name="S173284" DealerAmount="52"
DealerCurrencyId="840" ProviderAmount="6250" ProviderCurrencyId="524" />
                </Packages>
                </Company>
                </Companies>
                </Country>
                </CountryList>
</PPResponse>
```

4. DealerPackagesEx() method fails:

```
<PPResponse Type="DealerPackages" Key="20b0dac4-d224-eb11-942f-005056b219f6"
Result="003"> <ResultMessage>AUTHENTICATION FAILED- INVALID LOGIN OR PASSWORD</
ResultMessage> </PPResponse>
```

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

4. Response codes

The list of response codes values that can be received within PAY724 CORE system

	Code	Number	
	SUCCESS	000	Operation successfully completed.
	TECHNICAL_ERROR	001	
	DATABASE_ERROR	002	
	USERNAME_OR_PASSWORD_WRONG	003	Authentication failed because wrong user name or password provided. Correct the mistake and make another request.
	OPERATION_TIME_OUT	004	Unknown
	RECORD_ALREADY_EXIST	005	
	REFERENCE_NUMBER_ALREADY_USED	006	
	UNAUTHORIZED_INSTITUTION_ERROR	007	
	NOT_ENOUGH_DEPOSIT	008	
	NOT_EXIST_SUBSCRIBER	009	
	DOUBLE_PAYMENT	010	Success
	UTILITY_COMPANY_ERROR	011	Unknown
	UTILITY_COMPANY_CONNECTION_ERROR	012	Unknown
	INVALID_INSTITUTION	013	
	INVALID_PARAMETER	014	
	NOT_ACTIVE_SUBSCRIBER	015	
	AMOUNT_TOO_LOW	016	
	AMOUNT_TOO_HIGH	017	
	NOT_FOUND_REFERENCE_NUMBER	018	
	NOT_EXIST_UTILITY_COMPANY	019	
	COMMISSION_AMOUNT_TOO_LOW	020	
	COMMISSION_AMOUNT_TOO_HIGH	021	
	SUBSCRIBER_TYPE_ERROR	022	
	AMOUNT_INPUT_CONDITIONS_ERROR	023	
	NO_PAYMENT	024	
	INQUIRY_NOT_FOUND	025	Pay request could not be completed because the corresponding Check record was not found
	SUBSCRIBER_NOT_REGISTERED	026	
	INSTITUTION_IS_PASSIVE	027	
	UTILITY_COMPANY_NOT_FOUND	028	
	SALEPOINT_TYPE_NOT_FOUND	029	
	UTILITY_COMPANY_SERVICE_NOT_FOUND	030	
	SALEPOINT_TYPE_NOT_MATCH	039	
	DEALER_AMOUNT_TOO_LOW	031	
	DEALER_AMOUNT_TOO_HIGH	032	

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

	Code	Number	
	NOT_ENOUGH_USER_DEPOSIT	048	
	NOT_FOUND_RECORD	064	
	OPERATION_FORBIDDEN	068	Unknown
	USER_IS_BLOCKED	069	Authentication failed – user was blocked. Please contact the manager for more details.
	SUSPECIOUS_PAYMENT_OPERATION	099	
	CRITICAL_ERROR	100	
	REQUEST_IN_QUEUE	111	Request was successfully added to the payment queue.
	CURRENCY_RATES_NOT_AVAILABLE	201	Operation could not be completed because necessary currency rates were not properly set.
	OPERATION_STATUS_CONFLICT	202	Pay request could not be completed because the operation conflict was detected.
	INVALID_ACCOUNT_PARAM	210	Invalid account value provided for Check(), Pay() or GetStatus() methods.
	INVALID_EXTERNAL_DATE_PARAM	211	Invalid ExternalDate value provided for Check() or Pay() methods. Please, check if it corresponds to the ISO8601 format (“yyyy-MM-ddTHH:mm:ss”).
	UNKNOWN_ERROR	600	
	UTILITY_COMPANY_CRITICAL_ERROR	601	
	PROVIDER_CRITICAL_ERROR	602	
	UTILITY_COMPANY_TECHNICAL_ERROR	603	
	SYSTEM_IS_NOT_AVAILABLE	606	The System is temporarily not available (may be when system is turned off). Please, try later.

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

5. Salespointtypes

The list of salespointtype values that can be used within PAY724 CORE system

	Code	Description	Notes
	3	Integrator	Payments, coming through integrator partners
	32	WEB	Payments, received through a web-site
	33	internal IT solution	Payments, registered in a partners internal system integrated with PAY724 CORE API
	34	POS	Payments, registered in POS-devices
	35	Kiosk	Payments, received through self-service kioks
	36	mobile app	Payments, received through a mobile application

6. PaySourceType

The list of PaySourceType values that can be used within PAY724 CORE system

	Code	Description	Notes
	1	Cash	
	2	Credit card	
	3	PayPal	
	4	WebMoney	

© 2014 UNIPAY DANISMANLIK YAZILIM TEKNOLOJILERI LTD./ CONFIDENTIAL

7. Addendum

Packages' Specification

1. Check() According to main Check Method Specification

Check() method serves to verify if there is a possibility to receive a payment for the specified service provider with the specified parameters (account number, service code/package etc.) and initialize payment operation. Account number is verified only if the service provider offers such possibility. Otherwise the input parameters are validated only.
Pay() method can be invoked only after receiving successful Check() method response.

	Parameter name	Code
1.	CompanyCode	78
2.	ServiceCode	Service id see table 1
3.	Account	String , test +9779809399558
4.	Special1	PRODUCT CODE, from table 1
5.	Special2	empty
6.	ExternalDate	`yyyy-MM-ddTHH:mm:ss`
7.	ExternalId	long
8.	SalesPointType	3
9.	UserName	string
10.	UserPassword	string

2. Pay() According to main Pay Method Specification

Pay() method is used to register a payment.

	Parameter name	Type
1.	CompanyCode	78
2.	ServiceCode	Service id see table 1
3.	Account	String, test +9779809399558
4.	CurrencyCode	524
5.	Amount	Long PRICE, from table 1
6.	Special1	PRODUCT CODE, from table 1
7.	Special2	empty
8.	ExternalDate	`yyyy-MM-ddTHH:mm:ss`
9.	ExternalId	long
10.	OperationId	long
11.	PaySourceType	1
12.	SalesPointType	3
13.	UserName	string
14.	UserPassword	string

TABLE 1. NCell Data Service Package list.

For Testbed:

	SERVICE CODE	PRODUCT CODE	PRICE	Description
1.	3	Per_Day_300 MB	98.99 Rs	Get 300MB All-time data every day for 7 days
2.	3	Per_Day_500 MB	498.83 Rs	Get 500MB All-time data every day for 30 days

TABLE 1. NCell Voice Service Package list.

For For Testbed:

	SERVICE CODE	PRODUCT CODE	PRICE	Description
1.	4	S173284	62.50 Rs	75 min weekly voice pack

TABLE 1. NTC Data Service Package list.

For Testbed:

	SERVICE CODE	PRODUCT CODE	PRICE	Description
1.	10	1	100.00 Rs	TEST PACKAGE

TABLE 1. NTC Voice Service Package list.

For Testbed:

	SERVICE CODE	PRODUCT CODE	PRICE	Description
1.	11	1	100.00 Rs	TEST PACKAGE

TABLE 1. NTC Recommended (**Voice/SMS/Data**) Service Package list.

For Testbed:

	SERVICE CODE	PRODUCT CODE	PRICE	Description
1.	12	1	100.00 Rs	TEST PACKAGE