

There are 2 stages where error may happen in a program

- During compilation -> Syntax Error
- During execution -> Exceptions

▼ Syntax Error

- Something in the program is not written according to the program grammar.
- Error is raised by the interpreter/compiler
- You can solve it by rectifying the program

```
# Examples of syntax error
print 'hello world'
```

```
File "<ipython-input-3-4655b84ba7b7>", line 2
    print 'hello world'
      ^
```

SyntaxError: Missing parentheses in call to 'print'. Did you mean print('hello world')?

SEARCH STACK OVERFLOW

▼ Other examples of syntax error

- Leaving symbols like colon, brackets
- Misspelling a keyword
- Incorrect indentation
- empty if/else/loops/class/functions

```
a = 5
if a==3
    print('hello')
```

```
File "<ipython-input-68-efc58c10458d>", line 2
    if a==3
      ^
```

SyntaxError: invalid syntax

SEARCH STACK OVERFLOW

```
a = 5
iff a==3:
    print('hello')
```

```
File "<ipython-input-69-d1e6fae154d5>", line 2
```

```
    iff a==3:
```

```
        ^
```

```
SyntaxError: invalid syntax
```

SEARCH STACK OVERFLOW

```
a = 5
```

```
if a==3:
```

```
    print('hello')
```

```
File "<ipython-input-70-ccc702dc036c>", line 3
```

```
    print('hello')
```

```
        ^
```

```
IndentationError: expected an indented block
```

SEARCH STACK OVERFLOW

```
# IndexError
```

```
# The IndexError is thrown when trying to access an item at an invalid index.
```

```
L = [1,2,3]
```

```
L[100]
```

```
-----  
IndexError                                Traceback (most recent call last)
```

```
<ipython-input-71-c90668d2b194> in <module>
```

```
    2 # The IndexError is thrown when trying to access an item at an invalid index.
```

```
    3 L = [1,2,3]
```

```
----> 4 L[100]
```

```
IndexError: list index out of range
```

SEARCH STACK OVERFLOW

```
# ModuleNotFoundError
```

```
# The ModuleNotFoundError is thrown when a module could not be found.
```

```
import mathi
```

```
math.floor(5.3)
```

```
-----  
ModuleNotFoundError                                Traceback (most recent call last)  
<ipython-input-73-cbdaf00191df> in <module>  
      1 # ModuleNotFoundError  
      2 # The ModuleNotFoundError is thrown when a module could not be found.  
----> 3 import math  
      4 math.floor(5.3)
```

KeyError

The KeyError is thrown when a key is not found

```
d = {'name': 'nitish'}  
d['age']
```

```
-----  
KeyError                                           Traceback (most recent call last)  
<ipython-input-74-453afa1c9765> in <module>  
      3  
      4 d = {'name': 'nitish'}  
----> 5 d['age']
```

KeyError: 'age'

SEARCH STACK OVERFLOW

TypeError

The TypeError is thrown when an operation or function is applied to an object of an inappropriate type.
1 + 'a'

```
-----  
TypeError                                           Traceback (most recent call last)  
<ipython-input-78-2a3eb3f5bb0a> in <module>  
      1 # TypeError  
      2 # The TypeError is thrown when an operation or function is applied to an object  
inappropriate type.  
----> 3 1 + 'a'
```

TypeError: unsupported operand type(s) for +: 'int' and 'str'

SEARCH STACK OVERFLOW

ValueError

The ValueError is thrown when a function's argument is of an inappropriate type.
int('a')

```
-----
ValueError                                Traceback (most recent call last)
<ipython-input-76-e419d2a084b4> in <module>
```

```
# NameError
```

```
# The NameError is thrown when an object could not be found.
```

```
print(k)
```

```
-----
NameError                                Traceback (most recent call last)
<ipython-input-79-e3e8aaa4ec45> in <module>
      1 # NameError
      2 # The NameError is thrown when an object could not be found.
----> 3 print(k)
```

```
NameError: name 'k' is not defined
```

SEARCH STACK OVERFLOW

```
# AttributeError
```

```
L = [1,2,3]
```

```
L.upper()
```

```
# Stacktrace
```

```
-----
AttributeError                            Traceback (most recent call last)
<ipython-input-80-dd5a29625ddc> in <module>
      1 # AttributeError
      2 L = [1,2,3]
----> 3 L.upper()
```

```
AttributeError: 'list' object has no attribute 'upper'
```

SEARCH STACK OVERFLOW

▼ Exceptions

If things go wrong during the execution of the program(runtime). It generally happens when something unforeseen has happened.

- Exceptions are raised by python runtime
- You have to take it on the fly

Examples

- Memory overflow
- Divide by 0 -> logical error
- Database error

```
# Why is it important to handle exceptions
# how to handle exceptions
# -> Try except block
```

```
# let's create a file
with open('sample.txt','w') as f:
    f.write('hello world')
```

```
# try catch demo
try:
    with open('sample1.txt','r') as f:
        print(f.read())
except:
    print('sorry file not found')
```

```
    sorry file not found
```

```
# catching specific exception
try:
    m=5
    f = open('sample1.txt','r')
    print(f.read())
    print(m)
    print(5/2)
    L = [1,2,3]
    L[100]
except FileNotFoundError:
    print('file not found')
except NameError:
    print('variable not defined')
except ZeroDivisionError:
    print("can't divide by 0")
except Exception as e:
    print(e)
```



[Errno 2] No such file or directory: 'sample1.txt'

```
# else
try:
    f = open('sample1.txt','r')
except FileNotFoundError:
    print('file nai mili')
except Exception:
    print('kuch to lafda hai')
else:
    print(f.read())
```

```

file nai mili

# finally
# else
try:
    f = open('sample1.txt','r')
except FileNotFoundError:
    print('file nai mili')
except Exception:
    print('kuch to lafda hai')
else:
    print(f.read())
finally:
    print('ye to print hoga hi')

file nai mili
ye to print hoga hi

```

```

# raise Exception
# In Python programming, exceptions are raised when errors occur at runtime.
# We can also manually raise exceptions using the raise keyword.

```

```

# We can optionally pass values to the exception to clarify why that exception was raised

```

```

raise ZeroDivisionError('aise hi try kar raha hu')
# Java
# try -> try
# except -> catch
# raise -> throw

```

```

-----
ZeroDivisionError                                Traceback (most recent call last)
<ipython-input-106-5a07d7d89433> in <module>
----> 1 raise ZeroDivisionError('aise hi try kar raha hu')

ZeroDivisionError: aise hi try kar raha hu

```

SEARCH STACK OVERFLOW

```

class Bank:

    def __init__(self,balance):
        self.balance = balance

    def withdraw(self,amount):
        if amount < 0:
            raise Exception('amount cannot be -ve')
        if self.balance < amount:

```

```
        raise Exception('paise nai hai tere paas')
    self.balance = self.balance - amount
```

```
obj = Bank(10000)
try:
    obj.withdraw(15000)
except Exception as e:
    print(e)
else:
    print(obj.balance)

    paise nai hai tere paas
```

```
class MyException(Exception):
    def __init__(self,message):
        print(message)
```

```
class Bank:

    def __init__(self,balance):
        self.balance = balance

    def withdraw(self,amount):
        if amount < 0:
            raise MyException('amount cannot be -ve')
        if self.balance < amount:
            raise MyException('paise nai hai tere paas')
        self.balance = self.balance - amount
```

```
obj = Bank(10000)
try:
    obj.withdraw(5000)
except MyException as e:
    pass
else:
    print(obj.balance)

    5000
```

```
# creating custom exceptions
# exception hierarchy in python
```

```
# simple example
```

```
class SecurityError(Exception):
```

```
def __init__(self,message):
    print(message)

def logout(self):
    print('logout')

class Google:

    def __init__(self,name,email,password,device):
        self.name = name
        self.email = email
        self.password = password
        self.device = device

    def login(self,email,password,device):
        if device != self.device:
            raise SecurityError('bhai teri to lag gayi')
        if email == self.email and password == self.password:
            print('welcome')
        else:
            print('login error')

obj = Google('nitish','nitish@gmail.com','1234','android')

try:
    obj.login('nitish@gmail.com','1234','windows')
except SecurityError as e:
    e.logout()
else:
    print(obj.name)
finally:
    print('database connection closed')
```

```
bhai teri to lag gayi
logout
database connection closed
```


[Colab paid products](#) - [Cancel contracts here](#)

