


Data Augmentation, and Auto-Encoders

B.Tech. Data Science, Second Year, NMIMS

By,

Bilal Hungund, Data Scientist, Halliburton



Convolution & operation

0	1	0	1	0	1
0	1	0	1	0	1
0	1	0	1	0	1
0	1	0	1	0	1
0	1	0	1	0	1
0	1	0	1	0	1

6x6 image

Filter (Weights)

-1	1	-1
2	3	2
1	1	1

3x3 Filter

$$n - f + 1$$

$$= 6 - 3 + 1$$

$$= 4$$

Output Size

4	4	4	4
4
:	:	:	:
:	:	:	:

4x4



Output without padding

Stride = 1
(step size)

With Padding

0	0	0	1	1	1
0	0	0	1	1	1
0	0	0	1	1	1
0	0	0	1	1	1
0	0	0	1	1	1
0	0	0	1	1	1

4x4 $\xrightarrow{\text{padding}}$ 6x6

Padding

Filter

1	-1
1	-1



4x4

Pooling

25	48	11	58
192	10	20	110
38	0	9	31
50	8	23	47

Stride = 2
(Recommended
for Pooling)

25	48
192	10

11	58
20	110

Pooling
⇒

38	0
50	8

9	31
23	47

Max Pooling



192	110
50	47


69	50
22	28

Average Pooling

Backpropagation in CNN

Convolution Neural Network (CNN) for Classification

 `tf.keras.layers.Conv2D`
 `tf.keras.activations.*`
 `tf.keras.layers.MaxPool2D`



- 1) Convolution: Filters to generate feature maps
- 2) Non-linearity: often relu
- 3) Backpropagation
- 4) Pooling: Downsampling feature maps

Image Augmentation

- Simple and powerful tool to help you avoid overfitting
- If data and its scope is limited then chance of potential future prediction is also limited
- Example: You have a dataset of cats but in testing set you have a cat lying down. Thus making difficult for model to recognize
Solution: Rotating the images

TensorFlow Image Data Generator

→ rotation_range [0 - 180°]

→ width_shift_range
height_shift_range } shifting [0 - 1]
portion of shifting

→ shear_range [0 - 1]

→ zoom_range [0 - 1]

→ horizontal_flip [True, False]

(rescale, fill_mode)

Auto-Encoders


- It is a special type of neural network architectures in which the output is same as the input.
- It is trained in an unsupervised manner in order to learn extremely low representations of an input data.
- These low level features are deformed back to its actual data.
- It is a regression task where the network is asked to predict its input (model identity function).

Auto - Encoders architecture

Encoding architecture: It comprises series of layers with decreasing number of nodes and ultimately reduces to a latent view representation

Latent View Representation: It represents the lowest level space in which the inputs are reduced and information preserved.

Decoding architecture: It is the mirror image of the encoder but in which number of nodes in every layer increases and ultimately outputs the similar (almost) input.



Encoders $z = f(Wx + b)$

Decoders $\hat{x} = f'(W'z + b)$

Loss $L(x, \hat{x}) = |x - \hat{x}|$

Use cases

- Image Reconstruction
- Image Enhancement
- Image Compression
- Image Denoising
- Feature Extraction
- Binary Classification

References

- <https://towardsdatascience.com/understanding-variational-autoencoders-vaes-f70510919f73>
- <https://medium.com/analytics-vidhya/mathematical-prerequisites-for-understanding-autoencoders-and-variational-autoencoders-vaes-8f854025390e>