

oracle tp 5

Partie 1:

1-

a-

```
SQL> select tablespace_name from dba_tablespaces  
2 ;
```

TABLESPACE_NAME

SYSTEM
SYSAUX
UNDOTBS1
TEMP
USERS

b-

```
SQL> select tablespace_name,extent_management from dba_tablespaces;
```

TABLESPACE_NAME	EXTENT_MAN
-----------------	------------

SYSTEM	LOCAL
SYSAUX	LOCAL
UNDOTBS1	LOCAL
TEMP	LOCAL
USERS	LOCAL

c-

```
SQL> select tablespace_name,status from dba_tablespaces;
```

TABLESPACE_NAME	STATUS
-----------------	--------

SYSTEM	ONLINE
SYSAUX	ONLINE
UNDOTBS1	ONLINE
TEMP	ONLINE
USERS	ONLINE

d-

```
SQL> select tablespace_name,contents from dba_tablespaces;
```

TABSPACE_NAME	CONTENTS
SYSTEM	PERMANENT
SYS_AUX	PERMANENT
UNDOTBS1	UNDO
TEMP	TEMPORARY
USERS	PERMANENT

2-

a-

```
SQL> SELECT FILE_NAME, TABLESPACE_NAME FROM DBA_DATA_FILES;
```

FILE_NAME	TABSPACE_NAME
C:\ORACLE\APP\ORACLE\ORADATA\XE\USERS.DBF	USERS
C:\ORACLE\APP\ORACLE\ORADATA\XE\SYS_AUX.DBF	UNDOTBS1
C:\ORACLE\APP\ORACLE\ORADATA\XE\UNDOTBS1.DBF	SYS_AUX

FILE_NAME	TABSPACE_NAME
C:\ORACLE\APP\ORACLE\ORADATA\XE\SYSTEM.DBF	SYSTEM

b-

```
SQL> SELECT TABLESPACE_NAME, EXTENT_MANAGEMENT FROM DBA_TABLESPACES;
```

TABSPACE_NAME	EXTENT_MAN
SYSTEM	LOCAL
SYS_AUX	LOCAL
UNDOTBS1	LOCAL
TEMP	LOCAL
USERS	LOCAL

```
SQL> SELECT TABLESPACE_NAME, STATUS FROM DBA_TABLESPACES;
```

TABLESPACE_NAME	STATUS
SYSTEM	ONLINE
SYSAUX	ONLINE
UNDOTBS1	ONLINE
TEMP	ONLINE
USERS	ONLINE

c-

```
SQL> SELECT TABLESPACE_NAME, CONTENTS FROM DBA_TABLESPACES;
```

TABLESPACE_NAME	CONTENTS
SYSTEM	PERMANENT
SYSAUX	PERMANENT
UNDOTBS1	UNDO
TEMP	TEMPORARY
USERS	PERMANENT

b-

2-

a-

```
SQL> SELECT FILE_NAME, TABLESPACE_NAME FROM DBA_DATA_FILES;
```

FILE_NAME	TABLESPACE_NAME
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\USERS.DBF	USERS
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\SYSAUX.DBF	UNDOTBS1
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\UNDOTBS1.DBF	SYSAUX
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\SYSTEM.DBF	SYSTEM

b-

```
SQL> SELECT FILE_NAME, ROUND(BYTES/1024/1024, 2) AS SIZE_MB FROM DBA_DATA_FILES;
```

```
FILE_NAME
```

```
SIZE_MB
```

```
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\USERS.DBF  
100
```

```
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\SYSAUX.DBF  
25
```

```
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\UNDOTBS1.DBF  
690
```

```
FILE_NAME
```

```
SIZE_MB
```

```
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\SYSTEM.DBF
```

C-

```
SQL> SELECT FILE_NAME, STATUS FROM DBA_DATA_FILES;
```

```
FILE_NAME
```

```
STATUS
```

```
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\USERS.DBF  
AVAILABLE
```

```
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\SYSAUX.DBF  
AVAILABLE
```

```
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\UNDOTBS1.DBF  
AVAILABLE
```

```
FILE_NAME
```

```
STATUS
```

```
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\SYSTEM.DBF  
AVAILABLE
```

3-

a-

```
SQL> SELECT NAME FROM V$DATAFILE;
```

```
NAME
```

```
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\SYSTEM.DBF  
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\UNDOTBS1.DBF  
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\SYSAUX.DBF  
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\USERS.DBF
```

```
SQL> |
```

b-

```
SQL> SELECT NAME, ROUND(BYTES/1024/1024, 2) AS SIZE_MB FROM V$DATAFILE;
```

```
NAME
```

```
-----  
SIZE_MB
```

```
-----  
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\SYSTEM.DBF  
360
```

```
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\UNDOTBS1.DBF  
690
```

```
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\SYSAUX.DBF  
25
```

```
NAME
```

```
-----  
SIZE_MB
```

```
-----  
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\USERS.DBF  
100
```

C-

```
SQL> SELECT NAME, STATUS FROM V$DATAFILE;
```

```
NAME
```

```
-----  
STATUS
```

```
-----  
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\SYSTEM.DBF  
SYSTEM
```

```
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\UNDOTBS1.DBF  
ONLINE
```

```
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\SYSAUX.DBF  
ONLINE
```

```
NAME
```

```
-----  
STATUS
```

```
-----  
C:\ORACLEXE\APP\ORACLE\ORADATA\XE\USERS.DBF  
ONLINE
```

4-

Permanent:

```
SQL> SELECT PROPERTY_VALUE FROM DATABASE_PROPERTIES  
2 WHERE PROPERTY_NAME = 'DEFAULT_PERMANENT_TABLESPACE';
```

```
PROPERTY_VALUE
```

```
-----  
SYSTEM
```

Temporary:

```
SQL> SELECT PROPERTY_VALUE FROM DATABASE_PROPERTIES
2 WHERE PROPERTY_NAME = 'DEFAULT_TEMP_TABLESPACE';
```

PROPERTY_VALUE

TEMP

SQL> |

Partie 2:

1-

```
SQL> CREATE TABLESPACE lbstest DATAFILE 'C:\tbstest01.dbf' SIZE 5M AUTOEXTEND ON NEXT 1M MAXSIZE 50M EXTENT MANAGEMENT LOCAL AUTOALLOCATE;
```

Tablespace created.

2-

```
SQL> SELECT TABLESPACE_NAME, STATUS, CONTENTS, EXTENT_MANAGEMENT
2 FROM DBA_TABLESPACES
3 WHERE TABLESPACE_NAME = 'LBSTEST';
```

TABLESPACE_NAME	STATUS	CONTENTS	EXTENT_MAN
LBSTEST	ONLINE	PERMANENT	LOCAL

SQL>

```
SQL> SELECT FILE_NAME, BYTES, AUTOEXTENSIBLE, MAXBYTES
2 FROM DBA_DATA_FILES
3 WHERE TABLESPACE_NAME = 'LBSTEST';
```

FILE_NAME

FILE_NAME	BYTES	AUT	MAXBYTES
C:\TBSTEST01.DBF	5242880	YES	52428800

3-

```
SQL> ALTER TABLESPACE lbstest ADD DATAFILE 'C:\tbstest02.dbf' SIZE 10M AUTOEXTEND OFF;
```

Tablespace altered.

4-

```
SQL> SELECT TABLESPACE_NAME, SUM(BYTES)/1024/1024 AS TOTAL_MB
2 FROM DBA_DATA_FILES
3 WHERE TABLESPACE_NAME = 'LBSTEST'
4 GROUP BY TABLESPACE_NAME;
```

TABLESPACE_NAME	TOTAL_MB
LBSTEST	15

```
SQL> ALTER DATABASE DATAFILE 'C:\tbstest01.dbf' RESIZE 15M;
```

```
Database altered.
```

5-

6-

```
SQL> ALTER DATABASE DATAFILE 'C:\tbstest02.dbf' AUTOEXTEND ON NEXT 2M MAXSIZE 30M;
```

```
Database altered.
```

```
SQL> ALTER TABLESPACE lbstest RENAME TO tbstest1;
```

```
Tablespace altered.
```

```
SQL>
```

```
SQL> DROP TABLESPACE tbstest1 INCLUDING CONTENTS AND DATAFILES;
```

```
Tablespace dropped.
```

7-10

11-

```
SQL> SELECT VALUE FROM V$PARAMETER WHERE NAME = 'db_block_size';
```

```
VALUE
```

```
-----  
8192
```

```
SQL> CREATE TABLESPACE tbstest2
```

```
2 DATAFILE 'C:\tbstest201.dbf' SIZE 10M
```

```
3 AUTOEXTEND ON NEXT 1M MAXSIZE 30M
```

```
4 EXTENT MANAGEMENT LOCAL UNIFORM SIZE 128K;
```

```
Tablespace created.
```

12-

13-16

```
SQL> -- Attempt to drop (will fail)
```

```
SQL> DROP TABLESPACE tempo;
```

```
DROP TABLESPACE tempo
```

```
*
```

```
ERROR at line 1:
```

```
ORA-12906: cannot drop default temporary tablespace
```

```
SQL>
```

```
SQL> -- Solution:
```

```
SQL> ALTER DATABASE DEFAULT TEMPORARY TABLESPACE temp;
```

```
Database altered.
```

```
SQL> DROP TABLESPACE tempo INCLUDING CONTENTS AND DATAFILES;
```

```
Tablespace dropped.
```

Partie 3:

1-

```
SQL> SELECT SEGMENT_NAME, TABLESPACE_NAME, EXTENTS, BLOCKS  
2 FROM DBA_SEGMENTS  
3 WHERE OWNER = 'SCOTT';
```

no rows selected

```
SQL> SELECT * FROM DBA_EXTENTS  
2 WHERE SEGMENT_NAME = 'EMP' AND OWNER = 'SCOTT';
```

no rows selected

2-

```
SQL> SELECT TABLESPACE_NAME, SUM(BYTES)/1024 AS FREE_KB  
2 FROM DBA_FREE_SPACE  
3 GROUP BY TABLESPACE_NAME  
4 ORDER BY FREE_KB;
```

TABLESPACE_NAME	FREE_KB
SYSTEM	7488
TBTEST2	9216
UNDOTBS1	20736
SYSAUX	39296
USERS	99776

3-

scripts:


```

SQL> PROMPT Espace libre par tablespace
Espace libre par tablespace
SQL> SET LINESIZE 100
SQL> SET PAGESIZE 100
SQL> COLUMN "Tablespace" FORMAT A20
SQL> COLUMN "Octets libres" FORMAT 999,999,999
SQL>
SQL> SELECT TABLESPACE_NAME "Tablespace",
  2          SUM(BYTES) "Octets libres"
  3 FROM DBA_FREE_SPACE
  4 GROUP BY TABLESPACE_NAME
  5 ORDER BY 2 ASC;

```

Tablespace	Octets libres
SYSTEM	7,667,712
TBTEST2	9,437,184
UNDOTBS1	21,233,664
SYSAUX	40,239,104
USERS	102,170,624

```

SQL> PROMPT Objets de l'usager &1
Enter value for 1: SET LINESIZE 120
Objets de l'usager SET LINESIZE 120
SQL> SET PAGESIZE 100
SQL> COLUMN "Objets appartenant à &1" FORMAT A40
Enter value for 1: COLUMN "Type" FORMAT A10
SP2-0158: unknown COLUMN option "Type"
SQL> COLUMN "noLigne" FORMAT 999
SQL>
SQL> SELECT OBJECT_NAME "Objets appartenant à &1",
  2          OBJECT_TYPE "Type",
  3          ROWNUM "noLigne"
  4 FROM DBA_OBJECTS
  5 WHERE OWNER = UPPER('&1')
  6 AND OBJECT_TYPE IN ('TABLE', 'INDEX')
  7 AND ROWNUM <= &2
  8 ORDER BY OBJECT_NAME;
Enter value for 1: 1
old  1: SELECT OBJECT_NAME "Objets appartenant à &1",
new  1: SELECT OBJECT_NAME "Objets appartenant à 1",
Enter value for 1: 100
old  5: WHERE OWNER = UPPER('&1')
new  5: WHERE OWNER = UPPER('100')
Enter value for 2: 5
old  7: AND ROWNUM <= &2
new  7: AND ROWNUM <= 5

no rows selected

```

