Practical no . 3 : FILE HANDLING COMMANDS

Aim : to use file system and file handling commands

Touch

This command is use to make and write into it .

```
vboxuser@bilal:~$ touch bilalpatel
vboxuser@bilal:~$ ls
abc.text  bilal  bilalpatel  Desktop  Documents  Downloads  Music  Pictures  Public  snap  Templates  Videos
vboxuser@bilal:~$
```

Help

This command is use to display the info about help option.

```
vboxuser@bilal:~$ help
GNU bash, version 5.2.21(1)-release (x86_64-pc-linux-gnu)
These shell commands are defined internally.  Type `help' to see this list.
Type `help name' to find out more about the function `name'.
Use `info bash' to find out more about the shell in general.
Use `man -k' or `info' to find out more about commands not in this list.

A star (*) next to a name means that the command is disabled.

 job_spec [&]                                          history [-c] [-d offset] [n] or history -anrw [filename]>
 (( expression ))                                      if COMMANDS; then COMMANDS; [ elif COMMANDS; then COMMAN>
 . filename [arguments]                                jobs [-lnprs] [jobspec ...] or jobs -x command [args]
 :                                                     kill [-s sigspec | -n signum | -sigspec] pid | jobspec .>
 [ arg... ]                                            let arg [arg ...]
 [[ expression ]]                                      local [option] name[=value] ...
 alias [-p] [name[=value] ... ]                        logout [n]
 bg [job_spec ...]                                     mapfile [-d delim] [-n count] [-O origin] [-s count] [-t>
 bind [-lpsvPSVX] [-m keymap] [-f filename] [-q name] [-u >  popd [-n] [+N | -N]
 break [n]                                             printf [-v var] format [arguments]
 builtin [shell-builtin [arg ...]]                     pushd [-n] [+N | -N | dir]
 caller [expr]                                         pwd [-LP]
 case WORD in [PATTERN [| PATTERN]...) COMMANDS ;;]... esa>  read [-ers] [-a array] [-d delim] [-i text] [-n nchars] >
 cd [-L|[-P [-e]] [-@]] [dir]                          readarray [-d delim] [-n count] [-O origin] [-s count] [>
 command [-pVv] command [arg ...]                      readonly [-aAf] [name[=value] ...] or readonly -p
 compgen [-abcdefgjksuv] [-o option] [-A action] [-G globp>  return [n]
```

man

- This command displays the manual of the software

```
MAN(1)                                   Manual pager utils                                   MAN(1)

NAME
       man - an interface to the system reference manuals

SYNOPSIS
       man [man options] [[section] page ...] ...
       man -k [apropos options] regexp ...
       man -K [man options] [section] term ...
       man -f [whatis options] page ...
       man -l [man options] file ...
       man -w|-W [man options] page ...

DESCRIPTION
       man  is the system's manual pager.  Each page argument given to man is normally the name of a program, utility
       or function.  The manual page associated with each of these arguments is then found and displayed.  A section,
       if provided, will direct man to look only in that section of the manual.  The default action is to  search  in
       all  of  the  available sections following a pre-defined order (see DEFAULTS), and to show only the first page
       found, even if page exists in several sections.

       The table below shows the section numbers of the manual followed by the types of pages they contain.

       1   Executable programs or shell commands
       2   System calls (functions provided by the kernel)
       3   Library calls (functions within program libraries)
       4   Special files (usually found in /dev)
       5   File formats and conventions, e.g. /etc/passwd
       6   Games
       7   Miscellaneous (including macro packages and conventions), e.g. man(7), groff(7), man-pages(7)
       8   System administration commands (usually only for root)
       9   Kernel routines [Non standard]
 Manual page man(1) line 1 (press h for help or q to quit)
```

4 more —help

- Show more

```
vboxuser@bilal:~$ more --help

Usage:
 more [options] <file>...

Display the contents of a file in a terminal.

Options:
 -d, --silent          display help instead of ringing bell
 -f, --logical         count logical rather than screen lines
 -l, --no-pause        suppress pause after form feed
 -c, --print-over      do not scroll, display text and clean line ends
 -p, --clean-print     do not scroll, clean screen and display text
 -e, --exit-on-eof     exit on end-of-file
 -s, --squeeze         squeeze multiple blank lines into one
 -u, --plain           suppress underlining and bold
 -n, --lines <number>  the number of lines per screenful
 -<number>             same as --lines
 +<number>             display file beginning from line number
 +/<pattern>           display file beginning from pattern match
```

pwd

This commands prints the current working directory

```
vboxuser@bilal:~$ pwd patelbilal
/home/vboxuser
vboxuser@bilal:~$
```

cd

Change directory

```
vboxuser@bilal:~$ cd patelbilal
vboxuser@bilal:~/patelbilal$
```

mkdir

Thus commands creates a new directory

```
vboxuser@bilal:~$ mkdir patelbilal
vboxuser@bilal:~$ ls
abc.text  bilalpatel  Desktop  Documents  Downloads  Music  patelbilal
vboxuser@bilal:~$
```

rmdir

This commands removes a directory

```
vboxuser@bilal:~/patelbilal$ rmdir patelbilal
vboxuser@bilal:~/patelbilal$
```

9) ls

- Displays all the documents in the directory

```
vboxuser@bilal:~$ mkdir patelbilal
vboxuser@bilal:~$ ls
abc.text  bilalpatel  Desktop  Documents  Downloads  Music  patelbilal
vboxuser@bilal:~$
```

```
vboxuser@bilal:~$ cat >patelbilal
bash: patelbilal: Is a directory
vboxuser@bilal:~$ cat -n patelbilal
cat: patelbilal: Is a directory
vboxuser@bilal:~$ cat patelbilal
cat: patelbilal: Is a directory
vboxuser@bilal:~$ od patelbilal
od: patelbilal: Is a directory
0000000
vboxuser@bilal:~$ wc patelbilal
wc: patelbilal: Is a directory
      0       0       0 patelbilal
vboxuser@bilal:~$ od -b patelbilal
od: patelbilal: Is a directory
0000000
vboxuser@bilal:~$ od -t patelbilal
od: invalid character 'p' in type string ‘patelbilal’
vboxuser@bilal:~$ od -c patelbilal
od: patelbilal: Is a directory
0000000
vboxuser@bilal:~$ od -x patelbilal
od: patelbilal: Is a directory
0000000
vboxuser@bilal:~$ file patelbilal
patelbilal: directory
vboxuser@bilal:~$
```