

HW8.2. Parallelism Principles

The Hamming distance between two bitstrings of equal length is the number of locations in which the bits differ. For example, `hamming(0b1011101, 0b1001001) == 2`.

Consider the following implementation of `Hamming`:

```
uint32_t hamming(uint32_t x, uint32_t y) {
    uint32_t mask, ham_dist = 0;
    #pragma omp for
    for (int i = 0; i <= 31; i++) {
        mask = 1 << i;
        if ((y & mask) != (x & mask))
            ham_dist++;
    }
    return ham_dist;
}
```

Q1: For each variable, determine if it can be made shared, or must be private in order for the above code to work properly. Note that we generally prefer to use shared variables when possible.

Q1.1: `x`

☒ shared

☐ private

Q1.2: `y`

☒ shared

☐ private

Q1.3: `mask`

☐ shared

☒ private

Q1.4: `i`

☐ shared

☒ private

Q1.5: Is a data race possible on any variable that must be shared? If so, what variables cause the data race?

☐ (a) `x`

☐ (b) `y`

☐ (c) `mask`

☐ (d) `i`

☒ (e) `ham_dist`

☐ (f) A data race is not possible

Select all possible options that apply.

Try a new variant

Homework 8

Assessment overview

Total points: 30/100

Score: 30%

Question

Value: 10

History: 10

Awarded points: 10/10

Report an error in this question

Previous question

Next question

Attached files

No attached files

Attach a file

Attach text

Correct answer

Q1: For each variable, determine if it can be made shared, or must be private in order for the above code to work properly. Note that we generally prefer to use shared variables when possible.

Q1.1: **x**
shared

Q1.2: **y**
shared

Q1.3: **mask**
private

Q1.4: **i**
private

Q1.1-Q1.4: Note that we only read **x and **y**, so it is safe to share them. For **mask**, **i**, the value of the variable needs to be different for each thread, or else all threads would do the same thing. As such, we need to make them private.**

Q1.5: Is a data race possible on any variable that must be shared? If so, what variables cause the data race?
(e) ham_dist

Q1.5: Currently, the addition to **ham_dist is a data race. Two threads can read it at the same time, increment based on their own calculations, and store it back. This would result in incorrect values, since one did not read the updated result from the other. We would either need a critical segment, or a reduction keyword to ensure that **ham_dist** is correctly updated.**

Submitted answer 2 **correct: 100%**
Submitted at 2022-11-09 03:24:05 (PST)

 hide ^

Q1: For each variable, determine if it can be made shared, or must be private in order for the above code to work properly. Note that we generally prefer to use shared variables when possible.

Q1.1: **x**
shared **✓ 100%**

Q1.2: **y**
shared **✓ 100%**

Q1.3: **mask**
private **✓ 100%**

Q1.4: **i**
private **✓ 100%**

Q1.5: Is a data race possible on any variable that must be shared? If so, what variables cause the data race?
(e) ham_dist **✓**
✓ 100%

Submitted answer 1 **partially correct: 80%**
Submitted at 2022-11-09 03:23:50 (PST)

 show v