

```

{
  "task": "integrate_network_architecture_feedback",
  "description": "Incorporate expert review feedback into the home
network optimization guide to transition absolute claims into nuanced,
technically precise documentation while adding missing critical
architectural layers.",
  "tech": {
    "frontend": "Markdown",
    "backend": "OpenWrt / Linux Kernel Networking Stack",
    "database": "dnsmasq / unbound / netfilter"
  },
  "constraints": {
    "timebox": "N/A",
    "budget": "N/A",
    "must_haves": [
      "Replace 'hardcoded backdoors' with accurate attack surface
language.",
      "Strengthen OpenWrt vs DD-WRT classification using structured
comparison.",
      "Clarify DNS privacy limitations (DoT/DoH vs SNI/IP
visibility).",
      "Expand DNS provider options with NextDNS and ControlD
trade-offs.",
      "Balance DoT vs DoH deployment use cases (router vs client
level).",
      "Qualify WireGuard kernel space benefits relative to OS
platform.",
      "Contextualize OpenVPN throughput penalties based on hardware
architecture (MIPS vs x86).",
      "Expand Policy-Based Routing matrix to include banking, gaming,
and streaming bypasses.",
      "Formalize stateful firewall rules for IoT/Guest segmentation.",
      "Refine SQM throughput configurations to 90-97% of measured
capacity for queue control.",
      "Incorporate specific non-overlapping Wi-Fi channel layouts
(2.4/5/6 GHz).",
      "Add comprehensive sections for IPv6 security/leak protection,
automated maintenance schedules, network-wide ad-blocking integration,
and SSH/admin hardening."
    ],
    "no_go": [
      "Do not use evaluative or subjective language (e.g., 'good',
'bad', 'excellent').",
      "Do not remove existing optimization steps from the baseline
deployment pipeline."
    ]
  },
  "output": {

```

```

    "format": "Technical Documentation",
    "level_of_detail": "Advanced / Production-ready Reference
Implementation",
    "phases": [
        "1. Baseline Hardening & Firmware Engine",
        "2. Encrypted DNS & Privacy Verification Engine",
        "3. Core Network Routing & Resource Allocation Optimization",
        "4. Deterministic Traffic Segmentation & Firewall Policies",
        "5. Physical Layer & Radio Frequency Optimization"
    ]
}

```

1. Baseline Hardening & Firmware Engine

Firmware Selection Framework

For deployment on supported hardware architectures, OpenWrt is the baseline recommendation due to its active upstream maintenance, implementation of modern Linux kernels, package repository ecosystem, and native implementation of advanced queuing disciplines and virtual local area networking (VLAN) architectures.

Firmware	Recommendation Level	Architectural Justification
OpenWrt	Primary Deployment Target	Active maintenance, modern LTS kernels, native opkg repository, integrated SQM (Cake), native 802.1Q VLAN support, native kernel-space WireGuard.
DD-WRT	Alternative Legacy	Restricted development ecosystem, variance in kernel modernization, divergent configuration paths for advanced policy routing.
Tomato / FreshTomato	Alternative Legacy	Stable for legacy Broadcom-based chipsets; limited scaling capabilities on modern multi-core SoC architectures.
ISP Stock Firmware	Fallback Only	Variable update lifecycles, proprietary closed-source codebases, frequent absence of granular routing, queuing, and firewall controls.

Security Risk Assessment Clarification: Proprietary OEM firmware may introduce expanded attack surfaces due to unneeded vendor cloud integrations, persistent telemetry operations, delayed upstream security patch ingestion, or non-configurable vendor-specific services. This

documentation categorizes these as expanded attack surfaces rather than intentional malicious backdoors.

Management Plane Hardening Protocol

- 1. Administrative Access Control:** * Modify the default administrative username to a unique identifier.
 - Enforce an administrative passphrase matching or exceeding 32 characters of pseudo-random entropy.
- 2. Secure Shell (SSH) Access Configuration:**
 - Disable password-based authentication completely within the dropbear or OpenSSH daemon settings.
 - Inject authorized cryptographic public keys (ssh-ed25519) for all administrative devices.
 - Bind the SSH daemon exclusively to the secure management VLAN interface; explicitly disable WAN-side listening.
- 3. Universal Plug and Play (UPnP) & WPS:**
 - Globally disable Wi-Fi Protected Setup (WPS) to eliminate PIN brute-force vulnerabilities.
 - Globally disable UPnP to prevent unauthenticated, internal client-side modifications of the gateway NAT table. Implement explicit, manual port-forwarding mappings only where technically required.
- 4. Lifecycle Maintenance Execution:**
 - Implement automated tracking of stable upstream branch updates.
 - Establish a bi-weekly or monthly automated/manual verification schedule to compile and flash microcode, package updates, and kernel security patches.

2. Encrypted DNS & Privacy Verification Engine

Encrypted Transport Protocol Comparison

Encrypted DNS architectures protect the transport layer between the local stub/forwarding resolver and the upstream authoritative or recursive provider. They do not anonymize egress traffic destinations.

- **DNS over TLS (DoT - Port 853):** Optimal for router-level implementation. Operates over a dedicated cryptographic port, simplifying stateful firewall inspection, traffic classification, and routing tracking.
- **DNS over HTTPS (DoH - Port 443):** Optimal for client-level bypass implementations. Blends natively into standard HTTPS traffic streams, increasing resistance to stateful inspection blocking or protocol-specific throttling.

Upstream DNS Provider Feature Matrix

The selection of an upstream recursive resolver dictates the content filtering, compliance, and latency footprint of the network layer.

Provider	Core Functional Mechanism	Architectural Trade-off
Cloudflare (1.1.1.1)	Anycast routing optimized for	Minimal structural content or

Provider	Core Functional Mechanism	Architectural Trade-off
	low-latency resolution.	malware filtering by default.
Quad9 (9.9.9.9)	Real-time threat intelligence blocklists integrated at the ingestion layer.	Lacks granular, user-defined domain or analytics customization.
Mullvad	Strict non-logging operations with zero data retention policies.	Lacks structural policy customization interfaces.
NextDNS	Dynamic cloud-managed policy matrices incorporating granular ad, tracker, and malware lists.	Requires account linkage; tier structures apply based on monthly query volume thresholds.
ControlD	Advanced policy routing engine capable of conditional proxy configurations at the DNS layer.	Increased configuration complexity; premium tiers required for complex profile scheduling.

Upstream Privacy Leak Realities

While DoT and DoH eliminate cleartext eavesdropping of DNS payloads, they do not mask subsequent network operations from the upstream Internet Service Provider (ISP). The ISP retains visibility over:

- The destination Layer 3 IP addresses of all unproxied egress traffic.
- The volume, frequency, and temporal patterns of connection bursts.
- The cleartext Server Name Indication (SNI) string transmitted during the initial TLS handshake, unless Server Name Indication encryption protocols (e.g., Encrypted Client Hello - ECH) are explicitly supported and enforced by both the local browser client and the destination authoritative web server.

3. Core Network Routing & Resource Allocation Optimization

Virtual Private Network Virtualization Parameters

When selecting tunneling protocols for transit security, the underlying system architecture dictates the throughput threshold.

- **WireGuard Integration:** On Linux-based architectures (such as OpenWrt), WireGuard executes natively within kernel space. This design bypasses the context-switching penalties associated with user-space memory copies, achieving minimal CPU overhead and maximizing performance on embedded system-on-chip (SoC) platforms.
- **OpenVPN Constraints:** OpenVPN operates primarily within user space, relying on frequent context shifts across the kernel-user space boundary via a virtual TUN/TAP network interface.

[MIPS Architecture / Consumer SoC]

OpenVPN ---> 30 - 50 Mbps (High context-switching overhead)

WireGuard ---> Line Rate (Kernel-space execution)


[x86 Architecture / Dedicated Appliance]

OpenVPN ---> 500+ Mbps (Overcome by raw CPU clock speed)

WireGuard ---> Multi-Gbps (Saturates high-speed interfaces)

Policy-Based Routing (PBR) Logic Matrix

To maximize deterministic performance, traffic must be programmatically divided between encrypted VPN tunnels and direct ISP Wide Area Network (WAN) interfaces based on destination profiles and performance tolerances.



Smart Queue Management (SQM) Calibration Engine

Deploying Smart Queue Management running the Cake queuing discipline resolves bufferbloat by maintaining control over packet scheduling at the edge interface.

[ISP Modem Node] <=== (Uncontrolled Queue / Bloat) ===> [Router Edge Interface (SQM Active)]

|
Configured Target:

90% - 97%

of Maximum Measured
Capacity

1. **Mechanism of Action:** SQM artificially constrains the upload and download thresholds of the router's edge interface to a value slightly lower than the physical synchronization limit of the upstream provider link. This enforces queue serialization within the router's memory architecture rather than allowing the upstream provider's modem buffers to fill.
2. **Calibration Methodology:** * Execute consecutive, unthrottled bandwidth tests during peak network congestion periods to establish real baseline limits.
 - o Initialize the SQM ingress and egress limits to **90%** of the verified minimum

- capacity.
- Incrementally adjust the threshold upward toward a ceiling of **97%** while monitoring ICMP execution sequences under full link saturation. Stop adjustments when latency spikes indicate buffer inflation at the upstream modem.

4. Deterministic Traffic Segmentation & Firewall Policies

802.1Q VLAN Logical Topology

To prevent lateral movement following a device compromise, isolate network segments into distinct Layer 2 broadcast domains controlled by stateful Layer 3 firewall policies.

```
[ Physical Router Ports / Core Switching Architecture ]
|
+---> VLAN 10 (Main LAN Domain) -----> [ Secure Production
Systems ]
|
+---> VLAN 20 (IoT Isolation Domain) ---> [ Embedded Smart Devices
/ Appliances ]
|
+---> VLAN 30 (Guest Transient Domain) --> [ Untrusted External
Hardware ]
```

Stateful Netfilter/Firewall Matrix

The firewall must enforce deterministic rules blocking cross-VLAN initialization while allowing reciprocal states.

Source Zone	Destination Zone	Protocol	Connection Tracking State	Policy Action
VLAN 10 (LAN)	VLAN 20 (IoT)	Any	NEW, ESTABLISHED, RELATED	ACCEPT
VLAN 20 (IoT)	VLAN 10 (LAN)	Any	ESTABLISHED, RELATED	ACCEPT
VLAN 20 (IoT)	VLAN 10 (LAN)	Any	NEW	DROP
VLAN 20 (IoT)	WAN (Internet)	Explicit	NEW, ESTABLISHED, RELATED (Limit to required endpoints)	ACCEPT
VLAN 30 (Guest)	VLAN 10 (LAN)	Any	All States	DROP
VLAN 30 (Guest)	VLAN 20 (IoT)	Any	All States	DROP
VLAN 30 (Guest)	WAN (Internet)	Any	NEW, ESTABLISHED, RELATED	ACCEPT

Network-Wide Content Interception Integration

Incorporate a network-wide ad and tracker filtration engine (e.g., Pi-hole, AdGuard Home, or native OpenWrt packages like adblock / simple-adblock) at the DNS resolution layer:

- Deploy the interception engine to listen across all internal VLAN interfaces.
- Implement a stateful NAT forwarding rule matching Port 53 to intercept rogue client devices hardcoded to bypass local DNS parameters. This forces their traffic through the internal recursive loop.
- Configure authoritative blocking to return NXDOMAIN or 0.0.0.0 responses for domains identified on tracking, advertisement, and telemetry distribution matrices.

IPv6 Security Lifecycle Deployment

If IPv6 allocation is provisioned by the service provider (via Native, DHCPv6-PD, or SLAAC configurations):

- **Symmetric Firewall Hardening:** Mirror all IPv4 ingress protections within the IPv6 netfilter framework (ip6tables / nftables). Explicitly deny unauthorized incoming connection attempts directed at global unicast addresses assigned to internal clients.
- **Leak Mitigation Metrics:** Verify that the deployed VPN routing engine accounts for IPv6 traffic. If a policy dictates routing a client via a VPN interface, ensure an equal IPv6 default gateway is defined inside the tunnel. If the VPN target provider does not route IPv6 payloads, explicitly drop all egress IPv6 traffic matching that client's identifier to force automated IPv4 failover and prevent unencrypted traffic leaks through the primary WAN.

5. Physical Layer & Radio Frequency Optimization

2.4 GHz Spectrum Configuration

- **Channel Assignment:** Restrict channel allocations strictly to **Channel 1**, **Channel 6**, or **Channel 11**.
- **Channel Bandwidth:** Enforce a maximum channel width of **20 MHz**. Expanding to 40 MHz within the 2.4 GHz band introduces severe co-channel and adjacent-channel interference due to overlapping spectrum boundaries, reducing overall network capacity.

5 GHz Spectrum Configuration

- **Channel Bandwidth:** Deploy an **80 MHz** allocation as the standard baseline configuration. This delivers high data rates while maintaining adequate channel separation options.
- **160 MHz Operational Constraints:** Deploy 160 MHz channel configurations only when local RF site surveys confirm zero local radar deployments (requiring DFS evasion mechanisms), when the ambient noise floor is exceptionally low, and when the primary client hardware profiles explicitly support 2x2 or 4x4 160 MHz streams. If these conditions are not met, 160 MHz channels degrade stability and performance due to increased exposure to ambient noise.

6 GHz Spectrum Configuration (Wi-Fi 6E / Wi-Fi 7)

- **Client Placement Matrix:** Prioritize high-bandwidth, line-of-sight compute nodes and primary infrastructure backhauls for migration into the 6 GHz spectrum layer.
- **Legacy Decoupling:** Keep legacy IoT components isolated on the 2.4 GHz infrastructure. This reserves the 5 GHz and 6 GHz spectrum layers for high-throughput, low-latency communication workloads.