

1. Content    Padding    Border    Margin.
2. Use `display: flex;`
3. `position: static;`
4. A grid container is the parent with `display: grid`. A grid item is a child inside the grid container.
5. `px` means pixels. It is an absolute unit because its size does not depend on the parent element's font size.
6. `#FF0000`, `red`, and `rgb(255, 0, 0)` are three different ways to write the same red colour.
7. Use the `font-family` property.
8. `box-sizing: border-box;` makes the declared width and height include the content, padding, and border.
9. `row`
10. It moves relative to its normal position on the page.
11. `justify-content` aligns items on the main axis, while `align-items` aligns items on the cross axis.
12. `fr` means a fraction of the available space. `1fr 2fr` makes the second column twice as wide as the first.
13. An absolute element is positioned relative to its closest positioned parent. If the parent is static, it looks for another positioned ancestor; if the parent is relative, it is positioned relative to that parent.
14. `em` is based on the parent's font size. `rem` is based on the root (`html`) font size.
15. The "a" means alpha. It controls transparency.
16. `line-height` controls the space between lines of text. A unitless value such as 1.5 works well with different font sizes.
17. Use the `gap` property, such as `gap: 20px;`
18. `flex-wrap` allows flex items to move to a new line when there is not enough space.
19. Margin collapse happens when vertical margins of adjacent block elements combine instead of adding together. The larger margin may be used.
20. `position: sticky;` keeps an element in its normal position until a scroll point is reached, then it sticks to the set position.
21. Use `vw/vh` when you want sizing based on the screen (viewport). Use `%` when you want sizing based on the parent/container.