

Safety Data Sheet

according to 91/155/EEC and ISO 11014-1

Date of printing: 10.11.2003

Page: 1/7

Revised: 15.01.2003

SDS No.: 029-00033123.0000

1. Identification of the substance/preparation and company

Product

Product name

Sika® Activator

Manufacturer/supplier information

Manufacturer/supplier:

SIKA Schweiz AG

Street/postbox:

Tüffenwies 16

Town/City and Post Code:

Zürich

Country:

Switzerland

Phone:

+4114364040

Telefax:

+4114364584

Emergency information phone:

079 309 06 29 Out of office hours only

2. Composition/information on ingredients

Chemical characterization

Bonding agent, containing solvent

Hazardous ingredients

Designation according to 67/548/EEC

CAS No. Concentration Danger symbols R phrases

EEC No.

• heptane (and isomers)

142-82-5 25 - 50 % F, Xn, N 11, 38, 50/53, 65, 67

205-563-8

• methylcyclohexane

108-87-2 25 - 50 % F, Xn, N 11, 38, 51/53, 65, 67

203-624-3

• cyclohexane

110-82-7 1 - 2.5 % F, Xn, N 11, 38, 50/53, 65, 67

203-806-2

• Naphtha (petroleum), hydrotreated light

64742-49-0 10 - 25 % F, Xn, N 11, 51/53, 65, 66, 67

265-151-9

• N-[3-(trimethoxysilyl)propyl]ethylenediamine

1760-24-3 2.5 - 10 % Xi 41, 43

217-164-6

• Ethanol

64-17-5 2.5 - 10 % F 11

200-578-6

• Tris(dodecylbenzenesulphonato-0)(propan-2-olato)titanium

61417-55-8 2.5 - 10 % Xn 10, 22, 38, 41

262-777-4

Product name: **Sika® Activator**

Date of printing: 10.11.2003

Page: 2/7

Revised: 15.01.2003

SDS No.: 029-00033123.0000

*** 3. Hazards identification**

Hazards identification

F	Highly flammable
Xn	Harmful
N	Dangerous to environment

Information on hazards to man and to the environment

11	Highly flammable.
36/38	Irritating to eyes and skin.
43	May cause sensitization by skin contact.
50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
65	Harmful: may cause lung damage if swallowed
67	Vapours may cause drowsiness and dizziness

*** 4. First-aid measures**

General instructions

In any case show the physician the Safety Data Sheet

After inhalation

In the event of symptoms take medical treatment.

After skin contact

In case of contact with skin wash off immediately with soap and water

Consult a doctor if skin irritation persists.

After eye contact

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water.

Summon a doctor immediately.

After ingestion

Do not induce vomiting.

Summon a doctor immediately.

*** 5. Fire-fighting measures**

Suitable extinguishing media

alcohol-resistant foam
dry powder
carbon dioxide

Unsuitable extinguishing media for safety reasons

Full water jet

Exposure hazard arising from the product, its combustion products or resulting gases

In the event of fire the following can be released:

Carbon monoxide (CO)

*** 5. Fire-fighting measures (continued)**

Carbondioxide (CO₂)

Nitrogen oxides (NO_x)

Special protective equipment for fire-fighting

Use breathing apparatus.

Additional information

Fire residues and contaminated firefighting medium must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

*** 6. Accidental release measures**

Personal precautions

Ensure adequate ventilation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

Environmental precautions

Do not allow to enter drains or waterways

In case of entry into waterways, soil or drains, inform the responsible authorities.

Procedures for cleaning up

Avoid sparking.

Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder).

When picked up, treat material as prescribed under heading "Disposal".

*** 7. Handling and storage**

Handling

Instructions for safe handling

See chapter 8 / Personal protective equipment.

Instructions for fire and explosion protection

Keep away from sources of ignition - no smoking.

Vapours may form explosive mixtures with air

Take precautionary measures against electrostatic loading.

Storage

Requirements for storage rooms and containers

Keep container tightly closed and dry in a cool, well-ventilated place

Combined storage instructions

Keep away from food, beverages and animal feedstocks.

Additional information regarding storage

Protect from frost.

Product name: **Sika® Activator**

Date of printing: 10.11.2003

Page: 4/7

Revised: 15.01.2003

SDS No.: 029-00033123.0000

*** 7. Handling and storage (continued)**

Protect from heat and direct sunlight

Protect from atmospheric moisture and water

*** 8. Exposure controls/personal protection**

Personal protective equipment

General protective and hygiene measures

Take care for sufficient ventilation or exhaust on the workshop place.

Avoid contact with eyes and skin

Use barrier skin cream.

Remove soiled or soaked clothing immediately.

Do not eat, drink or smoke during work time.

Wash hands before breaks and after work.

Respiratory protection

In case of insufficient ventilation.

Ori-nasal mask suitable for organic vapours.

Class of vapour filter is depending on
pollutant concentration on the scene.

Hand protection

Butyl rubber/nitrile rubber gloves

Eye protection

Safety glasses

Body protection

Working clothes

9. Physical and chemical properties

Appearance

Physical state: liquid

Colour: slightly yellowish

Odour: petrol-like

Data relevant to safety

Boiling point

78 °C

Method

Flash point

-4 °C

Density at 20°C

0.71 g/cm³

Viscosity at 23°C

2 mPas

Viscosity at 23°C
(efflux time)

11 s

4mm/DIN 53211

Product name: **Sika® Activator**

Date of printing: 10.11.2003

Page: 5/7

Revised: 15.01.2003

SDS No.: 029-00033123.0000

9. Physical and chemical properties (continued)

VOC (solvents)	94.42 %
VOC (CH)	94.42 %

* 10. Stability and reactivity

Conditions to avoid

Formation of explosive gas/air mixtures.

Materials to avoid/dangerous reactions

No hazardous reactions when stored and handled according to prescribed instructions.

Thermal decomposition and hazardous decomposition products

No decomposition if used as prescribed.

* 11. Toxicological information

Sensitization

Sensitization/allergic reaction possible.

Allergic reaction can may be observeed in sensitive persons, even on very low concentrations.

Experience on humans

When skin contact:

Irritation.

Repeated exposure may cause skin dryness or cracking

Frequent/longterm skin contact:

May cause dermatitis.

When eyes contact:

Irritation.

When inhalation:

Vapours have a narcotic effect. Reaction-time and sense of coordination may be affected.

When swallowed:

Harmful: may cause lung damage if swallowed

* 12. Ecological information

Additional information

Do not allow to enter waste water drain, waterways or soil.

* 13. Disposal considerations

Product name: **Sika® Activator**

Date of printing: 10.11.2003

Page: 6/7

Revised: 15.01.2003

SDS No.: 029-00033123.0000

*** 13. Disposal considerations (continued)**

Packaging

Recommendations

Completely emptied packagings can be given for recycling.

Packaging that cannot be cleaned should be disposed of as product waste

*** 14. Transport information**

ADR/RID

UN 1866 Class: 3 Packing group: II Class.code: F1

Proper shipping name

Resin solution

Label No.: 3

IMO/IMDG

UN 1866 Class: 3 Packing group: II

EmS: 3-05

Proper shipping name

Resin solution, flammable

Label No.: 3

IATA/ICAO

UN 1866 Class: 3 Packing group: II

Proper shipping name

Resin solution, flammable

Label No.: 3

*** 15. Regulatory information**

Labelling according to EEC Directive

The product is classified and labelled in accordance with EC directives/the relevant national laws.

Relevant hazardous ingredients for labelling

Contains: heptane (and isomers)
methylcyclohexane
Naphtha (petroleum), hydrotreated light
N-[3-(trimethoxysilyl)propyl]ethylenediamine

Danger symbols

F Highly flammable

Xn Harmful

N Dangerous to environment

R phrases

11 Highly flammable.

36/38 Irritating to eyes and skin.

43 May cause sensitization by skin contact.

50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Product name: **Sika® Activator**

Date of printing: 10.11.2003

Page: 7/7

Revised: 15.01.2003

SDS No.: 029-00033123.0000

*** 15. Regulatory information (continued)**

65	Harmful: may cause lung damage if swallowed
67	Vapours may cause drowsiness and dizziness

S phrases

24	Avoid contact with skin.
33	Take precautionary measures against static discharges.
37	Wear suitable gloves.
51	Use only in well-ventilated areas.

*** 16. Other information**

asterisk (*) on left margin marks modification of previous version

R-phrases of the ingredients listed in chapter 2

10	Flammable.
11	Highly flammable.
22	Harmful if swallowed.
38	Irritating to skin.
41	Risk of serious damage to eyes.
43	May cause sensitization by skin contact.
50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
65	Harmful: may cause lung damage if swallowed
66	Repeated exposure may cause skin dryness or cracking
67	Vapours may cause drowsiness and dizziness

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.