KaiOS 字符串本地化工具指南

© 2019 KaiOS Technologies, Inc. All Rights Reserved

Confidential and Proprietary

1. 语言列表

Languages_all.json

语言本地化文件夹

- KaiOS 2.0: ../distribution/locales/languages all.json
- KaiOS 2.5: ../gaia/tree/app-split/locales/language_all.json

打开json文件,里面是对应的各语言缩写及其全称

language_all.json:

```
languages_all.json 995 Bytes
       "af-ZA" : "Afrikaans",
      "ar-SA" : "عربي",
"bn-IN" : "বাংলা (IN)",
"de-DE" : "Deutsch",
      "en-GB" : "English (GB)",
      "en-US" : "English (US)",
 8
      "es-US" : "Español (US)",
 9
      "es-ES" : "Español (ES)",
      "fa-IR"
                ,"(IR) فارسى" :
      "fr-CA"
 11
                : "French (CA)",
       "fr-FR"
                 : "Français (FR)",
 13
       "hi-HI"
                 ः "हिन्दी",
 14
       "hu-HU"
                 : "Magyar",
15
       "id-ID"
                 : "Bahasa Indonesia",
      "it-IT"
                 : "Italiano",
17
      "ms-MY" : "Melayu",
      "ne-IN" : "नेपाली",
18
19
      "nl-NL" : "Nederlands",
      "pl-PL" : "Polski",
21
      "pt-BR" : "Português (do Brasil)",
                : "Português (Portugal)",
      "pt-PT"
               : "Română",
       "ro-RO"
 24
                 : "Русский",
25
      "sw-ZA"
                 : "Kiswahili",
      "ta-IN" : "தமிழ்",
       "th-TH" : "Mus",
27
28
      "tr-TR" : "Türkce".
29
      "ur-PK" : "aayl",
      "vi-VN" : "Tiếng Việt",
30
      "zh-CN" : "中文 (简体)",
32
      "zu-ZA" : "isiZulu"
33 }
```

2. 语言翻译

2.1 en-US 翻译 (开发阶段的默认翻译)


开发人员会根据UX spec来创建string对应的en-US翻译,其他所有语言的翻译都要以en-US作为base。

所在文件夹:

- ../apps/APP/locales/APP.LOCALE.properties => en-US: ../apps/APP/locales.APP.en-US.properties
- ../shared/locales/APP/APP.LOCAL.properties => en-US: ../shared/locales/APP/APP.en-US.properties
- ../apps/APP/manifest.w ebapp => APP 名称

APP => 在实际目录下会被不同的APP名称所替代

Apps文件夹:



gaia/shared文件夹:




manifest.webapp:

```
},
"locales": {
    "en-US": {
        "name": "Bookmark",
        "description": "Bookmark Manager"
},
```


2.2 多语言翻译(语言也会包含en-US,因为有时候需要对en-US翻译做定制)

- 每个语言的翻译都会对应不同的文件夹
- gaia/locales/LOCALE/apps (/Apps文件夹中用到的字符串所对应的翻译,此处的string对应2.1章节中的../apps/APP/locales/APP.LOCALE.properties)
- gaia/locales/LOCALE/shared (Apps文件夹中用到的字符串所对应的翻译, 此处的string对应2.1章节中的../shared/locales/APP/APPLOCAL.properties)
- gaia/locales/LOCALE/apps/APP/manifest.properties (APP 名称)

LOCALE => 在实际目录下会被不同的语言名称所替代



3. Thon-lang



4. 环境配置

操作系统: Ubuntu

工具: Perl 下载路径

kaios@kaios1604:~\$ cat /etc/issue Ubuntu 16.04 LTS \n \l

```
This is perl 5, version 22, subversion 1 (v5.22.1) built for x86_64-linux-gnu-th
read-multi
(with 73 registered patches, see perl -V for more detail)
Copyright 1987-2015, Larry Wall
```

5. 使用perl工具导出/导入/复用翻译

5.1 导出字符串

首先,请更新代码库至最新版本。然后使用perl工具从Apps和gaia/shared目录下导出一份Excel表格(见下图示例),其中会包含最新的en-US,string ID,refname等列,同时将从gaia/locales中导出对应的其他语言的翻译。

将工具包放在gaia/locales目录下,然后运行以下命令:

命令行:

• cd /home/kaios/Desktop/kaios2.5/KaiOS/gaia/locales/thon-lang

• perl -CS langexportT2M.pl -f xx.xls -x

(ps: 请重命名xx.xls文件)

导出的字串表示例:

4	A	В	C	D	E	F	G	H	I	J
path		▼ filename	v string v	refname	en-US 🔻	uz-Cyrl▼	or-IN	as-IN	▼ lo-LA	▼ fr-FR ▼ 1
: /apps	/antitheft/	anti-theft	remote-ring-header	antitheft:anti-theft:remote-ri						Sonnerie
/apps	/antitheft/	anti-theft	remote-ring-text1	antitheft:anti-theft:remote-ri	This device is ringi:	ng by				Sonnerie
/apps	/antitheft/	anti-theft	remote-ring-text2	antitheft:anti-theft:remote-ri	remote Anti-theft ac	count.				compte an
i /apps	/antitheft/	anti-theft	ringer-dismiss	antitheft:anti-theft:ringer-di	Dismiss					Ignorer
) /apps	/bluetooth/	bluetooth	active-pair	bluetooth:bluetooth:active-pai	Confirm devices to p	air				
'/apps	/bluetooth/	bluetooth	active-pair-confirmation	bluetooth:bluetooth:active-pai	To pair with {{devic	e}}, make	sure that	both dev	ices cur	rently have
} /apps	/bluetooth/	bluetooth	active-pair-passkey	bluetooth:bluetooth:active-pai	To pair with {{devic	e}}, enter	the passl	cey on th	ne device	
/apps	/bluetooth/	bluetooth	active-pair-pincode	bluetooth:bluetooth:active-pai	To pair with {{devic	e}}, enter	the PIN	n the de	vice.	
0 /apps	/bluetooth/	bluetooth	bluetooth	bluetooth:bluetooth	Bluetooth			Ţ		
1 /apps	/bluetooth/	bluetooth	bluetooth-address	bluetooth:bluetooth:bluetooth-	-Bluetooth Address					
2 /apps	/bluetooth/	bluetooth	bluetooth-address-unavaila	bluetooth:bluetooth:bluetooth	Not available					
3 /apps	/bluetooth/	bluetooth	bluetooth-devices-nearby	bluetooth:bluetooth:bluetooth-	Nearby Devices					
4 /apps	/bluetooth/	bluetooth	bluetooth-enable-msg	bluetooth:bluetooth:bluetooth-	Turn Bluetooth on to	view devi	ices in th	e area.		
5 /apps	/bluetooth/	bluetooth	bluetooth-header	bluetooth:bluetooth:bluetooth-	-{{bluetooth}}					
6 /apps	/bluetooth/	bluetooth	bluetooth-name-maxlength-a	bluetooth:bluetooth:bluetooth	Your device name exc	eeds {{le	ngth}} cha:	racters.	Please r	etry again.
7 /apps	/bluetooth/	bluetooth	bluetooth-new-name	bluetooth:bluetooth:bluetooth-	New name					

处理manifest(APP名称)字串时,需手动从以下目录拷贝, (locales/LOCALE/apps/APP/manifest.properties),然后粘贴整理在表格中,具体请参照章节2.2及下图的示例表格格式。

示例表格:

path	filename	string	refname	en-US
/apps/bluetooth/locales	manifest	name	bluetooth:manifest:name	Bluetooth

5.2 将翻译导入DB

导入DB的翻译格式同样是Excel表格,前面几列请保持和从Apps和gaia/shared导出的英文string表格(详情见章节5.1)一致的内容,另外还有Manifest字串。然后在表格添加要导入的语言列。

将工具包放在../gaia/locales同级目录下,然后运行以下命令:

命令行:

- 路径: cd /home/kaios/Desktop/kaios2.5/KaiOS/gaia/locales/thon-lang
- 导入Excel文件,导出locales文件: perl -CS langimport.pl -f xx.xls

示例表格:

A		В	C	D	E	F	G	H	I	J
path		filename	▼ string	refname -	en-US -	uz-Cyrl -	or-IN	▼ as-IN	▼ lo-LA	▼ fr-FR ▼
/apps/antithef	:/	anti-theft	remote-ring-header	antitheft:anti-theft:remote-r	Remote Ring					Sonnerie
/apps/antithef	:/	anti-theft	remote-ring-text1	antitheft:anti-theft:remote-r	This device is ringi	ng by				Sonnerie
/apps/antithef	:/	anti-theft	remote-ring-text2	antitheft:anti-theft:remote-r	remote Anti-theft ac	count.				compte an
/apps/antithef	:/	anti-theft	ringer-dismiss	antitheft:anti-theft:ringer-d	Dismiss					Ignorer
/apps/bluetooth	1/	bluetooth	active-pair	bluetooth:bluetooth:active-pa	Confirm devices to p	air				
/apps/bluetooth	1/	bluetooth	active-pair-confirmation	bluetooth:bluetooth:active-pa	To pair with {{devic	e}}, make	sure tha	t both de	vices cur	rently have
/apps/bluetooth	1/	bluetooth	active-pair-passkey	bluetooth:bluetooth:active-pa	To pair with {{devic	e}}, enter	r the pas	skey on t	he device	
/apps/bluetootl	1/	bluetooth	active-pair-pincode	bluetooth:bluetooth:active-pa	To pair with {{devic	e}}, enter	the PIN	on the d	evice.	
/apps/bluetooth	1/	bluetooth	bluetooth	bluetooth:bluetooth:bluetooth	Bluetooth			Ī		
/apps/bluetooth	ı/	bluetooth	bluetooth-address	bluetooth:bluetooth:bluetooth	Bluetooth Address					
/apps/bluetooth	1/	bluetooth	bluetooth-address-unavail	a bluetooth:bluetooth:bluetooth	Not available					
/apps/bluetooth	1/	bluetooth	bluetooth-devices-nearby	bluetooth:bluetooth:bluetooth	Nearby Devices					
/apps/bluetootl	1/	bluetooth	bluetooth-enable-msg	bluetooth:bluetooth:bluetooth	Turn Bluetooth on to	view devi	ices in t	he area.		
/apps/bluetooth	ı/	bluetooth	bluetooth-header	bluetooth:bluetooth:bluetooth	-{{bluetooth}}					
/apps/bluetootl	n/	bluetooth	bluetooth-name-maxlength-	a bluetooth:bluetooth:bluetooth	Your device name exc	eeds {{le	ngth}} ch	aracters.	Please r	etry again.
/apps/bluetooth	1/	bluetooth	bluetooth-new-name	bluetooth:bluetooth:bluetooth	New name					

表格中的语言缩写必须与language_all.json文件中的名称保持一致。详情参见章节 1。

5.3 复用翻译

很多新提交/更新的字串都可以从翻译库中复用翻译。同样,使用对应的perl复用工具可以完成复用。

命令行:

• 路径: cd /home/kaios/Desktop/kaios2.5/KaiOS/gaia/locales/thon-lang

• 执行复用:

- Step 1: perl -CS inlNpatheng.pl -n original excel.xls -f xx.xls(1) -x
- Step 2: perl -CS inlNpatheng2.pl -n xx.xls(1) sheet + translation from DB.xls -f xxx.xls -x

(ps: 请重命名xx.xls文件)

在step 1中,原始表格包含两个sheet,前一个sheet中是新string列表,后一个sheet是要复用的string列表。

在step 2中,表格 xx.xls(1) sheet + translation from DB.xls 同样也要包含两个sheet。第一个sheet是你在step 1中导出的表格内容,xx.xls(1)。第二个sheet和step 1中的第二个sheet相同。

这里对此操作稍作解释。step 1中用到的脚本是 inINpatheng.pl,复用的原理是比较两个sheet中的refname和en-US,如果两项都匹配,那么会直接复用sheet2中的翻译到sheet1中。而step 2中用到的 inINpatheng2.pl脚本,是拿step 1中没法复用的string,去比较翻译DB中的英文,如果两个sheet中英文一致,并且英文是包含两个单词以上,脚本也会做一个复用,这样在保证翻译质量的条件下最大限度的降低待翻译的string数量。

两个sheet中的翻译语言缩写需要完全一致,但语言顺序可以打乱。比如你想要复用ABC三个语言,sheet 2中只需要保证有ABC这三个语言列,顺序没有要求,可以是ABC,ACB.BCA等等。

Sheet 1

path	filename	string	▼ refname
/apps/antitheft/	anti-theft	remote-ring-header	antitheft:anti-theft:remote-riRemote Ring Sonnerie à distancUkwenza Idivayisi
/apps/antitheft/	anti-theft	remote-ring-text1	antitheft:anti-theft:remote-riThis device is ringirSonnerie de l'appLe divayisi iyakha
/apps/antitheft/	anti-theft	remote-ring-text2	antitheft:anti-theft:remote-riremote Anti-theft acccompte antivol à dye-akhawunti eviml
/apps/antitheft/	anti-theft	ringer-dismiss	antitheft:anti-theft:ringer-diDismiss Ignorer Chitha
/apps/bluetooth/	bluetooth	active-pair	bluetooth:bluetooth:active-paiConfirm devices to pair
/apps/bluetooth/	bluetooth	active-pair-confirmation	bluetooth:bluetooth:active-pai To pair with {{device}}, make sure that both devices cur:
/apps/bluetooth/	bluetooth	active-pair-passkey	bluetooth:bluetooth:active-pai To pair with {{device}}, enter the passkey on the device.
/apps/bluetooth/	bluetooth	active-pair-pincode	bluetooth:bluetooth:active-paiTo pair with {{device}}, enter the PIN on the device.
/apps/bluetooth/	bluetooth	bluetooth	bluetooth:bluetooth Bluetooth
/apps/bluetooth/	bluetooth	bluetooth-address	bluetooth:bluetooth-bluetooth Address
/apps/bluetooth/	bluetooth	bluetooth-address-unavai	ilabluetooth:bluetooth:bluetooth-Not available
/apps/bluetooth/	bluetooth	bluetooth-devices-nearby	/ bluetooth:bluetooth:bluetooth-Nearby Devices
/apps/bluetooth/	bluetooth	bluetooth-enable-msg	bluetooth:bluetooth:bluetooth-Turn Bluetooth on to view devices in the area.
/apps/bluetooth/	bluetooth	bluetooth-header	bluetooth:bluetooth-{{bluetooth}}
/apps/bluetooth/	bluetooth	bluetooth-name-maxlength	n-abluetooth:bluetooth:bluetooth-Your device name exceeds {{length}} characters. Please ro
/apps/bluetooth/	bluetooth	bluetooth-new-name	bluetooth:bluetooth-New name
/apps/bluetooth/	bluetooth	bluetooth-paired-devices	bluetooth:bluetooth:bluetooth-Paired devices
/apps/bluetooth/	bluetooth	bluetooth-pairing-reques	st-bluetooth:bluetooth:bluetooth-Bluetooth pairing request
/anns/hluetooth/	hluetooth	hluetooth-status-descrin	nti bluetooth:bluetooth-bluetooth-Rluetooth is disabled

Sheet 2

path	▼ filename	string	refname	▼ en-US	▼ fr-FR 🖈	km-KH vzu-ZA v
/apps/antitheft/	anti-theft	remote-ring-header	antitheft:anti-the	ft:remote-riRemote Ring	Sonnerie	à distancUkwenza I
/apps/antitheft/	anti-theft	remote-ring-text1	antitheft:anti-the	ft:remote-riThis device is	ringir Sonnerie	de l'appLe divayi
/apps/antitheft/	anti-theft	remote-ring-text2	antitheft:anti-the	ft:remote-riremote Anti-th	eft accompte an	tivol à cye-akhawu
/apps/antitheft/	anti-theft	ringer-dismiss	antitheft:anti-the	ft:ringer-diDismiss	Ignorer	Chi tha
/apps/bluetooth/	bluetooth	device-status-pairing	bluetooth:bluetoot	h:device-staPairing with d	leviceAssociati	on avec lUkubhangq
/apps/bluetooth/	bluetooth	device-status-tap-connect	bluetooth:bluetoot	h:device-staPress \"Select	\" to pAppuyer s	ur SélectChofoza \
/apps/bluetooth/	bluetooth	device-status-waiting	bluetooth:bluetoot	h:device-staWaiting for ot	her devAttente d	l'un autrIlinde en
/apps/bluetooth/	bluetooth	error-connect-msg	bluetooth:bluetoot	h:error-connCheck that the	deviceVérifiez	que l'ar Hlola uku
/apps/bluetooth/	bluetooth	error-connect-title	bluetooth:bluetoot	h:error-connUnable to conn	ect de Impossibl	e de conrAyikwazi
/apps/bluetooth/	bluetooth	error-pair-checkpin	bluetooth:bluetoot	h:error-pairDo you want to	try paVoulez-vo	us réessaUyafuna y
/apps/bluetooth/	bluetooth	error-pair-fail	bluetooth:bluetoot	h:error-pair {{devicename}}	isn't {{devicen	ame}} ne {{devicen
/apps/bluetooth/	bluetooth	error-pair-pincode	bluetooth:bluetoot	h:error-pairUnable to pair	with Impossibl	e de s'aAyikwazi
/apps/bluetooth/	bluetooth	error-pair-title	bluetooth:bluetoot	h:error-pairUnable To Pair	DeviceAppairage	de l'arAyikwazi
/apps/bluetooth/	bluetooth	error-pair-toofast	bluetooth:bluetoot	h:error-pairUnable to pair	with Impossibl	e de s'aAyikwazi
/apps/bluetooth/	bluetooth	error-transfer-settings	bluetooth:bluetoot	h:error-tranBluetooth file	transiÉchec du	transfertUkuthumel
/apps/bluetooth/	bluetooth	error-transfer-title	bluetooth:bluetoot	h:error-tranBluetooth file	transiÉchec du	transfertUkuthumel
/apps/bluetooth/	bluetooth	ok	bluetooth:bluetoot	h:ok OK	OK	KULUNGILE
/apps/bluetooth/	bluetooth	pair	bluetooth:bluetoot	h:pair Pair	Appairer	Bhangqa
/apps/bluetooth/	bluetooth	pair-view-title	bluetooth:bluetoot	h:pair-view-Bluetooth Requ	est Demande E	luetooth Isicelo S
/apps/bluetooth/	bluetooth	paired-failed	bluetooth:bluetoot	h:paired-faiFailed to pair	with Impossibl	e d'appaYehluleki

6. COMPILE FLAG

- LOCALE_BASEDIR=locales/
- LOCALES FILE=locales/languages all.json
- GAIA_DEFAULT_LOCALE=en-US

In Makefile#L62-75

- ifdef LOCALE BASEDIR
- REBUILD=1
- endif
- ifdef LOCALES_FILE
- REBUILD=1
- ondif
- sinclude local.mk

Setting in Dev phase, stored in Makefile#L470

- GAIA_LOCALES_PATH? =locales
- LOCALES_FILE? =shared/resources/languages.json
- GAIA_LOCALE_SRCDIRS=\$(GAIA_DIR)\$(SEP)shared \$(GAIA_APPDIRS)
- GAIA_DEFAULT_LOCALE? =en-US

故障排除 (TBC...)

1. 导入过程中报错

```
Use of uninitialized value $result in substitution (s///) at langimport.pl line 253,
Use of uninitialized value $result in substitution (s///) at langimport.pl line 254,
Use of uninitialized value $result in substitution (s///) at langimport.pl line 255.
Use of uninitialized value $result in substitution (s///) at langimport.pl line 251.
Use of uninitialized value $result in substitution (s///) at langimport.pl line 253,
Use of uninitialized value $result in substitution (s///) at langimport.pl line 253,
Use of uninitialized value $result in substitution (s///) at langimport.pl line 254.
Use of uninitialized value $result in substitution (s///) at langimport.pl line 255.

>> www.www.settings ...

-> Preparing ../bn.!N/apps/settings.properties ...
Can't locate object method 'copy' via package "../bn.!N/apps/settings.properties" (perhaps you forgot to load "../bn.!N/apps/settings.yroperties") at langimport.pl line 345.
cyinglang@AI-TG38:-/kaios2.5_tcl/gaia/locales/thon-langimport.pl line 345.
```

Kai: 确保使用的电脑操作系统为Ubuntu。

尝试在导入脚本 langimport.pl 第26行后面加入一行,然后重试:

use File::Copy;

```
use strict;
use warnings;
use utf8;
use Encode qw(decode);
use Spreadsheet::XLSX;
use File::Path;
```

2. 导出过程中出现warning

```
properties../sw-ZA/shared/keypad/keypad.properties../sw-ZA/shared/phone_types.properties../ko-KA/apps/kaios-plus/manifest.properties../ko-KA/apps/kaios-plus/service.properties../ho-KA/apps/kaios-plus/service.properties../ho-IL/apps/kaios-plus/service.properties../ho-IL/apps/kaios-plus/service.properties../ho-IL/apps/kaios-plus/service.properties../ho-IL/apps/kaios-plus/service.properties../ho-IL/apps/kaios-plus/service.properties../ho-IL/apps/kaios-plus/service.properties../ho-IL/apps/kaios-plus/service.properties../ho-IL/apps/kaios-plus/service.properties../ho-IL/apps/kaios-plus/service.properties../ho-IL/apps/kaios-plus/service.properties../ho-IL/apps/kaios-plus/service.properties../ho-IL/apps/kaios-plus/service.properties../ho-IL/apps/kaios-plus/service.properties../ho-IL/apps/kaios-plus/service.properties../ho-IL/apps/kaios-plus/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properties../ho-IL/apps/service.properti
```

Kai: 此类warning是正常的,请忽略。

3. en-US 翻译定制不生效

Kai: 请先参考章节2.1

若要定制en-US翻译,请确保修改的properties文件在apps和 gaia/shared目录下,而不是在gaia/locales下。此路径下只有修改除 en-US外其他语言的翻译才会生效。

4. 无法成功复用翻译

Kai:

- 检查两个sheet的表头,确保前七列是顺序和名称是一致的。两个sheet中的语言缩写名称也要保持一致。具体请参照章节 5.5。
- 将A列"path" 整列替换为D列的"pathimport",然后重试。

path	▼ filename	string	refname	▼ en-US	▼ fr-FR ▼ km-KH ▼ zu-ZA ▼
/apps/antitheft/	anti-theft	remote-ring-header	antitheft:anti-t	heft:remote-riRemote Rin	g Sonnerie à distandUkwenza I
/apps/antitheft/	anti-theft	remote-ring-text1	antitheft:anti-t	heft:remote-riThis devic	e is ringirSonnerie de l'appLe divayi
/apps/antitheft/	anti-theft	remote-ring-text2	antitheft:anti-t	heft:remote-riremote Ant	i-theft accompte antivol à cye-akhawu
/apps/antitheft/	anti-theft	ringer-dismiss	antitheft:anti-t	heft:ringer-diDismiss	Ignorer Chitha
/apps/bluetooth/	bluetooth	device-status-pairing	bluetooth:blueto	oth:device-staPairing wi	th deviceAssociation avec lUkubhangq
/apps/bluetooth/	bluetooth	device-status-tap-connect	bluetooth:blueto	oth:device-staPress \"Se	lect\" to pAppuyer sur SélectChofoza \
/apps/bluetooth/	bluetooth	device-status-waiting	bluetooth:blueto	oth:device-staWaiting fo	r other devAttente d'un autrIlinde en
/apps/bluetooth/	bluetooth	error-connect-msg	bluetooth:blueto	oth:error-connCheck that	the deviceVérifiez que l'arHlola uku
/apps/bluetooth/	bluetooth	error-connect-title	bluetooth:blueto	oth:error-connUnable to	connect de Impossible de conrAyikwazi
/apps/bluetooth/	bluetooth	error-pair-checkpin	bluetooth:blueto	oth:error-pairDo you wan	t to try paVoulez-vous réessaUyafuna y
/apps/bluetooth/	bluetooth	error-pair-fail	bluetooth:blueto	oth:error-pair {{devicena	me}} isn't {{devicename}} ne {{devicen
/apps/bluetooth/	bluetooth	error-pair-pincode	bluetooth:blueto	oth:error-pairUnable to	pair with (Impossible de s'aAyikwazi
/apps/bluetooth/	bluetooth	error-pair-title	bluetooth:blueto	oth:error-pairUnable To	Pair DeviceAppairage de l'arAyikwazi
/apps/bluetooth/	bluetooth	error-pair-toofast	bluetooth:blueto	oth:error-pairUnable to	pair with (Impossible de s'aAyikwazi
/apps/bluetooth/	bluetooth	error-transfer-settings	bluetooth:blueto	oth:error-tranBluetooth	file transféchec du transfertUkuthumel
/apps/bluetooth/	bluetooth	error-transfer-title	bluetooth:blueto	oth:error-tranBluetooth	file transfÉchec du transfertUkuthumel
/apps/bluetooth/	bluetooth	ok	bluetooth:blueto	oth:ok OK	OK KULUNGILE
/apps/bluetooth/	bluetooth	pair	bluetooth:blueto	oth:pair Pair	Appairer Bhangqa
/apps/bluetooth/	bluetooth	pair-view-title	bluetooth:blueto	oth:pair-view-Bluetooth	Request Demande Bluetooth Isicelo S
/apps/bluetooth/	bluetooth	paired-failed	bluetooth:blueto	oth:paired-faiFailed to	pair with Impossible d'appaYehluleki

5. 如何新增/删除语言

Kai: 首先请在gaia/locales中新增/删除所需语言的locales文件。同时要修改language_all.json文件,按照原来的格式新加/删除所需的语言行。

```
languages all.json 995 Bytes
```

```
1 { "af-ZA"
                "Afrikaans",
     "ar-SA"
              "عربي",
"वाश्ना (IN)",
     "bn-IN"
 5
     "de-DE"
               : "Deutsch",
 6
     "en-GB"
               : "English (GB)",
 7
               : "English (US)",
     "en-US"
 8
     "es-US"
               : "Español (US)",
 9
      "es-ES"
                : "Español (ES)",
10
      "fa-IR"
                ,"(IR) فارسى":
11
      "fr-CA"
                : "French (CA)",
      "fr-FR"
                : "Français (FR)",
                : "हिन्दी",
13
     "hi-HI"
               : "Magyar",
14 "hu-HU"
15 "id-ID"
              : "Bahasa Indonesia",
16 "it-IT"
               : "Italiano",
17
               : "Melayu",
     "ms-MY"
               : "नेपाली",
18
     "ne-IN"
19
     "n1-NL"
               : "Nederlands",
     "p1-PL"
20
               : "Polski",
                : "Português (do Brasil)",
21
      "pt-BR"
      "pt-PT"
                : "Português (Portugal)",
      "no-RO"
                : "Românâ",
                : "Русский",
24
     "ru-RU"
                : "Kiswahili",
     "sw-ZA"
     "ta-IN"
                : "தமிழ்",
     "th-TH"
               : "ไทย" ,
               : "Türkçe",
28
      "tr-TR"
29
      "un-PK"
               ,"اردو":
30
      "vi-VN"
               : "Tiếng Việt",
31
      "zh-CN"
               : "中文 (简体)",
                : "isiZulu"
     "zu-ZA"
33 }
```