

tpsccli MCP server 0.2.0 — dtpos CONFIG files — Test Cases

The nine tools driven from a Claude Code session against the real dtpos 4.04 CONFIG folder, OPTIONS.TPS first; every write read back with a select - tick steps, paste the JSON results, record verdicts, print a PDF report.



tpsccli MCP server 0.2.0 — dtpos CONFIG files (OPTIONS.TPS) from a Claude Code session — Test Completion Report

Test results — a dated, signed completion report.

Feature	tpsccli MCP server 0.2.0 — dtpos CONFIG files (OPTIONS.TPS) from a Claude Code session
Tester	Claude Code session (mcp__tpsccli tools)
Reviewer / Lead	—
Date	2026-09-20
Build / version under test	be95a64
Environment	WINVMB40B / Microsoft Windows NT 10.0.26200.0 / PowerShell 7.6.0 / node v20.18.1 / Claude Code (Opus 5)
Component / area	mcp\dist\server.js (MCP client: Claude Code session (mcp__tpsccli tools))
Ticket / branch	feature/tpsccli-mcp
Report generated	2026-09-20 19:41

PASS — cleared to merge

All CORE and HIGH priority cases passed.

17
PASS

0
FAIL

1
BLOCKED

0
N/A

0
NOT RUN

Results detail

Case	Priority	Result	Title	Notes
TC-01	CORE	PASS	The registered server is connected and the session sees its nine tools	every check matched: nine tools loaded (tps_set_roots among them), server 0.2.0 / exe 0.1.0, roots [] PowerShell: <code>claudemcp list 2>&1 Select-String tpsccli; "node \$(node --version) / \$env:COMPUTERNAME / \$([System.Environment]::OSVersion.VersionString) / PowerShell \$(\$PSVersionTable.PSVersion)"; Get-Date -Format s; "OWNER set: \$([bool]\$env:TPSCCLI_OWNER)"</code> tpsccli: <code>node C:\Projects\GitHub\tpsccli\mcp\dist\server.js --allow-writes - ✓ Connected</code> node v20.18.1 / WINVMB40B / Microsoft Windows NT 10.0.26200.0 / PowerShell 7.6.0 2026-09-20T19:19:50 OWNER set: False Assistant answer after /mcp reconnected tpsccli (this session): the loaded mcp__tpsccli_* schemas are tps_version, tps_list_files, tps_set_roots, tps_describe, tps_select, tps_insert, tps_update, tps_delete and tps_query (nine). Tool call: <code>tps_version {}</code> <code>{"server":"0.2.0","exe":{"ok":true,"op":null,"version":"0.1.0","complete":true},"roots":[]}</code>
TC-02	CORE	PASS	Fresh work copy of the CONFIG folder	every check matched PowerShell: <code>New-Item -ItemType Directory -Force 'C:\Projects\GitHub\tpsccli\mcp\work\config' Out-Null ; Copy-Item 'C:\Projects\GitLab\POS\dtpos_404_data\CONFIG*.TPS' 'C:\Projects\GitHub\tpsccli\mcp\work\config' -Force ; (Get-ChildItem 'C:\Projects\GitHub\tpsccli\mcp\work\config*.TPS').Count</code> 64 Tool call: <code>tps_describe {"file": "C:\Projects\GitHub\tpsccli\mcp\work\config\OPTIONS.TPS"}</code> <code>{"ok":true,"op":"describe","file":"C:\Projects\GitHub\tpsccli\mcp\work\config\OPTIONS.TPS","encrypted":false,"records":407,"columns":[{"name":"CUSTOMER","type":"STRING","size":32},{name":"MODULE","type":"STRING","size":32},{name":"VARIABLE","type":"STRING","size":32},{name":"VALUE","type":"STRING","size":64},{name":"ENTRYPICTURE","type":"STRING","size":20},{name":"DESCRIPTION","type":"STRING","size":50},{name":"COMMENTS","type":"STRING","size":1024}],keys":[{"name":"OPTKEY","primary":false,"unique":true,"nocase":true,"components":[{"col":"CUSTOMER","asc":true},{col":"MODULE","asc":true},{col":"VARIABLE","asc":true}],name":"DESCRIPTKEY","primary":false,"unique":false,"nocase":true,"optional":true,"components":[{"col":"CUSTOMER","asc":true},{col":"MODULE","asc":true},{col":"DESCRIPTION","asc":true}]},complete":true}</code>

TC-03	CORE	PASS	Listing without a root: tps_list_files by directory, then tps_set_roots makes CONFIG the root	every check matched: directory listing 64 entries; tps_set_roots replaced the (empty) set; the bare name resolved in the new root; the bare listing gave the same 64 entries. OPTIONS.TPS modified stamp unchanged across the describe (06:23:55.647Z before and after). Tool call: tps_list_files {"directory": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG"} <pre>{ "files": [{ "name": "ACCESS.TPS", "path": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\ACCESS.TPS", "size": 62208, "modified": "2026-09-16T14:08:19.354Z" }, { "name": "BAUDRATE.TPS", "path": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\BAUDRATE.TPS", "size": 1024, "modified": "2026-09-20T05:18:01.936Z" }, { "name": "OPTIONS.TPS", "path": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS", "size": 118016, "modified": "2026-09-20T06:23:55.647Z" }, { "name": "WSFILESX.TPS", "path": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\WSFILESX.TPS", "size": 1536, "modified": "2026-09-20T05:18:04.849Z" }] }</pre> (abridged: 64 entries, every path under C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG) PowerShell: (Get-ChildItem 'C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG*.TPS').Count ; (Get-Item 'C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS').Length 64 118016 Tool call: tps_set_roots {"roots": ["C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG"]} <pre>{ "roots": ["C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG"] }</pre> Tool call: tps_describe {"file": "OPTIONS.TPS"} <pre>{ "ok": true, "op": "describe", "file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS", "encrypted": false, "records": 407, "columns": [{ "name": "CUSTOMER", "type": "STRING", "size": 32, "name": "MODULE", "type": "STRING", "size": 32, "name": "VARIABLE", "type": "STRING", "size": 32, "name": "VALUE", "type": "STRING", "size": 64, "name": "ENTRYPICTURE", "type": "STRING", "size": 20, "name": "DESCRIPTION", "type": "STRING", "size": 50, "name": "COMMENTS", "type": "STRING", "size": 1024 }], "keys": [{ "name": "OPTKEY", "primary": false, "unique": true, "nocase": true, "components": [{ "col": "CUSTOMER", "asc": true }, { "col": "MODULE", "asc": true }, { "col": "VARIABLE", "asc": true }] }, { "name": "DESCRIPTKEY", "primary": false, "unique": false, "nocase": true, "optional": true, "components": [{ "col": "CUSTOMER", "asc": true }, { "col": "MODULE", "asc": true }, { "col": "DESCRIPTION", "asc": true }] }], "complete": true }</pre> Tool call: tps_list_files {} <pre>{ "files": [{ "name": "ACCESS.TPS", "path": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\ACCESS.TPS", "size": 62208, "modified": "2026-09-16T14:08:19.354Z" }, { "name": "BAUDRATE.TPS", "path": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\BAUDRATE.TPS", "size": 1024, "modified": "2026-09-20T05:18:01.936Z" }, { "name": "OPTIONS.TPS", "path": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS", "size": 118016, "modified": "2026-09-20T06:23:55.647Z" }, { "name": "WSFILESX.TPS", "path": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\WSFILESX.TPS", "size": 1536, "modified": "2026-09-20T05:18:04.849Z" }] }</pre> (abridged: 64 entries, every path under C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG)												
TC-04	CORE	PASS	Describe OPTIONS.TPS	every check matched: seven STRING columns 32/32/32/64/20/50/1024; OPTKEY unique nocase (CUSTOMER, MODULE, VARIABLE); DESCRIPTKEY non-unique nocase optional (CUSTOMER, MODULE, DESCRIPTION); neither primary Tool call: tps_describe {"file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS"} <pre>{ "ok": true, "op": "describe", "file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS", "encrypted": false, "records": 407, "columns": [{ "name": "CUSTOMER", "type": "STRING", "size": 32, "name": "MODULE", "type": "STRING", "size": 32, "name": "VARIABLE", "type": "STRING", "size": 32, "name": "VALUE", "type": "STRING", "size": 64, "name": "ENTRYPICTURE", "type": "STRING", "size": 20, "name": "DESCRIPTION", "type": "STRING", "size": 50, "name": "COMMENTS", "type": "STRING", "size": 1024 }], "keys": [{ "name": "OPTKEY", "primary": false, "unique": true, "nocase": true, "components": [{ "col": "CUSTOMER", "asc": true }, { "col": "MODULE", "asc": true }, { "col": "VARIABLE", "asc": true }] }, { "name": "DESCRIPTKEY", "primary": false, "unique": false, "nocase": true, "optional": true, "components": [{ "col": "CUSTOMER", "asc": true }, { "col": "MODULE", "asc": true }, { "col": "DESCRIPTION", "asc": true }] }], "complete": true }</pre>												
TC-05	CORE	PASS	Select option rows by module and by full key	every check matched Tool call: tps_select {"file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS", "columns": ["CUSTOMER", "VARIABLE", "VALUE"], "where": "MODULE = 'Tenders'"} <pre>{ "ok": true, "op": "select", "columns": [{ "name": "CUSTOMER", "type": "STRING" }, { "name": "VARIABLE", "type": "STRING" }, { "name": "VALUE", "type": "STRING" }], "rows": [["JDA", "Accept All Manual Credit Cards", "N", "JDA", "EBT Default Expiration", "1249"], ["DLT", "EnableQuickCash", "N", "DLT", "QuickCashMode", "I", "DLT", "AmountOKThreshold", "999.99"], ["DLT", "AmountOKCashBack", "N", "DLT", "AmountOKCashBack", "N", "DLT", "AmountOKCashBack", "N"]], "row_count": 6, "truncated": false, "complete": true }</pre> Tool call: tps_select {"file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS", "columns": ["VARIABLE", "VALUE"], "where": "CUSTOMER = 'DLT' AND MODULE = 'BOPIIS'", "order_by": "VARIABLE"} <pre>{ "ok": true, "op": "select", "columns": [{ "name": "VARIABLE", "type": "STRING" }, { "name": "VALUE", "type": "STRING" }], "rows": [["CheckInterval", "10"], ["Enabled", "N"], ["Path", "C:\\JDA\\BOPIIS\\JSON"], ["UnprocessedPath", "C:\\JDA\\BOPIIS\\Unprocessed"], ["ValidTypes", "1,2,3"], ["WarningThreshold", "20"]], "row_count": 6, "truncated": false, "complete": true }</pre> Tool call: tps_select {"file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS", "columns": ["VALUE"], "where": "CUSTOMER = 'DLT' AND MODULE = 'Tenders' AND VARIABLE = 'QuickCashMode'"} <pre>{ "ok": true, "op": "select", "columns": [{ "name": "VALUE", "type": "STRING" }], "rows": [["I"]], "row_count": 1, "truncated": false, "complete": true }</pre>												
TC-06	HIGH	PASS	Order, page and cap the 407 option rows, and read them as a table	every check matched Tool call: tps_select {"file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS", "columns": ["CUSTOMER", "MODULE", "VARIABLE", "VALUE"], "order_by": "CUSTOMER, MODULE, VARIABLE", "limit": 12} <pre>{ "ok": true, "op": "select", "columns": [{ "name": "CUSTOMER", "type": "STRING" }, { "name": "MODULE", "type": "STRING" }, { "name": "VARIABLE", "type": "STRING" }, { "name": "VALUE", "type": "STRING" }], "rows": [["DLT", "AssociateSale", "DefaultAllowPurchase", "V"], ["DLT", "AssociateSale", "ReportDayOfWeek", "2"], ["DLT", "BOPIIS", "CheckInterval", "10"], ["DLT", "BOPIIS", "Enabled", "N"], ["DLT", "BOPIIS", "Path", "C:\\JDA\\BOPIIS\\JSON"], ["DLT", "BOPIIS", "UnprocessedPath", "C:\\JDA\\BOPIIS\\Unprocessed"], ["DLT", "BOPIIS", "ValidTypes", "1,2,3"], ["DLT", "BOPIIS", "WarningThreshold", "20"], ["DLT", "BottleDeposit", "INVColor", "00999"], ["DLT", "Canada", "GSTOnlyTaxCode", "GST"], ["DLT", "Canada", "PrintShelfTagUOM", "N"], ["DLT", "Canada", "ShelfTagPriceChangeDept", "010,012,014"]], "row_count": 12, "truncated": true, "complete": true }</pre> Tool call: tps_select {"file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS", "columns": ["CUSTOMER", "MODULE", "VARIABLE", "VALUE"], "order_by": "CUSTOMER, MODULE, VARIABLE", "limit": 12, "offset": 12} <pre>{ "ok": true, "op": "select", "columns": [{ "name": "CUSTOMER", "type": "STRING" }, { "name": "MODULE", "type": "STRING" }, { "name": "VARIABLE", "type": "STRING" }, { "name": "VALUE", "type": "STRING" }], "rows": [["DLT", "Device", "Serial Secondary Scanner Port", "COM7"], ["DLT", "EOD", "AutoCloseTSP", "V"], ["DLT", "EOD", "AutoEODEndTime", "3:00:00"], ["DLT", "EOD", "AutoEODStartDelay", "30"], ["DLT", "EOD", "AutoEODStartTime", "21:00:00"], ["DLT", "EOD", "PurgeDefaultEmployeesInDays", "90"], ["DLT", "GiftCard", "CashOutMaxAmount", "15.00"], ["DLT", "GiftCard", "EnableIncommProcessing", "N"], ["DLT", "GiftCard", "GiftCardDepartment", "EG"], ["DLT", "GiftCard", "GiftCardMaximum", "100.00"], ["DLT", "GiftCard", "GiftCardMinimum", "5.00"], ["DLT", "GiftCard", "GiftCardType", "00950"]], "row_count": 12, "truncated": true, "complete": true }</pre> Tool call: tps_select {"file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS", "columns": ["CUSTOMER"], "limit": 0} <pre>{ "ok": true, "op": "select", "columns": [{ "name": "CUSTOMER", "type": "STRING" }], "rows": [["JDA", "JDA", ...], ["DLT"]], "row_count": 407, "truncated": false, "complete": true }</pre> (abridged: 407 rows) Tool call: tps_select {"file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS", "columns": ["CUSTOMER", "MODULE", "VARIABLE"], "order_by": "CUSTOMER, MODULE, VARIABLE", "limit": 3, "format": "table"} <table><tr><th>CUSTOMER</th><th>MODULE</th><th>VARIABLE</th></tr><tr><td>DLT</td><td>AssociateSale</td><td>DefaultAllowPurchase</td></tr><tr><td>DLT</td><td>AssociateSale</td><td>ReportDayOfWeek</td></tr><tr><td>DLT</td><td>BOPIIS</td><td>CheckInterval</td></tr></table> (3 rows, truncated by LIMIT)	CUSTOMER	MODULE	VARIABLE	DLT	AssociateSale	DefaultAllowPurchase	DLT	AssociateSale	ReportDayOfWeek	DLT	BOPIIS	CheckInterval
CUSTOMER	MODULE	VARIABLE														
DLT	AssociateSale	DefaultAllowPurchase														
DLT	AssociateSale	ReportDayOfWeek														
DLT	BOPIIS	CheckInterval														

TC-07	CORE	PASS	Every CONFIG file with compressed pages describes (regression for the DeRle fix)	every check matched: CACODE 107/7, COMNDMST 97/50, CRPCMCFG 42/4, EODMNT 133/10, ERRORMSG 247/3, INCOMMCC 56/8, keybrdrv 67/7, OPTIONS 407/7, PMINTHDR 137/8, RPTDEF 12/14: SCRFIELD gives the documented multi-table limit Ten tool calls tps_describe {"file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\NAME.TPS"}; records / columns from each result (full JSON in the session transcript): <pre>CACODE 107 / 7 (ok true) COMNDMST 97 / 50 (ok true) CRPCMCFG 42 / 4 (ok true) EODMNT 133 / 10 (ok true) ERRORMSG 247 / 3 (ok true) INCOMMCC 56 / 8 (ok true) keybrdrv 67 / 7 (ok true) OPTIONS 407 / 7 (ok true) PMINTHDR 137 / 8 (ok true) RPTDEF 12 / 14 (ok true)</pre> Tool call: tps_describe {"file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\SCRFIELD.TPS"} {"ok":false,"op":"describe","error":{"code":"DEFINITION_UNREADABLE","message":"File holds more than one table (1 and 17669); multi-table TPS files are not supported"},"complete":true}
TC-08	MED	BLOCKED	Encrypted CONFIG files need the owner string from the environment	owner string not available (\$env:TPSCLI_OWNER not set on this machine); step 1 matched, steps 2 and 3 not performed Tool call: tps_describe {"file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\ACCESS.TPS"} {"ok":false,"op":"describe","error":{"code":"OWNER_REQUIRED","message":"Not a plain TopSpeed file; if it is encrypted pass --owner"},"complete":true}
TC-09	HIGH	PASS	Reading the real OPTIONS.TPS leaves its content unchanged	every check matched: SHA-256 and LastWriteTimeUtc identical before and after the describe and the uncapped select (reads open ReadOnly) PowerShell: \$h1 = (Get-FileHash 'C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS').Hash ; \$m1 = (Get-Item 'C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS').LastWriteTimeUtc ; \$h1 ; \$m1 2A48EF8633B1ED990952EE36F4CDF0D7949A5BA7079759922EFB4EF7DA40E7E 2026-09-20T06:23:55.6467310Z Tool call: tps_describe {"file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS"} {"ok":true,"op":"describe","file":"C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS","encrypted":false,"records":407,"columns":[{"name":"CUSTOMER","type":"STRING","size":32},{ "name":"MODULE","type":"STRING","size":32},{ "name":"VARIABLE","type":"STRING","size":32},{ "name":"VALUE","type":"STRING","size":64},{ "name":"ENTRYPICTURE","type":"STRING","size":20},{ "name":"DESCRIPTION","type":"STRING","size":50},{ "name":"COMMENTS","type":"STRING","size":1024}], "keys":[{"name":"OPTKEY","primary":false,"unique":true,"nocase":true,"components":[{"col":"CUSTOMER","asc":true},{ "col":"MODULE","asc":true},{ "col":"VARIABLE","asc":true}], "name":"DESCRIPTKEY","primary":false,"unique":false,"nocase":true,"optional":true,"components":[{"col":"CUSTOMER","asc":true},{ "col":"MODULE","asc":true},{ "col":"DESCRIPTION","asc":true}]}], "complete":true} Tool call: tps_select {"file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS", "columns": ["CUSTOMER"], "limit": 0} {"ok":true,"op":"select","columns":[{"name":"CUSTOMER","type":"STRING"}],"rows":[{"JDA"}, {"JDA"}, ... , {"DLT"}, {"DLT"}],"row_count":407,"truncated":false,"complete":true} (abridged: 407 rows) PowerShell: \$h2 = (Get-FileHash 'C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS').Hash ; \$m2 = (Get-Item 'C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS').LastWriteTimeUtc ; (\$h1 -eq \$h2) ; (\$m1 -eq \$m2) 2A48EF8633B1ED990952EE36F4CDF0D7949A5BA7079759922EFB4EF7DA40E7E 2026-09-20T06:23:55.6467310Z True True
TC-10	CORE	PASS	Dry run an UPDATE against the real OPTIONS.TPS: validated, nothing written	every check matched: parse_only true, no matched/affected; value still I; hash unchanged PowerShell: \$h1 = (Get-FileHash 'C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS').Hash ; \$h1 2A48EF8633B1ED990952EE36F4CDF0D7949A5BA7079759922EFB4EF7DA40E7E Tool call: tps_query {"sql": "UPDATE [C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS] SET VALUE = 'C' WHERE CUSTOMER = 'DLT' AND MODULE = 'Tenders' AND VARIABLE = 'QuickCashMode'", "parse_only": true} {"ok":true,"op":"update","parse_only":true,"complete":true} Tool call: tps_select {"file": "C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS", "columns": ["VALUE"], "where": "CUSTOMER = 'DLT' AND MODULE = 'Tenders' AND VARIABLE = 'QuickCashMode'" } {"ok":true,"op":"select","columns":[{"name":"VALUE","type":"STRING"}],"rows":[{"I"}],"row_count":1,"truncated":false,"complete":true} PowerShell: \$h2 = (Get-FileHash 'C:\\Projects\\GitLab\\POS\\dtpos_404_data\\CONFIG\\OPTIONS.TPS').Hash ; \$h1 -eq \$h2 2A48EF8633B1ED990952EE36F4CDF0D7949A5BA7079759922EFB4EF7DA40E7E True
TC-11	CORE	PASS	Insert an option row into the copy and read it back	every check matched Tool call: tps_insert {"file": "C:\\Projects\\GitHub\\tpsccli\\mcp\\work\\config\\OPTIONS.TPS", "values": {"CUSTOMER": "UTS", "MODULE": "Test", "VARIABLE": "InsertedByMcp", "VALUE": "yes", "ENTRYPICTURE": "@s64", "DESCRIPTION": "Inserted by the unit-test instrument", "COMMENTS": "TC-11"}} {"ok":true,"op":"insert","affected":1,"complete":true} Tool call: tps_select {"file": "C:\\Projects\\GitHub\\tpsccli\\mcp\\work\\config\\OPTIONS.TPS", "where": "CUSTOMER = 'UTS'" } {"ok":true,"op":"select","columns":[{"name":"CUSTOMER","type":"STRING"}, {"name":"MODULE","type":"STRING"}, {"name":"VARIABLE","type":"STRING"}, {"name":"VALUE","type":"STRING"}, {"name":"ENTRYPICTURE","type":"STRING"}, {"name":"DESCRIPTION","type":"STRING"}, {"name":"COMMENTS","type":"STRING"}],"rows":[{"UTS", "Test", "InsertedByMcp", "yes", "@s64", "Inserted by the unit-test instrument", "TC-11"}],"row_count":1,"truncated":false,"complete":true} Tool call: tps_describe {"file": "C:\\Projects\\GitHub\\tpsccli\\mcp\\work\\config\\OPTIONS.TPS"} {"ok":true,"op":"describe","file":"C:\\Projects\\GitHub\\tpsccli\\mcp\\work\\config\\OPTIONS.TPS","encrypted":false,"records":408,"columns":[{"name":"CUSTOMER","type":"STRING","size":32},{ "name":"MODULE","type":"STRING","size":32},{ "name":"VARIABLE","type":"STRING","size":32},{ "name":"VALUE","type":"STRING","size":64},{ "name":"ENTRYPICTURE","type":"STRING","size":20},{ "name":"DESCRIPTION","type":"STRING","size":50},{ "name":"COMMENTS","type":"STRING","size":1024}], "keys":[{"name":"OPTKEY","primary":false,"unique":true,"nocase":true,"components":[{"col":"CUSTOMER","asc":true},{ "col":"MODULE","asc":true},{ "col":"VARIABLE","asc":true}], "name":"DESCRIPTKEY","primary":false,"unique":false,"nocase":true,"optional":true,"components":[{"col":"CUSTOMER","asc":true},{ "col":"MODULE","asc":true},{ "col":"DESCRIPTION","asc":true}]}], "complete":true}
TC-12	CORE	PASS	Duplicate key is refused, in any letter case, and the select still shows one row	every check matched Tool call: tps_insert {"file": "C:\\Projects\\GitHub\\tpsccli\\mcp\\work\\config\\OPTIONS.TPS", "values": {"CUSTOMER": "UTS", "MODULE": "Test", "VARIABLE": "InsertedByMcp", "VALUE": "again"}} {"ok":false,"op":"insert","error":{"code":"DUPLICATE_KEY","message":"Duplicate value for key OPTKEY","key":"OPTKEY"},"outcome":"none","complete":true} Tool call: tps_insert {"file": "C:\\Projects\\GitHub\\tpsccli\\mcp\\work\\config\\OPTIONS.TPS", "values": {"CUSTOMER": "uts", "MODULE": "test", "VARIABLE": "insertedbymcp", "VALUE": "again"}} {"ok":false,"op":"insert","error":{"code":"DUPLICATE_KEY","message":"Duplicate value for key OPTKEY","key":"OPTKEY"},"outcome":"none","complete":true} Tool call: tps_select {"file": "C:\\Projects\\GitHub\\tpsccli\\mcp\\work\\config\\OPTIONS.TPS", "columns": ["VALUE"], "where": "CUSTOMER = 'UTS'" } {"ok":true,"op":"select","columns":[{"name":"VALUE","type":"STRING"}],"rows":[{"yes"}],"row_count":1,"truncated":false,"complete":true}

[illegible]

Sign-off

Tester	— · — · —
Reviewer / Lead	— · — · —
Owner	— · — · —