Computer Graphic Note

Jiechang Shi

Version: 1.00

Update: September 25, 2019

1 Class 1: Overview

1. Frame Buffer
   - Pixel: One element of a frame buffer
   - Pixel depth: Number of bytes per-pixel in the buffer
   - Resolution: Width × Height
   - Buffer size: Total memory allocated for frame buffer
   - **Exam Question**: Given Resolution and Pixel depth, Asked Buffer size
   - Z Value: For solving the hidden-surface removal(HSR) problem

2 Class 2,3: Rasterization

1. For each pixel on screen, the sample point of that pixel is the center point of that pixel, which have **integer** coordinates. For examples, $(3, 2)$.
2. A simple problem: Rasterizing Lines

   Program Description: Given two endpoints, $P = (x_0, y_0)$, $R = (x_1, y_1)$ find the pixels that make up the line.

   Note that: Lines are infinitely thin so they rarely fall on pixel sample point.

   A Feasible Description: Rasterize lines as **closest** pixels to actual lines, with 2 requirement
   - No Gap
   - Minimize error(distance to true line)

   To make this question simplify: Only consider situation that $|x_1 - x_0| \geq |y_1 - y_0| \geq 0 \wedge |x_1 - x_0| \neq 0$, which means the $-1 \leq slope \leq 1$. Otherwise we just exchange x and y.

   A basic Algorithm: $k = \frac{y_1 - y_0}{x_1 - x_0}$, $d = y_0 - kx_0$, for each $x_0 \leq x \leq x_1$, $y = ROUND(kx + d)$. This method by brute force is inefficient because of the multiplication and the function $ROUND()$.

   Basic Incremental Algorithm: for each $x_0 \leq x_i < x_{i+1} \leq x_1$, $y_{i+1} = y_i + k$, However, the successsive addition of a real number can lead to a **cumulative error buildup**!

   Midpoint Line Algorithm:
   - For $0 \leq k \leq 1$
   - For one approximate point $P = (x, y)$, we only have 2 choices for the next point $E = (x + 1, y)$ and $NE = (x + 1, y + 1)$, we should choose the one which is closer to $k(x + 1) + d$
   - Calculate the middle point $M = (x + 1, y + \frac{1}{2})$

- If the **Intersection point** Q is below M, take E as next, otherwise take NE as next.
- Note that: we consider this equation:

$$f(x,y) = ax + by + c = (y_1 - y_0)x - (x_1 - x_0)y + (x_1y_0 - y_1x_0)$$

  We assume $a > 0$
- For a point (x, y)
  if $f(x, y) = 0$, (x, y) lies on the line.
  if $f(x, y) < 0$, (x, y) lies upon the line.
  if $f(x, y) > 0$, (x, y) lies below the line.
- So we have to test $f(M) = a(x + 1) + b(y + \frac{1}{2}) + c = f(Former) + a + \frac{b}{2}$
- Assum $a > 0$, if $f(M) > 0$ choose NE otherwise choose E
- Update $f(Former)$:
  If we choose E, $f(Former) = f(Former) + a$
  If we choose NE, $f(Former) = f(Former) + a + b$
  Note that:a and b are **constant integer**, so here is no **cumulative error issuse**

3. A harder problem: Triangles Rasterization

   Why Triangle:
   - Triangles (*tris*) are a simple explicit 3D surface representation.
   - Convex and concave polygons (*polys*) can be decomposed into triangles.
   - Tris are planar and unambiguously defined by three vertex(*verts*) coordinates (*coords*).

   Definition: Find and draw **pixel** samples **inside** *tri* edges and interpolate parameters defined at *verts*

4. **Rasterizxation and Hidden Surface Removal(HSR) Algorithm Classes**:
   - Image order rasterization: ray tracing/ ray casting
     traverse pixel, process each in world-space
     transform rays from image-space to world-space
   - Object order rasterization: scan-line / LEE
     traverse triangles, process each in image-space
     transform objects from model-space to image-space

5. **LEE Linear Expression Evaluation Algorithm**:
   - We already discussed in *Midpoint Line Algorithm* that how to determine a point is on the left(up) or right(below) the line, just *a quick review here*:
     Assume the lien have a positive *slope*
     For an Edge Equation E, for point (x, y): $E(x, y) = dY(x - X) - dX(y - Y)$
     if $E(x, y) = 0$, (x, y) lies on the line.
     if $E(x, y) < 0$, (x, y) lies right(below) the line.
     if $E(x, y) > 0$, (x, y) lies left(up) the line.
   - For **Rasterization**:
     Compute LEE result for all three edges.
     Pixels with **consistent sign** for all three edges are inside the *tri*.
     Include **edge pixels** on left or right edges.
   - LEE need to check every pixel in the bounding box.
   - LEE is very good in parallel(SIMD) system.
   - Furthermore: Given 3 random *verts* how to find CW edge cycle
     Determine L/R and Top/Bot edges for edge-pixel ownership

6. **Scan Line Rasterizer**:

- Sort vets by Y
- Setup edge DDAs for edges
- Sort edges by L or R(The long edge on left or right)
- Start from Top Vertice, and switch DDA when hit the middle vertice.

7. **Interpolate Z**:
   A general 3D plane equation has 4 terms: $Ax + By + Cz + D = 0$
   (A, B, C) is the normal of that plane, so $(X, Y, Z)_0 \times (X, Y, Z)_1 = (A, B, C)$
   Then plug any vertex coord into equation and solve for D.
   Given (A, B, C, D) and any point (x, y) can solve z
8. **Used Z-buffer to remove hidden surfaces**
   Initial Z-buffer to MAXINT at the begining of every frame
   Interpolate vertex Z values to get Z_{pix}
   Only write new pixel to the buffer if $Z_{pix} < Z_{buffer}$
   Notice that Z should always **bigger or equal to zero!**
9. Hidden Line Removal(HLR):
   Simple z-buffer does not work when the render only draws edge(outlines of polygons).
   Need edge-crossing and object sorting methods.
10. **Painter's Algorithm**: render in order front to back
    A object is in front of another object means:
    Z of all verts of one object is less than the other.
    This algorithm not work if Z-sort is ambiguous.
11. **Warnock Algorithm**:
    Subdivide screen untril a leaf region has a simple front/back relationship.
    Leaf regions have one or zero surfaces visible, and the smallest region is usually a pixel
    Usually use quad tree subdivision
12. **BSP-Tree**:
    View-Independent binary tree(pre-calculated) allows a view-dependent front-to-back or back-to-front traversal of surfaces.
    Use Painter Algorithm to do back-to-front traversal.
    Useful for **transparency** - full depth-sort of all surface.
13. **Culling**:
    - Culling with portals: pre-compute the invisible part.
    - Culling by View Frustum: Skip a triangle iff all its vertices are beyond **the same screen edge**!
      Pitfall: If the vertices are beyond different edge, some part of the *tri* might still in the screen. Image a giant *tri* that cover the whole screen.
    - Backface Culling: For **closed(water-tight)** objects, surfaces with **oriented-normals facing away** from the camera are never visible.
      Pitfall: BF Culling only work for water-tight object!
    - Frustum: Only visible triangles are drawn into the frame buffer.

3 Class 4,5,6,7:Transformations

- Linear transformations (*Xforms*) define a mapping of coordinates (*coords*) in one coordinate frame to another.

$$V_b = X_{ba} V_a$$

- **Homogeneous Vector** (V) is 4×1 columns $(x, y, z, w)^T$
- **Homogeneous Transforms** (X) is 4×4 matrix
- From Homogeneous Vector to 3D Vector:

$$x = \frac{x}{w}, y = \frac{y}{w}, z = \frac{z}{w}$$

- **Why** we use Homogeneous Vector?

  We want to uniform the transform matrix including translation, scaling, rotation in the same form of matrix.

3.1 Transformation Matrix

1. **Translation**:

$$T(t_x, t_y, t_z) \Rightarrow \begin{bmatrix} 1 & 0 & 0 & t_x \\ 0 & 1 & 0 & t_y \\ 0 & 0 & 1 & t_z \\ 0 & 0 & 0 & 1 \end{bmatrix}, T^{-1}(t_x, t_y, t_z) = T(-t_x, -t_y, -t_z)$$

2. **Scaling**:

$$S(s_x, s_y, s_z) \Rightarrow \begin{bmatrix} s_x & 0 & 0 & 0 \\ 0 & s_y & 0 & 0 \\ 0 & 0 & s_z & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}, S^{-1}(s_x, s_y, s_z) = S(\frac{1}{s_x}, \frac{1}{s_y}, \frac{1}{s_z})$$

3. **Rotation, CCW**:

$$R_x(\theta) \Rightarrow \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & cos\theta & -sin\theta & 0 \\ 0 & sin\theta & cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}, R_x^{-1}(\theta) = R_x^T(\theta)$$

$$R_y(\theta) \Rightarrow \begin{bmatrix} cos\theta & 0 & sin\theta & 0 \\ 0 & 1 & 0 & 0 \\ -sin\theta & 0 & cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}, R_y^{-1}(\theta) = R_y^T(\theta)$$

$$R_z(\theta) \Rightarrow \begin{bmatrix} cos\theta & -sin\theta & 0 & 0 \\ sin\theta & cos\theta & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}, R_z^{-1}(\theta) = R_z^T(\theta)$$

4. Pitfall: commutative property is for S,R only.

   Here assume **uniform scaling** in all dimensions.

   If S is not an uniform scaling matrix. S,R don't have commutative property.

3.2 Spaces Transformation

1. **NDC to Output Device**

$$X_{sp} \Rightarrow \begin{bmatrix} \frac{xs}{2} & 0 & 0 & \frac{xs}{2} \\ 0 & -\frac{ys}{2} & 0 & \frac{ys}{2} \\ 0 & 0 & MAXINT & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

Note that:

Output Device is **RH coords** and origin in **upper left**.$X \in [0, xs), Y \in [0, ys), Z \in [0, MAXINT]$

NDC is **LH coords** and origin at screen center. $X, Y \in [-1, 1], Z \in [0, 1]$

2. **Perspective Projection**

$$X_{pi} \Rightarrow \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & \frac{1}{d} & 0 \\ 0 & 0 & \frac{1}{d} & 1 \end{bmatrix}$$

What is d And **Why** there are two $\frac{1}{d}$?

- Assume camera is on $(0, 0, -d)$, perspective(also image) plane is $z = 0$, a object in world space is (X, Y, Z)
- Defined FOV(field of view) as the angle the camera can see.
- Note: $X \in [-1, 1]$, so the distant(d) from Forcus point to view plane can be calculate by this equation:

$$\frac{1}{d} = tan(\frac{FOV}{2})$$

- Futher More: The object project to view plane can be calculate by these equations:

$$\frac{X}{Z + d} = \frac{x}{d} \Rightarrow x = \frac{X}{\frac{Z}{d} + 1}$$

$$\frac{Y}{Z + d} = \frac{y}{d} \Rightarrow y = \frac{Y}{\frac{Z}{d} + 1}$$

$$\frac{Z}{Z + d} = \frac{z}{d} \Rightarrow z = \frac{Z}{\frac{Z}{d} + 1}$$

$$(x, y, z) = (\frac{X}{\frac{Z}{d} + 1}, \frac{Y}{\frac{Z}{d} + 1}, \frac{Z}{\frac{Z}{d} + 1})$$

- Write this 3D vector to Homogeneous Vector:

$$(x, y, z, w) = (X, Y, Z, \frac{Z}{d} + 1)$$

- Futher: We forcus on the **range** of Z now is $z \in (-\infty, d)$.

  But in NDC we hope $z \in [0, 1)$ So:

  We delete all vector that $Z < 0$, because they cannot project to the view plane.

  For $z >= 0$, we define $z' = \frac{z}{d}$
- $(x, y, z', w) = (X, Y, \frac{Z}{d}, \frac{Z}{d} + 1) = X_{pi} * (X, Y, Z, 1)$

Pitfall: **Do Z interpolation in Perspective Plane!**

Why we need the farest plane?

Asymptotic curve of $Z\ vs.\ z$, that z increase slower when Z is large.

It might map different Z to the same z

3.3 Camera Matrix

1. Assume camera position is c, camera look-at point is l, here c and l are both in world coordinate. And the world up vector is $\vec{up}$
2. Camera Z-axis **in world coordinate** is

$$\vec{Z} = \frac{\vec{cl}}{||\vec{cl}||}$$

3. Camera Y-axis **in world coordinate** is the orthogonal(vertical) part of world-up vector to Z-axis which is

$$\vec{up'} = \vec{up} - (\vec{up} \cdot \vec{Z})\vec{Z}$$

$$\vec{Y} = \frac{\vec{up'}}{||\vec{up'}||}$$

4. Camera X-axis **in world coordinate** is orthogonal to both Y and Z axises. So:

$$\vec{X} = \vec{Y} \times \vec{Z}$$

5. Build the X_{wi} from camera space to world space:
   X-axis vector $[1,0,0]$ in camera space should be $\vec{X}$ in world space, also for Y,Z-axis vectors, So:

$$X_{wi} \Rightarrow \begin{bmatrix} X_x & Y_x & Z_x & 0 \\ X_y & Y_y & Z_y & 0 \\ X_z & Y_z & Z_z & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

6. Also we need to add the translation of the camera to the Matrix:

$$X_{wi} \Rightarrow \begin{bmatrix} X_x & Y_x & Z_x & c_x \\ X_y & Y_y & Z_y & c_y \\ X_z & Y_z & Z_z & c_z \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

7. Now we can get the inverst matrix X_{iw}:

$$X_{iw} \Rightarrow \begin{bmatrix} X_x & X_y & X_z & -X \cdot c \\ Y_x & Y_y & Y_z & -Y \cdot c \\ Z_x & Z_y & Z_z & -Z \cdot c \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

8. In this proof we know that: If we know the X,Y,Z-axis in world coordinate for a specific space, we can easily build and inverst the translation from or to that space.
   This method can also be used to **proof the general rotation matrix**.
9. Orbit a Model about a Point
   The idea is the same as place camera.
   Need to care about **which space** you current in!