Computer Graphic Note

Jiechang Shi

Version: 1.1

Update: November 6, 2019

1 Class 1: Overview

1. Frame Buffer
   - Pixel: One element of a frame buffer
   - Pixel depth: Number of bytes per-pixel in the buffer
   - Resolution: Width × Height
   - Buffer size: Total memory allocated for frame buffer
   - **Exam Question**: Given Resolution and Pixel depth, Asked Buffer size
   - Z Value: For solving the hidden-surface removal(HSR) problem

2 Class 2,3: Rasterization

1. For each pixel on screen, the sample point of that pixel is the center point of that pixel, which have **integer** coordinates. For examples, $(3, 2)$.

2. A simple problem: Rasterizing Lines

   Program Description: Given two endpoints, $P = (x_0, y_0)$, $R = (x_1, y_1)$ find the pixels that make up the line.

   Note that: Lines are infinitely thin so they rarely fall on pixel sample point.

   A Feasible Description: Rasterize lines as **closest** pixels to actual lines, with 2 requirement
   - No Gap
   - Minimize error(distance to true line)

   To make this question simplify: Only consider situation that $|x_1 - x_0| \geq |y_1 - y_0| \geq 0 \wedge |x_1 - x_0| \neq 0$, which means the $-1 \leq slope \leq 1$. Otherwise we just exchange x and y.

   A basic Algorithm: $k = \frac{y_1 - y_0}{x_1 - x_0}$, $d = y_0 - kx_0$, for each $x_0 \leq x \leq x_1$, $y = ROUND(kx + d)$. This method by brute force is inefficient because of the multiplication and the function $ROUND()$.

   Basic Incremental Algorithm: for each $x_0 \leq x_i < x_{i+1} \leq x_1$, $y_{i+1} = y_i + k$, However, the successsive addition of a real number can lead to a **cumulative error buildup**!

   Midpoint Line Algorithm:
   - For $0 \leq k \leq 1$
   - For one approximate point $P = (x, y)$, we only have 2 choices for the next point $E = (x + 1, y)$ and $NE = (x + 1, y + 1)$, we should choose the one which is closer to $k(x + 1) + d$
   - Calculate the middle point $M = (x + 1, y + \frac{1}{2})$
   - If the **Intersection point** Q is below M, take E as next, otherwise take NE as next.
   - Note that: we consider this equation:

   $$f(x, y) = ax + by + c = (y_1 - y_0)x - (x_1 - x_0)y + (x_1 y_0 - y_1 x_0)$$

   We assume $a > 0$
   - For a point (x, y)

     if $f(x, y) = 0$, (x, y) lies on the line.

     if $f(x, y) < 0$, (x, y) lies upon the line.

     if $f(x, y) > 0$, (x, y) lies below the line.
   - So we have to test $f(M) = a(x + 1) + b(y + \frac{1}{2}) + c = f(Former) + a + \frac{b}{2}$
   - Assum $a > 0$, if $f(M) > 0$ choose NE otherwise choose E
   - Update $f(Former)$:

     If we choose E, $f(Former) = f(Former) + a$

     If we choose NE, $f(Former) = f(Former) + a + b$

     Note that:a and b are **constant integer**, so here is no **cumulative error issuse**

3. A harder problem: Triangles Rasterization

   Why Triangle:
   - Triangles (*tris*) are a simple explicit 3D surface representation.
   - Convex and concave polygons (*polys*) can be decomposed into triangles.
   - Tris are planar and unambiguously defined by three vertex(*verts*) coordinates (*coords*).

   Definition: Find and draw **pixel** samples **inside** *tri* edges and interpolate parameters defined at *verts*

4. **Rasterizxation and Hidden Surface Removal(HSR) Algorithm Classes**:
   - Image order rasterization: ray tracing/ ray casting

     traverse pixel, process each in world-space

<u>transform</u> rays from image-space to world-space

- Object order rasterization: scan-line / LEE

<u>traverse</u> triangles, process each in image-space

<u>transform</u> objects from model-space to image-space

5. **LEE Linear Expression Evaluation Algorithm**:
   - We already discussed in *Midpoint Line Algorithm* that how to determine a point is on the left(up) or right(below) the line, just *a quick review here*:

     Assume the lien have a positive *slope*

     For an Edge Equation E, for point (x, y): $E(x, y) = dY(x - X) - dX(y - Y)$

     if $E(x, y) = 0$, (x, y) lies on the line.

     if $E(x, y) < 0$, (x, y) lies right(below) the line.

     if $E(x, y) > 0$, (x, y) lies left(up) the line.

   - For **Rasterization**:

     Compute LEE result for all three edges.

     Pixels with **consistent sign** for all three edges are inside the *tri*.

     Include **edge pixels** on left or right edges.

   - LEE need to check every pixel in the bounding box.
   - LEE is very good in parallel(SIMD) system.
   - Furthermore: Given 3 random *verts* how to find CW edge cycle

     Determine L/R and Top/Bot edges for edge-pixel ownership

6. **Scan Line Rasterizer**:
   - Sort vets by Y
   - Setup edge DDAs for edges
   - Sort edges by L or R(The long edge on left or right)
   - Start from Top Vertice, and switch DDA when hit the middle vertice.

7. **Interpolate Z**:

   A general 3D plane equation has 4 terms: $Ax + By + Cz + D = 0$

   (A, B, C) is the normal of that plane, so $(X, Y, Z)_0 \times (X, Y, Z)_1 = (A, B, C)$

   Then plug any vertex coord into equation and solve for D.

   Given (A, B, C, D) and any point (x, y) can solve z

8. **Used Z-buffer to remove hidden surfaces**

   Initial Z-buffer to MAXINT at the begining of every frame

   Interpolate vertex Z values to get Z_{pix}

   Only write new pixel to the buffer if $Z_{pix} < Z_{buffer}$

   Notice that Z should always **bigger or equal to zero!**

9. Hidden Line Removal(HLR):

   Simple z-buffer does not work when the render only draws edge(outlines of polygons).

   Need edge-crossing and object sorting methods.

10. **Painter's Algorithm**: render in order front to back

    A object is in front of another object means:

    Z of all verts of one object is less than the other.

    This algorithm not work if Z-sort is ambiguous.

11. **Warnock Algorithm**:

    Subdivide screen untril a leaf region has a simple front/back relationship.

    Leaf regions have one or zero surfaces visible, and the smallest region is usually a pixel

Usually use quad tree subdivision

12. **BSP-Tree**:

View-Independent binary tree(pre-calculated) allows a view-dependent front-to-back or back-to-front traversal of surfaces.

Use Painter Algorithm to do back-to-front traversal.

Useful for **transparency** - full depth-sort of all surface.

13. **Culling**:

- Culling with portals: pre-compute the invisible part.
- Culling by View Frustum: Skip a triangle iff all its vertices are beyond **the same screen edge**!
  Pitfall: If the vertices are beyond different edge, some part of the *tri* might still in the screen. Image a giant *tri* that cover the whole screen.
- Backface Culling: For **closed(water-tight)** objects, surfaces with **oriented-normals facing away** from the camera are never visible.
  Pitfall: BF Culling only work for water-tight object!
- Frustum: Only visible triangles are drawn into the frame buffer.

12. **BSP-Tree**:

3 Class 4,5,6,7:Transformations

- Linear transformations (*Xforms*) define a mapping of coordinates (*coords*) in one coordinate frame to another.

$$V_b = X_{ba}V_a$$

- **Homogeneous Vector** (V) is 4×1 columns $(x, y, z, w)^T$
- **Homogeneous Transforms** (X) is 4×4 matrix
- From Homogeneous Vector to 3D Vector:

$$x = \frac{x}{w}, y = \frac{y}{w}, z = \frac{z}{w}$$

- **Why** we use Homogeneous Vector?

  We want to uniform the transform matrix including translation, scaling, rotation in the same form of matrix.

3.1 Transformation Matrix

1. **Translation**:

$$T(t_x, t_y, t_z) \Rightarrow \begin{bmatrix} 1 & 0 & 0 & t_x \\ 0 & 1 & 0 & t_y \\ 0 & 0 & 1 & t_z \\ 0 & 0 & 0 & 1 \end{bmatrix}, T^{-1}(t_x, t_y, t_z) = T(-t_x, -t_y, -t_z)$$

2. **Scaling**:

$$S(s_x, s_y, s_z) \Rightarrow \begin{bmatrix} s_x & 0 & 0 & 0 \\ 0 & s_y & 0 & 0 \\ 0 & 0 & s_z & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}, S^{-1}(s_x, s_y, s_z) = S(\frac{1}{s_x}, \frac{1}{s_y}, \frac{1}{s_z})$$

3. **Rotation, CCW**:

$$R_x(\theta) \Rightarrow \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & cos\theta & -sin\theta & 0 \\ 0 & sin\theta & cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}, R_x^{-1}(\theta) = R_x^T(\theta)$$

$$R_y(\theta) \Rightarrow \begin{bmatrix} cos\theta & 0 & sin\theta & 0 \\ 0 & 1 & 0 & 0 \\ -sin\theta & 0 & cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}, R_y^{-1}(\theta) = R_y^T(\theta)$$

$$R_z(\theta) \Rightarrow \begin{bmatrix} cos\theta & -sin\theta & 0 & 0 \\ sin\theta & cos\theta & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}, R_z^{-1}(\theta) = R_z^T(\theta)$$

4. Pitfall: <u>commutative</u> property is for S,R only.

   Here assume **uniform scaling** in all dimensions.

   If S is not an uniform scaling matrix. S,R don't have commutative property.

3.2 Spaces Transformation

1. **NDC to Output Device**

$$X_{sp} \Rightarrow \begin{bmatrix} \frac{xs}{2} & 0 & 0 & \frac{xs}{2} \\ 0 & -\frac{ys}{2} & 0 & \frac{ys}{2} \\ 0 & 0 & MAXINT & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

Note that:

Output Device is **RH coords** and origin in **upper left**. $X \in [0, xs), Y \in [0, ys), Z \in [0, MAXINT]$

NDC is **LH coords** and origin at screen center. $X, Y \in [-1, 1], Z \in [0, 1]$

2. **Perspective Projection**

$$X_{pi} \Rightarrow \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & \frac{1}{d} & 0 \\ 0 & 0 & \frac{1}{d} & 1 \end{bmatrix}$$

What is d And **Why** there are two $\frac{1}{d}$?

- Assume camera is on $(0, 0, -d)$, perspective(also image) plane is $z = 0$, a object in world space is (X, Y, Z)
- Defined FOV(field of view) as the angle the camera can see.
- Note: $X \in [-1, 1]$, so the distant(d) from Forcus point to view plane can be calculate by this equation:

$$\frac{1}{d} = tan(\frac{FOV}{2})$$

- Futher More: The object project to view plane can be calculate by these equations:

$$\frac{X}{Z + d} = \frac{x}{d} \Rightarrow x = \frac{X}{\frac{Z}{d} + 1}$$

$$\frac{Y}{Z + d} = \frac{y}{d} \Rightarrow y = \frac{Y}{\frac{Z}{d} + 1}$$

$$\frac{Z}{Z + d} = \frac{z}{d} \Rightarrow z = \frac{Z}{\frac{Z}{d} + 1}$$

$$(x, y, z) = (\frac{X}{\frac{Z}{d} + 1}, \frac{Y}{\frac{Z}{d} + 1}, \frac{Z}{\frac{Z}{d} + 1})$$

- Write this 3D vector to Homogeneous Vector:

$$(x, y, z, w) = (X, Y, Z, \frac{Z}{d} + 1)$$

- Futher: We forcus on the **range** of Z now is $z \in (-\infty, d)$.

  But in NDC we hope $z \in [0, 1)$ So:

  We delete all vector that $Z < 0$, because they cannot project to the view plane.

  For $z >= 0$, we define $z' = \frac{z}{d}$

- $(x, y, z', w) = (X, Y, \frac{Z}{d}, \frac{Z}{d} + 1) = X_{pi} * (X, Y, Z, 1)$

Pitfall: **Do Z interpolation in Perspective Plane!**

Why we need the farest plane?

Asymptotic curve of Z $vs.$ z, that z increase slower when Z is large.

It might map different Z to the same z

3.3 Camera Matrix

1. Assume camera position is c, camera look-at point is l, here c and l are both in world coordinate. And the world up vector is $\vec{up}$

2. Camera Z-axis **in world coordinate** is

$$\vec{Z} = \frac{\vec{cl}}{||\vec{cl}||}$$

3. Camera Y-axis **in world coordinate** is the orthogonal(vertical) part of world-up vector to Z-axis which is

$$\vec{up'} = \vec{up} - (\vec{up} \cdot \vec{Z})\vec{Z}$$

$$\vec{Y} = \frac{\vec{up'}}{||\vec{up'}||}$$

4. Camera X-axis **in world coordinate** is orthogonal to both Y and Z axises. So:

$$\vec{X} = \vec{Y} \times \vec{Z}$$

5. Build the X_{wi} from camera space to world space:

   X-axis vector $[1,0,0]$ in camera space should be $\vec{X}$ in world space, also for Y,Z-axis vectors, So:

$$X_{wi} \Rightarrow \begin{bmatrix} X_x & Y_x & Z_x & 0 \\ X_y & Y_y & Z_y & 0 \\ X_z & Y_z & Z_z & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

6. Also we need to add the translation of the camera to the Matrix:

$$X_{wi} \Rightarrow \begin{bmatrix} X_x & Y_x & Z_x & c_x \\ X_y & Y_y & Z_y & c_y \\ X_z & Y_z & Z_z & c_z \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

7. Now we can get the inverst matrix X_{iw}:

$$X_{iw} \Rightarrow \begin{bmatrix} X_x & X_y & X_z & -X \cdot c \\ Y_x & Y_y & Y_z & -Y \cdot c \\ Z_x & Z_y & Z_z & -Z \cdot c \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

8. In this proof we know that: If we know the X,Y,Z-axis in world coordinate for a specific space, we can easily build and inverst the translation from or to that space.

   This method can also be used to **proof the general rotation matrix**.

9. Orbit a Model about a Point

   The idea is the same as place camera.

   Need to care about **which space** you current in!

4   Class8-10 Illumination and Shading

1. Global vs. Local Illumination

   Global: Models indirect illumination and occlusions Local: Only models direct illumination

2. Irradiance

$$E = \int_\Omega I(x,\omega)cos\theta dx$$

   Note: $I(x,\omega)$ is the light intensity arriving from all directions and entering the hemisphere Ω over unit serface area.

   Also we only care the vertical(normal) part of the light, we dismiss all lights parallel to the surface by using $\cos\theta$

3. Simplified lighting:

   Assume all lights are distant-point light.

   - Source have **uniform** intensity distribution
   - Neglect distance fallout
   - Direction to source is constant within scene
   - Using 2 parameters to define a light:

     $direction(x,y,z)$ vector from surface to light source

     $intensity(r,g,b)$ of the light

4. specular reflection and diffuse reflection

   - Color shift by attenuation of RPG components for all reflection
   - Specular Reflection Model(View-Dependent):

$$L_j(V) = L_e \cdot K_s \cdot (V \cdot R)^{spec}$$

$$R = 2(N \cdot L)N - L$$

     Note: V and R should be normalized.

     Direction: Reflection occurs mainly in the "mirror" R direction, but there is some spread in similar directions V.

     $spec$ controls the distribution of intensity about R. Higher value of $spec$ make the surface smoother

     K_s controls the color attenuation of Surface.

   - Diffuse Reflection Models(View-Independent):

$$L_j = L_e \cdot K_d(L \cdot N)$$

     Direction: All **output** directions are the same. But we only care vertical **input** light.

     L and N should be normalized.

     K_d is the surtface attenuation component.

   - Ambient Light

$$L_j = L_a \cdot K_a$$

     Direction: All input and output directions are the same.

     Only one ambient light is needed and allowed.

   - Complete Shading Equation:

$$Color = (K_s \sum L_e \cdot (V \cdot R)^{spec}) + (K_d \sum L_e \cdot (L \cdot N)) + (L_a \cdot K_a)$$

5. Detail about HW4(Lighting Implementation)

- $\vec{L}$ denotes the direction to a infinity-far point-light source
- $\vec{E}$ denotes the camera direction. If camera is far away, $\vec{E}$ is constant(In HW4.)
- $\vec{N}$ is specified at triangle vertices.
- $\vec{R}$ must be computed for each lighting calculation (at **a point**).

  Calculation of $\vec{R}$:

$$\vec{R} = 2(\vec{N} \cdot \vec{L})\vec{N} - \vec{L}$$

  Avoiding sqrt-root in this calculation
- Choosing a Shading Space: Wee need all $\vec{L}, \vec{E}, \vec{N}, \vec{R}$ in some affine(pre-perspective) space

  Suggest use **Image Space** for HW4.

  Model space is also a reasonable choice since Normal vectors are already in that space. This is most **efficient**!
- **Image Space Lighting (ISL)**

  Create a Transformation stack from model space to image space.

  Need to **normalized the Scale and delete translation** for each matrix, **only maintain the rotation**, before push into this stack!
- **Check** the sign of $\vec{N} \cdot \vec{E}$ and $\vec{N} \cdot \vec{L}$:

  Both positive: Compute lighting model.

  Both negative: **Flip normal($\vec{N}$)** and compute lighting model.

  Different sign: Skip it.
- **Check** the sign of $\vec{R} \cdot \vec{E}$: If negative, set to 0.
- **Check** color overflow(> 1.0): Set to 1.
- **Compute Color** at all pixels:

  Per Face - flat shading

  Per Vertex - interpolate vertex colors, Gouraud Shading(specular highlights are undersampled, aliased).

  Per Pixel - interpolate normals, Phong Shading (Expensive computation, but better sampling)

  Set **Shading Modes Parameter** for different lighting calculation.
- **Pitfall** in **Phong** Interpolation:

  Need to **normalize** the interpolation normal vector.

4.1 Class10: Something More About Shading

1. Non-Uniform Scaling:

   A non-uniform scaling alters the relationship between the surface orientation and the Normal Vector.

   So we **cannot** use the same matrix M for transformation of the Normals and the vertex coordinates.

   We can fix this by using a different transformation $Q = f(M)$ for transforming the Normals.
2. How to create a matrix for Normals:

   In HW4, We create a matrix **dismiss all** scale matrix.

   For Detail:

   As the definition of Normals:

$$\vec{N}^T \cdot \vec{P} = 0$$

   After include the transform matrix:

$$(Q\vec{N})^T \cdot (M\vec{P}) = 0$$

By Definition of Matrix Multiplyer:

$$\vec{N}^T \cdot Q^T \cdot M \cdot \vec{P} = 0$$

Since we already know $\vec{N}^T \cdot \vec{P} = 0$ we only need the inner part equal to identity matrix:

$$Q^T \cdot M = I, Q = (M^{-1})^T$$

Note that: If we only used uniform scaling: $S = I$ after normalization.

If we compute Q for each M pushed on the X_{im} transform stack, the resulting X_n stack has Q and therefore allows non-uniform scaling.

3. Model Space Lighting(MSL):

Only need to transform Global lighting parameters once per models.

Also need to transform Eye/camera direction into model space.

$$\vec{N}^T \cdot Q^T \cdot M \cdot \vec{P} = 0$$

5 Class 11-13: Texture Mapping

5.1 Screen-Space Parameter Interpolation

1. In Z-buffer interpolation, we know that linear interpolation for z is **wrong in image space**, we need to interpolate in **perspective space**.

2. Accurate interpolation of RGB color or Normal vectors should also take perspective into account.
   But we can ignore the color and normal interpolation error.

3. Interpolation for **Texture Function**: checkerboard Example: Using Linear Interpolation for $u \& v$ is also wrong!

4. How to compute perspective-correct interpolation of u, v at each pixel.
   - For each parameter P, we used P^s to denote the value in perspective space.
   - Note that: For Z interpolation $V_z^s = \frac{V_z}{\frac{V_z}{d}+1} = \frac{V_z \cdot d}{V_z + d}$
   - Rescale V_z^s to $V_z^s \in [0, Z_{max}]$

   $$V_z^s = \frac{V_z \cdot d}{V_z + d} \cdot (\frac{Z_{max}}{d}) = \frac{V_z \cdot Z_{max}}{V_z + d}$$

   - We can also get the invert equation:

   $$V_z = \frac{V_z^s \cdot d}{Z_{max} - V_z^s}$$

   - For parameter from image space to perspective space:

   $$P^s = \frac{P}{\frac{V_z}{d} + 1} = \frac{Pd}{V_z + d}$$

   - Also we can get inver equation:

   $$P = \frac{P^s(V_z + d)}{d}$$

   - We don't have V_z but we already calculated V_z^s in HW2, so we can used that:

   $$P^s = \frac{P}{(\frac{V_z^s}{Z_{max}-V_z^s} + 1)}$$

   $$P = P^s \cdot \frac{V_z^s}{Z_{max} - V_z^s} + 1$$

   - Note that we only have V_z^s and Z_{max} in this equation that we already know the value, we don't need to care d and some other parameter.
   - We used $V_z' = \frac{V_z^s}{Z_{max}-V_z^s}$ to simplify the equation:

   $$P^s = \frac{P}{V_z' + 1}$$

   $$P = P^s \cdot (V_z' + 1)$$

5. The Step for Parameter interpolation:
   Get V_z^p for each vertex.
   Transform P to perspective space P^s for each vertex.
   Interpolate V_z^p for each pixel.
   Interpolate P^s for each pixel.
   Transform P^z back to P by using V_z^p for each pixel.

5.2   Texture

1. Scale u, v to Texture Image Size:

   (u, v) coords range over $[0, 1]$

   2D Image is a pixel array of $xs - 1, ys - 1$

   But $u * (xs - 1)$ might not be Integer so we need to interpolate the color for non-Integer (u, v) coordinate from nearest 4 Integer point.

   $$Color(p) = (1 - s)(1 - t)A + s(1 - t)B + stC + (1 - s)tD$$

2. For Phong Shading, using texture function $f(u, v)$ to replace k_d and k_a

3. For Gouraud Shading, using $f(u, v)$ to replace all k_s, k_d and k_a

4. Procedural Texture

5. Bump Texture: Alter normals at each pixel to create bump.

6. Noise Texture:

   - Perlin Noise:(Ref(Chinese): https://www.cnblogs.com/leoin2012/p/7218033.html
   - Input: (x, y, z) for 3D and (u, v) in 2D
   - Output: double value between 0 and 1
   - We have 2 Pseudo Random Grid for each Integer Point(x,y,z are integers):
     - Noise Matrix(d): The color of Point for noise
     - Gradient Matrix(g): A random unit vector for each Point
   - For each input vector(u, v), if (u, v) isn't Integer, we found 4-corners Integer Point: $(i, j), (i + 1, j), (i, j + 1), (i + 1, j + 1)$
   - For each Integer Point, we use **dot product** of distant vector(from (u, v) to Integer Point) and gradient vector to get the noise value.
   - In perlin noise every interpolation is in 1-D. So 2-D need first interpolate y-axis(twice) and then interpolate x-axis. 3-D need 7 interpolation. We used linear-interpolation in slides but we can use **Fade** function(easy curves) for better interpolation.
   - Turbulence: Sum noise with diminishing amplitude:

   $$turbulence(x) = \sum_{k}^{i=0} \frac{1}{2^i} |noise(2^i x)|$$

7. Evironment(Reflection) Mapping:

   - Basic Idea: During rendering, compute the reflection of Eye vector(not the light vector)
   - **Ignore the position of surface point** in scene. We assume all points are on center point of the scene.
   - Light and scenery are all merge into environment texture.
   - No object inter-reflection or shadow
   - Blur texture to simulate diffuse reflection
   - Sharp texture to simulate specular reflection

8. Cube Map:

   - Transform each Eye reflection vector R back to world space
   - Find Max component: indicated which face of cube it would intersect
   - Compute intersection of R with cube face:

     Move all Reflection ray tail to center of cube. Rescale the max component(for example$y$) of vector R to 1.0.

     The other 2 component(x, z) indicate the texture-pixel.

9. Refraction Map:

- Use Snell's law to compute refraction vector
- Color aberration simulated with $f(\lambda)$ refraction angle for multiple color bands

5.3   Implementation Of Texutre(HW5)

1. Step1: Texture coordinates: surface point $\rightarrow (u, v)$
   Input: vertex in image space
   Output: (u, v)
2. Step2: $(u, v) \rightarrow$ RGB color
   Input: (u, v) Output: RGB color from image LUT
3. Interpolation of (u, v) need to be in perspective space.
4. Interpolation of 4-corner for non-Integer (u, v) is needed.

6 Class14-15 Antialiasing

6.1 The Source of Aliasing

1. Quantization error arise from insufficient accuracy of sample
2. Aliasing error arise from insufficient samples
3. Nyquist Theorem: Sample at least twice the rate of highest frequency present in the signal.

   f(t) filtered for cutoff freq ω_F (Remove high frequencies before sampling)

   Sample Rate $\frac{1}{T_0}$ is greater than $2\omega_F$

   Reconsturct(interpolate) with $sinc$ function
4. Solution: Band-limit the input signal before sampling.

6.2 Implement Antialiasing(HW6)

1. Antialiasing by jitter supersampling
2. Sample a pixel several with different center and weight

7 Final Exam Review

1. Shading Equation:

$$Color = (K_s \sum L_e \cdot (E \cdot R)^{spec}) + (K_d \sum L_e \cdot (L \cdot N)) + (L_a \cdot K_a)$$

   Know the meaning for every terms:
   - K_s, K_a, K_d
   - L_e, L_a
   - s
   - N, L, R, E
   - Equation1: $R = 2(N \cdot L)N - L$
2. Shading Mode:(Flat, Gouraud, Phong)
3. Texture
4. Calculate the normal: With Non-translate and Non-scale Matrix To Image Space
5. Other Topic:
   - Enviroment Shading