SkyBridge Compass: Supplementary Materials

Zi'ang Li, Peng Liu
Independent Researcher, Tianjin, China
E-mail: 2403871950@qq.com
Independent Researcher, Qiqihar, China

SUPPLEMENTARY TABLES

This document provides extended data tables referenced in the main paper. All data is derived from the artifact repository CSV files.

Correspondence with Main Text:

- Table S1 (Latency): Referenced in main paper Section 7, supports Table 17 and Fig. 8
- Table S2 (RTT): Referenced in main paper Section 7, supports Table 17
- Table S3 (Message Sizes): Referenced in main paper Section 7, supports Table 17 and Fig. 9
- Table S11 (Loopback Wire Sizes): Supports Table 3 (baseline comparison)
- Tables S12–S13 (Repeatability): Supports Section 7. Tables report observed batch count B and (when $B \geq 2$) 95% confidence intervals across batches; set `SKYBRIDGE_BENCH_BATCHES=3-5` to reproduce multi-batch CIs.
- Table S4 (Traffic Padding): Supports Section 7 (traffic analysis mitigation quantization/overhead)
- Table S6 (Real-network micro-study): STUN path + 12 kB-class payload measurements across Wi-Fi / hotspot labels (generated from `Artifacts/realnet_*`). (Cross-NAT inbound-reachability depends on ISP/upstream equipment and may be infeasible without administrative control; see note below.)
- Table S7 (Dedicated EC2 direct-path validation): external Linux direct TCP run (no tunnel) with `n=50` per payload for the pinned artifact date.
- Table S8 (Kernel-level emulation cross-check): dummynet/netem comparison under shared profile IDs, supporting Section 7.7.
- Table S9 (iOS microbench metadata): per-device hardware/software/thermal metadata and run configuration for the schema v3 JSON artifacts supporting Table 9. For the frozen artifact date (`2026-01-23`), the iOS compatibility-matrix gate passes for the tested iPad/iPhone deployment set (no schema-version incompatibility observed).
- Table S10 (v1/v2 bridge comparison): liboqs PQC v1 baseline versus v2 FS latency/RTT and payload-byte delta, supporting main-paper Section 7.
- Tables S18–S20 (Platform/runtime matrix): Apple provider availability plus Android/Ubuntu version-tier suite policy mapping used by negotiation.
- Table S19 (Cross-platform contract consistency): static source-based checker output across iOS/macOS, Android, and Ubuntu for suite parity, encoding, fallback guardrails, and trust path.
- Table S24 (Boundary-stress cases and operator runbook): explicit in-model vs out-of-model classification for pairing social engineering, endpoint compromise classes, and audit-log abuse, with expected event signals and required operator actions.
- Tables S14–S25 (Protocol/Audit Appendices): wire-format validation rules, suite identifiers, PQC coverage and platform support matrices, key-size references, security event taxonomy, and an implementation-to-file mapping. These materials support auditability and reproducibility claims in main paper Sections 4, 5, and 6.

TABLE S1
Supplementary Table S1: Full Handshake Latency Statistics.

Configuration	N	mean (ms)	std (ms)	p50 (ms)	p95 (ms)	p99 (ms)
Classic	1000	2.454	0.072	2.429	2.586	2.780
liboqs PQC	1000	2.976	0.376	2.889	3.656	4.299
CryptoKit PQC	5000	5.443	0.482	5.351	6.272	6.857

TABLE S2
Supplementary Table S2: Full RTT Statistics.

Configuration	N	mean (ms)	p50 (ms)	p95 (ms)	p99 (ms)
Classic	1000	0.563	0.553	0.593	0.653
liboqs PQC	1000	0.990	0.914	1.474	1.799
CryptoKit PQC	5000	2.501	2.404	3.095	3.574

TABLE S3
Supplementary Table S3: Message Size Breakdown by Field.

Message	Total (B)	Signature (B)	KeyShare (B)	Identity (B)	Overhead (B)
MessageA.Classic	293	64	32	36	161
MessageB.Classic	318	64	32	36	186
MessageA.PQC-liboqs	6507	3309	1088	1956	154
MessageB.PQC-liboqs	5419	3309	0	1956	154
MessageA.PQC-liboqs-v2fs	6550	3309	1088	1956	197
MessageB.PQC-liboqs-v2fs	5451	3309	32	1956	154
MessageA.PQC-CryptoKit	6514	3309	1088	1956	161
MessageB.PQC-CryptoKit	5419	3309	0	1956	154
MessageA.XWing	6641	3309	1216	1956	160
MessageB.XWing	5419	3309	0	1956	154
MessageA.PQC	6507	3309	1088	1956	154
MessageB.PQC	5419	3309	0	1956	154
Finished	38	0	0	0	38

TABLE S4
Supplementary Table S4: SBP2 traffic padding quantization summary. “raw”/“padded” are aggregate bytes across events; overhead is relative to raw. Top bucket reports the most frequent bucket size (share).

Label	wraps	unwraps	raw (B)	padded (B)	overhead (%)	top bucket
rx	0	112000	736918806	1451759104	97%	256B (37%)
CP/fileTransferRequest	7991	0	2916715	4091392	40%	512B (100%)
CP/heartbeat	8069	0	451864	2065664	357%	256B (100%)
CP/systemCommand	7940	0	1675340	2032640	21%	256B (100%)
DP/32B	4792	0	325856	1226752	276%	256B (100%)
DP/300B	4768	0	1602048	2441216	52%	512B (100%)
DP/900B	4839	0	4529304	4955136	9%	1024B (100%)
DP/1400B	4764	0	6841104	9756672	43%	2048B (100%)
DP/4KiB	4837	0	19986484	39624704	98%	8192B (100%)
DP/16KiB	3956	0	64957520	129630208	100%	32768B (100%)
DP/64KiB	4044	0	265173168	530055168	100%	131072B (100%)

TABLE S5

Supplementary Table S5: SBP2 bucket-cap sensitivity study. We vary the maximum bucket size (cap) and report padding overhead, cap coverage (fraction of frames whose framed payload exceeds the cap), and a privacy proxy (bucket entropy) for representative handshake, control, and data-plane workloads.

Label	64 KiB cap				128 KiB cap				256 KiB cap			
	all (%)	padded (%)	>cap (%)	entropy (b)	all (%)	padded (%)	>cap (%)	entropy (b)	all (%)	padded (%)	>cap (%)	entropy (b)
HS/MessageA	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*
HS/MessageB	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*
HS/Finished	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*	*n/a*
CP/heartbeat	357%	357%	0%	0.00	357%	357%	0%	0.00	357%	357%	0%	0.00
CP/systemCommand	21%	21%	0%	0.00	21%	21%	0%	0.00	21%	21%	0%	0.00
CP/fileTransferRequest	40%	40%	0%	0.00	40%	40%	0%	0.00	40%	40%	0%	0.00
DP/32B	276%	276%	0%	0.00	276%	276%	0%	0.00	276%	276%	0%	0.00
DP/300B	52%	52%	0%	0.00	52%	52%	0%	0.00	52%	52%	0%	0.00
DP/900B	9%	9%	0%	0.00	9%	9%	0%	0.00	9%	9%	0%	0.00
DP/1400B	43%	43%	0%	0.00	43%	43%	0%	0.00	43%	43%	0%	0.00
DP/4KiB	98%	98%	0%	0.00	98%	98%	0%	0.00	98%	98%	0%	0.00
DP/16KiB	100%	100%	0%	0.00	100%	100%	0%	0.00	100%	100%	0%	0.00
DP/rdpMix	1%	7%	79%	2.57	15%	32%	36%	1.78	36%	36%	0%	1.47
DP/fileMix	<0.1%	*n/a*	100%	2.58	12%	56%	64%	2.22	49%	49%	0%	0.95

Notes: all is overhead across all wrapped frames (including passthrough); *padded* is overhead restricted to frames that entered bucket padding. *n/a* denotes "not applicable" (handshake messages are padded by SBP1 rather than SBP2) or "no padded frames observed" for that cap/label. – denotes "not observed" in the sampled protocol trace. The >cap rate is computed as the fraction of frames where (payload bytes + SBP2 header) exceeds the configured cap; this can drive *all* toward near-zero while preserving non-zero >cap.

Note: Cross-NAT direct inbound tests (no overlay/relay) are not universally feasible. In particular, double-NAT topologies (ISP router/modem upstream) and IPv6 inbound filtering can prevent any inbound reachability even when devices have global IPv6 addresses. In such environments, all client samples time out with empty connect-time fields, and we omit those rows from the main table to avoid conflating "connectivity unavailable" with protocol performance.

Wire Size Summary:

- Classic: $293 + 318 + 2 \times 38 = 687$ B
- PQC: $6507 + 5419 + 2 \times 38 = 12{,}002$ B
- X-Wing (`2026-01-23` snapshot): $6641 + 5419 + 2 \times 38 = 12{,}136$ B
- Real-network micro-study payload labels use the payload-only sizes above; the transport harness adds a fixed 4-byte length prefix that is excluded from these labels.

Table S11: Loopback Wire-Size Baselines

Values are cert-dependent (localhost certificate). Noise-XX wire size is pattern-dependent and reflects the XX pattern used in this baseline. SkyBridge loopback wire sizes include framing and transport overhead; payload-only sizes are reported in Table S3.

Table S12: Repeatability Across Batches (Latency)

Table S13: Repeatability Across Batches (RTT)

Interpretation note: CryptoKit PQC RTT exhibits higher *between-batch* variance than Classic/liboqs in our environment (Apple Silicon, macOS 26.x), so its across-batch 95% CI can be substantially wider. Per-batch iteration counts are configuration-dependent in this artifact snapshot (Classic/liboqs N=1000, CryptoKit N=5000). This reflects run-to-run scheduler/load sensitivity rather than an arithmetic error; raw batch values are directly recorded in `Artifacts/handshake_rtt_2026-01-23.csv`.

Data Sources

All data is generated from the artifact CSV files:

- `Artifacts/handshake_bench_2026-01-23.csv` (Tables S1, S12)
- `Artifacts/handshake_rtt_2026-01-23.csv` (Tables S2, S13)
- `Artifacts/message_sizes_2026-01-23.csv` (Table S3)
- `Artifacts/traffic_padding_2026-01-23.csv` (Table S4)
- `Artifacts/traffic_padding_sensitivity_2026-01-23.csv` (Table S5)
- `Artifacts/network_emulation_kernel_2026-01-23.csv` (Table S8)
- `Artifacts/ios_microbench_2026-01-23.csv` (Table 9, Table S9)
- `Artifacts/realnet_microstudy_2026-01-23.csv` (Table S6)
- `Artifacts/baseline_summary_*.csv` (Table S11)

Regenerate the benchmark CSVs with `Scripts/run_paper_eval.sh` from the artifact repository. Then build all paper/supplementary tables with `Scripts/make_tables.py`, which uses the main-paper pinned artifact date (or explicit `ARTIFACT_DATE`) to avoid mixing datasets across runs. System-level impact artifacts (`system_impact_...`) are produced by a dedicated suite, but follow the same artifact-date suffix convention used in the main paper.

Evidence Layering for This Revision

Main-paper claims and all primary figures/tables are anchored to the `2026-01-23` dataset family listed above. Any expanded checks introduced during revision are reported as **additional validation** in Supplementary sections and are used to strengthen robustness discussion; they do not replace or redefine the main-paper primary statistics.

Artifact release:

- URL: https://github.com/billlza/Skybridge-Compass

TABLE S6

Supplementary Table S6: Real-network micro-study (STUN path + TCP payload). Each row is one network condition label. STUN metrics capture path RTT/loss and a conservative NAT classification. E2E metrics report success rate and p50 completion time for two payload sizes (classic 687 B vs PQC 12,002 B), along with the delta (PQC minus classic). A fixed 4-byte transport length prefix is excluded from the payload-byte labels. Failure taxonomy is summarized for the PQC size as timeout rate and other failure rate. Labels with zero successful E2E samples on both payload sizes are omitted because timing percentiles are undefined.

Label	IFace	Exp	Con	NAT	STUN loss	STUN RTT p50/p95 (ms)	ok_c	$p50_c$ (ms)	ok_p	$p50_p$ (ms)	Δp50 (ms)	PQC fail (to/other)
ec2_ssh_tunnel	wifi	0	0	unknown	0.1200	62.301/64.751	1.0000	204.607	1.0000	287.435	82.828	0.0000/0.0000
hotspot_ssh_tunnel	wifi	1	1	unknown	0.3200	223.066/426.633	1.0000	240.546	1.0000	280.219	39.673	0.0000/0.0000
wifi_direct	wifi	0	0	unknown	0.1800	166.881/169.392	1.0000	139.747	1.0000	165.242	25.495	0.0000/0.0000

TABLE S7

Dedicated EC2 direct-path validation (external Linux, no tunnel, `ARTIFACT_DATE=2026-01-23`). Endpoint: `54.92.79.99:44444`; harness: `Scripts/run_real_network_e2e_linux.py`; `n=50` per payload.

Payload (B)	Success rate	p50 total (ms)	p95 total (ms)	p99 total (ms)
687	1.0000	130.601	139.426	140.970
12,002	1.0000	132.925	140.858	148.236

- Git ref: `817e11aa5806`
- Commit: `817e11aa5806`
- Source archive: `817e11aa5806.zip` SHA256=`05d6961a26ec0f5b57b8821cfc8337dec1ba37ec8deb5f9dd5e7b1c7bdcb2378`
- Source archive: `817e11aa5806.tar.gz` SHA256=`5b9130d64e5217376da98e20286f078fd8693d998796d64d4e503e981f2dea2b`

SUPPLEMENTARY METHODS AND DETAILS

Wire Format and Validation Rules

Key Share Semantics: The `keyShares[].shareBytes` field has suite-dependent interpretation:

- **DH suites (X25519):** `shareBytes` = ephemeral public key (32 bytes)
- **KEM suites (ML-KEM-768):** `shareBytes` = encapsulated key / ciphertext (`enc`, 1088 bytes)

This distinction matters: for DH, the Responder uses the Initiator's public key to compute a shared secret; for KEM, the Initiator encapsulates to the Responder's long-term KEM public key (obtained during pairing), and `shareBytes` carries the resulting `enc`. The Responder decapsulates using their private key.

Forward Secrecy Note: This is a static KEM exchange to a long-term KEM public key, and thus does *not* provide traditional PFS semantics. If the long-term KEM private key is compromised later, a passive attacker who recorded ciphertexts may be able to recover past session keys.

Nonce Freshness: Each party contributes a 32-byte nonce (`clientNonce` in A, `serverNonce` in B). Both are bound into the KDF info parameter, ensuring symmetric freshness and enabling a unique session identifier:

```
handshakeId = SHA256(replayTag ||
initiatorNonce || responderNonce ||
suiteWireIdLE)
```

To prevent short-window replay attacks, implementations SHOULD cache recent `handshakeId` values (or the `(initiatorNonce, responderNonce)` pair) and reject duplicates within a configurable window (default: 5 minutes).

Key Share Binding:

- The `keyShares[]` array contains at most two entries to bound message size. Under the two-attempt strategy, each `MessageA` is homogeneous (PQC/hybrid-only or classic-only), so the two entries (if present) belong to the same suite group for that attempt.
- Each entry is a `(suiteId, shareBytes)` tuple.
- The Responder MUST select a suite for which the Initiator provided a key share; otherwise reject with `missingKeyShare`.
- This binds negotiation to actual cryptographic material, preventing the "TLS key_share mismatch" class of bugs.

Explicit Key Confirmation (Finished Frames):

- The Responder sends a short `Finished_R2I` frame authenticated under the newly derived session keys. The Initiator verifies it and replies with `Finished_I2R`.
- A session is established only after both Finished frames are verified, reducing responder-side half-open state under failures.
- Finished frames are fixed-size authenticated messages (38 bytes each: 4-byte magic, 1-byte version, 1-byte direction, 32-byte HMAC), adding negligible wire overhead compared to PQC payloads.
- Finished MACs are computed over the handshake transcript using per-direction keys: `finishedMAC = HMAC-SHA256(finishedKey, transcriptHash)`

```
finishedKey_R2I = HKDF(sessionKey,
  info="SkyBridge-FINISHED|R2I|")
finishedKey_I2R = HKDF(sessionKey,
  info="SkyBridge-FINISHED|I2R|")
```

Anti-Downgrade Invariant:

- The Initiator MUST verify that `selectedSuite` is a member of `supportedSuites[]` it originally sent.
- It MUST also confirm that `keyShares[]` contains an entry for `selectedSuite`.
- Since `sigB` commits to `MessageA` via `transcriptA`, it binds the initiator's proposal.
- Any tampering with the initiator's offered suites or key shares will cause `sigB` verification to fail.

Canonical Encoding Rules (V1 Wire Format):

- `supportedSuites[]`: preference order, signed as-is (first = most preferred)
- `keyShares[]`: entries follow the suite preference order; only suites with provided shares appear
- All lists use 2-byte little-endian length prefix
- All integers use little-endian encoding
- Canonical encoding is byte-for-byte specified. Implementations MUST NOT reserialize with language-native encoders (e.g., JSON, PropertyList), as this may introduce non-determinism

TABLE S8

Supplementary Table S8: Kernel-level network emulation cross-check (shared profiles from `Scripts/netem_profiles.json`). Common profiles (mild/moderate/severe) are reported for both dummynet and netem when available; reorder is netem-only and marked *n/a* for dummynet by design. On some macOS setups, dummynet with localhost endpoint can under-shape absolute delay, so cross-tool interpretation emphasizes completion robustness over millisecond parity unless a non-localhost endpoint is used. Data from `Artifacts/network_emulation_kernel_2026-01-23.csv`.

Profile	Suite	dummynet comp.	dummynet p95	dummynet p99	netem comp.	netem p95	netem p99
mild	Classic	1.0000	273.8	289.7	1.0000	253.4	1221.8
mild	liboqs PQC	1.0000	316.0	366.1	1.0000	240.5	1214.6
mild	CryptoKit PQC	1.0000	347.8	470.6	1.0000	249.0	1229.8
moderate	Classic	1.0000	277.6	293.8	1.0000	1431.0	1513.9
moderate	liboqs PQC	1.0000	314.5	408.4	1.0000	1371.4	1573.1
moderate	CryptoKit PQC	1.0000	300.9	310.6	1.0000	1332.6	1475.5
severe	Classic	1.0000	277.4	305.6	1.0000	1889.0	3284.1
severe	liboqs PQC	1.0000	312.2	326.2	1.0000	1933.5	2126.9
severe	CryptoKit PQC	1.0000	308.6	315.0	1.0000	1897.2	3908.0
reorder	Classic	*n/a*	*n/a*	*n/a*	1.0000	233.8	253.3
reorder	liboqs PQC	*n/a*	*n/a*	*n/a*	1.0000	232.8	242.0
reorder	CryptoKit PQC	*n/a*	*n/a*	*n/a*	1.0000	241.3	253.3

TABLE S9

Supplementary Table S9: iOS micro-benchmark device metadata (`Artifacts/ios_microbench_2026-01-23.csv`).

Device label	Model	System	Build	Chip/machine	Thermal	Config
ipad16_3	iPad	26.3	Version 26.3 (Build 23D127)	iPad16,3	nominal	warmup=10, N=1000, B=3
iphone17_1	iPhone	26.2.1	Version 26.2.1 (Build 23C71)	iPhone17,1	fair	warmup=10, N=1000, B=3

TABLE S10

Supplementary Table S10: liboqs PQC v1/v2 bridge comparison (N=1000, warmup=10). v1 uses `ML-KEM-768`; v2 uses `ML-KEM-768-FS` with additional ephemeral contribution composition. Observed v2-v1 deltas: mean latency +0.76 ms, p95 latency +0.79 ms, payload bytes +75 B.

Configuration	mean latency (ms)	p95 latency (ms)	p50 RTT (ms)	p95 RTT (ms)	payload handshake (B)
liboqs v1	2.98	3.66	0.91	1.47	12,002
liboqs v2 FS	3.73	4.44	1.24	1.87	12,077

TABLE S11

Loopback wire-size baselines from pcap capture (N=1000). Wire bytes count full packet lengths observed on the loopback interface; TLS/QUIC/DTLS values are cert-dependent.

Protocol	Wire p50 (B)	Wire p95 (B)
TLS 1.3	8,824	8,948
QUIC	7,830	14,427
WebRTC DTLS	3,090	3,162
Noise XX	2,560	2,672
SkyBridge (classic)	4,874	5,028
SkyBridge (liboqs)	37,779	44,609
SkyBridge (CryptoKit)	19,009	19,257

Endianness rationale: V1 wire format uses little-endian to align with platform conventions (ARM64 native order). The V2 TLV format uses network byte order (big-endian) for TLV length fields to align with TLV conventions in IETF protocols. The two formats serve different purposes: V1 is the on-wire message encoding and is used as transcript input in v1 deployments (byte-for-byte deterministic). V2 TLV is an optional transcript-hashing format for forward compatibility and is exercised by regression tests; it is not used on the wire in v1.

Note: The 32-byte `clientNonce`/`serverNonce` in message fields are distinct from the 12-byte `aeadNonce` used internally by AES-GCM for authenticated encryption.

Suite Identifiers and Wire Format

A **suite** defines the handshake tuple `(KEM, SIG, AEAD, KDF)` used for the KEM-DEM envelope and transcript binding. Data-plane AEAD is negotiated separately and is fixed to AES-256-GCM in v1. Algorithm suite identifiers use a structured 16-bit wire format enabling forward compatibility:

Note: X-Wing is a hybrid KEM combining X25519 + ML-KEM-768; it does not include a signature algorithm. The suite identifier specifies the full primitive set, with ML-DSA-65 as the preferred signature algorithm when available. In v1, protocol signatures are bound to the suite group: ML-DSA-65 for PQC/hybrid suites and Ed25519 for classic suites. Secure Enclave P-256 ECDSA is used only for optional device proof-of-possession and is not used for the main protocol signatures (`sigA`/`sigB`).

**Post-rekey guarantee:* in Bootstrap-Assisted mode, business traffic remains blocked until PQC rekey succeeds. Runtime assurance labels reported by the implementation are `pqc_strict`, `bootstrap_assisted`, `legacy_classic`, and `unknown`.

Unknown suite identifiers are parsed as `unknown(wireId)` rather than causing parse failures. This allows older clients to gracefully reject unsupported suites during negotiation.

Transport/MTU considerations: handshake messages are length-prefixed and carried on reliable control channels (TCP or QUIC streams). Fragmentation and reassembly are handled by transport, not by the handshake format. QUIC datagrams are reserved for latency-critical media frames; for other payload types, senders must respect the maximum datagram size and chunk accordingly.

KEM-DEM Envelope

The sealed box structure encapsulates KEM-based authenticated encryption output with explicit DoS protection. Our construc-

TABLE S12
Supplementary Table S12: Repeatability across independent benchmark batches (latency). Table reports observed batch count B. Cells report mean and (when $B \geq 2$) $\pm$ 95% CI across batches; configuration-specific N after 10 warmup runs (Classic=1000, liboqs PQC=1000, CryptoKit PQC=5000).

Configuration	B	N/batch	mean (ms)	p50 (ms)	p95 (ms)
Classic	3	1000	2.452 ± 0.010	2.430 ± 0.012	2.589 ± 0.029
liboqs PQC	3	1000	2.997 ± 0.122	2.909 ± 0.112	3.687 ± 0.225
CryptoKit PQC	3	5000	5.880 ± 4.243	5.777 ± 4.226	6.784 ± 4.339

TABLE S13
Supplementary Table S13: Repeatability across independent benchmark batches (RTT). Table reports observed batch count B. Cells report mean and (when $B \geq 2$) $\pm$ 95% CI across batches; configuration-specific N after 10 warmup runs (Classic=1000, liboqs PQC=1000, CryptoKit PQC=5000).

Configuration	B	N/batch	mean (ms)	p50 (ms)	p95 (ms)
Classic	3	1000	0.562 ± 0.007	0.554 ± 0.005	0.596 ± 0.019
liboqs PQC	3	1000	0.994 ± 0.045	0.917 ± 0.034	1.494 ± 0.086
CryptoKit PQC	3	5000	2.243 ± 1.111	2.150 ± 1.104	2.841 ± 1.141

TABLE S14
Message field validation rules.

Field	Validation	Failure Action
version	Must equal protocol version (1)	Reject with versionMismatch
supportedSuites	Must contain at least one suite supported by local implementation; unknown IDs are ignored for negotiation but still transcript-bound	Reject with suiteNegotiationFailed
keyShares	Unique suiteId per entry, max 2 entries, each shareBytes must match its suiteId's expected length	Reject with invalidMessageFormat
selectedSuite	Must be in supportedSuites AND have matching keyShare	Reject with missingKeyShare
clientNonce/serverNonce	Must be 32 bytes	Reject with invalidMessageFormat
sigA/sigB	Must verify against respective identityPubKey	Reject with signatureVerificationFailed

TABLE S15
Encoding scope (V1 vs V2).

Component	Encoding	Length endianness	Used in v1 deployment
`MessageA`/`MessageB` wire bytes	V1 deterministic	little-endian	yes
Transcript hash input (v1)	V1 deterministic	little-endian	yes
Transcript hash input (v2)	V2 TLV canonical	big-endian	no (experimental)

TABLE S16
Suite identifier ranges and components.

Range	Category	Suite Components	Examples
0x00xx	Hybrid PQC (preferred)	X-Wing KEM, ML-DSA-65, AES-256-GCM, HKDF-SHA256	0x0001
0x01xx	Pure PQC	ML-KEM-768, ML-DSA-65, AES-256-GCM, HKDF-SHA256	0x0101
0x10xx	Classic	X25519 DHKEM, Ed25519, AES-256-GCM, HKDF-SHA256	0x1001
0xF0xx	Experimental	Reserved for testing	-

TABLE S17
Post-quantum coverage by policy and established suite (v1). "PQC confidentiality" refers to resistance against store-now-decrypt-later adversaries *while long-term KEM private keys remain uncompromised*; v1 does not claim PFS for KEM-based PQC suites.

Policy	Outcome	KEM / key establishment	Protocol signature (`sigA`/`sigB`)	PQ conf.	PQ auth.	PFS
default	PQC established	ML-KEM-768 (static recipient key)	ML-DSA-65	yes	yes	no
default	classic fallback	X25519 ephemeral DH	Ed25519	no	no	yes
strictPQC (Compliance)	PQC established	ML-KEM-768 (static recipient key)	ML-DSA-65	yes	yes	no
strictPQC (Compliance)	PQC unavailable	– (handshake fails)	–	–	–	–
strictPQC (Bootstrap-Asst.)	Control-only classic bootstrap for paired KEM-key recovery; mandatory PQC rekey	X25519 pre-rekey; ML-KEM-768 post-rekey	Ed25519 pre-rekey; ML-DSA-65 post-rekey	yes*	yes*	no

tion follows the KEM-DEM (Key Encapsulation Mechanism + Data Encapsulation Mechanism) paradigm: KEM.Encapsulate() → HKDF-SHA256 → AES-256-GCM. We call this an "HPKE-inspired KEM-DEM envelope" to distinguish it from RFC 9180 HPKE, which includes additional features such as multiple modes (Base, PSK, Auth, AuthPSK), context exporters, and a more complex key schedule.

We model v1 as a constrained HPKE Base-mode instance: the KEM encapsulation yields a shared secret, HKDF-Extract/Expand derives an AEAD key/nonce with domain-separated info (role, suite ID, transcript hash), and AEAD provides confidentiality and ciphertext integrity under unique nonces. This makes the security dependencies explicit and isolates deviations from RFC 9180 to the simplified header/nonce/tag framing.

On Apple 26+ platforms, CryptoKit provides native HPKE with quantum-secure cipher suites including X-Wing (ML-KEM-768 + X25519). When available, implementations SHOULD use CryptoKit's HPKE API directly rather than this compatibility envelope.

Security Goals:

- **PQC suites:** ML-KEM provides IND-CCA2 KEM security (per FIPS 203).
- **Classic suites:** X25519 ephemeral-DH encapsulation (DHKEM-style); security relies on the X25519/Gap-DH assumption and HKDF key separation.
- **Payload encryption:** INT-CTXT and IND-CPA via AES-256-GCM in v1 (compat KEM-DEM), and RFC 9180 HPKE AEAD in v2 (e.g., ChaCha20-Poly1305 in our classic provider).
- **Key separation:** HKDF with context-specific info parameters including role binding.

Not Covered (delegated to RFC 9180 HPKE on Apple 26+):

- Sender authentication modes (Auth, AuthPSK)
- Incremental AEAD for streaming

Used in our handshake (classic v2):

- HPKE exporter for deriving the per-session shared secret with explicit context binding

Format Versions:

The implementation supports two sealed box formats:

v1 (Compatibility KEM-DEM): Used when native HPKE is unavailable. Explicit nonce and tag fields.

Header (17 bytes):

magic	version	suite	flags
4B	1B	2B	2B
encLen	nonceLen	tagLen	ctLen
2B	1B	1B	4B

Body (v1):

encapsulatedKey	nonce	ciphertext	tag
encLen	12B	ctLen	16B

v2 (Native HPKE): Used with CryptoKit HPKE. Nonce and tag are embedded in the AEAD output.

Header (17 bytes):

magic	version	suite	flags
4B	1B	2B	2B
encLen	nonceLen	tagLen	ctLen
2B	0	0	4B

Body (v2):

encapsulatedKey	ciphertext (AEAD output)
encLen	ctLen (includes auth tag)

Version Detection: Parsers distinguish v1 from v2 by checking `nonceLen` and `tagLen`:

- v1: `nonceLen = 12`, `tagLen = 16`
- v2: `nonceLen = 0`, `tagLen = 0` (AEAD details encapsulated by library)

Length limits enforce DoS protection:

- `encLen <= 4096` bytes (sufficient for ML-KEM-768's 1088-byte ciphertext)
- v1: `nonceLen = 12` bytes, `tagLen = 16` bytes (AES-GCM fixed)
- v2: `nonceLen = 0`, `tagLen = 0` (embedded in ciphertext)
- `ctLen <= 64KB` (handshake phase, pre-authentication window)
- `ctLen <= 256KB` (post-authentication)

Parsing uses overflow-safe arithmetic and validates each field before allocation.

Platform Support Matrix

[1] ML-KEM-1024 and ML-DSA-87 are available in CryptoKit on Apple 26+ but not currently used by our implementation. [2] X-Wing (wireId 0x0001) is negotiated only when runtime/provider support is available on both peers; otherwise tiered fallback selects ML-KEM-768 or classic according to policy.

Compatibility markers `0x0102` (ML-KEM-768-FS) and `0x1002` (P-256 marker) are parsed in the current Android/Ubuntu snapshot for forward compatibility and catalog parity, but remain non-negotiable by default until full end-to-end contract support is enabled.

Native PQC Integration

The `ApplePQCCryptoProvider` wraps CryptoKit ML-KEM and ML-DSA APIs, enabling platform-backed PQC suites and HPKE-based encapsulation. This construction (KEM → HKDF → AEAD) is inspired by HPKE but does not implement the full RFC 9180 specification. On Apple 26+ platforms, CryptoKit exposes HPKE cipher suites including X-Wing (ML-KEM-768 with X25519), enabling a standards-aligned replacement for our compatibility envelope. This layer can then be replaced with direct CryptoKit PQ-HPKE calls.

Conditional Compilation Strategy

The `HAS_APPLE_PQC_SDK` flag gates **all** PQC type references. Importantly, `@available` only controls *runtime* availability; it does not prevent *compile-time* failures when the SDK lacks the PQC symbols.

For reproducible builds across toolchains, we intentionally **do not** enable `HAS_APPLE_PQC_SDK` by default in SwiftPM (because `.when(platforms: [.macOS])` does not reflect SDK availability and will break older Xcode builds). Instead, projects inject the flag from build settings **only** when compiling with the Apple 26 SDK (Xcode 26+): `OTHER_SWIFT_FLAGS = $(inherited) -DHAS_APPLE_PQC_SDK`

This keeps the codebase buildable on older Xcode versions (classic provider path), while enabling native CryptoKit PQC providers only when the correct SDK is present.

TABLE S18
Platform/runtime support matrix (Apple + cross-platform runtime policy).

Platform	PQC Provider	Algorithms	Notes
macOS 26+	ApplePQCProvider	ML-KEM-768, ML-KEM-1024[1], ML-DSA-65, ML-DSA-87[1]	Native CryptoKit
macOS 14–15	OQSPQCProvider	ML-KEM-768, ML-DSA-65	liboqs fallback
macOS 14–15	ClassicProvider	X25519, Ed25519	If liboqs unavailable
iOS 26+	ApplePQCProvider	ML-KEM-768, ML-KEM-1024[1], ML-DSA-65, ML-DSA-87[1]	Native CryptoKit
iOS 17–18	ClassicProvider	X25519, Ed25519	liboqs not bundled
Android 17+	Runtime tier policy	X-Wing[2] → ML-KEM-768 (liboqs) → X25519	Prefer hybrid if available; fallback is evented + cooldown-limited
Android 14–16	Runtime tier policy	ML-KEM-768 (liboqs) → X25519	PQC first, then classic fallback under policy gate
Android 13 and below	Runtime tier policy	X25519, Ed25519	Classic-only baseline
Ubuntu 24–25	Runtime tier policy	X-Wing[2] → ML-KEM-768 (liboqs) → X25519	Prefer hybrid if available; per-peer fallback cooldown enforced
Ubuntu 22–23	Runtime tier policy	ML-KEM-768 (liboqs) → X25519	PQC first, then classic fallback under policy gate
Ubuntu 20–21	Runtime tier policy	X25519, Ed25519	Classic-only baseline

TABLE S19
Cross-platform contract-consistency snapshot (`ARTIFACT_DATE=2026-01-23`). Generated by `Scripts/check_cross_platform_interop.py`.

Check	Result	Notes
Suite catalog parity (IDs 0x0001, 0x0101, 0x0102, 0x1001, 0x1002)	PASS	iOS/macOS, Android, Ubuntu aligned
Wire endianness (UInt16 little-endian fields)	PASS	Encoding/decoding contract aligned
Signature-selection contract (PQC → ML-DSA-65, classic → Ed25519)	PASS	Cross-platform rule alignment
Timeout-triggered fallback blocked	PASS	Timeout not in default fallback gate
Per-peer fallback cooldown guard	PASS	Explicit cooldown paths present
Trust-pinning path	PASS	Pinned identity-fingerprint path present

Security Event Emission

All cryptographic decisions emit structured events. The `SecurityEventEmitter` actor implements backpressure with per-subscriber queues and meta-event rate limiting to prevent recursive overflow.

Secure Enclave Integration

For hardware-backed signing, the `SigningCallback` protocol enables Secure Enclave integration. The `HandshakeDriver` prioritizes callback-based signing over raw key material, ensuring private keys never leave the Secure Enclave.

Availability and fallback. Secure Enclave–backed ML-DSA/ML-KEM keys are only available on macOS 26+ via CryptoKit. On macOS 14–15, PQC operations fall back to liboqs (software), and Secure Enclave is used only for P-256 ECDSA proof-of-possession keys. When Secure Enclave PQC is enabled, the implementation relies on CryptoKit key types `SecureEnclave.MLDSA*` and `SecureEnclave.MLKEM*`, both gated by macOS 26+ SDK and runtime availability checks.

Signing Key Hierarchy

The system supports two complementary signing mechanisms:

1) **CryptoProvider signing (Protocol Signature):** Uses the active suite's signature algorithm (Ed25519 for classic, ML-DSA-65 for PQC) for protocol-level identity verification. Keys are managed by the CryptoProvider and stored in software. This is the primary signature used in `sigA`/`sigB` fields of handshake messages.
2) **Secure Enclave signing (Device PoP):** Uses EC P-256 with ECDSA via `SecureEnclaveSigningCallback` to prove the peer controls a key stored in Secure Enclave. Private keys never leave the Secure Enclave hardware. Note: This provides proof-of-possession of a hardware-backed key, not full device attestation (Apple does not expose a general-purpose attestation API with certificate chains at the application layer). The security value derives from the key being pinned during initial pairing.

Implementation Note. `DeviceIdentityKeyManager` creates P-256 keys in Secure Enclave (when available) for hardware-backed device identity. These keys are used for the optional `seSigA`/`seSigB` proof-of-possession signatures, NOT for the primary protocol signatures (`sigA`/`sigB`). The primary protocol signatures use Ed25519 (classic) or ML-DSA-65 (PQC) keys generated by the CryptoProvider.

The `FallbackSigningCallback` provides automatic fallback from Secure Enclave to CryptoProvider when hardware signing is unavailable (e.g., on devices without Secure Enclave or when the key has not been provisioned).

Use Case Separation:

- CryptoProvider (Ed25519/ML-DSA): Primary protocol signatures, cross-platform interoperability, suite-negotiated
- Secure Enclave (P-256 ECDSA): Optional hardware-backed proof-of-possession, proving control of a non-exportable key

Both mechanisms can coexist in a single handshake: CryptoProvider for primary protocol signatures (`sigA`/`sigB`), Secure Enclave for optional hardware-backed proof-of-possession (`seSigA`/`seSigB`).

Signature Verification Rules:

- Primary signatures (`sigA`/`sigB`) are mandatory and must verify against the peer's `identityPubKey`.
- For paired peers, `identityPubKey` must match the pinned value from initial pairing.

TABLE S20
Cross-platform runtime suite-policy matrix used in this revision.

Platform range	Preferred suite order	Fallback policy note
Android 17+	X-Wing (if supported) → ML-KEM-768 (liboqs) → X25519	Classic fallback requires whitelist reason + per-peer cooldown
Android 14–16	ML-KEM-768 (liboqs) → X25519	PQC-first, classic as controlled fallback
Android 13 and below	X25519 only	Classic-only baseline
Ubuntu 24–25	X-Wing (if supported) → ML-KEM-768 (liboqs) → X25519	Classic fallback requires whitelist reason + per-peer cooldown
Ubuntu 22–23	ML-KEM-768 (liboqs) → X25519	PQC-first, classic as controlled fallback
Ubuntu 20–21	X25519 only	Classic-only baseline

- Optional SE signatures (`seSigA`/`seSigB`) elevate trust when present and valid.
- Verification order: primary signature, identity pinning, optional SE signature.

Pre-Negotiation Signature Selection and Two-Attempt Strategy

A fundamental challenge in our protocol is the "chicken-and-egg" problem: `sigA` must be generated *before* suite negotiation completes, yet the signature algorithm should be consistent with the negotiated suite. We resolve this through pre-negotiation signature selection and a two-attempt strategy.

Pre-Negotiation Signature Selection: The signature algorithm for `sigA` is determined by the `offeredSuites` in MessageA, not by the final `selectedSuite`. The `PreNegotiationSignatureSelector` builds offered suites based on the attempt strategy and selects the appropriate signature algorithm (ML-DSA-65 for PQC suites, Ed25519 for classic).

Homogeneity Invariant: Each attempt's `offeredSuites` must be homogeneous with respect to `sigAAlgorithm`: ML-DSA-65 requires all PQC suites; Ed25519 requires all classic suites. This invariant is enforced at compile-time through the type system and at runtime through `HandshakeDriver` initialization validation.

Two-Attempt Strategy: To support interoperability between PQC-capable and classic-only devices, we employ a two-attempt strategy: (1) PQC attempt with ML-DSA-65 signatures, then (2) classic fallback with Ed25519 if the PQC attempt fails due to provider unavailability or *local pre-send* suite-negotiation failure. In particular, for a classic-only peer without a pinned PQC KEM public key from pairing, the PQC attempt fails locally during `MessageA` construction (no key shares → `suiteNegotiationFailed`), so fallback is immediate and is not driven by network timeout.

Strict Policy Modes:

- **Compliance Mode:** strict fail-closed semantics; no classic establishment.
- **Bootstrap-Assisted Mode:** for paired peers with missing or stale KEM identity keys, allow one temporary classic control channel (`pairingIdentityExchange` only), then require successful PQC rekey before business traffic.

Fallback Security (default policy classic fallback): Not all failures trigger default-mode classic fallback.

Allowed:

- `pqcProviderUnavailable`
- `suiteNotSupported`
- `suiteNegotiationFailed` (local pre-send branch only)

Blocked:

TABLE S21
ML-DSA-65 Key Sizes (FIPS 204 Compliance).

Component	Expected	Measured	Status
Public Key	1952 B	1952 B	OK
Secret Key	4032 B	4032 B	OK
Signature	3309 B	3309 B	OK

- `timeout`
- `suiteNegotiationFailed` after remote input / after-send
- `signatureVerificationFailed`
- `identityMismatch`
- `replayDetected`

Timeout-based fallback is explicitly blocked to prevent attackers from forcing downgrade through packet dropping. Per-peer fallback is rate-limited (default 5-minute cooldown) to prevent rapid downgrade cycling.

Strict Bootstrap-Assisted triggers:

- `suiteNegotiationFailed` with paired trust and missing KEM identity key.
- `timeout` with paired trust and existing KEM key record (stale-key recovery).

During this strict recovery path, non-control business messages are blocked until PQC rekey succeeds; recovery completion/failure is emitted as `handshake_fallback` security events.

ML-DSA Key Sizes

Key Size Reference

[1] Apple CryptoKit uses a seed-based compact format for private key serialization (`integrityCheckedRepresentation`). This is more storage-efficient than the FIPS 203/204 expanded format. Public keys use `rawRepresentation` which matches FIPS standard sizes. Measurements performed on macOS 26.0 (Tahoe) SDK.

[2] Not measured directly; projected from the seed-based pattern observed in ML-KEM-768/ML-DSA-65 (ratio of FIPS expanded size to Apple compact size). These algorithms are available in CryptoKit but not exercised by our current benchmark suite.

Security Event Types

Boundary Stress Cases and Operator Runbook

Rows marked out-of-model are not covered by theorem-level security claims in main-paper Section 5; they are included to make deployment response obligations explicit.

TABLE S22
Key size reference.

Algorithm	Public Key	Private Key (Apple)[1]	Private Key (FIPS)	Ciphertext/Signature
ML-KEM-768	1184 B	96 B	2400 B	1088 B
ML-KEM-1024	1568 B	128 B[2]	3168 B	1568 B
ML-DSA-65	1952 B	64 B	4032 B	3309 B
ML-DSA-87	2592 B	96 B[2]	4896 B	4627 B
X25519	32 B	32 B	-	32 B
Ed25519	32 B	32 B	-	64 B

TABLE S23
Security event types.

Event Type	Severity	Trigger
`cryptoProviderSelected`	info/warning	Provider factory selection
`cryptoDowngrade`	warning	PQC to classic fallback
`handshakeFailed`	warning	Any handshake failure
`signatureVerificationFailed`	high	Invalid peer protoSignature
`secureEnclaveVerificationFailed`	warning	Invalid secureEnclaveSignature
`identityMismatch`	high	identityPubKey does not match pinned key
`contextZeroized`	info	Sensitive material cleared
`suiteNegotiationFailed`	warning	No common suite found
`unexpectedStateTransition`	high	Actor reentrancy detected

TABLE S24
Boundary-stress cases: model scope, expected audit signals, and operator actions.

Boundary-stress case	Model status	Expected signal surface	Required operator action	Claim impact
Pairing social engineering (user pins attacker key)	Out-of-model (pairing assumption failure)	No cryptographic alert at pairing time; later key-change conflicts may appear as `identityMismatch`	Revoke trust record, require authenticated re-pairing (QR/PIN or equivalent), quarantine previously trusted channel	Authentication claims do not apply until re-pair completes
Endpoint compromise (read-only key/material exposure)	Partially out-of-model (endpoint integrity degraded)	Potential abnormal `cryptoDowngrade`/ `handshakeFailed` bursts; possible forensics-only detection	Enter strict mode where feasible, rotate affected long-term keys, investigate endpoint posture before restoring trust	Secrecy claims degrade to compromise window assumptions
Endpoint compromise (signing-capable attacker)	Out-of-model for protocol-level peer trust	Handshake-level signatures may still verify; compromise usually inferred from external telemetry	Immediate endpoint quarantine, key revocation/rotation, forced re-pairing for all peers	Mutual-authentication guarantees no longer hold for compromised endpoint
Audit-log injection/truncation attempt on local store	In-model for integrity checking of emitted records; out-of-model for fully privileged host tamper	Hash-chain discontinuity or missing mandatory fields for downgrade events	Treat chain break as incident, preserve evidence snapshot, fail closed for automated compliance checks	Audit replayability claims hold only while logging substrate integrity assumptions hold

X-Wing Wire Size (Measured)

X-Wing is a hybrid KEM combining X25519 + ML-KEM-768. In our v1 handshake, the initiator carries only a KEM ciphertext in MessageA; thus X-Wing increases the MessageA keyshare from 1088 B (ML-KEM-768) to 1216 B in the `2026-01-23` snapshot, while MessageB remains keyshare-free. We measure X-Wing directly via the native CryptoKit provider (wireId 0x0001) and report per-field sizes in Supplementary Table S3 (`MessageA.XWing`/`MessageB.XWing`), using the X-Wing snapshot dated `2026-01-23`. The field breakdown is:

- MessageA.XWing: 3309 (signature) + 1216 (keyshare) + 1956 (identity) + 160 (overhead) = 6641 B
- MessageB.XWing: 3309 (signature) + 0 (keyshare) + 1956 (identity) + 154 (overhead) = 5419 B
- Finished: 38 B

Total handshake size is **12,136 B**. Relative to the payload-only baseline (12,002 B), the +134 B delta reflects +128 B X-Wing keyshare expansion and +6 B framing overhead in this snapshot.

Reproducibility

Test Commands.

- One-shot evaluation: `Scripts/run_paper_eval.sh`
- Individual suite run: `swift test` with `-filter TestName`
- Representative suite names:
  - `HandshakeBenchmarkTests`
  - `HandshakeFaultInjectionBenchTests`
  - `PolicyDowngradeBenchTests`
  - `MessageSizeSnapshotTests`
- CSV outputs are date-stamped under `Artifacts/`. To pin one dataset, set `ARTIFACT_DATE=2026-01-23` or `SKYBRIDGE_ARTIFACT_DATE=2026-01-23`.

System-impact artifact hygiene (snapshot 2026-01-23). For `Artifacts/system_impact_2026-01-23.csv`, we performed one integrity cleanup pass and removed one duplicated embedded header row before table generation. Final file summary:

- 13,801 total lines (1 header + 13,800 data rows)
- Per-suite row counts consistent with benchmark design: `ideal`=1000, `rtt100_j50`=1000, `rtt50_j20`=2600
- No fully duplicated data rows remain

Repeatability (Multi-batch). Repeatability tables report observed batch count B and (when $B \geq 2$) mean $\pm$ 95% confidence intervals across independent batches. To reproduce multi-batch CIs, rerun with process restarts: `ARTIFACT_DATE=2026-01-23 SKYBRIDGE_BENCH_BATCHES=3-5 bash Scripts/run_paper_eval.sh`.

Real-network micro-study (External validity). We use two lightweight scripts:

- `Scripts/run_real_network_probe.swift`: STUN RTT + conservative NAT classification
- `Scripts/run_real_network_e2e.swift`: TCP connect + first-byte + completion timing for payload-only handshake baselines (classic 687 B, PQC 12,002 B; transport uses a fixed 4-byte length prefix)

Pin filenames with `ARTIFACT_DATE=2026-01-23`, run across labels (same Wi-Fi / cross-NAT / hotspot), then aggregate with `python3 Scripts/aggregate_realnet.py`.

iOS on-device microbench import. Run the iOS app path `Settings → PQC → Self-test/Bench` (warmup=10, N=1000, B=3). Export:

- `ios_microbench_<date>_ipad16_3.json`
- `ios_microbench_<date>_iphone17_1.json`

Use `<date>=2026-01-23` for the frozen artifact snapshot. Place files under `Artifacts/`, then run `python3 Scripts/aggregate_ios_microbench.py`.

Kernel-level emulation cross-check. Run `Scripts/run_network_emulation_kernel.sh` (requires sudo/network-admin capability), then aggregate with `python3 Scripts/aggregate_kernel_emulation.py`. Shared profile IDs come from `Scripts/netem_profiles.json`; reorder is netem-only and dummynet entries are marked *n/a*.

Note on inbound reachability. Some home networks do not provide an inbound-reachable IPv4 address (e.g., double NAT behind an ISP router, CGNAT, DS-Lite, or WAN IPv4 shown as `0.0.0.0`). In these cases, IPv4 port-forwarding experiments will fail (client samples report `timeout` with empty `connect_ms`). For a true cross-NAT condition without modifying upstream equipment, prefer IPv6 direct connectivity (when available) with an explicit IPv6 firewall allow-rule for TCP `44444`. If only an overlay/relay path is feasible, label the condition accordingly (e.g., `cross_nat_via_relay`) and interpret results as overlay-mediated connectivity rather than raw Internet inbound reachability.

Regression Testing

Transcript integrity uses V1 (deterministic) and V2 (TLV canonical) encoding formats, validated with 14 test cases (100% pass rate). TLV encoding uses 1-byte tags, 4-byte big-endian length fields, and variable-length values. The complete regression matrix validates Requirements 12.1–12.6; all 15 regression tests pass, and all 3 compile-fail harness tests correctly produce compile errors.

Key Properties: (1) P-256 cannot be used as a protocol signature algorithm (compile-time enforced); (2) PQC attempts use only PQC suites, classic attempts use only classic suites; (3) Default-mode classic fallback is limited to whitelisted local capability errors, while strict Bootstrap-Assisted recovery is limited to paired KEM-key refresh triggers; (4) Legacy P-256 requires authenticated channel or existing TrustRecord; (5) All fallback and legacy acceptance events include full audit context.

Artifact Map

Table S25 maps implementation components to source files in the artifact repository (https://github.com/billlza/Skybridge-Compass, ref=`817e11aa5806`, commit=`817e11aa5806`).

TABLE S25
Implementation artifact map.

Component	File (Lines)
Provider Protocol	`Sources/SkyBridgeCore/P2P/CryptoProviderProtocol.swift` (L24–113)
Handshake Types	`Sources/SkyBridgeCore/P2P/HandshakeTypes.swift` (L297–320)
Provider Factory	`Sources/SkyBridgeCore/P2P/CryptoProviderFactory.swift` (L18–179)
Handshake Driver	`Sources/SkyBridgeCore/P2P/HandshakeDriver.swift` (L258–338, L1042–1145)
Handshake Context	`Sources/SkyBridgeCore/P2P/HandshakeContext.swift` (L27–100, L862–933)
Secure Bytes	`Sources/SkyBridgeCore/P2P/SecureBytes.swift` (L25–99)
Message Signatures	`Sources/SkyBridgeCore/P2P/HandshakeMessages.swift` (L557–569, L801–821)
Apple PQC Provider	`Sources/SkyBridgeCore/P2P/Providers/ApplePQCProvider.swift` (L27–152)
Security Events	`Sources/SkyBridgeCore/Security/SecurityEventEmitter.swift` (L22–136)
SE Signing	`Sources/SkyBridgeCore/P2P/SecureEnclaveSigningCallback.swift` (L40–94)
Signature Selector	`Sources/SkyBridgeCore/P2P/PreNegotiationSignatureSelector.swift` (L69–96)
Route-Aware Discovery	`Sources/SkyBridgeCore/P2P/P2PDiscoveryService.swift` (L278–457)
Connection State Guarding	`Sources/SkyBridgeCore/DeviceDiscovery/UnifiedOnlineDeviceManager.swift` (L940–989)
Active Transfer Route Selection	`Sources/SkyBridgeCore/FileTransfer/FileTransferManager.swift` (L104–213)