

Network and Web Security

Browser storage


Dr Sergio Maffeis

Department of Computing

Course web page: <https://331.websec.fun>

HTTP state management

- HTTP is a stateless protocol
 - Each request-response exchange is independent of the previous one
 - Compare with TCP: after initial handshake, data-ack packets are tied by increasing session numbers
- Web applications need to keep their own state
 - Server-side: can save files, access databases
 - Client-side: in 1994 Netscape introduced Cookies
 - Key-value pairs stored by the browser on behalf of a web application
- Cookies are used for
 - Storing website preferences
 - Storing session tokens
 - Tracking users
- Current specification is IETF RFC 6265, from 2011
 - Some basic guarantees on browser implementations
 - “At least 4096 bytes per cookie”
 - “At least 50 cookies per domain”
 - “At least 3000 cookies total”



Cookies in HTTP

- First client request carries no cookies

```
Remote Address: 216.58.211.163:443
Request URL: https://www.google.co.uk/
Request Method: GET
```

- The server sets each cookie using a response header
 - Set-Cookie: name = value; [(attribute [= value];)*]
 - Optional attributes tell browser how to handle that cookie

```
set-cookie: PREF=ID=52bad12bb5ef8029:FF=0:TM=1425900847:LM=1425900847:S=dImeFFdj
reBPRx0o; expires=Wed, 08-Mar-2017 11:34:07 GMT; path=/; domain=.google.co.uk
set-cookie: NID=67=qYQJrMMAbvyKM5s8GkkD2EW9aKAYUrdI03AebEQI3y01B8qSNxfnfRJK9QTAR
H20cEbFgZ_dMDmQF_mxG4uKGmBGP7sEsfVEHxSrE1jFosFIsgic2BLK9AWg6MkerKBo; expires=Tu
e, 08-Sep-2015 11:34:07 GMT; path=/; domain=.google.co.uk; HttpOnly
status: 200
```

- Browser includes relevant cookies for subsequent requests in one request header
 - Cookie: (name = value;)+ ...


```
cookie: PREF=ID=52bad12bb5ef8029:FF=0:TM=1425900847:LM=1425900847:S=dImeFFdjreBP
Rx0o; NID=67=qYQJrMMAbvyKM5s8GkkD2EW9aKAYUrdI03AebEQI3y01B8qSNxfnfRJK9QTARH20cE
bFgZ_dMDmQF_mxG4uKGmBGP7sEsfVEHxSrE1jFosFIsgic2BLK9AWg6MkerKBo
```

Cookie attributes

- **Domain** = *domain*
 - Send cookie back when *domain* is suffix of requested domain
 - Cookie for `example.com` is sent to `login.example.com`
 - Must be a non-trivial suffix of host domain: cannot set for “.com, .co.uk, .googlecode.com”
 - The [Public Suffix List](#) is used to keep track of valid suffixes
 - Defaults to host of URL that caused the response
- **Path** = *path*
 - Send cookie back when *path* is prefix of request path
 - Cookie for `example.com/login` is not sent to `example.com/`
 - Defaults to path of URL that caused the response
- **Expires** = *date* (similar for Max-Age)
 - Date in the future: store *persistent* cookie on file until *date*
 - Date in the past: delete the cookie immediately
 - Null (default): keep *session-only* cookie in memory until browser is closed
- **Secure**
 - Send the cookie only over HTTPS
 - Provides confidentiality against network attacker
- **HttpOnly**
 - Prevent non-HTTP APIs (for example JavaScript) from accessing cookie
 - Mitigates risk of cookie theft via XSS
- **SameSite**
 - Experimental feature, already supported by Chrome, Firefox and Opera
 - Mitigates cross-origin information leakage (for example CSRF and tracking, as we shall see later in the course)
 - **Strict**: cookie is sent only from a page with same domain
 - **Lax**: don't block for top-level cross-domain navigation with safe HTTP methods (GET, OPTIONS, HEAD, TRACE)
 - **None**: as of February 2020 Chrome assumes **Lax** by default, unless one specifies **None**, and uses also attribute **Secure**

Cookies in the browser

- Cookies are also accessible to JavaScript in the browser
 - `document.cookie` provides access to all the cookies **in scope** for the document origin
- Examples
 - Write: `document.cookie = "userid=123; path=/; secure";`
 - Delete: `document.cookie = "userid=; path=/; expires=Thu, 01 Jan 1970 00:00:01 GMT";`
 - Read: `alert(document.cookie);` (this will not show `httponly` cookies)



Cookie scope

- Cookie origin: domain, path
- Cookie is identified by name and origin
- Cookie scope is determined by origin and secure attribute
- Browser request sends all cookies that are in scope to server
 - All the server sees is the name=value pairs
 - Attributes are not sent back
- Example
 - We added 2 “NID” cookies (42,43) for different Google origins using JavaScript

Cookie store for https://www.google.co.uk/maps

| Name ▲ | Value | Domain | Path | Expires / ... | Size | HTTP | Secure |
|--------|--------------|-------------------|-------|---------------|------|------|--------|
| NID | 43 | .www.google.co.uk | /maps | 2015-09... | 5 | | |
| NID | 67=m9e7s... | .google.co.uk | / | 2015-09... | 134 | ✓ | |
| NID | 42 | .www.google.co.uk | / | 2015-09... | 5 | | ✓ |
| OGPC | 4061130-17: | .google.co.uk | / | 2015-04... | 15 | | |
| PREF | ID=4c1471... | .google.co.uk | / | 2017-03... | 94 | | |

Request header for https://www.google.co.uk/maps

cookie: NID=43; PREF=ID=4c1471102240a913:U=8a7add608648797c:FF=0:TM=1425832665:LM=1425832823:S=tL9sk5NbFUSpdqGo; NID=67=m9e7s8GTbMN0eX4sSKYZRBHV2ld-N6lURDfqUQnSg7LxWP-M81IG_qEEu8flvA46az0vUfh_wAZ1Y8m8JIbPSPuHc70EehZ7SXDxE88PtIemEK8T2YI60-AvgRjWkHsm; OGPC=4061130-16:; NID=42

Security considerations

- Server does not see cookie attributes
 - `example.com` cannot tell if cookie was set by `subdomain.example.com`
 - Cannot tell if cookie is effectively `httponly` or was written by JavaScript
- Path does not restrict visibility of cookies
 - Path in cookie origin is only meant to improve efficiency
 - Send to server only the cookies that are needed for a specific request
 - Scripts from different path can
 - Load iframe with page from target path
 - Access `document.cookie` of iframe thanks to SOP (which ignores path)
- Cookie integrity is not guaranteed
 - User can access cookies SQLite database in browser
 - Any JavaScript from the same origin can set/edit cookies
 - Even **secure** does not guarantee cookie integrity
 - Secure cookies can be set by JavaScript (risk of XSS, injection)
 - Active network attacker can intercept HTTPS response and set cookie with spoofed HTTP response: next request sends tampered “secure” cookie

HTML5 browser storage

- HTML5 also provides Web Storage and Indexed Database APIs.
 - We look at Web Storage (easier to use, larger adoption)
 - Implements client-side state using lists of key-value pairs
- `window.localStorage`
 - Associated to page origin
 - Data is kept until it is deleted explicitly
- `window.sessionStorage`
 - Associated to current tab **and** page origin
 - Data is kept until the tab is closed
- JavaScript API (where `xxx` = `localStorage` or `sessionStorage`)
 - `xxx.length` //return list length
 - `xxx.key(n)` //read n-th key in list
 - `xxx.getItem(k)` or `xxx.k` //read value of k
 - `xxx.setItem(k,v)` //set value v for key k
 - `xxx.removeItem(k)` //remove entry with key k
 - `xxx.clear()` //delete all entries
- HTML5 storage is not sent/set over HTTP
 - Up to the page if/how to involve the server (AJAX, GET/POST, etc.)
 - Attacker model is script injection, XSS

Attack: Resident XSS

Target page:

```
<html><body>
Welcome user:
<script>
    document.write(localStorage.getItem("user_name"));
</script>
</body></html>
```

Attack vector:

```
localStorage.setItem("user_name", "<script>alert('XSS!')</script>");
```

- Resident XSS (RXSS) is a variant of DOM-based XSS that exploits browser storage
 - Cookie, Web storage, Indexed DB, etc.
- Attacker must already be able to inject JavaScript to exploit the RXSS
 - **RXSS remains effective also after vulnerable page is patched**
 - Unlike DOM-based and Reflected XSS
 - RXSS cannot be detected by server, IDS, XSS Auditor
 - Unlike Reflected, Stored XSS
- Countermeasure: do not trust values stored in the browser (*defense-in-depth*)
 - Sanitise stored values like other user input
 - Periodically validate, refresh or delete stored data