

Blockchain Privacy Ring Signatures




Ring Signatures - Rivest, Shamir, Tauman



Signature solutions:

- Digital signatures | ➡ verifies against a specific public key
- Group signatures
- Ring signatures | ➡ verify against a set of public keys
- Linkable Ring signatures

“Set” Signatures

- Group signatures  well defined group
- Ring signatures  ad-hoc groups (great for cryptocurrencies)
- *Linkable* Ring signatures  reveal if a signer **already** produced a signature
- **Anonymity**
An adversary cannot identify which ring signature corresponds to which of the public keys in the ring.
- **Unforgeability**
An adversary cannot produce a valid signature, if it does not know a secret key corresponding to a public key included in the ring.
- **Exculpability**
An adversary cannot produce a valid signature that links to the signature of another member of the ring, whose key the adversary does not control.
- **Linkability**
Any two signatures produced by the same signer within the same ring are publicly linkable (i.e., anyone can detect that they were produced by the same signer).

“Set” Signatures

- Group signatures → well defined group
- Ring signatures → ad-hoc groups (great for cryptocurrencies)
- *Linkable* Ring signatures → reveal if a signer **already** produced a signature

- **Anonymity**

An adversary cannot identify which ring signature corresponds to which of the public keys in the ring.



- **Unforgeability**

An adversary cannot produce a valid signature, if it does not know a secret key corresponding to a public key included in the ring.

- **Exculpability**

An adversary cannot produce a valid signature that links to the signature of another member of the ring, whose key the adversary does not control.

- **Linkability**

Any two signatures produced by the same signer within the same ring are publicly linkable (i.e., anyone can detect that they were produced by the same signer).

Ring Signatures - Rivest, Shamir, Tauman

- Verify against **a set** of public keys. Computationally infeasible to determine which of the group members signed.
- Groups can be formed on an ad-hoc basis (vs. group signatures)
- $O(n)$ for the resulting signature size
n == number of public keys
- Does not hide transaction amounts!

Ring Signatures - Rivest, Shamir, Tauman

- Verify against **a set** of public keys. Computationally infeasible to determine which of the group members signed.
- Groups can be formed on an ad-hoc basis (vs. group signatures)
- $O(n)$ for the resulting signature size
n == number of public keys
- Does not hide transaction amounts!



<https://www.getmonero.org/resources/research-lab/pubs/MRL-0005.pdf>