

# Computer Languages

# Language

Means of communication

Arbitrary

Must be agreement between parties

Codified as grammar

# Atom

Smallest particle or atom is a word

Subatomic particles exist: syllables, phonemes, and graphemes

We will restrict ourselves to words

# Words

Word associates a concept

In natural language, we have types of words:

Nouns

Verbs

Adverbs

Adjectives

Pronouns

Prepositions

Conjunctions

Interjections

# Types of Words

Nouns:

Name a person, place, thing, or idea (e.g., dog, city, happiness).

Pronouns:

Take the place of a noun to avoid repeating it (e.g., he, she, they, it).

Verbs:

Show an action or a state of being (e.g., run, is, eat).

Adjectives:

Describe or modify a noun or a pronoun (e.g., big, happy, red).

Adverbs:

Describe or modify a verb, an adjective, or another adverb, often telling how, when, or where (e.g., quickly, very, yesterday).

Prepositions:

Show the relationship of time, place, or position between words (e.g., in, on, under, before).

Conjunctions:

Connect words, phrases, or clauses together (e.g., and, but, because).

Interjections:

Express strong emotion or sudden feeling (e.g., wow, ouch, hey).

# Combining Words

An ordered set of words creates a statement

With a set of words  $S$ , almost infinite (factorial) number of combinations.

Some combinations have meaning

Most don't

# Combining Statements

An ordered set of statements creates a conversation or program

Extremely large set of possible conversations (programs).

Some conversations (programs) have meaning or usefulness

Most don't

# Language Hierarchy

Program

Statement[s]

Word[s]

# Syntax versus Semantics

Correct syntax follows the language rules

Correct semantics is the correct meaning

Correctness requires syntax and semantics

# Context

The situation, setting, or environment

The surrounding that helps explain a word or statement

# Context Free

The situation, setting, or environment does not alter the meaning of a word or statement

My **name** is Bill.

What is your **name**?

# Context Sensitive

The situation, setting, or environment alters the meaning

Lance Armstrong wanted the Tour de France  
**record** wins

Please press the **record** button

Meaning changes based the word environment

# Keywords

Reserved word

Only has one use

Context free

Only has one meaning

Examples: if procedure module else while

# Symbols

Abstraction

Creates an association

May change or mutate an association (mutable)

Function of time

Known as a variable

Example :  $\alpha \leftarrow 1$        $\alpha$  is the symbol or  
variable

# Reducing Complexity

Using keywords and allowing only one possible context (context free) makes the language simpler and easier to understand


Most programming languages are almost context free

C, C++, and Rust are almost context free

# Formal Language Specification

We can use another language to describe our language of interest


One such description is BNF



# Metalanguages

---


- A *metalanguage* is a language used to talk about a language (usually a different one)
- We can use English as its own metalanguage (e.g. describing English grammar in English)
- It is essential to distinguish between the metalanguage terms and the object language terms



# BNF

---


- BNF stands for either Backus-Naur Form or Backus Normal Form
- BNF is a metalanguage used to describe the grammar of a programming language
- BNF is formal and precise
  - BNF is a notation for **context-free grammars**
- BNF is essential in compiler construction
- There are many dialects of BNF in use, but...
- ...the differences are almost always minor



# BNF

---


- $\langle \rangle$  indicate a *nonterminal* that needs to be further expanded, e.g.  $\langle variable \rangle$
- Symbols not enclosed in  $\langle \rangle$  are *terminals or keywords*; they represent themselves, e.g. *if*, *while*, *(*
- The symbol  $::=$  means *is defined as*
- The symbol  $|$  means *or*; it separates alternatives, e.g.  $\langle addop \rangle ::= + \mid -$
- This is *all there is* to “plain” BNF; but we will discuss *extended* BNF (**EBNF**) later in this lecture



# BNF uses recursion

---


- $\langle integer \rangle ::= \langle digit \rangle \mid \langle integer \rangle \langle digit \rangle$   
*or*  
 $\langle integer \rangle ::= \langle digit \rangle \mid \langle digit \rangle \langle integer \rangle$
- Recursion is all that is needed (at least, in a formal sense)



# Recursion

---


- Recursion is the process where a concept, function, or process depends on or calls a simpler version of itself to solve a problem
- A recursive solution or definition requires two main parts to work properly without running forever
  - **Base case:** The simplest scenario or stopping condition that ends the recursion and returns a direct answer
  - **Recursive case:** The step where the process breaks the problem down and calls or applies itself to a smaller piece of the original problem.



# Recursion

---

- $\langle integer \rangle ::= \langle digit \rangle$ 
  - Base case



# BNF uses recursion


---

- $\langle integer \rangle ::= \langle integer \rangle \langle digit \rangle$

*or*

$\langle integer \rangle ::= \langle digit \rangle \langle integer \rangle$


- Recursion case



# BNF uses recursion

---


- $\langle integer \rangle ::= \langle digit \rangle \mid \langle integer \rangle \langle digit \rangle$   
*or*  
 $\langle integer \rangle ::= \langle digit \rangle \mid \langle digit \rangle \langle integer \rangle$
- Recursion is all that is needed (at least, in a formal sense)
- "Extended BNF" allows repetition as well as recursion
- Repetition is usually better when using BNF to construct a compiler



# BNF Examples I

---


- $\langle \textit{digit} \rangle ::=$   
 $0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$
- $\langle \textit{if statement} \rangle ::=$   
 $\textit{if} ( \langle \textit{condition} \rangle ) \langle \textit{statement} \rangle$   
 $\mid \textit{if} ( \langle \textit{condition} \rangle ) \langle \textit{statement} \rangle$   
 $\textit{else} \langle \textit{statement} \rangle$



# BNF Examples II

---


- $\langle \text{unsigned integer} \rangle ::=$   
 $\langle \text{digit} \rangle \mid \langle \text{unsigned integer} \rangle \langle \text{digit} \rangle$
- $\langle \text{integer} \rangle ::=$   
 $\langle \text{unsigned integer} \rangle$   
 $\mid + \langle \text{unsigned integer} \rangle$   
 $\mid - \langle \text{unsigned integer} \rangle$



# BNF Examples III

---


- $\langle identifier \rangle ::=$ 
  - $\langle letter \rangle$
  - |  $\langle identifier \rangle \langle letter \rangle$
  - |  $\langle identifier \rangle \langle digit \rangle$
- $\langle block \rangle ::= \{ \langle statement list \rangle \}$
- $\langle statement list \rangle ::=$ 
  - $\langle statement \rangle$
  - |  $\langle statement list \rangle \langle statement \rangle$



# BNF Examples IV

---


- *<statement> ::=*
  - <block>*
  - | *<assignment statement>*
  - | *<break statement>*
  - | *<continue statement>*
  - | *<do statement>*
  - | *<for loop>*
  - | *<goto statement>*
  - | *<if statement>*
  - | ...



# Extended BNF

---


- The following are pretty standard:
  - `//` enclose an optional part of the rule
    - Example:  
$$\langle \text{if statement} \rangle ::=$$
$$\text{if} ( \langle \text{condition} \rangle ) \langle \text{statement} \rangle \text{ } [ \text{else } \langle \text{statement} \rangle ]$$
  - `{ }` mean the enclosed can be repeated any number of times (including zero)
    - Example:  
$$\langle \text{parameter list} \rangle ::= ( )$$
$$| ( \text{ } [ \langle \text{parameter} \rangle , \text{ } [ \langle \text{parameter} \rangle ] \text{ } )$$



# Variations

---

- The preceding notation is the original and most common notation
  - BNF was designed before we had boldface, color, more than one font, etc.
  - A typical modern variation might:
    - Use boldface to indicate multi-character terminals
    - Quote single-character terminals (because boldface isn't so obvious in this case)
- Example:
  - *if\_statement* ::=  
    **if** "(" *condition* ")" *statement* [ **else** *statement* ]



# Limitations of BNF

---

- No easy way to impose length limitations, such as maximum length of variable names
- No easy way to describe ranges, such as 1 to 31
- No way *at all* to impose distributed requirements, such as, a variable must be declared before it is used
- Describes *only syntax, not semantics*
- Nothing clearly better has been devised

# Classifying Computer Languages

Hardware (binary) level: assembly languages

High Level (text) level: human written languages  
translated to binary code

# Translation to Binary

Compiled language: all statements at once  
C, C++, Rust

Interpreted language: a statement at a time  
Python, Bash, Tcl

# Types of Computer Languages

- **Procedural Programming**
- **Object-Oriented Programming (OOP)**
- **Functional Programming**
- **Scripting Languages**
- **Logic Programming**

# Types of Computer Languages

## **Procedural Programming:**

- Follows a strict, top-down sequence of statements or commands to achieve an output.
- Organized around modules known as functions or procedures.
- Examples: C, Pascal, and BASIC.

# Types of Computer Languages

## **Object-Oriented Programming (OOP):**

- Treats software programs as a collection of interacting "objects".
- Combines data fields (attributes) and behavior (methods) into singular structures.
- Examples: Java, Python, and C++

# Types of Computer Languages

## **Functional Programming:**

- Focuses on evaluating mathematical functions rather than executing a sequential list of steps.
- Prioritizes state immutability to ensure predictable program behavior.
- Examples: Haskell, Scala, and F#

# Types of Computer Languages

## **Scripting Languages:**

- Designed to automate specific tasks or manage dynamic actions within existing applications.
- Examples: Bash, Perl, and Tcl.

# Types of Computer Languages

## **Logic Programming:**

- Rather than giving step-by-step commands, the programmer inputs a framework of facts and rules.
- The computer's logic system figures out how to find a valid solution.
- Example: Prolog

# Imperative vs Declarative

## Imperative

- Explicit control of statement sequence
- Explicit control of states
- Explicit control of flow
  
- Burden on Programmer
- Can be efficient

# Declarative

## Declarative

- Focus on result rather than how to achieve it
- Implicit control of states
- Implicit control of statement flow
  
- Burden on the compiler
- Less efficient in general

# Imperative Example

## Python:

```
numbers = [1, 2, 3, 4, 5]
even_numbers = []
for num in numbers:
    if num % 2 == 0:
        even_numbers.append(num)
```

# Declarative Example

## **Python:**

```
numbers = [1, 2, 3, 4, 5]
```

```
even_numbers = [num for num in numbers if  
num % 2 == 0]
```

# Declarative Example

**SQL:**

```
SELECT * FROM users WHERE  
age > 21;
```

# Class study

**C, C++, Rust:**

Focus on imperative  
programming