

Loops and Iteration

Where We Left Off

Arrays hold many values of one type

Operators compute with each value

Functions name a group of statements

Missing: a way to **repeat** statements

Doing Something 100 Times

```
sum = sum + psi[0] ;  
sum = sum + psi[1] ;  
sum = sum + psi[2] ;  
...  
sum = sum + psi[99] ;
```

100 lines that differ in **one number**
And if the array grows to 10,000?

What a Loop Is

A **loop** repeats a block of statements

It keeps going while a **condition** is true


Each pass through the block is one **iteration**

The same few lines run 100 or 10,000 times

Every Loop Has Four Parts

1. **Initialize** set up before the first pass
2. **Test** should we run the body again?
3. **Body** the work, done once per iteration
4. **Update** move toward the end

How a Loop Flows



The while Loop: C and C++

```
while ( condition ) {  
    body  
}
```

Test the condition

If true, run the body and test again

If false, continue after the closing brace

The while Loop: Rust

```
while condition {  
    body  
}
```

No parentheses needed

Braces are **required**

The condition must be a **bool**

Example: Count Down

C, C++:

```
int n = 10 ;  
while ( n > 0 ) {  
    printf ( "%d\n", n ) ;  
    n = n - 1 ;  
}
```

Point to the four parts

Example: Count Down in Rust

```
let mut n = 10 ;  
while n > 0 {  
    println! ( "{}", n ) ;  
    n -= 1 ;  
}
```

n must be **mut** because the update changes it

Example: Wait for the Sensor

```
while ( !sensor_ready ( ) ) {  
    // do nothing - just ask again  
}  
counts = read_adc ( ) ;
```

This is **polling**: asking again and again until the answer changes

The Test Comes First

```
int n = 0 ;  
while ( n > 0 ) {  
    ...                never runs  
}
```

If the condition is false at the start,
the body runs **zero** times

do ... while: C and C++

```
do {  
    body  
} while ( condition ) ;
```

The body runs **first**, then the test

The body always runs **at least once**

Note the semicolon at the end

Example: Read Until Valid

```
do {  
    counts = read_adc ( ) ;  
} while ( counts == 0 || counts >= 4095 ) ;
```

You must read at least once before
you can check the value

0 and 4095 mean the sensor is open or shorted

Rust Has No `do ... while`

Use **loop** with a **break**:

```
let mut counts ;  
loop {  
    counts = read_adc ( ) ;  
    if counts > 0 && counts < 4095 { break ; }  
}
```

The test moves to the **end** of the body

The for Loop: C and C++

```
for ( init ; test ; update ) {  
    body  
}
```

All the loop control on **one line**

```
for ( int i = 0 ; i < 4 ; i++ ) {  
    ...  
}
```


Tracing a for Loop

```
int a[4] = { 5, 3, 8, 2 } ;  
int sum = 0 ;  
  
for ( int i = 0 ; i < 4 ; i++ ) {  
    sum += a[i] ;  
}
```

i	i < 4	sum
0	true	5
1	true	8
2	true	16
3	true	18
4	false	done

The body runs 4 times; the test runs 5 times.

for is while in Disguise

```
for ( int i = 0 ; i < 4 ; i++ ) {  
    sum += a[i] ;  
}
```

is the same as

```
int i = 0 ;  
while ( i < 4 ) {  
    sum += a[i] ;  
    i++ ;  
}
```

Example: Sum an Array in C

```
float psi[100] ;  
float sum = 0.0f ;  
  
for ( int i = 0 ; i < 100 ; i++ ) {  
    sum += psi[i] ;  
}  
  
float average = sum / 100.0f ;
```

Off by One

```
for ( int i = 0 ; i <= 100 ; i++ )  
    sum += psi[i] ;           reads psi[100]
```

An array of 100 has indices **0 to 99**

Use **$i < N$** , not **$i \leq N$**

C and C++: reads garbage. Rust: panics.

The Loop Variable's Scope

```
for ( int i = 0 ; i < 4 ; i++ ) { ... }
```

```
printf ( "%d", i ) ;
```

error

A variable declared in the `for` exists
only inside the loop

Declare it before the loop if you need it after

The Unsigned Countdown Trap

```
for ( size_t i = n - 1 ; i >= 0 ; i-- )
```

size_t is **unsigned** - it is never below 0

After 0 comes 18,446,744,073,709,551,615

i >= 0 is always true: the loop **never ends**

Rust Has No C-Style for

In Rust, **for** walks through a collection of values, one at a time

```
for i in 0..4 {  
    sum += a[i] ;  
}
```

No init, no test, no update to get wrong

Ranges

<code>0..5</code>	<code>0 1 2 3 4</code>	end excluded
<code>0..=5</code>	<code>0 1 2 3 4 5</code>	end included
<code>(0..5).rev ()</code>	<code>4 3 2 1 0</code>	reversed
<code>(0..10).step_by (2)</code>	<code>0 2 4 6 8</code>	every other

A range is a value that produces numbers
in order

Example: Sum an Array in Rust

```
let psi : [f32 ; 100] = [0.0 ; 100] ;  
let mut sum = 0.0 ;
```

```
for i in 0..psi.len ( ) {  
    sum += psi[i] ;  
}
```

```
let average = sum / psi.len ( ) as f32 ;
```

Iterate Over the Elements

```
for p in psi.iter ( ) {  
    sum += *p ;  
}
```

No index at all

p **borrow**s each element in turn

*p is its contents - no bounds to get wrong

Changing Elements in Rust

```
for p in psi.iter_mut ( ) {  
    *p = *p * 2.0 ;  
}
```

`iter_mut ( )` borrows each element as **&mut**

`psi` must be declared **let mut**

Index and Value Together

```
for ( i, p ) in psi.iter ( ).enumerate ( ) {  
    println! ( "reading {} = {} psi", i, p ) ;  
}
```

enumerate pairs each element with its index:
(0, psi[0]), (1, psi[1]), ...

Range-based for in C++

```
std::array<float, 100> psi ;
```

```
for ( float p : psi ) {  
    sum += p ;  
}
```

C++11 and later

p is a **copy** of each element in turn

Changing Elements in C++

```
for ( float &p : psi ) {  
    p = p * 2.0f ;  
}
```

p is a **reference** - another name for each element

Without the & only the copy changes

Looping Over Structs in C++

```
std::array<sample_t, 100> history ;
```

```
for ( const auto &s : history ) {  
    sum += s.psi ;  
}
```

auto: let the compiler work out the type

const &: read without copying 16 bytes

Iteration vs Indexing

Indexing: you count, then look up
psi[i] - you can count wrong

Iteration: the collection hands you
each element in turn
for p in psi - nothing to count

An **iterator** is the thing that hands them out

One Loop, Three Languages

C: for (int i = 0 ; i < n ; i++)
 sum += psi[i] ;

C++: for (float p : psi)
 sum += p ;

Rust: for p in psi.iter () {
 sum += *p ;
 }

break: Leave the Loop Now

```
int alarm_at = -1 ;  
for ( int i = 0 ; i < n ; i++ ) {  
    if ( psi[i] > 80.0f ) {  
        alarm_at = i ;  
        break ;  
    }  
}
```

Stop at the **first** reading over 80 psi

continue: Skip This One

```
for ( int i = 0 ; i < n ; i++ ) {  
    if ( counts[i] == 0 || counts[i] >= 4095 )  
        continue ;  
    sum += adc_to_psi ( counts[i] ) ;  
    good++ ;  
}
```

Skip the faulty readings, keep going

Rust's loop

```
loop {  
    body  
}
```

Repeats **forever** until a `break`

Clearer than `while true`
when you really mean "until I say stop"

loop Can Give Back a Value

```
let counts = loop {  
    let c = read_adc ( ) ;  
    if c > 0 && c < 4095 {  
        break c ;  
    }  
} ;
```

break value ends the loop with a result

Infinite Loops on Purpose

Embedded programs **never end**:

<code>while (1) { ... }</code>	C
<code>for (; ;) { ... }</code>	C, C++
<code>loop { ... }</code>	Rust

Arduino's `loop ( )` function is called forever by a hidden `for ( ; ; )`

Infinite Loops by Accident

Forgot the update:

```
while ( n > 0 ) { printf ( "%d", n ) ; }
```

Update goes the wrong way:

```
for ( int i = 0 ; i < 10 ; i-- )
```

Test can never become false:

```
for ( double x = 0.0 ; x != 1.0 ; x += 0.1 )
```

Nested Loops

A loop inside a loop

The inner loop runs **completely** for each pass of the outer loop

`uint8_t image[3][4] ;` 3 rows of 4

	<i>c = 0</i>	<i>c = 1</i>	<i>c = 2</i>	<i>c = 3</i>
<i>r = 0</i>	1	2	3	4
<i>r = 1</i>	5	6	7	8
<i>r = 2</i>	9	10	11	12

The numbers show the visiting order

Example: Nested Loops in C

```
for ( int r = 0 ; r < 3 ; r++ ) {  
    for ( int c = 0 ; c < 4 ; c++ ) {  
        image[r][c] = 0 ;  
    }  
}
```

3 x 4 = 12 iterations of the inner body

Example: Nested Loops in Rust

```
for r in 0..3 {  
    for c in 0..4 {  
        image[r][c] = 0 ;  
    }  
}
```

Or without indices:

```
for row in image.iter_mut ( ) {  
    for px in row.iter_mut ( ) { *px = 0 ; }  
}
```

Breaking Out of Two Loops

`break` leaves only the **innermost** loop

Rust: label the outer loop

```
'outer : for r in 0..3 {  
    for c in 0..4 {  
        if image[r][c] == 255 { break 'outer ; }  
    }  
}
```

C, C++: use a flag, or move the loops into a function and return

Looping Over an Array of Structs

```
sample_t history[100] ;  
float sum = 0.0f ;  
  
for ( int i = 0 ; i < 100 ; i++ ) {  
    sum += history[i].psi ;  
}
```

Index the array, then reach the member

Example: Min and Max in C

```
float lo = psi[0], hi = psi[0] ;  
  
for ( size_t i = 1 ; i < n ; i++ ) {  
    if ( psi[i] < lo ) lo = psi[i] ;  
    if ( psi[i] > hi ) hi = psi[i] ;  
}
```

Start from the first element, not from 0

Example: Min and Max in Rust

```
let mut lo = psi[0] ;  
let mut hi = psi[0] ;  
  
for p in psi.iter ( ) {  
    if *p < lo { lo = *p ; }  
    if *p > hi { hi = *p ; }  
}
```

A Loop Inside a Function

```
float average ( const float *psi, size_t n ) {  
    if ( n == 0 ) return 0.0f ;  
    float sum = 0.0f ;  
    for ( size_t i = 0 ; i < n ; i++ )  
        sum += psi[i] ;  
    return sum / (float) n ;  
}
```

Same Function in Rust

```
fn average ( psi : &[f32] ) -> f32 {  
    if psi.is_empty ( ) { return 0.0 ; }  
    let mut sum = 0.0 ;  
    for p in psi.iter ( ) {  
        sum += *p ;  
    }  
    sum / psi.len ( ) as f32  
}
```


Example: Moving Average

Smooth noisy readings: average the last W

```
for ( size_t i = W - 1 ; i < n ; i++ ) {  
    float sum = 0.0f ;  
    for ( size_t k = 0 ; k < W ; k++ )  
        sum += psi[i - k] ;  
    smooth[i] = sum / W ;  
}
```

Moving Average in Rust

```
for i in ( W - 1 )..n {  
    let window = &psi[ i + 1 - W ..= i ] ;  
    let mut sum = 0.0 ;  
    for p in window.iter ( ) { sum += *p ; }  
    smooth[i] = sum / W as f32 ;  
}
```

A **slice** of W elements replaces the inner index

Example: Count the 1 Bits

```
int count = 0 ;  
while ( x != 0 ) {  
    count += x & 1 ;  
    x >>= 1 ;  
}
```

Test the low bit, shift, repeat

Rust has it built in: `x.count_ones ( )`

Rust: Loops Without a Loop

```
let sum : f32 = psi.iter ( ).sum ( ) ;
```

```
let n_high = psi.iter ( )  
    .filter ( | p | **p > 80.0 )  
    .count ( ) ;
```

Iterator methods run the loop for you

C++: Standard Algorithms

```
#include <numeric>
#include <algorithm>
```

```
float sum = std::accumulate (
    psi.begin ( ), psi.end ( ), 0.0f ) ;
```

```
auto hi = std::max_element (
    psi.begin ( ), psi.end ( ) ) ;
```

Recursion: Another Way to Repeat

A function that calls **itself**

```
unsigned long factorial ( unsigned n ) {  
    if ( n <= 1 ) return 1 ;  
    return n * factorial ( n - 1 ) ;  
}
```

Every problem needs a **stopping case**

Iteration or Recursion?

Each recursive call pushes a **stack frame**

factorial (5) uses 5 frames

A loop uses **one**

Too deep: **stack overflow**

Prefer a loop unless the problem is
naturally recursive - trees, for example

Loops in the Debugger

break main.c:12 if i == 97

stop only on the iteration you care about

watch sum

stop every time sum changes

display i

print i automatically at every stop

Loop Invariants

What is **always true** at the top of each pass?

sum holds the total of $\text{psi}[0] \dots \text{psi}[i-1]$

True before the first pass ($\text{sum} = 0, i = 0$)

Kept true by each pass

At exit, $i = n$ - so sum is the whole total

Choosing a Loop

Every element Rust `for p in ...` C++ `for`
`( p : ... )`

Known count `for`

Until a condition `while`

At least once `do ... while` / Rust `loop +`
`break`

Forever `while ( 1 )` / `loop`

Loops Across the Languages

	C	C++	Rust
while	yes	yes	yes
do while	yes	yes	loop + break
for (; ;)	yes	yes	no
for each	no	for (x : c)	for x in c
loop	no	no	yes
labeled break	no	no	yes

What We Can Now Do

Repeat statements with while, do, for, loop

Iterate over every element without an index

Control the loop with break and continue

Nest loops for tables and images

Check the four parts: init, test, body, update

Let's practice

Exercise: Using **looppractice**