

BREADTH-FIRST SEARCH & DEPTH-FIRST SEARCH

MSCI 240: Algorithms & Data Structures

lecture summary

shortest path
breadth-first search (BFS) algorithm
BFS example
connected components
depth-first search (DFS) algorithm
DFS example
BFS & DFS space and time complexity

slides by Mark Hancock

2

Topic	Building Java Programs	Algorithms (Sedgewick)
classes, ADTs	chapter 8	1.2
arrays	chapter 7	
ArrayList<T>	chapter 10	1.3
Stack/Queue	chapter 14, (11)	1.3
LinkedList	chapter 16	1.3
Complexity		1.4
Searching	chapter 13	pp. 46-47
Sorting		chapter 2.1-2.3
Recursion	chapter 12	1.1 (p. 25)
Binary Trees	chapter 17	chapter 3.1-3.2
Dictionaries	chapter 18.1	chapter 3.4
Graphs	N/A (Wikipedia good)	chapter 4.1
Heaps/Priority Queues	chapter 18.2	chapter 2.4

slides by Mark Hancock


3

shortest path

slides by Mark Hancock

4


e.g., nodes = computers, edges = connections



slides by Mark Hancock

5


what's the quickest way from your computer to info?



slides by Mark Hancock

6

what's the quickest way from your computer to info?




- a) 3,4,2,5,6,7,9,10 (L=8)
- b) 3,2,5,6,9,10 (L=5)
- c) 3,2,5,12,10 (L=4)

how can you be sure it's the **shortest**?

slides by Mark Hancock

7



how do we find
shortest paths
in larger graphs?

slides by Mark Hancock (image source: <http://facs.leidenuniv.nl/~takeshi/SNACS/>)

8

breadth-first search (BFS)

slides by Mark Hancock

9

BFS description

starts from a **source** vertex, s

traverses edges of graph, G , to discover every vertex **reachable** from s

finds **shortest path** from s to every other vertex
all these paths make a **BFS tree**

slides by Mark Hancock

10

BFS algorithm outline

basic idea: visit **all edges** before moving on to the **next vertex**

keep track of **next vertex** with a queue (starts with just s in it)

take the **front** element off the queue (call this u)

add all vertices adjacent to u to the queue (i.e., visit all its edges),
but **only** if they haven't been visited yet

as you visit each vertex, v , keep track of:

distance from v to s – to keep track of path length (u 's distance + 1)

v 's **parent** – the vertex (u) that is visiting this vertex first

slides by Mark Hancock

11

```
public class IntGraphList {
    private HashMap<Integer, LinkedList<Integer>> adjacencyList;

    //...
    public void breadthFirstSearch(int source) {
        // next slide ...
    }
}
```

slides by Mark Hancock

12

```

public void breadthFirstSearch(int source) {
    Map<Integer, Integer> distances = new HashMap<>(); // vertices to integers
    Map<Integer, Integer> parents = new HashMap<>(); // vertices to vertices

    for (int node : adjacencyList.keySet()) { // for every vertex
        distances.put(node, -1); // initialize distance and parent
        parents.put(node, null);
    }

    Queue<Integer> q = new LinkedList<>(); // keep track of "visited" vertices
    distances.put(source, 0);
    q.add(source);

    while (!q.isEmpty()) {
        int u = q.remove();
        for (int v : adjacencyList.get(u)) { // for every vertex adjacent to u
            if (distances.get(v) == -1) { // if v is not yet visited
                distances.put(v, distances.get(u) + 1);
                parents.put(v, u);
                q.add(v);
            }
        }
        // do something with distances, and/or parents
    }
}

```

slides by Mark Hancock

13

example: breadthFirstSearch(3);

```

while (!q.isEmpty()) {
    int u = q.remove();
    for (int v : adjacencyList.get(u)) {
        if (distances.get(v) == -1) {
            distances.put(v, distances.get(u) + 1);
            parents.put(v, u);
            q.add(v);
        }
    }
}

```

slides by Mark Hancock

14

vertex	distance	parent
3	0	null
1	1	3
2	1	3
4	1	3
5	2	2
6	3	5
7	3	5
8	3	5
12	3	5
9	4	6
11	4	7
10	4	12

q [3, 1, 2, 4, 5, 6, 7, 8, 12, 9, 11, 10]

slides by Mark Hancock

15

vertex	distance	parent
3	0	null
1	1	3
2	1	3
4	1	3
5	2	2
6	3	5
7	3	5
8	3	5
12	3	5
9	4	6
11	4	7
10	4	12

BFS Tree

slides by Mark Hancock

16

connected components

slides by Mark Hancock

17

your computer

your condo?


your ISP

info

slides by Mark Hancock


18

in this graph there are 2 connected components



slides by Mark Hancock


19



how many
connected
components?

slides by Mark Hancock (image source: <http://lacs.leidenuniv.nl/~takeshy/SNACS/>)

20




slides by Mark Hancock

21

same graph!

\therefore 2 connected components each



slides by Mark Hancock

22

depth-first search (DFS)

slides by Mark Hancock

23

DFS description

does **not** require a source vertex
but **can** have a starting point

traverses edges of graph, G , depth-first to discover
connected components
every vertex **reachable** from every other vertex

all these paths make a **DFS tree**

slides by Mark Hancock

24

DFS algorithm outline

idea: keep visiting vertices **as far as you can** before trying another path

keep track of **next vertex** with a stack/recursion

keep pushing onto stack (recursive case) for next unvisited node

only pop off stack (base case) when all adjacent nodes visited

as you visit each vertex, v , keep track of:

whether v is visited – mark visited as soon as recursion called on v

v 's **parent** – the vertex (u) that is visiting this vertex first

slides by Mark Hancock

25

```
public class IntGraphList {
    private HashMap<Integer, LinkedList<Integer>> adjacencyList;

    // ...
    public void depthFirstSearch() {
        Map<Integer, Boolean> visited = new HashMap<>();
        Map<Integer, Integer> parents = new HashMap<>();

        for (int v : adjacencyList.keySet()) { // for every vertex
            visited.put(v, false);
            parents.put(v, null);
        }

        for (int v : adjacencyList.keySet()) { // for every vertex
            dfsVisit(v, visited, parents); // recursive method
        }
    }
    // ...
}
```

slides by Mark Hancock

26


```
private void dfsVisit(int u, Map<Integer, Boolean> visited,
    Map<Integer, Integer> parents) {

    visited.put(u, true);
    for (int v : adjacencyList.get(u)) { // for every v adjacent to u
        if (!visited.get(v)) {
            parents.put(v, u);
            dfsVisit(v, visited, parents);
        }
    }
}
```

slides by Mark Hancock

27


example: depthFirstSearch()



```
private void dfsVisit(...) {
    visited.put(u, true);
    for (int v : adjacencyList.get(u)) {
        if (!visited.get(v)) {
            parents.put(v, u);
            dfsVisit(v, visited, parents);
        }
    }
}
```

slides by Mark Hancock

28



vertex	visited	parent
1	true	null
2	true	1
3	true	2
6	true	2
4	true	6
5	true	4
8	true	5
9	true	8
10	true	8
7	true	4
11	true	7
12	true	11

slides by Mark Hancock

29

BFS & DFS complexity

slides by Mark Hancock

30

let

$n = |V|$ = number of vertices

$m = |E|$ = number of edges

space complexity:

adjacency matrix $\rightarrow O(n^2)$

adjacency list $\rightarrow O(n + m)$

slides by Mark Hancock

31

how much additional space does BFS use? $\rightarrow O(n)$

how much additional space does DFS use? $\rightarrow O(n)$

what's the order of growth of BFS? $\rightarrow O(n + m)$

what's the order of growth of DFS? $\rightarrow O(n + m)$

slides by Mark Hancock

32

<https://www.cs.usfca.edu/~galles/visualization/BFS.html>

<https://www.cs.usfca.edu/~galles/visualization/DFS.html>

slides by Mark Hancock

33


clicker question

slides by Mark Hancock

34

what order does BFS(6) visit each of the nodes in the following graph, assuming nodes are in ascending order in the adjacency lists:

- A. 6,2,1,5,7,3,0,4
- B. 7,6,5,4,3,2,1,0
- C. 6,2,5,0,1,4,7,3
- D. 6,2,5,1,7,4,0,3
- E. 0,2,3,4,1,6,7,5




slides by Mark Hancock

35

what order does DFS(6) visit each of the nodes in the following graph, assuming nodes are in ascending order in the adjacency lists:

- A. 6,2,1,5,7,3,0,4
- B. 7,6,5,4,3,2,1,0
- C. 6,2,5,0,1,4,7,3
- D. 6,2,5,1,7,4,0,3
- E. 0,2,3,4,1,6,7,5



slides by Mark Hancock

36

in order to find the shortest path between two nodes in a graph, you could use the following algorithm(s):

- A. DFS
- B. BFS
- C. adjacency list
- D. adjacency matrix
- E. any of the above

slides by Mark Hancock

37

if DFS is run on a graph that also happens to already be a tree, it will produce the same tree as BFS

- A. true
- B. false

slides by Mark Hancock

38

if DFS is run on a graph that also happens to already be a tree, it will visit nodes in the same order as BFS

- A. true
- B. false

slides by Mark Hancock

39

next:
priority queue implementation (heaps)

slides by Mark Hancock

40
