

## A little more about constraints

- A pedagogically great article on constraints (even if it is a trade article)
- Pollack, has been added to box, readings

7:Semantics/Triggers/View

Database Systems

1

## Purpose [Pollack 2016]

- Prevent bad data from being entered into tables of interest.
- Enforce business logic at the database-level.
- Documentation of important database rules.
- Enforce relational integrity between any number of tables.
- Improve database performance.
- Enforce uniqueness.

7:Semantics/Triggers/View

Database Systems

2

## Views: A Database Mechanism

1. For expressing a subroutine like mechanism
2. For capturing application semantics
3. For defining alternate data models of the actual DB

7:Semantics/Triggers/View

Database Systems

3

## Views: A Database Mechanism

1. For expressing a subroutine like mechanism
2. For capturing application semantics
3. For defining alternate data models of the actual DB

Applications (later):

- Data Integration
- Expression and Compilation of Inheritance in UML

Today's Objectives:

- Gross concept
- Syntax and Semantics
- Logical (unmaterialized) vs. Materialized Views

7:Semantics/Triggers/View

Database Systems

4

## Recall:

- Relational operators take relation(s) as arguments, return a relation as their value.
- SQL query returns a table.

7Views

Database Systems

5

## To Define a View:

```
CREATE VIEW view-name AS
    select, from, where
```

“*view-name*” can then be used nearly anywhere a table name can be used.

7Views

Database Systems

6

## Example 1:

Suppose we have a table:

Student(first, last, address, SS#)

```
CREATE VIEW view-name AS a SFW query
```

We need to be diligent about privacy of SS#s:

```
CREATE VIEW publicStudent AS
SELECT first, last, address
FROM Student
```

```
SELECT *
FROM publicStudent PS
WHERE PS.last = 'Smith'
```

What does this return?  
What does it not return?

7Views

Database Systems

7

## Semantics: Rewrite as Nested Query

```
SELECT *
FROM publicStudent PS
WHERE PS.last = 'Smith'
```

```
SELECT *
FROM (SELECT first, last, address
      FROM Student)
      AS PS
WHERE PS.last = 'Smith'
```

```
CREATE VIEW publicStudent AS
SELECT first, last, address
FROM Student
```

7Views

Database Systems

8

## 2 Things to Observe

1. publicStudent is, effectively, a different model of the data.  
*//speaks to being able to restructure the data model*
2. As a new model, it hides information.  
*// an implementation of privacy and security*

7:Semantics/Triggers/View

Database Systems

9

## DBA Moment

- Never exploit Social Security number as a key.

7:Views


Database Systems

10

## DBA Moment:

- Never exploit Social Security number as a key.

Subtly:



what get's used as the fk?

7:Views

Database Systems

11

## [Legacy] Three Schema Model - A word about security

*A database guys perspective - everything's a schema*

- ANSI/SPARC introduced the three schema model in 1975  
*// Legacy - in this case, even before my time, but it makes the point*
- It provides a framework describing the role and purpose of data modeling

7:Views

Database Systems

12

## Three Schema Model Design with Security in Mind

- External schema or user view
  - Representation of how users view the database
- Conceptual schema
  - A logical view of the database containing a description of all the data and relationships
- Internal schema
  - A representation of a conceptual schema as physically stored on a particular product

7Views

Database Systems

13

Example 1, above:

- transform a data model for security

Example 2, next:

- use as a subroutine

7:Semantics/Triggers/View

Database Systems

14

## Example 2:

```
CREATE VIEW CheapBeer
  SELECT DISTINCT name, b_id
  FROM Beers, Sells
  WHERE Beer.b_id = Sells.b_id AND
         Sells.price < (SELECT AVG(price)
                        FROM Sells);
```

7Views

Database Systems

15

## Query: Really Cheap Beer

```
SELECT name
FROM CheapBeer, Sells
WHERE CheapBeer.b_id = Sells.b_id AND
       Sells.price < (SELECT AVG(price)
                      FROM Sells);
```

**\*\* CheapBeer are those that are less than the average. The join condition will limit the next calculation to those beers that are less than average cost. i.e. the average of those that are less than average.**

7Views

Database Systems

16

## Where can I not use a view?

- Consider:

```
INSERT INTO publicStudent( 'Jeff' , ' Zhu' , ' Jester' )
```

```
CREATE VIEW publicStudent
SELECT first, last, address
FROM Student
```

- Base Relation:

```
Student(first, last, address, SS#)
```

>SS# is missing... can't do it,  
or

- insert NULL ?
- it depends... vendor*

7Views

Database Systems

17

## Implementation Logical vs. Materialized

- Materialize: The view's query result is computed and saved to disk.  
\*\* In SQL, reserved keyword, Materialize, inserted as part of view definition.
- What happens when a row is added to base relation

7:Semantics/Triggers/View

Database Systems

18

## What about?

- Consider:

```
INSERT INTO Student( 'Jeff' , 'Zhu' , ' Jester' , 123-45-6789)
// inserting into a base relation
```

- What happens to?:

```
CREATE VIEW publicStudent
SELECT first, last, address
FROM Student
```

- It depends on the implementation

~~Next slide, then~~

- ~~Relational Algebra, on board,~~
- ~~Where have we seen this before?~~

7Views

Database Systems

19

## Materialized View (Oracle)

### CREATE MATERIALIZED VIEW

- Query is executed and result stored

### REFRESH MATERIALIZED VIEW

- replaces the contents of a materialized view (re-executes the query)

7:Semantics/Triggers/View

Database Systems

20

## Incremental Maintenance of a View

- Key axiom: \*\*|X| is join

$$(R \cup S) |X| T = (R |X| T) \cup (S |X| T)$$

- So, if View,  $V = (S |X| T)$
  - Insert Into S, rows R, to create S'
- $$V' = S' |X| T$$

7:Semantics/Triggers/View

Database Systems

21

## Incremental Maintenance of a View

- Key axiom: \*\*|X| is join

$$(R \cup S) |X| T = (R |X| T) \cup (S |X| T)$$

7:Semantics/Triggers/View

Database Systems

22

## Incremental Maintenance of a View

$$(R \cup S) |X| T = (R |X| T) \cup (S |X| T)$$

So, if View,  $V = (S |X| T)$

- Insert Into S, rows R, i.e.  $S' = (R \cup S)$
- New view contents,  $V'$ ,  $V' = S' |X| T$

$$\begin{aligned} V' &= (R \cup S) |X| T \\ &= (R |X| T) \cup (S |X| T) \\ &= (R |X| T) \cup V \end{aligned}$$

7:Semantics/Triggers/View

Database Systems

23

## Incremental Maintenance of Materialized Views

- Incremental axioms exist for all relational operators.
- If interested see qian91 paper in recommended readings.

7:Semantics/Triggers/View

Database Systems

24

## Logical Implementation

7:Semantics/Triggers/View

Database Systems

25

## Logical: Query optimizer operates on the plan


7:Semantics/Triggers/View

Database Systems

26

## Query plan on board...

- Details will be posted
- Basics, initial logical plan




7:Semantics/Triggers/View

Database Systems

27

- Basics, initial logical plan
- Replace View-Name, with logical plan of the view's defining query.
- Let the optimizer do it's job...



7:Semantics/Triggers/View

Database Systems

28

## Where can I not use a view?

- Consider:

```
INSERT INTO publicStudent( 'Jeff' , ' Zhu' , ' Jester' )
```

```
CREATE VIEW publicStudent
SELECT first, last, address
FROM Student
```

- Base Relation:

```
Student(first, last, address, SS#)
```

>SS# is missing

- insert into Student table the row + NULL ?
- it depends... vendor*

7Views

Database Systems

29

## What about deleting from a view?

- Could work for the examples....
- What about in general?
- What to do? Put the developer in control

Options:

- programmer can pick flags and their settings
- allow triggers on views

7:Semantics/Triggers/View

Database Systems

30

## In Oracle

```
CREATE [OR REPLACE] VIEW [{FORCE | NOFORCE}] VIEW view_name
[(alias_name[, alias_name...])] AS subquery
[WITH {CHECK OPTION | READ ONLY} CONSTRAINT constraint_name];
```

[http://www.java2s.com/Tutorial/Oracle/0160\\_View/CreatingandUsingaView.htm](http://www.java2s.com/Tutorial/Oracle/0160_View/CreatingandUsingaView.htm)

- 8.WITH CHECK OPTION specifies that only the rows that would be retrieved by the subquery can be inserted, updated, or deleted.
- 9.By default, rows are not checked that they are retrievable by the subquery before they are inserted, updated, or deleted.
- 10.constraint\_name specifies the name of the WITH CHECK OPTION or READ ONLY constraint.
- 11.WITH READ ONLY specifies that rows may only read from the base tables.

7Views

Database Systems

31