A MATSim-based framework to Incorporate High Resolution Built Environment Data for Modelling Walkability and Cyclability

Corin Staves[1] *(PhD Student)*
SM Labib[2] *(Assistant Professor)*
Irena Itova[1] *(Research Associate)*
Qin Zhang[1] *(Research Associate)*
James Woodcock[1] *(Programme Lead in Public Health Modelling)*
Rolf Moeckel[3] *(Associate Professor)*
Belen Zapata-Diomedi[4] *(Postdoctoral Fellow)*

[1] MRC Epidemiology Unit, University of Cambridge
[2] Faculty of Geosciences, Utrecht University
[3] Professorship for Travel Behaviour, Technical University of Munich
[4] Centre for Urban Research, Royal Melbourne Institute of Technology

MATSim User Meeting
Zurich, 5 September 2023

Contents

Built Environment Influences Active Travel

Pedestrian and Cycling Infrastructure

- Width
- Surface quality
- Separation from traffic
- Traffic speed / volume

Junctions and Crossings

- Signal type
- Crossing speed / volume

Built Environment Influences Active Travel

Vehicle Infrastructure

- Traffic filters
- Freight loading zones

Ambience

- Tree cover
- Green visibility
- Points of interest
- Streetlighting

Influences on Travel Behavior

- Route Choice

- Mode Choice

- Trip Generation

- Public transport subscription

- Bicycle ownership

- Car ownership

- Choice of residence / workplace

Lots of research on this topic…

▪ Examples in **Public Health research**…

 o Cain, K. L., Millstein, R. A., Sallis, J. F., Conway, T. L., Gavand, K. A., Frank, L. D., Saelens, B. E., Geremia, C. M., Chapman, J., Adams, M. A., Glanz, K., & King, A. C. (2014). Contribution of streetscape audits to explanation of physical activity in four age groups based on the Microscale Audit of Pedestrian Streetscapes (MAPS). Social Science & Medicine, 116, 82–92. https://doi.org/10.1016/j.socscimed.2014.06.042

 o Zapata-Diomedi, B., Herrera, A. M. M., & Veerman, J. L. (2016). The effects of built environment attributes on physical activity-related health and health care costs outcomes in Australia. *Health & Place, 42*, 19–29. https://doi.org/10.1016/j.healthplace.2016.08.010

▪ Examples in **Transport modelling**…

 o Cervero, R., & Kockelman, K. (1997). Travel demand and the 3Ds: Density, diversity, and design. Transportation Research Part D: Transport and Environment, 2(3), 199–219. https://doi.org/10.1016/S1361-9209(97)00009-6

 o Thao, V. T., & Ohnmacht, T. (2020). The impact of the built environment on travel behavior: The Swiss experience based on two National Travel Surveys. Research in Transportation Business & Management, 36, 100386. https://doi.org/10.1016/j.rtbm.2019.100386

▪ Examples in **MATSim**…

 o Ziemke, Dominik et al. *Modeling bicycle traffic in an agent-based transport simulation.* Procedia Computer Science, 2017 (https://doi.org/10.1016/j.procs.2017.05.424)

 o Antoniou, Eleni et al. *Simulation of e-bike and e-scooter trips using MATSim. Presented at MUM2022* (*https://ethz.ch/content/dam/ethz/special-interest/baug/ivt/ivt-dam/events/2022/05/31/presentations/Antoniou_EtAl_MUM_2022_Presentation.pdf*)

Walkability and Cyclability as an **Accessibility** indicator

- **Describes a location** (e.g., household or workplace)

- Indicator of **travel behavior** and **social equity**

- Typically use **aggregate**, **area-level** measurements of land use and/or the transport network

- Examples:
  - *Density of pedestrian or cycle paths in an area*
  - *Network connectivity*
  - *Land use diversity*
  - *Number of shops within 800m (10-minute) walk*
  - *Some aggregation of the above*

Walkability and Cyclability: Common Limitations

- **Spatial aggregation**
  - Modifiable Aerial Unit Problem (MAUP)

- **Hard cutoffs**
  - Smooth decay functions are more behaviorally realistic

- **Assumption of independence** between built environment, network, and land use
  - People perceive the built environment as they use the network to get places
  - Assuming independence distorts modelled relationship and assessments

Why?

- *Simple to develop and describe*
- *Challenging to integrating built environment, network, and land use*
- *Computational feasibility*


https://www.open-accessibility.org

Research Overview and Methods

Developing a fully disaggregate walkability and cyclability assessment tool

Main Research Goals (Overview):

1. Incorporate built environment characteristics into a MATSim network at the street segment (link) resolution

2. Specify an active mode accessibility model incorporating the **built environment, transport network,** and **land use** through a two-component approach

3. Efficiently estimate accessibilities at any level of disaggregation, e.g.:
    * Zones
    * Grid cells
    * Exact households

Study Area: Greater Manchester

Research Goals:

1. Incorporate built environment characteristics into a MATSim network at the street segment (link) resolution

2. *Specify an active mode accessibility model incorporating the **built environment, transport network,** and **land use** through a two-component approach*

3. *Estimate accessibilities at any level of disaggregation, e.g.:*
   - *Zones*
   - *Grid cells*
   - *Exact households*

Goal 1: Incorporating Built Environment Attributes into MATSim

- Road infrastructure information
- Posted speed
- Sidewalk, Cycleway

- Road width
- Traffic calming features
- Digital Surface Model
- Digital Terrain Model
- Points of Interest

- Observed 85th % speed
- Crossings, signals
- Cycle infrastructure (Bee Network)
- Streetlights (Bee Network)
- Canopy data (City of Trees)

- Normalized Difference Vegetation index (Sentinel-2)

- Modal filters
- Quietness index

- Crime locations

Total of 65 link attributes

Examples:

85th % Speed (KPH)
- 1 - 13
- 13 - 32
- 32 - 44
- 44 - 60
- 60 - 128

Sidewalk
- No
- Yes
- Both Side
- Not Applicable

Eye level Greenness Visibility
- 0 - 0.091
- 0.091 - 0.279
- 0.279 - 0.477
- 0.477 - 0.696
- 0.696 - 0.873

Result (network.xml):

```xml
<link id="404423rtn" from="210689" to="344813" length="7.834059578968688" freespeed="13.4112" capacity="600.0" permlanes="1.0" oneway="1" modes="ca
    <attributes>
        <attribute name="POIs" class="java.lang.Double">0.0</attribute>
        <attribute name="aadt" class="java.lang.Double">1226.4529</attribute>
        <attribute name="aadt2" class="java.lang.Double">0.0</attribute>
        <attribute name="aadtFwd" class="java.lang.Double">613.22645</attribute>
        <attribute name="allowsCar" class="java.lang.Boolean">true</attribute>
        <attribute name="allowsCarFwd" class="java.lang.Boolean">true</attribute>
        <attribute name="crime" class="java.lang.Double">0.0</attribute>
        <attribute name="cross85PercSpeed" class="java.lang.Double">NaN</attribute>
        <attribute name="crossAadt" class="java.lang.Double">NaN</attribute>
        <attribute name="crossLanes" class="java.lang.Double">NaN</attribute>
        <attribute name="crossSpeedLimitMPH" class="java.lang.Double">NaN</attribute>
        <attribute name="crossVehicles" class="java.lang.Boolean">false</attribute>
        <attribute name="crossWidth" class="java.lang.Double">NaN</attribute>
        <attribute name="cycleosm" class="java.lang.String">null</attribute>
        <attribute name="cycleway" class="java.lang.String">no</attribute>
        <attribute name="disconnected_bike" class="java.lang.Boolean">false</attribute>
        <attribute name="disconnected_car" class="java.lang.Boolean">false</attribute>
        <attribute name="disconnected_walk" class="java.lang.Boolean">false</attribute>
        <attribute name="dismount" class="java.lang.Boolean">false</attribute>
        <attribute name="edgeID" class="java.lang.Integer">404423</attribute>
        <attribute name="endsAtJct" class="java.lang.Boolean">false</attribute>
        <attribute name="fwd" class="java.lang.Boolean">false</attribute>
        <attribute name="hgvPOIs" class="java.lang.Double">0.0</attribute>
        <attribute name="junction" class="java.lang.String">no</attribute>
        <attribute name="motorway" class="java.lang.Boolean">false</attribute>
        <attribute name="name" class="java.lang.String">New Drake Green</attribute>
        <attribute name="ndvi" class="java.lang.Double">0.390443881352742</attribute>
        <attribute name="negPOIs" class="java.lang.Double">0.0</attribute>
        <attribute name="osmID" class="java.lang.Integer">699773100</attribute>
        <attribute name="quietness" class="java.lang.Integer">80</attribute>
        <attribute name="shannon" class="java.lang.Double">0.0</attribute>
        <attribute name="speedLimitMPH" class="java.lang.Integer">30</attribute>
```

Research Goals:

1. *Incorporate built environment characteristics into a MATSim network at the street segment (link) resolution*

2. Specify an active mode accessibility model incorporating the **built environment, transport network,** and **land use** through a two-component approach

3. *Estimate accessibilities at any level of disaggregation, e.g.:*
   - *Zones*
   - *Grid cells*
   - *Exact households*

Two-component Accessibility Model

Function of **destination locations** and the **impedance of reaching them**:

$$A_i = \sum_j f(W_j, c_{ij})$$

Where:

- W_j *is the weight of destinations*

- c_{ij} *is the cost of reaching them (potential to incorporate built environment)*

- $f(\ )$ *is some decreasing function (usually exponential)*

Background:

- *Hansen, W. G. (1959). How Accessibility Shapes Land Use. Journal of the American Institute of Planners, 25(2), 73–76. https://doi.org/10.1080/01944365908978307*

- *Used predominantly in **transport modelling** to evaluate **car** and **public transport** accessibility*

- *Research gap w.r.t. using this for **active modes** and **built environment***

Composite Link Cost

Included Elements	Origin
Distance	**Dominant in existing tools**
Travel time	**MATSim Bicycle Extension** (Ziemke et al. 2019)
Gradient	
Surface type (e.g., asphalt, gravel, sand, …)	
Ambience (e.g., greenness, POIs, lighting, …)	**New**
Link Stress (e.g., vehicle traffic, cycle infrastructure, …)	**From guidance in UK Cycle Infrastructure Design Handbook (https://www.gov.uk/government/publications/cycle-infrastructure-design-ltn-120)**
Intersection Stress (e.g., crossing type, crossing traffic/speed, …)	

Costs are aggregated from the link to the route level, along the **least-cost** path

Composite Link stress (s_l)

For each link, we score its **stress** based on guidance from the UK Department for Transport.

Function of **infrastructure type & separation** and **traffic speed & volume**

- **Example for cycling:**

Composite Junction stress (s_j)

We score stress for each intersection based on the **signalization**, **crossing type**, and **crossing traffic speed & volume**

Speed Limit	Total traffic flow to be crossed (pcu)	Maximum number of lanes to be crossed in one movement	Uncontrolled	Cycle Priority	Parallel	Signal	Grade separated
≥ 60mph	Any	Any	pink	pink	pink	pink	green
40 mph and 50 mph	> 10000	Any	pink	pink	pink	green	green
	6000 to 10000	2 or more	pink	pink	pink	green	green
	0-6000	2	pink	pink	pink	green	green
	0-10000	1	orange	pink	pink	green	green
< 30mph	> 8000	> 2	pink	pink	pink	green	green
	> 8000	2	pink	pink	orange	green	green
	4000-8000	2	orange	orange	green	green	green
	0-4000	2	orange	green	green	green	green
	0-4000	1	green	green	green	green	green

Composite Link Ambience

We score the **ambience** (or "attractiveness") for each link based on:

- Shannon diversity index
- Points of interest
- Green visibility (daytime)
- Street lighting (at nighttime)
- Crime rates

Cost Function

$$c_l \;=\; m_{tt}tt_l \;+\; m_\nabla \nabla_l x_l \;+\; m_c c_l x_l \;+\; m_a a_l x_l \;+\; m_s s_l x_l \;+\; m_s s_j x_j$$

time (s) | gradient | surface comfort

From
MATSim Bicycle Extension
(Ziemke et al., 2019)

link ambience
- eye level green
- shannon index
- POIs
- street lighting
- "negative" POIs
- crime

link stress
- bike/pedestrian infrastructure
- traffic volumes
- traffic speed

intersection stress
- crossing type
- crossing volume
- crossing speed

Based on UK DfT
Cycle Design Handbook

Where
x_l is the length of link l, x_j is the width of intersection j at the to-node of link l
m is the marginal cost of each link attribute,
attributes tt_l, ∇_l, c_l, a_l, s_l, and s_j as defined above. c_l, a_l, s_l, and s_j are restricted to the range 0–1.

Decay function

Vale, D. S., & Pereira, M. (2017). The influence of the impedance function on gravity-based pedestrian accessibility measures: A comparative analysis. *Environment and Planning B: Urban Analytics and City Science*, *44*(4), 740–763. https://doi.org/10.1177/0265813516641685

"Cumulative gaussian" decay function

Vale, D. S., & Pereira, M. (2017). The influence of the impedance function on gravity-based pedestrian accessibility measures: A comparative analysis. *Environment and Planning B: Urban Analytics and City Science*, 44(4), 740–763. https://doi.org/10.1177/0265813516641685

Decay function: Implementation in MATSim

```java
public class CumulativeGaussian extends DecayFunction {
    5 usages
    final private double a;
    3 usages
    final private double v;
    1 usage    Corin Staves
    public CumulativeGaussian(double a, double v, Double cutoffDist, Double cutoffTime) {
        super(cutoffTime, cutoffDist);
        this.a = a;
        this.v = v;
    }
    1 usage    Corin Staves
    public CumulativeGaussian(double a, double v) {
        super(Double.NaN, Double.NaN);
        this.a = a;
        this.v = v;
    }
    4 usages    Corin Staves
    public double getDecay(double cost) { return cost <= a ? 1. : Math.exp(-1 * (cost - a) * (cost - a) / v); }

}
```

Research Goals:

1. *Incorporate built environment characteristics into a MATSim network at the street segment (link) resolution*

2. *Specify an active mode accessibility model incorporating the* **built environment, transport network,** *and* **land use** *through a two-component approach*

3. Estimate accessibilities at any level of disaggregation, e.g.:
   - Zones
   - Grid cells
   - Exact households

MATSim tools & data structures

SpeedyGraph

- A "highly optimized data structure" for representing a MATSim network"
- Originally developed by SBB to efficiently calculate skim matrices
- https://github.com/SchweizerischeBundesbahnen/matsim-sbb-extensions
- *Enhanced to include pre-calculated link disutilies*

LeastCostPathTree

- Efficiently calculates least cost path trees to *all* nodes using the *SpeedyGraph* structure
- Specifying cutoffs reduces computation time further
- Also developed for MATSim SBB extensions

Steps

1. Convert network to a *SpeedyGraph*

2. Snap destinations to nodes

3. For every analysis point
   - Build a *LeastCostPathTree*
   - Loop over every destination node and calculate two-component accessibility based on cost, destination weight, and chosen decay function

Calculating Accessibility of Points

- Identify closest network link

- Define "pseudo-node" at point

- Define two "pseudo-links" between point and to/from node of closest link

- Calculate accessibility at new "pseudo-node"

Calculating Accessibility of Polygons

- If polygon contains at least one node, use the average accessibility of the nodes in the polygon

Calculating Accessibility for Polygons

- If polygon contains at least one node, use the average accessibility of the nodes in the polygon

- If polygon contains no nodes, calculate polygon centroid and use point method

Example: Walking accessibility to Foodstores

Analysis units: Households
**Destinations:** Food stores
Impedance: Distance only
Decay: Cumulative Gaussian

$$A_i = \sum_j O_j \delta_{ij}, \qquad \text{for } C_{ij} \leq a$$

$$A_i = \sum_j O_j e^{-\frac{(C_{ij}-a)^2}{v}} \qquad \text{for } C_{ij} > a$$

with a = 200, v = 57700

(decay function specification from Vale and Pereira, 2017)

Legend:
- Foodstore Locations

Walkability (normalised)
- 0 - 0.05
- 0.05 - 0.1
- 0.1 - 0.15
- 0.15 - 0.2
- 0.2 - 0.25
- 0.25 - 0.3
- 0.3 - 0.35
- 0.35 - 0.4
- 0.4 - 0.45
- 0.45 - 0.5
- 0.5 - 0.55
- 0.55 - 0.6
- 0.6 - 0.65
- 0.65 - 0.7
- 0.7 - 0.75
- 0.75 - 0.8
- 0.8 - 0.85
- 0.85 - 0.9
- 0.9 - 0.95
- 0.95 - 1

UKRI — MRC Epidemiology Unit · UNIVERSITY OF CAMBRIDGE · Utrecht University · Technical University of Munich TUM · RMIT UNIVERSITY

# Example: Cycling accessibility to foodstores

Analysis units: Hexagonal Grid cells (50m radius)
**Destinations:** Food stores
Decay function: Exponential (α parameter based on observed trips)
Impedance: Distance only   Composite (incorporating ambience/stress)

Ratio: Composite vs. Distance-based Accessibility

Difference
Accessibility
Ratio

- 0,791701 - 1,313447
- 1,313448 - 1,835193
- 1,835194 - 2,356939
- 2,356940 - 2,878686
- 2,878687 - 3,400432

Capabilities

- Forward/active and backward/passive accessibility (or a combination)

- Variation in fine-grained zones/polygons

- Destinations with Multiple access points

- Non-contiguous polygons

- Any impedance (cost) function

- Any decay function

- Can specify cutoff distances/times to improve runtime

- Open source: https://github.com/jibeproject/matsim-jibe/tree/master/src/main/java/accessibility

Summary

- Evaluating impacts of the built environment on walkability and cyclability is a **research focus** across geographic, urban, social, transport, and health sciences

- Simple, one-dimensional indicators dominate, despite their theoretical and behavioral limitations

- Tools and frameworks developed for MATSim facilitate computationally feasible **high-resolution evaluation** of walkability and cyclability which incorporates the built environment, network, and land use

"**Joining Impact Models of Transport with Spatial Measures of the Built Environment**"

https://jibeproject.com

Professor James Woodcock
University of Cambridge

Dr Belen Zapata-Diomedi
RMIT University

This project has received funding from the European Research Council (ERC) under the Horizon 2020 research and innovation programme (grant agreement No 817754).

This material reflects only the author's views and the Commission is not liable for any use that may be made of the information contained therein.