University of Nottingham
UK | CHINA | MALAYSIA

Newcastle University

GEOSPATIAL SYSTEMS
CENTRE FOR DOCTORAL TRAINING

UKRI Engineering and Physical Sciences Research Council

A MATSim model for a low carbon future mobility in the UK context

David Alvarez Castro

/DACNC/ /d-alv/ d.alvarez2@newcastle.ac.uk @David_AlvCas

UKRI EPSRC

Supervisory team

Alistair Ford
Philip James
Roberto Palacín
Dominik Ziemke

1. PhD project aims

To **identify**

- infrastructure interventions
- changing human behaviour

to **reduce GHG emissions** in urban areas in the Tyne and Wear region of England (blue area on the map) and enable the agents the use of **active modes**.



Transport icons have been designed using resources from Flaticon.com

1. PhD project aims

To **identify**

- infrastructure interventions
- changing human behaviour

to **reduce GHG emissions** in urban areas in the Tyne and Wear region of England (blue area on the map) and enable the agents the use of **active modes**.



Four innovations to simulate transport scenarios with MATSim in the UK context:

1) a new, open-access and very detailed synthetic population methodology for any region in the UK;
2) an additional network attribute ("quietness")
3) a bicycle contribution code update
4) tailored "stick" and "carrot" scenarios

Transport icons have been designed using resources from Flaticon.com

Engineering and Physical Sciences Research Council

2. Synthetic population

Demand

- **Synthetic population**
- Socio-demographic
- Activity plan

Tools:
SPENSER platform (UoL)
Own developed codes (NU)
PAM (Arup)
OSMOX (Arup)

Datasets:
Census 2011
ONS 2019
National Travel Survey
OpenStreetMap

A simplified digital twin of the actual population (**2019**).

2.6 million inhabitants in
area of study

Engineering and Physical Sciences Research Council

2. Synthetic population

Demand

- **Synthetic population**
- **Socio-demographic**
- Activity plan

Tools:
SPENSER platform (UoL)
Own developed codes (NU)
PAM (Arup)
OSMOX (Arup)

Datasets:
Census 2011
ONS 2019
National Travel Survey
OpenStreetMap

Individual characteristics	Family dependencies	Mobility access	Spending power
Person ID	Marital status	Driving licence	Economic activity
Household ID	Children dependency	Car access	Occupation
Age		Bike access	Annual Gross Income
Sex			

SPENSER (UoL). Link: https://lida.leeds.ac.uk/research-projects/spenser-synthetic-population-estimation-and-scenario-projection-model/

2. Synthetic population

Demand

- **Synthetic population**
- Socio-demographic
- **Activity plan**

Tools:
SPENSER platform (UoL)
Own developed codes (NU)
PAM (Arup)
OSMOX (Arup)

Datasets:
Census 2011
ONS 2019
National Travel Survey
OpenStreetMap

Individual characteristics	Family dependencies	Mobility access	Spending power
Person ID	Marital status	Driving licence	Economic activity
Household ID	Children dependency	Car access	Occupation
Age		Bike access	Annual Gross Income
Sex			



National Travel Survey (NTS). Link: https://beta.ukdataservice.ac.uk/datacatalogue/studies/study?id=7553

2. Synthetic population

Demand

- **Synthetic population**
- Socio-demographic
- **Activity plan**

Tools:
SPENSER platform (UoL)
Own developed codes (NU)
PAM (Arup)
OSMOX (Arup)

Datasets:
Census 2011
ONS 2019
National Travel Survey
OpenStreetMap

Individual characteristics	Family dependencies	Mobility access	Spending power
Person ID	Marital status	Driving licence	Economic activity
Household ID	Children dependency	Car access	Occupation
Age		Bike access	Annual Gross Income
Sex			

Similar socio-demographic attributes



National Travel Survey (NTS). Link: https://beta.ukdataservice.ac.uk/datacatalogue/studies/study?id=7553

2. Synthetic population

Demand

- Synthetic population
- Socio-demographic
- Activity plan

Tools:
SPENSER platform (UoL)
Own developed codes (NU)
PAM (Arup)
OSMOX (Arup)

Datasets:
Census 2011
ONS 2019
National Travel Survey
OpenStreetMap

Individual characteristics | **Family dependencies** | **Mobility access** | **Spending power**





PAM (Arup). Link: https://github.com/arup-group/pam
OSMOX (Arup). Link: https://github.com/arup-group/osmox
OpenStreetMap. Link: https://download.geofabrik.de/

3. Network

Supply

Network

Tools:
Osmium,
UK2GTFS,
PUMA (Arup),
GeNet (Arup)

Datasets:
OpenStreetMap
UK GTFS
Defra DEM
Cyclestreet

A simplified digital representation of the road and public transport network

3. Network

Supply

Network

Tools:
Osmium,
UK2GTFS (ITS Leeds),
PUMA (Arup),
GeNet (Arup)

Datasets:
OpenStreetMap
UK GTFS
Defra DEM
Cyclestreet

Roads



GTFS

Osmium: Link: https://osmcode.org/osmium-tool/
UK2GTFS Link: https://itsleeds.github.io/UK2GTFS/

OpenStreetMap. Link: https://download.geofabrik.de/
UK GTFS: Links: https://data.atoc.org/rail-industry-data
https://www.travelinedata.org.uk/

3. Network

Supply

Network

Tools:
Osmium,
UK2GTFS (ITS Leeds),
PUMA (Arup),
GeNet (Arup)

Datasets:
OpenStreetMap
UK GTFS
Defra DEM
Cyclestreet



Roads GTFS Altitude and gradient

GeNet (Arup). Link:: https://github.com/arup-group/genet
Defra DEM: Link: https://environment.data.gov.uk/DefraDataDownload/?Mode=survey

3. Network

Supply

Network

Tools:
Osmium,
UK2GTFS (ITS Leeds),
PUMA (Arup),
GeNet (Arup)

Datasets:
OpenStreetMap
UK GTFS
Defra DEM
Cyclestreet

Roads

GTFS

Altitude and gradient



Cycleability rating

Cyclestreets. Cycleability ratings https://bikedata.cyclestreets.net/cycleability/

3. 1. Cycleability rating



Cycleability rating

Factors included:

- Road type
- Cycle infrastructure
- Path widths/quality
- Barriers, obstructions
- Land ownership
- Surface type and quality
- Kerbs

```
<link id="135000" from="5223735686025143745" to="5223735685278458531" length="59.8291710397853" freespeed="4.4705" capacity="435.0" permlanes="1.0"
    <attributes>
        <attribute name="cyclable" class="java.lang.String">1</attribute>
        <attribute name="geometry" class="java.lang.String">ibc}eroAooina}gB{ncpE_o|[cjqwCow~Z</attribute>
        <attribute name="osm:way:highway" class="java.lang.String">residential</attribute>
        <attribute name="osm:way:maxspeed" class="java.lang.String">20 mph</attribute>
        <attribute name="osm:way:osmid" class="java.lang.String">67624770</attribute>
        <attribute name="quietness" class="java.lang.String">0.6</attribute>
        <attribute name="slope" class="java.lang.String">-0.018093156425236068</attribute>
    </attributes>
</link>
```

Values between 0.0 and 1.0

0.0: very poor
1.0: excellent

Cyclestreets. Cycleability ratings https://bikedata.cyclestreets.net/cycleability/

Demand

Synthetic population

Supply

Network



Population
+
Network

GEOSPATIAL SYSTEMS
CENTRE FOR DOCTORAL TRAINING

University of Nottingham
UK | CHINA | MALAYSIA

Newcastle University

UKRI Engineering and Physical Sciences Research Council

4. Bicycle contribution extension update

Bicycle contribution (Ziemke et al, (2019))

Extension of the agent-based transport simulation framework MATSim for bicycle traffic.

- Road comfort (OSM tags: surface, highway, smoothness)
- Road infrastructure type (OSM tag: highway)
- Road gradient (DEM)

Ziemke, Dominik, Simon Metzler, and Kai Nagel. "Bicycle traffic and its interaction with motorized traffic in an agent-based transport simulation framework." Future Generation Computer Systems 97 (2019): 30-40. https://doi.org/10.1016/j.future.2018.11.005

4. Bicycle contribution extension update

Bicycle contribution (Ziemke et al, (2019))

Extension of the agent-based transport simulation framework MATSim for bicycle traffic.

- ~~Road comfort (OSM) (surface, highway, smoothness)~~
- ~~Road infrastructure type (OSM) (highway)~~
- Road gradient (DEM)
- Road quietness (Cyclestreets)

Marginal utility of quietness

$$\beta_{quietness\ (a)} = \beta^{max\ quietness\ (a)} \cdot (1 - quietness\ (a))$$

Ziemke, Dominik, Simon Metzler, and Kai Nagel. "Bicycle traffic and its interaction with motorized traffic in an agent-based transport simulation framework." Future Generation Computer Systems 97 (2019): 30-40. https://doi.org/10.1016/j.future.2018.11.005

5. MATSim simulation



5. MATSim simulation. Calibration

Parameter	Values
Population sample	20%
Number of iterations	1,500
Controler	Qsim
Modes	car, car passenger, bike, walk, PT (bus. rail, metro, ferry)
Car use	Only by those with access to car: considerCarAvailability (true)
PT	Deterministic, SwissRailRaptor, SBBPt, useCapacityConstraints (false), access and egress (walk)
Bicycle extension	Marginal utility of comfort (0.0), infrastructure (0.0), gradient (-0.02), quietness (-0.035)
Strategies	80%, ReRoute (0.1), TimeAllocationMutator (0.1), SubtourModeChoice (0.1), ChangeExpBeta (0.7)
ASC	Car: -0.37 Car_passenger: -1.7 Bike: -1.1 Walk: 0.0 Bus: -7.2 Rail: -0.001 Subway: -0.001 Ferry: -0.001

5. MATSim simulation. Validation results

% of transport modes used



% of transport modes used (commuting only)



% of transport modes used (school trip only)



5. MATSim simulation. Validation results

Average trip time (min) per transport mode



Average trip distance (km) per transport mode



5. MATSim simulation. Validation results









5. MATSim simulation. Validation results



1



3







2





4

6. Full PhD project methodology



7. Tailored “stick” and “carrot” scenarios

The phrase “**stick and carrot**" is a metaphor for the use of a combination of reward and punishment to induce a desired behaviour (Wikipedia).

Image taken from Wikipedia https://en.wikipedia.org/wiki/Carrot_and_stick

7. Tailored “stick” and “carrot” scenarios

Preliminarily results

1. Ultimate cycle network scenario

Carrot scenario:

Duplicated network only allowed for bikes

Quietness = 1.0 (fully safe and segregated cycle paths)

Transport mode	Change
Car (all)	- 0.52 %
PT	+ 0.37%
Walk	- 0.59%
Bike	+ 0.74%

Engineering and Physical Sciences Research Council

7. Tailored “stick” and “carrot” scenarios

Preliminarily results

1. Ultimate cycle network scenario

Carrot scenario:

Duplicated network only allowed for bikes

Quietness = 1.0 (fully safe and segregated cycle paths)

Stick + carrot scenario:

Carrot scenario

+

Flow capacity reduced proportionally (no. of lanes) to transfer road car space to cycle paths

Transport mode	Change
Car (all)	- 0.52 %
PT	+ 0.37%
Walk	- 0.59%
Bike	+ 0.74%

Transport mode	Change
Car (all)	- 1.94%
PT	+ 1.21%
Walk	- 0.32%
Bike	+ 1.06%

Engineering and Physical Sciences Research Council

7. Tailored “stick” and “carrot” scenarios

Preliminarily results

2. Low Traffic Neighbourhoods scenario

Stick scenario:

Cars only allowed in motorway, trunk, primary, secondary and tertiary links (red links in the image)

Quietness = 1.0 (fully safe and segregated cycle paths) in the other links

Transport mode	Change
Car (all)	- 3.24%
PT	+ 2.95%
Walk	+ 0.98%
Bike	- 0.7%

7. Tailored “stick” and “carrot” scenarios

Preliminarily results

Stick scenario:

Car users (drivers and passengers) **pay a daily penalty**

£10

3. Pay as you drive scenario

Transport mode	Change
Car (all)	- 8.9%
PT	+ 5.5%
Walk	+ 1.89%
Bike	+ 1.51%

7. Tailored “stick” and “carrot” scenarios

Preliminarily results

Stick scenario:

Car users (drivers and passengers) **pay a daily penalty**

£10

Stick scenario:

Car users (drivers and passengers) **receive a monetary penalty per km driven.**

£0.50 per km

3. Pay as you drive scenario

Transport mode	Change
Car (all)	- 8.9%
PT	+ 5.5%
Walk	+ 1.89%
Bike	+ 1.51%

Transport mode	Change
Car (all)	- 6.43%
PT	+ 4.72%
Walk	+ 0.6%
Bike	+ 1.0%

7. Tailored “stick” and “carrot” scenarios

Work in progress

4. Active travel reward scenario

<u>Carrot scenario:</u>

Active travel users receive a **monetary reward** per km walked/cycled

£0.50 per km
£0.20 per km

Engineering and Physical Sciences Research Council

7. Tailored “stick” and “carrot” scenarios

Work in progress

5. Cycle Hubs scenario (PT + AT)

Carrot scenario:

Cyclist are allowed to access and egress metro stations.

New cycle hubs set up next to metro stations.

Agents can leave the bicycles in a secure and safety place

7. Tailored “stick” and “carrot” scenarios

Work in progress

Global stick and carrot scenario:

Combination of previous single policies to enable the agents to use more active travel modes instead of private motor vehicles

Suggestions and comments
to improve the model and scenarios are
very welcome!

Thank you
for your attention

University of Nottingham
UK | CHINA | MALAYSIA

Newcastle University

GEOSPATIAL SYSTEMS
CENTRE FOR DOCTORAL TRAINING

UKRI Engineering and Physical Sciences Research Council

A MATSim model for a low carbon future mobility in the UK context

David Alvarez Castro

/DACNC/ /d-alv/ d.alvarez2@newcastle.ac.uk @David_AlvCas

UKRI EPSRC

Supervisory team

Alistair Ford
Philip James
Roberto Palacín
Dominik Ziemke