




























slb		Client Job Objective	BHA Name Category GeoUnit		Comments		Unit	in		m	psi degF lbs	
Diagram	Asset	Features Specifications Comments	Description	OD (in)	Length (m)	Cumulated Length (m)	Dist. Point From Bot. BHA (m)	Weight (lbs)	Pressure Rating (psi)	Temperature Rating (°F)	Compression Rating (lbs)	Tension Rating (lbs)
	PEH-SAA		Cable Head	2,125	0.45	26.75		9.0	20 000	350	20 000	25 000
	SAH-SAA		Swivel	2,125	0.56	26.30		11.0	20 000	350	20 000	25 000
	TTSA-SAA		Tension Compression Sub	2,125	0.29	25.75		11.3	25 000	350	20 000	25 000
	WIRED-SAA w/ AH-357	Release on command and timer w/ battery, Battery: 320F FN: 2 in GS	Release Device	2,125	1.12	25.46		27.0	20 000	350	25 000	25 000
	SPTEC-AA		Telemetry Cartridge	2,125	1.01	24.34		24.0	20 000	350	20 000	25 000
	SPEPC-AA		Power Cartridge	2,125	1.55	23.33		36.8	20 000	350	20 000	25 000
	SPHYS-BA		Tractor Hydraulic Module	2,125	0.63	21.78		24.0	20 000	350	20 000	25 000
	SPDRS-BA	Tractor force: 225 lb/drive Opening range: 2.25 in to 10.5 in Max speed: 5,000 f/hr	Tractor Drive Section	2,125	1.06	21.15	20.17	33.0	20 000	350	20 000	25 000
	SPDRS-BA	Tractor force: 225 lb/drive Opening range: 2.25 in to 10.5 in Max speed: 5,000 f/hr	Tractor Drive Section	2,125	1.06	20.08	19.11	33.0	20 000	350	20 000	25 000
	SPCPS-BA		Tractor Compensator	2,125	0.90	19.02		24.0	28 500	350	20 000	25 000
	SPDRS-BA	Tractor force: 225 lb/drive Opening range: 2.25 in to 10.5 in Max speed: 5,000 f/hr	Tractor Drive Section	2,125	1.06	18.12	17.15	33.0	20 000	350	20 000	25 000
	SPDRS-BA	Tractor force: 225 lb/drive Opening range: 2.25 in to 10.5 in Max speed: 5,000 f/hr	Tractor Drive Section	2,125	1.06	17.06	16.08	33.0	20 000	350	20 000	25 000
	AH-343		Hydraulic Termination	2,125	0.45	16.00		10.0	20 000	350	20 000	25 000
	SPCCL-AA	CCL 1.97 ft from top P&T	CCL P&T	2,125	0.82	15.55	14.95	21.5	20 000	350	20 000	25 000
	WIRED-SAA w/ AH-357	Release on command and timer w/ battery, Battery: 320F FN: 2 in GS	Release Device	2,125	1.12	14.73		27.0	20 000	350	25 000	25 000
	SPPAC-AA		PSP Adapter Cartridge	2,125	0.77	13.62		20.0	15 000	350	20 000	25 000
	AH-392		Adapter 1-11/16 in 22 pins male to 3-1/8 in	3,125	0.18	12.85		6.8	20 000	350	15 000	15 000
	MSPC-CB	P&T	Power Cartridge	3,125	1.12	12.67		85.0	20 000	300	40 000	60 000
	MSPY-BA		Hydraulic Module & Compensator	3,125	2.18	11.55		121.0	30 000	350	40 000	60 000
	MSPA-BA	Opening range: 3.125 to 5.1 in	Anchor Module	3,125	1.86	9.37	9.05	125.0	30 000	300	40 000	60 000
	MSPLT-AA	Length retracted 7.2 ft 20 in stroke 40k lb push pull Thru wire linear actuator	Linear Actuator Module	3,125	2.70	7.51		115.0	30 000	300	40 000	60 000
	MSPST-AA	Opening range: 3.125 to 5.1 in	Shifter Module	3,125	1.69	4.81	3.53	62.0	30 000	300	40 000	60 000
	AH-435		Thru Wire Hydraulic Termination - 3-1/8 24	3,125	0.33	3.12		20.0	30 000	300	40 000	60 000
	AH-326		Adapter 3-1/8 in 24 sockets male to 1-11/16	3,125	0.24	2.80		10.4	20 000	350	1 000	15 000
	PTCA-A		PSP Telemetry Conversion Adapter	1,688	0.94	2.55		20.0	15 000	300	1 000	10 000
	MFC-24J-S	GoWell	24 fingers GoWell Multifinger Caliper	1,889	1.57	1.61		52.2	15 000	300	1 000	10 000
	BNS-P		PSP Bottom Nose	1,688	0.04	0.04		5.0	20 000	350	10 000	10 000
27 Assets				3,125	26.75			1 000	15 000	300	1 000	10 000