Department of Electronic and Telecommunication Engineering University of Moratuwa, Sri Lanka

EN 2053 - Communication Systems and Networks



Assignment on Wireless Communication

Submitted by

Thalagala B.P. 180631J

Submitted on

September 3, 2020

Contents

1	Mo	odeling the RF propagation Model Using Matlab		
	1.1	Relationship between Free Space Path Loss and Frequency		2
	1.2	2 Rain attenuation, Fog attenuation and Atmospheric gas attenuation with Frequenc		3
		1.2.1 I	Rain attenuation - Recommendation ITU-R P.838-3, 2005	3
		1.2.2 I	Fog attenuation - Recommendation ITU-R P.840-3, 2013	4
		1.2.3	Atmospheric gas attenuation - Recommendation ITU-R P.676-10, 2013	4
	1.3	Total Pa	ath Loss with Frequency	5
	1 4	Codes a	nd Models for Task 1	6

1 Modeling the RF propagation Model Using Matlab

1.1 Relationship between Free Space Path Loss and Frequency

Consider following meanings for the parameters

 P_{RX} = Received Power at the Receiving Antenna

 P_{TX} = Transmitted Power at the Transmitting Antenna

f = Frequency of the wave in Hz f_{GHz} = Frequency of the wave in GHz d = Distance between the antennas in m d_{km} = Distance between the antennas in km G_{TX} = Directive gain of the Transmitter

 G_{RX} = Directive gain of the Receiver c = Velocity of the electromagnetic waves in a vacuum

The relationship between above parameters can be given as follows

$$P_{RX} = P_{TX} \cdot \frac{c^2}{(4\pi \cdot f \cdot d)^2} \cdot G_{TX} \cdot G_{RX}$$

From the above equation, free space path loss, say L

$$L = \frac{(4\pi \cdot f \cdot d)^2}{c^2}$$

By considering $10.log_{10}()$ in both sides, Free Space Path Loss in dB, say L_{dB}

$$\begin{split} \log_{10}(L) &= 10.\log_{10}(\frac{(4\pi.f.d)^2}{c^2}) \\ L_{dB} &= 10.\log_{10}((4\pi.f.d)^2) - 10.\log_{10}(c^2) \\ &= 20.\log_{10}(4\pi.f.d) - 20.\log_{10}(c) \\ &= 20.\log_{10}(4\pi) - 20.\log_{10}(c) + 20.\log_{10}(f) + 20.\log_{10}(d) \\ &= 20.\log_{10}(\frac{4\pi}{c}) + 20.\log_{10}(f) + 20.\log_{10}(d) \\ &= -147.5522168 + 20.\log_{10}(f_{GHz}.10^9) + 20.\log_{10}(f_{GHz}) + 20.\log_{10}(10^3) + 20.\log_{10}(d_{km}.10^3) \\ &= -147.5522168 + 20.\log_{10}(10^9) + 20.\log_{10}(f_{GHz}) + 20.\log_{10}(10^3) + 20.\log_{10}(d_{km}) \\ &= -147.5522168 + 180 + 20.\log_{10}(f_{GHz}) + 60 + 20.\log_{10}(d_{km}) \\ &= -147.5522168 + 240 + 20.\log_{10}(f_{GHz}) + 20.\log_{10}(d_{km}) \\ &= -147.5522168 + 240 + 20.\log_{10}(f_{GHz}) + 20.\log_{10}(d_{km}) \\ &= +92.44778322 + 20.\log_{10}(f_{GHz}) + 20.\log_{10}(d_{km}) \end{split}$$

Since transmitter and receiver are located at distance of 10km apart, by substituting $d_{km} = 10$.

Free Space Path Loss in dB, L_{dB} as a function of frequency in Giga Hertz

$$L_{dB}(f_{GHz}) = +112.44778322 + 20.\log_{10}(f_{GHz})$$

Note: Axes of the following plots are given in the logarithmic scale and range of frequency was chosen from 10 GHz to 1000 GHz since some of the ITU-R models are only defined in that range.




Figure 1: Relationship between Free Space Path Loss and Frequency

1.2 Rain attenuation, Fog attenuation and Atmospheric gas attenuation with Frequency

Note: For the generation of following plots three of the Matlab built-in functions, namely rainpl(), gaspl(), fogpl() which are developed according to the ITU-R P Series recommendations were used and links for their documentations are given at the Reference section.

1.2.1 Rain attenuation - Recommendation ITU-R P.838-3, 2005

The following plot shows how losses due to rain varies with frequency. The plot assumes the followings in addition to the provided information in the Task 1.

Elevation angle of the propagation path = 0Polarization tilt angle of the signal = 0

In general, horizontal polarization represents the worse case for propagation loss due to rain.




Figure 2: Relationship between Rain attenuation and Frequency

1.2.2 Fog attenuation - Recommendation ITU-R P.840-3, 2013

The following plot shows how losses due to fog/cloud varies with frequency. The plot assumes the following provided information in the Task 1.

Ambient Temperature in Celsius = 31 Liquid Water Density in g/m^3 = 0.5




Figure 3: Relationship between Fog attenuation and Frequency

1.2.3 Atmospheric gas attenuation - Recommendation ITU-R P.676-10, 2013

The plot below shows how the propagation loss due to atmospheric gases varies with the frequency. The plot assumes the followings in addition to the provided information in the Task 1.

Dry air pressure in Pa = 101325Water Vapor Density in $g/m^3 = 30.4$




Figure 4: Relationship between Atmospheric gas attenuation and Frequency

1.3 Total Path Loss with Frequency




Figure 5: Relationship between Total Path Loss and Frequency




Figure 6: Relationship between Various Path Losses and Frequency

1.4 Codes and Models for Task 1

```
%% Initialization
2
   clear; close all; clc
  \%\% === Free Space Path Loss with Frequency ====
3
4
5
   %Defining the frequency range in GigaHertz
6 \mid f_{GHz} = 10:1000;
7
  %Free Space Path Loss Model obtained from calculations
8 | freeSpaceLoss = 112.44778322 + 20*log10(f_GHz);
9
10 | % Plotting Data
11 | figure;
12 loglog(f_GHz,freeSpaceLoss, 'LineWidth', 2);
13 grid on;
14 | xlabel('Frequency in GHz');
15 | ylabel('Free Space Path Loss in dB');
16 | title('Free Space Path Loss'); legend('FreeSpacePL');
17
18 | fprintf('Program paused. Press enter to continue.\n');
19
   pause;
20 %% ===
           Rain Attenuation with Frequency ====
21
22 | range = 10e3; % Distance between transmitter and receiver in m
23 | rainrate = 20; % Rain rate in mm/h
24 \mid \text{elev} = 0;
                  % Elevation angle of the propagation path
25 \mid tau = 0;
                  % Polarization tilt angle of the signal
26
27 | % Defining the frequency range in Hertz
28 | freq = f_GHz*1e9;
29 | % calculating Rain Attenuation
30 | rainAttenuation = rainpl(range, freq, rainrate, elev, tau);
31
32 % Plotting Data
33 | figure;
34 | loglog(f_GHz,rainAttenuation, 'LineWidth', 2);
35 \mid \texttt{grid} \ \texttt{on};
36 | xlabel('Frequency in GHz');
37 | ylabel('Rain Attenuation in dB')
38 | title('Rain Attenuation for Horizontal Polarization');
39 | legend('RainPL');
40
41 | fprintf('Program paused. Press enter to continue.\n');
42
   pause;
43
   | %% === Fog Attenuation with Frequency ====
44
45 | temp = 31; % Ambient Temperature in celcious
46 | dens = 0.5; % Liquid Water Density in g/m^3
47
48 | % calculating Fog Attenuation
49 | fogAttenuation = fogpl(range, freq, temp, dens);
50
51 | % Plotting Data
52 | figure;
53 | loglog(f_GHz, fogAttenuation, 'LineWidth', 2);
54 grid on;
```

```
55 | xlabel('Frequency in GHz');
56 | ylabel('Fog Attenuation in dB')
57 | title('Fog Attenuation'); legend('FogPL');
58
59 | fprintf('Program paused. Press enter to continue.\n');
   pause;
60
61
   %% ===
           Atmospheric Gases Attenuation with Frequency ====
62
63 \mid rou = 30.4;
                     % Water Vapor Density in g/m<sup>3</sup>
64 | p = 101325;
                    % Atmospheric Pressure in Pa at sea level
65
66 % calculating Fog Attenuation
67
   gasAttenuation = gaspl(range, freq, temp, p, rou);
68
69 | % Plotting Data
70 | figure;
71 | loglog(f_GHz,gasAttenuation, 'LineWidth', 2);
72 grid on;
73 | xlabel('Frequency in GHz');
74 | ylabel('Atmospheric Gases Attenuation in dB')
75 | title('Atmospheric Gases Attenuation'); legend('GasPL');
76
77
   fprintf('Program paused. Press enter to continue.\n');
78
   pause;
   \%\% ====== Total Path Loss with Frequency ======
79
80
81 % Calculating total Attenuation
82
   Totalpathloss = freeSpaceLoss + rainAttenuation + ...
83
                     fogAttenuation +gasAttenuation;
84
85 | % Plotting Data
86 figure;
87 | loglog(f_GHz, Totalpathloss, 'LineWidth', 2);
88 grid on;
89 | xlabel('Frequency in GHz');
90 | ylabel('Total Path Loss in dB')
91 | title('Total Path Loss'); legend('TotalPL')
92
93 | fprintf('Program paused. Press enter to continue.\n');
94
   pause;
95 \mid \%\% ===== To view all losses on the same figure =====
96
97
   figure;
   loglog(f_GHz,freeSpaceLoss, 'LineWidth', 2);
99
   hold on;
100 | loglog(f_GHz, rainAttenuation, 'LineWidth', 2);
   loglog(f_GHz,fogAttenuation, 'LineWidth', 2);
101
102 | loglog(f_GHz, gasAttenuation, 'LineWidth', 2);
103 loglog(f_GHz, Totalpathloss, 'LineWidth', 2);
104 grid on;
105 | xlabel('Frequency in GHz');
106 | ylabel('Path Loss in dB')
107 | title('Propagation Losses with Frequency')
108 | legend('FreeSpacePL', 'RainPL', 'GasPL', 'GasPL', 'TotalPL');
```