# EN4720: Security in Cyber-Physical Systems Exercise — Infrastructure Security

Name: Thalagala B. P. Index No: 180631J

June 18, 2023

This is an individual exercise!

Due Date: 20 June 2023 by 11.59 PM

This exercise has to be carried out using a Linux-based PC/virtual machine. Read all the instructions and questions before attempting the exercise. Add answers under each question and submit the resulting PDF.

## Section 1

In this section, you will implement Firewall rules using **iptables** and **ufw** Linux commands. Moreover, you will scan network ports of a remote device using **nmap** Linux command.

For all the questions in this section, add a screenshot of the terminal (including all the commands you ran to perform the task) unless specified otherwise. The evaluator should be able to see each step that you followed to perform each task. In all screenshots, the areas marked (which are unique to your terminal display) in Figure 1 (the sample answer to Question 1) must be visible.

1. View the currently logged in user.

```
bimalka98@LAP-BIMALKA98: ~/ex5 _ _ © S

bimalka98@LAP-BIMALKA98: ~/ex570x35

bimalka98@LAP-BIMALKA98: ~/ex5$ whoami

bimalka98

bimalka98@LAP-BIMALKA98: ~/ex5$ [
```

Figure 1: Currently logged-in user

#### Creating Firewall Rules with iptables

2. Use dpkg -1 | grep iptables command to check whether iptables is installed on your system. If it does not existing in your system, install it by running sudo apt-get install iptables.

```
bimalka98@LAP-BIMALKA98: ~/ex5

bimalka98@LAP-BIMALKA98: ~/ex570x35

bimalka98@LAP-BIMALKA98: ~/ex5$ dpkg -l | grep iptables

ii iptables

amd64 administration tools for packet filte

ring and NAT

bimalka98@LAP-BIMALKA98: ~/ex5$
```

Figure 2: Checking whether iptables is installed on the system

3. Check all available iptables rules in your system using the command /sbin/iptables -n -L .

```
bimalka98@LAP-BIMALKA98: ~/ex5
oimalka98@LAP-BIMALKA98:~/ex5$ iptables -n -L
atal: can't open lock file /run/xtables.lock: Permission denied
oimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -n -L
Chain INPUT (policy ACCEPT)
                                           destination
target
           prot opt source
Chain FORWARD (policy ACCEPT)
                                           destination
target
           prot opt source
Chain OUTPUT (policy ACCEPT)
target
           prot opt source
                                           destination
imalka98@LAP-BIMALKA98:~/ex5$
```

Figure 3: Checking all available iptables rules

4. Save all available iptables rules to a file named iptablesRule.v4 using iptables-save command.

```
bimalka98@LAP-BIMALKA98:-/ex5

bimalka98@LAP-BIMALKA98:-/ex570x35

bimalka98@LAP-BIMALKA98:-/ex570x35

bimalka98@LAP-BIMALKA98:-/ex5$ sudo iptables-save > iptablesRule.v4

bimalka98@LAP-BIMALKA98:-/ex5$ cat iptablesRule.v4

# Generated by iptables-save v1.8.4 on Fri Jun 16 23:27:10 2023

*filter
:INPUT ACCEPT [1315:659160]
:FORWARD ACCEPT [0:0]
:OUTPUT ACCEPT [1245:334577]

COMMIT

# Completed on Fri Jun 16 23:27:10 2023

bimalka98@LAP-BIMALKA98:-/ex5$
```

Figure 4: Saving all available iptables rules

5. Flush all the iptables rules that exist in your system and set a default policy to drop packets.

```
bimalka98@LAP-BIMALKA98: ~/ex5
 .malka98@LAP-BIMALKA98:~/ex5$ sudo iptables -F
oimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -P INPUT DROP
pimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -P FORWARD DROP
bimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -P OUTPUT DROP bimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -n -L
Chain INPUT (policy DROP)
            prot opt source
target
                                               destination
Chain FORWARD (policy DROP)
                                               destination
target
            prot opt source
Chain OUTPUT (policy DROP)
                                               destination
target
            prot opt source
oimalka98@LAP-BIMALKA98:~/ex5$
```

Figure 5: Flushing all the rules and setting a default policy to drop packets

6. Set iptables rules to permit input and output DNS traffic in your system.

```
imalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -A INPUT -p udp --dport 53 -j ACCEPT
imalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -A OUTPUT -p udp --dport 53 -j ACCEPT
imalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -n -L
Chain INPUT (policy DROP)
               prot opt source
                                                          destination
ACCEPT
               udp
                      -- 0.0.0.0/0
                                                          0.0.0.0/0
                                                                                        udp dpt:53
Chain FORWARD (policy DROP)
target
              prot opt source
                                                          destination
Chain OUTPUT (policy DROP)
              prot opt source
udp -- 0.0.0.0/0
                                                          destination
                                                          0.0.0.0/0
                                                                                         udp dpt:53
 imalka98@LAP-BIMALKA98:~/ex5$
```

Figure 6: Permitting input and output DNS traffic

7. Add iptables rules to accept local network incoming and outgoing traffic from the network 192.168.1.0/24.

```
bimalka98@LAP-BIMALKA98: ~/ex5
                                                                                       _ 0 😵
                                       |ka98@| ΔP-RIMΔ| KΔ98: ~/ey5 75y35
  malka98@LAP-BIMALKA98:~/ex5$ ifconfig
enp4s0: flags=4099<UP,BROADCAST,MULTICAST> mtu 1500
ether 2c:fd:a1:2c:4e:fb txqueuelen 1000 (Ethernet)
RX packets 0 bytes 0 (0.0 B)
         RX errors 0 dropped 0 overruns 0 frame 0 TX packets 0 bytes 0 (0.0 B)
         TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
enx0c5b8f279a64: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
         ether 0c:5b:8f:27:9a:64 txqueuelen 1000
                                                              (Ethernet)
         RX packets 1888 bytes 625794 (625.7 KB)
         RX errors 1321 dropped 0 overruns 0 frame 1321 TX packets 0 bytes 0 (0.0 B)
         TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
         inet 127.0.0.1 netmask 255.0.0.0
inet6 ::1 prefixlen 128 scopeid 0x10<host>
         loop txqueuelen 1000 (Local Loopback)
         RX packets 5113 bytes 544815 (544.8 KB)
         RX errors 0 dropped 0 overruns 0 frame 0
         TX packets 5113 bytes 544815 (544.8 KB)
         TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
wlp3s0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
         inet 192.168.8.102 netmask 255.255.255.0 broadcast 192.168.8.255
         inet6 fe80::f2c8:9c8/:6f2a:2d/1 prefixlen 64 scopeid 0x20<link>
ether 00:e1:8c:41:ce:1d txqueuelen 1000 (Ethernet)
         RX packets 221665 bytes 251795655 (251.7 MB)
         RX errors 0 dropped 0 overruns 0 frame 0
TX packets 120792 bytes 26998692 (26.9 MB)
TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
 imalka98@LAP-BIMALKA98:~/ex5$
```

Figure 7: Checking the CIDR of the current local network

```
bimalka98@LAP-BIMALKA98: ~/ex5
imalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -A INPUT -s 192.168.8.0/24 -j ACCEPT imalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -A OUTPUT -d 192.168.8.0/24 -j ACCEPT imalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -n -L
Chain INPUT (policy DROP)
target
ACCEPT
              prot opt source
udp -- 0.0.0.0/0
all -- 192.168.8.0/24
                                                             destination
                                                             0.0.0.0/0
0.0.0.0/0
                                                                                             udp dpt:53
ACCEPT
Chain FORWARD (policy DROP)
               prot opt source
                                                             destination
Chain OUTPUT (policy DROP)
target
               prot opt source
                                                             destination
                                                             0.0.0.0/0
192.168.8.0/24
                      -- 0.0.0.0/0
                                                                                             udp dpt:53
                       -- 0.0.0.0/0
imalka98@LAP-BIMALKA98:~/ex5$ 🗌
```

Figure 8: Adding rules to accept local network incoming and outgoing traffic

8. Configure iptables rules to allow all HTTP traffic.

```
pimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -A INPUT -p tcp --dport 80 -j ACCEPT rimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -A FORWARD -p tcp --dport 80 -j ACCEPT rimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -A OUTPUT -p tcp --dport 80 -j ACCEPT rimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -n -L
Chain INPUT (policy DROP)
target
               prot opt source
                                                              0.0.0.0/0
0.0.0.0/0
                       -- 0.0.0.0/0
                                                                                              udp dpt:53
                             192.168.8.0/24
ACCEPT
                                                              0.0.0.0/0
                                                                                              tcp dpt:80
                             0.0.0.0/0
Chain FORWARD (policy DROP)
                                                              destination
               prot opt source
                tcp -- 0.0.0.0/0
                                                              0.0.0.0/0
                                                                                               tcp dpt:80
Chain OUTPUT (policy DROP)
                                                              destination
target
ACCEPT
               prot opt source
                            0.0.0.0/0
                                                              0.0.0.0/0
192.168.8.0/24
                                                                                              udp dpt:53
                udp
ACCEPT
                       -- 0.0.0.0/0
                       -- 0.0.0.0/0
                                                              0.0.0.0/0
                                                                                              tcp dpt:80
ACCEPT
```

Figure 9: Configuring rules to allow all HTTP traffic

9. View all iptables rules in your system and save them to a file **iptablesRuleNew.v4**.

```
bimalka98@LAP-BIMALKA98: ~/ex5
                        MALKA98:~/ex5$ sudo iptables -n -L
Chain INPUT (policy DROP)
                                                             destination
arget
ACCEPT
               udp
all
                            0.0.0.0/0
192.168.8.0/24
                                                            0.0.0.0/0
0.0.0.0/0
                                                                                            udp dpt:53
ACCEPT
                            0.0.0.0/0
                                                             0.0.0.0/0
                                                                                            tcp dpt:80
ACCEPT
Chain FORWARD (policy DROP)
               prot opt source
tcp -- 0.0.0.0/0
                                                             destination
                                                             0.0.0.0/0
                                                                                             tcp dpt:80
Chain OUTPUT (policy DROP)
arget
               prot opt source
                                                             destination
               udp -- 0.0.0.0/0
all -- 0.0.0.0/0
 CCĔPT
                                                             0.0.0.0/0
                                                                                            udp dpt:53
                                                             192.168.8.0/24
                      -- 0.0.0.0/0
                                                             0.0.0.0/0
                                                                                            tcp dpt:80
 imalka98@LAP-BIMALKA98:-/ex5$ sudo iptables-save > iptablesRuleNew.v4
imalka98@LAP-BIMALKA98:~/ex5$ cat iptablesRuleNew.v4
 Generated by iptables-save v1.8.4 on Fri Jun 16 23:56:11 2023
*Tilter
:INPUT DROP [0:0]
:FORWARD DROP [0:0]
:OUTPUT DROP [715:100036]
-A INPUT -p udp -m udp --dport 53 -j ACCEPT
-A INPUT -s 192.168.8.0/24 -j ACCEPT
-A INPUT -p tcp -m tcp --dport 80 -j ACCEPT
  FORWARD -p tcp -m tcp --dport 80 -j ACCEPT
OUTPUT -p udp -m udp --dport 53 -j ACCEPT
OUTPUT -d 192.168.8.0/24 -j ACCEPT
A OUTPUT -p tcp -m tcp --dport 80 -j ACCEPT
 Completed on Fri Jun 16 23:56:11 2023
```

Figure 10: Viewing all rules and saving them to a file

10. Create a file called **iptablesCommands.sh** and put all commands you ran from steps 4, 5 and 6 in the file. After creating the file, flush your iptables commands again and run **iptablesCommands.sh** file. View the iptables rules now and compare with the previous result.

```
bimalka98@LAP-BIMALKA98: -/ex5

GNU nano 4.8 iptablesCommands.sh Modified

#!/bin/bash

# Flush all the iptables rules that exist in your system sudo iptables -F

# set a default policy to drop packets. sudo iptables -P INPUT DROP sudo iptables -P FORWARD DROP sudo iptables -P OUTPUT DROP

sudo iptables -P OUTPUT DROP

# Set iptables rules to permit input and output DNS traffic sudo iptables -A INPUT -p udp --dport 53 -j ACCEPT sudo iptables -A OUTPUT -p udp --dport 53 -j ACCEPT
```

Figure 11: Creating the shell script

```
bimalka98@LAP-BIMALKA98: ~/ex5
bimalka98@LAP-BIMALKA98:~/ex5$ nano iptablesCommands.sh
bimalka98@LAP-BIMALKA98:~/ex5$ ls -lh
-rw-rw-r-- 1 bimalka98 bimalka98 379 ජි
                                              17 00:12 iptablesCommands.sh
                                    482 ජූති
198 ජූති
rw-rw-r-- 1 bimalka98 bimalka98
                                              16 23:56 iptablesRuleNew.v4
                                              16 23:27 iptablesRuleOld.v4
rw-rw-r-- 1 bimalka98 bimalka98
                                    198 පිනි
rw-rw-r-- 1 bimalka98 bimalka98
                                              16 23:27 iptablesRule.v4
drwxrwxr-x 2 bimalka98 bimalka98 4.0K 🥸
                                              16 23:55 screenshots
bimalka98@LAP-BIMALKA98:~/ex5$ chmod +x iptablesCommands.sh
bimalka98@LAP-BIMALKA98:~/ex5$ ls -lh
total 20K
                                    379 ජූති
482 ජූති
198 ජූති
-rwxrwxr-x 1 bimalka98 bimalka98
                                              17 00:12 iptablesCommands.sh
                                              16 23:56 iptablesRuleNew.v4
16 23:27 iptablesRuleOld.v4
rw-rw-r-- 1 bimalka98 bimalka98
rw-rw-r-- 1 bimalka98 bimalka98
                                    198 ජූති
-rw-rw-r-- 1 bimalka98 bimalka98
                                              16 23:27 iptablesRule.v4
drwxrwxr-x 2 bimalka98 bimalka98 4.0K 萎わ
                                              16 23:55 screenshots
oimalka98@LAP-BIMALKA98:~/ex5$ cat iptablesCommands.sh
#!/bin/bash
# Flush all the iptables rules that exist in your system
sudo iptables -F
# set a default policy to drop packets.
sudo iptables -P INPUT DROP
sudo iptables -P FORWARD DROP
sudo iptables -P OUTPUT DROP
# Set iptables rules to permit input and output DNS traffic
sudo iptables -A INPUT -p udp --dport 53 -j ACCEPT
sudo iptables -A OUTPUT -p udp _-dport 53 -j ACCEPT
bimalka98@LAP-BIMALKA98:~/ex5$
```

Figure 12: Making the script executable

11. Finally, flush your iptables rules again. But this time, load the saved iptables rules from the file **iptablesRuleNew.v4** using **iptables-restore** command. View the iptables rules and compare them with the ones you have in step 8.

```
bimalka98@LAP-BIMALKA98: ~/ex5
                                                                           _ 0 🛚
oimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -n -L
[sudo] password for bimalka98:
Chain INPUT (policy DROP)
           prot opt source
                                           destination
target
           udp -- 0.0.0.0/0
all -- 192.168.8.0/24
ACCEPT
                                           0.0.0.0/0
                                                                  udp dpt:53
ACCEPT
                                           0.0.0.0/0
ACCEPT
           tcp -- 0.0.0.0/0
                                           0.0.0.0/0
                                                                  tcp dpt:80
Chain FORWARD (policy DROP)
           prot opt source
                                            destination
target
           tcp -- 0.0.0.0/0
ACCEPT
                                            0.0.0.0/0
                                                                  tcp dpt:80
Chain OUTPUT (policy DROP)
                                           destination
target
           prot opt source
ACCEPT
                                           0.0.0.0/0
           udp -- 0.0.0.0/0
                                                                  udp dpt:53
           all -- 0.0.0.0/0
ACCEPT
                                            192.168.8.0/24
ACCEPT tcp -- 0.0.0.0/0 0.0.0.0/0 pimalka98@LAP-BIMALKA98:~/ex5$ ./iptablesCommands.sh
ACCEPT
                                                                  tcp dpt:80
bimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -n -L
Chain INPUT (policy DROP)
                                            destination
           prot opt source
target
           udp -- 0.0.0.0/0
ACCEPT
                                            0.0.0.0/0
                                                                  udp dpt:53
Chain FORWARD (policy DROP)
target
           prot opt source
                                            destination
Chain OUTPUT (policy DROP)
                                            destination
target
           prot opt source
ACCEPT
           udp -- 0.0.0.0/0
                                            0.0.0.0/0
                                                                  udp dpt:53
oimalka98@LAP-BIMALKA98:~/ex5$
```

Figure 13: Executing the shell script

```
bimalka98@LAP-BIMALKA98: ~/ex5
oimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -n -L
Chain INPUT (policy DROP)
           prot opt source
                                              destination
target
ACCEPT
           udp -- 0.0.0.0/0
                                              0.0.0.0/0
                                                                     udp dpt:53
Chain FORWARD (policy DROP)
           prot opt source
                                              destination
Chain OUTPUT (policy DROP)
           prot opt source
                                              destination
target
ACCĒPT udp -- 0.0.0.0/0 0.0.0.
bimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -F
                                                                     udp dpt:53
ACCEPT
                                              0.0.0.0/0
oimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables-restore < iptablesRuleNew.v4
oimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -n -L
Chain INPUT (policy DROP)
target
           prot opt source
                                              destination
           udp -- 0.0.0.0/0
all -- 192.168.8.0/24
ACCEPT
                                              0.0.0.0/0
                                                                     udp dpt:53
ACCEPT
                                              0.0.0.0/0
ACCEPT
           tcp -- 0.0.0.0/0
                                              0.0.0.0/0
                                                                     tcp dpt:80
Chain FORWARD (policy DROP)
target
           prot opt source
                                              destination
ACCEPT
           tcp -- 0.0.0.0/0
                                              0.0.0.0/0
                                                                      tcp dpt:80
Chain OUTPUT (policy DROP)
           prot opt source
                                              destination
target
           udp -- 0.0.0.0/0
all -- 0.0.0.0/0
\Delta CCFPT
                                              0.0.0.0/0
                                                                     udp dpt:53
ACCEPT
                                              192.168.8.0/24
ACCEPT
ACCEPT tcp -- 0.0.0.0/0
pimalka98@LAP-BIMALKA98:~/ex5$ |
                                              0.0.0.0/0
                                                                      tcp dpt:80
```

Figure 14: Flushing current rules and restoring saved rules

#### Creating Firewall Rules with UFW

The scenario comprises of two virtual machines (VM1 IP - 192.168.46.140 and VM2 IP - 192.168.46.141) running on a host (HOST IP - 192.168.46.1) machine. VM1 is an Ubuntu virtual machine that has a firewall implemented/configured.

The current firewall ruleset is as below.

```
Chain INPUT (policy DROP)
target prot opt source destination

Chain FORWARD (policy DROP)
target prot opt source destination

Chain OUTPUT (policy DROP)
target prot opt source destination
```

All chain policies are set to drop traffic. To implement base rules, you can use the following commands:

- Delete any current rules associated with UFW using sudo ufw reset
- Disable UFW using sudo ufw disable
- Flush all iptables rules using sudo iptables -F
- Enable UFW using sudo ufw enable
- Deny outgoing traffic using sudo ufw default deny outgoing
- 12. Implement the following network administration in VM1:
  - Access to VM1 from VM2 must only be allowed over FTP and Telnet.
  - Access to VM1 from HOST must only be allowed over SSH
  - Allow all outgoing traffic from VM1 with the exception of access to HTTP websites

In this task, you are asked to implement UFW rules on the ubuntu machine. You can pretend that VM2 and HOST exist in your network. List the commands you used to achieve the above. Add a screenshot of the terminal output after running the command sudo ufw status numbered.

If the firewall is physically implemented, you could have tested the connections using PuTTY or the command line.

```
bimalka98@LAP-BIMALKA98: ~/ex5
                           bimalka98@LAP-BIMALKA98: ~/ex5 7
 imalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -n -L
Chain INPUT (policy ACCEPT)
target
           prot opt source
                                            destination
Chain FORWARD (policy ACCEPT)
                                            destination
target
           prot opt source
Chain OUTPUT (policy ACCEPT)
target
           prot opt source
                                            destination
pimalka98@LAP-BIMALKA98:~/ex5$ sudo ufw status numbered
Status: inactive
oimalka98@LAP-BIMALKA98:~/ex5$
```

Figure 15: Current firewall rules

```
bimalka98@LAP-BIMALKA98:~/ex5

bimalka98@LAP-BIMALKA98:~/ex5

bimalka98@LAP-BIMALKA98:~/ex5

bimalka98@LAP-BIMALKA98:~/ex5

bimalka98@LAP-BIMALKA98:~/ex5

bimalka98@LAP-BIMALKA98:~/ex5

Resetting all rules to installed defaults. Proceed with operation (y|n)? y

Backing up 'user.rules' to '/etc/ufw/user.rules.20230617_233502'

Backing up 'after.rules' to '/etc/ufw/before.rules.20230617_233502'

Backing up 'user6.rules' to '/etc/ufw/user6.rules.20230617_233502'

Backing up 'before6.rules' to '/etc/ufw/before6.rules.20230617_233502'

Backing up 'after6.rules' to '/etc/ufw/after6.rules.20230617_233502'

bimalka98@LAP-BIMALKA98:~/ex5$ sudo ufw disable

Firewall stopped and disabled on system startup

bimalka98@LAP-BIMALKA98:~/ex5$ sudo iptables -F

bimalka98@LAP-BIMALKA98:~/ex5$ sudo ufw enable

Firewall is active and enabled on system startup

bimalka98@LAP-BIMALKA98:~/ex5$ sudo ufw default deny outgoing

Default outgoing policy changed to 'deny'
(be sure to update your rules accordingly)

bimalka98@LAP-BIMALKA98:~/ex5$
```

Figure 16: Implementing the base rules

```
8:~/ex5$ sudo iptables -n -L
bimalka98@LAP-BIMALKA98:-/ex5$ sudo iptables -
Chain INPUT (policy DROP)
target prot opt source desti
ufw-before-logging-input all -- 0.0.0.0/0
ufw-before-input all -- 0.0.0.0/0
ufw-after-input all -- 0.0.0.0/0
ufw-after-logging-input all -- 0.0.0.0/0
ufw-reject-input all -- 0.0.0.0/0
ufw-reject-input all -- 0.0.0.0/0
                                                                                             destination
                                                                                                                               0.0.0.0/0
                                                                                                            0.0.0.0/0
                                                                                                           0.0.0.0/0 0.0.0.0/0
                                                                                                            0.0.0.0/0
Chain FORWARD (policy DROP)
chain Furward (policy DROP)
target prot opt source desting
ufw-before-logging-forward all -- 0.0.0.0/0
ufw-before-forward all -- 0.0.0.0/0
ufw-after-forward all -- 0.0.0.0/0
ufw-after-logging-forward all -- 0.0.0.0/0
ufw-reject-forward all -- 0.0.0.0/0
ufw-track-forward all -- 0.0.0.0/0
                                                                                             destination
                                                                                                                                    0.0.0.0/0
                                                                                                               0.0.0.0/0
                                                                                                               0.0.0.0/0
 Chain OUTPUT (policy DROP)
target prot opt source desti
ufw-before-logging-output all -- 0.0.0.0/0
ufw-before-output all -- 0.0.0.0/0
ufw-after-output all -- 0.0.0.0/0
                                                                                             destination
                                                                                                                                 0.0.0.0/0
                                                                                                               0.0.0.0/0
                                                                                                             0.0.0.0/0
ufw-after-logging-output all -- 0.0.0.0/0
ufw-reject-output all -- 0.0.0.0/0
ufw-track-output all -- 0.0.0.0/0
                                                                                                             0.0.0.0/0
0.0.0.0/0
0.0.0.0/0
 Chain ufw-after-forward (1 references)
target
                                                                                             destination
target prot opt source dest
ufw-skip-to-policy-input udp -- 0.0.0.0/0
ufw-skip-to-policy-input udp -- 0.0.0.0/0
                                                                                             destination
                                                                                                                                                                                udp dpt:137
udp dpt:138
                                                                                                                                0.0.0.0/0
                                                                                                                                0.0.0.0/0
```

Figure 17: iptables after setting up the base rules

Following network administration in VM1 is configured using the associated commands given below.

- Access to VM1 from VM2 must only be allowed over FTP and Telnet sudo ufw allow in from 192.168.46.141 to any port 21 proto tcp sudo ufw allow in from 192.168.46.141 to any port 23 proto tcp
- Access to VM1 from HOST must only be allowed over SSH sudo ufw allow in from 192.168.46.1 to any port 22 proto tcp
- Allow all outgoing traffic from VM1 with the exception of access to HTTP websites sudo ufw default allow outgoing sudo ufw deny out to any port 80 proto tcp

```
ex5$ sudo ufw allow in from 192.168.46.141 to any port 21 proto
Rule added
 malka980LAP-BIMALKA98:~/ex5$ sudo ufw allow in from 192.168.46.141 to any port 23 proto tco
Rule added
           QLAP-BIMALKA98:~/ex5$ sudo ufw allow in from 192.168.46.1 to any port 22 proto tcp
Rule added

pimalka98@LAP-BIMALKA98:~/ex5$ sudo ufw default allow outgoing

Default outgoing policy changed to 'allow'

(be sure to update your rules accordingly)

pimalka98@LAP-BIMALKA98:~/ex5$ sudo ufw deny out to any port 80 proto tcp
Rule added (v6)
pimalka980LAP-BIMALKA98:~/ex5$ sudo ufw status numbered
Status: active
                                         ALLOW IN
                                                         192.168.46.141
     21/tcp
                                         ALLOW IN
                                                          192.168.46.141
     22/tcp
                                         ALLOW IN
                                                          192.168.46.1
                                         DENY OUT
                                                          Anywhere
     80/tcp (v6)
                                         DENY OUT
                                                         Anywhere (v6)
                                                                                              (out)
  malka98@LAP-BIMALKA98:~/ex5$
```

Figure 18: Output after running the command sudo ufw status numbered

```
398@LAP-BIMALKA98:~/ex5$ sudo iptables -n -L
    hain INPUT (policy DROP)
thath Invol (potty) body)
target prot opt source dest
ufw-before-logging-input all -- 0.0.0.0/0
ufw-before-input all -- 0.0.0.0/0
ufw-after-input all -- 0.0.0.0/0
ufw-after-logging-input all -- 0.0.0.0/0
ufw-reject-input all -- 0.0.0.0/0
ufw-track-input all -- 0.0.0.0/0
                                                                                                                                                                                                                  destination
                                                                                                                                                                                                                                                                                                 0.0.0.0/0
                                                                                                                                                                                                                                                        0.0.0.0/0
                                                                                                                                                                                                                                                  0.0.0.0/0
                                                                                                                                                                                                                                                                                         0.0.0.0/0
                                                                                                                                                                                                                                                        0.0.0.0/0
                                                                                                                                                                                                                                                  0.0.0.0/0
  Chain FORWARD (policy DROP)
thath roward (pottey boor)
target prot opt source destin
ufw-before-logging-forward all -- 0.0.0.0/0
ufw-before-forward all -- 0.0.0.0/0
ufw-after-forward all -- 0.0.0.0/0
ufw-after-logging-forward all -- 0.0.0.0/0
ufw-reject-forward all -- 0.0.0.0/0
ufw-track-forward all -- 0.0.0.0/0
                                                                                                                                                                                                                  destination
                                                                                                                                                                                                                                                                                                           0.0.0.0/0
                                                                                                                                                                                                                                                                  0.0.0.0/0
                                                                                                                                                                                                                                                           0.0.0.0/0
                                                                                                                                                                                                                                                                  0.0.0.0/0
                                                                                                                                                                                                                                                             0.0.0.0/0
  Chain OUTPUT (policy ACCEPT)
 target prot opt source desti
ufw-before-logging-output all -- 0.0.0.0/0
                                                                                                                                                                                                                  destination
                                                                                                                                                                                                                                                                                                       0.0.0.0/0
  of the fore-output all -- 0.0.0.0/0 of the original origi
                                                                                                                                                                                                                                                             0.0.0.0/0
                                                                                                                                                                                                                                                         0.0.0.0/0
   fw-after-logging-output
                                                                                                                                                                                                                                                                                                0.0.0.0/0
                                                                                                                                            0.0.0.0/0
                                                                                                                                                                                                                                                            0.0.0.0/0
   fw-reject-output all --
    fw-track-output
                                                                                                                                         0.0.0.0/0
```

Figure 19: iptables ruleset after mentioned configurations

```
prot opt source
tcp -- 192.168.46.141
tcp -- 192.168.46.141
                                                  destination
                                                 0.0.0.0/0
0.0.0.0/0
                                                                           tcp dpt:23
                       192.168.46.1
                                                 0.0.0.0/0
                                                                           tcp dpt:22
Chain ufw-user-limit (0 references)
                                                  destination
            prot opt source all -- 0.0.0.0/0
                                                                           limit: avg 3/min burst 5 LOG
                                                 0.0.0.0/0
          level 4 prefix "[UFW LIMIT BLOCK]
all -- 0.0.0.0/0 0
                                                  0.0.0.0/0
                                                                           reject-with icmp-port-unread
                                                  destination
             prot opt source all -- 0.0.0.0/0
                                                 0.0.0.0/0
Chain ufw-user-logging-forward (0 references)
target prot opt source destination
Chain ufw-user-logging-input (0 references)
arget
             prot opt source
                                                  destination
Chain ufw-user-logging-output (0 references)
                                                  destination
             prot opt source
Chain ufw-user-output (1 references)
                                                  destination
             prot opt source
                  -- 0.0.0.0/0
                                                 0.0.0.0/0
                                                                           tcp dpt:80
             tcp
```

Figure 20: Mentioned configurations in the iptables

#### Scan systems with NMAP

In this section, you will scan for the Ports of a remote host. You will need to have two devices connected to the same local network to perform this task.

13. View ip addresses of both devices using hostname -I command.

Your answer here

14. Scan one host from the other host for TCP and UDP ports using nmap command.

Your answer here

## Section 2

15. Briefly explain VLANs, VPNs, DMZs and Network Segmentation concepts outlining their similarities and differences.

Your answer here

16. Perform a comparison between IPsec and SSL.

Table 1: Comparison of IPsec and SSL

| IPsec            | SSL              |
|------------------|------------------|
| Your answer here | Your answer here |
| Your answer here | Your answer here |

17. Explain the differences between an IDS, an IPS, and a firewall?

### Your answer here

18. What is the difference between anomaly detection and signature or heuristic-based intrusion detection?

Your answer here