## **REC-CIS**

GE23131-Programming Using C-2024

Quiz navigation Show one page at a time Finish review

Question 1

Marked out of

Flag question

Correct

3.00

Input: 2 3

Status Finished

**Duration** 17 days 4 hours

Input format:

Started Monday, 23 December 2024, 5:33 PM

Write a program that prints a simple chessboard.

Completed Friday, 6 December 2024, 1:11 PM

The first line contains the number of inputs T. The lines after that contain a different values for size of the chessboard Output format: for black spaces.

Print a chessboard of dimensions size \* size. Print a Print W for white spaces and B

5 Output: **WBW BWB WBW WBWBW BWBWB WBWBW BWBWB WBWBW** 

**Answer:** (penalty regime: 0 %) #include<stdio.h> int main(){ int t ,size,i,j; 3 scanf("%d",&t); 4 5 while(t--){ scanf("%d",&size); 6 for(i=0;i<size;i++){</pre> 7 for(j=0;j<size;j++){</pre> 8  $if((i + j)\%2 == 0){$ 9 10 11 }else{ 12 13 14 printf("\n"); 15 16 17 18 return 0;

printf("W");

printf("B");

Got

WBW

BWB WBW

WBWBW

BWBWB

WBWBW

**BWBWB** 

WBWBW

19 Input Expected WBW BWB WBW WBWBW **BWBWB** WBWBW **BWBWB** WBWBW Passed all tests! Let's print a chessboard! Write a program that takes input: The first line contains T, the number of test cases

Question 2 Correct Marked out of 5.00 Flag question Each test case contains an integer N and also the starting character of the chessboard **Output Format** Print the chessboard as per the given examples Sample Input / Output

Input:

2

2 W

3 B

WB

BW

**BWB** 

**WBW** 

**BWB** 

4

5

6

7

8

9

10 11

12 13 14

15 16

Answer: (penalty regime: 0 %)

2 v int main(){

#include<stdio.h>

int T,N,i,j; char start;

while(T--){

return 0;

Input Expected Got

WB

BW

BWB WBW

BWB

WB

BW

BWB

WBW BWB

2 W

3 B

scanf("%d",&T);

scanf("%d %c",&N,&start);

 $for(j = 0; j < N; j++){$ 

printf("%c",(i+j)%2 == 0?start:(start == 'W'?'B':'

for  $(i = 0; i < N; i++){}$ 

printf("\n");

Output:

Question 3 Incorrect Marked out of

7.00

Flag question

> 102030405026027028029030 \*\*6070809022023024025 \*\*\*\*10011012019020021 \*\*\*\*\*13014017018 \*\*\*\*\*\*15016 **Answer:** (penalty regime: 0 %) 2 \* int main(){ 3 4 5 6 9 10

10203010011012 \*\*4050809 \*\*\*\*607 If N= 4, then pattern will be: 1020304017018019020 \*\*50607014015016 \*\*\*\*809012013 \*\*\*\*\*10011 Constraints 2 <= N <= 100

First line contains T, the number of test cases Each test case contains a single integer N Output First line print Case #i where i is the test case number In the subsequent line, print the pattern

Output 10203010011012 \*\*4050809 1020304017018019020 \*\*50607014015016 \*\*\*\*809012013 \*\*\*\*\*10011

scanf("%d",&t); for(ti = 0;ti<t;ti++){</pre> v =0; scanf("%d",&n); printf("case#%d\n") \_\_tester\_\_.c: In function 'main': \_\_tester\_\_.c:8:23: error: format '%d' expects a matching 'int' argument [-We printf("case#%d\n") int \_\_tester\_\_.c:8:28: error: expected ';' before '}' token printf("case#%d\n") \_\_tester\_\_.c:3:26: error: unused variable 'i2' [-Werror=unused-variable] 3 | int n,v,P3,c,in,i,i1,i2,t,ti; \_\_tester\_\_.c:3:23: error: unused variable 'i1' [-Werror=unused-variable] 3 | int n,v,P3,c,in,i,i1,i2,t,ti; \_\_tester\_\_.c:3:21: error: unused variable 'i' [-Werror=unused-variable] 3 | int n,v,P3,c,in,i,i1,i2,t,ti; \_\_tester\_\_.c:3:18: error: unused variable 'in' [-Werror=unused-variable]

Passed all tests! < Decode the logic and print the Pattern that corresponds to given input. If N= 3

then pattern will be:

Input Format

Test Case 1

Case #1 \*\*\*\*607 Case #2

#include<stdio.h>

Case #3

int n,v,P3,c,in,i,i1,i2,t,ti;

Syntax Error(s) 9 | } 3 | int n,v,P3,c,in,i,i1,i2,t,ti; \_\_tester\_\_.c:3:16: error: unused variable 'c' [-Werror=unused-variable]

3 | int n,v,P3,c,in,i,i1,i2,t,ti;

3 | int n,v,P3,c,in,i,i1,i2,t,ti;

3 | int n,v,P3,c,in,i,i1,i2,t,ti;

cc1: all warnings being treated as errors

\_\_tester\_\_.c:3:13: error: unused variable 'P3' [-Werror=unused-variable]

\_\_tester\_\_.c:3:11: error: variable 'v' set but not used [-Werror=unused-but-

Finish review