Table: agents

Column Name	Data Type	Definition	Business Meaning
agentid	integer (key)	A unique identifier for each individual agent.	A unique ID number that connects each agent to the booking they made in the engagements table.
agtfirstname	string	The agent's first name.	The agent's first name used to identify them.
agtlastname	string	The agent's last name.	The agent's last name used to identify them.
agtstreetaddress	string	The street of the agent's address.	The street on which the agent lives.
agtcity	string	The city of the agent's address.	The city in which the agent lives.
agtstate	string	The state of the agent's address.	The state in which the agent lives.
agtzipcode	integer	The zipcode of the agent's address.	The specific location of the agent.
agtphonenumber	string	The agent's phone number.	The agent's work phone number through which to contact them.
datehired	date	Year-Month-Day of the date the agent was hired.	The date the agent was hired to work for TuneWorks to track how long the agent has been working in the company.
salary	integer	The agent's salary (yearly pay).	The base amount of money the agent makes in a year.
commissionrate	integer (decimal)	A percentage in decimal form.	The percentage of the booking contract price that each agent receives for each

			engagement, earned on top of their salary amount.

Table: entertainer_members

Column Name	Data Type	Definition	Business Meaning
entertainerid	integer	A unique identifier referencing the entertainer record this member belongs to.	Connects a member to a specific entertainer.
memberid	integer	A unique identifier referencing the individual member record.	Identifies which member is associated with the entertainer.
status	smallinteger	A numeric code indicating the member's current status within the entertainer's group (1 = active, 2 = inactive)	Check whether the member is active or not.

Table: members

Column Name	Data Type	Definition	Business Meaning
memberid	integer	A unique identifier assigned to each individual member record.	Primary key for the members table.
mbrfirstname	String	Member's first name.	Used to identify the member.
mbrlastname	String	Member's last name.	Used to identify the member.
mbrphonenumber	String	Member's phone number.	Used to communicate with the member.
gender	String	Member's gender.	Allows demographic or diversity-based

			analysis.

Table: engagements

Column Name	Data Type	Definition	Business Meaning
engagementnumber	integer	A unique identifier assigned to each engagement record. Not necessarily sequential.	Each engagement has a distinct ID. Used as the primary key for this table.
startdate	date	The calendar date when an engagement begins.	Represents the start day of the booking.
starttime	time	The exact start time of the engagement on the start date.	Combined with startdate, it defines the precise start timestamp of an event.
stopdate	date	The calendar date when an engagement ends.	Represents the end day of the booking.
stoptime	time	The exact endtime of the engagement on the stop date	Combined with stopdate, it defines the precise end timestamp of an event.
contractprice	integer	The price for the engagement	The revenue earned from each engagement.
customerid	integer	A unique identifier assigned to each customer	Identifies the customer who booked the engagement. Foreign key to the customer table
agentid	integer	A unique identifier assigned to each agent	Identifies the responsible booking agent. Foreign key to the agents table
entertainerid	integer	A unique identifier	Identifies which

		assigned to each entertainer	performer was booked. Foreign key to the entertainers table

Table: customers

Column Name	Data Type	Definition	Business Meaning	relationships
customerid	integer(key)	A unique identifier assigned to each customer.	Each customer has a distinct ID. Used as the primary key for this table.	
custfirstname	string	Customer's first name.	The customer's first name used to identify them.	
custlastname	varchar	Customer's last name.	The customer's last name used to identify them.	
custstreetaddress	varchar	The street address for each customer.	The street on which the customer lives.	
custcity	varchar	The city of the customer's address.	The city in which the customer lives.	
custstate	varchar	The state of the agent's address.	The state in which the customer lives.	
custzipcode	varchar	The zip code of the agent's address.	The specific location of the customer.	
custphonenumber	varchar	The customer's phone number.	The customer's phone number through which to contact them.	

Table: entertainer_style

Column Name	Data Type	Definition	Business Meaning
entertainerid	integer	Unique identifier for each entertainer.	Links to the Entertainers table. Identifies which entertainer the style belongs to.
styleid	integer	Unique identifier for each performance style or genre.	Links to the musical_styles table. Indicates the type of performance.
stylestrength	integer	Numeric scale indicating how strongly the entertainer performs in this style (1–3).	Reflects entertainer's proficiency level or expertise in that style. Useful for customer matching.

Table: musical_styles

Column Name	Data Type	Definition	Business Meaning
styleid	integer	A unique numeric identifier assigned to each musical style record.	Serves as the primary key for this table and is referenced by entertainer_style. Distinguishes one musical style from another.
stylename	varchar	The name of the musical style or genre.	Represents the type of music that entertainers can perform and customers can request when booking.

Table: Musical Preferences

Column Name	Data Type	Definition	Business Meaning
Customerid	int	A unique numeric identifier is assigned to each client who wants to book entertainment	Links customers to this table to indicate their ranked preferences for entertainment styles.
Styleid	int	A unique numeric identifier that represents a genre from the music styles table	Shows the music styles that customers want most
Preferencesq	int	A numeric value of 1, 2, or 3 to rank the preferred styles of entertainment for each customer	Can be used by agents to manage entertainment bookings. In scenarios where double bookings can be an issue, ranked preferences can determine which customers value the entertainment more, while providing the agent with backup options.

Table: ztblSkipLable

Column Name	Data Type	Definition	Business Meaning
labelcount	integer	A simple numeric value that increases by 1 for each record.	Used by the systems to keep a running count or to label rows in order. This table does not store any customer, entertainer, or engagement info.

Table: ztblDays

Column Name	Data Type	Definition	Business Meaning

datefield	date	A single calendar date value for each row.	A list of consecutive dates used by the system for time calculations, testing, or joining with other tables when analyzing data by day.

Table: ztblWeeks

Column Name	Data Type	Definition	Business Meaning
weekstart	date	The first day of the week.	Marks when each week begins. Used for grouping or summarizing data by week.
weekend	date	The last day of the week.	Marks when each week ends. Used for grouping or summarizing data by week.

SQL Final Project

Table: Entertainers

Column Name	Data Type	Definition	Business Meaning
Entertainerid	Integer	Unique identifier in system for each entertainer	Serves as the primary key for the entertainers table. Links back to the engagements, entertainer_styles, and entertainer_members tables.
Entstagename	String	The name of each entertainer	Provides the unique name for entertainers and also brands the performers

Entssn	Integer	Government social security number	This is for tax implications for both the agent and the entertainer. These are not individual SSNs. These are for the entities.
Entstreetaddress	String	Physical mailing address for the entertainers	Allows the user to see the physical address to mail business cards / tax information to
Entcity	String	Residing city of the entertainer	Identifies the residing cities
Entstate	String	Residing state of the entertainer	Identifies the residing state
Entzipcode	Integer	Residing zip code of the entertainer	Identifies the zip code
Entphonenumber	Integer	Phone number for entertainers	Primary contact numbers to get a hold of the entertainers
Entwebpage	String	Website for entertainers	Links to advertise events, promote, and brand the entertainers on the web
Entemailaddress	String	Email address for entertainers	Primary email address to get in contact with the entertainers
Dateentered	Date	The date that the data was entered in the entertainers table	Serves as the entry date for changes made to the entertainers' details

Phase 1: Data Familiarization & Documentation