

kubepod.sh

`kubepod.sh` 基于 `kubect1` 命令封装，操作k8s的脚本，可以安全高效的访问k8s。只提供对k8s的访问命令，不提供删除的操作

安装

```
chmod +x kubepod.sh  
mv kubepod.sh /usr/local/bin/kubepod
```

`kubepod.sh` 支持以下操作

查看日志

```
sh kubepod.sh logs {POD_NAME}
```

等同于 `kubect1 logs -f -n {podname}`

该命令支持 `podname` 模糊匹配，如果匹配到多个容器，直接输入序号

```
-bash-4.2# sh kubepod.sh logs knowledge  
1) pie-engine-common/knowledge-7864cbf96c-htcsf  
2) pie-engine-common/knowledge-build-5dc8877bb6-j4rvb  
3) pie-engine-common/knowledge-build-docsify-7ffb8b8cd8-rg58p  
4) pie-engine-common/knowledge-build-server-57469585f4-cfm6v  
5) pie-engine-common/knowledge-build-server-test-657c44c46f-5sd9q  
6) pie-engine-common/knowledge-build-test-6c9865d945-hkm8j  
7) pie-engine-common/knowledge-recommend-679bfbd8dc-hb7lh  
8) pie-engine-common/knowledge-web-75cf766668-8t6mg  
#? 输入编号
```

```
-bash-4.2# sh kubepod.sh logs knowledge
1) pie-engine-common/knowledge-7864cbf96c-htcsf
2) pie-engine-common/knowledge-build-5dc8877bb6-j4rvb
3) pie-engine-common/knowledge-build-docsify-7ffb8b8cd8-rg58p
4) pie-engine-common/knowledge-build-server-57469585f4-cfm6v
5) pie-engine-common/knowledge-build-server-test-657c44c46f-5sd9q
6) pie-engine-common/knowledge-build-test-6c9865d945-hkm8j
7) pie-engine-common/knowledge-recommend-679bfb8dc-hb7lh
8) pie-engine-common/knowledge-web-75cf766668-8t6mg
#? 1
kubectl logs -f -n pie-engine-common knowledge-7864cbf96c-htcsf
```

进入容器

```
sh kubepod.sh exec {POD_NAME}
```

等同于 `kubectl exec -it -n {podname} /bin/bash`

该命令支持 `podname` 模糊匹配，如果匹配到多个容器，直接输入序号

查看服务部署的端口

```
sh kubepod.sh svc {POD_NAME}
```

等同于 `kubectl get svc -A | grep {podname}`

查看Pod的状态

```
sh kubepod.sh desc {POD_NAME}
```

等同于 `kubectl describe pod -n {podname}`

该命令支持 `podname` 模糊匹配，如果匹配到多个容器，直接输入序号

查看Pod列表



```
sh kubepod.sh pods
```

等同于 `kubectl get pods -A`

查看Svc列表



```
sh kubepod.sh svcs
```

等同于 `kubectl get svc -A`

查看Deployment列表



```
sh kubepod.sh deploys
```

等同于 `kubectl get deployments -A`